

ENGINE ARCHITECTURE & GAME DESIGN

Architecting the 2D Shmup

Systems, Choreography, and Engine Design for High-Performance Scrolling Shooters

Architecting the 2D Shmup

Systems, Choreography, and Engine Design for High-Performance Scrolling Shooters


Welcome to **Architecting the 2D Shmup**. This book is an advanced, engineering-centric guide to building high-performance, commercial-grade 2D Shoot 'Em Up (Shmup) games and custom engines.

Target Audience & Philosophy

This text assumes you are a **competent software engineer** familiar with data structures, algorithms, linear algebra, and systems programming concepts. We will not waste your time explaining what a vector is, how a `for` loop works, or how to install a compiler.

Instead, we focus on the **hard systems-engineering challenges** unique to scrolling shooters:

- Sustaining tens of thousands of active projectiles and entities at a rock-solid 60/120+ FPS with zero runtime allocations.
- Designing deterministic fixed-timestep game loops and state snapshotting architectures.
- Crafting smooth parametric spline path-following systems stabilized via numerical arc-length integration.
- Formulating complex danmaku (bullet curtain) mathematics and reactive emitter domain-specific languages (DSLs).
- Structuring time-indexed level timelines, event queues, and deterministic replay systems.
- Designing multi-phase, hierarchical, destructible boss encounters using Hierarchical State Machines (HSMs) and dynamic difficulty (Rank) systems.
- Architecting an in-engine Level & Wave Editor featuring interactive spline control points, timeline scrubbers, and live hot-reloading.
- Engineering low-latency game feel ("juice"), screen trauma systems, and audio voice-coalescing mixers.



💡 Pseudocode & Code Policy

To remain universally applicable across modern systems languages (such as C++, Rust, C#, Zig, or custom engine environments), code throughout this book is presented in **typed, idiomatic algorithmic pseudocode**.

We explicitly **do not provide a monolithic, copy-pasteable codebase**. Turning these mathematical models, cache-conscious data layouts, and state machine architectures into a functioning game engine is the reader's implementation journey.

Table of Contents

Chapter	Title	Primary Focus
[Chapter 1](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md)	The Anatomy of a Modern 2D Shmup	Genre taxonomy, gameplay pillars, frame budgets, latency mitigation.
[Chapter 2](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md)	Engine Architecture & Core Simulation Loop	Fixed timestep accumulators, ECS vs. DOD, zero-alloc object pools, generational handles.
[Chapter 3](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md)	High-Performance Collision & Spatial Partitioning	Spatial hash grids, dynamic BVH, SAT narrow phase, graze mechanics, Continuous Collision Detection (CCD).
[Chapter 4](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md)	Bullet Choreography & Danmaku Mathematics	Polar transformations, spiral/curtain trigonometry, parametric trajectories, emitter DSLs.
[Chapter 5](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md)	Enemy Path Following, Kinematics & Formation Flight	Bézier and Catmull-Rom splines, arc-length LUT parameterization, Reynolds steering, formation anchoring.
[Chapter 6](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md)	Level Representation, Timeline Sequencing & Scripting	Time-indexed streams vs spatial scrolling, declarative schemas, coroutines, deterministic replays.

Chapter	Title	Primary Focus
[Chapter 7](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md)	Boss Architecture & Choreography	Hierarchical State Machines, multi-part scene graphs, attack telegraphing, Battle Rank calculus.
[Chapter 8](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md)	Level Editor Architecture & Tooling	In-engine tooling, timeline scrubbers, interactive spline handles, command pattern undo/redo, hot reloading.
[Chapter 9](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md)	Visual FX, Audio, and "Game Feel" (Juice)	GPU sprite batching, screen-space distortion shaders, trauma-decay screen shake, voice coalescing.
[Chapter 10](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md)	Synthesis & Implementation Exercises	Complete engine blueprint, 5-phase milestone roadmap, capstone challenges, and bibliography.

✂ Prerequisites

To extract maximum value from this material, you should be comfortable with:

1. **Linear Algebra & Vector Calculus:** Dot products, cross/perp products, matrix transformations, polar coordinates, parametric curves, numerical integration.
2. **Systems Programming & Memory Topologies:** Cache lines (L1/L2/L3), CPU prefetchers, contiguous arrays vs linked structures, memory fragmentation, structure-of-arrays (SoA) layouts.
3. **State Machine Formulations:** Finite State Machines (FSM), Hierarchical State Machines (HSM), and Behavior Trees.

Summary (Table of Contents)

- [Introduction](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/README.md)
- [Chapter 1: The Anatomy of a Modern 2D Shmup](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md)
 - [1.1 Taxonomy and Lineage of Scrolling Shooters](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md#11-taxonomy-and-lineage-of-scrolling-shooters)
 - [1.2 Fundamental Mechanics and Micro-Rules](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md#12-fundamental-mechanics-and-micro-rules)
 - [1.3 Technical Constraints and Real-Time Budgets](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md#13-technical-constraints-and-real-time-budgets)
 - [1.4 Input Latency and Controller Polling Dynamics](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch01_anatomy_of_a_shmup.md#14-input-latency-and-controller-polling-dynamics)
- [Chapter 2: Engine Architecture & Core Simulation Loop](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md)
 - [2.1 Deterministic Fixed Timestep Simulation](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md#21-deterministic-fixed-timestep-simulation)
 - [2.2 Architectural Paradigms: OOP vs. DOD vs. ECS](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md#22-architectural-paradigms-oop-vs-dod-vs-ecs)
 - [2.3 High-Velocity Object Pooling & Generational Indices](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md#23-high-velocity-object-pooling--generational-indices)
 - [2.4 Decoupled Event Dispatching and Systems Bus](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md#24-decoupled-event-dispatching-and-systems-bus)
- [Chapter 3: High-Performance Collision & Spatial Partitioning](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md)

- [3.1 The Collision Complexity Crisis](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md#31-the-collision-complexity-crisis)
- [3.2 Broad-Phase Spatial Partitioning Data Structures](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md#32-broad-phase-spatial-partitioning-data-structures)
- [3.3 Narrow-Phase Primitives and Separating Axis Theorem (SAT)](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md#33-narrow-phase-primitives-and-separating-axis-theorem-sat)
- [3.4 Continuous Collision Detection (CCD) for High-Velocity Beams](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md#34-continuous-collision-detection-ccd-for-high-velocity-beams)
- [3.5 Multi-Hull Architecture: Hitbox, Hurtbox, and Graze-Box](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md#35-multi-hull-architecture-hitbox-hurtbox-and-graze-box)
- [Chapter 4: Bullet Choreography & Danmaku Mathematics](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md)
 - [4.1 Polar Coordinate Geometry and Radial Emitters](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md#41-polar-coordinate-geometry-and-radial-emitters)
 - [4.2 Non-Linear Trajectories and Trigonometric Transforms](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md#42-non-linear-trajectories-and-trigonometric-transforms)
 - [4.3 Interception Mathematics: Leading Target Trajectories](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md#43-interception-mathematics-leading-target-trajectories)
 - [4.4 Segmented Kinematic Beams and Laser Whips](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md#44-segmented-kinematic-beams-and-laser-whips)

- [4.5 Declarative Bullet Scripting & Emitter DSL Architecture](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md#45-declarative-bullet-scripting-emitter-dsl-architecture)
- [Chapter 5: Enemy Path Following, Kinematics & Formation Flight](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md)
 - [5.1 Parametric Splines in 2D Space](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md#51-parametric-splines-in-2d-space)
 - [5.2 The Arc-Length Parameterization Problem & Speed Stabilization](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md#52-the-arc-length-parameterization-problem--speed-stabilization)
 - [5.3 Look-Up Table (LUT) Inversion and Simpson's Rule Integration](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md#53-look-up-table-lut-inversion-and-simpsons-rule-integration)
 - [5.4 Autonomous Steering Behaviors and Target Interception](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md#54-autonomous-steering-behaviors-and-target-interception)
 - [5.5 Squadron Hierarchy and Formation Flight Matrices](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md#55-squadron-hierarchy-and-formation-flight-matrices)
- [Chapter 6: Level Representation, Timeline Sequencing & Scripting](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md)
 - [6.1 Spatial vs. Timeline-Driven Level Models](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md#61-spatial-vs-timeline-driven-level-models)
 - [6.2 Multi-Track Timeline Sequencing Data Structures](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md#62-multi-track-timeline-sequencing-data-structures)
 - [6.3 Scripting Engines & Coroutine Level Orchestration](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md#63-scripting-engines--coroutine-level-orchestration)

- [6.4 Deterministic State Snapshotting & Input-Frame Replay](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md#64-deterministic-state-snapshotting--input-frame-replay)
- [Chapter 7: Boss Architecture & Choreography](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md)
 - [7.1 Control Architectures: HSMs vs. Behavior Trees](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md#71-control-architectures-hsms-vs-behavior-trees)
 - [7.2 Multi-Part Hierarchical Scene Graphs & Destructible Entities](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md#72-multi-part-hierarchical-scene-graphs--destructible-entities)
 - [7.3 Phase Transitions, Timeouts, and Enrage Choreography](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md#73-phase-transitions-timeouts-and-enrage-choreography)
 - [7.4 Visual Telegraphing and Fairness Rules](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md#74-visual-telegraphing-and-fairness-rules)
 - [7.5 Battle Rank: Dynamic Difficulty Adjustment (DDA) Calculus](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md#75-battle-rank-dynamic-difficulty-adjustment-dda-calculus)
- [Chapter 8: Level Editor Architecture & Tooling](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md)
 - [8.1 In-Engine Immediate GUI vs. External Editor Architecture](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md#81-in-engine-immediate-gui-vs-external-editor-architecture)
 - [8.2 Multi-Track Timeline Scrubber with Scrubbing & Step Precision](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md#82-multi-track-timeline-scrubber-with-scrubbing--step-precision)
 - [8.3 Interactive Bezier/Spline Canvas & Tangent Handle Gizmos](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md#83-interactive-bezierspline-canvas--tangent-handle-gizmos)

- [8.4 The Command Pattern for Unlimited Undo/Redo](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md#84-the-command-pattern-for-unlimited-undo-redo)
- [8.5 Live Simulation Hot-Reloading & In-Situ State Injection](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md#85-live-simulation-hot-reloading--in-situ-state-injection)
- [Chapter 9: Visual FX, Audio, and "Game Feel" (Juice)](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md)
 - [9.1 High-Volume GPU Sprite Batching & Instanced Particles](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md#91-high-volume-gpu-sprite-batching--instanced-particles)
 - [9.2 Post-Processing & Screen-Space Distortion Shaders](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md#92-post-processing--screen-space-distortion-shaders)
 - [9.3 Impact Physics: Hitstop, Freeze-Frames, and Trauma Decay](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md#93-impact-physics-hitstop-freeze-frames-and-trauma-decay)
 - [9.4 Audio Voice Limiting, Coalescing, and Dynamic Ducking](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md#94-audio-voice-limiting-coalescing-and-dynamic-ducking)
- [Chapter 10: Synthesis & Implementation Exercises](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md)
 - [10.1 The Master Engine Blueprint](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md#101-the-master-engine-blueprint)
 - [10.2 Five-Phase Incremental Milestone Roadmap](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md#102-five-phase-incremental-milestone-roadmap)
 - [10.3 Capstone Engineering Challenges](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md#103-capstone-engineering-challenges)
 - [10.4 Canonical Bibliography & Further Reading](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-

book/book/ch10_synthesis_and_implementation_exercises.md#104-canonical-bibliography--
further-reading)


Chapter 1: The Anatomy of a Modern 2D Shmup

The Shoot 'Em Up (colloquially **shmup**, or STG in Japan for *Shooting Game*) is one of video game history's purest algorithmic genres. Stripped of complex narrative branches, physical ragdoll simulation, and dynamic 3D lighting pipelines, the shmup operates as an ultra-high-velocity, deterministic choreography of thousands of active mathematical entities.

To the casual observer, a shmup is simply moving a ship and firing lasers. To the systems engineer, a shmup is a **real-time spatial simulation engine** with strict sub-millisecond per-frame budgets, zero-allocation memory constraints, high-density collision culling, and microsecond-level input responsiveness.

1.1 Taxonomy and Lineage of Scrolling Shooters

Understanding the technical design requirements begins with classifying the mechanical sub-genres. The engineering requirements differ significantly depending on the archetype.



1. Danmaku / Bullet Hell (Cave, Touhou, Takumi)

- **Visual & Spatial Characteristics:** The screen is saturated with thousands of slow to medium-velocity projectiles forming geometric tapestries (spirals, rings, roses, rosettes).
- **Core Player Paradigm:** The player sprite might be 64×64 pixels, but the lethal hitbox is an infinitesimal dot (2×2 to 4×4 pixels) centered at the core.
- **Architectural Implications:** Extreme projectile count (10,000--50,000 active entities), demanding $O(1)$ allocation pools, efficient SIMD transform evaluations, and optimized spatial broad-phase culling.

2. Classic Arcade / Toaplan-Style (Raiden, Truxton, Batsugun)

- **Visual & Spatial Characteristics:** Lower projectile counts (50--300 active bullets), but bullets travel at extreme velocities, often traversing half the screen in a few frames.
- **Core Player Paradigm:** Player hitbox closely mirrors the physical sprite hull (20×30 pixels). Precision positioning and macro-routing dominate over micro-dodging.
- **Architectural Implications:** Demands Continuous Collision Detection (CCD) or swept-volume raycasts to prevent high-velocity projectiles from tunneling through the player ship between discrete simulation ticks.

3. Euroshmup (Tyrian, Project-X, Xenon 2)


- **Visual & Spatial Characteristics:** Heavy momentum/inertia on player movement, health bars/shields rather than single-hit-kill mechanics, persistent currency/shop upgrades.
- **Architectural Implications:** Requires continuous kinematic physics integration (drag, mass, acceleration curves) rather than instantaneous discrete arcade velocity vectors.

4. Gimmick / Polarity Shooters (Ikaruga, Radiant Silvergun)

- **Visual & Spatial Characteristics:** State-switching mechanics (e.g., Black/White polarity where opposing color bullets kill, but matching color bullets are absorbed to charge a super-weapon).
- **Architectural Implications:** Dual-layer collision pipelines and instantaneous entity state transforms, requiring bitmask-based collision filtering.

1.2 Fundamental Mechanics and Micro-Rules

A high-performance shmup engine is constructed around precise, non-negotiable micro-mechanics.



Hitbox vs. Hurtbox vs. Graze-Box Disparity

In modern shmups, an entity possesses multiple concentric geometric collision boundaries:

$$\text{Hitbox} \supset \text{Core} \subset \text{Hitbox} \supset \text{Graze} \subset \text{Sprite} \supset \text{Visual}$$

1. **Lethal Hitbox:** A tiny geometric circle or Axis-Aligned Bounding Box (AABB) centered on the player's pilot cockpit. Touching an enemy projectile's lethal radius triggers life loss or bomb auto-trigger.
2. **Graze-Box (Scratch Aura):** A larger concentric hull. When an enemy bullet intersects the graze-box *without* intersecting the lethal hitbox:
 - A graze event is dispatched.
 - The bullet is tagged as `grazed = true` (or assigned a cooldown timer) to prevent awarding millions of points per second from a single stationary bullet.
 - Global multiplier counters increment, building hyper-meter gauge.
3. **Enemy Hurtbox:** Large polygon or composite multi-hull structure mapping to the physical hull of enemy ships, destructible turrets, and weak-points.

Battle Rank (Dynamic Difficulty Adjustment)


Top-tier shmups (such as *Battle Garegga*, *Armed Police Batrider*, and *Crimson Clover*) implement an internal **Rank Variable** ($R \in [0.0, 1.0]$) or an integer accumulator $R \in [0, 2^{32} - 1]$.

$$R_{t+1} = \text{clamp} \left(R_t + \sum \Delta R_{\text{actions}} - \sum \Delta R_{\text{penalties}} ; R_{\min} ; R_{\max} \right)$$

- **Rank Increases when:** The player stays alive per second, picks up power-up items, upgrades shot power, or collects point medals.
- **Rank Decreases when:** The player expends a bomb or loses a life.
- **Rank Directly Modulates Engine Systems:**
 - Emitter firing rates ($f_{\text{fire}} = f_{\text{base}} \times (1.0 + \alpha R)$).
 - Projectile velocities ($v = v_{\text{base}} \times (1.0 + \beta R)$).
 - Bullet density (number of ways in a radial spread $N = N_{\text{base}} + \lfloor \gamma R \rfloor$).
 - Enemy health pools ($HP = HP_{\text{base}} \times (1.0 + \delta R)$).

1.3 Technical Constraints and Real-Time Budgets

A commercial shmup engine operates under tighter deterministic timing constraints than almost any other genre.



The 60 / 120 / 240 Hz Frame Budgets

Target Refresh Rate	Total Frame Budget	Max Simulation Budget	Max Render Budget	Target Entity Capacity
60 FPS	16.66 ms	10.0 ms	4.5 ms	50,000 projectiles
120 FPS	8.33 ms	5.0 ms	2.5 ms	30,000 projectiles
240 FPS	4.16 ms	2.5 ms	1.2 ms	15,000 projectiles

The Zero-Allocation Mandate

During gameplay:

- **Zero dynamic heap allocations** (`malloc`, `new`, vector resizing, string concatenations) may occur within the simulation tick.
- Managed runtimes (C#, Java) must produce **zero garbage collection pressure**; any GC collection pause ($> 2\text{ ms}$) will cause a dropped frame, instantly resulting in an unfair player death.
- All entity pools, bullet buffers, particle arrays, spatial hash grids, and audio event queues must be **pre-allocated at level load** into contiguous flat buffers.

1.4 Input Latency and Controller Polling Dynamics

In a bullet hell shooter, a player must navigate gaps measuring fractions of a millimeter between bullets traveling at hundreds of pixels per second. A delay of 2 frames (**33.3 ms**) renders high-level micro-dodging impossible.



Key Latency Reduction Principles

1. **Poll Directly Before Simulation:** Query hardware raw input (DirectInput, XInput, evdev, SDL GameController) immediately before executing the fixed simulation tick, rather than caching it in an OS event queue.
2. **Double Buffering vs. Triple Buffering:** Triple buffering introduces an extra frame of latency (+16.6 ms). Engines targeting competitive play utilize strict V-Sync synchronization with speculative wait loops (`WaitableSwapchain` in DX12/Vulkan) or Variable Refresh Rate (G-Sync/FreeSync) presentation.
3. **Sub-Frame Input Timestamps:** For high-end arcade replay fidelity, capture hardware input with high-resolution microsecond timestamps (μs). If an input arrives halfway through a frame, apply sub-tick fractional movement or queue it precisely for the next simulation tick.

1.5 Summary Checklist for Engine Architects

Before writing a single line of rendering code, ensure your architecture answers these five questions:

1. **Memory:** Is every simulation entity pre-allocated in contiguous arrays with zero runtime allocations?
2. **Determinism:** Can the simulation run headlessly without a GPU at 10,000 ticks/sec and produce bit-identical replays?
3. **Collision:** Can the broad-phase structure cull 20,000 bullets against 500 enemy hurtboxes in $< 2.5 \text{ ms}$?
4. **Kinematics:** Does the path-following engine support constant-velocity spline traversal via arc-length parameterization?
5. **Tooling:** Can a level designer scrub the game timeline back and forth like a video editor while tweaking bullet emitters?

In [\[Chapter 2\]\(file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch02_engine_architecture_and_core_loop.md\)](#), we construct the foundation: the deterministic fixed-timestep game loop, Data-Oriented ECS architecture, and zero-allocation object pools.

Chapter 2: Engine Architecture & Core Simulation Loop

In a game where twenty thousand projectiles interact with hundreds of enemy segments every sixteenth of a second, software architecture is not an academic debate—it is the difference between an unplayable slideshow and an electrifying, rock-solid arcade experience.


This chapter establishes the core simulation backbone: deterministic fixed-timestep game loops, cache-conscious Data-Oriented Design (DOD), zero-allocation object pools, and generational handle systems.

2.1 Deterministic Fixed Timestep Simulation

Variable delta-time loops (`position += velocity * dt`) are disastrous for shmups. They introduce non-deterministic floating-point divergence, frame-rate dependent collision tunneling, and make replay recording mathematically impossible.

A professional shmup simulation must run on a **strict, deterministic fixed timestep** (Δt_{fixed} , typically $\frac{1}{60} \text{ s} \approx 16.666 \text{ ms}$ or $\frac{1}{120} \text{ s} \approx 8.333 \text{ ms}$).

CODE



The Accumulator Algorithm & Spiral-of-Death Protection

If the CPU encounters a sudden heavy workload (e.g., OS background task), `frame_time` spikes. If unhandled, the while-loop attempts to simulate dozens of ticks in a single frame, which consumes even more CPU time, causing `frame_time` to grow further in a catastrophic feedback loop known as the **Spiral of Death**.

We solve this by clamping the maximum elapsed delta-time per frame:

RUST

```
// Pseudocode: Deterministic Fixed Timestep Loop with Accumulator Clamp
struct TimeState {
    fixed_delta: f64,      // e.g., 1.0 / 60.0 (0.0166667s)
    max_frame_time: f64,   // Clamp to e.g. 0.10s (max 6 catch-up ticks)
    accumulator: f64,
    current_time: f64,
}

fn run_frame(time_state: &mut TimeState, engine: &mut Engine) {
    let new_time = get_high_resolution_time();
    let mut frame_time = new_time - time_state.current_time;
    time_state.current_time = new_time;

    // Prevent Spiral of Death by clamping frame_time
    if frame_time > time_state.max_frame_time {
        frame_time = time_state.max_frame_time;
    }

    time_state.accumulator += frame_time;

    // Execute discrete simulation ticks
    while time_state.accumulator ≥ time_state.fixed_delta {
        engine.snapshot_previous_transforms(); // Save state for render interpolation
        engine.fixed_update(time_state.fixed_delta);
        time_state.accumulator -= time_state.fixed_delta;
    }

    // Calculate sub-frame blend factor for butter-smooth rendering
    let alpha = (time_state.accumulator / time_state.fixed_delta) as f32;
    engine.render(alpha);
}
```

State Interpolation for Variable Refresh Rates (144Hz / 240Hz Monitors)

When running a **60 Hz** simulation on a **144 Hz** or **240 Hz** monitor, the renderer will execute multiple times between simulation ticks. Without interpolation, entities appear to stutter.

For any visual entity, we blend between its previous tick transform and current tick transform using $\alpha \in [0.0, 1.0)$:

$$\vec{P}_{\text{render}} = (1 - \alpha) \vec{P}_{\text{prev}} + \alpha \vec{P}_{\text{curr}}$$

$$\theta_{\text{render}} = \text{slerp}(\theta_{\text{prev}}, \theta_{\text{curr}}, \alpha)$$

2.2 Architectural Paradigms: OOP vs. DOD vs. ECS

Why Traditional Object-Oriented Polymorphism Fails

In traditional OOP, one might model bullets as an inheritance hierarchy:



Iterating over **30,000** pointers to polymorphic `Entity*` objects induces:

1. **Cache Miss Hell:** Each bullet is allocated at an arbitrary heap address. The CPU's L1 cache line (**64 bytes**) is loaded, one pointer dereference occurs, and the rest of the cache line is wasted.
2. **Virtual Method Call Overhead:** Calling `virtual void update(dt)` disables compiler inlining and forces branch predictor stalls on indirect function pointers.

Data-Oriented Design (DOD) & Structure of Arrays (SoA)

Modern processors can stream contiguous memory through SIMD vector units at over **50 GB/sec**. To leverage this, we transform our memory layout from **Array of Structures (AoS)** to **Structure of Arrays (SoA)**.

CODE

AoS (Array of Structures) - Cache Inefficient for Position Updates:

[Pos.x, Pos.y, Vel.x, Vel.y, Radius, Color, SpriteID, Grazed, Lifetime] → [Pos.x, Pos.y ...]
 48 Bytes (Only 16 bytes needed for movement)

SoA (Structure of Arrays) - 100% Cache Line Utilization:

Positions X: [x0, x1, x2, x3, x4, x5, x6, x7, x8, x9 ...] ← 16 floats fit in a single 64B

Positions Y: [y0, y1, y2, y3, y4, y5, y6, y7, y8, y9 ...]

Velocities X: [vx0, vx1, vx2, vx3, vx4, vx5, vx6 ...]

Velocities Y: [vy0, vy1, vy2, vy3, vy4, vy5, vy6 ...]

ECS Component Splitting for High-Density Danmaku

In a pure Entity Component System (or an archetype-based ECS such as Flecs or Bevy), components are split into dense, packed arrays:

RUST

```
// Projectile System Data Layout in SoA Format
struct ProjectilePool {
    capacity: usize,
    count: usize,

    // Contiguous parallel arrays aligned to 64-byte boundaries
    pos_x: Array<f32>,
    pos_y: Array<f32>,
    vel_x: Array<f32>,
    vel_y: Array<f32>,
    radius: Array<f32>,
    flags: Array<u8>,          // Bitfield: [Active:1, Grazed:1, Polar:1, Homing:1]
    sprite_id: Array<u16>,
    lifetime: Array<f32>,
}

fn update_projectiles(pool: &mut ProjectilePool, dt: f32) {
    let n = pool.count;
    // Compiles directly to AVX-512 / NEON vector instructions
    for i in 0..n {
        pool.pos_x[i] += pool.vel_x[i] * dt;
        pool.pos_y[i] += pool.vel_y[i] * dt;
        pool.lifetime[i] -= dt;
    }
}
```

2.3 High-Velocity Object Pooling & Generational Indices

In a shmup, thousands of bullets and particles spawn and despawn every second. We cannot call `malloc` or `free`. We pre-allocate all entity buffers at initialization and manage them using an $O(1)$ **In-Place Singly-Linked Free List**.

CODE

INITIAL PRE-ALLOCATED BUFFER (All Slots Free):

```

Index:   [ 0 ]   [ 1 ]   [ 2 ]   [ 3 ]   [ 4 ]
NextFree: 1     2     3     4     NONE (-1)
FreeHead → 0

```

AFTER ALLOCATING 2 BULLETS (Slots 0 and 1 occupied):

```

Index:   [ 0:ACTIVE ] [ 1:ACTIVE ] [ 2:FREE ] [ 3:FREE ] [ 4:FREE ]
FreeHead → 2

```

AFTER DESPAWNING BULLET AT INDEX 0 (0 re-linked to head):

```

Index:   [ 0:FREE ]   [ 1:ACTIVE ] [ 2:FREE ] [ 3:FREE ] [ 4:FREE ]
NextFree: 2           3           4           NONE
FreeHead → 0

```

The Stale Reference Bug and Generational Handles

If an enemy locks onto a projectile or another entity by storing a raw array index `idx = 4`, and that projectile dies on frame 100, slot `4` may be recycled on frame 101 for an entirely different entity. The enemy would now be tracking the wrong entity!

We solve this using **Generational Handles** (also known as a **Slot Map**).

CODE

```
Handle = (Index: u32, Generation: u32)
```



RUST

```
// Generational Handle SlotMap Architecture
struct Slot<T> {
    data: T,
    generation: u32,
    is_alive: bool,
    next_free: u32,
}

struct GenerationalPool<T> {
    slots: Array<Slot<T>>,
    free_head: u32,
    active_count: u32,
    capacity: u32,
}

struct EntityHandle {
    index: u32,
    generation: u32,
}

impl<T> GenerationalPool<T> {
    fn allocate(&mut self, initial_data: T) → Result<EntityHandle, OutOfMemoryError> {
        if self.free_head == INVALID_INDEX {
            return Err(OutOfMemoryError);
        }

        let slot_idx = self.free_head;
        let slot = &mut self.slots[slot_idx];

        self.free_head = slot.next_free;
        slot.data = initial_data;
        slot.is_alive = true;
        self.active_count += 1;

        Ok(EntityHandle {
            index: slot_idx,
            generation: slot.generation,
        })
    }

    fn free(&mut self, handle: EntityHandle) → bool {
        let slot = &mut self.slots[handle.index];

        // Validate handle generation against slot generation
        if !slot.is_alive || slot.generation != handle.generation {
            return false; // Stale handle reference! Safely ignore.
        }
    }
}
```

```

    }

    slot.is_alive = false;
    slot.generation += 1; // Invalidate all existing handles to this slot
    slot.next_free = self.free_head;
    self.free_head = handle.index;
    self.active_count -= 1;

    true
}

fn get(&self, handle: EntityHandle) → Option<T> {
    let slot = &self.slots[handle.index];
    if slot.is_alive && slot.generation == handle.generation {
        Some(&slot.data)
    } else {
        None // Stale or dead entity
    }
}
}

```

2.4 Decoupled Event Dispatching and Systems Bus

Gameplay systems (such as enemy health systems) should never directly call sound players, particle spawners, or score popups. Doing so creates tight coupling and ruins deterministic simulation replay.

Instead, simulation systems push lightweight, flat event structs into a pre-allocated **Ring-Buffered Event Queue**. Non-deterministic or side-effect systems (Audio Engine, VFX Manager, HUD Renderers) drain these events at the end of the frame.

CODE

SIMULATION PHASE (Deterministic):

Enemy Hurt System

→ Push Event: EnemyKilled { id: 42, pos: (120, 300), score: 5000 }

Graze System

→ Push Event: PlayerGrazed { bullet_id: 104, pos: (240, 500) }

FLAT EVENT RING BUFFER (Pre-allocated)

Audio Mixer System
(Triggers Explosion)Particle Emitter
(Spawns Debris)Score & HUD System
(Displays "+5000")

RUST

```
// Low-overhead Ring-Buffered Event Queue
enum GameEvent {
    EnemyDestroyed { entity_id: u32, position: Vec2, score_value: u32, enemy_type: u16 },
    BulletGrazed { player_id: u8, bullet_pos: Vec2 },
    PlayerDied { player_id: u8, death_pos: Vec2 },
    BombActivated { player_id: u8, screen_pos: Vec2 },
}

struct EventBus {
    buffer: Array<GameEvent, 2048>, // Pre-allocated fixed capacity
    write_head: usize,
    count: usize,
}

impl EventBus {
    fn publish(&mut self, event: GameEvent) {
        if self.count < 2048 {
            self.buffer[self.write_head] = event;
            self.write_head = (self.write_head + 1) % 2048;
            self.count += 1;
        }
    }

    fn drain<F>(&mut self, mut handler: F) where F: FnMut(GameEvent) {
        let read_start = (self.write_head + 2048 - self.count) % 2048;
        for i in 0..self.count {
            let idx = (read_start + i) % 2048;
            handler(self.buffer[idx]);
        }
        self.count = 0;
    }
}
```

2.5 Frame Execution Lifecycle

The complete execution lifecycle for a single simulation frame is summarized in the following sequence:

MERMAID

```
sequenceDiagram
    autonumber
    participant MainLoop as Game Loop Driver
    participant Input as Hardware Input Poller
    participant Timeline as Timeline & Spawner
    participant Kinematics as Splines & Projectiles
    participant Spatial as Spatial Hash Broadphase
    participant Collision as SAT Narrowphase & Graze
    participant Events as Ring Event Bus
    participant Render as Interpolated Render Pipeline

    MainLoop->>Input: Poll hardware state (raw joystick/keys)
    MainLoop->>Timeline: Step level clock & advance wave triggers
    MainLoop->>Kinematics: Update enemy splines & integrate danmaku positions
    MainLoop->>Spatial: Clear and repopulate spatial grid buckets
    MainLoop->>Collision: Query broadphase & evaluate narrow SAT hulls
    Collision->>Events: Emit Graze, Damage, and Death events
    MainLoop->>Events: Drain events to Audio & Particle sub-systems
    MainLoop->>Render: Interpolate transforms (alpha) & issue draw calls
```

With our deterministic loop, zero-allocation memory pools, and decoupled event dispatch in place, we proceed to **[Chapter 3](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch03_spatial_partitioning_and_collision.md)** to tackle the central computational bottleneck: high-performance spatial partitioning and collision queries.

Chapter 3: High-Performance Collision & Spatial Partitioning

In a 2D shmup, collision detection is the primary computational bottleneck. When twenty thousand enemy bullets, five hundred high-fire-rate player shot pellets, forty enemy ships, and multi-segmented laser beams exist simultaneously, an unoptimized naive collision test will cripple even high-end desktop CPUs.

This chapter details the math and algorithms needed to cull, partition, and resolve tens of thousands of collision queries in under **2.0 ms**.

3.1 The Collision Complexity Crisis

A naive collision loop performs pairwise tests between every projectile and every target entity:

$$\text{Comparisons}_{\text{naive}} = N_{\text{player_bullets}} \times M_{\text{enemies}} + N_{\text{enemy_bullets}} \times M_{\text{player_hulls}}$$

For **500** player bullets against **300** enemy targets, plus **25,000** enemy bullets against the player's core hitbox and graze aura:

$$\text{Comparisons} = (500 \times 300) + (25,000 \times 2) = 150,000 + 50,000 = 200,000 \text{ checks/frame}$$

At 60 frames per second, this demands **12,000,000 geometric intersection tests every second**. If complex polygon or oriented bounding box checks are used, frame rates collapse.

We conquer this using a two-stage pipeline:

1. **Broad-Phase Culling:** Rapidly discards **99.8** of non-colliding pairs using spatial partitioning in $O(N)$ time.
2. **Narrow-Phase Geometry:** Evaluates exact mathematical intersections only for surviving candidate pairs using SIMD-accelerated geometric algorithms.



3.2 Broad-Phase Spatial Partitioning Data Structures

Selecting the correct spatial structure requires analyzing the motion characteristics of a shmup:

- Almost **100% of all entities move every single frame**.
- Tree structures (like Quadtrees or Dynamic BVH trees) suffer massive performance degradation because nodes must be re-inserted, re-balanced, and memory allocated every tick.

Spatial Structure	Update Cost (N moving items)	Query Cost	Memory Overhead	Cache Locality	Verdict for Shmups
Naive All-Pairs	$O(1)$	$O(N \times M)$	Zero	Excellent	✗ Unusable for > 500 entities
Quadtree	$O(N \log N)$ (rebuild/rebalance)	$O(\log N)$	High (node pointers)	Poor (pointer chasing)	⚠ Acceptable for static terrain
Dynamic BVH	$O(N \log N)$ (tree rotations)	$O(\log N)$	Moderate	Moderate	⚠ Great for large composite bosses
Uniform Spatial Hash Grid	$O(N)$ (flat array write)	$O(1)$ average	Very Low (flat arrays)	Optimal (Contiguous)	✓ Industry Standard for Danmaku

The Uniform Spatial Hash Grid Architecture

A spatial hash grid subdivides the 2D playfield into uniform cells of size S_{cell} (typically 32×32 or 64×64 pixels).

CODE

```

PLAYFIELD (e.g., 640×960 px)
Cell Size = 64px (10 columns x 15 rows = 150 Cells)

Cell Index = (y / CellSize) * GridWidth + (x / CellSize)

```

0	1	2	3	4
5	6	7	8	9
10	11	12	13	14

Enemy Ship in Cell 2

Player Bullet queries only Cells [1,2,3, 6,7,8]

Zero-Allocation Spatial Hash Implementation

Instead of using dynamic vectors inside each grid cell (which causes memory fragmentation), we implement the grid using two pre-allocated flat integer arrays: **Cell Heads** and **Next Pointers** (a flattened linked-list over array indices).



RUST

```

// High-Performance Flat Spatial Hash Grid
const CELL_SIZE: f32 = 64.0;
const GRID_COLS: usize = 16; // e.g., 1024px width
const GRID_ROWS: usize = 20; // e.g., 1280px height
const TOTAL_CELLS: usize = GRID_COLS * GRID_ROWS;
const MAX_ENTITIES: usize = 32768;

struct SpatialGrid {
    cell_heads: Array<i32, TOTAL_CELLS>, // Index to first entity in cell (-1 if empty)
    entity_next: Array<i32, MAX_ENTITIES>, // Pointer to next entity in same cell
}

impl SpatialGrid {
    fn clear(&mut self) {
        // Fast SIMD memset to -1
        fill_memory(&mut self.cell_heads, -1);
    }

    // Compute 1D bucket index from 2D coordinates
    fn cell_coord(&self, x: f32, y: f32) → Option<usize> {
        if x < 0.0 || y < 0.0 { return None; }
        let cx = (x / CELL_SIZE) as usize;
        let cy = (y / CELL_SIZE) as usize;
        if cx < GRID_COLS && cy < GRID_ROWS {
            Some(cy * GRID_COLS + cx)
        } else {
            None
        }
    }

    // Insert entity in O(1) time without heap allocation
    fn insert(&mut self, entity_idx: usize, pos_x: f32, pos_y: f32) {
        if let Some(cell_idx) = self.cell_coord(pos_x, pos_y) {
            self.entity_next[entity_idx] = self.cell_heads[cell_idx];
            self.cell_heads[cell_idx] = entity_idx as i32;
        }
    }

    // Query all entities within neighboring 3x3 cells
    fn query_range<F>(&self, pos_x: f32, pos_y: f32, radius: f32, mut visitor: F)
    where F: FnMut(usize) {
        let min_cx = max(0, ((pos_x - radius) / CELL_SIZE) as i32);
        let max_cx = min(GRID_COLS as i32 - 1, ((pos_x + radius) / CELL_SIZE) as i32);
        let min_cy = max(0, ((pos_y - radius) / CELL_SIZE) as i32);
        let max_cy = min(GRID_ROWS as i32 - 1, ((pos_y + radius) / CELL_SIZE) as i32);

```

```

    for cy in min_cy..max_cy {
        for cx in min_cx..max_cx {
            let cell_idx = (cy as usize) * GRID_COLS + (cx as usize);
            let mut curr = self.cell_heads[cell_idx];
            while curr != -1 {
                visitor(curr as usize);
                curr = self.entity_next[curr as usize];
            }
        }
    }
}


```

3.3 Narrow-Phase Primitives and Separating Axis Theorem (SAT)

Once broad-phase culling yields candidate pairs, narrow-phase checks determine precise intersection.

CODE

NARROW-PHASE HIERARCHY



1. Circle-vs-Circle Test (Squared Distance Optimization)

Never call square root (`sqrt`) in bullet collision loops. Compare squared distance against squared radius sums:

$$\Delta x = x_2 - x_1, \quad \Delta y = y_2 - y_1$$


$$\text{Colliding} \iff (\Delta x^2 + \Delta y^2) \leq (r_1 + r_2)^2$$

2. Separating Axis Theorem (SAT) for Oriented Bounding Boxes (OBB)

When enemy bosses rotate, their rectangular wings and laser turrets rotate. Axis-Aligned Bounding Boxes (AABB) become overly loose, leading to false hits. We must test **Oriented Bounding Boxes (OBBs)** using the **Separating Axis Theorem (SAT)**.

***Theorem (SAT):** Two convex 2D polygons do not intersect if and only if there exists a 1D axis along which the projections of the two polygons do not overlap.*

For two 2D oriented rectangles **A** and **B**, we only need to test **4 candidate projection axes**: the 2 local normal axes of **A**, and the 2 local normal axes of **B**.



RUST

```
// 2D Separating Axis Theorem (SAT) for Oriented Bounding Boxes
struct OBB {
    center: Vec2,
    extents: Vec2,    // Half-width and half-height (unrotated)
    rotation: f32,    // Radians
}

fn intersect_obb_obb(a: OBB, b: OBB) → bool {
    // Compute unit orientation vectors (local axes)
    let axes_a = [
        Vec2::new(cos(a.rotation), sin(a.rotation)),
        Vec2::new(-sin(a.rotation), cos(a.rotation)),
    ];
    let axes_b = [
        Vec2::new(cos(b.rotation), sin(b.rotation)),
        Vec2::new(-sin(b.rotation), cos(b.rotation)),
    ];

    let distance_vector = b.center - a.center;

    // Test all 4 potential separating axes
    for axis in [axes_a[0], axes_a[1], axes_b[0], axes_b[1]] {
        // Project center distance onto current axis
        let projected_distance = abs(dot(distance_vector, axis));

        // Project half-extents of OBB A onto current axis
        let radius_a = a.extents.x * abs(dot(axes_a[0], axis)) +
            a.extents.y * abs(dot(axes_a[1], axis));


        // Project half-extents of OBB B onto current axis
        let radius_b = b.extents.x * abs(dot(axes_b[0], axis)) +
            b.extents.y * abs(dot(axes_b[1], axis));

        // If a separating gap exists along this axis, no collision occurs
        if projected_distance > (radius_a + radius_b) {
            return false;
        }
    }

    true // Overlap confirmed along all 4 axes → Collision detected!
}
```



3.4 Continuous Collision Detection (CCD) for High-Velocity Beams

In arcade-style shooters, high-velocity sniper bullets and player lasers travel at speeds exceeding **2,000 pixels/sec**. In a discrete **60 Hz** simulation, an entity advances by ≥ 35 pixels per tick. If a player's hitbox radius is **3 pixels**, a projectile will skip clean through the ship between ticks without triggering a collision. This is known as **bullet tunneling**.



Swept-Circle vs. Circle Continuous Test (Capsule Intersection)

Instead of testing point-in-circle at frame $N + 1$, we model the bullet's motion from $\vec{A}$ to $\vec{B}$ as a **capsule** (a line segment swept by the bullet's radius r_{bullet}).



RUST

```
// Continuous Collision Detection: Swept Circle vs Stationary Target Circle
fn intersect_swept_circle(
    start_pos: Vec2,
    end_pos: Vec2,
    bullet_radius: f32,
    target_pos: Vec2,
    target_radius: f32,
) → bool {
    let segment = end_pos - start_pos;
    let to_target = target_pos - start_pos;
    let seg_len_sq = dot(segment, segment);

    // If bullet is stationary, perform static circle test
    if seg_len_sq < 0.0001 {
        let dist_sq = dot(to_target, to_target);
        let total_r = bullet_radius + target_radius;
        return dist_sq ≤ (total_r * total_r);
    }

    // Project target center onto bullet motion segment, clamped to [0.0, 1.0]
    let t = clamp(dot(to_target, segment) / seg_len_sq, 0.0, 1.0);

    // Find closest point on swept trajectory segment to target center
    let closest_point = start_pos + segment * t;
    let delta = target_pos - closest_point;
    let dist_sq = dot(delta, delta);

    let total_radius = bullet_radius + target_radius;
    dist_sq ≤ (total_radius * total_radius)
}
```

3.5 Multi-Hull Architecture: Hitbox, Hurtbox, and Graze-Box

Entities register multiple collision layers using a **Collision Bitmask Matrix**.

RUST

```
// Bitflags for Collision Layers and Filter Masks
const LAYER_PLAYER_HITBOX: u32    = 1 << 0;
const LAYER_PLAYER_GRAZEBBOX: u32 = 1 << 1;
const LAYER_PLAYER_BULLET: u32   = 1 << 2;
const LAYER_ENEMY_HURTBOX: u32    = 1 << 3;
const LAYER_ENEMY_BULLET: u32    = 1 << 4;
const LAYER_ITEM_PICKUP: u32     = 1 << 5;

// Layer Interaction Mask Matrix:
// LAYER_ENEMY_BULLET interacts with (LAYER_PLAYER_HITBOX | LAYER_PLAYER_GRAZEBBOX)
// LAYER_PLAYER_BULLET interacts with (LAYER_ENEMY_HURTBOX)
```

RUST

```
// Multi-Hull Player Evaluation Routine
fn evaluate_enemy_bullet_vs_player(
    bullet_pos: Vec2,
    bullet_r: f32,
    player: &Player,
    bus: &mut EventBus
) {
    let dist_sq = distance_squared(bullet_pos, player.core_pos);

    // 1. Test Lethal Core Hitbox First (Highest Priority)
    let lethal_r = bullet_r + player.core_radius;
    if dist_sq ≤ (lethal_r * lethal_r) {
        bus.publish(GameEvent::PlayerDied { player_id: player.id, death_pos: player.core_pos });
        return;
    }

    // 2. Test Outer Graze Aura (Only if lethal test missed)
    let graze_r = bullet_r + player.graze_radius;
    if dist_sq ≤ (graze_r * graze_r) {
        bus.publish(GameEvent::BulletGrazed { player_id: player.id, bullet_pos });
    }
}
```

3.6 Chapter Takeaways & Performance Targets

1. **Broad-phase culling is non-negotiable:** A 64px Uniform Spatial Hash Grid reduces pairwise queries from 200,000 to < 200 per tick.
2. **Never allocate during collision ticks:** Maintain flat index-linked buckets in pre-allocated static arrays.
3. **Squared distance over sqrt:** Omit square roots across all circle-circle calculations.
4. **Use CCD for hyper-velocity projectiles:** Swept-circle capsule tests eliminate bullet tunneling.

With collision and spatial indexing running at microsecond speeds, we turn to **[Chapter 4]** (file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch04_bullet_choreography_and_danmaku_math.md) to explore the trigonometry, vector calculus, and emitter choreography behind complex danmaku patterns.

Chapter 4: Bullet Choreography & Danmaku Mathematics

Danmaku (*bullet curtain*) is the visual poetry and mathematical soul of the modern shooting game. What appears to a player as an overwhelming, chaotic wall of neon energy is, in reality, a collection of elegant parametric equations executed in polar coordinates.

This chapter uncovers the mathematics of bullet emitters, trigonometric geometries, quadratic target interception, segmented laser kinematics, and domain-specific scripting architectures.


4.1 Polar Coordinate Geometry and Radial Emitters


While game rendering takes place in 2D Cartesian space (x, y) , bullet choreography is almost exclusively authored in **Polar Coordinate Space** (r, θ) :

$$x = x_{\text{origin}} + r \cos(\theta), \quad y = y_{\text{origin}} + r \sin(\theta)$$

$$\vec{v} = (s \cos(\theta), s \sin(\theta))$$

where s is linear velocity (speed), and θ is the trajectory angle in radians.





1. The N -Way Arc Spread

To fire an N -way spread of bullets centered around a base targeting angle θ_0 with a total spread arc of Φ :

$$\Delta\theta = \frac{\Phi}{N-1} \quad (\text{for } N > 1)$$

$$\theta_i = \left(\theta_0 - \frac{\Phi}{2}\right) + i \cdot \Delta\theta, \quad \text{for } i \in [0, N-1]$$

2. The Rotating Spiral Emitter

A multi-arm rotating spiral updates its base angle incrementally on every firing tick:

$$\theta_{\text{base}}(t) = \theta_0 + \omega \cdot t$$

$$\theta_{i,\text{arm}}(t) = \theta_{\text{base}}(t) + i \cdot \left(\frac{2\pi}{M}\right), \quad \text{for } i \in [0, M-1]$$

where ω is the angular velocity in radians/second, and M is the number of spiral arms.

3. Complex Geometric Curves (Rhodonea / Rose Patterns)

By modulating emission speed or angular offsets using trigonometric polynomials, we generate harmonic curtain patterns.

A **Rhodonea (Rose) Curve** emitter modulates bullet speed or offset as a function of the emission angle:

$$r(\theta) = A \cos(k\theta)$$

RUST

```
// Pseudocode: Harmonic Rose Emitter Generator
fn emit_rose_pattern(
    pool: &mut ProjectilePool,
    origin: Vec2,
    base_angle: f32,
    petals: f32,          // Parameter 'k'
    bullet_count: usize,
    base_speed: f32,
) {
    let angle_step = (2.0 * PI) / (bullet_count as f32);

    for i in 0..bullet_count {
        let theta = base_angle + (i as f32) * angle_step;
        // Modulate bullet speed based on petal harmonic function
        let speed = base_speed * (0.4 + 0.6 * abs(cos(petals * theta * 0.5)));

        let velocity = Vec2::new(speed * cos(theta), speed * sin(theta));
        pool.spawn_bullet(origin, velocity, BulletType::Needle);
    }
}
```

4.2 Non-Linear Trajectories and Trigonometric Transforms

Linear bullets traveling at constant velocities produce rigid patterns. Elite danmaku engines incorporate time-dependent parametric transforms.

CODE

PARAMETRIC TRAJECTORY STYLES

Decelerate & Turn



Sinusoidal Wavy Beam

~ ~ ~ ~ ~ ~ ~ ~ ▶
(Oscillating)

1. Velocity Staging (Pause-and-Aim / Acceleration Curves)

Bullets often spawn with high initial velocity, decelerate to a complete stop, recalculate their angle toward the player, and accelerate outward:

$$s(t) = \begin{cases} s_0 - a_{\text{brake}} \cdot t & \text{if } t < t_{\text{stop}} \\ 0 & \text{if } t_{\text{stop}} \leq t < t_{\text{resume}} \\ a_{\text{accel}} \cdot (t - t_{\text{resume}}) & \text{if } t \geq t_{\text{resume}} \end{cases}$$

2. Curvilinear Angular Drift

Instead of moving in a straight line, bullets can have a non-zero angular derivative $\dot{\theta}(t)$:

$$\theta_{t+\Delta t} = \theta_t + \omega_{\text{drift}} \cdot \Delta t$$

$$\vec{v}(t + \Delta t) = (s \cos(\theta_t + \Delta t), s \sin(\theta_t + \Delta t))$$

3. Sinusoidal Perturbation (Wavy Trajectories)


To create serpentine, undulating streams, we apply a perpendicular sinusoidal displacement vector to the primary motion vector $\vec{v}_{\text{forward}}$:

$$\vec{n}_{\perp} = (-\sin(\theta), \cos(\theta))$$

$$\vec{P}(t) = \vec{P}_O + \vec{v}_{\text{forward}} \cdot t + \vec{n}_{\perp} \cdot \left(A \sin(\omega t + \phi) \right)$$

4.3 Interception Mathematics: Leading Target Trajectories

Aiming directly at the player's current position ($\theta = \text{atan2}(y_P - y_E, x_P - x_E)$) is trivial for players to dodge by streaming (tapping slightly in one direction). High-threat enemies calculate **predictive leading trajectories** to intercept a moving player.



Mathematical Derivation of Quadratic Interception

Let the player ship be at position $\vec{P}_T$ moving with constant velocity $\vec{v}_T$. Let the emitter be at position $\vec{P}_E$. The enemy fires a bullet with known speed s_B at time $t = 0$.

We seek the future time $t > 0$ such that the bullet reaches the player's future position:

$$\vec{P}_T(t) = \vec{P}_T + \vec{v}_T \cdot t$$

$$|\vec{P}_T(t) - \vec{P}_E| = s_B \cdot t$$

Let relative displacement be $\vec{D} = \vec{P}_T - \vec{P}_E$. Squaring both sides:

$$|\vec{D} + \vec{v}_T \cdot t|^2 = (s_B \cdot t)^2$$

$$(\vec{D} \cdot \vec{D}) + 2(\vec{D} \cdot \vec{v}_T)t + (\vec{v}_T \cdot \vec{v}_T)t^2 = s_B^2 t^2$$

Rearranging into standard quadratic form $at^2 + bt + c = 0$:

$$a = (\vec{v}_T \cdot \vec{v}_T) - s_B^2$$

$$b = 2(\vec{D} \cdot \vec{v}_T)$$

$$c = (\vec{D} \cdot \vec{D})$$

RUST

```

// Predictive Interception Calculation
fn calculate_lead_angle(
    emitter_pos: Vec2,
    target_pos: Vec2,
    target_vel: Vec2,
    bullet_speed: f32,
) → Option<f32> {
    let d = target_pos - emitter_pos;

    let a = dot(target_vel, target_vel) - (bullet_speed * bullet_speed);
    let b = 2.0 * dot(d, target_vel);
    let c = dot(d, d);

    let discriminant = b * b - 4.0 * a * c;

    // If discriminant < 0, target is traveling faster than bullet speed and moving away
    if discriminant < 0.0 {
        return None; // Cannot intercept; fallback to direct aiming
    }

    let sqrt_disc = sqrt(discriminant);
    let t1 = (-b - sqrt_disc) / (2.0 * a);
    let t2 = (-b + sqrt_disc) / (2.0 * a);

    // Select the smallest positive arrival time t
    let t = match (t1 > 0.0, t2 > 0.0) {
        (true, true) => min(t1, t2),
        (true, false) => t1,
        (false, true) => t2,
        (false, false) => return None,
    };


    // Calculate future target position and resulting firing angle
    let intercept_point = target_pos + target_vel * t;
    let aim_vector = intercept_point - emitter_pos;

    Some(atan2(aim_vector.y, aim_vector.x))
}

```

4.4 Segmented Kinematic Beams and Laser Whips

Continuous curved lasers (such as the sweeping lasers in *Gradius V* or *DoDonPachi*) cannot be represented by simple circles or static boxes. They are modeled as **Kinematic Spline Node Chains**.



Mechanics of the Laser Node Chain

1. A head node updates its position and orientation according to the emitter's transform.
2. Trailing nodes follow previous positions from a fixed-length circular history buffer (distance-constrained kinematic chain).
3. Collision narrow-phase tests each link as a swept capsule segment between node i and node $i + 1$.
4. The GPU renders the laser by generating a dynamic triangle strip with UV coordinates mapped along the segment chain length.

4.5 Declarative Bullet Scripting & Emitter DSL Architecture

Hardcoding complex patterns in imperative code makes choreography rigid and painful to balance. Production shmup engines utilize a **Declarative Emitter Domain-Specific Language (DSL)** or a bytecode-compiled virtual machine (similar to *BulletML* or Lua coroutine choreographers).

CODE

EMITTER SCRIPT DOMAIN HIERARCHY

```
<Emitter>
├── <Action name="SpiralBarrage">
│   ├── <Repeat count="36">
│   │   ├── <Fire angle="prev + 10" speed="350" type="Orb" />
│   │   └── <Wait ticks="3" />
│   └── </Repeat>
└── </Action>
```

A Micro-Interpreter for Emitter Bytecode

Instead of allocating memory for string parsing at runtime, scripts are compiled offline into a dense byte stream executed by a stack-based **Emitter Virtual Machine**.



RUST

```
// Emitter VM Bytecode Instructions
enum EmitterOpcode {
    Fire { angle_offset: f32, speed: f32, bullet_type: u16 },
    SetAngularVelocity { omega: f32 },
    WaitTicks { count: u16 },
    LoopStart { count: u16 },
    LoopEnd,
    AimAtPlayer,
    Halt,
}

struct EmitterInstance {
    bytecode_ptr: usize,
    wait_counter: u16,
    loop_stack: Array<LoopFrame, 4>,
    loop_depth: usize,
    current_angle: f32,
    angular_speed: f32,
    position: Vec2,
}

fn step_emitter_vm(
    instance: &mut EmitterInstance,
    program: &[EmitterOpcode],
    pool: &mut ProjectilePool,
    player_pos: Vec2
) {
    if instance.wait_counter > 0 {
        instance.wait_counter -= 1;
        instance.current_angle += instance.angular_speed;
        return;
    }

    while instance.bytecode_ptr < program.len() {
        match program[instance.bytecode_ptr] {
            EmitterOpcode::Fire { angle_offset, speed, bullet_type } => {
                let theta = instance.current_angle + angle_offset;
                let vel = Vec2::new(speed * cos(theta), speed * sin(theta));
                pool.spawn_bullet(instance.position, vel, bullet_type);
                instance.bytecode_ptr += 1;
            }
            EmitterOpcode::WaitTicks { count } => {
                instance.wait_counter = count;
                instance.bytecode_ptr += 1;
                break; // Yield execution until next tick
            }
        }
    }
}
```



```

EmitterOpcode::AimAtPlayer => {
    let delta = player_pos - instance.position;
    instance.current_angle = atan2(delta.y, delta.x);
    instance.bytecode_ptr += 1;
}
EmitterOpcode::LoopStart { count } => {
    instance.loop_stack[instance.loop_depth] = LoopFrame {
        start_ptr: instance.bytecode_ptr + 1,
        remaining: count,
    };
    instance.loop_depth += 1;
    instance.bytecode_ptr += 1;
}
EmitterOpcode::LoopEnd => {
    let frame = &mut instance.loop_stack[instance.loop_depth - 1];
    frame.remaining -= 1;
    if frame.remaining > 0 {
        instance.bytecode_ptr = frame.start_ptr;
    } else {
        instance.loop_depth -= 1;
        instance.bytecode_ptr += 1;
    }
}
EmitterOpcode::Halt => {
    break;
}
}
}
}

```

4.6 Chapter Takeaways & Pattern Design Checklist

1. **Polar coordinates dominate:** Author bullet emitters in terms of angular step ($\Delta\theta$), radial speed (s), and base rotation (θ_0).
2. **Predictive aiming stops streaming:** Interception calculation via quadratic equations punishes players who mindlessly tap across the screen.
3. **Use bytecode VM or coroutines:** Decouple emitter choreography from engine code; compile declarative scripts into flat bytecode.
4. **Modulate harmonics:** Rose curves, epicycloids, and angular derivatives create organic, geometric bullet curtains without extra collision overhead.

In [\[Chapter 5\]\(file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch05_path_following_and_formation_flight.md\)](#), we shift from projectile dynamics to enemy choreography: parametric splines, arc-length parameterization, and squadron formation flight.


Chapter 5: Enemy Path Following, Kinematics & Formation Flight

A defining characteristic of arcade shmups is the acrobatic entrance and exit maneuvers of enemy waves. In games like *Galaga*, *Gradius*, *Ikaruga*, and *DoDonPachi*, enemy squadrons swoop across the screen in tight geometric formations, bank gracefully along curving trajectories, and break off into tactical attack runs.

Implementing this requires solving a notorious computer graphics and kinematics challenge: **Arc-Length Parameterized Spline Traversal**.

5.1 Parametric Splines in 2D Space

Linear waypoint interpolation (`pos = lerp(A, B, t)`) produces sharp, robotic corners that look jarring. To achieve smooth cinematic flight, we use **Parametric Splines**.



1. Cubic Bézier Curves

A Cubic Bézier curve is defined by four control points: $\mathbf{P}_0$ (start), $\mathbf{P}_1$ (start tangent handle), $\mathbf{P}_2$ (end tangent handle), and $\mathbf{P}_3$ (end):

$$\mathbf{B}(t) = (1-t)^3\mathbf{P}_0 + 3(1-t)^2t\mathbf{P}_1 + 3(1-t)t^2\mathbf{P}_2 + t^3\mathbf{P}_3, \quad t \in [0, 1]$$

Its velocity vector (first derivative) is:

$$\mathbf{B}'(t) = 3(1-t)^2(\mathbf{P}_1 - \mathbf{P}_0) + 6(1-t)t(\mathbf{P}_2 - \mathbf{P}_1) + 3t^2(\mathbf{P}_3 - \mathbf{P}_2)$$

2. Centripetal Catmull-Rom Splines

While Bézier curves are ideal for designer-authored standalone paths, **Catmull-Rom Splines** are preferred when stitching together long sequences of waypoints because the curve is guaranteed to pass *directly* through every control point with C^1 tangential continuity.

Standard uniform Catmull-Rom splines suffer from cusps and self-intersections when control points are spaced unevenly. We utilize the **Centripetal formulation** ($\alpha = 0.5$):

$$t_{i+1} = t_i + |\mathbf{P}_{i+1} - \mathbf{P}_i|^\alpha$$

RUST

```
// Centripetal Catmull-Rom Segment Evaluation
fn evaluate_catmull_rom(
    p0: Vec2, p1: Vec2, p2: Vec2, p3: Vec2,
    t: f32 // Normalized segment parameter [0, 1]
) -> Vec2 {
    let t2 = t * t;
    let t3 = t2 * t;

    // Standard Catmull-Rom Basis Matrix
    let v0 = (p2 - p0) * 0.5;
    let v1 = (p3 - p1) * 0.5;


    p1 * (2.0 * t3 - 3.0 * t2 + 1.0) +
    p2 * (-2.0 * t3 + 3.0 * t2) +
    v0 * (t3 - 2.0 * t2 + t) +
    v1 * (t3 - t2)
}
```

5.2 The Arc-Length Parameterization Problem & Speed Stabilization

The most common rookie engine bug in path-following is incrementing t linearly over time:

$$t_{\text{next}} = t_{\text{curr}} + \frac{\text{speed}}{\text{total_time}} \cdot \Delta t \quad \text{[INCORRECT!]}$$

Because $\mathbf{B}(t)$ is non-linear in spatial distance, evaluating equal increments of t causes the enemy ship to **violently accelerate through stretched sections and crawl through tight curves**.



The Arc-Length Integral

The physical distance $s(t)$ traveled along a curve from parameter 0 to t is the integral of the speed:

$$s(t) = \int_0^t |\mathbf{B}'(u)|, du = \int_0^t \sqrt{\left(\frac{dx}{du}\right)^2 + \left(\frac{dy}{du}\right)^2}, du$$

This integral has no general closed-form analytical solution for cubic polynomials. We must compute it numerically.

5.3 Look-Up Table (LUT) Inversion and Simpson's Rule Integration

To achieve $O(1)$ constant-speed path sampling at runtime, we pre-calculate an **Arc-Length Look-Up Table (LUT)** when baking or loading the level.

CODE

FORWARD INTEGRATION
t in [0.0, 1.0]
|
▼ (Numerical Simpson's Rule)
Cumulative Length s(t)

LUT INVERSION
Distance s in [0, L]
|
▼ (Binary Search + Lerp)
Exact Curve Parameter t(s)

RUST

```
// Arc-Length Parameterization Data Structure
const LUT_SAMPLES: usize = 128; // 128 samples provides sub-pixel precision

struct SplinePathLUT {
    samples_t: Array<f32, LUT_SAMPLES>,
    samples_dist: Array<f32, LUT_SAMPLES>,
    total_length: f32,
}

// Numerical Integration using Composite Simpson's Rule
fn bake_spline_lut(p0: Vec2, p1: Vec2, p2: Vec2, p3: Vec2) → SplinePathLUT {
    let mut lut = SplinePathLUT::default();
    lut.samples_t[0] = 0.0;
    lut.samples_dist[0] = 0.0;

    let mut cumulative_dist = 0.0;
    let n = LUT_SAMPLES - 1;
    let dt = 1.0 / (n as f32);

    for i in 1..=n {
        let t_curr = (i as f32) * dt;
        let t_prev = ((i - 1) as f32) * dt;
        let t_mid = (t_prev + t_curr) * 0.5;

        // Composite Simpson's rule: (dt / 6) * (f(a) + 4f(m) + f(b))
        let speed_prev = evaluate_derivative(p0, p1, p2, p3, t_prev).length();
        let speed_mid = evaluate_derivative(p0, p1, p2, p3, t_mid).length();
        let speed_curr = evaluate_derivative(p0, p1, p2, p3, t_curr).length();

        let step_dist = (dt / 6.0) * (speed_prev + 4.0 * speed_mid + speed_curr);
        cumulative_dist += step_dist;

        lut.samples_t[i] = t_curr;
        lut.samples_dist[i] = cumulative_dist;
    }

    lut.total_length = cumulative_dist;
    lut
}
```

Inverting the LUT at Runtime

To sample the curve at an exact physical distance $d \in [0, \text{total_length}]$:

RUST

```
// Invert Arc-Length Table: Given Distance → Return Normalized Parameter t
fn sample_spline_at_distance(lut: &SplinePathLUT, distance: f32) → f32 {
    let clamped_d = clamp(distance, 0.0, lut.total_length);

    // Binary search to locate the bounding distance interval [dist[i], dist[i+1]]
    let mut low = 0;
    let mut high = LUT_SAMPLES - 1;

    while low < high - 1 {
        let mid = (low + high) / 2;
        if lut.samples_dist[mid] ≤ clamped_d {
            low = mid;
        } else {
            high = mid;
        }
    }

    // Linearly interpolate between the two closest sample points
    let d0 = lut.samples_dist[low];
    let d1 = lut.samples_dist[high];
    let segment_alpha = if (d1 - d0) > 0.0001 { (clamped_d - d0) / (d1 - d0) } else { 0.0 };

    let t0 = lut.samples_t[low];
    let t1 = lut.samples_t[high];

    t0 + segment_alpha * (t1 - t0)
}
```


5.4 Autonomous Steering Behaviors and Target Interception

Not all enemies follow rigid, pre-baked splines. Interceptor drones, suicide craft, and elite escorts utilize **Reynolds Autonomous Steering Behaviors**.

$$\vec{F}_{\text{steering}} = \text{truncate}(\left(\vec{v}_{\text{desired}} - \vec{v}_{\text{current}} \right), F_{\text{max}}) ;$$

CODE

REYNOLDS ARRIVE BEHAVIOR
Slowing Radius R





RUST

```
// 2D Reynolds Steering Behaviors
struct SteeringAgent {
    position: Vec2,
    velocity: Vec2,
    max_speed: f32,
    max_force: f32,
}

impl SteeringAgent {
    // Seek with Arrival Deceleration Zone
    fn arrive(&self, target: Vec2, slowing_radius: f32) → Vec2 {
        let to_target = target - self.position;
        let distance = to_target.length();

        if distance < 0.001 {
            return -self.velocity; // Stop completely
        }

        // Ramp down speed inside slowing radius
        let target_speed = if distance < slowing_radius {
            self.max_speed * (distance / slowing_radius)
        } else {
            self.max_speed
        };

        let desired_velocity = (to_target / distance) * target_speed;
        let steering_force = desired_velocity - self.velocity;

        truncate_vector(steering_force, self.max_force)
    }


    // Path Following with Predictive Lookahead Point
    fn follow_path(&self, lut: &SplinePathLUT, current_dist: &mut f32, lookahead_dist: f32, dt: f32) {
        // Advance virtual anchor point along spline
        *current_dist += self.max_speed * dt;
        let target_dist = *current_dist + lookahead_dist;

        let t_target = sample_spline_at_distance(lut, target_dist);
        let target_pos = evaluate_spline_position(t_target);

        self.arrive(target_pos, 40.0)
    }
}
```

5.5 Squadron Hierarchy and Formation Flight Matrices

Authoring complex wave swoops for a 5-ship squadron does not require 5 individual spline paths. Instead, we choreograph **one Virtual Leader Anchor**, and evaluate follower positions using **Local Transform Offsets**.



The 2D Formation Transformation Equation

Let the virtual anchor have position $\vec{P}_{\text{anchor}}(t)$ and heading angle $\theta_{\text{anchor}}(t)$ (*derived from the spline tangent derivative* $\mathbf{B}'(t)$).

For a squadron member with local formation offset $\vec{O}_i = (x_{\text{local}}, y_{\text{local}})$:

$$\mathbf{R}(\theta) = [\cos(\theta) \quad -\sin(\theta) \quad \sin(\theta) \quad \cos(\theta)]$$

$$\vec{P}_{\text{world}, i} = \vec{P}_{\text{anchor}} + \mathbf{R}(\theta) \cdot \vec{O}_i$$

RUST

```
// Squadron Formation Update Routine
struct FormationWingman {
    entity_handle: EntityHandle,
    local_offset: Vec2,
    bank_angle_bias: f32,
}

struct Squadron {
    virtual_anchor_dist: f32,
    speed: f32,
    spline_lut_id: usize,
    wingmen: Array<FormationWingman, 8>,
    count: usize,
}

fn update_squadron_formation(squad: &mut Squadron, engine: &mut Engine, dt: f32) {
    squad.virtual_anchor_dist += squad.speed * dt;

    let lut = engine.get_spline_lut(squad.spline_lut_id);
    let t = sample_spline_at_distance(lut, squad.virtual_anchor_dist);

    let anchor_pos = evaluate_spline_position(lut, t);
    let anchor_tangent = evaluate_spline_tangent(lut, t);
    let heading_angle = atan2(anchor_tangent.y, anchor_tangent.x);

    let cos_h = cos(heading_angle);
    let sin_h = sin(heading_angle);

    for i in 0..squad.count {
        let wingman = &squad.wingmen[i];
        if let Some(entity) = engine.get_entity_mut(wingman.entity_handle) {
            // Apply 2D rotation matrix: R(theta) * offset
            let rotated_x = wingman.local_offset.x * cos_h - wingman.local_offset.y * sin_h;
            let rotated_y = wingman.local_offset.x * sin_h + wingman.local_offset.y * cos_h;

            entity.transform.position = anchor_pos + Vec2::new(rotated_x, rotated_y);
            // Point ship sprite in direction of flight with banking roll
            entity.transform.rotation = heading_angle;
        }
    }
}
```

5.6 Chapter Takeaways & Kinematics Checklist

1. **Never step raw t on splines:** Always construct an Arc-Length Look-Up Table (LUT) with numerical Simpson's rule integration.
2. **Prefer Centripetal Catmull-Rom for multi-point paths:** Eliminates loop artifacts and cusps.
3. **Use Virtual Leader Anchors for squadrons:** Saves CPU memory and makes formation editing intuitive for designers.
4. **Blend splines with steering:** Allow enemy craft to follow splines for entrance choreographies, then smoothly detach into Reynolds steering behaviors for aggressive targeting runs.

In [Chapter 6](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch06_level_representation_and_scripting.md), we construct the stage timeline engine: event queues, trigger systems, level scripting DSLs, and deterministic replay capture.

Chapter 6: Level Representation, Timeline Sequencing & Scripting

In platformers and RPGs, levels are defined spatially: tiles, collision polygons, and triggers placed across a 2D grid. In a classic 2D scrolling shooter, spatial position is secondary. A shmup level is fundamentally a **musical score of choreographed time events**.

This chapter explores how to represent, sequence, script, and replay entire stages with sub-frame precision.

6.1 Spatial vs. Timeline-Driven Level Models

Early 1980s shooters tied enemy spawns directly to camera scroll distance:

Spawn Condition : $Y_{\text{camera}} \geq Y_{\text{trigger}}$ [SPATIAL MODEL]



Why Pure Spatial Scrolling Breaks Down


1. **Camera Pauses (Mid-Boss Encounters):** When the camera halts for a 45-second boss battle, distance stops advancing ($\Delta Y = 0$), yet internal attack patterns, adds, and timers continue running.

2. **Variable Camera Speeds & Acceleration:** Modern shmups frequently modulate scroll velocity (e.g., hyper-speed hyperspace dashes, zero-G drift sections, or reverse scrolling).
3. **Pacing Gating (Clear-to-Advance):** High-tempo arcade games hold the camera until all enemies in a wave are eliminated, rewarding skilled speed-runners with faster level progression.

The Modern Master Timeline Model

A modern shmup stage is modeled as a **Time-Indexed Event Stream** driven by a master level clock

t_{stage} :



6.2 Multi-Track Timeline Sequencing Data Structures

To organize complex stage choreographies without creating monolithic script files, we decompose the level into **Parallel Timeline Tracks**.

CODE

```

TRACK 0: ENEMY SPAWNS      [W1: 4 Drone] [W2: 2 Heavy] [W3: Swarm]
TRACK 1: CAMERA VELOCITY   [200 px/s] [400 px/s] [PAUSE: 0]
TRACK 2: ENVIRONMENT/FX    [Cloud Layer] [Asteroid Storm] [Warning!]
TRACK 3: SCRIPT TRIGGERS   [Save Point 1] [Gate: W2]

```

The Min-Heap / Priority Queue Timeline Dispatcher

Because events are scheduled chronologically, we store un-triggered timeline events in a **Min-Heap** sorted by **trigger timestamp**. At every simulation tick, we peek at the top of the heap; if `event.timestamp ≤ current_time`, we pop and execute it in $O(1)$ amortized time.



RUST

```

// Priority Queue Stage Event Dispatcher
enum StageEventPayload {
    SpawnSquadron { squadron_def_id: u32, spline_id: u32, speed: f32 },
    SetScrollSpeed { new_speed: f32, transition_time: f32 },
    PlayDialogue { voice_id: u32, portrait_id: u32, duration: f32 },
    LockCameraAtBarrier { barrier_id: u32 },
    TriggerBossPhase { boss_id: u32, phase_index: u8 },
}

struct StageEvent {
    timestamp: f64,           // Exact trigger time in seconds
    payload: StageEventPayload,
}

struct StageTimeline {
    current_time: f64,
    event_queue: BinaryMinHeap<StageEvent>, // Sorted ascending by timestamp
    active_gates: Array<GateCondition, 8>,
}

impl StageTimeline {
    fn tick(&mut self, dt: f64, engine: &mut Engine) {
        // If a barrier gate is blocking time progression, check its condition
        if self.is_gated(engine) {
            return;
        }

        self.current_time += dt;

        // Drain all events whose timestamp has passed
        while let Some(event) = self.event_queue.peek() {
            if event.timestamp <= self.current_time {
                let ready_event = self.event_queue.pop().unwrap();
                self.dispatch_event(ready_event, engine);
            } else {
                break; // Earliest upcoming event is in the future
            }
        }
    }

    fn dispatch_event(&mut self, event: StageEvent, engine: &mut Engine) {
        match event.payload {
            StageEventPayload::SpawnSquadron { squadron_def_id, spline_id, speed } => {
                engine.spawn_squadron(squadron_def_id, spline_id, speed);
            }
            StageEventPayload::SetScrollSpeed { new_speed, transition_time } => {

```

```

        engine.camera_system.set_target_speed(new_speed, transition_time);
    }
    StageEventPayload::LockCameraAtBarrier { barrier_id } => {
        self.active_gates.push(GateCondition::WaitForBarrierDestruction(barrier_id));
    }
    // ... remaining payload handlers
}
}
}

```

6.3 Scripting Engines & Coroutine Level Orchestration

Declarative timelines (JSON/YAML) are fantastic for static wave spawns, but dynamic level pacing (e.g., *"wait until all 4 escort cruisers are dead, then spawn 3 heavy mechs"* or *"if player has Rank > 80%, spawn elite red battalion"*) is vastly simpler to write imperatively using **Coroutines** (Lua, Wren, or C#/Rust async state machines).

COROUTINE EXECUTION FLOW:

```

[Spawn Wave 1] → Yield: Wait(5.0s) → [Spawn Escorts] → Yield: WaitForAllDead(Wave 2)
                                                    |
                                                    (Resumes instantly
                                                    when last enemy dies)

```

RUST

```
// Pseudocode: Stage Scripting Coroutine DSL
async fn execute_stage_1(stage: &mut StageContext) {
    // 00:00 - Introduction & Ambient Starfield
    stage.set_background("deep_space_nebula");
    stage.set_scroll_speed(150.0, 0.0);
    stage.wait_seconds(3.0).await;

    // 00:03 - Opening Wave: Pincer Formation
    let w1_left = stage.spawn_squadron("drone_scout", "spline_left_dive", 300.0);
    let w1_right = stage.spawn_squadron("drone_scout", "spline_right_dive", 300.0);
    stage.wait_seconds(4.0).await;

    // 00:07 - Dynamic Difficulty Check (Rank Scaling)
    if stage.get_battle_rank() > 0.75 {
        // High rank bonus wave
        stage.spawn_squadron("elite_stealth_fighter", "spline_swoop_center", 450.0);
    }

    // 00:15 - Gated Mid-Boss Encounter
    stage.set_scroll_speed(0.0, 2.0); // Decelerate camera to a halt
    let mid_boss = stage.spawn_boss("crustacean_dreadnought_v1", Vec2::new(320.0, -100.0));

    // Engine halts stage timeline progression until mid-boss entity is destroyed
    stage.wait_until_destroyed(mid_boss).await;

    // Resume high-speed scroll after midboss kill
    stage.trigger_screen_flash(1.0, 1.0, 1.0);
    stage.set_scroll_speed(600.0, 1.0); // Warp speed transition
    stage.wait_seconds(2.0).await;
}
```

6.4 Deterministic State Snapshotting & Input-Frame Replay

Replays in high-level shmups are not video recordings. They are **Input-Stream Logs**. An entire 45-minute playthrough can be stored in a file measuring less than **500 KB**.

CODE

REPLAY ARCHITECTURE

Play Session: [Input Poller] → Save to File: [Replay Stream (.rpl)]

Playback: [Fixed Sim Loop] ← Read from File
 (Zero GPU / Headless Verification capable at 10,000 FPS)

1. The Input Frame Buffer Format

At every fixed simulation tick (**60 Hz**), we pack player input into a compact 16-bit struct:

RUST

```
// Compact 2-Byte Input Frame Representation
struct InputFrame {
    buttons: u8, // Bitfield: [Shot:1, Bomb:1, Focus/Slow:1, WeaponSwitch:1, Start:1]
    axis_x: i8,  // Clamped -127 to +127 (or -1, 0, 1 for digital d-pad)
    axis_y: i8,  // Clamped -127 to +127
}
```

2. Seeded Deterministic PRNG

Never call standard library non-deterministic random functions (`rand()` or `Math.random()`). Use a seedable, fast, deterministic generator such as **PCG32** or **xoshiro256****.

RUST

```
// Seedable Deterministic PCG32 PRNG
struct PCG32 {
    state: u64,
    inc: u64,
}

impl PCG32 {
    fn new(seed: u64, sequence: u64) → Self {
        let mut pcg = PCG32 { state: 0, inc: (sequence << 1) | 1 };
        pcg.next_u32();
        pcg.state += seed;
        pcg.next_u32();
        pcg
    }

    fn next_u32(&mut self) → u32 {
        let old_state = self.state;
        self.state = old_state.wrapping_mul(6364136223846793005).wrapping_add(self.inc);
        let xorshifted = (((old_state >> 18) ^ old_state) >> 27) as u32;
        let rot = (old_state >> 59) as u32;
        (xorshifted >> rot) | (xorshifted << ((!rot + 1) & 31))
    }

    fn next_f32_range(&mut self, min: f32, max: f32) → f32 {
        let val = (self.next_u32() as f64) / (u32::MAX as f64);
        (min + (val as f32) * (max - min))
    }
}
```

3. Savestates & Instant Practice Mode Snapshots

To implement a professional "Practice Mode" where players can jump instantly to any phase of a boss or section of a level, the engine serializes the complete simulation state:

RUST

```
// Complete Simulation Savestate Snapshot
struct SimulationSnapshot {
    tick_index: u64,
    timeline_time: f64,
    prng_state: PCG32,
    player_data: PlayerState,
    active_bullets: ProjectilePool,
    active_enemies: EnemyPool,
    spatial_grid: SpatialGrid,
    event_bus: EventBus,
}
```

Because our architecture uses flat, contiguous arrays and generational handles with zero heap pointers, saving and restoring a state is an instantaneous memory block copy (`memcpy`), taking under **0.1 ms**.

6.5 Chapter Takeaways & Pipeline Checklist

1. **Decouple time from camera scroll:** Use a timeline clock t_{stage} with priority-queue event dispatch.
2. **Support asynchronous barrier gating:** Allow coroutines to pause time progression until wave conditions or boss phases are resolved.
3. **Replay by logging inputs:** Capture a 2-byte input struct per tick; combine with a seeded PRNG for 100% deterministic replays.
4. **Instant savestates:** Flat data layouts enable zero-cost `memcpy` snapshotting for practice modes and tool debugging.

In [Chapter 7](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch07_boss_architecture_and_choreography.md), we examine the climax of every stage: multi-phase boss architecture, hierarchical scene graphs, and dynamic difficulty rank calculus.


Chapter 7: Boss Architecture & Choreography

The boss encounter is the theatrical and mechanical crescendo of a shmup stage. From the multi-stage mechanical behemoths of *Darius* and *R-Type* to the divine, pattern-weaving avatars of *Touhou Project* and *Mushihimesama*, boss battles test the player's routing, reaction speed, and nerve.

Engineering a boss requires coordinating **Hierarchical State Machines (HSMs)**, multi-part 2D scene graphs, bullet clear/cancel transitions, visual telegraphing, and dynamic difficulty scaling.

7.1 Control Architectures: HSMs vs. Behavior Trees

A boss is not a simple linear enemy. It progresses through multiple distinct health bars, reveals new attack forms, reacts to player proximity, and enters desperation states when near death.



Hierarchical State Machine (HSM) vs. Behavior Trees (BT)

While Behavior Trees are common in 3D open-world AI, **Hierarchical State Machines (HSMs)** are far superior for shmup bosses:

- **Deterministic Predictability:** Shmup patterns must be strictly choreographed so players can memorize dodging geometry.
- **Hierarchical Scoping:** A boss can share global sub-states (e.g., *Core Taking Damage Flash*, *Timer Countdown*, *Parts Orbiting*) while switching specific attack sub-states.



RUST

```
// Hierarchical Boss State Pattern
enum BossPhaseState {
    Entrance { timer: f32, target_pos: Vec2 },
    Phase1_DualSpirals { cycle_timer: f32, attack_variant: u8 },
    PhaseTransition { timer: f32, next_phase: u8 },
    Phase2_LaserSweeps { sweep_angle: f32, direction: f32 },
    Enrage_BulletTornado { intensity: f32 },
    Defeated { explosion_timer: f32, step: usize },
}

struct BossController {
    current_phase: BossPhaseState,
    phase_index: u8,
    max_phases: u8,
    health_current: f32,
    health_max_per_phase: f32,
    phase_timeout_seconds: f32,
    phase_timer: f32,
    is_invulnerable: bool,
}

impl BossController {
    fn update(&mut self, dt: f32, engine: &mut Engine) {
        self.phase_timer += dt;

        // Check for Phase Timeout (Prevent infinite stalling)
        if self.phase_timer ≥ self.phase_timeout_seconds && !self.is_invulnerable {
            self.trigger_phase_transition(engine, true /* timed_out */);
            return;
        }

        // Check for Health Depletion
        if self.health_current ≤ 0.0 && !self.is_invulnerable {
            self.trigger_phase_transition(engine, false /* killed */);
            return;
        }

        // Execute phase-specific logic
        match &mut self.current_phase {
            BossPhaseState::Phase1_DualSpirals { cycle_timer, attack_variant } => {
                *cycle_timer += dt;
                // Dispatch emitter barrages...
            }
            BossPhaseState::PhaseTransition { timer, next_phase } => {
                *timer -= dt;
                if *timer ≤ 0.0 {

```

```

        self.enter_phase(*next_phase, engine);
    }
}
// ... remaining state logic
}
}
}

```

7.2 Multi-Part Hierarchical Scene Graphs & Destructible Entities

Iconic shmup bosses are massive composite structures. A single boss might consist of a main chassis, two destructible armored wings, four independently aiming laser turrets, and an exposed core.

CODE

```

BOSS SCENE GRAPH TOPOLOGY
    [ Main Core ]
    (Root Transform)
    /           \
[ Left Wing ]   [ Right Wing ]
(Local: -120, +20) (Local: +120, +20)
 /   \         /   \
[Laser Turret] [Armor Plate] [Laser Turret] [Armor Plate]

```

2D Forward Kinematics Matrix Propagation

Each child part maintains a **Local Transform** $(\vec{p}_{\text{local}}, \theta_{\text{local}}, \vec{s}_{\text{local}})$. The engine updates the hierarchy using standard 2D homogeneous transformation matrices:

$$\mathbf{M}_{\text{world}, \text{child}} = \mathbf{M}_{\text{world}, \text{parent}} \times \mathbf{M}_{\text{local}, \text{child}}$$

RUST

```
// 2D Hierarchical Scene Node
struct SceneNode2D {
    local_pos: Vec2,
    local_rotation: f32,
    world_matrix: Mat3x2,
    parent_index: Option<usize>,
    is_destructible: bool,
    health: f32,
    is_alive: bool,
    emitter_id: Option<usize>,
}

fn update_scene_hierarchy(nodes: &mut [SceneNode2D]) {
    for i in 0..nodes.len() {
        let local_matrix = Mat3x2::from_pos_rot(nodes[i].local_pos, nodes[i].local_rotation);

        nodes[i].world_matrix = match nodes[i].parent_index {
            Some(parent_idx) => nodes[parent_idx].world_matrix * local_matrix,
            None => local_matrix, // Root node
        };
    }
}
```

Mechanical Consequences of Sub-Component Destruction

Destruction of a sub-component should dynamically reshape the boss's mechanics:

- **Disabling Attacks:** Destroying the left missile bay disables that emitter entirely.
- **Enrage Compensation:** When both wings are severed, the core enters an aggressive rapid-fire state.
- **Score & Secret Routing:** Destroying all parts before destroying the core awards a lucrative *Technical Destruction Bonus* or unlocks secret second-loop paths.

7.3 Phase Transitions, Timeouts, and Enrage Choreography

Phase transitions require careful state handling to prevent unfair player deaths.

CODE

```
PHASE 1 FINISH → 1. Trigger Bullet-Cancel (All bullets → Gems/Items)
                  2. Grant Boss Invulnerability (I-Frames)
                  3. Play Stagger/VFX Animation
                  4. Reposition Boss to Phase 2 Origin
                  5. Initialize Phase 2 Health Bar & Emitters
```


RUST

```
// Bullet Cancel & Score Conversion Routine
fn cancel_all_enemy_bullets(pool: &mut ProjectilePool, engine: &mut Engine) {
    for i in 0..pool.count {
        if pool.is_active(i) {
            let pos = pool.get_position(i);
            pool.deactivate(i);

            // Spawn Score Crystal / Gem at bullet position
            engine.spawn_score_pickup(pos, PickupType::ScoreGem);
            // Spawn subtle dissipation particle
            engine.particle_system.spawn_dissipate(pos);
        }
    }
}
```

7.4 Visual Telegraphing and Fairness Rules

High-density bullet hell games maintain a sacred contract with the player: **every death must be the player's fault**. Unavoidable attacks, off-screen snipes, and deceptive hitboxes break this contract.



Core Telegraphing Principles

1. **Low-Alpha Pre-Fire Guides:** Super-lasers and sniper shots must project a transparent tracking line or aiming laser **30–60** frames before turning lethal.
2. **Audio Stingers & Pitch Shifts:** High-threat attacks should precede with an unmistakable audio charge-up sound.
3. **Palette & Contrast Isolation:**
 - Boss bullets must use high-contrast vibrant colors (e.g., magenta, cyan, bright amber) with white cores.
 - Backgrounds behind bosses must be desaturated or dimmed to guarantee immediate bullet silhouette visibility.

7.5 Battle Rank: Dynamic Difficulty Adjustment (DDA) Calculus

To challenge world-class arcade veterans without alienating beginners, commercial shmup bosses scale dynamically according to the **Battle Rank Formula**.

CODE

DYNAMIC RANK MODULATION
Rank Value (R) in [0.0, 1.0]

Bullet Count Speed Spread Arc Health

$N = N_0 \cdot (1 + R)$ $v = v_0 \cdot (1 + 0.5R)$ $\Phi = \Phi_0 \cdot (1 - 0.2R)$ $HP = HP_0 \cdot (1 + 0.3R)$

RUST

```
// Dynamic Difficulty Rank Calculator
struct RankSystem {
    current_rank: f32, // Normalized 0.0 (Easiest) to 1.0 (Hardest)
    rank_per_second: f32,
    rank_per_powerup: f32,
    rank_loss_per_death: f32,
    rank_loss_per_bomb: f32,
}

impl RankSystem {
    // Compute scaled bullet count for an emitter based on rank
    fn scale_bullet_count(&self, base_count: usize, max_bonus: usize) → usize {
        base_count + ((max_bonus as f32) * self.current_rank).round() as usize
    }

    // Compute scaled bullet velocity based on rank
    fn scale_bullet_speed(&self, base_speed: f32, max_multiplier: f32) → f32 {
        base_speed * (1.0 + (max_multiplier - 1.0) * self.current_rank)
    }

    // Compute boss health scaling
    fn scale_boss_health(&self, base_health: f32) → f32 {
        base_health * (1.0 + 0.5 * self.current_rank)
    }
}
```

7.6 Chapter Takeaways & Boss Design Checklist

1. **Use HSMs for phase control:** Keep attack states strictly separated from entrance and defeat choreography.
2. **Transform hierarchies via 2D matrix multiplication:** Model wings, turrets, and armor plates as child scene nodes.
3. **Always cancel bullets on phase clear:** Reward the player with score gems and visual breathing room.

4. **Telegraph high-speed attacks:** Never fire instant-kill beams without a pre-fire guide laser or audio cue.
5. **Tune patterns via Battle Rank:** Make bullet count and velocity scale cleanly with player skill.

In [Chapter 8](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch08_level_editor_architecture_and_tooling.md), we build the engine's creative control center: the in-engine level editor, timeline scrubber, interactive spline handles, and command pattern undo/redo systems.


Chapter 8: Level Editor Architecture & Tooling

A game engine is only as expressive as its authoring tools. Handcrafting thousands of spline coordinates, enemy wave timings, and bullet emitter parameters in raw JSON or code files is slow, tedious, and prone to calibration errors.

This chapter details the architecture of an **In-Engine Level & Wave Editor**, featuring multi-track timeline scrubbing, interactive Bézier tangent gizmos, a robust Command-Pattern undo/redo stack, and live simulation hot-reloading.

8.1 In-Engine Immediate GUI vs. External Editor Architecture

When building tooling for a high-performance 2D shmup, developers face a classic architectural choice: an **External Standalone IDE** (Qt, WPF, Electron) vs. an **In-Engine Embedded Editor** (Dear ImGui, Nuklear).




Why In-Engine Immediate-Mode Tooling Reigns Supreme

1. **Zero IPC / Serialization Friction:** The editor runs in the same memory space as the engine, directly mutating live entity pools and spline LUTs without network sockets or inter-process pipes.
2. **Exact Physics & Shader Fidelity:** What the designer sees while dragging a spline handle is rendered using the exact GPU shaders, particle buffers, and post-processing passes as the final game.
3. **Instant Play-Edit Toggle:** Pressing `F1` or `Spacebar` toggles between pausing the timeline to tweak a curve and instantly testing the dodge routing in real time.

8.2 Multi-Track Timeline Scrubber with Scrubbing & Step Precision

The core of a shmup editor is the **Multi-Track Timeline Canvas**. Designers must be able to drag a scrubber needle across time, jump between wave markers, and step forward or backward by single simulation ticks (**16.6 ms**).



The Bidirectional Time-Scrubbing Algorithm

Moving forward in time is simple (advance simulation ticks). Scrubbing *backwards* in time is mathematically non-trivial in a mutable simulation.

We solve reverse scrubbing using **Keyframe State Snapping + Fast-Forward Re-Simulation**:

CODE

SCRUBBING BACKWARDS FROM t=14.3s TO t=11.0s

1. Find nearest previous snapshot: Keyframe at t=10.0s (Tick 600)
2. Fast-copy snapshot memory: memcpy(live_sim, snapshot_10s)
3. Headless fast-forward simulation: Run 60 ticks without rendering
4. Arrive at target time: Exact state reconstructed at t=11.0s!

RUST

```
// Timeline Scrubbing Engine
struct EditorScrubber {
    timeline_duration: f64,
    current_time: f64,
    is_paused: bool,
    playback_speed: f64, // 0.25x, 0.5x, 1.0x, 2.0x
    snapshot_interval: f64, // Snapshot every 5.0 seconds
    snapshots: Map<u64, SimulationSnapshot>,
}

impl EditorScrubber {
    fn scrub_to_time(&mut self, target_time: f64, engine: &mut Engine) {
        self.current_time = clamp(target_time, 0.0, self.timeline_duration);
        let target_tick = (self.current_time * 60.0).round() as u64;


        // 1. Locate the closest preceding keyframe snapshot
        let snapshot_key = (target_tick / 300) * 300; // Snapshots every 300 ticks (5s)

        if let Some(snapshot) = self.snapshots.get(&snapshot_key) {
            engine.restore_snapshot(snapshot);

            // 2. Fast-forward headless simulation ticks to exact target
            let ticks_to_advance = target_tick - snapshot.tick_index;
            for _ in 0..ticks_to_advance {
                engine.headless_fixed_update(1.0 / 60.0);
            }
        }
    }
}
```

8.3 Interactive Bezier/Spline Canvas & Tangent Handle Gizmos

Designing enemy flight paths requires direct spatial manipulation of spline control points and tangent handles directly on the game viewport.



Screen-to-World Ray Picking and Handle Selection

When the designer clicks the mouse on the viewport:

RUST

```
// Handle Picking & Tangent Constraint System
enum TangentConstraint {
    Mirrored, // Opposite handle matches angle and length
    Aligned,  // Opposite handle matches angle, free length
    Free,     // Tangents completely independent (sharp corners)
}

struct SplineGizmo {
    selected_spline_id: Option<usize>,
    selected_node_idx: Option<usize>,
    selected_handle: Option<HandleType>, // Anchor, InTangent, OutTangent
}

fn handle_viewport_click(gizmo: &mut SplineGizmo, splines: &[Spline], mouse_world: Vec2) {
    const PICK_RADIUS: f32 = 12.0;

    for (s_idx, spline) in splines.iter().enumerate() {
        for (n_idx, node) in spline.nodes.iter().enumerate() {
            if distance(mouse_world, node.anchor) ≤ PICK_RADIUS {
                gizmo.selected_spline_id = Some(s_idx);
                gizmo.selected_node_idx = Some(n_idx);
                gizmo.selected_handle = Some(HandleType::Anchor);
                return;
            }
            if distance(mouse_world, node.out_tangent) ≤ PICK_RADIUS {
                gizmo.selected_spline_id = Some(s_idx);
                gizmo.selected_node_idx = Some(n_idx);
                gizmo.selected_handle = Some(HandleType::OutTangent);
                return;
            }
        }
    }
}
```

Live Ghosting and Speed Heatmaps


As a designer drags a tangent handle, the editor immediately:

1. Re-bakes the Arc-Length Look-Up Table (LUT) in $< 10\mu\text{s}$.

2. Renders a **Ghost Trail**: a dotted visualization along the curve where the distance between dots represents physical velocity, and color shifts from green to red based on centrifugal curvature acceleration ($\kappa = \frac{|\mathbf{B}' \times \mathbf{B}''|}{|\mathbf{B}'|^3}$).

8.4 The Command Pattern for Unlimited Undo/Redo

Every mutation performed in the editor—moving a control point, modifying a bullet emitter angle, inserting an enemy wave—must be recorded as a command on an **Undo/Redo Stack**.



Merging Continuous Mouse Drag Actions (Transaction Coalescing)

If a user drags a spline handle across the screen for 2 seconds, generating 120 mouse move events, we must not flood the undo stack with 120 tiny steps. We implement **Command Merging**:



RUST

```
// Editor Command Pattern with Continuous Action Coalescing
trait EditorCommand {
    fn execute(&mut self, stage: &mut StageData);
    fn undo(&mut self, stage: &mut StageData);
    fn can_merge_with(&self, next: &dyn EditorCommand) → bool;
    fn merge_with(&mut self, next: Box<dyn EditorCommand>);
}

struct MoveSplineNodeCommand {
    spline_id: usize,
    node_idx: usize,
    old_position: Vec2,
    new_position: Vec2,
    timestamp: f64,
}

impl EditorCommand for MoveSplineNodeCommand {
    fn execute(&mut self, stage: &mut StageData) {
        stage.splines[self.spline_id].nodes[self.node_idx].anchor = self.new_position;
        stage.rebake_spline_lut(self.spline_id);
    }


    fn undo(&mut self, stage: &mut StageData) {
        stage.splines[self.spline_id].nodes[self.node_idx].anchor = self.old_position;
        stage.rebake_spline_lut(self.spline_id);
    }

    fn can_merge_with(&self, next: &dyn EditorCommand) → bool {
        // Merge drag updates on the same node occurring within 0.5s of each other
        if let Some(other) = next.as_any().downcast_ref::<MoveSplineNodeCommand>() {
            return self.spline_id == other.spline_id &&
                self.node_idx == other.node_idx &&
                (other.timestamp - self.timestamp) < 0.5;
        }
        false
    }

    fn merge_with(&mut self, next: Box<dyn EditorCommand>) {
        let other = next.as_any().downcast_ref::<MoveSplineNodeCommand>().unwrap();
        self.new_position = other.new_position;
        self.timestamp = other.timestamp;
    }
}
```

8.5 Live Simulation Hot-Reloading & In-Situ State Injection

To maximize iteration speed, the engine must support **Live Asset Hot-Reloading**. When a designer saves a stage file or tweaks an emitter script in an external text editor:





8.6 Chapter Takeaways & Tooling Checklist

1. **Embed tools directly in-engine:** Use immediate-mode GUI overlays (Dear ImGui) for zero IPC latency and identical graphics fidelity.
2. **Implement bidirectional scrubbing:** Combine keyframe snapshots with headless forward ticks to scrub time backwards smoothly.
3. **Coalesce continuous commands:** Prevent drag events from cluttering the undo/redo stack.
4. **Provide visual feedback:** Render speed-colored ghost trails and arc-length tangent handles on the live viewport.

In [Chapter 9](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch09_vfx_audio_and_game_feel.md), we explore the sensory art and engineering of "juice": GPU particle batching, shockwave distortion shaders, trauma-decay screen shake, and audio voice coalescing.

Chapter 9: Visual FX, Audio, and "Game Feel" (Juice)


The difference between a dry, clinical tech demo and an exhilarating arcade masterpiece lies in "**Juice**"—the sensory feedback systems that amplify every action, explosion, and near-miss.

In a genre defined by extreme kinetic density, visual and auditory effects must not only look and sound spectacular; they must also be engineered for extreme efficiency so they never compromise the 60 FPS deterministic simulation budget.

9.1 High-Volume GPU Sprite Batching & Instanced Particles

Rendering 30,000 projectiles, 10,000 debris sparks, and 500 ships using individual draw calls (`glDrawElements` / `DrawIndexed`) will stall the graphics driver with API overhead.

The entire frame's bullets and particles must be dispatched in **one or two Instanced Draw Calls**.



GPU Instance Buffer Layout

We pack instance attributes into a tight 32-byte struct aligned to GPU memory standards:

RUST

```
// GPU Hardware Instance Struct (32 Bytes)
struct GPUInstanceData {
    world_pos: Vec2,      // 8 bytes (x, y)
    scale: Vec2,          // 8 bytes (scale_x, scale_y)
    rotation_rad: f32,    // 4 bytes
    uv_rect: [u16; 4],    // 8 bytes (atlas u, v, w, h normalized)
    tint_color: u32,      // 4 bytes (RGBA8 packed)
}
```


GLSL

```
// GLSL / HLSL Instanced Vertex Shader
#version 450 core
layout(location = 0) in vec2 in_quad_vertex; // Local quad [-0.5, 0.5]
layout(location = 1) in vec2 in_world_pos;   // Per-instance
layout(location = 2) in vec2 in_scale;       // Per-instance
layout(location = 3) in float in_rotation;   // Per-instance
layout(location = 4) in vec4 in_uv_bounds;   // Per-instance
layout(location = 5) in vec4 in_tint_color;   // Per-instance

out vec2 frag_uv;
out vec4 frag_tint;

uniform mat4 u_ortho_projection;

void main() {
    // 2D Rotation Matrix
    float cos_r = cos(in_rotation);
    float sin_r = sin(in_rotation);
    mat2 rot_mat = mat2(cos_r, -sin_r, sin_r, cos_r);

    vec2 local_scaled = in_quad_vertex * in_scale;
    vec2 world_pos = (rot_mat * local_scaled) + in_world_pos;

    gl_Position = u_ortho_projection * vec4(world_pos, 0.0, 1.0);


    // Map quad [0,1] to texture atlas sub-rectangle
    frag_uv = in_uv_bounds.xy + (in_quad_vertex + vec2(0.5)) * in_uv_bounds.zw;
    frag_tint = in_tint_color;
}
```

9.2 Post-Processing & Screen-Space Distortion Shaders

High-energy events (such as Bomb detonations, Hyper activation, or Boss part explosions) warp the fabric of the screen using **Screen-Space Refraction Distortion**.

CODE

SHOCKWAVE POST-PROCESSING PIPELINE



GLSL

```

// Fragment Shader: Dynamic Expanding Shockwave Ring
#version 450 core
in vec2 uv;
out vec4 final_color;

uniform sampler2D u_scene_texture;
uniform vec2 u_shockwave_center; // Normalized screen space [0, 1]
uniform float u_shockwave_radius; // Expanding ring radius
uniform float u_ring_thickness; // Width of ripple band (e.g. 0.05)
uniform float u_distortion_force; // Refraction intensity

void main() {
    vec2 dir_to_center = uv - u_shockwave_center;
    float dist = length(dir_to_center);

    vec2 distorted_uv = uv;

    // Check if current pixel lies inside the shockwave ring
    if (dist >= (u_shockwave_radius - u_ring_thickness) && dist <= (u_shockwave_radius + u_ring_thickness)) {
        float band_diff = (dist - u_shockwave_radius) / u_ring_thickness;
        // Cubic spline falloff for smooth refraction ripple
        float wave_factor = sin(band_diff * 3.14159);

        vec2 offset_dir = normalize(dir_to_center);
        distorted_uv += offset_dir * (wave_factor * u_distortion_force);
    }

    final_color = texture(u_scene_texture, distorted_uv);
}

```

9.3 Impact Physics: Hitstop, Freeze-Frames, and Trauma Decay

1. Hitstop (Impact Micro-Pauses)

When a massive laser strike, point-blank shotgun blast, or bomb detonates, the game simulation freezes completely for **2--6** frames while visual particles continue to shimmer. This provides tactile weight to impacts.



2. The Trauma-Based Screen Shake System

Naive screen shake applies random jitter ($x \in [-\text{shake}, +\text{shake}]$), which feels jittery and disconnected. A professional screen shake engine uses the **Trauma Exponent Model** (formulated by Squirrel Eiserloh).

$$\text{Trauma} \in [0.0, 1.0]$$

$$\text{Shake} = \text{Trauma}^2 \quad \text{or} \quad \text{Trauma}^3$$

$$\Delta X = \text{MaxOffset}_X \cdot \text{Shake} \cdot \text{SimplexNoise}(\text{seed}_1, t)$$


$$\Delta Y = \text{MaxOffset}_Y \cdot \text{Shake} \cdot \text{SimplexNoise}(\text{seed}_2, t)$$

$$\Delta \theta = \text{MaxAngle} \cdot \text{Shake} \cdot \text{SimplexNoise}(\text{seed}_3, t)$$

CODE

TRAUMA EXPONENT CURVE (Trauma^2):

Shake Power



RUST

```
// Trauma-Based 2D Camera Shake Model
struct CameraTrauma {
    trauma: f32,           // 0.0 to 1.0
    decay_rate: f32,       // e.g., 1.2 per second
    max_offset_x: f32,     // e.g., 32.0 pixels
    max_offset_y: f32,     // e.g., 32.0 pixels
    max_angle_rad: f32,    // e.g., 0.08 radians (~4.5 degrees)
    noise_time: f32,
}

impl CameraTrauma {
    fn add_trauma(&mut self, amount: f32) {
        self.trauma = clamp(self.trauma + amount, 0.0, 1.0);
    }

    fn update(&mut self, dt: f32) → (Vec2, f32) {
        self.trauma = max(0.0, self.trauma - self.decay_rate * dt);
        self.noise_time += dt * 30.0; // Fast noise sampling frequency

        if self.trauma ≤ 0.001 {
            return (Vec2::ZERO, 0.0);
        }


        // Non-linear power factor provides explosive peak with smooth low-end settle
        let shake = self.trauma * self.trauma;

        let offset_x = self.max_offset_x * shake * perlin_1d(self.noise_time);
        let offset_y = self.max_offset_y * shake * perlin_1d(self.noise_time + 100.0);
        let angle    = self.max_angle_rad * shake * perlin_1d(self.noise_time + 200.0);

        (Vec2::new(offset_x, offset_y), angle)
    }
}
```

9.4 Audio Voice Limiting, Coalescing, and Dynamic Ducking

In a dense wave wipe where 80 enemy drones explode in a single frame, playing 80 simultaneous explosion audio samples will distort the sound mix, exceed hardware voice limits, and blow out the player's speakers.



RUST

```

// Audio Voice Coalescing and Throttle Manager
struct AudioSystem {
    sound_cooldowns: Map<SoundEffectId, u32>,
    active_voices: usize,
    max_voices: usize, // e.g., 32 concurrent voices
}

impl AudioSystem {
    fn play_sfx_throttled(
        &mut self,
        sfx_id: SoundEffectId,
        base_volume: f32,
        cooldown_ticks: u32
    ) {
        // Prevent same SFX from firing multiple times within cooldown window
        if let Some(ticks) = self.sound_cooldowns.get(&sfx_id) {
            if *ticks > 0 {
                return; // Coalesced / Dropped to prevent blowout
            }
        }

        if self.active_voices ≥ self.max_voices {
            return; // Voice limit reached
        }

        // Apply pitch jitter to prevent sterile mechanical repetition
        let pitch_jitter = 1.0 + deterministic_random_range(-0.05, 0.05);
        play_hardware_sound(sfx_id, base_volume, pitch_jitter);

        self.sound_cooldowns.insert(sfx_id, cooldown_ticks);
    }
}

```


9.5 Chapter Takeaways & Juice Checklist

1. **Batch rendering via GPU instancing:** Stream instance buffers to render 50,000 entities in a single draw call.
2. **Use trauma-squared screen shake:** Jitter is amateur; continuous Perlin noise driven by **Trauma**² provides visceral weight.
3. **Incorporate hitstop:** Micro-pause simulation frames on critical impacts to emphasize power.
4. **Coalesce audio events:** Throttle repetitive explosion and bullet sound triggers to preserve mix clarity and dynamic range.

In [Chapter 10](file:///D:/Playing/coding-agent-experiments/antigravity-shmup-book/book/ch10_synthesis_and_implementation_exercises.md), we assemble the complete architecture into a cohesive blueprint, outline a 5-phase reader implementation roadmap, and present capstone engineering challenges.

Chapter 10: Synthesis & Implementation Exercises

You now possess the foundational mathematical models, data structures, and systems architectures required to engineer a world-class 2D shmup engine.

This concluding chapter synthesizes these independent systems into a unified architectural blueprint, outlines a 5-phase milestone roadmap for constructing your engine from scratch, and presents advanced capstone engineering challenges.

10.1 The Master Engine Blueprint

Below is the complete system topology and execution pipeline of our production-grade 2D shmup architecture:



CODE

OS / HARDWARE
Raw Joystick Poll (XInput) • V-Sync Swapchain

MASTER FIXED TIMESTEP SIMULATION LOOP (1/60s or 1/120s Deterministic Tick)

1. TIMELINE & CHOREOGRAPHY SYSTEM

- Advance Level Clock ($t_{\text{stage}} += dt$)
- Drain Priority Queue & Evaluate Barrier Gates
- Step Boss Hierarchical State Machine (HSM) & Dynamic Battle Rank

Spawns & State Updates

2. KINEMATICS & EMITTER SYSTEM (SoA Memory Layout)

- Execute Emitter Bytecode VM (Polar Trigonometry & Rhodonea Curves)
- Update Spline Paths using Arc-Length Parameterization LUTs
- Apply Reynolds Autonomous Steering Forces & Virtual Anchor Offsets
- SIMD Velocity Integration ($Pos += Vel * dt$)

Transformed Entity Positions

3. BROAD-PHASE SPATIAL PARTITIONING (Uniform Hash Grid)

- Clear Cell Head Buckets (~1 SIMD fill)
- Re-bin 30,000+ entities into flat index arrays in $O(N)$ time

Candidate Collision Pairs (~150 pairs)


4. NARROW-PHASE COLLISION & RESOLUTION

- Circle-Circle Squared Distance Tests
- Separating Axis Theorem (SAT) for Rotated Boss Hulls / OBBs
- Swept-Capsule Continuous Collision Detection (CCD) for Fast Lasers
- Multi-Hull Evaluation (Lethal Core vs Graze Aura)

Hit, Graze, Death, and Bomb Events

5. RING-BUFFERED EVENT BUS

- Publish Flat Event Structs (Zero Dynamic Allocation)



10.2 Five-Phase Incremental Milestone Roadmap

Do not attempt to build the entire engine in one pass. Follow this proven, progressive milestone roadmap:



Phase 1: Fixed-Timestep Core & 50,000 Zero-Alloc Bullet Benchmark

- **Objective:** Establish the deterministic loop and zero-allocation memory pools.
- **Deliverables:**

1. Fixed timestep loop with accumulator and spiral-of-death clamp.
2. Structure-of-Arrays (SoA) projectile pool holding **50,000** active bullets.
3. GPU instanced quad renderer rendering all **50,000** moving bullets at **60 + FPS**.

Phase 2: Spatial Partitioning, SAT Narrow-Phase & Continuous Collision

- **Objective:** Build broad-phase spatial hash culling and multi-hull collision queries.
- **Deliverables:**
 1. Flat Uniform Spatial Hash Grid (**64px** cell size) with zero runtime heap allocations.
 2. Circle-circle squared distance and OBB Separating Axis Theorem (SAT) collision solvers.
 3. Swept-circle Continuous Collision Detection (CCD) preventing bullet tunneling.
 4. Lethal core hitbox vs. graze aura dual-hull registration.

Phase 3: Arc-Length Spline Kinematics & Formation Squadrons

- **Objective:** Enable smooth, constant-speed enemy flight and formation choreography.
- **Deliverables:**
 1. Cubic Bézier and Centripetal Catmull-Rom spline evaluators.
 2. Arc-Length Look-Up Table (LUT) generator using Composite Simpson's Rule.
 3. Look-Up Table binary-search inverter for constant velocity ($s \rightarrow t$).
 4. Virtual Leader Anchor system driving 5-ship squadron formations via 2D rotation matrices.

Phase 4: Time-Indexed Level Sequencer & Multi-Phase Boss HSM

- **Objective:** Construct the level choreography engine and boss state machine.
- **Deliverables:**
 1. Multi-track level timeline driven by a priority-queue event dispatcher.
 2. Coroutine-based stage runner supporting barrier wait gates.
 3. Hierarchical State Machine (HSM) controlling a 3-phase boss encounter.
 4. Multi-part destructible boss scene graph with dynamic Battle Rank scaling.

Phase 5: In-Engine ImGui Timeline Editor, Undo/Redo & Juice

- **Objective:** Deliver professional authoring tooling and high-impact game feel.
- **Deliverables:**
 1. In-engine Dear ImGui overlay with interactive viewport Bézier tangent handles.
 2. Multi-track timeline scrubber supporting bidirectional scrubbing via keyframe snapshotting.
 3. Command Pattern transaction stack for unlimited Undo/Redo.

4. Trauma-squared camera shake, hitstop micro-pauses, shockwave distortion shaders, and audio voice coalescing.

10.3 Capstone Engineering Challenges

For the senior engineer seeking to push engine architecture to commercial perfection, implement these three capstone challenges:

Challenge A: Headless 10,000 FPS Deterministic Replay Fuzzer & State Diffing

- **The Task:** Build a standalone headless CLI test harness that executes your game simulation with no GPU or audio initialized.
- **Requirements:**
 - Run 60-minute replay logs (**216,000** ticks) in under **15 seconds**.
 - Inject fuzzy random player inputs and compute a 64-bit CRC / cryptographic hash of the entire entity pool every 60 ticks.
 - Assert that running identical inputs across different CPU architectures (x86_64 vs ARM64) produces bit-identical simulation state hashes.

Challenge B: Dynamic Laser-Whip IK Chain with Swept OBB Collisions

- **The Task:** Construct a multi-link segmented laser whip weapon (similar to the iconic Force Laser in *R-Type* or *RayForce*).
- **Requirements:**
 - Model a 32-node kinematic chain with distance constraints and angular damping.
 - Implement continuous swept-capsule collision queries along every link.
 - Dynamically generate a GPU triangle strip mesh with animated scrolling UV coords and additive glow blending.

Challenge C: Real-Time Bullet Density Heatmap & Automated Dodging Solver

- **The Task:** Develop an AI navigation diagnostic tool for your Level Editor.
- **Requirements:**
 - Subdivide the screen into a **128 × 128** threat grid.
 - Evaluate future projectile trajectories over a **30–60** frame lookahead window to compute a dynamic spatial risk cost-field.

- Use **A*** or Dynamic Dijkstra search to prove whether a designer-authored bullet pattern is mathematically survivable by a player ship.

10.4 Canonical Bibliography & Further Reading

Game Engine Architecture & Systems Programming

- **Nystrom, Robert.** *Game Programming Patterns*. Genever Benning, 2014. (Essential reading for the Command Pattern, Object Pools, and Subsystems).
- **Gregory, Jason.** *Game Engine Architecture, 3rd Edition*. CRC Press, 2018. (The definitive text on memory management, engine pipelines, and real-time game loops).
- **Acton, Mike.** *Data-Oriented Design and C++*. CppCon Keynote, 2014. (The foundational manifesto on cache locality, SoA transformations, and hardware-aware programming).
- **Fiedler, Glenn.** *Fix Your Timestep!* Gaffer on Games, 2004. (The canonical formulation of the fixed-timestep accumulator game loop).

Computational Geometry, Splines & Danmaku Mathematics

- **Salomon, David.** *Curves and Surfaces for Computer Graphics*. Springer, 2006. (Rigorous mathematical derivation of Bézier, B-Spline, and Catmull-Rom parameterizations).
- **Eberly, David H.** *3D Game Engine Design: A Practical Approach to Real-Time Computer Graphics*. Morgan Kaufmann, 2006. (Comprehensive proofs for Separating Axis Theorem (SAT) and continuous swept intersections).
- **Eiserloh, Squirrel.** *Math for Game Programmers: Juicing Your Cameras With Math*. GDC Talk, 2016. (The mathematical formulation of trauma-based screen shake and Perlin camera noise).
- **BulletML Specification & ABA Games.** *BulletML Parser Engine Architecture*. Kenta Cho, 2002. (The pioneering declarative bullet language).

Final Words

A great 2D shoot 'em up is a triumph of engineering discipline over brute force. By respecting the CPU cache, enforcing strict determinism, parameterizing splines with mathematical precision, and decoupling simulation from presentation, you build more than just a game—you build a high-performance simulation engine capable of delivering arcade perfection.

Now, take these blueprints and build your masterpiece.