合肥大學
HEFEI UNIVERSITY



Metaheuristic Optimization in Python: moptipy

Thomas Weise (汤卫思)
tweise@hfuu.edu.cn · https://thomasweise.github.io

School of Artificial Intelligence and Big Data
Hefei University
Hefei, Anhui, China

人工智能与大数据学院
合肥大学
中国安徽省合肥市

Version: 2026-10-12

Outline



1. Introduction
2. Log Files in `moptipy`
3. Repeatability and Replicability
4. Parallel and Distributed Runs
5. Summary
6. Advertisement



Introduction

Introduction to `moptipy`

- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].



Introduction to `moptipy`

- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.



Introduction to moptipy



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is https://thomasweise.github.io/moptipy.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.



Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.



Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.

Introduction to `moptipy`

- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232].

Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].

Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].
- Its companion package moptipyapps (`https://thomasweise.github.io/moptipyapps`) offers even more example application areas.

Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].
- Its companion package moptipyapps (`https://thomasweise.github.io/moptipyapps`) offers even more example application areas, including the Quadratic Assignment Problem (QAP)[40,212].

Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is `https://thomasweise.github.io/moptipy`.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].
- Its companion package moptipyapps (`https://thomasweise.github.io/moptipyapps`) offers even more example application areas, including the Quadratic Assignment Problem (QAP)[40,212], the Traveling Salesperson Problem (TSP)[140–142].

Introduction to `moptipy`

- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is https://thomasweise.github.io/moptipy.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].
- Its companion package moptipyapps (https://thomasweise.github.io/moptipyapps) offers even more example application areas, including the Quadratic Assignment Problem (QAP)[40,212], the Traveling Salesperson Problem (TSP)[140–142], the two-dimensional bin packing task[244,245].

Introduction to `moptipy`



- moptipy[231] – *Metaheuristic Optimization in Python* – as the name suggests, is a library with implementations of metaheuristic optimization methods in Python[227].
- Its core website is https://thomasweise.github.io/moptipy.
- moptipy offers different optimization algorithms, experiment execution, and result evaluation facilities.
- It allows you to execute fully replicable and self-documenting experiments in a parallel and distributed fashion.
- Moreover, it also provides the tools to statistically evaluate the experimental results and to plot various diagrams and charts.
- Additionally, it ships with two example application areas that can be used for testing algorithms, namely the Job Shop Scheduling Problem (JSSP)[225,229,232] and discrete optimization benchmarks such as those used in[232,233].
- Its companion package moptipyapps (https://thomasweise.github.io/moptipyapps) offers even more example application areas, including the Quadratic Assignment Problem (QAP)[40,212], the Traveling Salesperson Problem (TSP)[140–142], the two-dimensional bin packing task[244,245], as well as the Traveling Tournament Problem (TTP)[238].

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.

Wishlist

- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.
  3. We want experiments to run in parallel or even distribute them over several computers.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.
  3. We want experiments to run in parallel or even distribute them over several computers.
- Log files store the information collected during experiments.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.
  3. We want experiments to run in parallel or even distribute them over several computers.
- Log files store the information collected during experiments.
- Their structure lays the foundation for fulfilling the wishlist.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.
  3. We want experiments to run in parallel or even distribute them over several computers.
- Log files store the information collected during experiments.
- Their structure lays the foundation for fulfilling the wishlist: A good structure can lead to a natural propensity for parallelism, distribution, and self-documentation, a bad structure can make them impossible.

Wishlist



- When doing experiments with optimization algorithms, there are several basic features that we would like to have:
  1. We want experiments to be well-documented.
  2. We want experiments to be replicable.
  3. We want experiments to run in parallel or even distribute them over several computers.
- Log files store the information collected during experiments.
- Their structure lays the foundation for fulfilling the wishlist: A good structure can lead to a natural propensity for parallelism, distribution, and self-documentation, a bad structure can make them impossible.
- We here discuss how such features can be achieved.

Log Files in moptipy



Log Files should automatically contain...



- Log files should automatically contain the following information.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space,
  5. the total consumed FEs and runtime.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space,
  5. the total consumed FEs and runtime,
  6. the termination criteria.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space,
  5. the total consumed FEs and runtime,
  6. the termination criteria,
  7. optionally: the progress of the algorithm over time.

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space,
  5. the total consumed FEs and runtime,
  6. the termination criteria,
  7. optionally: the progress of the algorithm over time,
  8. the system configuration, including processor, memory, Operating System (OS), library versions...

Log Files should automatically contain...



- Log files should automatically contain the following information:
  1. all information about the algorithm and its configuration,
  2. all information about the problem instance,
  3. the random seed of the corresponding run,
  4. the end result: not just in terms of objective value, but the actual element of the solution space; also the point in search space if search $\neq$ solution space,
  5. the total consumed FEs and runtime,
  6. the termination criteria,
  7. optionally: the progress of the algorithm over time,
  8. the system configuration, including processor, memory, Operating System (OS), library versions..., and
  9. exceptions and the stack trace if something went wrong.

1 Log File for 1 Run



- For every single run of one algorithm on one problem instance, one log file should be generated which can describe this run completely.

1 Log File for 1 Run



- For every single run of one algorithm on one problem instance, one log file should be generated which can describe this run completely.
- Information should not be divided over multiple files (harder to understand + loss of files?).

1 Log File for 1 Run



- For every single run of one algorithm on one problem instance, one log file should be generated which can describe this run completely.
- Information should not be divided over multiple files (harder to understand + loss of files?).
- No more than one run should be stored in one file (What if experiments fails after first run? What about parallelism?)

1 Log File for 1 Run



- For every single run of one algorithm on one problem instance, one log file should be generated which can describe this run completely.
- Information should not be divided over multiple files (harder to understand + loss of files?).
- No more than one run should be stored in one file (What if experiments fails after first run? What about parallelism?)
- Information should be easy-to-read and easy-to-parse text with a clear and rigid and self-documenting structure.

1 Log File for 1 Run



- For every single run of one algorithm on one problem instance, one log file should be generated which can describe this run completely.
- Information should not be divided over multiple files (harder to understand + loss of files?).
- No more than one run should be stored in one file (What if experiments fails after first run? What about parallelism?)
- Information should be easy-to-read and easy-to-parse text with a clear and rigid and self-documenting structure.
- No complicated format like JavaScript Object Notation (JSON), YAML Ain't Markup Language™ (YAML), or Extensible Markup Language (XML)! (Makes parsing complex. Different people may use different subsets of their functionality.)

moptipy Log File Structure



```
BEGIN_PROGRESS
fes;timeMS;f
1;6;267
5;7;235
10;7;230
20;7;227
25;7;205
40;7;200
84;8;180
END_PROGRESS
```

Progress of the Algorithm over Time

fes ... consumed objective function evaluations

timeMS ... consumed runtime in milliseconds

f ... objective value of the fes-th evaluated solution

Here , only moves improving the best-so-far solution are logged.

The 10th solution that was evaluated had objective value 230. Its evaluation was completed 7ms after the begin of the run.

```
BEGIN_STATE
totalFEs: 84
totalTimeMillis: 8
bestF: 180
lastImprovementFE: 84
lastImprovementTimeMillis: 8
END_STATE
```

End State at the end of the optimization run

- totalFEs: total consumed FEs
- totalTimeMillis: total consumed runtime in milliseconds (ms)
- bestF: best objective value encountered
- lastImprovementFE: FE when the last improvement took place
- lastImprovementTimeMillis: ms when the last improvement took place

```
BEGIN_SETUP
p.name: LoggingProcessWithSearchSpace
p.class: moptipy.api._process_ss_log._ProcessSSLog
p.lowerBound: 180
p.upperBound: 482
p.maxTimeMillis: 120000
p.goalF: 180
p.randSeed: 652666920553094734 6
p.randSeed(hex): 0x5a9363100a272f12
p.randGenType: numpy.random._generator.Generator
p.randBitGenType: numpy.random._pcg64.PCG64
a.name: rls_swap2
a.class: moptipy.algorithms.so.rls.RLS
a.op0.name: shuffle
a.op0.class: moptipy.operators.permutations.
    op0_shuffle.Op0Shuffle
a.op1.name: swap2
a.op1.class: moptipy.operators.permutations.op1_swap2.Op1Swap2
y.name: gantt_demo
y.class: moptipy.examples.jssp.gantt_space.GanttSpace
y.shape: (5, 4, 3)
```

Algorithm and Problem Instance Information

- p.maxTimeMillis: maximum runtime, if specified
- p.goalF: goal objective value, if specified
- p.randSeed: random seed (decimal)
- p.randSeed(hex): random seed (hexadecimal)
- a.name: algorithm name
- a.class: algorithm class
- a.op0.name: nullary operator
- a.op1.name: unary operator
- y.name: solution space setup

```
y.dtype: h
y.inst.name: demo
y.inst.class: moptipy.examples.jssp.instance.Instance
y.inst.machines: 5
y.inst.jobs: 4
y.inst.makespanLowerBound: 180
y.inst.makespanUpperBound: 482
y.inst.dtype: b
f.name: makespan
f.class: moptipy.examples.jssp.makespan.Makespan
f.lowerBound: 180
f.upperBound: 482
x.name: perm4w5r
x.class: moptipy.spaces.permutations.Permutations
x.nvars: 20
x.dtype: b
x.min: 0
x.max: 3
x.repetitions: 5
g.name: operation_based_encoding
g.class: moptipy.examples.jssp.
    ob_encoding.OperationBasedEncoding
g.dtypeMachineIdx: b
g.dtypeJobIdx: b
g.dtypeJobTime: h
END_SETUP
```

- f.name: objective function
- f.class: moptipy.examples.jssp.makespan.Makespan
- f.lowerBound: lower and/or upper bound of
- f.upperBound: objective function, if any
- x.name: perm4w5r: search space setup
- g.name: operation_based_encoding
- g.class: moptipy.examples.jssp.ob_encoding.OperationBasedEncoding: decoder from search to solution space

```
BEGIN_SYS_INFO
session.start: 2023-06-20 04:51:52.514777+00:00
session.node: home
session.procesId: 0x3d08
session.cpuAffinity: 4;5
session.ipAddress: 192.168.1.109
version.Pillow: 9.4.0
version.contourpy: 1.0.6
version.cycler: 0.11.0
version.fonttools: 4.38.0
version.joblib: 1.2.0
version.kiwisolver: 1.4.4
version.llvmlite: 0.40.0
```

Information about the System Running the Experiment

versions of libaries used

```
version.matplotlib: 3.7.1
version.moptipy: 0.9.76
version.numba: 0.57.0
version.numpy: 1.24.3
version.packaging: 21.3
version.pdfo: 1.3.1
version.psutil: 5.9.5
version.pyparsing: 3.0.9
version.pythondateutil: 2.8.2
version.scikitlearn: 1.2.2
version.scipy: 1.10.1
version.six: 1.16.0
version.threadpoolctl: 3.1.0
hardware.machine: x86_64
hardware.nPhysicalCpus: 8
hardware.nLogicalCpus: 16
hardware.cpuMhz: (2200MHz..3700MHz)*16
hardware.byteOrder: little
hardware.cpu: AMD Ryzen 7 2700X Eight-Core Processor
hardware.memSize: 33595326464
python.version: 3.10.6 (main, May 29 2023, 11:10:38)
    [GCC 11.3.0]
python.implementation: CPython
os.name: Linux
os.release: 5.19.0-45-generic
os.version: 46~22.04.1-Ubuntu SMP PREEMPT_DYNAMIC Wed Jun 7
15:06:04 UTC 20
END_SYS_INFO
```

- hardware.machine: information about system hardware
- python.version: Python interpreter infos
- os.name: operating system information

```
BEGIN_RESULT_X
2;1;3;1;0;0;2;0;1;2;3;1;0;2;1;3;0;3;2;3
END_RESULT_X
```

Best Encoded Solution (if any)


```
BEGIN_RESULT_Y
1;20;30;0;30;40;3;145;165;2;170;180;1;0;20;0;40;60;2;60;80;3;16
5;180;2;0;30;0;60;80;1;80;130;3;130;145;1;30;60;3;60;90;0;90;13
0;2;130;170;3;0;50;2;80;92;1;130;160;0;160;170
END_RESULT_Y
```

Best Discovered Point in the Solution Space

Repeatability and Replicability



Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.
- ... but randomized algorithms are ... well ... randomized?

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.
- ... but randomized algorithms are ... well ... randomized?
- Use the same random seed $s \Longrightarrow$ algorithms become deterministic.

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.
- . . . but randomized algorithms are . . . well . . . randomized?
- Use the same random seed $s \implies$ algorithms become deterministic.
- Pass seeded random number generator to the algorithm.

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.
- . . . but randomized algorithms are . . . well . . . randomized?
- Use the same random seed $s \implies$ algorithms become deterministic.
- Pass seeded random number generator to the algorithm.
- No other source of randomness allowed.

Repeatable Runs



- 1 run = 1 optimization algorithm setup applied to 1 problem instance.
- Repeatable runs = execute one run again and the algorithm will perform exactly the same operations at exactly the same time steps.
- ... but randomized algorithms are ... well ... randomized?
- Use the same random seed $s \Longrightarrow$ algorithms become deterministic.
- Pass seeded random number generator to the algorithm.
- No other source of randomness allowed.
- The seeds s should be chosen fairly (no cherry picking possible) and in a well-defined, reproducible manner.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.
- It could be *"onemax_20"* for the 20-bit OneMax problem, or maybe *"swv15"* for an instance of the Job Shop Scheduling Problem (JSSP), for example.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.
- It could be *"onemax_20"* for the 20-bit OneMax problem, or maybe *"swv15"* for an instance of the Job Shop Scheduling Problem (JSSP), for example.
- Compute the SHA-512 digest[191] (hash) of the UTF-8 encoded[113,241] $\mathrm{name}(\mathcal{I})$ and get 64 bytes of data D.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.
- It could be *"onemax_20"* for the 20-bit OneMax problem, or maybe *"swv15"* for an instance of the Job Shop Scheduling Problem (JSSP), for example.
- Compute the SHA-512 digest[191] (hash) of the UTF-8 encoded[113,241] $\mathrm{name}(\mathcal{I})$ and get 64 bytes of data D.
- Divide the data D into two 32-byte chunks D_1 and D_2.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.
- It could be *"onemax_20"* for the 20-bit OneMax problem, or maybe *"swv15"* for an instance of the Job Shop Scheduling Problem (JSSP), for example.
- Compute the SHA-512 digest[191] (hash) of the UTF-8 encoded[113,241] $\mathrm{name}(\mathcal{I})$ and get 64 bytes of data D.
- Divide the data D into two 32-byte chunks D_1 and D_2.
- Seed two of NumPy's PCG64 pseudo random number generators[169,170], $\mathfrak{R}_1$ and $\mathfrak{R}_2$, with D_1 and D_2, respectively.

Seeds S for $nRuns$ Runs of Algorithm $\mathcal{A}$ on Instance $\mathcal{I}$



- $\mathrm{name}(\mathcal{I})$ be the user-defined name string of the problem instance $\mathcal{I}$.
- It could be *"onemax_20"* for the 20-bit OneMax problem, or maybe *"swv15"* for an instance of the Job Shop Scheduling Problem (JSSP), for example.
- Compute the SHA-512 digest[191] (hash) of the UTF-8 encoded[113,241] $\mathrm{name}(\mathcal{I})$ and get 64 bytes of data D.
- Divide the data D into two 32-byte chunks D_1 and D_2.
- Seed two of NumPy's PCG64 pseudo random number generators[169,170], $\mathfrak{R}_1$ and $\mathfrak{R}_2$, with D_1 and D_2, respectively.
- Draw unsigned 64-bit integers as seeds s alternatingly from $\mathfrak{R}_1$ and $\mathfrak{R}_2$ until $nRuns$ unique values have been collected.

Advantages of this Method

- Random seeds are generated by a deterministic and replicable procedure.

Advantages of this Method

- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.

Advantages of this Method

- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.

Advantages of this Method

- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.

Advantages of this Method

- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness.

Advantages of this Method



- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness:
  - Apply two algorithms to the same instance $\mathcal{I}$?

Advantages of this Method



- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness:
  - Apply two algorithms to the same instance $\mathcal{I}$?
  - They start with the same seeds.

Advantages of this Method



- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness:
  - Apply two algorithms to the same instance $\mathcal{I}$?
  - They start with the same seeds.
  - If they use the same operators to generate their starting points, then they start with the same initial solutions.

Advantages of this Method



- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness:
  - Apply two algorithms to the same instance $\mathcal{I}$?
  - They start with the same seeds.
  - If they use the same operators to generate their starting points, then they start with the same initial solutions.
  - Different algorithm performance will truly be due to the different decisions that the algorithms make, not a fluke due to different starting points...

Advantages of this Method



- Random seeds are generated by a deterministic and replicable procedure:
  - No cherry picking is possible.
  - If we first generate the set S_1 with $|S_1| = nRuns_1$ seeds and then generate the set S_2 with $|S_2| = nRuns_2$ seeds with $nRuns_2 > nRuns_1$ for the same problem instance $\mathcal{I}$, then $S_1 \subset S_2$, i.e., we can iteratively increase the number of runs in an experiment.
- The seeds are still pseudo-random and uniformly distributed.
- Fairness:
  - Apply two algorithms to the same instance $\mathcal{I}$?
  - They start with the same seeds.
  - If they use the same operators to generate their starting points, then they start with the same initial solutions.
  - Different algorithm performance will truly be due to the different decisions that the algorithms make, not a fluke due to different starting points...
- Different seeds for different instances avoids always using the same seeds, increases fairness.

Parallel and Distributed Runs



File and Directory Structure

- Assume that the base directory is "`results`".

File and Directory Structure



- Assume that the base directory is "`results`".
- One directory "`results/`$\mathrm{name}(\mathcal{A})$" is created for each algorithm setup $\mathcal{A}$, whereas $\mathcal{A}$ is user-defined, e.g., it could be "`rls_flip1`" for randomized local search (RLS) with a single-bit-flip operator.

File and Directory Structure



- Assume that the base directory is "`results`".
- One directory "`results/`$\mathrm{name}(\mathcal{A})$" is created for each algorithm setup $\mathcal{A}$, whereas $\mathcal{A}$ is user-defined, e.g., it could be "`rls_flip1`" for randomized local search (RLS) with a single-bit-flip operator.
- One directory "`results/`$\mathrm{name}(\mathcal{A})$`/`$\mathrm{name}(\mathcal{I})$" is created for each problem instance $\mathcal{I}$ to which algorithm setup $\mathcal{A}$ is applied.


File and Directory Structure



- Assume that the base directory is "`results`".
- One directory "`results/`$\mathrm{name}(\mathcal{A})$" is created for each algorithm setup $\mathcal{A}$, whereas $\mathcal{A}$ is user-defined, e.g., it could be "`rls_flip1`" for randomized local search (RLS) with a single-bit-flip operator.
- One directory "`results/`$\mathrm{name}(\mathcal{A})/\mathrm{name}(\mathcal{I})$" is created for each problem instance $\mathcal{I}$ to which algorithm setup $\mathcal{A}$ is applied.
- The file "`results/`$\mathrm{name}(\mathcal{A})/\mathrm{name}(\mathcal{I})/\mathrm{name}(\mathcal{A})_\mathrm{name}(\mathcal{I})_\mathrm{hex}(s)$`.tex`" is created for the run of algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ with random seed s.

File and Directory Structure

- The file "`results/`$\mathrm{name}(\mathcal{A})$`/`$\mathrm{name}(\mathcal{I})$`/`$\mathrm{name}(\mathcal{A})$`_`$\mathrm{name}(\mathcal{I})$`_`$\mathrm{hex}(s)$`.tex`" is created for the run of algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ with random seed s.



File and Directory Structure



- Assume that the base directory is "`results`".
- One directory "`results/`$\mathrm{name}(\mathcal{A})$" is created for each algorithm setup $\mathcal{A}$, whereas $\mathcal{A}$ is user-defined, e.g., it could be "`rls_flip1`" for randomized local search (RLS) with a single-bit-flip operator.
- One directory "`results/`$\mathrm{name}(\mathcal{A})$`/`$\mathrm{name}(\mathcal{I})$" is created for each problem instance $\mathcal{I}$ to which algorithm setup $\mathcal{A}$ is applied.
- The file "`results/`$\mathrm{name}(\mathcal{A})$`/`$\mathrm{name}(\mathcal{I})$`/`$\mathrm{name}(\mathcal{A})$`_`$\mathrm{name}(\mathcal{I})$`_`$\mathrm{hex}(s)$`.tex`" is created for the run of algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ with random seed s.

$\Rightarrow$ We have a clearly defined directory structure for experimental results.

File and Directory Structure



- Assume that the base directory is "`results`".
- One directory "`results/`$\mathrm{name}(\mathcal{A})$" is created for each algorithm setup $\mathcal{A}$, whereas $\mathcal{A}$ is user-defined, e.g., it could be "`rls_flip1`" for randomized local search (RLS) with a single-bit-flip operator.
- One directory "`results/`$\mathrm{name}(\mathcal{A})/\mathrm{name}(\mathcal{I})$" is created for each problem instance $\mathcal{I}$ to which algorithm setup $\mathcal{A}$ is applied.
- The file "`results/`$\mathrm{name}(\mathcal{A})/\mathrm{name}(\mathcal{I})/\mathrm{name}(\mathcal{A})_\mathrm{name}(\mathcal{I})_\mathrm{hex}(s)$`.tex`" is created for the run of algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ with random seed s.

$\Rightarrow$ We have a clearly defined directory structure for experimental results.

$\Rightarrow$ If the random seeds s are generated deterministically, then the same experiment will always yield the exactly same file names and directory structure *and* the file contents will also be the same (with the exception of stored clock time measurements, of course).

Sequential Experiment Execution

- File creation is atomic on most file systems.

Sequential Experiment Execution

- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).

Sequential Experiment Execution

- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.

Sequential Experiment Execution



- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.
- In a sequential experiment, we execute the runs (algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ using random seed s) one after the other.

Sequential Experiment Execution



- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.
- In a sequential experiment, we execute the runs (algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ using random seed s) one after the other.
- Before doing a run, we try to create the (empty) corresponding log file.

Sequential Experiment Execution



- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.
- In a sequential experiment, we execute the runs (algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ using random seed s) one after the other.
- Before doing a run, we try to create the (empty) corresponding log file.
- The name and directory location of the files are deterministic and clear (see previous slide).

Sequential Experiment Execution



- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.
- In a sequential experiment, we execute the runs (algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ using random seed s) one after the other.
- Before doing a run, we try to create the (empty) corresponding log file.
- The name and directory location of the files are deterministic and clear (see previous slide).
- If this file creation fails (because the file already exist), we skip the run.

Sequential Experiment Execution



- File creation is atomic on most file systems:
  - Creating a *new* file either succeeds or fails (e.g., if it already exits).
  - If two processes or threads try to create a new file at the same time, it will succeed for only one process and fail for the other.
- In a sequential experiment, we execute the runs (algorithm setup $\mathcal{A}$ on problem instance $\mathcal{I}$ using random seed s) one after the other.
- Before doing a run, we try to create the (empty) corresponding log file.
- The name and directory location of the files are deterministic and clear (see previous slide).
- If this file creation fails (because the file already exist), we skip the run.
- Otherwise, we perform the run, collect all information in memory, and write it to the log file after the run completes.

Experiment Crashes



- What happens if an experiment crashes / power outage?

Experiment Crashes

- What happens if an experiment crashes / power outage?
- Delete all files of zero size.

Experiment Crashes



- What happens if an experiment crashes / power outage?
- Delete all files of zero size.
- Restart the experiment.

Experiment Crashes

- What happens if an experiment crashes / power outage?
- Delete all files of zero size.
- Restart the experiment.
- Only the incomplete runs are lost.

Experiment Crashes

- What happens if an experiment crashes / power outage?
- Delete all files of zero size.
- Restart the experiment.
- Only the incomplete runs are lost.
- No need to worry which parts completed and which need to be re-done.

Experiment Crashes



- What happens if an experiment crashes / power outage?
- Delete all files of zero size.
- Restart the experiment.
- Only the incomplete runs are lost.
- No need to worry which parts completed and which need to be re-done.
- The state is always clear: If a log file has non-zero size, the corresponding run has completed. Otherwise, it crashed.

Experiment Crashes



- What happens if an experiment crashes / power outage?
- Delete all files of zero size.
- Restart the experiment.
- Only the incomplete runs are lost.
- No need to worry which parts completed and which need to be re-done.
- The state is always clear: If a log file has non-zero size, the corresponding run has completed. Otherwise, it crashed.
- Since random seeds, log files, and their locations are deterministic, starting the same experiment twice will do the same runs and produce the same log files (skipping all completed runs...).

Seeds + Directory Structure = Parallelism!



- If we start the experiment program twice in parallel with the same root directory `results`, then both processes will try to create the same log files.

Seeds + Directory Structure = Parallelism!



- If we start the experiment program twice in parallel with the same root directory `results`, then both processes will try to create the same log files.
- The one that succeeds will do the run, the one that fails will try the next run, and so on.

Seeds + Directory Structure = Parallelism!



- If we start the experiment program twice in parallel with the same root directory `results`, then both processes will try to create the same log files.
- The one that succeeds will do the run, the one that fails will try the next run, and so on.
- Parallelism for free!

Seeds + Directory Structure = Parallelism!



- If we start the experiment program twice in parallel with the same root directory `results`, then both processes will try to create the same log files.
- The one that succeeds will do the run, the one that fails will try the next run, and so on.
- Parallelism for free!
- No inter-process communication, no exchange of data, no mutexes, no job queues, no synchronization ... the file system takes care of everything for us.

Seeds + Directory Structure = Distribution!

- We can share a directory over the (local) network.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.
- We create the root experiment folder `results`.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.
- We create the root experiment folder `results`.
- We share the folder over two or more computers.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.
- We create the root experiment folder `results`.
- We share the folder over two or more computers.
- We start the sane experiment program once for each CPU core in the shared folder on each machine.

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.
- We create the root experiment folder `results`.
- We share the folder over two or more computers.
- We start the sane experiment program once for each CPU core in the shared folder on each machine.
- Distributed computing for free!

Seeds + Directory Structure = Distribution!



- We can share a directory over the (local) network.
- Almost all operating systems support this out of the box.
- If file creation is atomic for a file system, then it is also atomic if the folder is shared, because the network share "sits on top" of the basic file system.
- We create the root experiment folder `results`.
- We share the folder over two or more computers.
- We start the sane experiment program once for each CPU core in the shared folder on each machine.
- Distributed computing for free!
- No cluster frameworks, no sockets, no communication needed ... all is done for us for free.

Summary

Summary



- moptipy allows us to conduct replicable self-documenting experiments with metaheuristic optimization algorithms in Python.

Summary



- moptipy allows us to conduct replicable self-documenting experiments with metaheuristic optimization algorithms in Python.
- These experiments can be executed in parallel on several processors or distributed over a network.

Summary



- moptipy allows us to conduct replicable self-documenting experiments with metaheuristic optimization algorithms in Python.
- These experiments can be executed in parallel on several processors or distributed over a network.
- moptipy ships with a wide range of experiment execution and statistical evaluation tools, including the ability to draw various charts.

Summary



- moptipy allows us to conduct replicable self-documenting experiments with metaheuristic optimization algorithms in Python.
- These experiments can be executed in parallel on several processors or distributed over a network.
- moptipy ships with a wide range of experiment execution and statistical evaluation tools, including the ability to draw various charts.
- It also offers implementation and benchmark datasets of many the classical $\mathcal{NP}$-hard tasks from Operations Research (OR).

Summary




- moptipy allows us to conduct replicable self-documenting experiments with metaheuristic optimization algorithms in Python.
- These experiments can be executed in parallel on several processors or distributed over a network.
- moptipy ships with a wide range of experiment execution and statistical evaluation tools, including the ability to draw various charts.
- It also offers implementation and benchmark datasets of many the classical $\mathcal{NP}$-hard tasks from Operations Research (OR).
- If you are developing new algorithms, it is quite an ideal testbed to explore your methods!


Advertisement

Programming with Python

We have a freely available course book on *Programming with Python* at `https://thomasweise.github.io/programmingWithPython`, with focus on practical software development using the Python ecosystem of tools[227].




Databases

We have a freely available course book on *Databases* at `https://thomasweise.github.io/databases`, with actual practical examples using a real database management system (DBMS)[223].



Metaheuristic Optimization in Python: moptipy

We offer moptipy[231], a mature open source Python package for metaheuristic optimization, which implements several algorithms, can run self-documenting experiments in parallel and in a distributed fashion, and offers statistical evaluation tools.



谢谢您们！

Thank you!

Vielen Dank!



References I

[1] Joseph Adams, Egon Balas, and Daniel Zawack. "The Shifting Bottleneck Procedure for Job Shop Scheduling". *Management Science* 34(3):391–401, Mar. 1988. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.34.3.391 (cit. on p. 151).

[2] Miguel F. Anjos. *The QAPLIB Challenge*. Edinburgh, Scotland, UK: Miguel F. Anjos @ University of Edinburgh, Nov. 19, 2023. URL: https://www.miguelanjos.com/projects/2999 (visited on 2026-09-28). The document lists the 28 instances of QAPLIB [33,35] that had not yet been solved to optimality by the time of its writing. (Cit. on p. 155).

[3] Denis Antipov and Benjamin Doerr. "Precise Runtime Analysis for Plateaus". In: *15th International Conference on Parallel Problem Solving from Nature (PPSN XV)*. Vol. 2. Sept. 8–12, 2018, Coimbra, Portugal. Ed. by Anne Auger, Carlos M. Fonseca, Nuno Lourenço, Penousal Machado, Luís Paquete, and L. Darrell Whitley. Vol. 11102 of Lecture Notes in Computer Science (LNCS). Cham, Switzerland: Springer, 2018, pp. 117–128. ISSN: 0302-9743. ISBN: 978-3-319-99258-7. doi:10.1007/978-3-319-99259-4_10 (cit. on p. 155).

[4] David Lee Applegate, Robert E. Bixby, Vašek Chvátal, and William John Cook. *The Traveling Salesman Problem: A Computational Study*. 2nd ed. Vol. 17 of Princeton Series in Applied Mathematics. Princeton, NJ, USA: Princeton University Press, 2007. ISBN: 978-0-691-12993-8. This book also discusses the Concorde TSP solver. (Cit. on pp. 148, 158).

[5] David Lee Applegate and William John Cook. "A Computational Study of the Job-Shop Scheduling Problem". *ORSA Journal on Computing* 3(2):149–156, May 1991. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.3.2.149. The JSSP instances used were generated in Bonn in 1986. (Cit. on p. 151).

[6] Paul Gustav Heinrich Bachmann. *Die Analytische Zahlentheorie / Dargestellt von Paul Bachmann*. Vol. Zweiter Theil of Zahlentheorie: Versuch einer Gesamtdarstellung dieser Wissenschaft in ihren Haupttheilen. Leipzig, Sachsen, Germany: B. G. Teubner, 1894. ISBN: 978-1-4181-6963-3. URL: http://gallica.bnf.fr/ark:/12148/bpt6k994750 (visited on 2023-12-13) (cit. on p. 163).

[7] Thomas Bäck, David B. Fogel, and Zbigniew "Zbyszek" Michalewicz, eds. *Handbook of Evolutionary Computation*. Bristol, England, UK: IOP Publishing Ltd and Oxford, Oxfordshire, England, UK: Oxford University Press, 1997. ISBN: 978-0-7503-0392-7 (cit. on p. 149).

[8] Daniel J. Barrett. *Efficient Linux at the Command Line*. Sebastopol, CA, USA: O'Reilly Media, Inc., Feb. 2022. ISBN: 978-1-0981-1340-7 (cit. on p. 152).

References II

[9] Roberto Battiti and Giampietro Tecchiolli. "Local Search with Memory: Benchmarking RTS". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 17:67–86, June 1995. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/BF01719249 (cit. on p. 156).

[10] Roberto Battiti and Giampietro Tecchiolli. "Simulated Annealing and Tabu Search in the Long Run: A Comparison on QAP Tasks". *Computers & Mathematics with Applications* 28(6):1–8, Sept. 1994. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0898-1221. doi:10.1016/0898-1221(94)00147-2 (cit. on pp. 156, 158).

[11] Roberto Battiti and Giampietro Tecchiolli. "The Reactive Tabu Search". 6(2):126–140, May 1994. doi:10.1287/ijoc.6.2.126. Applications of Reactive Tabu Search (RTS) to the 0-1 Knapsack and QAP. (Cit. on pp. 156, 158).

[12] Roberto Battiti and Giampietro Tecchiolli. "Training Neural Nets with the Reactive Tabu Search". *IEEE Transactions on Neural Networks* 6(5):1185–1200, Sept. 1995. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1045-9227. doi:10.1109/72.410361. See also "Training Neural Nets with the Reactive Tabu Search, Technical Report UTM 421, Trento, Alto Adige/Südtirol, Italy: University of Trento, 11 1993" (cit. on p. 156).

[13] James C. Bean. "Genetic Algorithms and Random Keys for Sequencing and Optimization". *ORSA Journal on Computing* 6(2):107–220, Spr. 1994. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.6.2.154. Applies the Random Keys encoding to scheduling and the QAP. See [14]. (Cit. on pp. 113, 148, 156).

[14] James C. Bean. *Genetics and Random Keys for Sequencing and Optimization*. Tech. rep. 92-43. Ann Arbor, MI, USA: University of Michigan, Department of Industrial & Operations Engineering, June 30, 1992. URL: https://www.math.wm.edu/~rrkinc/homework/RdmKeyGA.pdf (visited on 2026-10-01). See [13]. (Cit. on pp. 113, 148, 156).

[15] John Edward Beasley. "OR-Library: Distributing Test Problems by Electronic Mail". *The Journal of the Operational Research Society (JORS)* 41:1069–1072, Nov. 1990. London, England, UK: Taylor and Francis Ltd. and London, England, UK: Springer Nature Limited. ISSN: 0160-5682. doi:10.1057/jors.1990.166. See the website [16] (cit. on pp. 113, 151, 154).

[16] John Edward Beasley. *Welcome to OR-Library*. Uxbridge, Middlesex, England, UK: Brunel University of London, June 1990–Feb. 2018. URL: https://people.brunel.ac.uk/~mastjjb/jeb/info.html (visited on 2026-09-30). See the article [15]. Contains instances of the JSSP, 1D- and 2D-Packing, Knapsack, periodic TSPs, amongst others. (Cit. on pp. 113, 151, 154).

References III

[17] Andreas Beham, Michael Affenzeller, and Erik Pitzer. "Metaheuristic Algorithms for the Quadratic Assignment Problem: Performance and Comparison". In: *Innovative Technologies in Management and Science*. Ed. by Ryszard Klempous and Jan Nikodem. Vol. 10 of Topics in Intelligent Engineering and Informatics (TIEI). Cham, Switzerland: Springer, 2015, pp. 171–190. ISSN: 2193-9411. ISBN: 978-3-319-12651-7. doi:10.1007/978-3-319-12652-4_10. Algorithms like stochastic local search (SLS)/iterated local search (ILS), Simulated Annealing (SA), Tabu Search (TS), Variable Neighborhood Search (VNS), evolutionary algorithms (EAs), Memetic Algorithms (MAs) are compared and, with the exception of SA and EA, all perform best on some instance groups of QAPLIB. (Cit. on p. 155).

[18] Bengt-Erik Bengtsson. "Packing Rectangular Pieces— A Heuristic Approach". *The Computer Journal* 25(3):353–357, Aug. 1982. Oxford, Oxfordshire, England, UK: Oxford University Press. ISSN: 0010-4620. doi:10.1093/comjnl/25.3.353 (cit. on p. 147).

[19] Tim Berners-Lee. *Re: Qualifiers on Hypertext links...* Geneva, Switzerland: World Wide Web project, European Organization for Nuclear Research (CERN) and Newsgroups: alt.hypertext, Aug. 6, 1991. URL: https://www.w3.org/People/Berners-Lee/1991/08/art-6484.txt (visited on 2025-02-05) (cit. on p. 160).

[20] Tim Berners-Lee, Larry Masinter, and Mark P. McCahill. *Uniform Resource Locators (URL)*. Request for Comments (RFC) 1738. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Dec. 1994. URL: https://www.ietf.org/rfc/rfc1738.txt (visited on 2025-02-05) (cit. on p. 160).

[21] Muhammed Beyaz, Tansel Dökeroğlu, and Ahmet Cosar. "Robust Hyper-Heuristic Algorithms for the Offline Oriented/Non-Oriented 2D Bin Packing Problems". *Applied Soft Computing (ASOC)* 36:236–245, Nov. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/j.asoc.2015.06.063 (cit. on p. 147).

[22] Christian Bierwirth. "A Generalized Permutation Approach to Job Shop Scheduling with Genetic Algorithms". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 17(2–3):87–92, June 1995. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/BF01719250. URL: https://www.researchgate.net/publication/240263036 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP, see also [23]. (Cit. on pp. 115, 125, 151, 162).

References IV

[23] Christian Bierwirth, Dirk C. Mattfeld, and Herbert Kopfer. "On Permutation Representations for Scheduling Problems". In: *4th International Conference on Parallel Problem Solving from Nature (PPSN IV)*. Sept. 22–24, 1996, Berlin, Germany. Ed. by Hans-Michael Voigt, Werner Ebeling, Ingo Rechenberg, and Hans-Paul Schwefel. Vol. 1141 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 1996, pp. 310–318. ISSN: 0302-9743. ISBN: 978-3-540-61723-5. doi:10.1007/3-540-61723-X_995. URL: https://www.researchgate.net/publication/2753293 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP, see also [22]. (Cit. on pp. 114, 125, 151, 162).

[24] Jacek Błażewicz, Wolfgang Domschke, and Erwin Pesch. "The Job Shop Scheduling Problem: Conventional and New Solution Techniques". *European Journal of Operational Research* 93(1):1–33, Aug. 1996. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(95)00362-2 (cit. on p. 151).

[25] Joshua Bloch. *Effective Java*. Reading, MA, USA: Addison-Wesley Professional, May 2008. ISBN: 978-0-321-35668-0 (cit. on p. 151).

[26] Christian Blum and Verena Schmid. "Solving the 2D Bin Packing Problem by Means of a Hybrid Evolutionary Algorithm". In: *International Conference on Computational Science (ICCS'2013)*. June 5–7, 2013, Barcelona, Spain. Ed. by Vassil Alexandrov, Michael Lees, Valeria V. Krzhizhanovskaya, Jack J. Dongarra, and Peter M. A. Sloot. Vol. 18 of Procedia Computer Science. Amsterdam, The Netherlands: Elsevier B.V., 2013, pp. 899–908. ISSN: 1877-0509. doi:10.1016/j.procs.2013.05.255. An EA for the oriented two-dimensional Bin Packing Problem with free cuts (2BP|O|F) using the heuristic by Wong and Lee [237]. (Cit. on p. 147).

[27] Borko Bošković and Janez Brest. "Computational Search of Long Skew-Symmetric Binary Sequences with High Merit Factors". *MENDEL – Soft Computing Journal* 28(2):17–24, Dec. 2022. Brno, Czech Republic: Brno University of Technology (Vysoké učení technické v Brně). ISSN: 1803-3814. doi:10.13164/mendel.2022.2.017 (cit. on p. 152).

[28] Borko Bošković, Franc Brglez, and Janez Brest. "Low-Autocorrelation Binary Sequences: On Improved Merit Factors and Runtime Predictions to Achieve Them". *Applied Soft Computing (ASOC)* 56:262–285, July 2017. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/J.ASOC.2017.02.024 (cit. on p. 152).

[29] Ed Bott. *Windows 11 Inside Out*. Hoboken, NJ, USA: Microsoft Press, Pearson Education, Inc., Feb. 2023. ISBN: 978-0-13-769132-6 (cit. on p. 153).

References V

[30] Tim Bray. *The JavaScript Object Notation (JSON) Data Interchange Format*. Request for Comments (RFC) 8259. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Dec. 2017. URL: https://www.ietf.org/rfc/rfc8259.txt (visited on 2025-02-05) (cit. on p. 151).

[31] Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, and Eve Maler, eds. *Extensible Markup Language (XML) 1.0 (Fifth Edition)*. W3C Recommendation. Wakefield, MA, USA: World Wide Web Consortium (W3C), Nov. 26, 2008–Feb. 7, 2013. URL: http://www.w3.org/TR/2008/REC-xml-20081126 (visited on 2024-12-15) (cit. on p. 161).

[32] Janez Brest and Borko Bošković. "A Heuristic Algorithm for a Low Autocorrelation Binary Sequence Problem with Odd Length and High Merit Factor". *IEEE Access* 6:4127–4134, Jan. 2018. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 2169-3536. doi:10.1109/ACCESS.2018.2789916 (cit. on p. 152).

[33] Rainer E. Burkard, Eranda Çela, Stefan E. Karisch, Franz Rendl, Miguel F. Anjos, and Peter M. Hahn. *QAPLIB – A Quadratic Assignment Problem Library – Problem Instances and Solutions*. Edinburgh, Scotland, UK: University of Edinburgh, Apr. 20, 2012–Mar. 31, 2022. doi:10.7488/ds/3428. This is the 2012 status of the QAPLIB dataset from [35] (cit. on pp. 112, 116, 155).

[34] Rainer E. Burkard, Eranda Çela, Panos Miltiades Pardalos, and Leonidas S. Pitsoulis. "The Quadratic Assignment Problem". In: *Handbook of Combinatorial Optimization*. Ed. by Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham. 1st ed. Boston, MA, USA: Springer, 1998, pp. 1713–1809. ISBN: 978-1-4613-7987-4. doi:10.1007/978-1-4613-0303-9_27 (cit. on p. 155).

[35] Rainer E. Burkard, Stefan E. Karisch, and Franz Rendl. "QAPLIB – A Quadratic Assignment Problem Library". *Journal of Global Optimization* 10(4):391–403, June 1997. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1023/A:1008293323270. This article introduces QAPLIB, a set of benchmark problems for the QAP, now hosted at [33]. (Cit. on pp. 112, 116, 155).

[36] Rainer E. Burkard and Josef Offermann. "Entwurf von Schreibmaschinentastaturen mittels quadratischer Zuordnungsprobleme". *Zeitschrift für Operations Research (ZOR). now Mathematical Methods of Operations Research (MMOR)* 21:B121–B132, Aug. 1977. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag; now London, England, UK: Springer Nature Limited. ISSN: 0340-9422. doi:10.1007/BF01918175. Keyboard layout modeled as QAPs. (Cit. on p. 155).

References VI

[37] Eduardo Carvalho Pinto and Carola Doerr. *Towards a More Practice-Aware Runtime Analysis of Evolutionary Algorithms*. arXiv.org: Computing Research Repository (CoRR) abs/1812.00493. Ithaca, NY, USA: Cornell Universiy Library, Dec. 3, 2018. doi:10.48550/arXiv.1812.00493. URL: https://arxiv.org/abs/1812.00493 (visited on 2025-08-08). arXiv:1812.00493v1 [cs.NE] 3 Dec 2018 (cit. on p. 146).

[38] Vladimír Černý. "Thermodynamical Approach to the Traveling Salesman Problem: An Efficient Simulation Algorithm". *Journal of Optimization Theory and Applications* 45(1):41–51, Jan. 1985. New York, NY, USA: Springer Science+Business Media, LLC. ISSN: 0022-3239. doi:10.1007/BF00940812 (cit. on p. 156).

[39] Bo Chen, Chris N. Potts, and Gerhard J. Woeginger. "A Review of Machine Scheduling: Complexity, Algorithms and Approximability". In: *Handbook of Combinatorial Optimization*. Ed. by Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham. 1st ed. Boston, MA, USA: Springer, 1998, pp. 1493–1641. ISBN: 978-1-4613-7987-4. doi:10.1007/978-1-4613-0303-9_25. See also pages 21–169 in volume 3/3 by Norwell, MA, USA: Kluwer Academic Publishers. Discusses, amongst others, that the JSSP is $\mathcal{NP}$-hard. (Cit. on pp. 151, 163).

[40] Jiayang Chen (陈嘉阳), Zhize Wu (吴志泽), Sarah Louise Thomson, and Thomas Weise (汤卫思). "Frequency Fitness Assignment: Optimization Without Bias for Good Solution Outperforms Randomized Local Search on the Quadratic Assignment Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 27–37. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888600003837 (cit. on pp. 4–15, 149, 153, 155).

[41] T. C. Edwin Cheng, Bo Peng, and Zhipeng Lü. "A Hybrid Evolutionary Algorithm to Solve the Job Shop Scheduling Problem". *Annals of Operations Research* 242(2):223–237, July 2016. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/s10479-013-1332-5. A MA utlizing TS (cit. on p. 153).

[42] Philippe Chrétienne, Edward G. Coffman, Jan Karel Lenstra, and Zhen Liu, eds. *Scheduling Theory and Its Applications*. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd., Sept. 1995. ISBN: 978-0-471-94059-3 (cit. on p. 151).

References VII

[43] Nestor M. Cid-Garcia and Yasmin A. Rios-Solis. "Positions and Covering: A Two-Stage Methodology to Obtain Optimal Solutions for the 2D-Bin Packing Problem". *PLoS ONE* 15(4):e0229358, Apr. 2020. San Francisco, CA, USA: Public Library of Science (PLOS). ISSN: 1932-6203. doi:10.1371/journal.pone.0229358. An exact method for the two-dimensional Bin Packing Problem with free cuts and rotation (2BP|R|F) and the 2BP|O|F. (Cit. on p. 147).

[44] David Clinton and Christopher Negus. *Ubuntu Linux Bible*. 10th ed. Bible Series. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd., Nov. 10, 2020. ISBN: 978-1-119-72233-5 (cit. on p. 159).

[45] Coding Gears and Train Your Brain. *YAML Fundamentals for DevOps, Cloud and IaC Engineers*. Birmingham, England, UK: Packt Publishing Ltd, Mar. 2022. ISBN: 978-1-80324-243-9 (cit. on p. 161).

[46] Timothy W. Cole and Myung-Ja K. Han. *XML for Catalogers and Metadata Librarians (Third Millennium Cataloging)*. 1st ed. Dublin, OH, USA: Libraries Unlimited, May 23, 2013. ISBN: 978-1-59884-519-8 (cit. on p. 161).

[47] Stephen Arthur Cook. "The Complexity of Theorem-Proving Procedures". In: *Third Annual ACM Symposium on Theory of Computing (STOC'1971)*. May 3–5, 1971, Shaker Heights, OH, USA. Ed. by Michael A. Harrison, Ranan B. Banerji, and Jeffrey D. Ullman. New York, NY, USA: Association for Computing Machinery (ACM), 1971, pp. 151–158. ISBN: 978-1-4503-7464-4. doi:10.1145/800157.805047 (cit. on pp. 153, 163).

[48] William John Cook. *Concorde TSP Solver*. Waterloo, ON, Canada: University of Waterloo, 1997. URL: https://math.uwaterloo.ca/tsp/concorde (visited on 2026-09-26) (cit. on p. 148).

[49] William John Cook. *In Pursuit of the Traveling Salesman: Mathematics at the Limits of Computation*. Princeton, NJ, USA: Princeton University Press, 2012–Nov. 9, 2014. ISBN: 978-0-691-16352-9 (cit. on pp. 148, 152).

[50] William John Cook. *World TSP*. Waterloo, ON, Canada: University of Waterloo, 2013–Oct. 25, 2025. URL: http://www.math.uwaterloo.ca/tsp/world (visited on 2026-01-03) (cit. on pp. 152, 158).

[51] "csv – CSV File Reading and Writing". In: *Python 3 Documentation*. *The Python Standard Library*. Beaverton, OR, USA: Python Software Foundation (PSF), 2001–2025. URL: https://docs.python.org/3/library/csv.html (visited on 2024-11-14) (cit. on p. 148).

References VIII

[52] Cemre Çubukçuoğlu, Pirouz Nourian, M. Fatih Tasgetiren, I. Sevil Sariyildiz, and Shervin Azadi. "Hospital Layout Design Renovation as a Quadratic Assignment Problem with Geodesic Distances". *Journal of Building Engineering* 44:102952, Dec. 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 2352-7102. doi:10.1016/j.jobe.2021.102952 (cit. on p. 155).

[53] *Definition of Operations Research*. University of Western Ontario, London, ON, Canada: International Federation of Operational Research Societies (IFORS), 2020. URL: https://www.ifors.org/what-is-or (visited on 2026-01-01) (cit. on p. 154).

[54] Paul Deitel, Harvey Deitel, and Abbey Deitel. *Internet & World Wide Web: How to Program*. 5th ed. Hoboken, NJ, USA: Pearson Education, Inc., Nov. 2011. ISBN: 978-0-13-299045-5 (cit. on p. 160).

[55] Maxence Delorme, Manuel Iori, and Silvano Martello. "Bin Packing and Cutting Stock Problems: Mathematical Models and Exact Algorithms". *European Journal of Operational Research* 255(1):1–20, Nov. 2016. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2016.04.030 (cit. on p. 148).

[56] Ebru Demirkol, Sanjay V. Mehta, and Reha Uzsoy. "Benchmarks for Shop Scheduling Problems". *European Journal of Operational Research* 109(1):137–141, Aug. 1998. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(97)00019-2 (cit. on p. 151).

[57] Justin Dennison, Cherokee Boose, and Peter van Rysdam. *Intro to NumPy*. Centennial, CO, USA: ACI Learning. Birmingham, England, UK: Packt Publishing Ltd, June 2024. ISBN: 978-1-83620-863-1 (cit. on p. 154).

[58] Miroslav Dimitrov. *New Classes of Binary Sequences with High Merit Factor*. arXiv.org: Computing Research Repository (CoRR). Ithaca, NY, USA: Cornell Universiy Library, June 24, 2022. doi:10.48550/arXiv.2206.12070. URL: https://arxiv.org/pdf/2206.12070 (visited on 2026-09-21). arXiv:2206.12070v1 [cs.IT] 24 Jun 2022 (cit. on p. 152).

[59] Miroslav Dimitrov, Tsonka Baitcheva, and Nikolay Nikolov. "Efficient Generation of Low Autocorrelation Binary Sequences". *IEEE Signal Processing Letters* 27:341–345, 2020. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1558-2361. doi:10.1109/LSP.2020.2972127 (cit. on p. 152).

[60] Slobodan Dmitrović. *Modern C for Absolute Beginners: A Friendly Introduction to the C Programming Language*. New York, NY, USA: Apress Media, LLC, Mar. 2024. ISBN: 979-8-8688-0224-9 (cit. on p. 148).

References IX

[61] Benjamin Doerr, Carola Doerr, and Franziska Ebel. "From Black-Box Complexity to Designing New Genetic Algorithms". *Theoretical Computer Science* 567:87–104, Feb. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/J.TCS.2014.11.028 (cit. on p. 154).

[62] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". In: *21st Genetic and Evolutionary Computation Conference Companion (GECCO'2019)*. July 13–17, 2019, Prague, Czech Republic. Ed. by Manuel López-Ibáñez, Anne Auger, and Thomas Stützle. New York, NY, USA: Association for Computing Machinery (ACM), 2019, pp. 1798–1806. ISBN: 978-1-4503-6748-6. doi:10.1145/3319619.3326810. See also [63,64] (cit. on p. 120).

[63] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". *Applied Soft Computing (ASOC)* 88:106027, Mar. 2020. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/j.asoc.2019.106027. See also [62,64] (cit. on pp. 120, 146, 150, 151, 154).

[64] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". (abs/1912.09237), Jan. 31, 2021. doi:10.48550/arXiv.1912.09237. URL: https://arxiv.org/abs/1912.09237 (visited on 2024-06-27). arXiv:1912.09237v2 [cs.NE] 31 Jan 2021, see also [62,63] (cit. on p. 120).

[65] Marco Dorigo, Mauro Birattari, and Thomas Stützle. "Ant Colony Optimization". *IEEE Computational Intelligence Magazine (CIM)* 1(4):28–39, Nov. 2006. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1556-603X. doi:10.1109/MCI.2006.329691. URL: https://www.researchgate.net/publication/308953674 (visited on 2025-07-25) (cit. on p. 147).

[66] Marco Dorigo, Vittorio Maniezzo, and Alberto Colorni. "Ant System: Optimization by a Colony of Cooperating Agents". *IEEE Transactions on Systems, Man, and Cybernetics – Part B: Cybernetics* 26(1):29–41, Feb. 1996. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1083-4419. doi:10.1109/3477.484436. URL: https://www.researchgate.net/publication/5589170 (visited on 2025-07-26) (cit. on p. 147).

[67] Marco Dorigo and Thomas Stützle. *Ant Colony Optimization*. Cambridge, MA, USA: MIT Press, 2004. ISBN: 978-0-262-04219-2 (cit. on p. 147).

[68] Ingy döt Net, Tina Müller, Pantelis Antoniou, Eemeli Aro, Thomas Smith, Oren Ben-Kiki, and Clark C. Evans. *YAML Ain't Markup Language (YAML™) version 1.2*. Revision 1.2.2. Seattle, WA, USA: YAML Language Development Team, Oct. 1, 2021. URL: https://yaml.org/spec/1.2.2 (visited on 2025-01-05) (cit. on p. 161).

References X

[69] Johann Dréo, Alain Pétrowski, Patrick Siarry, and Éric D. Taillard. *Metaheuristics for Hard Optimization – Methods and Case Studies*. Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2006. ISBN: 978-3-540-23022-9. doi:10.1007/3-540-30966-7. Discusses SA, TS, EAs, and Ant Colony Optimization (ACO). (Cit. on p. 155).

[70] Stefan Droste, Thomas Jansen, and Ingo Wegener. "On the Analysis of the $(1+1)$ Evolutionary Algorithm". *Theoretical Computer Science* 276(1-2):51–81, Apr. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/S0304-3975(01)00182-7 (cit. on pp. 146, 151, 152, 157).

[71] Stefan Droste, Thomas Jansen, and Ingo Wegener. "Upper and Lower Bounds for Randomized Search Heuristics in Black-Box Optimization". *Theoretical Computer Science* 39(4):525–544, July 2006. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1007/S00224-004-1177-Z (cit. on p. 154).

[72] Harald Dyckhoff and Ute Finke. *Cutting and Packing in Production and Distribution: A Typology and Bibliography*. Contributions to Management Science. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag, 1992. ISSN: 1431-1941. ISBN: 978-3-642-63487-1. doi:10.1007/978-3-642-58165-6 (cit. on p. 148).

[73] Kelly Easton, George L. Nemhauser, and Michael A. Trick. "The Traveling Tournament Problem Description and Benchmarks". In: *7th International Conference on Principles and Practice of Constraint Programming (CP'01)*. Nov. 26–Dec. 1, 2001, Paphos, Cyprus. Ed. by Toby Walsh. Vol. 2239 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2001, pp. 580–584. ISSN: 0302-9743. ISBN: 978-3-540-42863-3. doi:10.1007/3-540-45578-7_43 (cit. on p. 159).

[74] *ECMAScript Language Specification*. Standard ECMA-262, 3rd Edition. Geneva, Switzerland: Ecma International, Dec. 1999. URL: https://ecma-international.org/wp-content/uploads/ECMA-262_3rd_edition_december_1999.pdf (visited on 2024-12-15) (cit. on p. 151).

[75] Alwalid N. Elshafei. "Hospital Layout as a Quadratic Assignment Problem". *The Journal of the Operational Research Society (JORS)* 28(1):167–179, Apr. 1977. London, England, UK: Taylor and Francis Ltd. and London, England, UK: Springer Nature Limited. ISSN: 0160-5682. doi:10.1057/jors.1977.29 (cit. on p. 155).

References XI

[76] Bernhard Eschermann and Hans-Joachim Wunderlich. "Optimized Synthesis of Self-Testable Finite State Machines". In: *20th International Symposium Fault-Tolerant Computing (FTCS'1990): Digest of Papers*. June 26–28, 1990, Newcastle Upon Tyne, England, UK. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1990. ISBN: 978-0-8186-2051-5. doi:10.1109/FTCS.1990.89393 (cit. on p. 155).

[77] Thomas A. Feo and Mauricio G. C. Resende. "Greedy Randomized Adaptive Search Procedures". *Journal of Global Optimization* 6(2):109–133, Mar. 1995. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1007/BF01096763. Introduces Greedy Randomized Adaptive Search Procedures (GRASPs) and applies them to the set covering problem, among others, and lists many problem domains. (Cit. on p. 149).

[78] Luca Ferrari and Enrico Pirozzi. *Learn PostgreSQL*. 2nd ed. Birmingham, England, UK: Packt Publishing Ltd, Oct. 2023. ISBN: 978-1-83763-564-1 (cit. on p. 155).

[79] Paola Festa and Mauricio G. C. Resende. "An Annotated Bibliography of GRASP—Part I: Algorithms". *International Transactions on Operational Research (ITOR)* 16(1):1–24, Jan. 2009. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/j.1475-3995.2009.00663.x. See also [80] (cit. on pp. 122, 149).

[80] Paola Festa and Mauricio G. C. Resende. "An Annotated Bibliography of GRASP—Part II: Applications". *International Transactions on Operational Research (ITOR)* 16(2):131–172, Mar. 2009. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/j.1475-3995.2009.00664.x. See also [79] (cit. on pp. 122, 149).

[81] Simon Fischer. "A Polynomial Upper Bound for a Mutation-Based Algorithm on the Two-Dimensional Ising Model". In: *6th Genetic and Evolutionary Computation Conference (GECCO'2004), Part I*. June 26–30, 2004, Seattle, WA, USA. Ed. by Kalyanmoy Deb, Riccardo Poli, Wolfgang Banzhaf, Hans-Georg Beyer, Edmund K. Burke, Paul J. Darwen, Dipankar Dasgupta, Dario Floreano, James A. Foster, Mark Harman, Owen Holland, Pier Luca Lanzi, Lee Spector, Andrea Tettamanzi, Dirk Thierens, and Andrew M. Tyrrell. Vol. 3102 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2004, pp. 1100–1112. ISSN: 0302-9743. ISBN: 978-3-540-22344-3. doi:10.1007/978-3-540-24854-5_108 (cit. on pp. 150, 151).

References XII

[82] Simon Fischer and Ingo Wegener. "The One-Dimensional Ising Model: Mutation versus Recombination". *Theoretical Computer Science* 344(2-3):208–225, Nov. 2005. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/J.TCS.2005.04.002 (cit. on p. 150).

[83] Henry Fisher and Gerald L. Thompson. "Probabilistic Learning Combinations of Local Job-Shop Scheduling Rules". In: *Industrial Scheduling*. Ed. by John F. Muth and Gerald L. Thompson. Englewood Cliffs, NJ, USA: Prentice-Hall, 1963. Chap. 3.2, pp. 225–251 (cit. on p. 151).

[84] Charles Fleurent and Jacques A. Ferland. "Genetic Hybrids for the Quadratic Assignment Problem". In: *Quadratic Assignment and Related Problems, Proceedings of a DIMACS Workshop*. May 20–21, 1993, New Brunswick, NJ, USA: Rutgers University. Ed. by Panos Miltiades Pardalos and Henry Wolkowicz. Providence, RI, USA: American Mathematical Society (AMS), 1994, pp. 173–187. ISBN: 978-0-8218-6607-8. A MA using the TS from [206] as local search performs well. (Cit. on pp. 153, 155).

[85] Tobias Friedrich, Pietro Simone Oliveto, Dirk Sudholt, and Carsten Witt. "Analysis of Diversity-Preserving Mechanisms for Global Exploration". *Evolutionary Computation* 17(4):455–476, Win. 2009. Cambridge, MA, USA: MIT Press. ISSN: 1063-6560. doi:10.1162/evco.2009.17.4.17401 (cit. on p. 159).

[86] Tobias Friedrich, Francesco Quinzan, and Markus Wagner. "Escaping Large Deceptive Basins of Attraction with Heavy-Tailed Mutation Operators". In: *20th Genetic and Evolutionary Computation Conference (GECCO'2018)*. July 15–19, 2018, Kyōto, Kyōto-fu, Japan. Ed. by Hernán E. Aguirre and Keiki Takadama. New York, NY, USA: Association for Computing Machinery (ACM), 2018, pp. 293–300. ISBN: 978-1-4503-5618-3. doi:10.1145/3205455.3205515 (cit. on pp. 151, 159).

[87] José E. Gallardo, Carlos Cotta, and Antonio J. Fernández. "A Memetic Algorithm for the Low Autocorrelation Binary Sequence Problem". In: *9th Genetic and Evolutionary Computation Conference (GECCO'2007)*. July 7–11, 2007, London, England, UK. Ed. by Hod Lipson. New York, NY, USA: Association for Computing Machinery (ACM), 2007, pp. 1226–1233. ISBN: 978-1-59593-697-4. doi:10.1145/1276958.1277195 (cit. on p. 152).

[88] Michael R. Garey and David Stifler Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. New York, NY, USA: W. H. Freeman and Company, 1979. ISBN: 978-0-7167-1045-5 (cit. on p. 158).

References XIII

[89] Mitsuo Gen, Yasuhiro Tsujimura, and Erika Kubota. "Solving Job-Shop Scheduling Problems by Genetic Algorithm". In: *Humans, Information and Technology: Proceedings of the 1994 IEEE International Conference on Systems, Man and Cybernetics (SMC'1994)*. Vol. 2. Oct. 2–5, 1994, San Antonio, TX, USA. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1994, pp. 1577–1582. ISBN: 978-0-7803-2129-8. doi:10.1109/ICSMC.1994.400072. Proposes a permutations-with-repetitions based encoding for the JSSP. (Cit. on pp. 125, 151, 162).

[90] Fred Glover. "Tabu Search – Part I". *ORSA Journal on Computing* 1(3):190–206, Sum. 1989. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.1.3.190 (cit. on p. 158).

[91] Fred Glover. "Tabu Search – Part II". *ORSA Journal on Computing* 2(1):4–32, Win. 1990. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.2.1.4 (cit. on p. 158).

[92] Fred Glover and Gary A. Kochenberger, eds. *Handbook of Metaheuristics*. Vol. 57 of International Series in Operations Research & Management Science (ISOR). Cham, Switzerland: Springer, 2003. ISSN: 0884-8289. ISBN: 978-0-306-48056-0. doi:10.1007/b101874 (cit. on p. 153).

[93] Fred Glover, Éric D. Taillard, and Dominique de Werra. "A User's Guide to Tabu Search". *Annals of Operations Research* 41(1):3–28, Mar. 1993. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/BF02078647. Special issue on TS. (Cit. on p. 158).

[94] José Fernando Gonçalves and Mauricio G. C. Resende. "A Biased Random Key Genetic Algorithm for two-dimensional Bin Packing Problem (2BP) and 3D Bin Packing Problems". *International Journal of Production Economics (IJPE)* 145(2):500–510, Oct. 2013. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0925-5273. doi:10.1016/j.ijpe.2013.04.019. Applies the Biased Random Key Genetic Algorithm (BRKGA) to the 2BP|R|F and 2BP|O|F as well as 3D packing. Continuous vectors are translated to permutations and orientation data which is then the input of a placement heuristic. (Cit. on pp. 147, 148).

References XIV

[95] José Fernando Gonçalves and Mauricio G. C. Resende. "An Extended Akers Graphical Method with a Biased Random-Key Genetic Algorithm for Job-Shop Scheduling". *International Transactions on Operational Research (ITOR)* 21(2):215–246, Mar. 2014. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/itor.12044. URL: http://mauricio.resende.info/doc/brkga-jss2011.pdf (visited on 2026-09-30). The BRKGA basically is a MA using a continuous encoding of permutations that are decoded to schedules using the method from [22,23,89,193] and then refined via a TS. (Cit. on pp. 148, 151).

[96] José Fernando Gonçalves and Mauricio G. C. Resende. "Biased Random-Key Genetic Algorithms for Combinatorial Optimization". *Journal of Heuristics* 17:487–525, Oct. 2010. London, England, UK: Springer Nature Limited. ISSN: 1381-1231. doi:10.1007/s10732-010-9143-1 (cit. on p. 148).

[97] Michael T. Goodrich. *A Gentle Introduction to NP-Completeness*. Irvine, CA, USA: University of California, Irvine, Apr. 2022. URL: https://ics.uci.edu/~goodrich/teach/cs165/notes/NPComplete.pdf (visited on 2025-08-01) (cit. on pp. 162, 163).

[98] Ronald Lewis Graham, Eugene Leighton Lawler, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. "Optimization and Approximation in Deterministic Sequencing and Scheduling: A Survey". Annals of Discrete Mathematics (5):287–326. Ed. by Peter Ladislaw Hammer, Ellis Lane Johnson, and Bernhard H. Korte, 1979. ISSN: 0167-5060. doi:10.1016/S0167-5060(08)70356-X. An early review on JSSPs and FSSPs. (Cit. on pp. 149, 151).

[99] Martin Grötschel, Michael Jünger, and Gerhard Reinelt. "Optimal Control of Plotting and Drilling Machines: A Case Study". *Zeitschrift für Operations Research (ZOR). now Mathematical Methods of Operations Research (MMOR)* 35(1):61–84, Jan. 1991. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag; now London, England, UK: Springer Nature Limited. ISSN: 0340-9422. doi:10.1007/BF01415960. This paper tackles circuit board plotting and drilling problems by modelling (parts of) them as symmetric Traveling Salesperson Problems (STSPs). (Cit. on p. 158).

[100] Gregory Z. Gutin and Abraham P. Punnen, eds. *The Traveling Salesman Problem and its Variations*. Vol. 12 of Combinatorial Optimization (COOP). New York, NY, USA: Springer New York, May 2002. ISSN: 1388-3011. doi:10.1007/b101971 (cit. on p. 158).

[101] Pierre Hansen, Nenad Mladenović, and José Andrés Moreno Pérez. "Variable Neighbourhood Search: Methods and Applications. Invited Survey". *4OR* 6(4):319–360, Dec. 2008. ISSN: 1619-4500. doi:10.1007/s10288-008-0089-1. URL: https://www.researchgate.net/publication/225155945 (visited on 2026-10-02) (cit. on p. 160).

References XV

[102] Charles R. Harris, K. Jarrod Millman, Stéfan van der Walt, Ralf Gommers, Pauli "pv" Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith, Robert Kern, Matti Picus, Stephan Hoyer, Marten H. van Kerkwijk, Matthew Brett, Allan Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi, Christoph Gohlke, and Travis E. Oliphant. "Array programming with NumPy". *Nature* 585:357–362, 2020. London, England, UK: Springer Nature Limited. ISSN: 0028-0836. doi:10.1038/S41586-020-2649-2 (cit. on p. 154).

[103] Michael Hausenblas. *Learning Modern Linux*. Sebastopol, CA, USA: O'Reilly Media, Inc., Apr. 2022. ISBN: 978-1-0981-0894-6 (cit. on p. 152).

[104] Christian Heimes. "`defusedxml` 0.7.1: XML Bomb Protection for Python stdlib Modules". In: Mar. 8, 2021. URL: https://pypi.org/project/defusedxml (visited on 2024-12-15) (cit. on p. 161).

[105] Matthew Helmke. *Ubuntu Linux Unleashed 2021 Edition*. 14th ed. Reading, MA, USA: Addison-Wesley Professional, Aug. 2020. ISBN: 978-0-13-668539-5 (cit. on p. 159).

[106] Keld Helsgaun. "General k-opt Submoves for the Lin–Kernighan TSP Heuristic". *Mathematical Programming Computation* 1(2-3):119–163, July 2009. London, England, UK: Springer Nature Limited. ISSN: 1867-2949. doi:10.1007/s12532-009-0004-6. URL: https://www2.seas.gwu.edu/~simhaweb/champalg/tsp/papers/Helsgaun2.pdf (visited on 2026-09-26) (cit. on p. 152).

[107] Keld Helsgaun. "An Effective Implementation of the Lin-Kernighan Traveling Salesman Heuristic". 126(1):106–130, Oct. 2000. doi:10.1016/S0377-2217(99)00284-2. URL: http://akira.ruc.dk/~keld/research/LKH/LKH-2.0/DOC/LKH_REPORT.pdf (visited on 2026-09-26) (cit. on p. 152).

[108] André Henning. "Praktische Job-Shop Scheduling-Probleme". PhD thesis. Jena, Thüringen, Germany: Friedrich-Schiller-Universität Jena, Aug. 2002. URL: http://www.db-thueringen.de/servlets/DocumentServlet?id=873 (visited on 2026-09-30). Alternate url: https://nbn-resolving.org/urn:nbn:de:gbv:27-20060809-115700-4. Applies MA-like algorithms to the JSSP. (Cit. on pp. 151, 153).

[109] Holger H. Hoos and Thomas Stützle. *Stochastic Local Search: Foundations & Applications*. The Morgan Kaufmann Series in Artificial Intelligence. Amsterdam, The Netherlands: Elsevier B.V., 2005. ISBN: 978-1-55860-872-6. doi:10.1016/B978-1-55860-872-6.X5016-1 (cit. on pp. 153, 157).

References XVI

[110] Holger H. Hoos and Thomas Stützle. *SATLIB – The Satisfiability Library*. 1.4.4. Vancouver, BC, Canada: The University of British Columbia (UBC), May 11, 2001. URL: https://www.cs.ubc.ca/~hoos/SATLIB/index-ubc.html (visited on 2026-09-20). See paper [111] (cit. on pp. 127, 156).

[111] Holger H. Hoos and Thomas Stützle. "SATLIB: An Online Resource for Research on SAT". In: *SAT2000 – Highlights of Satisfiability Research in the Year 2000*. Ed. by Ian Philip Gent, Toby Walsh, and Hans van Maaren. Vol. 63 of Frontiers in Artificial Intelligence and Applications. Amsterdam, The Netherlands: IOS Press BV, Jan. 2000, pp. 283–292. ISSN: 0922-6389. ISBN: 978-1-58603-061-2. See the website [110] (cit. on pp. 127, 156).

[112] John Hunt. *A Beginners Guide to Python 3 Programming*. 2nd ed. Undergraduate Topics in Computer Science (UTICS). Cham, Switzerland: Springer, 2023. ISSN: 1863-7310. ISBN: 978-3-031-35121-1. doi:10.1007/978-3-031-35122-8 (cit. on p. 155).

[113] *Information Technology – Universal Coded Character Set (UCS)*. International Standard ISO/IEC 10646:2020. Geneva, Switzerland: International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC), Dec. 2020 (cit. on pp. 49–54, 144, 159, 160).

[114] Manuel Iori, Vinícius Loti de Lima, Silvano Martello, Flávio K. Miyazaw, and Michele Monaci. "Exact Solution Techniques for Two-Dimensional Cutting and Packing". *European Journal of Operational Research* 289(2):399–415, Mar. 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2020.06.050. See also arXiv:2004.12619v1 [math.OC] 27 Apr 2020 at doi:10.1016/j.ejor.2020.06.050. (Cit. on p. 147).

[115] Christoph Jabs, Dieter Vandesande, Jeremias Berg, Johannes Fichte, George Katsirelos, Ruben Martins, André Schidler, and Dominik Schreiber. *MaxSAT Evaluation: Complete Benchmark Collection*. 2026th ed. Geneva, Switzerland: zenodo (hosted by European Organization for Nuclear Research (CERN)), July 9, 2026. doi:10.5281/zenodo.21283148. All versions of this dataset can be reached directly via doi:10.5281/zenodo.21283147. See also https://github.com/maxsat-evaluations/data and https://maxsat-evaluations.github.io. (Cit. on p. 153).

[116] Dean Jacobs, Jan Prins, Peter Siegel, and Kenneth Wilson. "Monte Carlo Techniques in Code Optimization". In: *15th Annual Workshop on Microprogramming (MICRO 15)*. Oct. 5–7, 1982. Ed. by Joseph Allen Fisher, William J. Tracz, and Bill Hopkins. Palo Alto, CA, USA: Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE) and New York, NY, USA: Association for Computing Machinery (ACM), Oct. 1982, pp. 143–148. doi:10.5555/800036.800944. See [117] (cit. on p. 128).

References XVII

[117] Dean Jacobs, Jan Prins, Peter Siegel, and Kenneth Wilson. "Monte Carlo Techniques in Code Optimization". *ACM SIGMICRO Newsletter* 13(4):143–148, Dec. 1982. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 1050-916X. doi:10.1145/1014194.800944. See [116] (cit. on pp. 127, 156).

[118] Stefan Jakobs. "On Genetic Algorithms for the Packing of Polygons". *European Journal of Operational Research* 88(1):165–181, Jan. 1996. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(94)00166-9 (cit. on p. 150).

[119] Wassim Jaziri, ed. *Tabu Search*. London, England, UK: IntechOpen Limited, Aug. 1, 2008. ISBN: 978-3-902613-34-9. doi:10.5772/65. URL: https://www.intechopen.com/books/6114 (visited on 2026-09-30) (cit. on p. 158).

[120] Robert Johansson. *Numerical Python: Scientific Computing and Data Science Applications with NumPy, SciPy and Matplotlib*. New York, NY, USA: Apress Media, LLC, Dec. 2018. ISBN: 978-1-4842-4246-9 (cit. on p. 154).

[121] David Stifler Johnson, Gregory Z. Gutin, Lyle Andrew McGeoch, Anders Yeo, Weixiong Zhang, and Alexei Zverovitch. *Experimental Analysis of Heuristics for the ATSP*. Ed. by Gregory Z. Gutin and Abraham P. Punnen. New York, NY, USA, May 2002. doi:10.1007/0-306-48213-4_10. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP/papers/atspchap.pdf (visited on 2026-09-25) (cit. on p. 158).

[122] David Stifler Johnson and Lyle Andrew McGeoch. *Experimental Analysis of Heuristics for the STSP*. Ed. by Gregory Z. Gutin and Abraham P. Punnen. New York, NY, USA, May 2002. doi:10.1007/0-306-48213-4_9. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP/papers/stspchap.pdf (visited on 2026-09-25) (cit. on p. 158).

[123] David Stifler Johnson, Lyle Andrew McGeoch, Fred Glover, and Cesar Rego. *8th DIMACS Implementation Challenge: The Traveling Salesman Problem*. June 1, 2000–Nov. 19, 2013. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP (visited on 2026-09-25) (cit. on p. 158).

[124] Selmer Martin Johnson. "Optimal Two- and Three-Stage Production Schedules with Setup Times Included". *Naval Research Logistics Quarterly* I(1):61–68, Mar. 1954. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0894-069X. doi:10.1002/nav.3800010110. URL: https://www.rand.org/content/dam/rand/pubs/papers/2008/P402.pdf (visited on 2023-12-06) (cit. on p. 149).

References XVIII

[125] Scott Kirkpatrick, C. Daniel Gelatt, Jr., and Mario P. Vecchi. "Optimization by Simulated Annealing". *Science Magazine* 220(4598):671–680, May 13, 1983. Washington, D.C., USA: American Association for the Advancement of Science (AAAS). ISSN: 0036-8075. doi:10.1126/science.220.4598.671. URL: https://www.researchgate.net/publication/6026283 (visited on 2025-08-08) (cit. on p. 156).

[126] Robert Klein. *Scheduling of Resource-Constrained Projects*. Vol. 10 of Operations Research/Computer Science Interfaces Series (ORCS). New York, NY, USA: Springer New York, 2000. ISSN: 1387-666X. ISBN: 978-0-7923-8637-7. doi:10.1007/978-1-4615-4629-0 (cit. on p. 149).

[127] Donald Ervin Knuth. "Big Omicron and Big Omega and Big Theta". *ACM SIGACT News* 8(2):18–24, Apr.–June 1976. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 0163-5700. doi:10.1145/1008328.1008329 (cit. on p. 163).

[128] Donald Ervin Knuth. *Fundamental Algorithms*. 3rd ed. Vol. 1 of The Art of Computer Programming. Reading, MA, USA: Addison-Wesley Professional, 1997. ISBN: 978-0-201-89683-1 (cit. on pp. 157, 163).

[129] Katie Kodes. *Intro to XML, JSON, & YAML*. London, England, UK: Payhip, 2019–Sept. 4, 2020 (cit. on p. 161).

[130] Tjalling Charles Koopmans and Martin Beckmann. "Assignment Problems and the Location of Economic Activities". *Econometrica* 25(1):53–76, 1957. New Haven, CT, USA: The Econometric Society and Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0012-9682. doi:10.2307/1907742 (cit. on p. 155).

[131] Jakob Krarup and Peter Mark Pruzan. "Computer-aided Layout Design". In: *Mathematical Programming in Use*. Ed. by Michel Louis Balinski and Claude Lemaréchal. Vol. 9 of. Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 1978. Chap. 6, pp. 75–94. ISSN: 0303-3929. ISBN: 978-3-642-00796-5. doi:10.1007/BFb0120827. Uses QAPs as model for designing architectural layouts. (Cit. on p. 155).

[132] Mark W. Krentel. "The Complexity of Optimization Problems". *Journal of Computer and System Sciences* 36(3):490–509, June 1988. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0022-0000. Explores the hardness (optimization) problems such TSP, Clique, and Coloring, where computing the optimal value is $\mathcal{NP}$-complete. (Cit. on p. 158).

[133] Edmund Landau. *Handbuch der Lehre von der Verteilung der Primzahlen*. Leipzig, Sachsen, Germany: B. G. Teubner, 1909. ISBN: 978-0-8218-2650-8 (cit. on p. 163).

References XIX

[134] Eugene Leighton Lawler, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. "Recent Developments in Deterministic Sequencing and Scheduling: A Survey". In: *Deterministic and Stochastic Scheduling: Proceedings of the NATO Advanced Study and Research Institute on Theoretical Approaches to Scheduling Problems*. June 6–17, 1981, Durham, England, UK. Ed. by Michael Anthony Howe Dempster, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. Vol. 84 of Nato Science Series C: Mathematical and Physical Science (ASIC). London, England, UK: Springer Nature Limited, Apr. 1982, pp. 35–73. ISBN: 978-90-277-1397-1. doi:10.1007/978-94-009-7801-0_3. The JSSP is $\mathcal{NP}$-hard. (Cit. on p. 151).

[135] Eugene Leighton Lawler, Jan Karel Lenstra, Alexander Hendrik George Rinnooy Kan, and David B. Shmoys. "Sequencing and Scheduling: Algorithms and Complexity". In: *Production Planning and Inventory*. Ed. by Stephen C. Graves, Alexander Hendrik George Rinnooy Kan, and Paul H. Zipkin. Vol. IV of Handbooks of Operations Research and Management Science. Amsterdam, The Netherlands: Elsevier B.V., 1993. Chap. 9, pp. 445–522. ISSN: 0927-0507. ISBN: 978-0-444-87472-6. doi:10.1016/S0927-0507(05)80189-6. URL: http://alexandria.tue.nl/repository/books/339776.pdf (visited on 2023-12-06). Discusses, amongst others, that the JSSP is $\mathcal{NP}$-hard. (Cit. on pp. 151, 163).

[136] Eugene Leighton Lawler, Jan Karel Lenstra, Alexander Hendrik George Rinnooy Kan, and David B. Shmoys. *The Traveling Salesman Problem: A Guided Tour of Combinatorial Optimization*. Estimation, Simulation, and Control – Wiley-Interscience Series in Discrete Mathematics and Optimization. Chichester, West Sussex, England, UK: Wiley Interscience, Sept. 1985. ISSN: 0277-2698. ISBN: 978-0-471-90413-7 (cit. on p. 158).

[137] Stephen R. Lawrence. "Resource Constrained Project Scheduling: An Experimental Investigation of Heuristic Scheduling Techniques". PhD thesis. Pittsburgh, PA, USA: Graduate School of Industrial Administration (GSIA), Carnegie-Mellon University, 1984 (cit. on p. 151).

[138] Kent D. Lee and Steve Hubbard. *Data Structures and Algorithms with Python*. Undergraduate Topics in Computer Science (UTICS). Cham, Switzerland: Springer, 2015. ISSN: 1863-7310. ISBN: 978-3-319-13071-2. doi:10.1007/978-3-319-13072-9 (cit. on p. 155).

[139] Xueping Li and Kaike Zhang. "Single Batch Processing Machine Scheduling with Two-Dimensional Bin Packing Constraints". *International Journal of Production Economics (IJPE)* 196:113–121, Feb. 2018. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0925-5273. doi:10.1016/j.ijpe.2017.11.015. Mentions some scheduling tasks of Additive Manufacturing jobs can be viewed as instance of the 2BP|R|F. (Cit. on p. 147).

References XX

[140] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Jörg Lässig, Daan van den Berg, Sarah Louise Thomson, and Thomas Weise (汤卫思). "Addressing the Traveling Salesperson Problem with Frequency Fitness Assignment and Hybrid Algorithms". *Soft Computing* 28(17-18):9495–9508, July 2024. London, England, UK: Springer Nature Limited. ISSN: 1432-7643. doi:10.1007/S00500-024-09718-8 (cit. on pp. 4–15, 149, 153, 158).

[141] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Jörg Lässig, Daan van den Berg, and Thomas Weise (汤卫思). "Solving the Traveling Salesperson Problem using Frequency Fitness Assignment". In: *IEEE Symposium Series on Computational Intelligence (SSCI'2022)*. Dec. 4–7, 2022, Singapore. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 2022. ISBN: 978-1-6654-8769-6. doi:10.1109/SSCI51031.2022.10022296 (cit. on pp. 4–15, 149, 153).

[142] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Matthias Thürer, Markus Wagner, and Thomas Weise (汤卫思). "Generating Small Instances with Interesting Features for the Traveling Salesperson Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 173–180. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888800003837 (cit. on pp. 4–15, 153).

[143] Shen Lin and Brian W. Kernighan. "An Effective Heuristic Algorithm for the Traveling-Salesman Problem". *Operations Research* 21(2):498–516, Mar.–Apr. 1973. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0030-364X. doi:10.1287/opre.21.2.498. URL: https://www.cs.princeton.edu/~bwk/btl.mirror/tsp.pdf (visited on 2026-09-26) (cit. on p. 152).

[144] Dequan Liu (刘德全) and Hongfei Teng (滕弘飞). "An Improved BL-Algorithm for EAGenetic Algorithm of the Orthogonal Packing of Rectangles". *European Journal of Operational Research* 112(2):413–420, Jan. 1999. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(97)00437-2 (cit. on p. 150).

[145] Andrea Lodi, Silvano Martello, and Michele Monaci. "Two-Dimensional Packing Problems: A Survey". *European Journal of Operational Research* 141(2):241–252, Sept. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(02)00123-6 (cit. on pp. 147, 148).

References XXI

[146] Andrea Lodi, Silvano Martello, and Daniele Vigo. "Heuristic and Metaheuristic Approaches for a Class of Two-Dimensional Bin Packing Problems". *INFORMS Journal on Computing* 11(4):345–357, Aut. 1999. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 1091-9856. doi:10.1287/ijoc.11.4.345 (cit. on p. 147).

[147] Andrea Lodi, Silvano Martello, and Daniele Vigo. "Recent Advances on Two-Dimensional Bin Packing Problems". *Discrete Applied Mathematics* 123(1–3):379–396, Nov. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0166-218X. doi:10.1016/S0166-218X(01)00347-X (cit. on pp. 147, 148).

[148] Eliane Maria Loiola, Nair Maria Maia de Abreu, Paulo Oswaldo Boaventura-Netto, Peter M. Hahn, and Tania Querido. "A Survey for the Quadratic Assignment Problem". *European Journal of Operational Research* 176(2):657–690, 2007. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2005.09.032 (cit. on p. 155).

[149] Mariana A. Londe, Luciana S. Pessoa, Carlos E. Andrade, and Mauricio G. C. Resende. *Biased Random-Key Genetic Algorithms: A Review*. arXiv.org: Computing Research Repository (CoRR) abs/2312.00961v2. Ithaca, NY, USA: Cornell Universiy Library, Dec. 6, 2023. doi:10.48550/arXiv.2312.00961. URL: https://arxiv.org/abs/2312.00961v2 (visited on 2024-06-27). arXiv:2312.00961v2 [cs.NE] 06 Dec 2023; See [150] (cit. on p. 132).

[150] Mariana A. Londe, Luciana S. Pessoa, Carlos E. Andrade, and Mauricio G. C. Resende. "Biased Random-Key Genetic Algorithms: A Review". *European Journal of Operational Research* 321(1):1–22, Feb. 2025. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2024.03.030. See [149] (cit. on pp. 132, 148).

[151] Marc Loy, Patrick Niemeyer, and Daniel Leuck. *Learning Java*. 5th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2020. ISBN: 978-1-4920-5627-0 (cit. on p. 151).

[152] Mark Lutz. *Learning Python*. 6th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2025. ISBN: 978-1-0981-7130-8 (cit. on p. 155).

[153] Reinhard Männer and Bernard Manderick, eds. *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Amsterdam, The Netherlands: Elsevier B.V., 1992.

[154] Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe, eds. *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0000195000003837.

References XXII

[155] Silvano Martello and Daniele Vigo. "Exact Solution of the Two-Dimensional Finite Bin Packing Problem". 44(3):388–399, Mar. 1998. doi:10.1287/mnsc.44.3.388 (cit. on p. 147).

[156] Stephan Mertens. "Exhaustive Search for Low-Autocorrelation Binary Sequences". *Journal of Physics A: Mathematical and General* 29(18):L473, Sept. 1996. Bristol, England, UK: IOP Publishing Ltd. ISSN: 0305-4470. doi:10.1088/0305-4470/29/18/005 (cit. on p. 152).

[157] Peter Merz and Bernd Freisleben. "A Comparison of MAMemetic Algorithms, TSTabu Search, and ACOAnt Colonies for the QAPQuadratic Assignment Problem". In: *Congress on Evolutionary Computation (CEC'1999)*. July 6–9, 1999, Washington, D.C., USA. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1999, pp. 2063–2070. doi:10.1109/CEC.1999.785529 (cit. on p. 155).

[158] Burkhard Militzer, Michele Zamparelli, and Dieter Beule. "Evolutionary Search for Low Autocorrelated Binary Sequences". *IEEE Transactions on Evolutionary Computation* 2(1):34–39, Apr. 1998. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/4235.728212 (cit. on p. 152).

[159] Alfonsas Misevičius. "A Tabu Search Algorithm for the Quadratic Assignment Problem". *Computational Optimization and Applications* 30:95–111, Jan. 2005. London, England, UK: Springer Nature Limited. ISSN: 0926-6003. doi:10.1007/s10589-005-4562-x (cit. on p. 158).

[160] Alfonsas Misevičius. "A Modified Simulated Annealing Algorithm for the Quadratic Assignment Problem". *Informatica* 14(4):497–514, Jan. 2003. Vilnius, Lithuania: Vilnius University, Institute of Data Science and Digital Technologies (DMSTI), Lithuanian Academy of Sciences. ISSN: 0868-4952. doi:10.15388/Informatica.2003.037 (cit. on p. 156).

[161] Alfonsas Misevičius. *An Implementation of the Iterated Tabu Search Algorithm for the Quadratic Assignment Problem*. Working Paper. Kaunas, Lithuania: Kaunas University of Technology, 2008. See also [162] (cit. on p. 133).

[162] Alfonsas Misevičius. "An Implementation of the Iterated Tabu Search Algorithm for the Quadratic Assignment Problem". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 34(3):665–690, July 2012. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/s00291-011-0274-z. See also [161] (cit. on pp. 133, 155, 158).

[163] Nenad Mladenović and Pierre Hansen. "Variable Neighborhood Search". *Computers & Operations Research* 24(11):1097–1100, Nov. 1997. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/S0305-0548(97)00031-2 (cit. on p. 160).

References XXIII

[164] Wai Ho Mow, Ke-Lin Du, and Wei Hsiang Wu. "New Evolutionary Search for Long Low Autocorrelation Binary Sequences". *IEEE Transactions on Aerospace and Electronic Systems* 51(1):290–303, Jan. 2015. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 0018-9251. doi:10.1109/TAES.2014.130518 (cit. on p. 152).

[165] Heinz Mühlenbein. "How Genetic Algorithms Really Work: Mutation and Hillclimbing". In: *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Ed. by Reinhard Männer and Bernard Manderick. Amsterdam, The Netherlands: Elsevier B.V., 1992, pp. 15–26. URL: https://www.researchgate.net/publication/284805798 (visited on 2025-08-15) (cit. on p. 154).

[166] Siegfried Nijssen and Thomas Bäck. "An Analysis of the Behavior of Simplified Evolutionary Algorithms on Trap Functions". *IEEE Transactions on Evolutionary Computation* 7(1):11–22, Feb. 2003. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2002.806169 (cit. on p. 157).

[167] Eugeniusz Nowicki and Czesław Smutnicki. "A Fast Taboo Search Algorithm for the Job Shop Problem". *Management Science* 42(6):783–938, June 1996. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.42.6.797 (cit. on p. 158).

[168] NumPy Team. *NumPy*. San Francisco, CA, USA: GitHub Inc and Austin, TX, USA: NumFOCUS, Inc. URL: https://numpy.org (visited on 2025-02-02) (cit. on p. 154).

[169] NumPy Team. "Permuted Congruential Generator (64-bit, PCG64)". In: *NumPy*. San Francisco, CA, USA: GitHub Inc and Austin, TX, USA: NumFOCUS, Inc., June 2022. URL: https://numpy.org/doc/2.4/numpy-ref.pdf (visited on 2025-12-28) (cit. on pp. 49–54, 154).

[170] Melissa E. O'Neill. *PCG: A Family of Simple Fast Space-Efficient Statistically Good Algorithms for Random Number Generation*. Tech. rep. HMC-CS-2014-0905. Claremont, CA, USA: Harvey Mudd College, Computer Science Department, Sept. 5, 2014. URL: https://www.cs.hmc.edu/tr/hmc-cs-2014-0905.pdf (visited on 2023-01-21) (cit. on pp. 49–54, 154).

[171] Regina O. Obe and Leo S. Hsu. *PostgreSQL: Up and Running*. 3rd ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Oct. 2017. ISBN: 978-1-4919-6336-4 (cit. on p. 155).

[172] Tom Packebusch and Stephan Mertens. "Low Autocorrelation Binary Sequences". *Journal of Physics A: Mathematical and Theoretical* 49(16):165001, Mar. 2016. Bristol, England, UK: IOP Publishing Ltd. ISSN: 1751-8121. doi:10.1088/1751-8113/49/16/165001 (cit. on p. 152).

References XXIV

[173] Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham, eds. *Handbook of Combinatorial Optimization*. 1st ed. Boston, MA, USA: Springer, 1998. ISBN: 978-1-4613-7987-4.

[174] Panos Miltiades Pardalos, Oleg V. Shylo, and Alkis Vazacopoulos. "Solving Job Shop Scheduling Problems Utilizing the Properties of Backbone and "Big Valley"". *Computational Optimization and Applications* 47(1):61–76, Sept. 2010. London, England, UK: Springer Nature Limited. ISSN: 0926-6003. doi:10.1007/s10589-008-9206-5. An algorithm similar to SA. (Cit. on pp. 151, 156).

[175] Francisco Parreño, Ramón Alvarez-Valdés, José Fernando Oliveira, and José Manuel Tamarit. "A Hybrid GRASP/VND Algorithm for Two- and Three-Dimensional Bin Packing". *Annals of Operations Research* 179(1):203–220, Sept. 2010. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/s10479-008-0449-4 (cit. on pp. 147, 149, 160).

[176] Bo Peng, Zhipeng Lü, and T. C. Edwin Cheng. "A Tabu Search/Path Relinking Algorithm to Solve the Job Shop Scheduling Problem". *Computers & Operations Research* 53:154–164, Jan. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/j.cor.2014.08.006. URL: http://arxiv.org/abs/1402.5613 (visited on 2026-09-30) (cit. on pp. 151, 158).

[177] Ferdinando Pezzella and Emanuela Merelli. "A Tabu Search Method Guided by Shifting Bottleneck for the Job Shop Scheduling Problem". *European Journal of Operational Research* 120(2):297–310, Jan. 2000. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(99)00158-7. URL: https://www2.cs.sfu.ca/CourseCentral/827/havens/papers/topic%5C%2310(JobShop)/Tabu%5C%20With%5C%20Shifting.pdf (visited on 2026-09-30) (cit. on p. 158).

[178] Martin Pincus. "Letter to the Editor – A Monte Carlo Method for the Approximate Solution of Certain Types of Constrained Optimization Problems". *Operations Research* 18(6):1225–1228, Nov.–Dec. 1970. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0030-364X. doi:10.1287/opre.18.6.1225 (cit. on p. 156).

[179] Marcelo Pinto, Cristóvão Silva, Matthias Thürer, and Samuel Moniz. "Survey in Operations Research and Management Science. Nesting and Scheduling Optimization of Additive Manufacturing Systems: Mapping the Territory". *Computers & Operations Research* 165(106592), Feb. 2024. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/j.cor.2024.106592. Mentions some scheduling tasks of Additive Manufacturing jobs can be viewed as instance of the 2BP|R|F. (Cit. on p. 147).

[180] *PostgreSQL Essentials: Leveling Up Your Data Work*. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2024 (cit. on p. 155).

References XXV

[181] S. D. Prestwich. *Improved Branch-and-Bound for Low Autocorrelation Binary Sequences*. arXiv.org: Computing Research Repository (CoRR) abs/1305.6187. Ithaca, NY, USA: Cornell Universiy Library, Apr. 3, 2024. doi:10.48550/arXiv.1305.6187. URL: https://arxiv.org/abs/1305.6187 (visited on 2013-07-23). arXiv:1305.6187v2 [cs.AI] 23 Jul 2013 (cit. on p. 152).

[182] *Programming Languages – C, Working Document of SC22/WG14*. International Standard ISO/IEC9899:2017 C17 Ballot N2176. Geneva, Switzerland: International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC), Nov. 2017. URL: https://files.lhmouse.com/standards/ISO%20C%20N2176.pdf (visited on 2024-06-29) (cit. on p. 148).

[183] Sanatan Rai and George Vairaktarakis. "NP-Complete Problems and Proof Methodology". In: *Encyclopedia of Optimization*. Ed. by Christodoulos A. Floudas and Panos Miltiades Pardalos. 2nd ed. Boston, MA, USA: Springer, Sept. 2008, pp. 2675–2682. ISBN: 978-0-387-74758-3. doi:10.1007/978-0-387-74759-0_462 (cit. on p. 163).

[184] Soraya B. Rana and L. Darrell Whitley. "Genetic Algorithm Behavior in the MAXSAT Domain". In: *5th International Conference on Parallel Problem Solving from Nature (PPSN V)*. Sept. 27–30, 1998, Amsterdam, The Netherlands. Ed. by Ágoston Endre Eiben, Thomas Bäck, Marc Schoenauer, and Hans-Paul Schwefel. Lecture Notes in Computer Science (LNCS). 1998, pp. 785–794. ISSN: 0302-9743. ISBN: 978-3-540-65078-2. doi:10.1007/BFb0056920 (cit. on p. 153).

[185] Gerhard Reinelt. "TSPLIB – A Traveling Salesman Problem Library". *ORSA Journal on Computing* 3(4):376–384, Aut. 1991. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.3.4.376 (cit. on p. 158).

[186] Gerhard Reinelt. *TSPLIB95*. Tech. rep. Heidelberg, Baden-Württemberg, Germany: Universität Heidelberg, Institut für Angewandte Mathematik, 1995–Apr. 28, 2016. URL: https://github.com/shredderzwj/TSPLIB (visited on 2026-09-25). The original Uniform Resource Locator (URL) of the repository has become defunct in 2026. Therefore, we provide the repository listed as main URL which contains the data. Additionally, you may also check https://github.com/thomasWeise/tspSuite of our own project *TSPSuite*, which contains all the TSPLib instances as well as Java code to load them. (Cit. on p. 158).

[187] Ernest E. Rothman, Rich Rosen, and Brian Jepson. *Mac OS X for Unix Geeks*. 4th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Sept. 2008. ISBN: 978-0-596-52062-5 (cit. on p. 153).

References XXVI

[188] Günter Rudolph. *Convergence Properties of Evolutionary Algorithms*. Vol. 35 of Forschungsergebnisse zur Informatik. Hamburg, Germany: Verlag Dr. Kovač, 1997. ISSN: 1435-6260. ISBN: 978-3-86064-554-3 (cit. on p. 152).

[189] Sartaj Sahni and Teofilo Francisco Gonzalez Arce. "P-complete Approximation Problems". *Journal of the ACM (JACM)* 23(3):555–565, July 1976. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 0004-5411. doi:10.1145/321958.321975. URL: https://sites.cs.ucsb.edu/~teo/papers/JACM-PCom.pdf (visited on 2026-02-21) (cit. on p. 155).

[190] Guntram Scheithauer. *Introduction to Cutting and Packing Optimization: Problems, Modeling Approaches, Solution Methods*. Vol. 263 of International Series in Operations Research & Management Science (ISOR). Cham, Switzerland: Springer, 2018. ISSN: 0884-8289. ISBN: 978-3-319-64402-8. doi:10.1007/978-3-319-64403-5 (cit. on p. 148).

[191] *Secure Hash Standard (SHS)*. Federal Information Processing Standards Publication (FiPS PUB) 180-4. Gaithersburg, MD, USA: U.S. Department of Commerce, National Institute of Standards and Technology (NIST), Aug. 2015. doi:10.6028/NIST.FIPS.180-4. URL: https://nvlpubs.nist.gov/nistpubs/FIPS/NIST.FIPS.180-4.pdf (visited on 2025-12-28) (cit. on pp. 49–54, 157).

[192] Yakov Shafranovich. *Common Format and MIME Type for Comma-Separated Values (CSV) Files*. Request for Comments (RFC) 4180. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Oct. 2005. URL: https://www.ietf.org/rfc/rfc4180.txt (visited on 2025-02-05) (cit. on p. 148).

[193] Guoyong Shi, Hitoshi Iima, and Nobuo Sannomiya. "New Encoding Scheme for Solving Job Shop Problems by Genetic Algorithm". In: *35th IEEE Conference on Decision and Control (CDC'96)*. Vol. 4. Dec. 11–13, 1996. Kōbe, Hyōgo-ken, Japan: Institute of Electrical and Electronics Engineers (IEEE), 1997, pp. 4395–4400. ISBN: 978-0-7803-3590-5. doi:10.1109/CDC.1996.577484. URL: https://www.researchgate.net/publication/224238934 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP. (Cit. on pp. 125, 151, 162).

[194] Oleg V. Shylo. *Job Shop Scheduling (Personal Homepage)*. Knoxville, TN, USA: Oleg V. Shylo, Aug. 2019. URL: http://optimizizer.com/jobshop.php (visited on 2026-09-30). Contains many JSSP benchmark instances. (Cit. on pp. 138, 151).

References XXVII

[195] Oleg V. Shylo and Hesam Shams. *Boosting Binary Optimization via Binary Classification: A Case Study of Job Shop Scheduling*. arXiv.org: Computing Research Repository (CoRR) abs/1808.10813. Proposes a TS using regression to adapt the tabu tenures for each variable of the solution vector of a JSSP separately. Many results are available in the GitHub repository https://github.com/quasiquasar/gta-jobshop-data; other results are published Shylo's website http://optimizizer.com/jobshop.php. Ithaca, NY, USA: Cornell Universiy Library, Aug. 31, 2018. doi:10.48550/arXiv.1808.10813. URL: https://arxiv.org/abs/1808.10813 (visited on 2026-09-30) (cit. on pp. 151, 158).

[196] Ellen Siever, Stephen Figgins, Robert Love, and Arnold Robbins. *Linux in a Nutshell*. 6th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Sept. 2009. ISBN: 978-0-596-15448-6 (cit. on p. 152).

[197] Bryan Sills, Brian Gardner, Kristin Marsicano, and Chris Stewart. *Android Programming: The Big Nerd Ranch Guide*. 5th ed. Reading, MA, USA: Addison-Wesley Professional, May 2022. ISBN: 978-0-13-764579-4 (cit. on p. 147).

[198] Drew Smith. *Modern Apple Platform Administration – macOS and iOS Essentials (2025)*. Birmingham, England, UK: Packt Publishing Ltd, Feb. 2025. ISBN: 978-1-80580-309-6 (cit. on p. 153).

[199] Hossein M. Soroush. "Scheduling in Stochastic Bicriteria Single Machine Systems with Set-up Times". *International Journal of Planning and Scheduling* 1(1–2):109–145, Jan. 2011. Geneva, Switzerland: Inderscience Publishers. ISSN: 2044-494X. doi:10.1504/IJPS.2011.044605. A scheduling problem is phrased as QAP. (Cit. on p. 155).

[200] Leon Steinberg. "The Backboard Wiring Problem: A Placement Algorithm". *SIAM Review* 3(1):37–50, Jan. 1961. Philadelphia, PA, USA: Society for Industrial and Applied Mathematics Publications (SIAM). ISSN: 0036-1445. doi:10.1137/1003003. The problem is modeled as a QAP (cit. on p. 155).

[201] Robert H. Storer, S. David Wu, and Renzo Vaccari. "New Search Spaces for Sequencing Problems with Application to Job Shop Scheduling". *Management Science* 38(10):1495–1509, Oct. 1992. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.38.10.1495 (cit. on p. 151).

References XXVIII

[202] Thomas Strecker and Leonhard Hennig. "Automatic Layouting of Personalized Newspaper Pages". In: *Operations Research Proceedings 2008: Selected Papers of the Annual International Conference of the German Operations Research Society (GOR)*. Sept. 3–5, 2008, Augsburg, Bayern, Germany: University of Augsburg. Ed. by Bernhard Fleischmann, Karl-Heinz Borgwardt, Robert Klein, and Axel Tuma. Vol. 2008 of Operations Research Proceedings (ORP), Gesellschaft für Operations Research e.V., (GOR). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2009, pp. 469–474. ISSN: 0721-5924. doi:10.1007/978-3-642-00142-0_76 (cit. on p. 147).

[203] Thomas Stützle. "Iterated Local Search for the Quadratic Assignment Problem". *European Journal of Operational Research* 174(3):1519–1539, Nov. 2006. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2005.01.066 (cit. on pp. 150, 155).

[204] Éric D. Taillard. "Benchmarks for Basic Scheduling Problems". *European Journal of Operational Research* 64(2):278–285, Jan. 1993. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(93)90182-M. URL: https://arodes.hes-so.ch/record/8224/files/Preprint.pdf (visited on 2026-02-20) (cit. on p. 151).

[205] Éric D. Taillard. "Comparison of Iterative Searches for the Quadratic Assignment Problem". *Location Science. Now incorporated into Computers & Operations Research* 3(2):87–105, Aug. 1995. Amsterdam, The Netherlands: Elsevier B.V. doi:10.1016/0966-8349(95)00008-6 (cit. on p. 158).

[206] Éric D. Taillard. "Robust Taboo Search for the Quadratic Assignment Problem". *Parallel Computing* 17(4–5):443–455, July 1991. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0167-8191. doi:10.1016/S0167-8191(05)80147-4 (cit. on pp. 123, 139, 155, 158).

[207] Éric D. Taillard and Luca M. Gambardella. *Adaptive Memories for the Quadratic Assignment Problem*. Tech. rep. IDSIA-87-97. Lugano, Switzerland: Istituto Dalle Molle Di Studi Sull Intelligenza Artificiale (IDSIA), Sept. 10, 1997. URL: https://mistic.iict-heig-vd.ch/taillard/articles.dir/TaillardGambardella1997.pdf (visited on 2026-09-28). A MA using TS from [206] as well as a ACO-based approach refining its solutions with a very simple SLS are presented. (Cit. on p. 155).

[208] Alkin Tezuysal and Ibrar Ahmed. *Database Design and Modeling with PostgreSQL and MySQL*. Birmingham, England, UK: Packt Publishing Ltd, July 2024. ISBN: 978-1-80323-347-5 (cit. on p. 155).

[209] *The JSON Data Interchange Syntax*. Standard ECMA-404, 2nd Edition. Geneva, Switzerland: Ecma International, Dec. 2017. URL: https://ecma-international.org/publications-and-standards/standards/ecma-404 (visited on 2024-12-15) (cit. on p. 151).

References XXIX

[210] *The Unicode Standard, Version 15.1: Archived Code Charts*. South San Francisco, CA, USA: The Unicode Consortium, Aug. 25, 2023. URL: https://www.unicode.org/Public/15.1.0/charts/CodeCharts.pdf (visited on 2024-07-26) (cit. on p. 159).

[211] Dirk Thierens, David Edward Goldberg, and Angela Guimarães Pereira. "Domino Convergence, Drift, and the Temporal-Salience Structure of Problems". In: pp. 535–540. doi:10.1109/ICEC.1998.700085 (cit. on p. 146).

[212] Sarah Louise Thomson, Gabriela Ochoa, Daan van den Berg, Tianyu Liang (梁天宇), and Thomas Weise (汤卫思). "Entropy, Search Trajectories, and Explainability for Frequency Fitness Assignment". In: *Parallel Problem Solving from Nature (PPSN XVIII)*. Vol. 1. Sept. 14–18, 2024, Hagenberg, Mühlkreis, Austria. Ed. by Michael Affenzeller, Stephan M. Winkler, Anna V. Kononova, Heike Trautmann, Tea Tušar, Penousal Machado, and Thomas Bäck. Vol. 15148 of Lecture Notes in Computer Science (LNCS). Cham, Switzerland: Springer. ISSN: 0302-9743. ISBN: 978-3-031-70054-5. doi:10.1007/978-3-031-70055-2_23. Explores RLS, RLS with FFA (FRLS), and SA on the QAP. (Cit. on pp. 4–15, 149, 153).

[213] Ulrich Wilhelm Thonemann and Andreas Bölte. *An Improved Simulated Annealing Algorithm for the Quadratic Assignment Problem*. Working Paper. Paderborn, Nordrhein-Westfalen, Germany: School of Business, Department of Production and Operations Research, University of Paderborn, 1994 (cit. on p. 156).

[214] Marco Tomassini. "Complex Networks Analysis of the Energy Landscape of the Low Autocorrelation Binary Sequences Problem". *Physica A: Statistical Mechanics and its Applications* 577:126089, Sept. 1, 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0378-4371. doi:10.1016/j.physa.2021.126089. Lists the LABS as $\mathcal{NP}$-hard. (Cit. on p. 152).

[215] Linus Torvalds. "The Linux Edge". *Communications of the ACM (CACM)* 42(4):38–39, Apr. 1999. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 0001-0782. doi:10.1145/299157.299165 (cit. on p. 152).

[216] *Unicode® 15.1.0*. South San Francisco, CA, USA: The Unicode Consortium, Sept. 12, 2023. ISBN: 978-1-936213-33-7. URL: https://www.unicode.org/versions/Unicode15.1.0 (visited on 2024-07-26) (cit. on p. 159).

References XXX

[217] Daan van den Berg, Florian Braam, Mark Moes, Emiel Suilen, and Sandjai Bhulai. "Almost Squares in Almost Squares: Solving the Final Instance". In: *5th International Conference on Data Analytics (DATA ANALYTICS'2016)*. Oct. 9–13, 2016, Venice, Venezia, Veneto, Italy. Ed. by Sandjai Bhulai and Ivana Semanjski. Wilmington, DE, USA: International Academy, Research, and Industry Association (IARIA), 2016, pp. 69–74. ISSN: 2308-4464. ISBN: 978-1-61208-510-4. URL: https://math.vu.nl/~sbhulai/publications/data_analytics2016b.pdf (visited on 2026-10-01). This poses a very interesting 2BP|R|F problem, where "almost squars," i.e., rectangles with sizes $(i, i+1)$, must be placed in an almost square. (Cit. on pp. 147, 148).

[218] Clarissa Van Hoyweghen, David Edward Goldberg, and Bart Naudts. "From Twomax To The Ising Model: Easy And Hard Symmetrical Problems". In: *4th Genetic and Evolutionary Computation Conference (GECCO'2002)*. July 9–13, 2002, New York, NY, USA. Ed. by William B. Langdon, Erick Cantú-Paz, Keith E. Mathias, Rajkumar Roy, David Davis, Riccardo Poli, Karthik Balakrishnan, Vasant G. Honavar, Günter Rudolph, Joachim Wegener, Larry Bull, Mitchell A. Potter, Alan C. Schultz, Julian F. Miller, Edmund K. Burke, and Natasa Jonoska. Burlington, MA, USA/San Mateo, CA, USA: Morgan Kaufmann Publishers, 2002, pp. 626–633. ISBN: 978-1-55860-878-8 (cit. on p. 159).

[219] Sander van Vugt. *Linux Fundamentals*. 2nd ed. Hoboken, NJ, USA: Pearson IT Certification, June 2022. ISBN: 978-0-13-792931-3 (cit. on p. 152).

[220] Dieter Vandesande, Christoph Jabs, Jeremias Berg, Johannes Fichte, George Katsirelos, Ruben Martins, André Schidler, and Dominik Schreiber. *MaxSAT Evaluation 2026: Solvers, Benchmarks & Results*. v1. Geneva, Switzerland: zenodo (hosted by European Organization for Nuclear Research (CERN)), July 14, 2026. doi:10.5281/zenodo.21358014. See also https://maxsat-evaluations.github.io. (Cit. on p. 153).

[221] Kristian Verduin, Sarah Louise Thomson, and Daan van den Berg. "Too Constrained for Genetic Algorithms. Too Hard for Evolutionary Computing. The Traveling Tournament Problem". In: *15th International Joint Conference on Computational Intelligence (IJCCI'23)*. Nov. 13–15, 2023, Rome, Italy. Ed. by Niki van Stein, Francesco Marcelloni, H. K. Lam, Marie Cottrell, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2023, pp. 246–257. ISSN: 2184-3236. ISBN: 978-989-758-674-3. doi:10.5220/0012192100003595 (cit. on p. 159).

References XXXI

[222] Petr Vilím, Philippe Laborie, and Paul Shaw. "Failure-Directed Search for Constraint-Based Scheduling". In: *12th International Conference on the Integration of AI and OR Techniques in Constraint Programming (CPAIOR'2015)*. Ed. by Laurent Michel. Vol. 9075 of Theoretical Computer Science and General Issues (LNTCS), sub-series of Lecture Notes in Computer Science (LNCS). Barcelona, Spain: Springer, 2015, pp. 437–453. ISSN: 2512-2010. ISBN: 978-3-319-18007-6. doi:10.1007/978-3-319-18008-3_30. URL: https://www.researchgate.net/publication/280223626 (visited on 2026-09-30) (cit. on p. 151).

[223] Thomas Weise (汤卫思). *Databases*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2025. URL: https://thomasweise.github.io/databases (visited on 2025-01-05) (cit. on pp. 109, 149).

[224] Thomas Weise (汤卫思). *Global Optimization Algorithms – Theory and Application*. self-published, 2009. URL: https://www.researchgate.net/publication/200622167 (visited on 2025-07-25) (cit. on pp. 149, 153, 156).

[225] Thomas Weise (汤卫思). *jsspInstancesAndResults: Results, Data, and Instances of the Job Shop Scheduling Problem*. San Francisco, CA, USA: GitHub Inc, 2019–2020. URL: https://github.com/thomasWeise/jsspInstancesAndResults (visited on 2025-08-20) (cit. on pp. 4–15, 151).

[226] Thomas Weise (汤卫思). *Programming with C*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2026. URL: https://thomasweise.github.io/programmingWithC (visited on 2026-05-10) (cit. on p. 148).

[227] Thomas Weise (汤卫思). *Programming with Python*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2024–2026. URL: https://thomasweise.github.io/programmingWithPython (visited on 2025-01-05) (cit. on pp. 4–15, 108, 155).

[228] Thomas Weise (汤卫思), Raymond Chiong, Jörg Lässig, Ke Tang (唐珂), Shigeyoshi Tsutsui, Wenxiang Chen (陈文祥), Zbigniew "Zbyszek" Michalewicz, and Xin Yao (姚新). "Benchmarking Optimization Algorithms: An Open Source Framework for the Traveling Salesman Problem". *IEEE Computational Intelligence Magazine (CIM)* 9(3):40–52, Aug. 2014. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1556-603X. doi:10.1109/MCI.2014.2326101. Applies a multitude of algorithms including SLSes, EAs, MAs, ACO, and EDAs to the TSPLib instances. (Cit. on pp. 158, 160).

References XXXII

[229] Thomas Weise (汤卫思), Xinlu Li (李新路), Yan Chen (陈岩), and Zhize Wu (吴志泽). "Solving Job Shop Scheduling Problems without using a Bias for Good Solutions". In: *23rd Genetic and Evolutionary Computation Conference (GECCO'2021), Companion Volume*. July 10–14, 2021, Lille, France. Ed. by Krzysztof Krawiec. New York, NY, USA: Association for Computing Machinery (ACM), 2021, pp. 1459–1466. ISBN: 978-1-4503-8351-6. doi:10.1145/3449726.3463124. Applies Frequency Fitness Assignment (FFA) to the JSSP. (Cit. on pp. 4–15, 162).

[230] Thomas Weise (汤卫思), Mingxu Wan (万明绪), Pu Wang (王璞), Ke Tang (唐珂), Alexandre Devert, and Xin Yao (姚新). "Frequency Fitness Assignment". *IEEE Transactions on Evolutionary Computation* 18(2):226–243, Apr. 2014. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2013.2251885. The article introducing FFA. (Cit. on p. 149).

[231] Thomas Weise (汤卫思) and Zhize Wu (吴志泽). "Replicable Self-Documenting Experiments with Arbitrary Search Spaces and Algorithms". In: *25th Conference on Genetic and Evolutionary Computation (GECCO'2023), Companion Volume*. July 15–19, 2023, Lisbon, Portugal. Ed. by Sara Silva and Luís Paquete. New York, NY, USA: Association for Computing Machinery (ACM), 2023, pp. 1891–1899. ISBN: 979-8-4007-0120-7. doi:10.1145/3583133.3596306. Introduces the experiment execution and data collection facilities of moptipy. (Cit. on pp. 4–15, 110, 153).

[232] Thomas Weise (汤卫思), Zhize Wu (吴志泽), Xinlu Li (李新路), and Yan Chen (陈岩). "Frequency Fitness Assignment: Making Optimization Algorithms Invariant under Bijective Transformations of the Objective Function Value". *IEEE Transactions on Evolutionary Computation* 25(2):307–319, Apr. 2021. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2020.3032090 (cit. on pp. 4–15, 146, 149, 151, 152, 154, 157, 159).

[233] Thomas Weise (汤卫思), Zhize Wu (吴志泽), Xinlu Li (李新路), Yan Chen (陈岩), and Jörg Lässig. "Frequency Fitness Assignment: Optimization without Bias for Good Solutions can be Efficient". *IEEE Transactions on Evolutionary Computation* 27(4):980–992, 2023. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2022.3191698. Applies many FFA-based algorithm variants to problems such as OneMax, LeadingOnes, Linear Harmonic Function (LinHarm), TwoMax, Trap, Jump, Plateau, Ising Model, and N-Queens. (Cit. on pp. 4–15, 146, 149, 151, 157, 159).

[234] Thomas Weise (汤卫思), Yuezhong Wu (吴越钟), Raymond Chiong, Ke Tang (唐珂), and Jörg Lässig. "Global versus Local Search: The Impact of Population Sizes on Evolutionary Algorithm Performance". *Journal of Global Optimization* 66(3):511–534, Feb. 2016. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1007/s10898-016-0417-5 (cit. on p. 158).

References XXXIII

[235] L. Darrell Whitley. "The GENITOR Algorithm and Selection Pressure: Why Rank-Based Allocation of Reproductive Trials is Best". In: *3rd International Conference on Genetic Algorithms (ICGA'1989)*. June 1989, Fairfax, VA, USA: George Mason University. Ed. by J. David Schaffer. Burlington, MA, USA/San Mateo, CA, USA: Morgan Kaufmann Publishers, 1989, pp. 116–123. ISBN: 978-1-55860-066-9. URL: https://www.researchgate.net/publication/2527551 (visited on 2025-08-08) (cit. on p. 152).

[236] James M. Wilson. "Gantt Charts: A Centenary Appreciation". *European Journal of Operational Research* 149(2):430–437, Sept. 2003. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(02)00769-5 (cit. on p. 149).

[237] L. Wong and Lai-Soon Lee. "Heuristic Placement Routines for Two-Dimensional Bin Packing Problem". 5(4):334–341, Dec. 2009. doi:/10.3844/jmssp.2009.334.341. URL: https://www.thescipub.com/pdf/jmssp.2009.334.341 (visited on 2026-10-02). A heuristic for the 2BP|R|F and the 2BP|O|F (cit. on p. 115).

[238] CAO Xiang (曹翔), Zhize Wu (吴志泽), Daan van den Berg, and Thomas Weise (汤卫思). "Randomized Local Search vs. NSGA-II vs. Frequency Fitness Assignment on The Traveling Tournament Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 38–49. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012891500003837 (cit. on pp. 4–15, 153, 159, 162).

[239] Takeshi Yamada and Ryohei Nakano. "A Genetic Algorithm Applicable to Large-Scale Job-Shop Instances". In: *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Ed. by Reinhard Männer and Bernard Manderick. Amsterdam, The Netherlands: Elsevier B.V., 1992, pp. 281–290. URL: https://www.researchgate.net/publication/220701684 (visited on 2026-09-30) (cit. on p. 151).

[240] Kinza Yasar and Craig S. Mullins. *Definition: Database Management System (DBMS)*. Newton, MA, USA: TechTarget, Inc., June 2024. URL: https://www.techtarget.com/searchdatamanagement/definition/database-management-system (visited on 2025-01-11) (cit. on p. 149).

[241] François Yergeau. *UTF-8, A Transformation Format of ISO 10646*. Request for Comments (RFC) 3629. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Nov. 2003. URL: https://www.ietf.org/rfc/rfc3629.txt (visited on 2025-02-05). See Unicode and [113] (cit. on pp. 49–54, 159, 160).

References XXXIV

[242] Jiazheng Zeng (曾嘉政), Thomas Weise (汤卫思), Zhize Wu (吴志泽), and Markus Wagner. "When Frequency Fitness Assignment Fails: Trapped States in Frequency-Guided Local Search". In: *28th Genetic and Evolutionary Computation Conference (GECCO'2026)*. July 13–17, 2026, San José, Costa Rica. Ed. by Leonardo Trujillo and Ting Hu. New York, NY, USA: Association for Computing Machinery (ACM), 2026, pp. 233–242. ISBN: 979-8-4007-2487-9. doi:10.1145/3795095.3805098. Explores $(1+1)$ evolutionary algorithm ($(1+1)$ EA), $(1+1)$ EA with FFA ($(1+1)$ FEA), RLS, and FRLS as well as hybrid algorithms on a variety of discrete benchmarks such as OneMax, LeadingOnes, LinHarm, Binary Integer (BinInt), TwoMax, Trap, Jump, Plateau, Ising Model, N-Queens and also applies them to the search for Low-Autocorrelation Binary Sequences (LABS). (Cit. on pp. 146, 149–152, 154–157, 159).

[243] Chaoyong Zhang, Xinyu Shao, Yunqing Rao, and Haobo Qiu. "Some New Results on Tabu Search Algorithm Applied to the Job-Shop Scheduling Problem". In: *Tabu Search*. Ed. by Wassim Jaziri. London, England, UK: IntechOpen Limited, Aug. 1, 2008. Chap. 8. ISBN: 978-3-902613-34-9. doi:10.5772/5593. URL: https://www.intechopen.com/chapters/4596 (visited on 2026-09-30) (cit. on pp. 151, 158).

[244] Rui Zhao (赵睿), Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Daan van den Berg, Matthias Thürer, and Thomas Weise (汤卫思). "Randomized Local Search on the 2D Rectangular Bin Packing Problem with Item Rotation". In: *26th Genetic and Evolutionary Computation Conference (GECCO'2024)*. July 14–18, 2024, Melbourne, VIC, Australia. Ed. by Xiaodong Li and Julia Handl. New York, NY, USA: Association for Computing Machinery (ACM), 2024, pp. 235–238. ISBN: 979-8-4007-0494-9. doi:10.1145/3638530.3654139 (cit. on pp. 4–15, 147, 150, 153).

[245] Rui Zhao (赵睿), Zhize Wu (吴志泽), Daan van den Berg, Matthias Thürer, Tianyu Liang (梁天宇), Ming Tan (檀明), and Thomas Weise (汤卫思). "Randomized Local Search for Two-Dimensional Bin Packing and a Negative Result for Frequency Fitness Assignment". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 15–26. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888500003837 (cit. on pp. 4–15, 147, 148, 150, 153).

Glossary I

$(1+1)$ EA The $(1+1)$ EA is a local search algorithm that retains the best solution x_c discovered so far during the search [37,70]. In each step, it applies a unary search operator to this best-so-far solution x_c and derives a new solution x_n. If the new solution x_n is *better or equally good* when compared with x_c, i.e., not worse, then it replaces it, i.e., is stored as the new x_c. If the search space are bit strings of length n, then the $(1+1)$ EA uses a unary search operator that flips each bit independently with probability m/n, where usually $m = 1$. This operator is the main difference to randomized local search (RLS). The $(1+1)$ EA is a special case of the $(\mu+\lambda)$ evolutionary algorithm ($(\mu+\lambda)$ EA) where $\mu = \lambda = 1$.

$(1+1)$ FEA The $(1+1)$ EA with FFA plugged in [232,233,242]. On the discrete bit-string domains, this algorithm has a very specific structure: Its unary search operator flips each bit with probability $1/n$, where n is the dimension of the search space, distinguishing it from the unary operator in FRLS which flips exactly one bit. On other domains, such as permutations, the term is used synonymously with FRLS.

$(\mu+\lambda)$ EA The $(\mu+\lambda)$ EA is an evolutionary algorithm (EA) where, in each generation, λ offspring solutions are generated from the current population of μ parent solutions. The offspring and parent populations are merged, yielding $\mu+\lambda$ solutions, from which then the best μ solutions are ratained to form the parent population of the next generation. If the search space is the bit strings of length n, then this algorithm usually applies a mutation operator flipping each bit independently with probability $1/n$.

BinInt The *Binary Integer Problem* is a benchmark problem for bit-string based black-box search [211,242]. It is very similar to OneMax: It tries to maximize the number of 1 bits in the bit string of a chosen dimension n. Different from OneMax, where each bit has the same weight in the objective function, the bits of BinInt have a exponentially increasing weight: The bit string is treated as a binary-encoded integer whose value should be maximized. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = 2^n - 1 - \sum_{i=1}^{n} 2^{i-1} \cdot x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately.

LinHarm The Linear Harmonic Function is a benchmark problem for bit-string based black-box search [63,70,242]. It is very similar to OneMax: It tries to maximize the number of 1 bits in the bit string of a chosen dimension n. Different from OneMax, where each bit has the same weight in the objective function, the bits of LinHarm have a linear increasing weight. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = \frac{1}{2}n(n+1) - \sum_{i=1}^{n} i \cdot x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately. The $(1+1)$ EA can solve this problem with an expected runtime in $\Theta(n \ln n)$ [63,70].

Glossary II

2BP In the two-dimensional Bin Packing Problem (BP), the goal is to pack rectangles into rectangular bins without overlap and such that their edges are parallel to the edges of the bins [114,145,147]. The 2BP is strongly $\mathcal{NP}$-hard [147]. The variants of this problem include the 2BP|O|F, 2BP|R|F, 2BP|O|G, and 2BP|R|G [146,147]. Different objective function for the 2BP|O|F and 2BP|R|F are presented in [244]. 2BPs have many practical applications, including cutting (wood, glas) [147], packing (transportation, warehouse) [147], and newspaper page layout [202].

2BP|O|F In the oriented 2BP with free cuts, the rectangles to pack have fixed orientations, i.e., cannot be rotated, but can otherwise be arranged freely [146,147,155,245]. Permutation-based search spaces can be used for this problem by using the Improved Bottom Left (IBL) encoding. The state-of-the-art (SOTA) for this problem comprises [21,26,43,94,175,245].

2BP|O|G In the oriented 2BP with guillotine cuts, the rectangles to pack have fixed orientations, i.e., cannot be rotated, and must be arranged such that they can be extracted by edge-to-edge cuts [146,147].

2BP|R|F In this variant of the 2BP with free cuts, the rectangles to pack can be rotated by 90° if need be and can freely be arranged [18,146,147,244,245]. Besides packing and cutting, this problem also occurs in scheduling and build formation in additive manufacturing [139,179]. The almost-squares-in-almost-squares (Asqas) problem [217] is also a 2BP|R|F. Search spaces based on signed permutations can be used for this problem by using the IBL encoding. The SOTA for this problem comprises [21,43,94,244,245].

2BP|R|G In this variant of the 2BP with guillotine cuts, the rectangles to pack can be rotated by 90° if need be, but must be arranged such that they can be extracted by edge-to-edge cuts [146,147].

ACO *Ant Colony Optimization* is a nature-inspired optimization method for combinatorial problems where solutions are generated by "ants" that move from node to node in a graph choosing edges based on (1) the simulated pheromone on the edges and (2) a per-edge heuristic value [65–67]. If an ant produced a good solution, "pheromone" is distributed over the edges it visited, making it more likely to be re-visited by other ants.

Android is a common operating system for mobile phones [197].

Glossary III

Asqas An "almost-square" be a rectangle with size $i \times (i+1)$ with $i \in \mathbb{N}_1$. The *almost-squares-in-almost-squares* problem [217] is a special case of the 2BP|R|F. Here, almost-square rectangles of sizes 1×2, 2×3, ..., $n \times (n+1)$ must be placed into an almost-square bin without waste. This requires that there exists a natural number $p \in \mathbb{N}_1$ such that $p(p+1) = \sum_{i=1}^{n} i(i+1)$ [217]. There are exacty five Asqas instances [217], namely with bin sizes 1×2 for $n = 1$, $p = 1$, 5×4 for $n = 3$, $p = 4$, 15×16 for $n = 8$, $p = 15$, 55×56 for $n = 20$, $p = 55$, and 119×120 for $n = 34$, $p = 119$.

ATSP The general case for TSPs are *asymmetric Traveling Salesperson Problems*, where the $n \times n$ distance matrix A does not need to be symmetric. In other words, it is possible that $\exists a, b \in 1..n$ with $A[a, b] \neq A[b, a]$. Notice that while such index tuple *may* exist, this is not always or necessarily the case. In this case, one may consider the STSP as a special case of the ATSP, while ATSPs may be considered as synonymous to TSPs.

BP The *Bin Packing Problem* [72,190] is one of the classical problems from OR. The goal is to pack a set of objects into containers, using as few containers as possible. Different flavors of BPs can be distinguished, e.g., by the number of dimensions [55,145] that the objects and containers have (see, e.g., the 2BP), and/or whether the objects can be rotated [245], as well as other constraints and limitations. Both the one- and two-dimensional BP are strongly $\mathcal{NP}$-hard [147].

BRKGA The *Biased Random Key Genetic Algorithm* is a EA with a continuous search space $\mathbb{X} \subset [0, 1]^n$ and a decoding function γ translating this space to something else and biased, uniform, and elitist mating strategies [96,150].The *bias* comes from the fact that one of the parents used for the binary operation is biased to be of higher fitness than the other parent [96]. Often, γ is the Random Keys encoding [13,14] procedure translating $\mathbb{X}$ to permutations of the first n natural numbers [95]. Sometimes, it is actually a MA further refining the translation result with a local search (LS) [95]. Sometimes the permutations are then further translated to more complex data structures, such as Gantt charts for the JSSP [95], or packing plans for 2BP 3D packing [94].

C is a programming language, which is very successful in system programming situations [60,182,226].

Concorde is an exact solver for the TSP[4,48,49], which could even solve the largest instance of TSPLib (with 85 900 cities) to optimality.

CSV *Comma-Separated Values* is a very common and simple text format for exchanging tabular or matrix data [192]. Each row in the text file represents one row in the table or matrix. The elements in the row are separated by a fixed delimiter, usually a comma (","), sometimes a semicolon (";"). Python offers some out-of-the-box CSV support in the `csv` module [51].

Glossary IV

DB A *database* is an organized collection of structured information or data, typically stored electronically in a computer system. Databases are discussed in our book *Databases* [223].

DBMS A *database management system* is the software layer located between the user or application and the database (DB). The DBMS allows the user/application to create, read, write, update, delete, and otherwise manipulate the data in the DB [240].

EA An *evolutionary algorithm* is a metaheuristic optimization method that maintains a population of candidate solutions, which undergo selection (where better solutions are chosen with higher probability) and reproduction (where mutation and recombination create a new candidate solution from one or two existing ones, repectively) [7,224].

FFA *Frequency Fitness Assignment* (中文: 频率适应度分配) is a algorithm plugin for optimization methods applied to discrete or combinatorial problems with not-too-many different possible objective values [230,232,233]. It replaces the objective values in all comparisons with their absolute encounter frequency so far during the search. FFA has successfully been applied to the Maximum Satisfiability (MaxSAT) [232,233], the TSP [140,141], and the QAP [40,212], amongst others. Its properties have been intensely researched on discrete benchmark functions such as OneMax, LeadingOnes, Trap, TwoMax, Jump, and Plateau [232,233,242]. The most common realizations of FFA so far are the $(1+1)$ FEA and FRLS.

FSSP The *Flow Shop Scheduling Problem* is a variant of a JSSP where all products go through the same sequence of machines [98,124].

Gantt chart Gantt charts are two-dimensional diagrams illustrating the steps of a process [126,236]. Their horizontal axis represents the time, the vertical axis represents work packages, machines, or workers. In the diagram area, bars located at certain vertical locations indicate that the work package, machine, or worker is processed or works at the time range covered by the bar as projected to the horizontal axis.

GRASP A *Greedy Randomized Adaptive Search Procedure* is a metaheuristic where each cycle consists of two main components [77,79,80]: First, a starting point is generated using a heuristic method (as opposed to being randomly sampled). Then, a LS is applied to refine the solution. Then, another cycle starts and proceeds in the same way. The overall best solution is retained as result. Many examples of applications of GRASPs are listed in [80]. GRASP in combination with VND has been applied to the 2BP|O|F in [175].

Glossary V

IBL
: The *improved bottom left* heuristic is a one-shot algorithm constructing a solution for 2BP [144]. For the 2BP|O|F problem variant, the input of the IBL algorithm is a permutation of the first n natural numbers, each number identifying one rectangle to be packed. For the 2BP|R|F problem flavor, the permutation elements are signed, where a negative sign indicates a rotation by 90° [144]. In [244,245] it is adapted to a multi-bin situation as follows: The algorithm iterates over the (potentially signed) permutation x and places the rectangles into the packing plan in the prescribed order. It first places the rectangle outside on top of the current bin b, with its bottom-right corner onto the top-right corner of the current bin b. It then moves the rectangle downwards and leftwards as far as possible, prioritizing the downward movement whenever possible. If the rectangle cannot be moved any further, it checks if it is completely contained in the bin b. If yes, it can remain there. Otherwise, a new bin is opened ($b \leftarrow b + 1$) and the rectangle is placed at its bottom-left corner. Once a new bin is opened, this bin is used for all further insertions. IBL is suitable as a decoding function γ inside an EA [144]. Historically, it improves upon the BL algorithm [118]: That algorithm cannot represent all possible optimal packings using a permutation, but the IBL can [144].

ILS
: An *iterated local search* is a variant of the LS which applies cycles of local search and perturbation [203]. First, an initial solution is generated and refined by the local search. Then the cycle begins: A perturbation, i.e., a large search move that likely destroys a good part of the solution, is applied. The resulting new solution is refined by local search. Then, an acceptance criterion decides whether we should use this or the previous solution to continue in the next cycle. ILS has successfully been applied to the QAP.

Ising Model
: The Ising models are benchmark problems for bit-string based black-box search [63,81,82,242]. Here, a neighborhood is defined around each bit. The bit needs to have the same value as all bits in the neighborhood structure T. Thus, we try to achieve that all bits have the same value. The objective function $f(x)$ of the minimization variant of this problem family can be defined as $f(x, T) = \sum_{(i,j)\in T} |x_i - x_j|$, where T contains the index pairs of neighboring bits and is defined differently for the Ising model instances Ising 1D and Ising 2D. The problems are highly epistatic, as all variables interact with some other variables.

Ising 1D
: The 1D is a benchmark problem for bit-string based black-box search [63,82,242]. The bits are arranged in a one-dimensional ring and we try to minimize the number of bits that have different values than their neighbors. Hence, the neighborhood structure T is defined as $T_{\mathbf{1D}} = \{(i + 1, (i + 1 \bmod n) + 1) \mid i \in [0..n - 1]\}$. The problems are highly epistatic, as all variables interact with some other variables. The $(1 + 1)$ EA has an expected runtime in $\mathcal{O}(n^3)$ on 1-Dimensional Ising Model (Ising 1D) [82].

Glossary VI

Ising 2D The 2D is a benchmark problem for bit-string based black-box search [63,81,242]. The bits are arranged in a two-dimensional torus and we try to minimize the number of bits that have different values than their neighbors. Hence, the neighborhood structure $T = T_{2D}$ is defined as the set of all $\{(\alpha + \beta N, \gamma + \delta N)\}$ pairs with $\alpha, \beta, \gamma, \delta \in 0..N-1$ and either $()\gamma = (\alpha + 1) \bmod N$ and $\delta = \beta$) or ($\gamma = \alpha$ and $\delta = (\beta + 1) \bmod N$) with $n = N^2$. The problems are highly epistatic, as all variables interact with some other variables. On a similar class of problems, the $(1+1)$ EA has an exponential expected runtime [81].

Java is another very successful programming language, with roots in the C family of languages [25,151].

JavaScript JavaScript is the predominant programming language used in websites to develop interactive contents for display in browsers [74].

JSON *JavaScript Object Notation* is a data interchange format [30,209] based on JavaScript [74] syntax.

JSSP The *Job Shop Scheduling Problem* [24,42,98,135] is one of the most prominent and well-studied scheduling tasks. In a JSSP instance, there are m machines and k jobs [204]. Each job must be processed once by each machine in a job-specific sequence and has a job-specific processing time on each machine. The goal is to find an assignment of jobs to machines that results in an overall shortest makespan, i.e., the schedule (Gantt chart) which can complete all the jobs in the shortest time. The JSSP is $\mathcal{NP}$-complete [39,134,135]. The 8 most common sets of JSSP benchmark instances are *abz* [1], *dmu* [56], *ft* [83], *la* [137], *orb* [5], *swv* [201], *ta* [204], and *yn* [239].Their data can be found (sometimes partially) in several repositories, such as the OR-Library [15,16], [194], and [225], the latter of which also contains many results from existing works. Encodings based on permutations with repetition are proposed in [22,23,89,193] and used in [232]. The SOTA of the JSSP includes [95,108,174,176,195,222,243].

Jump The Jump problem is a benchmark problem for bit-string based black-box search [70,86,242]. Like the OneMax, it tries to maximize the number of 1 bits in a bit string of chosen length n. However, the solutions representing the last ω bits around the optimum to flip are deceptive, meaning that they are actually worse and getting worse than surrounding solutions. The objective function $f(x)$ of the minimization variant is $n - \|x\|_1$ if $\|x\|_1 = n$ or $\|x\|_1 \leq n - \omega$ hold, and $\omega + \|x\|_1$ otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. This means that, the larger ω, the larger the deceptive basin around the optimum that an algorithm needs to cross. An $(1+1)$ EA will converge to the resulting local optimum and thus have an expected runtime of $\Theta(n^\omega + n \ln n)$ [70].In experiments, the $(1+1)$ FEA achieves polynomial runtime on Jump, seemingly in $\mathcal{O}(n^2 \ln n)$ [232,233,242].

Glossary VII

LABS *Low-Autocorrelation Binary Sequences* are bit strings of length n whose autocorrelation is as low as possible [27,28,32,58,59,87,156,158,164,172,181]. This means that sub-sequences of any length $1 \leq k < n$ should ideally never repeat. The objective function $f : \{0,1\}^n \mapsto \mathbb{N}_0$ represents the energy of a bit string x and is subject to minimization. We can define it as $f(x) = \sum_{k=1}^{n-1} \left(\sum_{i=0}^{n-1-k} s_i \cdot s_{i+k}\right)^2$ with $s_j = 2x_j - 1$. Such sequences are needed for communication engineering [28,32,164], cryptography[58,164], as well as modulation pulses in radar and sonar ranging[172]. The LABS is $\mathcal{NP}$-hard [214]. The SOTA on LABS contains [27,32,58,59,164].

LeadingOnes The LeadingOnes problem is a benchmark problem for bit-string based black-box search [188,235,242]. It tries to maximize the number of *leading* 1 bits in the bit string of a chosen dimension n. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = n - \sum_{i=1}^{n} \prod_{j=1}^{i} x_j$. Different from OneMax, the contribution to the objective value of the bit at index i thus depends on the state of all the bits *before* this index. The problem is unimodal, i.e., has only a single global optimum and no local optimum. Different from OneMax, it is not separable, i.e., we can optimize each variable separately. The expected runtime of $(1+1)$ EA on LeadingOnes is in $\Theta(n^2)$ [70]. The average runtime $(1+1)$ FEA on LeadingOnes seems to be slower by factor proportional to n, i.e., seems to be in $\mathcal{O}(n^3)$ [232].

Linux is the leading open source operating system, i.e., a free alternative to Microsoft Windows [8,103,196,215,219]. We recommend using it for this course, for software development, and for research. Learn more at https://www.linux.org. Its variant Ubuntu is particularly easy to use and install.

LK The *Lin-Kernighan* (LK) algorithm [143] is a SLS method for the TSP. The LK algorithm performs iterative k-opt moves, i.e., in each step, it constructs the two sets X and Y of k edges such that removing the edges in X from the current tour T and then adding the edges from Y to T results in a better tour.The LK algorithm is one of the most classical approaches to the TSP.

LKH The *Lin-Kernighan-Helsgaun* algorithm [49,106,107] is a SLS method for the TSP based on the Lin-Kernighan (LK) algorithm [143]. LKH-1 was proposed in [107] and LKH-2 in [106]. It holds the record in the *World TSP* [50] as of 2025.

LS A *local search* is an algorithm where a single "current" candidate solution is maintained and new solutions are selected from its neighborhood in each step. Most LSes are randomized, i.e., stochastic local search (SLS).

Glossary VIII



MA A *Memetic Algorithm* is an EA where each new solution is refined by a LS before it enters the population [224]. As LS, we can use, e.g., RLS, but TS [41,84] is maybe a better choise. Some SOTA algorithms in some domains may be classified as MAs, e.g., Lin-Kernighan Helsgaun (LKH) basically uses a population that is refined via a local search. MAs also worked well on the JSSP [41,108] and the TSP [84].

macOS or Mac OS is the operating system that powers Apple Mac(intosh) computers [187,198]. Learn more at https://www.apple.com/macos.

MaxSAT The goal of satisfiability problems is to find an assignment for n Boolean variables that make a given Boolean formula $F : \{0,1\}^n \mapsto \{0,1\}$ become true. In the *Maximum Satisfiability* problem (MaxSAT) [109], F is given in conjunctive normal form, i.e., the variables appear either directly or negated in m "or" clauses, which are all combined into one "and." The objective function $f(x)$, subject to minimization, computes the number of clauses which are false under the variable setting x. If $f(x) = 0$, then all clauses of F are true, which solves the problem. The MaxSAT problem is $\mathcal{NP}$-complete [47] and exhibits low epistasis but deceptiveness [184], making it hard for local searches. Typical benchmark instances can be found in SATLIB, which contains smaller-scale instances, and the up-to-date MaxSAT Evaluation (MSE), providing SOTA benchmarks, algorithms, and results.

metaheuristic A *metaheuristic* is an optimization algorithm which performs a cycle of trial and error during which candidate solutions are sampled from the solution space $\mathbb{Y}$ and evaluated using an objective function $f : \mathbb{Y} \mapsto \mathbb{R}$ [92,224]. The results of the objective function are used to decide which solution is promising. The neighborhoods around promising solutions *or* similarly-structured solutions are then sampled in the next cycle. Prominent metaheuristics are SLSes, SA, TS, and EAs.

Microsoft Windows is a commercial proprietary operating system [29]. It is widely spread, but we recommend using a Linux variant such as Ubuntu for software development and for our course. Learn more at https://www.microsoft.com/windows.

moptipy is the *Metaheuristic Optimization in Python* library [231]. It has been used in several different research works, including [40,140–142,212,238,244,245]. Algorithms implemented by moptipy include EAs, $(1+1)$ EA, RLS, SA, and the $(1+1)$ FEA, amongst others. Learn more at https://thomasweise.github.io/moptipy and https://thomasweise.github.io/moptipyapps.

MSE The *MaxSAT Evaluation* is a regularly updated set of benchmark instances for the MaxSAT [115]. It also includes solver software and benchmark results [220].

Glossary IX



N-Queens The N-Queens Problem is a benchmark problem for bit-string based black-box search [63,242]. The goal is to arrange N queens on an $N \times N$ chessboard so that none can attack the other. The search space has thus dimension $n = N^2$, with each bit standing for a field and encoding whether or not a queen is placed there. The objective function $f(x)$ of the minimization variant is $N - \left(\sum_{i=1}^{n} x_i\right) - N \sum_{\xi} \max\left\{0, Q_\xi(x) - 1\right\}$ where $Q_\xi(x)$ is the number of queens in the horizontal, vertical, or diagonale ξ. The problem is quite epistatic.

NumPy is a fundamental package for scientific computing with Python, which offers efficient array data structures [57,102,120]. Learn more at https://numpy.org [168].

OneMax OneMax is the simplest possible benchmark problem for bit-string based black-box search [71,165,242]. The goal is to maximize the number of 1 bits in the bit string of a chosen dimension n. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = n - \sum_{i=1}^{n} x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately. The expected runtime of $(1+1)$ EA on OneMax is in $\Theta(n \ln n)$ [61,165]. The average runtime $(1+1)$ FEA on OneMax seems to be slower by factor proportional to n, i.e., seems to be in $\mathcal{O}(n^2 \ln n)$ [232].

OR Operations Research (or Operational Research) is the application of sciences such as mathematics and computer science to the management and organization of systems, organizations, enterprises, factories, or projects. It encompasses the development and application of problem-solving methods and techniques (such as mathematical optimization, simulation, queueing theory and other stochastic models) with the goal to improve decision-making and efficiency [53].

OR-Library is a library of benchmark instances for various OR problems [15,16] located at https://people.brunel.ac.uk/~mastjjb/jeb/info.html. It contains instances of the JSSP, 1D- and 2D-Packing, Knapsack, periodic TSPs, amongst others.

OS Operating System, the system that runs your computer, see, e.g., Linux, Microsoft Windows, macOS, and Android.

PCG A *Permuted Congruential Generator* is a pseudo-random number generator [170]. Under NumPy, a 64-bit PCG is offered as a default method for generating seeding random number sequences [169]. You can import it via `from numpy.random import PCG64, Generator` and then create it from an `int` seed `h` via `Generator(PCG64(h))`.

Glossary X

Plateau The Plateau problem is a benchmark problem for bit-string based black-box search [3,242]. It is structured exactly like Jump, but instead of being deceptive, the last ω bits to flip around the optimum are neutral. The objective function $f(x)$ of the minimization variant is $n - \|x\|_{\mathbf{1}}$ if $\|x\|_{\mathbf{1}} = n$ or $\|x\|_{\mathbf{1}} \leq n - \omega$ hold, and ω otherwise, where $\|x\|_{\mathbf{1}} = \sum_{i=\mathbf{1}}^{n} x_i$. This means that, the larger ω, the larger the neutral plane around the optimum that an algorithm needs to cross. An $(1+1)$ EA has an expected runtime of $\Theta(n^{\omega})$ on plateaus [3]. The average runtime of the $(1+1)$ FEA on Plateaus is slower by a factor seemingly proportional in n.

PostgreSQL An open source object-relational DBMS [78,171,180,208]. See https://postgresql.org for more information.

Python The Python programming language [112,138,152,227], i.e., what you will learn about in our book [227]. Learn more at https://python.org.

QAP The *Quadratic Assignment Problem* is an optimization problem where the goal is to assign a set of n facilities to a set of n locations [34,40,130,148]. Such an assignment can be represented as a permutation x of the first n natural numbers, where x_i specifies the location where facility i should be placed. For each QAP instance, a distance matrix A is given, where $A[a, b]$ specifies the distance from location a to location b, as well as a flow matrix B, where $B[i, j]$ is the amount of material flowing (e.g., daily) from facility i to facility j. The objective function $f(x)$ then rates a permutation x as $f(x) = \sum_{i=\mathbf{1}}^{n} \sum_{j=\mathbf{1}}^{n} A[x_i, x_j] * B[i, j]$. The QAP is $\mathcal{NP}$-complete [69,189] and even among this problem class, is considered as particularly hard for metaheuristics [17,34,148,203]. The QAP has applications such as building layout [52,75,131], keyboard layout [36], circuit design [76], wiring [200], and scheduling [199]. Typical benchmark instances can be found in QAPLIB. SOTA algorithms for the QAP include [17,84,157,162,206,207].

QAPLIB is a library of 136 benchmark instances for the Quadratic Assignment Problem (QAP) [33,35], 28 of which have not yet been solved to optimality [2] (at least by 2023).

Glossary XI

Random Keys encoding is a decoding procedure $\gamma : \mathbb{X} \mapsto \mathbb{Y}$ that maps a continuous search space $\mathbb{X} \subset [0,1]^n$ which is a subset of the n-dimensional real numbers to the space $\mathbb{Y}$ of permutations of the first n natural numbers [13,14]. For example, on $n = 5$, the vector $x = (0.49, 0.91, 0.33, 0.75, 0.51)$ is translated to the permutation $y = (3, 1, 5, 4, 2)$, because $x_{\mathbf{3}} = 0.33$ has the smallest value, putting 3 at the beginning, $x_{\mathbf{1}} = 0.49$ the second-smallest, placing 1 second, ..., and $x_{\mathbf{2}} = 0.91$ being the largest value meaning that the last number in y will be 2 [14]. The advantage of the encoding is that we can search in $\mathbb{X}$ applying arbitrary mathematical operators, crossover, and mutation procedures, but will always get correct permutations. The disadvantage is that $|\mathbb{X}| \gg |\mathbb{Y}|$ and that there actually is no meaning underpinning moves in $\mathbb{X}$ in relation to their projected result in $\mathbb{Y}$.

RLS Randomized local search retains the best solution x_c discovered so far during the search and, in each step, it applies a unary search operator to this best-so-far solution x_c and derives a new solution x_n. If the new solution x_n is *better or equally good* when compared with x_c, i.e., not worse, then it replaces it, i.e., is stored as the new x_c. If the search space are bit strings of length n, then RLS uses a unary search operator that flips exactly one bit. This operator is the main difference to $(1 + 1)$ EA.

FRLS The RLS with FFA plugged in [242]. On the discrete bit-string domains, this algorithm has a very specific structure: Its unary search operator flips exactly one bit, distinguishing it from the unary operator in the $(1 + 1)$ FEA, which flips each bit with probability $1/n$. On other domains, such as permutations, we use the term synonymously with $(1 + 1)$ FEA.

RTS *Reactive Tabu Search* is a variant of TS where the length of the tabu list is adapted to the problem and to the current evolution of the search, and an escape strategy for diversifying the search is used when that is not sufficient [9–12]. It has successfully been applied to a wide range of problems, from the QAP [10,11], to Knapsack problems [9,11], the N-K landscape [9] to the training of neural networks [12].

SA *Simulated Annealing* is a SLS that sometimes accepts a worse solution [38,117,125,178,224]. The probability to do so decreases over time and with the difference in objective values, i.e.,is the lower the worse the new solution is. SA performed well on a variety of problems, including the QAP [160,213] and the JSSP [174].

SATLIB is a library of benchmark instances for the Maximum Satisfiability (MaxSAT) available at https://www.cs.ubc.ca/~hoos/SATLIB/index-ubc.html [110,111].

Glossary XII

SHA-512 SHA-512 is a cryptographic hash function belonging to the *Secure Hash Algorithm 2* family [191]. It is a one-way function that computes a checksum of 512 bits from data of arbitrary length. For the same data, the same checksum is computed. From the checksum, you cannot obtain the original data. Under Python, you can use `from hashlib import sha512` to get such a digest from a text string `s` via `bytearray(sha512(s.encode("utf8")).digest())`. Since the digest works with binary data, we first need to convert the text to such data. Here, we did this by encoding the string to UCS Transformation Format 8 (UCS).

SLS *Stochastic local search* is a local search (LS), one of the simplest metaheuristic search paradigms [109]: A single "current" candidate solution is maintained and new solutions are *stochastically* sampled from its neighborhood, i.e., in a way that involves random numbers. If these solutions are deemed interesting based on their objective value, they replace the "current". The cycle continues. Basic examples are RLS and $(1+1)$ EA. More complex examples that add mechanisms to escape local optima on top of the SLS paradigm are TS and SA.

SOTA State-of-the-Art, i.e., the best-performing methods for a field or problem type

stack trace A stack trace gives information the way in which one function invoked another. The term comes from the fact that the data needed to implement function calls is stored in a stack data structure [128]. The data for the most recently invoked function is on top, the data of the function that called is right below, the data of the function that called that one comes next, and so on. Printing a stack trace can be very helpful when trying to find out where an `Exception` occurred.

STSP A *symmetric Traveling Salesperson Problem* is a special case of the TSP, where the $n \times n$ distance matrix A is symmetric, i.e., $A[a,b] = A[b,a] \forall a, b \in 1..n$.

Trap The Trap problem is a benchmark problem for bit-string based black-box search [70,166,242]. It is structured exactly like OneMax, however the worst and the best solution are swapped. This makes the problem highly deceptive, as following the "gradient" in the search space leads the search away from the global optimum. For bit strings of length n, the objective function $f(x)$ of the minimization variant is 0 if $\|x\|_1 = 0$ and $n - \|x\|_1 - 1$ otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. An $(1+1)$ EA will converge to the resulting local optimum and thus have an expected runtime of $\Theta(n^n)$ [70]. In experiments, the $(1+1)$ FEA achieves polynomial runtime on Trap, seemingly in $\mathcal{O}(n^2 \ln n)$ [232,233,242].

Glossary XIII

TS *Tabu Search* is one of the most successful SLSes [90,91,93,119]. In order to avoid returning to previous solutions, it declares certain solutions or search moves as "tabu." For example, if a bit in a discrete problem has been flipped by the search operator, it may be forbidden to flip the bit again for some time, thus preventing the algorithm from getting trapped in a cycle. This rule may be overridden if a new best-so-far solution is discovered that outperforms all previous solutions, in which case it would be accepted (this is the so-called aspiration criterion). TS has performed well on the QAP [10,11,159,162,205,206] and on the JSSP [167,176,177,195,243].

TSP In an instance of the *Traveling Salesperson Problem*, also known as *Traveling Salesman Problem*, a set of n cities or locations as well as the distances between them are given [4,100,136,140,228,234]. The goal is to find the shortest round-trip tour that starts at one city, visits all the other cities one time each, and returns to the origin. The TSP is one of the most well-known $\mathcal{NP}$-hard combinatorial optimization problems [88,100,132]. The TSP has many applications[4], including in transportation, logistics, (circuit) plotting and drilling problems[99], telescope aiming, and genome sequencing. Solutions are often encoded as permutations x of the first n natural numbers, where each city gets a number and the order of numbers in the permutation corresponds to the order of cities in the tour. The distances between the n cities are usually given in a $n \times n$ distance matrix A, where $A[a, b]$ is the distance from city a to city b with $a, b \in 1..n$. Then, the objective function subject to minimization is $f(x) = A[x_n, x_{\mathbf{1}}] + \sum_{i=\mathbf{1}}^{n-\mathbf{1}} A[x_i, x_{i+\mathbf{1}}]$. Typical benchmark instances can be found in TSPLib [185,186], the 8th DIMACS challenge[121–123], and the *World TSP* repository[50].

TSPLib is a library of benchmark instances for the Traveling Salesperson Problem (TSP) [185,186]. Its original URL was available until 2025 and then became defunct. The repository https://github.com/shredderzwj/TSPLIB contains the data. Additionally, you may also check https://github.com/thomasWeise/tspSuite, which contains all the TSPLib instances as well as Java code to load them. The TSPLib contains 110 instances of the symmetric Traveling Salesperson Problems (STSPs) with scales n ranging from 14 to 85 900, but 93 instances have less than 2000 nodes. There also are 19 asymmetric Traveling Salesperson Problems (ATSPs) with scales $n \in 17..443$.

Glossary XIV

TTP The *Traveling Tournament Problem* is the combinatorial optimization problem of both efficiently and fairly organizing a tournament of n teams that play against each other in a pairwise fashion [73,238]. The efficient part boils down to arranging the games such that the total travel length is short, which is somewhat similar to the classical TSP. Initially, each team is at its home location. On each day, a team needs to travel if its scheduled game is not at its present location. On the last day, each team may need to travel back home unless their last game is a home game. The total travel length sums up the lengths of all travels over all teams. The fair part is represented in several constraints, such as doubleRoundRobin, compactness, maxStreak, and noRepeat. The TTP is $\mathcal{NP}$-hard [221].

TwoMax The TwoMax problem is a benchmark problem for bit-string based black-box search [86,218,242]. It has a global and a local optimum, both of about the same size, at opposite ends of the search space. For bit strings of length n, the objective function $f(x)$ of the minimization variant is 0 if $\|x\|_1 = n$ and $1 + n - \max\{\|x\|_1, n - \|x\|_1\}$ otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. An $(1+1)$ EA has a 50/50 chance to converge to the local or global optimum and thus has an expected runtime in $\Theta(n^n)$ [85,86]. In experiments, the $(1+1)$ FEA achieves polynomial runtime seemingly in $\mathcal{O}(n^2 \ln n)$ on TwoMax [232,233,242].

Ubuntu is a variant of the open source operating system Linux [44,105]. We recommend that you use this operating system to follow this class, for software development, and for research. Learn more at https://ubuntu.com. If you are in China, you can download it from https://mirrors.ustc.edu.cn/ubuntu-releases.

UCS Universal Coded Character Set, see Unicode

Unicode A standard for assigning characters to numbers [113,210,216]. The Unicode standard supports basically all characters from all languages that are currently in use, as well as many special symbols. It is the predominantly used way to represent characters in computers and is regularly updated and improved.

URI A *Uniform Resource Identifier* is an identifier for an abstract or physical resource in the internet [241]. It can be a URL, a name, or both. URIs are supersets of URLs. The connection strings of the PostgreSQL DBMS are examples of Uniform Resource Identifiers (URIs).

Glossary XV

URL A *Uniform Resource Locator* identifies a resource in the World Wide Web (WWW) and a way to obtain it by describing a network access mechanism. The most notable example of URLs is the text you write into web browsers to visit websites [20]. URLs are subsets of URIs.

UTF-8 The *UCS Transformation Format 8* is one standard for encoding Unicode characters into a binary format that can be stored in files [113,241]. It is the world wide web's most commonly used character encoding, where each character is represented by one to four bytes. It is backwards compatible with ASCII.

VND *Variable Neighborhood Descend*; see VNS. VND in combination with GRASP has been applied to the 2BP|O|F in [175].

VNS *Variable Neighborhood Search* is a metaheuristic framework combining a systematic change of neighborhood with LS [101,163]. A *neighborhood* structure in LS defines which solutions can be reached from a given solution within one search step. Usually, one uses a single unary operator and, hence, has a single neighborhood structure. However, for many problems, we can easily design many operators. For permutations, for example, one operator may swap two elements, another one may reverse a section of the permutation, and yet another one, while yet another one may rotate a subsequence one step to the left or right [228]. In the VNS framework, a multiple neighborhoods are investigated in a systematic fashion. Assume that we have a list of neighborhood structures. Variable Neighborhood Descend (VND) works in a deterministic fashion. It finds the best solution that can be reached in one step from the current solution under the current neighborhood. If this is better than the current solution, we accept it and continue with the first neighborhood. Otherwise, we continue with the next neighborhood in the list. In Basic VNS, instead of picking the best move from the current neighborhood, the first improving move is used. Also, at the beginning of each cycle, a random point from the current neighborhood around the current solution is chosen as starting point.

WWW World Wide Web [19,54]

Glossary XVI

XML The *Extensible Markup Language* is a text-based language for storing and transporting of data [31,46,120]. It allows you to define elements in the form `<myElement myAttr="x">...text..</myElement>`. Different from comma-separated values (CSV), elements in XML can be hierarchically nested, like `<a><b><c>test</c></b><b>bla</b></a>`, and thus easily represent tree structures. XML is one of most-used data interchange formats. To process XML in Python, use the `defusedxml` library [104], as it protects against several security issues.

YAML *YAML Ain't Markup Language™* is a human-friendly data serialization language for all programming languages [45,68,129]. It is widely used for configuration files in the DevOps environment. See https://yaml.org for more information.

$i..j$ with $i, j \in \mathbb{Z}$ and $i \leq j$ is the set that contains all integer numbers in the inclusive range from i to j. It always holds that $i..j \subset \mathbb{Z}$. For example, $5..9$ is equivalent to $\{5, 6, 7, 8, 9\}$

A the $n \times n$ distance matrix. $A[a, b]$ indicates the distance between locations a and b with $a, b \in 1..n$. A distance matrix can be symmetric, in which case $A[a, b] = A[b, a]\ \forall a, b \in 1..n$. Distance matrices represent the problem instance data in TSPs and part of the instance data of QAPs.

B the $n \times n$ flow matrix. $B[a, b]$ is the flow of goods between locations a and b with $a, b \in 1..n$. Flow matrices are one half of the problem instance data of QAPs.

$f(y)$ The *objective function* $f : \mathbb{Y} \mapsto \mathbb{R}$ can compute a cost or rating for each candidate solution y in the solution space $\mathbb{Y}$. The smaller this value, the better the solution, i.e., in the context of this work, objective functions are subject to minimization. Objective functions are not necessarily continuous and it is also quite common that they have integer or natural numbers as results, e.g., we often have $f : \mathbb{Y} \mapsto \mathbb{N}_0$ instead of $f : \mathbb{Y} \mapsto \mathbb{R}$.

Glossary XVII

$\gamma(x)$ The decoding function $\gamma : \mathbb{X} \mapsto \mathbb{Y}$ translates point from the search space $\mathbb{X}$ to one point y in the solution space $\mathbb{Y}$. It is a very common case that $\mathbb{X} = \mathbb{Y}$ and that the decoding function γ is the identity mapping. Examples for encodings that translate from a simple search space $\mathbb{X}$ to a complex solution data structure $\mathbb{Y}$ are the IBL algorithm that translates (potentially signed) permutations to two-dimensional packings on the 2BP, the permutation-based encoding of Gantt charts for the JSSP from [22,23,89,193,229], or the permutation-based encoding of game plans for the TTP from [238]. Encodings can also translate between types of search spaces. The Random Keys encoding, for example, translates from $[0, 1]^n$ to permutations of the first n natural numbers..

k the number of jobs in an instance of the JSSP.

m the number of machines in an instance of the JSSP.

n We usually use the value $n \in \mathbb{N}_0$ to denote the *scale*, i.e., the size of the problem to solve. This notion is very general in computer science and not limited to optimization. For example, if we sort a list or search in a list, the scale n is the length of the list, i.e., the number of elements in it. In a TSP, this may be the number of cities. In a discrete benchmark problem such as OneMax or Trap, this may be the number of bits over which the problem is defined. In a QAP, this may be the number of facilities and locations. In a MaxSAT problem, this may be the number of variables that are input to the Boolean formula that we want to become true. There are also problems where the scale is not defined straightforwardly like this. For example, in a JSSP, we have a number of machines and a number of jobs, which together define the size of the problem. But even then, the scale n relates to the size of the solution space $\mathbb{Y}$, and, hence, also of the search space $\mathbb{X}$, which usually grow exponentially with n. And this is already the main issue: The larger n, the (exponentially) larger the number of possible solutions and thus, the larger the runtime of algorithms..

$\mathbb{N}_0$ the set of the natural numbers *including* 0, i.e., 0, 1, 2, 3, and so on. It holds that $\mathbb{N}_0 \subset \mathbb{Z}$ and that $\mathbb{N}_0 = \mathbb{N}_1 \cup \{0\}$.

$\mathbb{N}_1$ the set of the natural numbers *excluding* 0, i.e., 1, 2, 3, 4, and so on. It holds that $\mathbb{N}_1 \subset \mathbb{Z}$ and that $\mathbb{N}_1 = \mathbb{N}_0 \setminus \{0\}$.

$\mathcal{NP}$ is the class of computational problems that can be solved in polynomial time by a non-deterministic machine and can be verified in polynomial time by a deterministic machine (such as a normal computer) [97].

Glossary XVIII

$\mathcal{NP}$-complete A decision problem is $\mathcal{NP}$-complete if it is in $\mathcal{NP}$ and all problems in $\mathcal{NP}$ are reducible to it in polynomial time [97,183]. A problem is $\mathcal{NP}$-complete if it is $\mathcal{NP}$-hard and if it is in $\mathcal{NP}$.

$\mathcal{NP}$-hard A problem is $\mathcal{NP}$-hard if all problems in $\mathcal{NP}$ are reducible to it in polynomial time [97]. Algorithms that guarantee to find the correct solutions of $\mathcal{NP}$-hard problems [39,47,135] have a worst-case runtime that grows exponentially with the problem scale.

$\Omega(g(x))$ If $f(x) = \Omega(g(x))$, then there exist positive numbers $x_0 \in \mathbb{R}^+$ and $c \in \mathbb{R}^+$ such that $f(x) \geq c * g(x) \geq 0 \forall x \geq x_0$ [127,128]. In other words, $\Omega(g(x))$ describes a lower bound for function growth.

$\mathcal{O}(g(x))$ If $f(x) = \mathcal{O}(g(x))$, then there exist positive numbers $x_0 \in \mathbb{R}^+$ and $c \in \mathbb{R}^+$ such that $0 \leq f(x) \leq c * g(x) \forall x \geq x_0$ [6,127,128,133]. In other words, $\mathcal{O}(g(x))$ describes an upper bound for function growth.

$\Theta(g(x))$ If $f(x) = \Theta(g(x))$, then $f(x) = \mathcal{O}(g(x))$ and $f(x) = \Omega(g(x))$ [127,128]. In other words, $\Theta(g(x))$ describes an exact order of function growth.

$\mathbb{R}$ the set of the real numbers.

$\mathbb{R}^+$ the set of the positive real numbers, i.e., $\mathbb{R}^+ = \{x \in \mathbb{R} : x > 0\}$.

$\mathbb{X}$ The search space $\mathbb{X}$ is the space through which an optimization algorithm navigates in order to find good solutions. The search operators of metaheuristics are used to sample points $x \in \mathbb{X}$, for example. On many benchmark problems, the objective functions f directly evaluate the elements $x \in \mathbb{X}$, i.e., are defined as $f : \mathbb{X} \mapsto \mathbb{R}$. However, very often these elements x are not the same data structures that the user is interested in and/or that the objective functions evaluate: It is common that the search space $\mathbb{X}$ is a simple and plain data structure that can be tackled with standard operations or mathematical tools, such as real vectors $\mathbb{R}^n$, permutations, or bit strings, whereas the solution space $\mathbb{Y}$ can be something more complicated. Then, the user only cares about the solutions $y \in \mathbb{Y}$ and not about the search space $\mathbb{X}$. A decoding $\gamma : \mathbb{X} \mapsto \mathbb{Y}$ is employed to translate the $x \in \mathbb{X}$ to $y = \gamma(x)$ with $y \in \mathbb{Y}$.

x a point in the search space $\mathbb{X}$.

Glossary XIX

$\mathbb{Y}$ the set of candidate solutions of an optimization problem is called the *solution space* $\mathbb{Y}$. The solution space corresponds to the data structure holding the candidate solutions y. These are the elements that are passed to the user after the optimization process is completed. They are also the parameters of the objective function(s) $f : \mathbb{Y} \mapsto \mathbb{R}$.

y a candidate solution $y \in \mathbb{Y}$ is one possible solution to an optimization problem. After the optimization process is completed, one or multiple such solutions are passed to the user.

$\mathbb{Z}$ the set of the integers numbers including positive and negative numbers and 0, i.e., . . . , -3, -2, -1, 0, 1, 2, 3, . . . , and so on. It holds that $\mathbb{Z} \subset \mathbb{R}$.