合肥大學
HEFEI UNIVERSITY

Frequency Fitness Assignment as a Research Direction

Thomas Weise (汤卫思)
tweise@hfuu.edu.cn · https://thomasweise.github.io

School of Artificial Intelligence and Big Data
Hefei University
Hefei, Anhui, China

人工智能与大数据学院
合肥大学
中国安徽省合肥市

Version: 2026-10-12

Outline

1. Introduction
2. Research Field: Optimization
3. Research Direction: Frequency Fitness Assignment
4. Our Results
5. Future Works
6. Summary
7. Advertisement



Introduction

Introduction

- Our team has two general research directions: Optimization[197] and Artificial Intelligence (AI).

Introduction

- Our team has two general research directions: Optimization[197] and Artificial Intelligence (AI).
- My students and I are members of the Optimization Direction.

Introduction



- Our team has two general research directions: Optimization[197] and Artificial Intelligence (AI).
- My students and I are members of the Optimization Direction.
- Today, I therefore want to first give a short introduction into the field of optimization, before delving into one of our concrete research topics, namely Frequency Fitness Assignment (FFA).

Research Field: Optimization

What is Optimization?

- There are two ways to look at optimization.

What is Optimization?

- The economic view.

Optimization Problem

An optimization problem is a situation which requires deciding for one choice from a set of possible alternatives in order to reach a predefined or required benefit at minimal costs.

What is Optimization?


- The mathematical view.

Optimization Problem

An optimization problem is a situation which requires deciding for one choice from a set of possible alternatives in order to reach a predefined or required benefit at minimal costs.


Solving an optimization problem requires finding an input element $x^\star$ within a set $\mathbb{X}$ of allowed elements for which a mathematical function $f\colon \mathbb{X} \mapsto \mathbb{R}$ takes on the smallest possible value.

Example: Function Optimization




- In the field of continuous optimization, we could literally try to find the minimum of a mathematical function $f : \mathbb{R}^n \mapsto \mathbb{R}$.

Example: Function Optimization




- In the field of continuous optimization, we could literally try to find the minimum of a mathematical function $f : \mathbb{R}^n \mapsto \mathbb{R}$.
- The search space $\mathbb{X}$ would then be the n-dimensional real vectors, i.e., $\mathbb{X} = \mathbb{R}^n$.

Example: Function Optimization




- In the field of continuous optimization, we could literally try to find the minimum of a mathematical function $f : \mathbb{R}^n \mapsto \mathbb{R}$.
- The search space $\mathbb{X}$ would then be the n-dimensional real vectors, i.e., $\mathbb{X} = \mathbb{R}^n$.
- The objective function would, well, be the function f.

Example: Function Optimization



- In the field of continuous optimization, we could literally try to find the minimum of a mathematical function $f : \mathbb{R}^n \mapsto \mathbb{R}$.
- The search space $\mathbb{X}$ would then be the n-dimensional real vectors, i.e., $\mathbb{X} = \mathbb{R}^n$.
- The objective function would, well, be the function f.
- The optimal solution $x^\star \in \mathbb{X}$ is the minimum of f.

Example: Function Optimization



- In the field of continuous optimization, we could literally try to find the minimum of a mathematical function $f : \mathbb{R}^n \mapsto \mathbb{R}$.
- The search space $\mathbb{X}$ would then be the n-dimensional real vectors, i.e., $\mathbb{X} = \mathbb{R}^n$.
- The objective function would, well, be the function f.
- The optimal solution $x^\star \in \mathbb{X}$ is the minimum of f.
- This is *not* what I am working on, though.

Example: Traveling Salesperson Problem

- In the Traveling Salesperson Problem (TSP)[4,90,121,125,201,209], the goal is to find the shortest round-trip tour through a set of n cities.



Example: Traveling Salesperson Problem

- In the Traveling Salesperson Problem (TSP)[4,90,121,125,201,209], the goal is to find the shortest round-trip tour through a set of n cities.
- The search space $\mathbb{X}$ thus is the set of all possible round-trip tours through these n cities, usually specified as permutations of the first n natural numbers.



Example: Traveling Salesperson Problem

- In the Traveling Salesperson Problem (TSP)[4,90,121,125,201,209], the goal is to find the shortest round-trip tour through a set of n cities.
- The search space $\mathbb{X}$ thus is the set of all possible round-trip tours through these n cities, usually specified as permutations of the first n natural numbers.
- The objective function $f : \mathbb{X} \mapsto \mathbb{R}$, subject to minimization, is the length of the tour.




Example: Traveling Salesperson Problem

- In the Traveling Salesperson Problem (TSP)[4,90,121,125,201,209], the goal is to find the shortest round-trip tour through a set of n cities.
- The search space $\mathbb{X}$ thus is the set of all possible round-trip tours through these n cities, usually specified as permutations of the first n natural numbers.
- The objective function $f : \mathbb{X} \mapsto \mathbb{R}$, subject to minimization, is the length of the tour.
- The optimal solution $x^\star \in \mathbb{X}$ is the shortest possible tour.




Example: Bin Packing Problem

- The goal of the Bin Packing Problem is to pack n objects, each having a specific size, into as few bins (also of a given size) as possible[219,220].




Example: Bin Packing Problem

- The goal of the Bin Packing Problem is to pack n objects, each having a specific size, into as few bins (also of a given size) as possible[219,220].
- The $\mathbb{X}$ comprises all possible packing orders of the n objects.




Example: Bin Packing Problem

- The goal of the Bin Packing Problem is to pack n objects, each having a specific size, into as few bins (also of a given size) as possible[219,220].
- The $\mathbb{X}$ comprises all possible packing orders of the n objects.
- The objective function f is the number of bins needed by a given packing order.



Example: Bin Packing Problem

- The goal of the Bin Packing Problem is to pack n objects, each having a specific size, into as few bins (also of a given size) as possible[219,220].
- The $\mathbb{X}$ comprises all possible packing orders of the n objects.
- The objective function f is the number of bins needed by a given packing order.
- The optimum $x^\star$ is the packing order requiring the fewest bins.



Optimization is Hard

- Finding the globally optimal solution $x^\star$ from the set of all possible solutions $\mathbb{X}$ is often an $\mathcal{NP}$-hard problem.




Optimization is Hard



- Finding the globally optimal solution $x^\star$ from the set of all possible solutions $\mathbb{X}$ is often an $\mathcal{NP}$-hard problem.
- Currently, there is no algorithm that can guarantee to find the optimal solution of every instance of a given $\mathcal{NP}$-hard problem in a runtime that is not longer than polynomial in the size of the problem (i.e., existing algorithms may need exponential runtime in the worst case).

Optimization is Hard

- Finding the globally optimal solution $x^\star$ from the set of all possible solutions $\mathbb{X}$ is often an $\mathcal{NP}$-hard problem.
- Currently, there is no algorithm that can guarantee to find the optimal solution of every instance of a given $\mathcal{NP}$-hard problem in a runtime that is not longer than polynomial in the size of the problem (i.e., existing algorithms may need exponential runtime in the worst case).



Optimization is Hard



- Finding the globally optimal solution $x^\star$ from the set of all possible solutions $\mathbb{X}$ is often an $\mathcal{NP}$-hard problem.
- Currently, there is no algorithm that can guarantee to find the optimal solution of every instance of a given $\mathcal{NP}$-hard problem in a runtime that is not longer than polynomial in the size of the problem (i.e., existing algorithms may need exponential runtime in the worst case).
- In other words, if we want to guarantee to find the best possible solution $x^\star$ for all possible instances of a problem, we often cannot really be much faster than testing all possible candidate solutions $x \in \mathbb{X}$ in the worst case.

Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.

Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.

Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.

Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.

Begin with a set $S_0 \subset \mathbb{X}$ of one or multiple randomly sampled solutions


Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.



Metaheuristics

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.



RLS and the $(1+1)$ EA



- stochastic local search (SLS) with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
        if $y_n \leq y_c$ **then**

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

RLS and the $(1+1)$ EA

- SLS with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according to this pattern[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- Let's start with RLS/$(1+1)$ EA and modify it to become SA.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $y_n \leq y_c$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $\mathfrak{R}_0^1 < e^{y_c - y_n}$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;


Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

while $\neg$ terminate **do**
$x_n \leftarrow$ `move`(x_c); $y_n \leftarrow f(x_n)$;

if $\mathfrak{R}_0^1 < e^{y_c - y_n}$ **then**



Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $\mathfrak{R}_0^1 < e^{y_c - y_n}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameter T_0.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    $T \leftarrow T_0$;
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameter T_0.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    $T \leftarrow T_0$;
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameter T_0.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $\tau \leftarrow \tau + 1$;
    $T \leftarrow T_0$;
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameters T_0 and ε.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $\tau \leftarrow \tau + 1$;
    $T \leftarrow T_0(1-\varepsilon)^{\tau-1}$; ▷ T decreases over time
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameters T_0 and ε.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$; ▷ preserve best!
  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $\tau \leftarrow \tau + 1$;
    $T \leftarrow T_0(1-\varepsilon)^{\tau-1}$; ▷ T decreases over time
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

- SA also remembers best-so-far solution x_B and its objective value y_B, because it could get lost.

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameters T_0 and ε.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$; ▷ preserve best!
  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $\tau \leftarrow \tau + 1$;
    $T \leftarrow T_0(1-\varepsilon)^{\tau-1}$; ▷ T decreases over time
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
      if $y_c < y_B$ **then** $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;

- SA also remembers best-so-far solution x_B and its objective value y_B, because it could get lost.

Simulated Annealing

- Simulated Annealing (SA)[110] is a local search that accepts also worsening moves, but with a probability that decreases over time and with the difference in solution quality.
- $\mathfrak{R}_0^1$ be a random number uniformly distributed in $[0, 1)$.
- High temperatures T increase the acceptance probability P of worse solutions, low T reduce it.
- P is regulated by temperature schedule with parameters T_0 and ε.

procedure SA($f : \mathbb{X} \mapsto \mathbb{R}$, T_0, ε)
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$; ▷ preserve best!
  $\tau \leftarrow 0$; ▷ τ is iteration counter
  while ¬ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $\tau \leftarrow \tau + 1$;
    $T \leftarrow T_0(1-\varepsilon)^{\tau-1}$; ▷ T decreases over time
    if $\mathfrak{R}_0^1 < e^{\frac{y_c - y_n}{T}}$ **then** ▷ always true if $y_n \leq y_c$
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
      if $y_c < y_B$ **then** $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  return x_B, y_B

- SA also remembers best-so-far solution x_B and its objective value y_B, because it could get lost.

Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.

Metaheuristic Optimization



- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.

Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.

Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.

Begin with a set $S_0 \subset \mathbb{X}$ of one or multiple randomly sampled solutions


Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.




Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.



Metaheuristic Optimization

- Because of this hardness of optimization, metaheuristic algorithms that follow the trial-and-error idea of iterative improvement have emerged.
- They drop the guarantee to find the optimal solution.
- They try to find good solutions within a feasible runtime.
- They (usually) start with random solutions.
- And then roughly follow this cycle.



The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.

The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$

The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$;

The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

The $(1+1)$ EA and RLS

- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**

The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$;

The $(1+1)$ EA and RLS



- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

The $(1+1)$ EA and RLS

- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
    randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
    while $\neg$ terminate **do**
        $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
        if $y_n \leq y_c$ **then**

The $(1+1)$ EA and RLS

- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$;

The $(1+1)$ EA and RLS

- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

The $(1+1)$ EA and RLS

- Local search with $|S_i| = |N_i| = 1$ is the simplest realization of the metaheuristic idea.
- Randomized local search (RLS) and the $(1+1)$ evolutionary algorithm ($(1+1)$ EA) work according the same pattern (and differ only in their unary search operator $move$)[33,61].
- They accept the new solution if it is better or equally good compared to the current solution.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

Research Field

- My students and I together work on solving discrete or combinatorial problems with metaheuristic algorithms.

Research Field

- My students and I together work on solving discrete or combinatorial problems with metaheuristic algorithms.
- We investigate classical hard problems that have discrete search spaces, such as bit strings or permutations.

Research Field

- My students and I together work on solving discrete or combinatorial problems with metaheuristic algorithms.
- We investigate classical hard problems that have discrete search spaces, such as bit strings or permutations.
- Here, the objective functions take on only natural numbers in $\mathbb{N}_0$.

Research Field

- My students and I together work on solving discrete or combinatorial problems with metaheuristic algorithms.
- We investigate classical hard problems that have discrete search spaces, such as bit strings or permutations.
- Here, the objective functions take on only natural numbers in $\mathbb{N}_0$.
- We try to enable metaheuristic algorithms to find better solutions for these problems.

Research Direction: Frequency Fitness Assignment



Metaheuristic Optimization Algorithms



- The most fundamental concept in metaheuristic optimization is

If you keep good solutions and modify them, you are likely to get better solutions.

Metaheuristic Optimization Algorithms



- The most fundamental concept in metaheuristic optimization is

If you keep good solutions and modify them, you are likely to get better solutions.

If you keep accepting better and better solutions, you will get really good solutions eventually.

Metaheuristic Optimization Algorithms



- The most fundamental concept in metaheuristic optimization is

If you keep good solutions and modify them, you are likely to get better solutions.

If you keep accepting better and better solutions, you will get really good solutions eventually.

- Algorithms like random sampling or exhaustive enumeration that do not at least statistically prefer better solutions have extremely bad performance.

Metaheuristic Optimization Algorithms



- The most fundamental concept in metaheuristic optimization is

If you keep good solutions and modify them, you are likely to get better solutions.

If you keep accepting better and better solutions, you will get really good solutions eventually.

- Algorithms like random sampling or exhaustive enumeration that do not at least statistically prefer better solutions have extremely bad performance.
- We challenge this principle.

Metaheuristic Optimization Algorithms



- The most fundamental concept in metaheuristic optimization is

If you keep good solutions and modify them, you are likely to get better solutions.

If you keep accepting better and better solutions, you will get really good solutions eventually.

- Algorithms like random sampling or exhaustive enumeration that do not at least statistically prefer better solutions have extremely bad performance.
- We challenge this principle.
- Our Frequency Fitness Assignment (FFA) does **not** prefer better solutions ... yet it can improve the performance of existing algorithms in several cases!

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.
- It changes the way the algorithm selects the interesting solutions S_{i+1} from the sets $P_i = S_i \cup N_i$.

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.
- It changes the way the algorithm selects the interesting solutions S_{i+1} from the sets $P_i = S_i \cup N_i$.
- It therefore maintains a table H with the encounter frequency of each objective value in the selection decisions.

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.
- It changes the way the algorithm selects the interesting solutions S_{i+1} from the sets $P_i = S_i \cup N_i$.
- It therefore maintains a table H with the encounter frequency of each objective value in the selection decisions.
- The table H is initially filled with zeros.

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.
- It changes the way the algorithm selects the interesting solutions S_{i+1} from the sets $P_i = S_i \cup N_i$.
- It therefore maintains a table H with the encounter frequency of each objective value in the selection decisions.
- The table H is initially filled with zeros.
- Before the selection step of the algorithm, $H[f(P_i[j])]$ for all $j \in 1..|P_i|$ is incremented by 1.

FFA: Idea



- Frequency Fitness Assignment (FFA) is a module that can be plugged into different existing algorithms.
- It changes the way the algorithm selects the interesting solutions S_{i+1} from the sets $P_i = S_i \cup N_i$.
- It therefore maintains a table H with the encounter frequency of each objective value in the selection decisions.
- The table H is initially filled with zeros.
- Before the selection step of the algorithm, $H[f(P_i[j])]$ for all $j \in 1..|P_i|$ is incremented by 1.
- Then, the frequencies $H[f(P_i[j])]$ replace the objective values $f(P_i[j])$ in the actual selection decisions.

FFA: (1+1) EA and (1+1) FEA

- Let's plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ EA with FFA ($(1+1)$ FEA).

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- We start with the $(1+1)$ EA.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{N})$

  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $y_n \leq y_c$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- We begin by initializing the frequency table H with all zeros.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;

    if $y_n \leq y_c$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- *Before* the selection decision, we increment the frequency values of the objective values of all current solutions.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $H[y_c] \leftarrow H[y_c] + 1$; $H[y_n] \leftarrow H[y_n] + 1$;
    if $y_n \leq y_c$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- Now the frequency values replace the objective values in the selection decisions.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;

  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $H[y_c] \leftarrow H[y_c] + 1$; $H[y_n] \leftarrow H[y_n] + 1$;
    if $H[y_n] \leq H[y_c]$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;

  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- Since we may now lose the best-so-far solution, we need to track it in additional variables.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $H[y_c] \leftarrow H[y_c] + 1$; $H[y_n] \leftarrow H[y_n] + 1$;
    if $H[y_n] \leq H[y_c]$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- Since we may now lose the best-so-far solution, we need to track it in additional variables.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $H[y_c] \leftarrow H[y_c] + 1$; $H[y_n] \leftarrow H[y_n] + 1$;
    if $H[y_n] \leq H[y_c]$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
      if $y_c < y_B$ **then** $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  return x_c, y_c

FFA: (1+1) EA and (1+1) FEA

- Since we may now lose the best-so-far solution, we need to track it in additional variables.
- ... which are then the return values of the $(1+1)$ FEA.

procedure $(1+1)$ EA$(f : \mathbb{X} \mapsto \mathbb{R})$
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    if $y_n \leq y_c$ **then** $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
  return x_c, y_c

procedure $(1+1)$ FEA$(f : \mathbb{X} \mapsto \mathbb{N})$
  $H \leftarrow (0, 0, \cdots, 0)$;
  randomly sample x_c from $\mathbb{X}$; $y_c \leftarrow f(x_c)$;
  $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  while $\neg$ terminate **do**
    $x_n \leftarrow \texttt{move}(x_c)$; $y_n \leftarrow f(x_n)$;
    $H[y_c] \leftarrow H[y_c] + 1$; $H[y_n] \leftarrow H[y_n] + 1$;
    if $H[y_n] \leq H[y_c]$ **then**
      $x_c \leftarrow x_n$; $y_c \leftarrow y_n$;
      if $y_c < y_B$ **then** $x_B \leftarrow x_c$; $y_B \leftarrow y_c$;
  return x_B, y_B

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.
- Solutions get less attractive the more often their corresponding objective values have been seen. This also holds for local optima...

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.
- Solutions get less attractive the more often their corresponding objective values have been seen. This also holds for local optima...
- Solutions with better objective values are no longer preferred over such with worse objective value.

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.
- Solutions get less attractive the more often their corresponding objective values have been seen. This also holds for local optima...
- Solutions with better objective values are no longer preferred over such with worse objective value.
- Instead, solutions with less-frequent objective values are preferred.

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.
- Solutions get less attractive the more often their corresponding objective values have been seen. This also holds for local optima...
- Solutions with better objective values are no longer preferred over such with worse objective value.
- Instead, solutions with less-frequent objective values are preferred.
- Algorithms using FFA are invariant under all injective transformations of the objective function value.

FFA: What does this do?



- The rating $H[f(x)]$ of a solution x depends only on how often solutions x' with $f(x') = f(x)$ have previously been seen in the optimization process.
- Static optimization problems become dynamic, because frequency fitness H changes over time.
- Solutions get less attractive the more often their corresponding objective values have been seen. This also holds for local optima...
- Solutions with better objective values are no longer preferred over such with worse objective value.
- Instead, solutions with less-frequent objective values are preferred.
- Algorithms using FFA are invariant under all injective transformations of the objective function value.
- They are less likely to get stuck at local optima, which is a problem for, e.g., the $(1+1)$ EA.

Our Results

Three Core Works

snippets of [205, 207, 208]

Frequency Fitness Assignment

Thomas Weise, *Member, IEEE,* Mingxu Wan, Pu Wang, *Member, IEEE,* Ke Tang, *Senior Member, IEEE,* Alexandre Devert, and Xin Yao, *Fellow, IEEE*

***Abstract*—Metaheuristic optimization procedures such as evolutionary algorithms are usually driven by an objective function that rates the quality of a candidate solution. However, it is not clear in practice whether an objective function adequately rewards intermediate solutions on the path to the global optimum and it may exhibit deceptiveness, epistasis, neutrality, ruggedness, and a lack of causality. In this paper, we introduce the frequency fitness H, subject to minimization, which rates how often solutions with the same objective value have been discovered so far. The ideas behind this method are that good solutions are difficult to find and that if an algorithm gets stuck at a local optimum, the frequency of the objective values of the surrounding solutions will increase over time, which will eventually allow it to leave that region again. We substitute a frequency fitness assignment process (FFA) for the objective function into several different optimization algorithms. We conduct a comprehensive set of experiments: the synthesis of algorithms with genetic programming (GP), the solution of MAX-SAT problems with genetic algorithms, classification with Memetic Genetic Programming, and numerical optimization with a (1+1) Evolution Strategy, to verify the utility of FFA. Given that they have no access to the original objective function at all, it is surprising that for some problems (e.g., the algorithm synthesis task) the FFA-based algorithm variants perform significantly better. However, this cannot be guaranteed for all tested problems. Thus, we also analyze scenarios where algorithms using FFA do not perform better or perform even worse than with the original objective functions.**

***Index Terms*—Combinatorial optimization, diversity, fitness assignment, frequency, genetic programming (GP), numerical optimization.**

I. Introduction

SINGLE-OBJECTIVE optimization is a process with the goal of finding [illegible] (global optimal, i.e., optimal) solutions x from within a space $\mathbb{X}$ of possible solutions. An objective function f serves as quality measure guiding the search. Black-box metaheuristic approaches are methods that only require such an objective function and search operations to solve an optimization problem without any further insight into their structure. The most prominent family of these methods are evolutionary algorithms, which have wide applications ranging from engineering, planning and scheduling, numerical optimization, to even program synthesis.

Most metaheuristic optimization methods start with a randomly generated set of candidate solutions. New points in the search space are derived by modifying or combining promising existing solutions. Promising here means having a better objective value than the other points visited so far, maybe combined with some considerations about diversity. The rationale is that in the ideal case, solutions that have better objective values should be closer to the global optimum or, at least, may have even better solutions in their vicinity.

The principle of tending to choose areas of the solution space for sampling where points with better objective values have previously been discovered is one of the most universally applied ideas in black-box optimization. Lehman and Stanley [1] argued that increasing fitness does not always reveal the best path through the search space. Building on their work, we believe that there is at least one other fundamental principle inherent to non-trivial optimization problems that can be exploited to solve them: good solutions (and hence, good objective values) are hard to find.

If [illegible]ns for optimization as sampling of the [illegible]nace [illegible]ould exploit [illegible]requ[illegible]

Manuscript [illegible]

Three Core Works

snippets of [205, 207, 208]

Frequency Fitness

Thomas Weise, *Member, IEEE,* Mingxu Wan, Pu Wang, *Me*
Alexandre Devert, and Xin Ya

***Abstract*—Metaheuristic optimization procedures such as evolutionary algorithms are usually driven by an objective function that rates the quality of a candidate solution. However, it is not clear in practice whether an objective function adequately rewards intermediate solutions on the path to the global optimum and it may exhibit deceptiveness, epistasis, neutrality, ruggedness, and a lack of causality. In this paper, we introduce the frequency fitness H, subject to minimization, which rates how often solutions with the same objective value have been discovered so far. The ideas behind this method are that good solutions are difficult to find and that if an algorithm gets stuck at a local optimum, the frequency of the objective values of the surrounding solutions will increase over time, which will eventually allow it to leave that region again. We substitute a frequency fitness assignment process (FFA) for the objective function into several different optimization algorithms. We conduct a comprehensive set of experiments: the synthesis of algorithms with genetic programming (GP), the solution of MAX-SAT problems with genetic algorithms, classification with Memetic Genetic Programming, and numerical optimization with a (1+1) Evolution Strategy, to verify the utility of FFA. Given that they have no access to the original objective function at all, it is surprising that for some problems (e.g., the algorithm synthesis task) the FFA-based algorithm variants perform significantly better. However, this cannot be guaranteed for all tested problems. Thus, we also analyze scenarios where algorithms using FFA do not perform better or perform even worse than with the original objective functions.**

***Index Terms*—Combinatorial optimization, diversity, fitness assignment, frequency, genetic programming (GP), numerical optimization.**

I. Introduction

SINGLE-OBJ VE optim ion is rocess with the goal of findi (g all i.e., al) so tions a

Frequency Fitness Assignment: Making Optimization Algorithms Invariant Under Bijective Transformations of the Objective Function Value

Thomas Weise, *Member, IEEE*, Zhize Wu, Xinlu Li, and Yan Chen

***Abstract*—Under frequency fitness assignment (FFA), the fitness corresponding to an objective value is its encounter frequency in fitness assignment steps and is subject to minimization. FFA renders optimization processes invariant under bijective transformations of the objective function value. On TwoMax, Jump, and Trap functions of dimension s, the classical (1 + 1)-EA with standard mutation at rate 1/s can have expected runtimes exponential in s. In our experiments, a (1 + 1)-FFA, the same algorithm but using FFA, exhibits mean runtimes that seem to scale as s^2 ln s. Since Jump and Trap are bijective transformations of OneMax, it behaves identical on all three. On OneMax, LeadingOnes, and Plateau problems, it seems to be slower than the (1 + 1)-EA by a factor linear in s. The (1 + 1)-FFA performs much better than the (1 + 1)-EA on W-Model and MaxSat instances. We further verify the bijection invariance by applying the Md5 checksum computation as transformation to some of the above problems and yield the same behaviors. Finally, we show that FFA can improve the performance of a memetic algorithm for job shop scheduling.**

***Index Terms*—(1+1)-EA, evolutionary algorithm (EA), frequency fitness assignment (FFA), job shop scheduling (JSS), problems, metaheuristic, optimization.**

I. Introduction

In this article, we uncover a so-far unexplored property of FFA: it is invariant under any bijective transformation of the objective function values. This is the strongest invariance known to us and encompasses all order-preserving mappings. Other examples for bijective transformations include the negation, permutation, or even encryption of the objective values. According to [3], invariance extends performance observed on a single function to an e associ inv ance cla at is, it generalizes from gle p class ri s. Th it hop fully es e pre tic

Three Core Works

snippets of [205, 207, 208]

Frequency Fitness

Thomas Weise, *Member, IEEE,* Mingxu Wan, Pu Wang, *Me*
Alexandre Devert, and Xin Ya

***Abstract*—Metaheuristic optimization procedures such as evolutionary algorithms are usually driven by an objective function that rates the quality of a candidate solution. However, it is not clear in practice whether an objective function adequately rewards intermediate solutions on the path to the global optimum and it may exhibit deceptiveness, epistasis, neutrality, ruggedness, and a lack of causality. In this paper, we introduce the frequency fitness H, subject to minimization, which rates how often solutions with the same objective value have been discovered so far. The ideas behind this method are that good solutions are difficult to find and that if an algorithm gets stuck at a local optimum, the frequency of the objective values of the surrounding solutions will increase over time, which will eventually allow it to leave that region again. We substitute a frequency fitness assignment process (FFA) for the objective function into several different optimization algorithms. We conduct a comprehensive set of experiments: the synthesis of algorithms with genetic programming (GP), the solution of MAX-nSAT problems with genetic algorithms, classification with Memetic Genetic Programming, and numerical optimization with a (1+1) Evolution Strategy, to verify the utility of FFA. Given that they have no access to the original objective function at all, it is surprising that for some problems (e.g., the algorithm synthesis task) the FFA-based algorithm variants perform significantly better. However, this cannot be guaranteed for all tested problems. Thus, we also analyze scenarios where algorithms using FFA do not perform better or perform even worse than with the original objective functions.**

***Index Terms*—Combinatorial optimization, diversity, fitness assignment, frequency, genetic programming (GP), numerical optimization.**

I. Introduction

SINGLE-OBJ[illegible]VE optimi[illegible]ion is [illegible]rocess with the goal of findi[illegible]g[illegible] all [illegible]i.e., [illegible]al] so[illegible]tions a[illegible]

Frequency Fitness A[illegible]
Optimization Algorith[illegible]
Bijective Transfo[illegible]
Objective Fu[illegible]

Thomas Weise, *Member, IEEE,* Z[illegible]

***Abstract*—Under frequency fitness assignment (FFA), the fitness corresponding to an objective value is its encounter frequency in fitness assignment steps and is subject to minimization. FFA renders optimization processes invariant under bijective transformations of the objective function value. On TwoMax, Jump, and Trap functions of dimension s, the classical (1 + 1)-EA with standard mutation at rate 1/s can have expected runtimes exponential in s. In our experiments, a (1 + 1)-FFA, the same algorithm but using FFA, exhibits mean runtimes that seem to scale as $s^2 \ln s$. Since Jump and Trap are bijective transformations of OneMax, it behaves identical on all three. On OneMax, LeadingOnes, and Plateau problems, it seems to be slower than the (1 + 1)-EA by a factor linear in s. The (1 + 1)-FFA performs much better than the (1 + 1)-EA on W-Model and MaxSat instances. We further verify the bijection invariance by applying the Md5 checksum computation as transformation to some of the above problems and yield the same behaviors. Finally, we show that FFA can improve the performance of a memetic algorithm for job shop scheduling.**

***Index Terms*—(1+1)-EA, evolutionary algorithm (EA), fitness assignment, frequency, genetic programming (GP), Jump, job shop scheduling, memetic algorithm, Md5, TwoMax, Trap.**

Frequency Fitness Assignment: Optimization Without Bias for Good Solutions Can Be Efficient

Thomas Weise , Zhize Wu, Xinlu Li, Yan Chen, and Jörg Lässig

***Abstract*—A fitness assignment process transforms the features (such as the objective value) of a candidate solution to a scalar fitness, which then is the basis for selection. Under frequency fitness assignment (FFA), the fitness corresponding to an objective value is its encounter frequency in selection steps and is subject to minimization. FFA creates algorithms that are not biased toward better solutions and are invariant under all injective transformations of the objective function value. We investigate the impact of FFA on the performance of two theory inspired, state-of-the-art evolutionary algorithms, the Greedy (2 + 1) GA and the self-adjusting (1 + (λ, λ)) GA. FFA improves their performance significantly on some problems that are hard for them. In our experiments, one FFA-based algorithm exhibited mean runtimes that appear to be polynomial on the theory-based benchmark problems in our study, including traps, jumps, and plateaus. We propose two hybrid approaches that use both direct and FFA-based optimization and find that they perform well. All FFA-based algorithms also perform better on satisfiability problems than any of the pure algorithm variants.**

***Index Terms*—Evolutionary algorithm (EA), FFA, frequency fitness assignment (FFA), Ising problems, jump problems, linear harmonic functions, MaxSat problem, *N*-queens problem, OneMax, Plateau problems, satisfiability, Trap function, TwoMax, *W*-model benchmark.**

I. Introduction

FITNESS [illegible]'s a[illegible]mp[illegible] many evo[illegible]
[illegible]ionary [illegible]) [illegible]e fe[illegible] [3]
so[illegible] [illegible]

Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.

Discrete Benchmark Functions


- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.

Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.


Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.
- The $(1+1)$ EA can easily solve the OneMax problem, where the goal is to find a bit string of all $1s^{150}$.




Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.
- The $(1+1)$ EA can easily solve the OneMax problem, where the goal is to find a bit string of all 1s[150].
- It needs $\mathbf{\Theta}(n^n)$ on traps[61], where the optimum and the worst solution are exchanged compared to OneMax.



Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.
- The $(1+1)$ EA can easily solve the OneMax problem, where the goal is to find a bit string of all 1s[150].
- It needs $\mathbf{\Theta}(n^n)$ on traps[61], where the optimum and the worst solution are exchanged compared to OneMax, as well as on TwoMax[76,192], which has one local and one global optimum.




Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.
- The $(1+1)$ EA can easily solve the OneMax problem, where the goal is to find a bit string of all 1s[150].
- It needs $\mathbf{\Theta}(n^n)$ on traps[61], where the optimum and the worst solution are exchanged compared to OneMax, as well as on TwoMax[76,192], which has one local and one global optimum.
- The $(1+1)$ FEA solves all three problems in polynomial time!

Discrete Benchmark Functions

- Discrete optimization algorithms work on bit strings of length n as search space and use only the objective values of the solutions they sample to solve a problem.
- They are usually tested on a variety of benchmark problems.
- We plug FFA into the $(1+1)$ EA and obtain the $(1+1)$ FEA.
- The $(1+1)$ EA can easily solve the OneMax problem, where the goal is to find a bit string of all 1s[150].
- It needs $\mathbf{\Theta}(n^n)$ on traps[61], where the optimum and the worst solution are exchanged compared to OneMax, as well as on TwoMax[76,192], which has one local and one global optimum.



- The $(1+1)$ FEA solves all three problems in polynomial time as well as the Jump problem, where the $(1+1)$ EA also needs exponential runtime!

Maximum Satisfiability Problem



- FFA on the Maximum Satisfiability (MaxSAT) Problem, one of the most famous discrete optimization problems [205, 207, 208].

Maximum Satisfiability Problem

- FFA on the Maximum Satisfiability (MaxSAT) Problem, one of the most famous discrete optimization problems [205, 207, 208].

> From Table I, we can see that **the highest number of failed runs at scale $s = 250$ of *any* algorithm using FFA is lower than the lowest number of failed runs of *any* pure algorithm at $s = 50$.** From Table II, we find that no FFA-based algorithm has a higher ERT at scale $s = 250$ than its pure variant on $s = 50$. On the scales $s \leq 75$, the FFA-based algorithms have a mean runtime which is between three and four orders of magnitude smaller that the ERT of the pure algorithms.

- Snippet of page 10 of [208] (copyright IEEE).
- Several different EAs with and without FFA

Traveling Salesperson Problem

- FFA on the Traveling Salesperson Problem (TSP): [125–127].

Traveling Salesperson Problem

- FFA on the Traveling Salesperson Problem (TSP): [125–127].
- Snippet of page 12 of [125] (copyright Springer).
- $(1+1)$ EA, $(1+1)$ FEA, Simulated Annealing (SA) w/o FFA, hybrids

In this work, we explored both the EA and SA on 56 symmetric instances from the benchmark set TSPLib (Reinelt 1991, 1995). The EA is unsuitable for this problem, but SA can find the optimum on many small and mid-sized instances. We then plug FFA into both algorithms and obtain the FEA and the FSA, respectively, which both exhibit very similar performance. **The FEA solves 27 of the instances in all of its runs, which SA can only achieve for 19 instances.** Plugging FFA into either the EA or SA thus substantially improved the number of runs in which the algorithms can find the optimum, however, both FFA-based variants suffer when the number of unique objective values is high.

• • •

Both types of **hybridization** methods significantly improve the average result quality compared to both the objective-guided and FFA-based FEA variants. **The SAFEA$_A$ discovers the optimal solutions in more runs than any other algorithm setup in our study.** It also finds the optimum most often in most instances and delivers the best approximation quality on most instances, compared to the other algorithms.

Quadratic Assignment Problem



- FFA on the Quadratic Assignment Problem (QAP): [36, 188].

Quadratic Assignment Problem

- FFA on the Quadratic Assignment Problem (QAP): [36, 188].
- Snippet of page 7 of [36] (copyright SciTePress).
- RLS w/o FFA

We find that the **FFA-based** randomized local search **FRLS does not just find better solutions than the objective-guided RLS algorithm on the vast majority of the QAPLIB instances**, it also keeps improving its current best solution for the complete computational budget of 10^8 FEs that we assigned to the runs. With this budget, **it can discover the optimal solutions of over 58% of the QAPLIB instances**. Had we assigned a larger budget – (Liang et al., 2022; Liang et al., 2024; Weise et al., 2021b; Weise et al., 2023) use 10^{10} FEs – we would likely have seen even more instances solved.

We furthermore confirm the remarkable ability of FFA to discover very diverse solutions (at least from the perspective of the objective function). It is known that on the QAP, many solutions tend to have the same objective values (Tayarani-N. and Prügel-Bennett, 2015). Yet, on some of the instances, more than half of the objective values discovered by FRLS were unique.

Job Shop Scheduling Problem



- FFA on the Job Shop Scheduling Problem (JSSP) Problem: [45, 202, 207].

Job Shop Scheduling Problem

- FFA on the Job Shop Scheduling Problem (JSSP) Problem: [45, 202, 207].

> The **end result quality delivered by (1+1)-FEA is better in average on the abz*, ft*, la*, orb*, and yn4* instance sets, both in terms of *best* and *mean*.** On swv*, the average for *mean* is better for (1+1)-FEA, while (1+1)-EA has a slight lead in *best*. The (1+1)-EA performs better on the dmu* and ta* instances. Since these two sets are larger (holding 160 out of the 242 instances), the (1+1)-EA comes out ahead in the overall averages, but with no more than a 1.5% advantage.

- Snippet of page 10 of [202] (copyright ACM).

Algorithm Synthesis and Genetic Programming

- FFA for algorithm synthesis and Genetic Programming (GP): [204, 205].

Algorithm Synthesis and Genetic Programming

- FFA for algorithm synthesis and Genetic Programming (GP): [204, 205].

> Fourth, we were able to confirm with great significance that **FFA** has a tremendous positive impact on the performance of GP, as it **can increase the success rate by 40%.**

- Snippet of page 7 of [204] (copyright IEEE).

Future Works

Future Works

- Apply FFA to other discrete and combinatorial problems.

Future Works

- Apply FFA to other discrete and combinatorial problems:
    1. Where can FFA improve the solution quality?

Future Works

- Apply FFA to other discrete and combinatorial problems:
  1. Where can FFA improve the solution quality?
  2. Where can it not do that?

Future Works

- Apply FFA to other discrete and combinatorial problems:
  1. Where can FFA improve the solution quality?
  2. Where can it not do that?
  3. Why?

Future Works

- Apply FFA to other discrete and combinatorial problems:
  1. Where can FFA improve the solution quality?
  2. Where can it not do that?
  3. Why?
- Plug FFA into more optimization algorithms.

Future Works

- Apply FFA to other discrete and combinatorial problems:
  1. Where can FFA improve the solution quality?
  2. Where can it not do that?
  3. Why?
- Plug FFA into more optimization algorithms.
- Combine "traditional" and FFA-based optimization, i.e., create hybrid algorithms, to reap the best of both worlds.

Summary




Summary

- Our students and I work on the big field of optimization.




Summary




- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.

Summary



- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.
- We have a very interesting and novel technique called Frequency Fitness Assignment (FFA).

Summary



- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.
- We have a very interesting and novel technique called Frequency Fitness Assignment (FFA).
- We are figuring out where it really can give us better results.

Summary



- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.
- We have a very interesting and novel technique called Frequency Fitness Assignment (FFA).
- We are figuring out where it really can give us better results.
- But we are not picky.

Summary



- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.
- We have a very interesting and novel technique called Frequency Fitness Assignment (FFA).
- We are figuring out where it really can give us better results.
- But we are not picky. For example,
  1. on the two-dimensional bin packing problem, we found out that a simple local search can actually outperform the complex SOTA metaheuristics and FFA could not improve the performance ... so we published this surprising result and the student graduated with it[219,220].

Summary



- Our students and I work on the big field of optimization.
- We try to improve the quality of solutions that metaheuristics can deliver on discrete or combinatorial problems.
- We have a very interesting and novel technique called Frequency Fitness Assignment (FFA).
- We are figuring out where it really can give us better results.
- But we are not picky. For example,
  1. on the two-dimensional bin packing problem, we found out that a simple local search can actually outperform the complex SOTA metaheuristics and FFA could not improve the performance ... so we published this surprising result and the student graduated with it[219,220], and
  2. on the Traveling Tournament Problem (TTP), we also got surprisingly good results with RLS[213] and SA.

Advertisement

Programming with Python

We have a freely available course book on *Programming with Python* at `https://thomasweise.github.io/programmingWithPython`, with focus on practical software development using the Python ecosystem of tools[200].




Databases

We have a freely available course book on *Databases* at `https://thomasweise.github.io/databases`, with actual practical examples using a real database management system (DBMS)[196].



Metaheuristic Optimization in Python: moptipy

We offer moptipy[206], a mature open source Python package for metaheuristic optimization, which implements several algorithms, can run self-documenting experiments in parallel and in a distributed fashion, and offers statistical evaluation tools.



谢谢您们！

Thank you!

Vielen Dank!



References I

[1] Joseph Adams, Egon Balas, and Daniel Zawack. "The Shifting Bottleneck Procedure for Job Shop Scheduling". *Management Science* 34(3):391–401, Mar. 1988. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.34.3.391 (cit. on p. 193).

[2] Miguel F. Anjos. *The QAPLIB Challenge*. Edinburgh, Scotland, UK: Miguel F. Anjos @ University of Edinburgh, Nov. 19, 2023. URL: https://www.miguelanjos.com/projects/2999 (visited on 2026-09-28). The document lists the 28 instances of QAPLIB [29,31] that had not yet been solved to optimality by the time of its writing. (Cit. on p. 197).

[3] Denis Antipov and Benjamin Doerr. "Precise Runtime Analysis for Plateaus". In: *15th International Conference on Parallel Problem Solving from Nature (PPSN XV)*. Vol. 2. Sept. 8–12, 2018, Coimbra, Portugal. Ed. by Anne Auger, Carlos M. Fonseca, Nuno Lourenço, Penousal Machado, Luís Paquete, and L. Darrell Whitley. Vol. 11102 of Lecture Notes in Computer Science (LNCS). Cham, Switzerland: Springer, 2018, pp. 117–128. ISSN: 0302-9743. ISBN: 978-3-319-99258-7. doi:10.1007/978-3-319-99259-4_10 (cit. on p. 196).

[4] David Lee Applegate, Robert E. Bixby, Vašek Chvátal, and William John Cook. *The Traveling Salesman Problem: A Computational Study*. 2nd ed. Vol. 17 of Princeton Series in Applied Mathematics. Princeton, NJ, USA: Princeton University Press, 2007. ISBN: 978-0-691-12993-8. This book also discusses the Concorde TSP solver. (Cit. on pp. 16–19, 190, 199).

[5] David Lee Applegate and William John Cook. "A Computational Study of the Job-Shop Scheduling Problem". *ORSA Journal on Computing* 3(2):149–156, May 1991. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.3.2.149. The JSSP instances used were generated in Bonn in 1986. (Cit. on p. 193).

[6] Paul Gustav Heinrich Bachmann. *Die Analytische Zahlentheorie / Dargestellt von Paul Bachmann*. Vol. Zweiter Theil of Zahlentheorie: Versuch einer Gesamtdarstellung dieser Wissenschaft in ihren Haupttheilen. Leipzig, Sachsen, Germany: B. G. Teubner, 1894. ISBN: 978-1-4181-6963-3. URL: http://gallica.bnf.fr/ark:/12148/bpt6k994750 (visited on 2023-12-13) (cit. on p. 203).

[7] Thomas Bäck, David B. Fogel, and Zbigniew "Zbyszek" Michalewicz, eds. *Handbook of Evolutionary Computation*. Bristol, England, UK: IOP Publishing Ltd and Oxford, Oxfordshire, England, UK: Oxford University Press, 1997. ISBN: 978-0-7503-0392-7 (cit. on p. 191).

References II

[8] Roberto Battiti and Giampietro Tecchiolli. "Local Search with Memory: Benchmarking RTS". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 17:67–86, June 1995. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/BF01719249 (cit. on p. 198).

[9] Roberto Battiti and Giampietro Tecchiolli. "Simulated Annealing and Tabu Search in the Long Run: A Comparison on QAP Tasks". *Computers & Mathematics with Applications* 28(6):1–8, Sept. 1994. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0898-1221. doi:10.1016/0898-1221(94)00147-2 (cit. on pp. 198, 199).

[10] Roberto Battiti and Giampietro Tecchiolli. "The Reactive Tabu Search". 6(2):126–140, May 1994. doi:10.1287/ijoc.6.2.126. Applications of Reactive Tabu Search (RTS) to the 0-1 Knapsack and QAP. (Cit. on pp. 198, 199).

[11] Roberto Battiti and Giampietro Tecchiolli. "Training Neural Nets with the Reactive Tabu Search". *IEEE Transactions on Neural Networks* 6(5):1185–1200, Sept. 1995. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1045-9227. doi:10.1109/72.410361. See also "Training Neural Nets with the Reactive Tabu Search, Technical Report UTM 421, Trento, Alto Adige/Südtirol, Italy: University of Trento, 11 1993" (cit. on p. 198).

[12] James C. Bean. "Genetic Algorithms and Random Keys for Sequencing and Optimization". *ORSA Journal on Computing* 6(2):107–220, Spr. 1994. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.6.2.154. Applies the Random Keys encoding to scheduling and the QAP. See [13]. (Cit. on pp. 157, 190, 197).

[13] James C. Bean. *Genetics and Random Keys for Sequencing and Optimization*. Tech. rep. 92-43. Ann Arbor, MI, USA: University of Michigan, Department of Industrial & Operations Engineering, June 30, 1992. URL: https://www.math.wm.edu/~rrkinc/homework/RdmKeyGA.pdf (visited on 2026-10-01). See [12]. (Cit. on pp. 157, 190, 197).

[14] John Edward Beasley. "OR-Library: Distributing Test Problems by Electronic Mail". *The Journal of the Operational Research Society (JORS)* 41:1069–1072, Nov. 1990. London, England, UK: Taylor and Francis Ltd. and London, England, UK: Springer Nature Limited. ISSN: 0160-5682. doi:10.1057/jors.1990.166. See the website [15] (cit. on pp. 157, 193, 196).

[15] John Edward Beasley. *Welcome to OR-Library*. Uxbridge, Middlesex, England, UK: Brunel University of London, June 1990–Feb. 2018. URL: https://people.brunel.ac.uk/~mastjjb/jeb/info.html (visited on 2026-09-30). See the article [14]. Contains instances of the JSSP, 1D- and 2D-Packing, Knapsack, periodic TSPs, amongst others. (Cit. on pp. 157, 193, 196).

References III

[16] Andreas Beham, Michael Affenzeller, and Erik Pitzer. "Metaheuristic Algorithms for the Quadratic Assignment Problem: Performance and Comparison". In: *Innovative Technologies in Management and Science*. Ed. by Ryszard Klempous and Jan Nikodem. Vol. 10 of Topics in Intelligent Engineering and Informatics (TIEI). Cham, Switzerland: Springer, 2015, pp. 171–190. ISSN: 2193-9411. ISBN: 978-3-319-12651-7. doi:10.1007/978-3-319-12652-4_10. Algorithms like SLS/iterated local search (ILS), SA, Tabu Search (TS), Variable Neighborhood Search (VNS), EAs, Memetic Algorithms (MAs) are compared and, with the exception of SA and EA, all perform best on some instance groups of QAPLIB. (Cit. on p. 197).

[17] Bengt-Erik Bengtsson. "Packing Rectangular Pieces— A Heuristic Approach". *The Computer Journal* 25(3):353–357, Aug. 1982. Oxford, Oxfordshire, England, UK: Oxford University Press. ISSN: 0010-4620. doi:10.1093/comjnl/25.3.353 (cit. on p. 189).

[18] Tim Berners-Lee. *Re: Qualifiers on Hypertext links...* Geneva, Switzerland: World Wide Web project, European Organization for Nuclear Research (CERN) and Newsgroups: alt.hypertext, Aug. 6, 1991. URL: https://www.w3.org/People/Berners-Lee/1991/08/art-6484.txt (visited on 2025-02-05) (cit. on p. 201).

[19] Tim Berners-Lee, Larry Masinter, and Mark P. McCahill. *Uniform Resource Locators (URL)*. Request for Comments (RFC) 1738. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Dec. 1994. URL: https://www.ietf.org/rfc/rfc1738.txt (visited on 2025-02-05) (cit. on p. 200).

[20] Muhammed Beyaz, Tansel Dökeroğlu, and Ahmet Cosar. "Robust Hyper-Heuristic Algorithms for the Offline Oriented/Non-Oriented 2D Bin Packing Problems". *Applied Soft Computing (ASOC)* 36:236–245, Nov. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/j.asoc.2015.06.063 (cit. on p. 189).

[21] Christian Bierwirth. "A Generalized Permutation Approach to Job Shop Scheduling with Genetic Algorithms". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 17(2–3):87–92, June 1995. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/BF01719250. URL: https://www.researchgate.net/publication/240263036 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP, see also [22]. (Cit. on pp. 159, 168, 193, 202).

References IV

[22] Christian Bierwirth, Dirk C. Mattfeld, and Herbert Kopfer. "On Permutation Representations for Scheduling Problems". In: *4th International Conference on Parallel Problem Solving from Nature (PPSN IV)*. Sept. 22–24, 1996, Berlin, Germany. Ed. by Hans-Michael Voigt, Werner Ebeling, Ingo Rechenberg, and Hans-Paul Schwefel. Vol. 1141 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 1996, pp. 310–318. ISSN: 0302-9743. ISBN: 978-3-540-61723-5. doi:10.1007/3-540-61723-X_995. URL: https://www.researchgate.net/publication/2753293 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP, see also [21]. (Cit. on pp. 158, 168, 193, 202).

[23] Jacek Błażewicz, Wolfgang Domschke, and Erwin Pesch. "The Job Shop Scheduling Problem: Conventional and New Solution Techniques". *European Journal of Operational Research* 93(1):1–33, Aug. 1996. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(95)00362-2 (cit. on p. 193).

[24] Joshua Bloch. *Effective Java*. Reading, MA, USA: Addison-Wesley Professional, May 2008. ISBN: 978-0-321-35668-0 (cit. on p. 193).

[25] Christian Blum and Verena Schmid. "Solving the 2D Bin Packing Problem by Means of a Hybrid Evolutionary Algorithm". In: *International Conference on Computational Science (ICCS'2013)*. June 5–7, 2013, Barcelona, Spain. Ed. by Vassil Alexandrov, Michael Lees, Valeria V. Krzhizhanovskaya, Jack J. Dongarra, and Peter M. A. Sloot. Vol. 18 of Procedia Computer Science. Amsterdam, The Netherlands: Elsevier B.V., 2013, pp. 899–908. ISSN: 1877-0509. doi:10.1016/j.procs.2013.05.255. An EA for the oriented two-dimensional Bin Packing Problem with free cuts (2BP|O|F) using the heuristic by Wong and Lee [212]. (Cit. on p. 189).

[26] Borko Bošković and Janez Brest. "Computational Search of Long Skew-Symmetric Binary Sequences with High Merit Factors". *MENDEL – Soft Computing Journal* 28(2):17–24, Dec. 2022. Brno, Czech Republic: Brno University of Technology (Vysoké učení technické v Brně). ISSN: 1803-3814. doi:10.13164/mendel.2022.2.017 (cit. on p. 194).

[27] Borko Bošković, Franc Brglez, and Janez Brest. "Low-Autocorrelation Binary Sequences: On Improved Merit Factors and Runtime Predictions to Achieve Them". *Applied Soft Computing (ASOC)* 56:262–285, July 2017. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/J.ASOC.2017.02.024 (cit. on p. 194).

[28] Janez Brest and Borko Bošković. "A Heuristic Algorithm for a Low Autocorrelation Binary Sequence Problem with Odd Length and High Merit Factor". *IEEE Access* 6:4127–4134, Jan. 2018. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 2169-3536. doi:10.1109/ACCESS.2018.2789916 (cit. on p. 194).

References V

[29] Rainer E. Burkard, Eranda Çela, Stefan E. Karisch, Franz Rendl, Miguel F. Anjos, and Peter M. Hahn. *QAPLIB – A Quadratic Assignment Problem Library – Problem Instances and Solutions*. Edinburgh, Scotland, UK: University of Edinburgh, Apr. 20, 2012–Mar. 31, 2022. doi:10.7488/ds/3428. This is the 2012 status of the QAPLIB dataset from [31] (cit. on pp. 156, 160, 197).

[30] Rainer E. Burkard, Eranda Çela, Panos Miltiades Pardalos, and Leonidas S. Pitsoulis. "The Quadratic Assignment Problem". In: *Handbook of Combinatorial Optimization*. Ed. by Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham. 1st ed. Boston, MA, USA: Springer, 1998, pp. 1713–1809. ISBN: 978-1-4613-7987-4. doi:10.1007/978-1-4613-0303-9_27 (cit. on p. 197).

[31] Rainer E. Burkard, Stefan E. Karisch, and Franz Rendl. "QAPLIB – A Quadratic Assignment Problem Library". *Journal of Global Optimization* 10(4):391–403, June 1997. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1023/A:1008293323270. This article introduces QAPLIB, a set of benchmark problems for the QAP, now hosted at [29]. (Cit. on pp. 156, 160, 197).

[32] Rainer E. Burkard and Josef Offermann. "Entwurf von Schreibmaschinentastaturen mittels quadratischer Zuordnungsprobleme". *Zeitschrift für Operations Research (ZOR). now Mathematical Methods of Operations Research (MMOR)* 21:B121–B132, Aug. 1977. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag; now London, England, UK: Springer Nature Limited. ISSN: 0340-9422. doi:10.1007/BF01918175. Keyboard layout modeled as QAPs. (Cit. on p. 197).

[33] Eduardo Carvalho Pinto and Carola Doerr. *Towards a More Practice-Aware Runtime Analysis of Evolutionary Algorithms*. arXiv.org: Computing Research Repository (CoRR) abs/1812.00493. Ithaca, NY, USA: Cornell Universiy Library, Dec. 3, 2018. doi:10.48550/arXiv.1812.00493. URL: https://arxiv.org/abs/1812.00493 (visited on 2025-08-08). arXiv:1812.00493v1 [cs.NE] 3 Dec 2018 (cit. on pp. 38–48, 72–82, 188).

[34] Vladimír Černý. "Thermodynamical Approach to the Traveling Salesman Problem: An Efficient Simulation Algorithm". *Journal of Optimization Theory and Applications* 45(1):41–51, Jan. 1985. New York, NY, USA: Springer Science+Business Media, LLC. ISSN: 0022-3239. doi:10.1007/BF00940812 (cit. on p. 198).

References VI

[35] Bo Chen, Chris N. Potts, and Gerhard J. Woeginger. "A Review of Machine Scheduling: Complexity, Algorithms and Approximability". In: *Handbook of Combinatorial Optimization*. Ed. by Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham. 1st ed. Boston, MA, USA: Springer, 1998, pp. 1493–1641. ISBN: 978-1-4613-7987-4. doi:10.1007/978-1-4613-0303-9_25. See also pages 21–169 in volume 3/3 by Norwell, MA, USA: Kluwer Academic Publishers. Discusses, amongst others, that the JSSP is $\mathcal{NP}$-hard. (Cit. on pp. 193, 203).

[36] Jiayang Chen (陈嘉阳), Zhize Wu (吴志泽), Sarah Louise Thomson, and Thomas Weise (汤卫思). "Frequency Fitness Assignment: Optimization Without Bias for Good Solution Outperforms Randomized Local Search on the Quadratic Assignment Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 27–37. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888600003837 (cit. on pp. 130, 131, 191, 195, 197).

[37] T. C. Edwin Cheng, Bo Peng, and Zhipeng Lü. "A Hybrid Evolutionary Algorithm to Solve the Job Shop Scheduling Problem". *Annals of Operations Research* 242(2):223–237, July 2016. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/s10479-013-1332-5. A MA utlizing TS (cit. on p. 194).

[38] Philippe Chrétienne, Edward G. Coffman, Jan Karel Lenstra, and Zhen Liu, eds. *Scheduling Theory and Its Applications*. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd., Sept. 1995. ISBN: 978-0-471-94059-3 (cit. on p. 193).

[39] Nestor M. Cid-Garcia and Yasmin A. Rios-Solis. "Positions and Covering: A Two-Stage Methodology to Obtain Optimal Solutions for the 2D-Bin Packing Problem". *PLoS ONE* 15(4):e0229358, Apr. 2020. San Francisco, CA, USA: Public Library of Science (PLOS). ISSN: 1932-6203. doi:10.1371/journal.pone.0229358. An exact method for the two-dimensional Bin Packing Problem with free cuts and rotation (2BP|R|F) and the 2BP|O|F. (Cit. on p. 189).

[40] Stephen Arthur Cook. "The Complexity of Theorem-Proving Procedures". In: *Third Annual ACM Symposium on Theory of Computing (STOC'1971)*. May 3–5, 1971, Shaker Heights, OH, USA. Ed. by Michael A. Harrison, Ranan B. Banerji, and Jeffrey D. Ullman. New York, NY, USA: Association for Computing Machinery (ACM), 1971, pp. 151–158. ISBN: 978-1-4503-7464-4. doi:10.1145/800157.805047 (cit. on pp. 195, 203).

References VII

[41] William John Cook. *Concorde TSP Solver*. Waterloo, ON, Canada: University of Waterloo, 1997. URL: https://math.uwaterloo.ca/tsp/concorde (visited on 2026-09-26) (cit. on p. 190).

[42] William John Cook. *In Pursuit of the Traveling Salesman: Mathematics at the Limits of Computation*. Princeton, NJ, USA: Princeton University Press, 2012–Nov. 9, 2014. ISBN: 978-0-691-16352-9 (cit. on pp. 190, 194).

[43] William John Cook. *World TSP*. Waterloo, ON, Canada: University of Waterloo, 2013–Oct. 25, 2025. URL: http://www.math.uwaterloo.ca/tsp/world (visited on 2026-01-03) (cit. on pp. 194, 199).

[44] Cemre Çubukçuoğlu, Pirouz Nourian, M. Fatih Tasgetiren, I. Sevil Sariyildiz, and Shervin Azadi. "Hospital Layout Design Renovation as a Quadratic Assignment Problem with Geodesic Distances". *Journal of Building Engineering* 44:102952, Dec. 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 2352-7102. doi:10.1016/j.jobe.2021.102952 (cit. on p. 197).

[45] Ege de Bruin, Sarah Louise Thomson, and Daan van den Berg. "Frequency Fitness Assignment on JSSP: A Critical Review". In: *26th European Conference on Applications of Evolutionary Computation (EvoApplications'2023), Held as Part of EvoStar'2023*. Apr. 12–14, 2023, Brno, Czech Republic. Ed. by João Correia, Stephen Smith, and Raneem Qaddoura. Vol. 13989 of Lecture Notes in Computer Science (LNCS). Cham, Switzerland: Springer, 2023, pp. 351–363. ISSN: 0302-9743. ISBN: 978-3-031-30228-2. doi:10.1007/978-3-031-30229-9_23. Independent reproduction of [202] (cit. on pp. 132, 133).

[46] *Definition of Operations Research*. University of Western Ontario, London, ON, Canada: International Federation of Operational Research Societies (IFORS), 2020. URL: https://www.ifors.org/what-is-or (visited on 2026-01-01) (cit. on p. 196).

[47] Paul Deitel, Harvey Deitel, and Abbey Deitel. *Internet & World Wide Web: How to Program*. 5th ed. Hoboken, NJ, USA: Pearson Education, Inc., Nov. 2011. ISBN: 978-0-13-299045-5 (cit. on p. 201).

[48] Maxence Delorme, Manuel Iori, and Silvano Martello. "Bin Packing and Cutting Stock Problems: Mathematical Models and Exact Algorithms". *European Journal of Operational Research* 255(1):1–20, Nov. 2016. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2016.04.030 (cit. on p. 190).

[49] Ebru Demirkol, Sanjay V. Mehta, and Reha Uzsoy. "Benchmarks for Shop Scheduling Problems". *European Journal of Operational Research* 109(1):137–141, Aug. 1998. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(97)00019-2 (cit. on p. 193).

References VIII

[50] Miroslav Dimitrov. *New Classes of Binary Sequences with High Merit Factor*. arXiv.org: Computing Research Repository (CoRR). Ithaca, NY, USA: Cornell Universiy Library, June 24, 2022. doi:10.48550/arXiv.2206.12070. URL: https://arxiv.org/pdf/2206.12070 (visited on 2026-09-21). arXiv:2206.12070v1 [cs.IT] 24 Jun 2022 (cit. on p. 194).

[51] Miroslav Dimitrov, Tsonka Baitcheva, and Nikolay Nikolov. "Efficient Generation of Low Autocorrelation Binary Sequences". *IEEE Signal Processing Letters* 27:341–345, 2020. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1558-2361. doi:10.1109/LSP.2020.2972127 (cit. on p. 194).

[52] Slobodan Dmitrović. *Modern C for Absolute Beginners: A Friendly Introduction to the C Programming Language*. New York, NY, USA: Apress Media, LLC, Mar. 2024. ISBN: 979-8-8688-0224-9 (cit. on p. 190).

[53] Benjamin Doerr, Carola Doerr, and Franziska Ebel. "From Black-Box Complexity to Designing New Genetic Algorithms". *Theoretical Computer Science* 567:87–104, Feb. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/J.TCS.2014.11.028 (cit. on p. 196).

[54] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". In: *21st Genetic and Evolutionary Computation Conference Companion (GECCO'2019)*. July 13–17, 2019, Prague, Czech Republic. Ed. by Manuel López-Ibáñez, Anne Auger, and Thomas Stützle. New York, NY, USA: Association for Computing Machinery (ACM), 2019, pp. 1798–1806. ISBN: 978-1-4503-6748-6. doi:10.1145/3319619.3326810. See also [55,56] (cit. on p. 163).

[55] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". *Applied Soft Computing (ASOC)* 88:106027, Mar. 2020. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 1568-4946. doi:10.1016/j.asoc.2019.106027. See also [54,56] (cit. on pp. 163, 188, 192, 193, 195).

[56] Carola Doerr, Furong Ye, Naama Horesh, Hao Wang, and Ofer M. ShirThomas Bäck. "Benchmarking Discrete Optimization Heuristics with IOHprofiler". (abs/1912.09237), Jan. 31, 2021. doi:10.48550/arXiv.1912.09237. URL: https://arxiv.org/abs/1912.09237 (visited on 2024-06-27). arXiv:1912.09237v2 [cs.NE] 31 Jan 2021, see also [54,55] (cit. on p. 163).

[57] Marco Dorigo, Mauro Birattari, and Thomas Stützle. "Ant Colony Optimization". *IEEE Computational Intelligence Magazine (CIM)* 1(4):28–39, Nov. 2006. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1556-603X. doi:10.1109/MCI.2006.329691. URL: https://www.researchgate.net/publication/308953674 (visited on 2025-07-25) (cit. on p. 189).

References IX

[58] Marco Dorigo, Vittorio Maniezzo, and Alberto Colorni. "Ant System: Optimization by a Colony of Cooperating Agents". *IEEE Transactions on Systems, Man, and Cybernetics – Part B: Cybernetics* 26(1):29–41, Feb. 1996. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1083-4419. doi:10.1109/3477.484436. URL: https://www.researchgate.net/publication/5589170 (visited on 2025-07-26) (cit. on p. 189).

[59] Marco Dorigo and Thomas Stützle. *Ant Colony Optimization*. Cambridge, MA, USA: MIT Press, 2004. ISBN: 978-0-262-04219-2 (cit. on p. 189).

[60] Johann Dréo, Alain Pétrowski, Patrick Siarry, and Éric D. Taillard. *Metaheuristics for Hard Optimization – Methods and Case Studies*. Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2006. ISBN: 978-3-540-23022-9. doi:10.1007/3-540-30966-7. Discusses SA, TS, EAs, and Ant Colony Optimization (ACO). (Cit. on p. 197).

[61] Stefan Droste, Thomas Jansen, and Ingo Wegener. "On the Analysis of the $(1 + 1)$ Evolutionary Algorithm". *Theoretical Computer Science* 276(1-2):51–81, Apr. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/S0304-3975(01)00182-7 (cit. on pp. 38–48, 72–82, 118–125, 188, 193, 194, 198).

[62] Stefan Droste, Thomas Jansen, and Ingo Wegener. "Upper and Lower Bounds for Randomized Search Heuristics in Black-Box Optimization". *Theoretical Computer Science* 39(4):525–544, July 2006. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1007/S00224-004-1177-Z (cit. on p. 196).

[63] Harald Dyckhoff and Ute Finke. *Cutting and Packing in Production and Distribution: A Typology and Bibliography*. Contributions to Management Science. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag, 1992. ISSN: 1431-1941. ISBN: 978-3-642-63487-1. doi:10.1007/978-3-642-58165-6 (cit. on p. 190).

[64] Kelly Easton, George L. Nemhauser, and Michael A. Trick. "The Traveling Tournament Problem Description and Benchmarks". In: *7th International Conference on Principles and Practice of Constraint Programming (CP'01)*. Nov. 26–Dec. 1, 2001, Paphos, Cyprus. Ed. by Toby Walsh. Vol. 2239 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2001, pp. 580–584. ISSN: 0302-9743. ISBN: 978-3-540-42863-3. doi:10.1007/3-540-45578-7_43 (cit. on p. 200).

[65] Alwalid N. Elshafei. "Hospital Layout as a Quadratic Assignment Problem". *The Journal of the Operational Research Society (JORS)* 28(1):167–179, Apr. 1977. London, England, UK: Taylor and Francis Ltd. and London, England, UK: Springer Nature Limited. ISSN: 0160-5682. doi:10.1057/jors.1977.29 (cit. on p. 197).

References X

[66] Bernhard Eschermann and Hans-Joachim Wunderlich. "Optimized Synthesis of Self-Testable Finite State Machines". In: *20th International Symposium Fault-Tolerant Computing (FTCS'1990): Digest of Papers*. June 26–28, 1990, Newcastle Upon Tyne, England, UK. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1990. ISBN: 978-0-8186-2051-5. doi:10.1109/FTCS.1990.89393 (cit. on p. 197).

[67] Thomas A. Feo and Mauricio G. C. Resende. "Greedy Randomized Adaptive Search Procedures". *Journal of Global Optimization* 6(2):109–133, Mar. 1995. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1007/BF01096763. Introduces Greedy Randomized Adaptive Search Procedures (GRASPs) and applies them to the set covering problem, among others, and lists many problem domains. (Cit. on p. 191).

[68] Luca Ferrari and Enrico Pirozzi. *Learn PostgreSQL*. 2nd ed. Birmingham, England, UK: Packt Publishing Ltd, Oct. 2023. ISBN: 978-1-83763-564-1 (cit. on p. 196).

[69] Paola Festa and Mauricio G. C. Resende. "An Annotated Bibliography of GRASP—Part I: Algorithms". *International Transactions on Operational Research (ITOR)* 16(1):1–24, Jan. 2009. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/j.1475-3995.2009.00663.x. See also [70] (cit. on pp. 165, 191).

[70] Paola Festa and Mauricio G. C. Resende. "An Annotated Bibliography of GRASP—Part II: Applications". *International Transactions on Operational Research (ITOR)* 16(2):131–172, Mar. 2009. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/j.1475-3995.2009.00664.x. See also [69] (cit. on pp. 165, 191).

[71] Simon Fischer. "A Polynomial Upper Bound for a Mutation-Based Algorithm on the Two-Dimensional Ising Model". In: *6th Genetic and Evolutionary Computation Conference (GECCO'2004), Part I*. June 26–30, 2004, Seattle, WA, USA. Ed. by Kalyanmoy Deb, Riccardo Poli, Wolfgang Banzhaf, Hans-Georg Beyer, Edmund K. Burke, Paul J. Darwen, Dipankar Dasgupta, Dario Floreano, James A. Foster, Mark Harman, Owen Holland, Pier Luca Lanzi, Lee Spector, Andrea Tettamanzi, Dirk Thierens, and Andrew M. Tyrrell. Vol. 3102 of Lecture Notes in Computer Science (LNCS). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2004, pp. 1100–1112. ISSN: 0302-9743. ISBN: 978-3-540-22344-3. doi:10.1007/978-3-540-24854-5_108 (cit. on pp. 192, 193).

References XI

[72] Simon Fischer and Ingo Wegener. "The One-Dimensional Ising Model: Mutation versus Recombination". *Theoretical Computer Science* 344(2-3):208–225, Nov. 2005. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0304-3975. doi:10.1016/J.TCS.2005.04.002 (cit. on p. 192).

[73] Henry Fisher and Gerald L. Thompson. "Probabilistic Learning Combinations of Local Job-Shop Scheduling Rules". In: *Industrial Scheduling*. Ed. by John F. Muth and Gerald L. Thompson. Englewood Cliffs, NJ, USA: Prentice-Hall, 1963. Chap. 3.2, pp. 225–251 (cit. on p. 193).

[74] Charles Fleurent and Jacques A. Ferland. "Genetic Hybrids for the Quadratic Assignment Problem". In: *Quadratic Assignment and Related Problems, Proceedings of a DIMACS Workshop*. May 20–21, 1993, New Brunswick, NJ, USA: Rutgers University. Ed. by Panos Miltiades Pardalos and Henry Wolkowicz. Providence, RI, USA: American Mathematical Society (AMS), 1994, pp. 173–187. ISBN: 978-0-8218-6607-8. A MA using the TS from [184] as local search performs well. (Cit. on pp. 194, 197).

[75] Tobias Friedrich, Pietro Simone Oliveto, Dirk Sudholt, and Carsten Witt. "Analysis of Diversity-Preserving Mechanisms for Global Exploration". *Evolutionary Computation* 17(4):455–476, Win. 2009. Cambridge, MA, USA: MIT Press. ISSN: 1063-6560. doi:10.1162/evco.2009.17.4.17401 (cit. on p. 200).

[76] Tobias Friedrich, Francesco Quinzan, and Markus Wagner. "Escaping Large Deceptive Basins of Attraction with Heavy-Tailed Mutation Operators". In: *20th Genetic and Evolutionary Computation Conference (GECCO'2018)*. July 15–19, 2018, Kyōto, Kyōto-fu, Japan. Ed. by Hernán E. Aguirre and Keiki Takadama. New York, NY, USA: Association for Computing Machinery (ACM), 2018, pp. 293–300. ISBN: 978-1-4503-5618-3. doi:10.1145/3205455.3205515 (cit. on pp. 118–125, 193, 200).

[77] José E. Gallardo, Carlos Cotta, and Antonio J. Fernández. "A Memetic Algorithm for the Low Autocorrelation Binary Sequence Problem". In: *9th Genetic and Evolutionary Computation Conference (GECCO'2007)*. July 7–11, 2007, London, England, UK. Ed. by Hod Lipson. New York, NY, USA: Association for Computing Machinery (ACM), 2007, pp. 1226–1233. ISBN: 978-1-59593-697-4. doi:10.1145/1276958.1277195 (cit. on p. 194).

[78] Michael R. Garey and David Stifler Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. New York, NY, USA: W. H. Freeman and Company, 1979. ISBN: 978-0-7167-1045-5 (cit. on p. 199).

References XII

[79] Mitsuo Gen, Yasuhiro Tsujimura, and Erika Kubota. "Solving Job-Shop Scheduling Problems by Genetic Algorithm". In: *Humans, Information and Technology: Proceedings of the 1994 IEEE International Conference on Systems, Man and Cybernetics (SMC'1994)*. Vol. 2. Oct. 2–5, 1994, San Antonio, TX, USA. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1994, pp. 1577–1582. ISBN: 978-0-7803-2129-8. doi:10.1109/ICSMC.1994.400072. Proposes a permutations-with-repetitions based encoding for the JSSP. (Cit. on pp. 168, 193, 202).

[80] Fred Glover. "Tabu Search – Part I". *ORSA Journal on Computing* 1(3):190–206, Sum. 1989. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.1.3.190 (cit. on p. 199).

[81] Fred Glover. "Tabu Search – Part II". *ORSA Journal on Computing* 2(1):4–32, Win. 1990. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.2.1.4 (cit. on p. 199).

[82] Fred Glover and Gary A. Kochenberger, eds. *Handbook of Metaheuristics*. Vol. 57 of International Series in Operations Research & Management Science (ISOR). Cham, Switzerland: Springer, 2003. ISSN: 0884-8289. ISBN: 978-0-306-48056-0. doi:10.1007/b101874 (cit. on p. 195).

[83] Fred Glover, Éric D. Taillard, and Dominique de Werra. "A User's Guide to Tabu Search". *Annals of Operations Research* 41(1):3–28, Mar. 1993. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/BF02078647. Special issue on TS. (Cit. on p. 199).

[84] José Fernando Gonçalves and Mauricio G. C. Resende. "A Biased Random Key Genetic Algorithm for two-dimensional Bin Packing Problem (2BP) and 3D Bin Packing Problems". *International Journal of Production Economics (IJPE)* 145(2):500–510, Oct. 2013. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0925-5273. doi:10.1016/j.ijpe.2013.04.019. Applies the Biased Random Key Genetic Algorithm (BRKGA) to the 2BP|R|F and 2BP|O|F as well as 3D packing. Continuous vectors are translated to permutations and orientation data which is then the input of a placement heuristic. (Cit. on pp. 189, 190).

References XIII

[85] José Fernando Gonçalves and Mauricio G. C. Resende. "An Extended Akers Graphical Method with a Biased Random-Key Genetic Algorithm for Job-Shop Scheduling". *International Transactions on Operational Research (ITOR)* 21(2):215–246, Mar. 2014. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0969-6016. doi:10.1111/itor.12044. URL: http://mauricio.resende.info/doc/brkga-jss2011.pdf (visited on 2026-09-30). The BRKGA basically is a MA using a continuous encoding of permutations that are decoded to schedules using the method from [21,22,79,174] and then refined via a TS. (Cit. on pp. 190, 193).

[86] José Fernando Gonçalves and Mauricio G. C. Resende. "Biased Random-Key Genetic Algorithms for Combinatorial Optimization". *Journal of Heuristics* 17:487–525, Oct. 2010. London, England, UK: Springer Nature Limited. ISSN: 1381-1231. doi:10.1007/s10732-010-9143-1 (cit. on p. 190).

[87] Michael T. Goodrich. *A Gentle Introduction to NP-Completeness*. Irvine, CA, USA: University of California, Irvine, Apr. 2022. URL: https://ics.uci.edu/~goodrich/teach/cs165/notes/NPComplete.pdf (visited on 2025-08-01) (cit. on p. 203).

[88] Ronald Lewis Graham, Eugene Leighton Lawler, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. "Optimization and Approximation in Deterministic Sequencing and Scheduling: A Survey". Annals of Discrete Mathematics (5):287–326. Ed. by Peter Ladislaw Hammer, Ellis Lane Johnson, and Bernhard H. Korte, 1979. ISSN: 0167-5060. doi:10.1016/S0167-5060(08)70356-X. An early review on JSSPs and FSSPs. (Cit. on pp. 191, 193).

[89] Martin Grötschel, Michael Jünger, and Gerhard Reinelt. "Optimal Control of Plotting and Drilling Machines: A Case Study". *Zeitschrift für Operations Research (ZOR). now Mathematical Methods of Operations Research (MMOR)* 35(1):61–84, Jan. 1991. Heidelberg, Baden-Württemberg, Germany: Physica-Verlag; now London, England, UK: Springer Nature Limited. ISSN: 0340-9422. doi:10.1007/BF01415960. This paper tackles circuit board plotting and drilling problems by modelling (parts of) them as symmetric Traveling Salesperson Problems (STSPs). (Cit. on p. 199).

[90] Gregory Z. Gutin and Abraham P. Punnen, eds. *The Traveling Salesman Problem and its Variations*. Vol. 12 of Combinatorial Optimization (COOP). New York, NY, USA: Springer New York, May 2002. ISSN: 1388-3011. doi:10.1007/b101971 (cit. on pp. 16–19, 199).

References XIV

[91] Pierre Hansen, Nenad Mladenović, and José Andrés Moreno Pérez. "Variable Neighbourhood Search: Methods and Applications. Invited Survey". *4OR* 6(4):319–360, Dec. 2008. ISSN: 1619-4500. doi:10.1007/s10288-008-0089-1. URL: https://www.researchgate.net/publication/225155945 (visited on 2026-10-02) (cit. on p. 201).

[92] Keld Helsgaun. "General k-opt Submoves for the Lin–Kernighan TSP Heuristic". *Mathematical Programming Computation* 1(2-3):119–163, July 2009. London, England, UK: Springer Nature Limited. ISSN: 1867-2949. doi:10.1007/s12532-009-0004-6. URL: https://www2.seas.gwu.edu/~simhaweb/champalg/tsp/papers/Helsgaun2.pdf (visited on 2026-09-26) (cit. on p. 194).

[93] Keld Helsgaun. "An Effective Implementation of the Lin-Kernighan Traveling Salesman Heuristic". 126(1):106–130, Oct. 2000. doi:10.1016/S0377-2217(99)00284-2. URL: http://akira.ruc.dk/~keld/research/LKH/LKH-2.0/DOC/LKH_REPORT.pdf (visited on 2026-09-26) (cit. on p. 194).

[94] André Henning. "Praktische Job-Shop Scheduling-Probleme". PhD thesis. Jena, Thüringen, Germany: Friedrich-Schiller-Universität Jena, Aug. 2002. URL: http://www.db-thueringen.de/servlets/DocumentServlet?id=873 (visited on 2026-09-30). Alternate url: https://nbn-resolving.org/urn:nbn:de:gbv:27-20060809-115700-4. Applies MA-like algorithms to the JSSP. (Cit. on pp. 193, 194).

[95] Holger H. Hoos and Thomas Stützle. *Stochastic Local Search: Foundations & Applications*. The Morgan Kaufmann Series in Artificial Intelligence. Amsterdam, The Netherlands: Elsevier B.V., 2005. ISBN: 978-1-55860-872-6. doi:10.1016/B978-1-55860-872-6.X5016-1 (cit. on pp. 195, 198).

[96] Holger H. Hoos and Thomas Stützle. *SATLIB – The Satisfiability Library*. 1.4.4. Vancouver, BC, Canada: The University of British Columbia (UBC), May 11, 2001. URL: https://www.cs.ubc.ca/~hoos/SATLIB/index-ubc.html (visited on 2026-09-20). See paper [97] (cit. on pp. 169, 198).

[97] Holger H. Hoos and Thomas Stützle. "SATLIB: An Online Resource for Research on SAT". In: *SAT2000 – Highlights of Satisfiability Research in the Year 2000*. Ed. by Ian Philip Gent, Toby Walsh, and Hans van Maaren. Vol. 63 of Frontiers in Artificial Intelligence and Applications. Amsterdam, The Netherlands: IOS Press BV, Jan. 2000, pp. 283–292. ISSN: 0922-6389. ISBN: 978-1-58603-061-2. See the website [96] (cit. on pp. 169, 198).

[98] John Hunt. *A Beginners Guide to Python 3 Programming*. 2nd ed. Undergraduate Topics in Computer Science (UTICS). Cham, Switzerland: Springer, 2023. ISSN: 1863-7310. ISBN: 978-3-031-35121-1. doi:10.1007/978-3-031-35122-8 (cit. on p. 196).

References XV

[99] *Information Technology – Universal Coded Character Set (UCS)*. International Standard ISO/IEC 10646:2020. Geneva, Switzerland: International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC), Dec. 2020 (cit. on p. 186).

[100] Manuel Iori, Vinícius Loti de Lima, Silvano Martello, Flávio K. Miyazaw, and Michele Monaci. "Exact Solution Techniques for Two-Dimensional Cutting and Packing". *European Journal of Operational Research* 289(2):399–415, Mar. 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2020.06.050. See also arXiv:2004.12619v1 [math.OC] 27 Apr 2020 at doi:10.1016/j.ejor.2020.06.050. (Cit. on p. 189).

[101] Christoph Jabs, Dieter Vandesande, Jeremias Berg, Johannes Fichte, George Katsirelos, Ruben Martins, André Schidler, and Dominik Schreiber. *MaxSAT Evaluation: Complete Benchmark Collection*. 2026th ed. Geneva, Switzerland: zenodo (hosted by European Organization for Nuclear Research (CERN)), July 9, 2026. doi:10.5281/zenodo.21283148. All versions of this dataset can be reached directly via doi:10.5281/zenodo.21283147. See also https://github.com/maxsat-evaluations/data and https://maxsat-evaluations.github.io. (Cit. on p. 195).

[102] Dean Jacobs, Jan Prins, Peter Siegel, and Kenneth Wilson. "Monte Carlo Techniques in Code Optimization". In: *15th Annual Workshop on Microprogramming (MICRO 15)*. Oct. 5–7, 1982. Ed. by Joseph Allen Fisher, William J. Tracz, and Bill Hopkins. Palo Alto, CA, USA: Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE) and New York, NY, USA: Association for Computing Machinery (ACM), Oct. 1982, pp. 143–148. doi:10.5555/800036.800944. See [103] (cit. on p. 170).

[103] Dean Jacobs, Jan Prins, Peter Siegel, and Kenneth Wilson. "Monte Carlo Techniques in Code Optimization". *ACM SIGMICRO Newsletter* 13(4):143–148, Dec. 1982. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 1050-916X. doi:10.1145/1014194.800944. See [102] (cit. on pp. 170, 198).

[104] Stefan Jakobs. "On Genetic Algorithms for the Packing of Polygons". *European Journal of Operational Research* 88(1):165–181, Jan. 1996. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(94)00166-9 (cit. on p. 192).

[105] Wassim Jaziri, ed. *Tabu Search*. London, England, UK: IntechOpen Limited, Aug. 1, 2008. ISBN: 978-3-902613-34-9. doi:10.5772/65. URL: https://www.intechopen.com/books/6114 (visited on 2026-09-30) (cit. on p. 199).

References XVI

[106] David Stifler Johnson, Gregory Z. Gutin, Lyle Andrew McGeoch, Anders Yeo, Weixiong Zhang, and Alexei Zverovitch. *Experimental Analysis of Heuristics for the ATSP*. Ed. by Gregory Z. Gutin and Abraham P. Punnen. New York, NY, USA, May 2002. doi:10.1007/0-306-48213-4_10. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP/papers/atspchap.pdf (visited on 2026-09-25) (cit. on p. 199).

[107] David Stifler Johnson and Lyle Andrew McGeoch. *Experimental Analysis of Heuristics for the STSP*. Ed. by Gregory Z. Gutin and Abraham P. Punnen. New York, NY, USA, May 2002. doi:10.1007/0-306-48213-4_9. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP/papers/stspchap.pdf (visited on 2026-09-25) (cit. on p. 199).

[108] David Stifler Johnson, Lyle Andrew McGeoch, Fred Glover, and Cesar Rego. *8th DIMACS Implementation Challenge: The Traveling Salesman Problem*. June 1, 2000–Nov. 19, 2013. URL: https://archive.dimacs.rutgers.edu/Challenges/TSP (visited on 2026-09-25) (cit. on p. 199).

[109] Selmer Martin Johnson. "Optimal Two- and Three-Stage Production Schedules with Setup Times Included". *Naval Research Logistics Quarterly* I(1):61–68, Mar. 1954. Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0894-069X. doi:10.1002/nav.3800010110. URL: https://www.rand.org/content/dam/rand/pubs/papers/2008/P402.pdf (visited on 2023-12-06) (cit. on p. 191).

[110] Scott Kirkpatrick, C. Daniel Gelatt, Jr., and Mario P. Vecchi. "Optimization by Simulated Annealing". *Science Magazine* 220(4598):671–680, May 13, 1983. Washington, D.C., USA: American Association for the Advancement of Science (AAAS). ISSN: 0036-8075. doi:10.1126/science.220.4598.671. URL: https://www.researchgate.net/publication/6026283 (visited on 2025-08-08) (cit. on pp. 49–61, 198).

[111] Robert Klein. *Scheduling of Resource-Constrained Projects*. Vol. 10 of Operations Research/Computer Science Interfaces Series (ORCS). New York, NY, USA: Springer New York, 2000. ISSN: 1387-666X. ISBN: 978-0-7923-8637-7. doi:10.1007/978-1-4615-4629-0 (cit. on p. 191).

[112] Donald Ervin Knuth. "Big Omicron and Big Omega and Big Theta". *ACM SIGACT News* 8(2):18–24, Apr.–June 1976. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 0163-5700. doi:10.1145/1008328.1008329 (cit. on p. 203).

[113] Donald Ervin Knuth. *Fundamental Algorithms*. 3rd ed. Vol. 1 of The Art of Computer Programming. Reading, MA, USA: Addison-Wesley Professional, 1997. ISBN: 978-0-201-89683-1 (cit. on p. 203).

References XVII

[114] Tjalling Charles Koopmans and Martin Beckmann. "Assignment Problems and the Location of Economic Activities". *Econometrica* 25(1):53–76, 1957. New Haven, CT, USA: The Econometric Society and Chichester, West Sussex, England, UK: John Wiley and Sons Ltd. ISSN: 0012-9682. doi:10.2307/1907742 (cit. on p. 197).

[115] John R. Koza. *Genetic Programming – On the Programming of Computers by Means of Natural Selection*. Complex Adaptive Systems. Cambridge, MA, USA: MIT Press, 1993. ISBN: 978-0-262-11170-6 (cit. on p. 191).

[116] Jakob Krarup and Peter Mark Pruzan. "Computer-aided Layout Design". In: *Mathematical Programming in Use*. Ed. by Michel Louis Balinski and Claude Lemaréchal. Vol. 9 of. Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 1978. Chap. 6, pp. 75–94. ISSN: 0303-3929. ISBN: 978-3-642-00796-5. doi:10.1007/BFb0120827. Uses QAPs as model for designing architectural layouts. (Cit. on p. 197).

[117] Mark W. Krentel. "The Complexity of Optimization Problems". *Journal of Computer and System Sciences* 36(3):490–509, June 1988. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0022-0000. Explores the hardness (optimization) problems such TSP, Clique, and Coloring, where computing the optimal value is $\mathcal{NP}$-complete. (Cit. on p. 199).

[118] Edmund Landau. *Handbuch der Lehre von der Verteilung der Primzahlen*. Leipzig, Sachsen, Germany: B. G. Teubner, 1909. ISBN: 978-0-8218-2650-8 (cit. on p. 203).

[119] Eugene Leighton Lawler, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. "Recent Developments in Deterministic Sequencing and Scheduling: A Survey". In: *Deterministic and Stochastic Scheduling: Proceedings of the NATO Advanced Study and Research Institute on Theoretical Approaches to Scheduling Problems*. June 6–17, 1981, Durham, England, UK. Ed. by Michael Anthony Howe Dempster, Jan Karel Lenstra, and Alexander Hendrik George Rinnooy Kan. Vol. 84 of Nato Science Series C: Mathematical and Physical Science (ASIC). London, England, UK: Springer Nature Limited, Apr. 1982, pp. 35–73. ISBN: 978-90-277-1397-1. doi:10.1007/978-94-009-7801-0_3. The JSSP is $\mathcal{NP}$-hard. (Cit. on p. 193).

References XVIII

[120] Eugene Leighton Lawler, Jan Karel Lenstra, Alexander Hendrik George Rinnooy Kan, and David B. Shmoys. "Sequencing and Scheduling: Algorithms and Complexity". In: *Production Planning and Inventory*. Ed. by Stephen C. Graves, Alexander Hendrik George Rinnooy Kan, and Paul H. Zipkin. Vol. IV of Handbooks of Operations Research and Management Science. Amsterdam, The Netherlands: Elsevier B.V., 1993. Chap. 9, pp. 445–522. ISSN: 0927-0507. ISBN: 978-0-444-87472-6. doi:10.1016/S0927-0507(05)80189-6. URL: http://alexandria.tue.nl/repository/books/339776.pdf (visited on 2023-12-06). Discusses, amongst others, that the JSSP is $\mathcal{NP}$-hard. (Cit. on pp. 193, 203).

[121] Eugene Leighton Lawler, Jan Karel Lenstra, Alexander Hendrik George Rinnooy Kan, and David B. Shmoys. *The Traveling Salesman Problem: A Guided Tour of Combinatorial Optimization*. Estimation, Simulation, and Control – Wiley-Interscience Series in Discrete Mathematics and Optimization. Chichester, West Sussex, England, UK: Wiley Interscience, Sept. 1985. ISSN: 0277-2698. ISBN: 978-0-471-90413-7 (cit. on pp. 16–19, 199).

[122] Stephen R. Lawrence. "Resource Constrained Project Scheduling: An Experimental Investigation of Heuristic Scheduling Techniques". PhD thesis. Pittsburgh, PA, USA: Graduate School of Industrial Administration (GSIA), Carnegie-Mellon University, 1984 (cit. on p. 193).

[123] Kent D. Lee and Steve Hubbard. *Data Structures and Algorithms with Python*. Undergraduate Topics in Computer Science (UTICS). Cham, Switzerland: Springer, 2015. ISSN: 1863-7310. ISBN: 978-3-319-13071-2. doi:10.1007/978-3-319-13072-9 (cit. on p. 196).

[124] Xueping Li and Kaike Zhang. "Single Batch Processing Machine Scheduling with Two-Dimensional Bin Packing Constraints". *International Journal of Production Economics (IJPE)* 196:113–121, Feb. 2018. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0925-5273. doi:10.1016/j.ijpe.2017.11.015. Mentions some scheduling tasks of Additive Manufacturing jobs can be viewed as instance of the 2BP|R|F. (Cit. on p. 189).

[125] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Jörg Lässig, Daan van den Berg, Sarah Louise Thomson, and Thomas Weise (汤卫思). "Addressing the Traveling Salesperson Problem with Frequency Fitness Assignment and Hybrid Algorithms". *Soft Computing* 28(17-18):9495–9508, July 2024. London, England, UK: Springer Nature Limited. ISSN: 1432-7643. doi:10.1007/S00500-024-09718-8 (cit. on pp. 16–19, 128, 129, 191, 195, 199).

References XIX

[126] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Jörg Lässig, Daan van den Berg, and Thomas Weise (汤卫思). "Solving the Traveling Salesperson Problem using Frequency Fitness Assignment". In: *IEEE Symposium Series on Computational Intelligence (SSCI'2022)*. Dec. 4–7, 2022, Singapore. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 2022. ISBN: 978-1-6654-8769-6. doi:10.1109/SSCI51031.2022.10022296 (cit. on pp. 128, 129, 191, 195).

[127] Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Matthias Thürer, Markus Wagner, and Thomas Weise (汤卫思). "Generating Small Instances with Interesting Features for the Traveling Salesperson Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 173–180. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888800003837 (cit. on pp. 128, 129, 195).

[128] Shen Lin and Brian W. Kernighan. "An Effective Heuristic Algorithm for the Traveling-Salesman Problem". *Operations Research* 21(2):498–516, Mar.–Apr. 1973. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0030-364X. doi:10.1287/opre.21.2.498. URL: https://www.cs.princeton.edu/~bwk/btl.mirror/tsp.pdf (visited on 2026-09-26) (cit. on p. 194).

[129] Dequan Liu (刘德全) and Hongfei Teng (滕弘飞). "An Improved BL-Algorithm for EAGenetic Algorithm of the Orthogonal Packing of Rectangles". *European Journal of Operational Research* 112(2):413–420, Jan. 1999. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(97)00437-2 (cit. on p. 192).

[130] Andrea Lodi, Silvano Martello, and Michele Monaci. "Two-Dimensional Packing Problems: A Survey". *European Journal of Operational Research* 141(2):241–252, Sept. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(02)00123-6 (cit. on pp. 189, 190).

[131] Andrea Lodi, Silvano Martello, and Daniele Vigo. "Heuristic and Metaheuristic Approaches for a Class of Two-Dimensional Bin Packing Problems". *INFORMS Journal on Computing* 11(4):345–357, Aut. 1999. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 1091-9856. doi:10.1287/ijoc.11.4.345 (cit. on p. 189).

[132] Andrea Lodi, Silvano Martello, and Daniele Vigo. "Recent Advances on Two-Dimensional Bin Packing Problems". *Discrete Applied Mathematics* 123(1–3):379–396, Nov. 2002. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0166-218X. doi:10.1016/S0166-218X(01)00347-X (cit. on pp. 189, 190).

References XX

[133] Eliane Maria Loiola, Nair Maria Maia de Abreu, Paulo Oswaldo Boaventura-Netto, Peter M. Hahn, and Tania Querido. "A Survey for the Quadratic Assignment Problem". *European Journal of Operational Research* 176(2):657–690, 2007. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2005.09.032 (cit. on p. 197).

[134] Mariana A. Londe, Luciana S. Pessoa, Carlos E. Andrade, and Mauricio G. C. Resende. *Biased Random-Key Genetic Algorithms: A Review*. arXiv.org: Computing Research Repository (CoRR) abs/2312.00961v2. Ithaca, NY, USA: Cornell Universiy Library, Dec. 6, 2023. doi:10.48550/arXiv.2312.00961. URL: https://arxiv.org/abs/2312.00961v2 (visited on 2024-06-27). arXiv:2312.00961v2 [cs.NE] 06 Dec 2023; See [135] (cit. on p. 175).

[135] Mariana A. Londe, Luciana S. Pessoa, Carlos E. Andrade, and Mauricio G. C. Resende. "Biased Random-Key Genetic Algorithms: A Review". *European Journal of Operational Research* 321(1):1–22, Feb. 2025. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2024.03.030. See [134] (cit. on pp. 175, 190).

[136] Marc Loy, Patrick Niemeyer, and Daniel Leuck. *Learning Java*. 5th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2020. ISBN: 978-1-4920-5627-0 (cit. on p. 193).

[137] Mark Lutz. *Learning Python*. 6th ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2025. ISBN: 978-1-0981-7130-8 (cit. on p. 196).

[138] Reinhard Männer and Bernard Manderick, eds. *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Amsterdam, The Netherlands: Elsevier B.V., 1992.

[139] Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe, eds. *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0000195000003837.

[140] Silvano Martello and Daniele Vigo. "Exact Solution of the Two-Dimensional Finite Bin Packing Problem". 44(3):388–399, Mar. 1998. doi:10.1287/mnsc.44.3.388 (cit. on p. 189).

[141] Stephan Mertens. "Exhaustive Search for Low-Autocorrelation Binary Sequences". *Journal of Physics A: Mathematical and General* 29(18):L473, Sept. 1996. Bristol, England, UK: IOP Publishing Ltd. ISSN: 0305-4470. doi:10.1088/0305-4470/29/18/005 (cit. on p. 194).

References XXI

[142] Peter Merz and Bernd Freisleben. "A Comparison of MAMemetic Algorithms, TSTabu Search, and ACOAnt Colonies for the QAPQuadratic Assignment Problem". In: *Congress on Evolutionary Computation (CEC'1999)*. July 6–9, 1999, Washington, D.C., USA. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 1999, pp. 2063–2070. doi:10.1109/CEC.1999.785529 (cit. on p. 197).

[143] Burkhard Militzer, Michele Zamparelli, and Dieter Beule. "Evolutionary Search for Low Autocorrelated Binary Sequences". *IEEE Transactions on Evolutionary Computation* 2(1):34–39, Apr. 1998. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/4235.728212 (cit. on p. 194).

[144] Alfonsas Misevičius. "A Tabu Search Algorithm for the Quadratic Assignment Problem". *Computational Optimization and Applications* 30:95–111, Jan. 2005. London, England, UK: Springer Nature Limited. ISSN: 0926-6003. doi:10.1007/s10589-005-4562-x (cit. on p. 199).

[145] Alfonsas Misevičius. "A Modified Simulated Annealing Algorithm for the Quadratic Assignment Problem". *Informatica* 14(4):497–514, Jan. 2003. Vilnius, Lithuania: Vilnius University, Institute of Data Science and Digital Technologies (DMSTI), Lithuanian Academy of Sciences. ISSN: 0868-4952. doi:10.15388/Informatica.2003.037 (cit. on p. 198).

[146] Alfonsas Misevičius. *An Implementation of the Iterated Tabu Search Algorithm for the Quadratic Assignment Problem*. Working Paper. Kaunas, Lithuania: Kaunas University of Technology, 2008. See also [147] (cit. on p. 176).

[147] Alfonsas Misevičius. "An Implementation of the Iterated Tabu Search Algorithm for the Quadratic Assignment Problem". *OR Spectrum: Quantitative Approaches in Management. Formerly Operations-Research-Spektrum* 34(3):665–690, July 2012. London, England, UK: Springer Nature Limited. ISSN: 0171-6468. doi:10.1007/s00291-011-0274-z. See also [146] (cit. on pp. 176, 197, 199).

[148] Nenad Mladenović and Pierre Hansen. "Variable Neighborhood Search". *Computers & Operations Research* 24(11):1097–1100, Nov. 1997. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/S0305-0548(97)00031-2 (cit. on p. 201).

[149] Wai Ho Mow, Ke-Lin Du, and Wei Hsiang Wu. "New Evolutionary Search for Long Low Autocorrelation Binary Sequences". *IEEE Transactions on Aerospace and Electronic Systems* 51(1):290–303, Jan. 2015. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 0018-9251. doi:10.1109/TAES.2014.130518 (cit. on p. 194).

References XXII

[150] Heinz Mühlenbein. "How Genetic Algorithms Really Work: Mutation and Hillclimbing". In: *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Ed. by Reinhard Männer and Bernard Manderick. Amsterdam, The Netherlands: Elsevier B.V., 1992, pp. 15–26. URL: https://www.researchgate.net/publication/284805798 (visited on 2025-08-15) (cit. on pp. 118–125, 196).

[151] Siegfried Nijssen and Thomas Bäck. "An Analysis of the Behavior of Simplified Evolutionary Algorithms on Trap Functions". *IEEE Transactions on Evolutionary Computation* 7(1):11–22, Feb. 2003. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2002.806169 (cit. on p. 198).

[152] Eugeniusz Nowicki and Czesław Smutnicki. "A Fast Taboo Search Algorithm for the Job Shop Problem". *Management Science* 42(6):783–938, June 1996. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.42.6.797 (cit. on p. 199).

[153] Regina O. Obe and Leo S. Hsu. *PostgreSQL: Up and Running*. 3rd ed. Sebastopol, CA, USA: O'Reilly Media, Inc., Oct. 2017. ISBN: 978-1-4919-6336-4 (cit. on p. 196).

[154] Tom Packebusch and Stephan Mertens. "Low Autocorrelation Binary Sequences". *Journal of Physics A: Mathematical and Theoretical* 49(16):165001, Mar. 2016. Bristol, England, UK: IOP Publishing Ltd. ISSN: 1751-8121. doi:10.1088/1751-8113/49/16/165001 (cit. on p. 194).

[155] Panos Miltiades Pardalos, Ding-Zhu Du, and Ronald Lewis Graham, eds. *Handbook of Combinatorial Optimization*. 1st ed. Boston, MA, USA: Springer, 1998. ISBN: 978-1-4613-7987-4.

[156] Panos Miltiades Pardalos, Oleg V. Shylo, and Alkis Vazacopoulos. "Solving Job Shop Scheduling Problems Utilizing the Properties of Backbone and "Big Valley"". *Computational Optimization and Applications* 47(1):61–76, Sept. 2010. London, England, UK: Springer Nature Limited. ISSN: 0926-6003. doi:10.1007/s10589-008-9206-5. An algorithm similar to SA. (Cit. on pp. 193, 198).

[157] Francisco Parreño, Ramón Alvarez-Valdés, José Fernando Oliveira, and José Manuel Tamarit. "A Hybrid GRASP/VND Algorithm for Two- and Three-Dimensional Bin Packing". *Annals of Operations Research* 179(1):203–220, Sept. 2010. London, England, UK: Springer Nature Limited. ISSN: 0254-5330. doi:10.1007/s10479-008-0449-4 (cit. on pp. 189, 191, 200).

References XXIII

[158] Bo Peng, Zhipeng Lü, and T. C. Edwin Cheng. "A Tabu Search/Path Relinking Algorithm to Solve the Job Shop Scheduling Problem". *Computers & Operations Research* 53:154–164, Jan. 2015. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/j.cor.2014.08.006. URL: http://arxiv.org/abs/1402.5613 (visited on 2026-09-30) (cit. on pp. 193, 199).

[159] Ferdinando Pezzella and Emanuela Merelli. "A Tabu Search Method Guided by Shifting Bottleneck for the Job Shop Scheduling Problem". *European Journal of Operational Research* 120(2):297–310, Jan. 2000. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(99)00158-7. URL: https://www2.cs.sfu.ca/CourseCentral/827/havens/papers/topic%5C%2310(JobShop)/Tabu%5C%20With%5C%20Shifting.pdf (visited on 2026-09-30) (cit. on p. 199).

[160] Martin Pincus. "Letter to the Editor – A Monte Carlo Method for the Approximate Solution of Certain Types of Constrained Optimization Problems". *Operations Research* 18(6):1225–1228, Nov.–Dec. 1970. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0030-364X. doi:10.1287/opre.18.6.1225 (cit. on p. 198).

[161] Marcelo Pinto, Cristóvão Silva, Matthias Thürer, and Samuel Moniz. "Survey in Operations Research and Management Science. Nesting and Scheduling Optimization of Additive Manufacturing Systems: Mapping the Territory". *Computers & Operations Research* 165(106592), Feb. 2024. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0305-0548. doi:10.1016/j.cor.2024.106592. Mentions some scheduling tasks of Additive Manufacturing jobs can be viewed as instance of the 2BP|R|F. (Cit. on p. 189).

[162] Riccardo Poli, William B. Langdon, and Nicholas Freitag McPhee. *A Field Guide to Genetic Programming*. lulu.com, 2008. ISBN: 978-1-4092-0073-4. URL: https://www.researchgate.net/publication/216301261 (visited on 2025-08-18) (cit. on p. 191).

[163] *PostgreSQL Essentials: Leveling Up Your Data Work*. Sebastopol, CA, USA: O'Reilly Media, Inc., Mar. 2024 (cit. on p. 196).

[164] S. D. Prestwich. *Improved Branch-and-Bound for Low Autocorrelation Binary Sequences*. arXiv.org: Computing Research Repository (CoRR) abs/1305.6187. Ithaca, NY, USA: Cornell Universiy Library, Apr. 3, 2024. doi:10.48550/arXiv.1305.6187. URL: https://arxiv.org/abs/1305.6187 (visited on 2013-07-23). arXiv:1305.6187v2 [cs.AI] 23 Jul 2013 (cit. on p. 194).

[165] *Programming Languages – C, Working Document of SC22/WG14*. International Standard ISO/IEC9899:2017 C17 Ballot N2176. Geneva, Switzerland: International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC), Nov. 2017. URL: https://files.lhmouse.com/standards/ISO%20C%20N2176.pdf (visited on 2024-06-29) (cit. on p. 190).

References XXIV

[166] Sanatan Rai and George Vairaktarakis. "NP-Complete Problems and Proof Methodology". In: *Encyclopedia of Optimization*. Ed. by Christodoulos A. Floudas and Panos Miltiades Pardalos. 2nd ed. Boston, MA, USA: Springer, Sept. 2008, pp. 2675–2682. ISBN: 978-0-387-74758-3. doi:10.1007/978-0-387-74759-0_462 (cit. on p. 203).

[167] Soraya B. Rana and L. Darrell Whitley. "Genetic Algorithm Behavior in the MAXSAT Domain". In: *5th International Conference on Parallel Problem Solving from Nature (PPSN V)*. Sept. 27–30, 1998, Amsterdam, The Netherlands. Ed. by Ágoston Endre Eiben, Thomas Bäck, Marc Schoenauer, and Hans-Paul Schwefel. Lecture Notes in Computer Science (LNCS). 1998, pp. 785–794. ISSN: 0302-9743. ISBN: 978-3-540-65078-2. doi:10.1007/BFb0056920 (cit. on p. 195).

[168] Gerhard Reinelt. "TSPLIB – A Traveling Salesman Problem Library". *ORSA Journal on Computing* 3(4):376–384, Aut. 1991. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0899-1499. doi:10.1287/ijoc.3.4.376 (cit. on p. 199).

[169] Gerhard Reinelt. *TSPLIB95*. Tech. rep. Heidelberg, Baden-Württemberg, Germany: Universität Heidelberg, Institut für Angewandte Mathematik, 1995–Apr. 28, 2016. URL: https://github.com/shredderzwj/TSPLIB (visited on 2026-09-25). The original Uniform Resource Locator (URL) of the repository has become defunct in 2026. Therefore, we provide the repository listed as main URL which contains the data. Additionally, you may also check https://github.com/thomasWeise/tspSuite of our own project *TSPSuite*, which contains all the TSPLib instances as well as Java code to load them. (Cit. on p. 199).

[170] Günter Rudolph. *Convergence Properties of Evolutionary Algorithms*. Vol. 35 of Forschungsergebnisse zur Informatik. Hamburg, Germany: Verlag Dr. Kovač, 1997. ISSN: 1435-6260. ISBN: 978-3-86064-554-3 (cit. on p. 194).

[171] Stuart J. Russell and Peter Norvig. *Artificial Intelligence: A Modern Approach (AIMA)*. 4th ed. Hoboken, NJ, USA: Pearson Education, Inc. ISBN: 978-1-292-40113-3. URL: https://aima.cs.berkeley.edu (visited on 2024-06-27) (cit. on p. 189).

[172] Sartaj Sahni and Teofilo Francisco Gonzalez Arce. "P-complete Approximation Problems". *Journal of the ACM (JACM)* 23(3):555–565, July 1976. New York, NY, USA: Association for Computing Machinery (ACM). ISSN: 0004-5411. doi:10.1145/321958.321975. URL: https://sites.cs.ucsb.edu/~teo/papers/JACM-PCom.pdf (visited on 2026-02-21) (cit. on p. 197).

[173] Guntram Scheithauer. *Introduction to Cutting and Packing Optimization: Problems, Modeling Approaches, Solution Methods*. Vol. 263 of International Series in Operations Research & Management Science (ISOR). Cham, Switzerland: Springer, 2018. ISSN: 0884-8289. ISBN: 978-3-319-64402-8. doi:10.1007/978-3-319-64403-5 (cit. on p. 190).

References XXV

[174] Guoyong Shi, Hitoshi Iima, and Nobuo Sannomiya. "New Encoding Scheme for Solving Job Shop Problems by Genetic Algorithm". In: *35th IEEE Conference on Decision and Control (CDC'96)*. Vol. 4. Dec. 11–13, 1996. Kōbe, Hyōgo-ken, Japan: Institute of Electrical and Electronics Engineers (IEEE), 1997, pp. 4395–4400. ISBN: 978-0-7803-3590-5. doi:10.1109/CDC.1996.577484. URL: https://www.researchgate.net/publication/224238934 (visited on 2026-09-30). Proposes a permutations-with-repetitions based encoding for the JSSP. (Cit. on pp. 168, 193, 202).

[175] Oleg V. Shylo. *Job Shop Scheduling (Personal Homepage)*. Knoxville, TN, USA: Oleg V. Shylo, Aug. 2019. URL: http://optimizizer.com/jobshop.php (visited on 2026-09-30). Contains many JSSP benchmark instances. (Cit. on pp. 180, 193).

[176] Oleg V. Shylo and Hesam Shams. *Boosting Binary Optimization via Binary Classification: A Case Study of Job Shop Scheduling*. arXiv.org: Computing Research Repository (CoRR) abs/1808.10813. Proposes a TS using regression to adapt the tabu tenures for each variable of the solution vector of a JSSP separately. Many results are available in the GitHub repository https://github.com/quasiquasar/gta-jobshop-data; other results are published Shylo's website http://optimizizer.com/jobshop.php. Ithaca, NY, USA: Cornell Universiy Library, Aug. 31, 2018. doi:10.48550/arXiv.1808.10813. URL: https://arxiv.org/abs/1808.10813 (visited on 2026-09-30) (cit. on pp. 193, 199).

[177] Hossein M. Soroush. "Scheduling in Stochastic Bicriteria Single Machine Systems with Set-up Times". *International Journal of Planning and Scheduling* 1(1–2):109–145, Jan. 2011. Geneva, Switzerland: Inderscience Publishers. ISSN: 2044-494X. doi:10.1504/IJPS.2011.044605. A scheduling problem is phrased as QAP. (Cit. on p. 197).

[178] Leon Steinberg. "The Backboard Wiring Problem: A Placement Algorithm". *SIAM Review* 3(1):37–50, Jan. 1961. Philadelphia, PA, USA: Society for Industrial and Applied Mathematics Publications (SIAM). ISSN: 0036-1445. doi:10.1137/1003003. The problem is modeled as a QAP (cit. on p. 197).

[179] Robert H. Storer, S. David Wu, and Renzo Vaccari. "New Search Spaces for Sequencing Problems with Application to Job Shop Scheduling". *Management Science* 38(10):1495–1509, Oct. 1992. Catonsville, MD, USA: The Institute for Operations Research and the Management Sciences (INFORMS). ISSN: 0025-1909. doi:10.1287/mnsc.38.10.1495 (cit. on p. 193).

References XXVI

[180] Thomas Strecker and Leonhard Hennig. "Automatic Layouting of Personalized Newspaper Pages". In: *Operations Research Proceedings 2008: Selected Papers of the Annual International Conference of the German Operations Research Society (GOR)*. Sept. 3–5, 2008, Augsburg, Bayern, Germany: University of Augsburg. Ed. by Bernhard Fleischmann, Karl-Heinz Borgwardt, Robert Klein, and Axel Tuma. Vol. 2008 of Operations Research Proceedings (ORP), Gesellschaft für Operations Research e.V., (GOR). Berlin/Heidelberg, Germany: Springer-Verlag GmbH Germany, 2009, pp. 469–474. ISSN: 0721-5924. doi:10.1007/978-3-642-00142-0_76 (cit. on p. 189).

[181] Thomas Stützle. "Iterated Local Search for the Quadratic Assignment Problem". *European Journal of Operational Research* 174(3):1519–1539, Nov. 2006. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/j.ejor.2005.01.066 (cit. on pp. 192, 197).

[182] Éric D. Taillard. "Benchmarks for Basic Scheduling Problems". *European Journal of Operational Research* 64(2):278–285, Jan. 1993. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/0377-2217(93)90182-M. URL: https://arodes.hes-so.ch/record/8224/files/Preprint.pdf (visited on 2026-02-20) (cit. on p. 193).

[183] Éric D. Taillard. "Comparison of Iterative Searches for the Quadratic Assignment Problem". *Location Science. Now incorporated into Computers & Operations Research* 3(2):87–105, Aug. 1995. Amsterdam, The Netherlands: Elsevier B.V. doi:10.1016/0966-8349(95)00008-6 (cit. on p. 199).

[184] Éric D. Taillard. "Robust Taboo Search for the Quadratic Assignment Problem". *Parallel Computing* 17(4–5):443–455, July 1991. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0167-8191. doi:10.1016/S0167-8191(05)80147-4 (cit. on pp. 166, 181, 197, 199).

[185] Éric D. Taillard and Luca M. Gambardella. *Adaptive Memories for the Quadratic Assignment Problem*. Tech. rep. IDSIA-87-97. Lugano, Switzerland: Istituto Dalle Molle Di Studi Sull Intelligenza Artificiale (IDSIA), Sept. 10, 1997. URL: https://mistic.iict-heig-vd.ch/taillard/articles.dir/TaillardGambardella1997.pdf (visited on 2026-09-28). A MA using TS from [184] as well as a ACO-based approach refining its solutions with a very simple SLS are presented. (Cit. on p. 197).

[186] Alkin Tezuysal and Ibrar Ahmed. *Database Design and Modeling with PostgreSQL and MySQL*. Birmingham, England, UK: Packt Publishing Ltd, July 2024. ISBN: 978-1-80323-347-5 (cit. on p. 196).

[187] Dirk Thierens, David Edward Goldberg, and Angela Guimarães Pereira. "Domino Convergence, Drift, and the Temporal-Salience Structure of Problems". In: pp. 535–540. doi:10.1109/ICEC.1998.700085 (cit. on p. 188).

References XXVII

[188] Sarah Louise Thomson, Gabriela Ochoa, Daan van den Berg, Tianyu Liang (梁天宇), and Thomas Weise (汤卫思). "Entropy, Search Trajectories, and Explainability for Frequency Fitness Assignment". In: *Parallel Problem Solving from Nature (PPSN XVIII)*. Vol. 1. Sept. 14–18, 2024, Hagenberg, Mühlkreis, Austria. Ed. by Michael Affenzeller, Stephan M. Winkler, Anna V. Kononova, Heike Trautmann, Tea Tušar, Penousal Machado, and Thomas Bäck. Vol. 15148 of Lecture Notes in Computer Science (LNCS). Cham, Switzerland: Springer. ISSN: 0302-9743. ISBN: 978-3-031-70054-5. doi:10.1007/978-3-031-70055-2_23. Explores RLS, RLS with FFA (FRLS), and SA on the QAP. (Cit. on pp. 130, 131, 191, 195).

[189] Ulrich Wilhelm Thonemann and Andreas Bölte. *An Improved Simulated Annealing Algorithm for the Quadratic Assignment Problem*. Working Paper. Paderborn, Nordrhein-Westfalen, Germany: School of Business, Department of Production and Operations Research, University of Paderborn, 1994 (cit. on p. 198).

[190] Marco Tomassini. "Complex Networks Analysis of the Energy Landscape of the Low Autocorrelation Binary Sequences Problem". *Physica A: Statistical Mechanics and its Applications* 577:126089, Sept. 1, 2021. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0378-4371. doi:10.1016/j.physa.2021.126089. Lists the LABS as $\mathcal{NP}$-hard. (Cit. on p. 194).

[191] Daan van den Berg, Florian Braam, Mark Moes, Emiel Suilen, and Sandjai Bhulai. "Almost Squares in Almost Squares: Solving the Final Instance". In: *5th International Conference on Data Analytics (DATA ANALYTICS'2016)*. Oct. 9–13, 2016, Venice, Venezia, Veneto, Italy. Ed. by Sandjai Bhulai and Ivana Semanjski. Wilmington, DE, USA: International Academy, Research, and Industry Association (IARIA), 2016, pp. 69–74. ISSN: 2308-4464. ISBN: 978-1-61208-510-4. URL: https://math.vu.nl/~sbhulai/publications/data_analytics2016b.pdf (visited on 2026-10-01). This poses a very interesting 2BP|R|F problem, where "almost squars," i.e., rectangles with sizes $(i, i+1)$, must be placed in an almost square. (Cit. on pp. 189, 190).

[192] Clarissa Van Hoyweghen, David Edward Goldberg, and Bart Naudts. "From Twomax To The Ising Model: Easy And Hard Symmetrical Problems". In: *4th Genetic and Evolutionary Computation Conference (GECCO'2002)*. July 9–13, 2002, New York, NY, USA. Ed. by William B. Langdon, Erick Cantú-Paz, Keith E. Mathias, Rajkumar Roy, David Davis, Riccardo Poli, Karthik Balakrishnan, Vasant G. Honavar, Günter Rudolph, Joachim Wegener, Larry Bull, Mitchell A. Potter, Alan C. Schultz, Julian F. Miller, Edmund K. Burke, and Natasa Jonoska. Burlington, MA, USA/San Mateo, CA, USA: Morgan Kaufmann Publishers, 2002, pp. 626–633. ISBN: 978-1-55860-878-8 (cit. on pp. 118–125, 200).

References XXVIII

[193] Dieter Vandesande, Christoph Jabs, Jeremias Berg, Johannes Fichte, George Katsirelos, Ruben Martins, André Schidler, and Dominik Schreiber. *MaxSAT Evaluation 2026: Solvers, Benchmarks & Results*. v1. Geneva, Switzerland: zenodo (hosted by European Organization for Nuclear Research (CERN)), July 14, 2026. doi:10.5281/zenodo.21358014. See also https://maxsat-evaluations.github.io. (Cit. on p. 195).

[194] Kristian Verduin, Sarah Louise Thomson, and Daan van den Berg. "Too Constrained for Genetic Algorithms. Too Hard for Evolutionary Computing. The Traveling Tournament Problem". In: *15th International Joint Conference on Computational Intelligence (IJCCI'23)*. Nov. 13–15, 2023, Rome, Italy. Ed. by Niki van Stein, Francesco Marcelloni, H. K. Lam, Marie Cottrell, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2023, pp. 246–257. ISSN: 2184-3236. ISBN: 978-989-758-674-3. doi:10.5220/0012192100003595 (cit. on p. 200).

[195] Petr Vilím, Philippe Laborie, and Paul Shaw. "Failure-Directed Search for Constraint-Based Scheduling". In: *12th International Conference on the Integration of AI and OR Techniques in Constraint Programming (CPAIOR'2015)*. Ed. by Laurent Michel. Vol. 9075 of Theoretical Computer Science and General Issues (LNTCS), sub-series of Lecture Notes in Computer Science (LNCS). Barcelona, Spain: Springer, 2015, pp. 437–453. ISSN: 2512-2010. ISBN: 978-3-319-18007-6. doi:10.1007/978-3-319-18008-3_30. URL: https://www.researchgate.net/publication/280223626 (visited on 2026-09-30) (cit. on p. 193).

[196] Thomas Weise (汤卫思). *Databases*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2025. URL: https://thomasweise.github.io/databases (visited on 2025-01-05) (cit. on pp. 153, 190).

[197] Thomas Weise (汤卫思). *Global Optimization Algorithms – Theory and Application*. self-published, 2009. URL: https://www.researchgate.net/publication/200622167 (visited on 2025-07-25) (cit. on pp. 4–6, 191, 194, 195, 198).

[198] Thomas Weise (汤卫思). *jsspInstancesAndResults: Results, Data, and Instances of the Job Shop Scheduling Problem*. San Francisco, CA, USA: GitHub Inc, 2019–2020. URL: https://github.com/thomasWeise/jsspInstancesAndResults (visited on 2025-08-20) (cit. on p. 193).

[199] Thomas Weise (汤卫思). *Programming with C*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2026. URL: https://thomasweise.github.io/programmingWithC (visited on 2026-05-10) (cit. on p. 190).

References XXIX

[200] Thomas Weise (汤卫思). *Programming with Python*. Hefei, Anhui, China (中国安徽省合肥市): Hefei University (合肥大学), School of Artificial Intelligence and Big Data (人工智能与大数据学院), 2024–2026. URL: https://thomasweise.github.io/programmingWithPython (visited on 2025-01-05) (cit. on pp. 152, 196).

[201] Thomas Weise (汤卫思), Raymond Chiong, Jörg Lässig, Ke Tang (唐珂), Shigeyoshi Tsutsui, Wenxiang Chen (陈文祥), Zbigniew "Zbyszek" Michalewicz, and Xin Yao (姚新). "Benchmarking Optimization Algorithms: An Open Source Framework for the Traveling Salesman Problem". *IEEE Computational Intelligence Magazine (CIM)* 9(3):40–52, Aug. 2014. Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE). ISSN: 1556-603X. doi:10.1109/MCI.2014.2326101. Applies a multitude of algorithms including SLSes, EAs, MAs, ACO, and EDAs to the TSPLib instances. (Cit. on pp. 16–19, 199, 201).

[202] Thomas Weise (汤卫思), Xinlu Li (李新路), Yan Chen (陈岩), and Zhize Wu (吴志泽). "Solving Job Shop Scheduling Problems without using a Bias for Good Solutions". In: *23rd Genetic and Evolutionary Computation Conference (GECCO'2021), Companion Volume*. July 10–14, 2021, Lille, France. Ed. by Krzysztof Krawiec. New York, NY, USA: Association for Computing Machinery (ACM), 2021, pp. 1459–1466. ISBN: 978-1-4503-8351-6. doi:10.1145/3449726.3463124. Applies FFA to the JSSP. (Cit. on pp. 132, 133, 162, 202).

[203] Thomas Weise (汤卫思) and Ke Tang (唐珂). "Evolving Distributed Algorithms with Genetic Programming". *IEEE Transactions on Evolutionary Computation* 16(2):242–265, Apr. 2012. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2011.2112666 (cit. on p. 191).

[204] Thomas Weise (汤卫思), Mingxu Wan (万明绪), Ke Tang (唐珂), and Xin Yao (姚新). "Evolving Exact Integer Algorithms with GPGenetic Programming". In: *IEEE Congress on Evolutionary Computation (CEC'2014)*. July 6–11, 2014, China, Beijing (中国北京市). Piscataway, NJ, USA: Institute of Electrical and Electronics Engineers (IEEE), 2014, pp. 1816–1823. ISBN: 978-1-4799-1488-3. doi:10.1109/CEC.2014.6900292 (cit. on pp. 134, 135).

[205] Thomas Weise (汤卫思), Mingxu Wan (万明绪), Pu Wang (王璞), Ke Tang (唐珂), Alexandre Devert, and Xin Yao (姚新). "Frequency Fitness Assignment". *IEEE Transactions on Evolutionary Computation* 18(2):226–243, Apr. 2014. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2013.2251885. The article introducing FFA. (Cit. on pp. 115–117, 126, 127, 134, 135, 191).

References XXX

[206] Thomas Weise (汤卫思) and Zhize Wu (吴志泽). "Replicable Self-Documenting Experiments with Arbitrary Search Spaces and Algorithms". In: *25th Conference on Genetic and Evolutionary Computation (GECCO'2023), Companion Volume*. July 15–19, 2023, Lisbon, Portugal. Ed. by Sara Silva and Luís Paquete. New York, NY, USA: Association for Computing Machinery (ACM), 2023, pp. 1891–1899. ISBN: 979-8-4007-0120-7. doi:10.1145/3583133.3596306. Introduces the experiment execution and data collection facilities of moptipy. (Cit. on pp. 154, 195).

[207] Thomas Weise (汤卫思), Zhize Wu (吴志泽), Xinlu Li (李新路), and Yan Chen (陈岩). "Frequency Fitness Assignment: Making Optimization Algorithms Invariant under Bijective Transformations of the Objective Function Value". *IEEE Transactions on Evolutionary Computation* 25(2):307–319, Apr. 2021. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2020.3032090 (cit. on pp. 115–117, 126, 127, 132, 133, 188, 191, 193, 194, 196, 198, 200).

[208] Thomas Weise (汤卫思), Zhize Wu (吴志泽), Xinlu Li (李新路), Yan Chen (陈岩), and Jörg Lässig. "Frequency Fitness Assignment: Optimization without Bias for Good Solutions can be Efficient". *IEEE Transactions on Evolutionary Computation* 27(4):980–992, 2023. Los Alamitos, CA, USA: IEEE Computer Society. ISSN: 1089-778X. doi:10.1109/TEVC.2022.3191698. Applies many FFA-based algorithm variants to problems such as OneMax, LeadingOnes, Linear Harmonic Function (LinHarm), TwoMax, Trap, Jump, Plateau, Ising Model, and N-Queens. (Cit. on pp. 115–117, 126, 127, 188, 191, 193, 198, 200).

[209] Thomas Weise (汤卫思), Yuezhong Wu (吴越钟), Raymond Chiong, Ke Tang (唐珂), and Jörg Lässig. "Global versus Local Search: The Impact of Population Sizes on Evolutionary Algorithm Performance". *Journal of Global Optimization* 66(3):511–534, Feb. 2016. London, England, UK: Springer Nature Limited. ISSN: 0925-5001. doi:10.1007/s10898-016-0417-5 (cit. on pp. 16–19, 199).

[210] L. Darrell Whitley. "The GENITOR Algorithm and Selection Pressure: Why Rank-Based Allocation of Reproductive Trials is Best". In: *3rd International Conference on Genetic Algorithms (ICGA'1989)*. June 1989, Fairfax, VA, USA: George Mason University. Ed. by J. David Schaffer. Burlington, MA, USA/San Mateo, CA, USA: Morgan Kaufmann Publishers, 1989, pp. 116–123. ISBN: 978-1-55860-066-9. URL: https://www.researchgate.net/publication/2527551 (visited on 2025-08-08) (cit. on p. 194).

[211] James M. Wilson. "Gantt Charts: A Centenary Appreciation". *European Journal of Operational Research* 149(2):430–437, Sept. 2003. Amsterdam, The Netherlands: Elsevier B.V. ISSN: 0377-2217. doi:10.1016/S0377-2217(02)00769-5 (cit. on p. 191).

References XXXI

[212] L. Wong and Lai-Soon Lee. "Heuristic Placement Routines for Two-Dimensional Bin Packing Problem". 5(4):334–341, Dec. 2009. doi:/10.3844/jmssp.2009.334.341. URL: https://www.thescipub.com/pdf/jmssp.2009.334.341 (visited on 2026-10-02). A heuristic for the 2BP|R|F and the 2BP|O|F (cit. on p. 159).

[213] CAO Xiang (曹翔), Zhize Wu (吴志泽), Daan van den Berg, and Thomas Weise (汤卫思). "Randomized Local Search vs. NSGA-II vs. Frequency Fitness Assignment on The Traveling Tournament Problem". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 38–49. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012891500003837 (cit. on pp. 144–150, 195, 200, 202).

[214] Takeshi Yamada and Ryohei Nakano. "A Genetic Algorithm Applicable to Large-Scale Job-Shop Instances". In: *Parallel Problem Solving from Nature 2 (PPSN-II)*. Sept. 28–30, 1992, Brussels, Belgium. Ed. by Reinhard Männer and Bernard Manderick. Amsterdam, The Netherlands: Elsevier B.V., 1992, pp. 281–290. URL: https://www.researchgate.net/publication/220701684 (visited on 2026-09-30) (cit. on p. 193).

[215] Kinza Yasar and Craig S. Mullins. *Definition: Database Management System (DBMS)*. Newton, MA, USA: TechTarget, Inc., June 2024. URL: https://www.techtarget.com/searchdatamanagement/definition/database-management-system (visited on 2025-01-11) (cit. on p. 191).

[216] François Yergeau. *UTF-8, A Transformation Format of ISO 10646*. Request for Comments (RFC) 3629. Wilmington, DE, USA: Internet Engineering Task Force (IETF), Nov. 2003. URL: https://www.ietf.org/rfc/rfc3629.txt (visited on 2025-02-05). See Unicode and [99] (cit. on p. 200).

[217] Jiazheng Zeng (曾嘉政), Thomas Weise (汤卫思), Zhize Wu (吴志泽), and Markus Wagner. "When Frequency Fitness Assignment Fails: Trapped States in Frequency-Guided Local Search". In: *28th Genetic and Evolutionary Computation Conference (GECCO'2026)*. July 13–17, 2026, San José, Costa Rica. Ed. by Leonardo Trujillo and Ting Hu. New York, NY, USA: Association for Computing Machinery (ACM), 2026, pp. 233–242. ISBN: 979-8-4007-2487-9. doi:10.1145/3795095.3805098. Explores $(1+1)$ EA, $(1+1)$ FEA, RLS, and FRLS as well as hybrid algorithms on a variety of discrete benchmarks such as OneMax, LeadingOnes, LinHarm, Binary Integer (BinInt), TwoMax, Trap, Jump, Plateau, Ising Model, N-Queens and also applies them to the search for Low-Autocorrelation Binary Sequences (LABS). (Cit. on pp. 188, 191–198, 200).

References XXXII

[218] Chaoyong Zhang, Xinyu Shao, Yunqing Rao, and Haobo Qiu. "Some New Results on Tabu Search Algorithm Applied to the Job-Shop Scheduling Problem". In: *Tabu Search*. Ed. by Wassim Jaziri. London, England, UK: IntechOpen Limited, Aug. 1, 2008. Chap. 8. ISBN: 978-3-902613-34-9. doi:10.5772/5593. URL: https://www.intechopen.com/chapters/4596 (visited on 2026-09-30) (cit. on pp. 193, 199).

[219] Rui Zhao (赵睿), Tianyu Liang (梁天宇), Zhize Wu (吴志泽), Daan van den Berg, Matthias Thürer, and Thomas Weise (汤卫思). "Randomized Local Search on the 2D Rectangular Bin Packing Problem with Item Rotation". In: *26th Genetic and Evolutionary Computation Conference (GECCO'2024)*. July 14–18, 2024, Melbourne, VIC, Australia. Ed. by Xiaodong Li and Julia Handl. New York, NY, USA: Association for Computing Machinery (ACM), 2024, pp. 235–238. ISBN: 979-8-4007-0494-9. doi:10.1145/3638530.3654139 (cit. on pp. 20–23, 144–150, 189, 192, 195).

[220] Rui Zhao (赵睿), Zhize Wu (吴志泽), Daan van den Berg, Matthias Thürer, Tianyu Liang (梁天宇), Ming Tan (檀明), and Thomas Weise (汤卫思). "Randomized Local Search for Two-Dimensional Bin Packing and a Negative Result for Frequency Fitness Assignment". In: *16th International Joint Conference on Computational Intelligence (IJCCI'24)*. Nov. 20–22, 2024, Porto, Portugal. Ed. by Francesco Marcelloni, Kurosh Madani, Niki van Stein, and Joaquim Filipe. Porto, Portugal: SciTePress: Science and Technology Publications, Lda, 2024, pp. 15–26. ISSN: 2184-3236. ISBN: 978-989-758-721-4. doi:10.5220/0012888500003837 (cit. on pp. 20–23, 144–150, 189, 190, 192, 195).

Glossary I

$(1+1)$ EA The $(1+1)$ EA is a local search algorithm that retains the best solution x_c discovered so far during the search [33,61]. In each step, it applies a unary search operator to this best-so-far solution x_c and derives a new solution x_n. If the new solution x_n is *better or equally good* when compared with x_c, i.e., not worse, then it replaces it, i.e., is stored as the new x_c. If the search space are bit strings of length n, then the $(1+1)$ EA uses a unary search operator that flips each bit independently with probability m/n, where usually $m = 1$. This operator is the main difference to randomized local search (RLS). The $(1+1)$ EA is a special case of the $(\mu+\lambda)$ evolutionary algorithm ($(\mu+\lambda)$ EA) where $\mu = \lambda = 1$.

$(1+1)$ FEA The $(1+1)$ EA with FFA plugged in [207,208,217]. On the discrete bit-string domains, this algorithm has a very specific structure: Its unary search operator flips each bit with probability $1/n$, where n is the dimension of the search space, distinguishing it from the unary operator in FRLS which flips exactly one bit. On other domains, such as permutations, the term is used synonymously with FRLS.

$(\mu+\lambda)$ EA The $(\mu+\lambda)$ EA is an evolutionary algorithm (EA) where, in each generation, λ offspring solutions are generated from the current population of μ parent solutions. The offspring and parent populations are merged, yielding $\mu+\lambda$ solutions, from which then the best μ solutions are ratained to form the parent population of the next generation. If the search space is the bit strings of length n, then this algorithm usually applies a mutation operator flipping each bit independently with probability $1/n$.

BinInt The *Binary Integer Problem* is a benchmark problem for bit-string based black-box search [187,217]. It is very similar to OneMax: It tries to maximize the number of 1 bits in the bit string of a chosen dimension n. Different from OneMax, where each bit has the same weight in the objective function, the bits of BinInt have a exponentially increasing weight: The bit string is treated as a binary-encoded integer whose value should be maximized. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = 2^n - 1 - \sum_{i=1}^{n} 2^{i-1} \cdot x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately.

LinHarm The Linear Harmonic Function is a benchmark problem for bit-string based black-box search [55,61,217]. It is very similar to OneMax: It tries to maximize the number of 1 bits in the bit string of a chosen dimension n. Different from OneMax, where each bit has the same weight in the objective function, the bits of LinHarm have a linear increasing weight. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = \frac{1}{2}n(n+1) - \sum_{i=1}^{n} i \cdot x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately. The $(1+1)$ EA can solve this problem with an expected runtime in $\Theta(n \ln n)$ [55,61].

Glossary II

2BP In the two-dimensional Bin Packing Problem (BP), the goal is to pack rectangles into rectangular bins without overlap and such that their edges are parallel to the edges of the bins [100,130,132]. The 2BP is strongly $\mathcal{NP}$-hard [132]. The variants of this problem include the 2BP|O|F, 2BP|R|F, 2BP|O|G, and 2BP|R|G [131,132]. Different objective function for the 2BP|O|F and 2BP|R|F are presented in [219]. 2BPs have many practical applications, including cutting (wood, glas) [132], packing (transportation, warehouse) [132], and newspaper page layout [180].

2BP|O|F In the oriented 2BP with free cuts, the rectangles to pack have fixed orientations, i.e., cannot be rotated, but can otherwise be arranged freely [131,132,140,220]. Permutation-based search spaces can be used for this problem by using the Improved Bottom Left (IBL) encoding. The SOTA for this problem comprises [20,25,39,84,157,220].

2BP|O|G In the oriented 2BP with guillotine cuts, the rectangles to pack have fixed orientations, i.e., cannot be rotated, and must be arranged such that they can be extracted by edge-to-edge cuts [131,132].

2BP|R|F In this variant of the 2BP with free cuts, the rectangles to pack can be rotated by 90° if need be and can freely be arranged [17,131,132,219,220]. Besides packing and cutting, this problem also occurs in scheduling and build formation in additive manufacturing [124,161]. The almost-squares-in-almost-squares (Asqas) problem [191] is also a 2BP|R|F. Search spaces based on signed permutations can be used for this problem by using the IBL encoding. The SOTA for this problem comprises [20,39,84,219,220].

2BP|R|G In this variant of the 2BP with guillotine cuts, the rectangles to pack can be rotated by 90° if need be, but must be arranged such that they can be extracted by edge-to-edge cuts [131,132].

ACO *Ant Colony Optimization* is a nature-inspired optimization method for combinatorial problems where solutions are generated by "ants" that move from node to node in a graph choosing edges based on (1) the simulated pheromone on the edges and (2) a per-edge heuristic value [57–59]. If an ant produced a good solution, "pheromone" is distributed over the edges it visited, making it more likely to be re-visited by other ants.

AI Artificial Intelligence, see, e.g., [171]

Glossary III

Asqas An "almost-square" be a rectangle with size $i \times (i+1)$ with $i \in \mathbb{N}_\mathbf{1}$. The *almost-squares-in-almost-squares* problem [191] is a special case of the 2BP|R|F. Here, almost-square rectangles of sizes 1×2, 2×3, $\ldots$, $n \times (n+1)$ must be placed into an almost-square bin without waste. This requires that there exists a natural number $p \in \mathbb{N}_\mathbf{1}$ such that $p(p+1) = \sum_{i=\mathbf{1}}^{n} i(i+1)$ [191]. There are exacty five Asqas instances [191], namely with bin sizes 1×2 for $n = 1$, $p = 1$, 5×4 for $n = 3$, $p = 4$, 15×16 for $n = 8$, $p = 15$, 55×56 for $n = 20$, $p = 55$, and 119×120 for $n = 34$, $p = 119$.

ATSP The general case for TSPs are *asymmetric Traveling Salesperson Problems*, where the $n \times n$ distance matrix A does not need to be symmetric. In other words, it is possible that $\exists a, b \in 1..n$ with $A[a, b] \neq A[b, a]$. Notice that while such index tuple *may* exist, this is not always or necessarily the case. In this case, one may consider the STSP as a special case of the ATSP, while ATSPs may be considered as synonymous to TSPs.

BP The *Bin Packing Problem* [63,173] is one of the classical problems from Operations Research (OR). The goal is to pack a set of objects into containers, using as few containers as possible. Different flavors of BPs can be distinguished, e.g., by the number of dimensions [48,130] that the objects and containers have (see, e.g., the 2BP), and/or whether the objects can be rotated [220], as well as other constraints and limitations. Both the one- and two-dimensional BP are strongly $\mathcal{NP}$-hard [132].

BRKGA The *Biased Random Key Genetic Algorithm* is a EA with a continuous search space $\mathbb{X} \subset [0, 1]^n$ and a decoding function γ translating this space to something else and biased, uniform, and elitist mating strategies [86,135].The *bias* comes from the fact that one of the parents used for the binary operation is biased to be of higher fitness than the other parent [86]. Often, γ is the Random Keys encoding [12,13] procedure translating $\mathbb{X}$ to permutations of the first n natural numbers [85]. Sometimes, it is actually a MA further refining the translation result with a local search (LS) [85]. Sometimes the permutations are then further translated to more complex data structures, such as Gantt charts for the JSSP [85], or packing plans for 2BP 3D packing [84].

C is a programming language, which is very successful in system programming situations [52,165,199].

Concorde is an exact solver for the TSP[4,41,42], which could even solve the largest instance of TSPLib (with 85 900 cities) to optimality.

DB A *database* is an organized collection of structured information or data, typically stored electronically in a computer system. Databases are discussed in our book *Databases* [196].

Glossary IV

DBMS A *database management system* is the software layer located between the user or application and the database (DB). The DBMS allows the user/application to create, read, write, update, delete, and otherwise manipulate the data in the DB [215].

EA An *evolutionary algorithm* is a metaheuristic optimization method that maintains a population of candidate solutions, which undergo selection (where better solutions are chosen with higher probability) and reproduction (where mutation and recombination create a new candidate solution from one or two existing ones, repectively) [7,197].

FFA *Frequency Fitness Assignment* (中文: 频率适应度分配) is a algorithm plugin for optimization methods applied to discrete or combinatorial problems with not-too-many different possible objective values [205,207,208]. It replaces the objective values in all comparisons with their absolute encounter frequency so far during the search. FFA has successfully been applied to the MaxSAT [207,208], the TSP [125,126], and the QAP [36,188], amongst others. Its properties have been intensely researched on discrete benchmark functions such as OneMax, LeadingOnes, Trap, TwoMax, Jump, and Plateau [207,208,217]. The most common realizations of FFA so far are the $(1+1)$ FEA and FRLS.

FSSP The *Flow Shop Scheduling Problem* is a variant of a JSSP where all products go through the same sequence of machines [88,109].

Gantt chart Gantt charts are two-dimensional diagrams illustrating the steps of a process [111,211]. Their horizontal axis represents the time, the vertical axis represents work packages, machines, or workers. In the diagram area, bars located at certain vertical locations indicate that the work package, machine, or worker is processed or works at the time range covered by the bar as projected to the horizontal axis.

GP *Genetic Programming* [115,162,197,203] is the application of metaheuristic optimization, usually in form of an EAs, to a search space comprised of tree data structures. These tree data structures often represent programs or mathematical expressions.

GRASP A *Greedy Randomized Adaptive Search Procedure* is a metaheuristic where each cycle consists of two main components [67,69,70]: First, a starting point is generated using a heuristic method (as opposed to being randomly sampled). Then, a LS is applied to refine the solution. Then, another cycle starts and proceeds in the same way. The overall best solution is retained as result. Many examples of applications of GRASPs are listed in [70]. GRASP in combination with VND has been applied to the 2BP|O|F in [157].

Glossary V

IBL
: The *improved bottom left* heuristic is a one-shot algorithm constructing a solution for 2BP [129]. For the 2BP|O|F problem variant, the input of the IBL algorithm is a permutation of the first n natural numbers, each number identifying one rectangle to be packed. For the 2BP|R|F problem flavor, the permutation elements are signed, where a negative sign indicates a rotation by 90° [129]. In [219,220] it is adapted to a multi-bin situation as follows: The algorithm iterates over the (potentially signed) permutation x and places the rectangles into the packing plan in the prescribed order. It first places the rectangle outside on top of the current bin b, with its bottom-right corner onto the top-right corner of the current bin b. It then moves the rectangle downwards and leftwards as far as possible, prioritizing the downward movement whenever possible. If the rectangle cannot be moved any further, it checks if it is completely contained in the bin b. If yes, it can remain there. Otherwise, a new bin is opened ($b \leftarrow b + 1$) and the rectangle is placed at its bottom-left corner. Once a new bin is opened, this bin is used for all further insertions. IBL is suitable as a decoding function γ inside an EA [129]. Historically, it improves upon the BL algorithm [104]: That algorithm cannot represent all possible optimal packings using a permutation, but the IBL can [129].

ILS
: An *iterated local search* is a variant of the LS which applies cycles of local search and perturbation [181]. First, an initial solution is generated and refined by the local search. Then the cycle begins: A perturbation, i.e., a large search move that likely destroys a good part of the solution, is applied. The resulting new solution is refined by local search. Then, an acceptance criterion decides whether we should use this or the previous solution to continue in the next cycle. ILS has successfully been applied to the QAP.

Ising Model
: The Ising models are benchmark problems for bit-string based black-box search [55,71,72,217]. Here, a neighborhood is defined around each bit. The bit needs to have the same value as all bits in the neighborhood structure T. Thus, we try to achieve that all bits have the same value. The objective function $f(x)$ of the minimization variant of this problem family can be defined as $f(x, T) = \sum_{(i,j)\in T} |x_i - x_j|$, where T contains the index pairs of neighboring bits and is defined differently for the Ising model instances Ising 1D and Ising 2D. The problems are highly epistatic, as all variables interact with some other variables.

Ising 1D
: The 1D is a benchmark problem for bit-string based black-box search [55,72,217]. The bits are arranged in a one-dimensional ring and we try to minimize the number of bits that have different values than their neighbors. Hence, the neighborhood structure T is defined as $T_{\mathbf{1}D} = \{(i+1, (i+1 \bmod n)+1) \mid i \in [0..n-1]\}$. The problems are highly epistatic, as all variables interact with some other variables. The $(1+1)$ EA has an expected runtime in $\mathcal{O}(n^3)$ on 1-Dimensional Ising Model (Ising 1D) [72].

Glossary VI

Ising 2D The 2D is a benchmark problem for bit-string based black-box search [55,71,217]. The bits are arranged in a two-dimensional torus and we try to minimize the number of bits that have different values than their neighbors. Hence, the neighborhood structure $T = T_{2D}$ is defined as the set of all $\{(\alpha + \beta N, \gamma + \delta N)\}$ pairs with $\alpha, \beta, \gamma, \delta \in 0..N-1$ and either $()\gamma = (\alpha + 1) \bmod N$ and $\delta = \beta$) or ($\gamma = \alpha$ and $\delta = (\beta + 1) \bmod N$) with $n = N^2$. The problems are highly epistatic, as all variables interact with some other variables. On a similar class of problems, the $(1 + 1)$ EA has an exponential expected runtime [71].

Java is another very successful programming language, with roots in the C family of languages [24,136].

JSSP The *Job Shop Scheduling Problem* [23,38,88,120] is one of the most prominent and well-studied scheduling tasks. In a JSSP instance, there are m machines and k jobs [182]. Each job must be processed once by each machine in a job-specific sequence and has a job-specific processing time on each machine. The goal is to find an assignment of jobs to machines that results in an overall shortest makespan, i.e., the schedule (Gantt chart) which can complete all the jobs in the shortest time. The JSSP is $\mathcal{NP}$-complete [35,119,120]. The 8 most common sets of JSSP benchmark instances are *abz* [1], *dmu* [49], *ft* [73], *la* [122], *orb* [5], *swv* [179], *ta* [182], and *yn* [214].Their data can be found (sometimes partially) in several repositories, such as the OR-Library [14,15], [175], and [198], the latter of which also contains many results from existing works. Encodings based on permutations with repetition are proposed in [21,22,79,174] and used in [207]. The SOTA of the JSSP includes [85,94,156,158,176,195,218].

Jump The Jump problem is a benchmark problem for bit-string based black-box search [61,76,217]. Like the OneMax, it tries to maximize the number of 1 bits in a bit string of chosen length n. However, the solutions representing the last ω bits around the optimum to flip are deceptive, meaning that they are actually worse and getting worse than surrounding solutions. The objective function $f(x)$ of the minimization variant is $n - \|x\|_1$ if $\|x\|_1 = n$ or $\|x\|_1 \leq n - \omega$ hold, and $\omega + \|x\|_1$ otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. This means that, the larger ω, the larger the deceptive basin around the optimum that an algorithm needs to cross. An $(1 + 1)$ EA will converge to the resulting local optimum and thus have an expected runtime of $\Theta(n^\omega + n \ln n)$ [61].In experiments, the $(1 + 1)$ FEA achieves polynomial runtime on Jump, seemingly in $\mathcal{O}(n^2 \ln n)$ [207,208,217].

Glossary VII

LABS *Low-Autocorrelation Binary Sequences* are bit strings of length n whose autocorrelation is as low as possible [26–28,50,51,77,141,143,149,154,164]. This means that sub-sequences of any length $1 \leq k < n$ should ideally never repeat. The objective function $f : \{0,1\}^n \mapsto \mathbb{N}_0$ represents the energy of a bit string x and is subject to minimization. We can define it as $f(x) = \sum_{k=1}^{n-1} \left(\sum_{i=0}^{n-1-k} s_i \cdot s_{i+k}\right)^2$ with $s_j = 2x_j - 1$. Such sequences are needed for communication engineering [27,28,149], cryptography[50,149], as well as modulation pulses in radar and sonar ranging[154]. The LABS is $\mathcal{NP}$-hard [190]. The SOTA on LABS contains [26,28,50,51,149].

LeadingOnes The LeadingOnes problem is a benchmark problem for bit-string based black-box search [170,210,217]. It tries to maximize the number of *leading* 1 bits in the bit string of a chosen dimension n. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = n - \sum_{i=1}^{n} \prod_{j=1}^{i} x_j$. Different from OneMax, the contribution to the objective value of the bit at index i thus depends on the state of all the bits *before* this index. The problem is unimodal, i.e., has only a single global optimum and no local optimum. Different from OneMax, it is not separable, i.e., we can optimize each variable separately. The expected runtime of $(1+1)$ EA on LeadingOnes is in $\Theta(n^2)$ [61]. The average runtime $(1+1)$ FEA on LeadingOnes seems to be slower by factor proportional to n, i.e., seems to be in $\mathcal{O}(n^3)$ [207].

LK The *Lin-Kernighan* (LK) algorithm [128] is a SLS method for the TSP. The LK algorithm performs iterative k-opt moves, i.e., in each step, it constructs the two sets X and Y of k edges such that removing the edges in X from the current tour T and then adding the edges from Y to T results in a better tour.The LK algorithm is one of the most classical approaches to the TSP.

LKH The *Lin-Kernighan-Helsgaun* algorithm [42,92,93] is a SLS method for the TSP based on the Lin-Kernighan (LK) algorithm [128]. LKH-1 was proposed in [93] and LKH-2 in [92]. It holds the record in the *World TSP* [43] as of 2025.

LS A *local search* is an algorithm where a single "current" candidate solution is maintained and new solutions are selected from its neighborhood in each step. Most LSes are randomized, i.e., stochastic local search (SLS).

MA A *Memetic Algorithm* is an EA where each new solution is refined by a LS before it enters the population [197]. As LS, we can use, e.g., RLS, but TS [37,74] is maybe a better choise. Some SOTA algorithms in some domains may be classified as MAs, e.g., Lin-Kernighan Helsgaun (LKH) basically uses a population that is refined via a local search. MAs also worked well on the JSSP [37,94] and the TSP [74].

Glossary VIII

MaxSAT
: The goal of satisfiability problems is to find an assignment for n Boolean variables that make a given Boolean formula $F : \{0,1\}^n \mapsto \{0,1\}$ become true. In the *Maximum Satisfiability* problem (MaxSAT) [95], F is given in conjunctive normal form, i.e., the variables appear either directly or negated in m "or" clauses, which are all combined into one "and." The objective function $f(x)$, subject to minimization, computes the number of clauses which are false under the variable setting x. If $f(x) = 0$, then all clauses of F are true, which solves the problem. The MaxSAT problem is $\mathcal{NP}$-complete [40] and exhibits low epistasis but deceptiveness [167], making it hard for local searches. Typical benchmark instances can be found in SATLIB, which contains smaller-scale instances, and the up-to-date MaxSAT Evaluation (MSE), providing SOTA benchmarks, algorithms, and results.

metaheuristic
: A *metaheuristic* is an optimization algorithm which performs a cycle of trial and error during which candidate solutions are sampled from the solution space $\mathbb{Y}$ and evaluated using an objective function $f : \mathbb{Y} \mapsto \mathbb{R}$ [82,197]. The results of the objective function are used to decide which solution is promising. The neighborhoods around promising solutions *or* similarly-structured solutions are then sampled in the next cycle. Prominent metaheuristics are SLSes, SA, TS, and EAs.

moptipy
: is the *Metaheuristic Optimization in Python* library [206]. It has been used in several different research works, including [36,125–127,188,213,219,220]. Algorithms implemented by moptipy include EAs, $(1+1)$ EA, RLS, SA, and the $(1+1)$ FEA, amongst others. Learn more at https://thomasweise.github.io/moptipy and https://thomasweise.github.io/moptipyapps.

MSE
: The *MaxSAT Evaluation* is a regularly updated set of benchmark instances for the MaxSAT [101]. It also includes solver software and benchmark results [193].

N-Queens
: The N-Queens Problem is a benchmark problem for bit-string based black-box search [55,217]. The goal is to arrange N queens on an $N \times N$ chessboard so that none can attack the other. The search space has thus dimension $n = N^2$, with each bit standing for a field and encoding whether or not a queen is placed there. The objective function $f(x)$ of the minimization variant is $N - \left(\sum_{i=1}^{n} x_i\right) - N \sum_{\xi} \max\left\{0, Q_\xi(x) - 1\right\}$ where $Q_\xi(x)$ is the number of queens in the horizontal, vertical, or diagonale ξ. The problem is quite epistatic.

Glossary IX

OneMax OneMax is the simplest possible benchmark problem for bit-string based black-box search [62,150,217]. The goal is to maximize the number of 1 bits in the bit string of a chosen dimension n. The objective function $f(x)$ of the minimization variant of this problem can be defined as $f(x) = n - \sum_{i=1}^{n} x_i$. The problem is unimodal, i.e., has only a single global optimum and no local optimum. It is fully separable, i.e., we can optimize each variable separately. The expected runtime of $(1+1)$ EA on OneMax is in $\Theta(n \ln n)$ [53,150]. The average runtime $(1+1)$ FEA on OneMax seems to be slower by factor proportional to n, i.e., seems to be in $\mathcal{O}(n^2 \ln n)$ [207].

OR Operations Research (or Operational Research) is the application of sciences such as mathematics and computer science to the management and organization of systems, organizations, enterprises, factories, or projects. It encompasses the development and application of problem-solving methods and techniques (such as mathematical optimization, simulation, queueing theory and other stochastic models) with the goal to improve decision-making and efficiency [46].

OR-Library is a library of benchmark instances for various OR problems [14,15] located at https://people.brunel.ac.uk/~mastjjb/jeb/info.html. It contains instances of the JSSP, 1D- and 2D-Packing, Knapsack, periodic TSPs, amongst others.

Plateau The Plateau problem is a benchmark problem for bit-string based black-box search [3,217]. It is structured exactly like Jump, but instead of being deceptive, the last ω bits to flip around the optimum are neutral. The objective function $f(x)$ of the minimization variant is $n - \|x\|_1$ if $\|x\|_1 = n$ or $\|x\|_1 \leq n - \omega$ hold, and ω otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. This means that, the larger ω, the larger the neutral plane around the optimum that an algorithm needs to cross. An $(1+1)$ EA has an expected runtime of $\Theta(n^\omega)$ on plateaus [3]. The average runtime of the $(1+1)$ FEA on Plateaus is slower by a factor seemingly proportional in n.

PostgreSQL An open source object-relational DBMS [68,153,163,186]. See https://postgresql.org for more information.

Python The Python programming language [98,123,137,200], i.e., what you will learn about in our book [200]. Learn more at https://python.org.

Glossary X

QAP The *Quadratic Assignment Problem* is an optimization problem where the goal is to assign a set of n facilities to a set of n locations [30,36,114,133]. Such an assignment can be represented as a permutation x of the first n natural numbers, where x_i specifies the location where facility i should be placed. For each QAP instance, a distance matrix A is given, where $A[a, b]$ specifies the distance from location a to location b, as well as a flow matrix B, where $B[i, j]$ is the amount of material flowing (e.g., daily) from facility i to facility j. The objective function $f(x)$ then rates a permutation x as $f(x) = \sum_{i=1}^{n} \sum_{j=1}^{n} A[x_i, x_j] * B[i, j]$. The QAP is $\mathcal{NP}$-complete [60,172] and even among this problem class, is considered as particularly hard for metaheuristics [16,30,133,181]. The QAP has applications such as building layout [44,65,116], keyboard layout [32], circuit design [66], wiring [178], and scheduling [177]. Typical benchmark instances can be found in QAPLIB. SOTA algorithms for the QAP include [16,74,142,147,184,185].

QAPLIB is a library of 136 benchmark instances for the Quadratic Assignment Problem (QAP) [29,31], 28 of which have not yet been solved to optimality [2] (at least by 2023).

Random Keys encoding is a decoding procedure $\gamma : \mathbb{X} \mapsto \mathbb{Y}$ that maps a continuous search space $\mathbb{X} \subset [0, 1]^n$ which is a subset of the n-dimensional real numbers to the space $\mathbb{Y}$ of permutations of the first n natural numbers [12,13]. For example, on $n = 5$, the vector $x = (0.49, 0.91, 0.33, 0.75, 0.51)$ is translated to the permutation $y = (3, 1, 5, 4, 2)$, because $x_{\mathbf{3}} = 0.33$ has the smallest value, putting 3 at the beginning, $x_{\mathbf{1}} = 0.49$ the second-smallest, placing 1 second, ..., and $x_{\mathbf{2}} = 0.91$ being the largest value meaning that the last number in y will be 2 [13]. The advantage of the encoding is that we can search in $\mathbb{X}$ applying arbitrary mathematical operators, crossover, and mutation procedures, but will always get correct permutations. The disadvantage is that $|\mathbb{X}| \gg |\mathbb{Y}|$ and that there actually is no meaning underpinning moves in $\mathbb{X}$ in relation to their projected result in $\mathbb{Y}$.

RLS Randomized local search retains the best solution x_c discovered so far during the search and, in each step, it applies a unary search operator to this best-so-far solution x_c and derives a new solution x_n. If the new solution x_n is *better or equally good* when compared with x_c, i.e., not worse, then it replaces it, i.e., is stored as the new x_c. If the search space are bit strings of length n, then RLS uses a unary search operator that flips exactly one bit. This operator is the main difference to $(1 + 1)$ EA.

FRLS The RLS with FFA plugged in [217]. On the discrete bit-string domains, this algorithm has a very specific structure: Its unary search operator flips exactly one bit, distinguishing it from the unary operator in the $(1 + 1)$ FEA, which flips each bit with probability $1/n$. On other domains, such as permutations, we use the term synonymously with $(1 + 1)$ FEA.

Glossary XI

RTS *Reactive Tabu Search* is a variant of TS where the length of the tabu list is adapted to the problem and to the current evolution of the search, and an escape strategy for diversifying the search is used when that is not sufficient [8–11]. It has successfully been applied to a wide range of problems, from the QAP [9,10], to Knapsack problems [8,10], the N-K landscape [8] to the training of neural networks [11].

SA *Simulated Annealing* is a SLS that sometimes accepts a worse solution [34,103,110,160,197]. The probability to do so decreases over time and with the difference in objective values, i.e.,is the lower the worse the new solution is. SA performed well on a variety of problems, including the QAP [145,189] and the JSSP [156].

SATLIB is a library of benchmark instances for the Maximum Satisfiability (MaxSAT) available at https://www.cs.ubc.ca/~hoos/SATLIB/index-ubc.html [96,97].

SLS *Stochastic local search* is a local search (LS), one of the simplest metaheuristic search paradigms [95]: A single "current" candidate solution is maintained and new solutions are *stochastically* sampled from its neighborhood, i.e., in a way that involves random numbers. If these solutions are deemed interesting based on their objective value, they replace the "current". The cycle continues. Basic examples are RLS and $(1+1)$ EA. More complex examples that add mechanisms to escape local optima on top of the SLS paradigm are TS and SA.

SOTA State-of-the-Art, i.e., the best-performing methods for a field or problem type

STSP A *symmetric Traveling Salesperson Problem* is a special case of the TSP, where the $n \times n$ distance matrix A is symmetric, i.e., $A[a,b] = A[b,a] \forall a,b \in 1..n$.

Trap The Trap problem is a benchmark problem for bit-string based black-box search [61,151,217]. It is structured exactly like OneMax, however the worst and the best solution are swapped. This makes the problem highly deceptive, as following the "gradient" in the search space leads the search away from the global optimum. For bit strings of length n, the objective function $f(x)$ of the minimization variant is 0 if $\|x\|_{\mathbf{1}} = 0$ and $n - \|x\|_{\mathbf{1}} - 1$ otherwise, where $\|x\|_{\mathbf{1}} = \sum_{i=\mathbf{1}}^{n} x_i$. An $(1+1)$ EA will converge to the resulting local optimum and thus have an expected runtime of $\Theta(n^n)$ [61]. In experiments, the $(1+1)$ FEA achieves polynomial runtime on Trap, seemingly in $\mathcal{O}(n^{\mathbf{2}} \ln n)$ [207,208,217].

Glossary XII

TS *Tabu Search* is one of the most successful SLSes [80,81,83,105]. In order to avoid returning to previous solutions, it declares certain solutions or search moves as "tabu." For example, if a bit in a discrete problem has been flipped by the search operator, it may be forbidden to flip the bit again for some time, thus preventing the algorithm from getting trapped in a cycle. This rule may be overridden if a new best-so-far solution is discovered that outperforms all previous solutions, in which case it would be accepted (this is the so-called aspiration criterion). TS has performed well on the QAP [9,10,144,147,183,184] and on the JSSP [152,158,159,176,218].

TSP In an instance of the *Traveling Salesperson Problem*, also known as *Traveling Salesman Problem*, a set of n cities or locations as well as the distances between them are given [4,90,121,125,201,209]. The goal is to find the shortest round-trip tour that starts at one city, visits all the other cities one time each, and returns to the origin. The TSP is one of the most well-known $\mathcal{NP}$-hard combinatorial optimization problems [78,90,117]. The TSP has many applications[4], including in transportation, logistics, (circuit) plotting and drilling problems[89], telescope aiming, and genome sequencing. Solutions are often encoded as permutations x of the first n natural numbers, where each city gets a number and the order of numbers in the permutation corresponds to the order of cities in the tour. The distances between the n cities are usually given in a $n \times n$ distance matrix A, where $A[a, b]$ is the distance from city a to city b with $a, b \in 1..n$. Then, the objective function subject to minimization is $f(x) = A[x_n, x_{\mathbf{1}}] + \sum_{i=\mathbf{1}}^{n-\mathbf{1}} A[x_i, x_{i+\mathbf{1}}]$. Typical benchmark instances can be found in TSPLib [168,169], the 8th DIMACS challenge[106–108], and the *World TSP* repository[43].

TSPLib is a library of benchmark instances for the Traveling Salesperson Problem (TSP) [168,169]. Its original URL was available until 2025 and then became defunct. The repository https://github.com/shredderzwj/TSPLIB contains the data. Additionally, you may also check https://github.com/thomasWeise/tspSuite, which contains all the TSPLib instances as well as Java code to load them. The TSPLib contains 110 instances of the symmetric Traveling Salesperson Problems (STSPs) with scales n ranging from 14 to 85 900, but 93 instances have less than 2000 nodes. There also are 19 asymmetric Traveling Salesperson Problems (ATSPs) with scales $n \in 17..443$.

Glossary XIII

TTP The *Traveling Tournament Problem* is the combinatorial optimization problem of both efficiently and fairly organizing a tournament of n teams that play against each other in a pairwise fashion [64,213]. The efficient part boils down to arranging the games such that the total travel length is short, which is somewhat similar to the classical TSP. Initially, each team is at its home location. On each day, a team needs to travel if its scheduled game is not at its present location. On the last day, each team may need to travel back home unless their last game is a home game. The total travel length sums up the lengths of all travels over all teams. The fair part is represented in several constraints, such as doubleRoundRobin, compactness, maxStreak, and noRepeat. The TTP is $\mathcal{NP}$-hard [194].

TwoMax The TwoMax problem is a benchmark problem for bit-string based black-box search [76,192,217]. It has a global and a local optimum, both of about the same size, at opposite ends of the search space. For bit strings of length n, the objective function $f(x)$ of the minimization variant is 0 if $\|x\|_1 = n$ and $1 + n - \max\left\{\|x\|_1, n - \|x\|_1\right\}$ otherwise, where $\|x\|_1 = \sum_{i=1}^{n} x_i$. An $(1+1)$ EA has a 50/50 chance to converge to the local or global optimum and thus has an expected runtime in $\Theta(n^n)$ [75,76]. In experiments, the $(1+1)$ FEA achieves polynomial runtime seemingly in $\mathcal{O}(n^2 \ln n)$ on TwoMax [207,208,217].

URI A *Uniform Resource Identifier* is an identifier for an abstract or physical resource in the internet [216]. It can be a URL, a name, or both. URIs are supersets of URLs. The connection strings of the PostgreSQL DBMS are examples of Uniform Resource Identifiers (URIs).

URL A *Uniform Resource Locator* identifies a resource in the World Wide Web (WWW) and a way to obtain it by describing a network access mechanism. The most notable example of URLs is the text you write into web browsers to visit websites [19]. URLs are subsets of URIs.

VND *Variable Neighborhood Descend*; see VNS. VND in combination with GRASP has been applied to the 2BP|O|F in [157].

Glossary XIV

VNS *Variable Neighborhood Search* is a metaheuristic framework combining a systematic change of neighborhood with LS [91,148]. A *neighborhood* structure in LS defines which solutions can be reached from a given solution within one search step. Usually, one uses a single unary operator and, hence, has a single neighborhood structure. However, for many problems, we can easily design many operators. For permutations, for example, one operator may swap two elements, another one may reverse a section of the permutation, and yet another one, while yet another one may rotate a subsequence one step to the left or right [201]. In the VNS framework, a multiple neighborhoods are investigated in a systematic fashion. Assume that we have a list of neighborhood structures. Variable Neighborhood Descend (VND) works in a deterministic fashion. It finds the best solution that can be reached in one step from the current solution under the current neighborhood. If this is better than the current solution, we accept it and continue with the first neighborhood. Otherwise, we continue with the next neighborhood in the list. In Basic VNS, instead of picking the best move from the current neighborhood, the first improving move is used. Also, at the beginning of each cycle, a random point from the current neighborhood around the current solution is chosen as starting point.

WWW World Wide Web [18,47]

$\circ^\star$ the superscript $\star$ symbol denotes that $\circ$ is a global optimum, i.e., there is no better solution than $\circ$.

$i..j$ with $i, j \in \mathbb{Z}$ and $i \leq j$ is the set that contains all integer numbers in the inclusive range from i to j. It always holds that $i..j \subset \mathbb{Z}$. For example, 5..9 is equivalent to $\{5, 6, 7, 8, 9\}$

A the $n \times n$ distance matrix. $A[a, b]$ indicates the distance between locations a and b with $a, b \in 1..n$. A distance matrix can be symmetric, in which case $A[a, b] = A[b, a]\ \forall a, b \in 1..n$. Distance matrices represent the problem instance data in TSPs and part of the instance data of QAPs.

B the $n \times n$ flow matrix. $B[a, b]$ is the flow of goods between locations a and b with $a, b \in 1..n$. Flow matrices are one half of the problem instance data of QAPs.

Glossary XV

$f(y)$ The *objective function* $f : \mathbb{Y} \mapsto \mathbb{R}$ can compute a cost or rating for each candidate solution y in the solution space $\mathbb{Y}$. The smaller this value, the better the solution, i.e., in the context of this work, objective functions are subject to minimization. Objective functions are not necessarily continuous and it is also quite common that they have integer or natural numbers as results, e.g., we often have $f : \mathbb{Y} \mapsto \mathbb{N}_0$ instead of $f : \mathbb{Y} \mapsto \mathbb{R}$.

$\gamma(x)$ The decoding function $\gamma : \mathbb{X} \mapsto \mathbb{Y}$ translates point from the search space $\mathbb{X}$ to one point y in the solution space $\mathbb{Y}$. It is a very common case that $\mathbb{X} = \mathbb{Y}$ and that the decoding function γ is the identity mapping. Examples for encodings that translate from a simple search space $\mathbb{X}$ to a complex solution data structure $\mathbb{Y}$ are the IBL algorithm that translates (potentially signed) permutations to two-dimensional packings on the 2BP, the permutation-based encoding of Gantt charts for the JSSP from [21,22,79,174,202], or the permutation-based encoding of game plans for the TTP from [213]. Encodings can also translate between types of search spaces. The Random Keys encoding, for example, translates from $[0, 1]^n$ to permutations of the first n natural numbers..

k the number of jobs in an instance of the JSSP.

m the number of machines in an instance of the JSSP.

n We usually use the value $n \in \mathbb{N}_0$ to denote the *scale*, i.e., the size of the problem to solve. This notion is very general in computer science and not limited to optimization. For example, if we sort a list or search in a list, the scale n is the length of the list, i.e., the number of elements in it. In a TSP, this may be the number of cities. In a discrete benchmark problem such as OneMax or Trap, this may be the number of bits over which the problem is defined. In a QAP, this may be the number of facilities and locations. In a MaxSAT problem, this may be the number of variables that are input to the Boolean formula that we want to become true. There are also problems where the scale is not defined straightforwardly like this. For example, in a JSSP, we have a number of machines and a number of jobs, which together define the size of the problem. But even then, the scale n relates to the size of the solution space $\mathbb{Y}$, and, hence, also of the search space $\mathbb{X}$, which usually grow exponentially with n. And this is already the main issue: The larger n, the (exponentially) larger the number of possible solutions and thus, the larger the runtime of algorithms..

Glossary XVI

$\mathbb{N_0}$ the set of the natural numbers *including* 0, i.e., 0, 1, 2, 3, and so on. It holds that $\mathbb{N_0} \subset \mathbb{Z}$ and that $\mathbb{N_0} = \mathbb{N_1} \cup \{0\}$.

$\mathbb{N_1}$ the set of the natural numbers *excluding* 0, i.e., 1, 2, 3, 4, and so on. It holds that $\mathbb{N_1} \subset \mathbb{Z}$ and that $\mathbb{N_1} = \mathbb{N_0} \setminus \{0\}$.

$\mathcal{NP}$ is the class of computational problems that can be solved in polynomial time by a non-deterministic machine and can be verified in polynomial time by a deterministic machine (such as a normal computer) [87].

$\mathcal{NP}$-complete A decision problem is $\mathcal{NP}$-complete if it is in $\mathcal{NP}$ and all problems in $\mathcal{NP}$ are reducible to it in polynomial time [87,166]. A problem is $\mathcal{NP}$-complete if it is $\mathcal{NP}$-hard and if it is in $\mathcal{NP}$.

$\mathcal{NP}$-hard A problem is $\mathcal{NP}$-hard if all problems in $\mathcal{NP}$ are reducible to it in polynomial time [87]. Algorithms that guarantee to find the correct solutions of $\mathcal{NP}$-hard problems [35,40,120] have a worst-case runtime that grows exponentially with the problem scale.

$\mathbf{\Omega}(g(x))$ If $f(x) = \mathbf{\Omega}(g(x))$, then there exist positive numbers $x_\mathbf{0} \in \mathbb{R}^+$ and $c \in \mathbb{R}^+$ such that $f(x) \geq c * g(x) \geq 0 \forall x \geq x_\mathbf{0}$ [112,113]. In other words, $\mathbf{\Omega}(g(x))$ describes a lower bound for function growth.

$\mathcal{O}(g(x))$ If $f(x) = \mathcal{O}(g(x))$, then there exist positive numbers $x_\mathbf{0} \in \mathbb{R}^+$ and $c \in \mathbb{R}^+$ such that $0 \leq f(x) \leq c * g(x) \forall x \geq x_\mathbf{0}$ [6,112,113,118]. In other words, $\mathcal{O}(g(x))$ describes an upper bound for function growth.

$\mathbf{\Theta}(g(x))$ If $f(x) = \mathbf{\Theta}(g(x))$, then $f(x) = \mathcal{O}(g(x))$ and $f(x) = \mathbf{\Omega}(g(x))$ [112,113]. In other words, $\mathbf{\Theta}(g(x))$ describes an exact order of function growth.

$\mathbb{R}$ the set of the real numbers.

$\mathbb{R}^+$ the set of the positive real numbers, i.e., $\mathbb{R}^+ = \{x \in \mathbb{R} : x > 0\}$.

$\mathbb{Y}$ the set of candidate solutions of an optimization problem is called the *solution space* $\mathbb{Y}$. The solution space corresponds to the data structure holding the candidate solutions y. These are the elements that are passed to the user after the optimization process is completed. They are also the parameters of the objective function(s) $f : \mathbb{Y} \mapsto \mathbb{R}$.

y a candidate solution $y \in \mathbb{Y}$ is one possible solution to an optimization problem. After the optimization process is completed, one or multiple such solutions are passed to the user.

$\mathbb{Z}$ the set of the integers numbers including positive and negative numbers and 0, i.e., . . . , -3, -2, -1, 0, 1, 2, 3, . . . , and so on. It holds that $\mathbb{Z} \subset \mathbb{R}$.