
COMPRESSION UNION M

15mm (1/2") Compression x Male 3/4", nylon olive, L

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **54034LF**





SIZING CHART (MM)

Part No.	L	W1	W2	TH1	TH2
54034LF		27.0	25.0	1/2" copper tube	R 3/4"

L = overall length assembled. W1 = body hex across flats. W2 = compression nut across flats. TH1 = tube end. TH2 = other end. All dimensions in millimetres.

SPECIFICATIONS

Connection **1/2" copper tube x R 3/4" male**

Maximum Pressure Rating **1600 kPa**

Working Temperature **1°C to 95°C**

MATERIAL CHART

Part	Material
Body	DR Lead Free Brass (CW511L)
Compression nut	DR Lead Free Brass (CW511L)
Olive	Nylon

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002387**
Certified to **AS 3688**
Lead Free

FEATURES

WaterMark Lead Free Approved

DR Lead Free Brass (CW511L) to AS 2345

Nylon olive included

Tested and certified to AS 3688

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.