
COMPRESSION ELBOW

20mm (3/4") Compression x Female 1/2", nylon oliv

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **54056LF**



Product photo to come

SIZING CHART (MM)

Part No.	L	H	W	TH1	TH2
54056LF		43.0	30.6	3/4" copper tube	G 1/2"

L = back of body to compression nut face, assembled. H = back of body to thread face. W1 = body hex across flats. W2 = compression nut across flats. TH1 = tube end. TH2 = threaded end. All dimensions in millimetres.

STANDARDS & APPROVALS

Lead Free

WaterMark Licence WM-002387
Certified to AS 3688
Lead Free

SPECIFICATIONS

Connection **3/4" copper tube x G 1/2" female**

Maximum Pressure Rating **1600 kPa**

Working Temperature **1°C to 95°C**

FEATURES

- WaterMark Lead Free Approved
- DR Lead Free Brass (CW511L) to AS 2345
- Nylon olive included
- Tested and certified to AS 3688

MATERIAL CHART

Part	Material
Body	DR Lead Free Brass (CW511L)
Compression nut	DR Lead Free Brass (CW511L)
Olive	Nylon

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.