
FLARE UNION FEMALE


20mm (3/4") 60° Flare x G 3/4" Female Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **56046LF**







SIZING CHART (MM)

Part No.	L	H	W	TH1	TH2
56046LF		36.4	31.5	G 3/4" 60° flare	G 3/4"

L = overall length assembled. H = overall height (largest hex across corners). W = largest hex across flats. TH1 = flare nut thread. TH2 = body end. All dimensions in millimetres.

SPECIFICATIONS

Connection **G 3/4" 60° flare x G 3/4" female**

Maximum Pressure Rating **1600 kPa**

Working Temperature **1°C to 95°C**

MATERIAL CHART

Part	Material
Body	DR Lead Free Brass (CW511L)
Flare nut	DR Lead Free Brass (CW511L)

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002387**
Certified to **AS 3688**
Lead Free

FEATURES

- WaterMark Lead Free Approved
- DR Lead Free Brass (CW511L) to AS 2345
- 60° cone flare seat
- Tested and certified to AS 3688

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.