
# REDUCING ADAPTOR

4 × 6mm (1/8" x 1/4") Male x Female Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **50003TLF**







## SIZING CHART (MM)

| Part No. | L | W | TH1 | TH2 |
|---|---|---|---|---|
| 50003TLF | 26.9 | 16.0 | R 1/8" | G 1/4" |

L = overall length. W = hex across flats. TH1 = male thread. TH2 = female thread. All dimensions in millimetres.

## SPECIFICATIONS

Working Temperature **1°C to 95°C**

Maximum Pressure Rating **1600 kPa**

Connection **R 1/8" male x G 1/4" female**

## MATERIAL CHART

| Part | Material |
|---|---|
| Adaptor | DR Lead Free Brass (CW511L) |

## STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WMKA02551**
Certified to **AS 3688**
Lead Free

## FEATURES

WaterMark Lead Free Approved

DR Lead Free Brass (CW511L) to AS 2345

Threads to AS ISO 7.1

Tested and certified to AS 3688


For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au


ISO 9001 Certified
Quality Management System


Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.