
REDUCING NIPPLE

32 × 25mm (1¼" x 1") BSPT Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **50296TLF**





SIZING CHART (MM)

Part No.	L	H	W	TH1	TH2
50296TLF	47.0	9.2	43.2	R 1-1/4"	R 1"

L = overall length. H = hex length. W = hex across flats. TH1 = large thread. TH2 = small thread. All dimensions in millimetres.

SPECIFICATIONS

Working Temperature **1°C to 95°C**

Maximum Pressure Rating **1600 kPa**

Connection **R 1-1/4" male x R 1" male** (BSPT taper)

MATERIAL CHART

Part	Material
Nipple	DR Lead Free Brass (CW511L)

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WMKA02551**
Certified to **AS 3688**
Lead Free

FEATURES

WaterMark Lead Free Approved

DR Lead Free Brass (CW511L) to AS 2345

Threads to AS ISO 7.1

Tested and certified to AS 3688

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.