
TPFNR FERRULE COCK

40 × 50mm Male x Union Capped Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **71315LF**





SIZING CHART (MM)

Part No.	L1	L2	H1	H2	W	TH1	TH2
71315LF		112.8	81.5			R 1-1/2"	G 2"

L1 = tapping port face to centreline. L2 = centreline to outlet face. H1 = outlet centreline to inlet end. H2 = overall height. W = body width. All dimensions in millimetres.

SPECIFICATIONS

Connection **R 1½" male (inlet) x G 2" male union (outlet)**

Test pressure **2500 kPa**

Working Temperature **1°C to 95°C**

MATERIAL CHART

Part	Material
Body	Lead Free Gunmetal
Cap	Capped top, Lead Free Brass
Tapping port plug	Plastic cap insert
Bush / washers	Brass / fibre

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002386**
Certified to **AS 3718**
Lead Free

FEATURES

- WaterMark Lead Free Approved
- Lead Free Gunmetal body
- Tapping Pressure Ferrule No Return
- Suits live (hot) tapping
- Tested and certified to AS 3718

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.