
STOPCOCK

50mm (2") Female x Female Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **71075LF**





SIZING CHART (MM)

Part No.	L	H	W	TH1	TH2
71075LF	139.0		71.0	G 2"	G 2"

L = overall length. H = pipe centreline to top of handle. W = end hex across flats. TH1 / TH2 = end connections. All dimensions in millimetres.

SPECIFICATIONS

Connection **G 2" female x G 2" female**

Test pressure **1500 kPa**

Working Temperature **1°C to 95°C**

MATERIAL CHART

Part	Material
Body	DR Lead Free Brass (CW511L)
Top section	71157LF (DR Lead Free Brass)
Jumper valve	DR Lead Free Brass, rubber washer
Bonnet washer	Red fibre

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002386**
Certified to **AS 3718**
Lead Free

FEATURES

- WaterMark Lead Free Approved
- DR Lead Free Brass (CW511L) to AS 2345
- Replaceable top section and jumper valve
- Tested and certified to AS 3718

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.