
STANDARD FERRULE

25 × 32mm Male x Union Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **R11302LF**





SIZING CHART (MM)

Part No.	L	H1	H2	W	TH1	TH2
R11302LF	53.75				R 1"	G 1-1/4"

L = centreline to outlet face. H1 = outlet centreline to inlet end. H2 = overall height. W = body width. All dimensions in millimetres.

SPECIFICATIONS

Connection **R 1" male (inlet) x G 1¼" male union (outlet)**

Test pressure **1500 kPa**

Working Temperature **1°C to 95°C**

MATERIAL CHART

Part	Material
Body	DR Lead Free Brass (CW511L)
Bonnet / top section	71165LF (DR Lead Free Brass)

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002386**
Certified to **AS 3718**
Lead Free

FEATURES

- WaterMark Lead Free Approved
- DR Lead Free Brass (CW511L) to AS 2345
- Standard ferrule for dry tapping
- Tested and certified to AS 3718

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.