
CONNECTOR NO.68

20mm (3/4") Tube x G 1" BSP Nut Lead Free

PRODUCT DATA SHEET

Thomas Gooden
Foundry Services

Part number **52445LF**





SIZING CHART (MM)

Part No.	L	H	W	D	TH
52445LF		45.3	39.2	19.07 - 19.17	G 1"

L = overall length assembled. H = overall height (nut across corners). W = nut across flats. D = capillary socket bore for copper tube (min - max). TH = nut female thread. All dimensions in millimetres.

STANDARDS & APPROVALS

Lead Free

WaterMark Licence **WM-002387**
Certified to **AS 3688**
Lead Free

SPECIFICATIONS

Working Temperature **1°C to 95°C**

Maximum Pressure Rating **1600 kPa**

Connection **3/4" copper tube (capillary) x G 1" female nut**

FEATURES

WaterMark Lead Free Approved

DR Lead Free Brass (CW511L) to AS 2345

Threads to AS 1722.2

Tested and certified to AS 3688

MATERIAL CHART

Part	Material
Connector	DR Lead Free Brass (CW511L)

For more information on **Thomas Gooden** products, contact:
Thomas Gooden Foundry Services
12 Stonny Batter Road, Minto NSW 2566 Australia
P. (02) 9603 9988 E. sales@thomasgooden.com.au
thomasgooden.com.au

ISO 9001 Certified
Quality Management System

Thomas Gooden Foundry Services Pty Ltd. All rights reserved 2026.
Specifications subject to change without notice. Drawing not to scale.