

```
//-----Extend Thread

class Runner extends Thread{

    @Override
    public void run() {
        for (int i = 0; i < 10; i++)
        {
            System.out.println("Hello " + i);
            try {
                Thread.sleep(100);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }
        }
    }
}

public class App {
    public static void main(String args[]){
        Runner runner1 = new Runner();
        runner1.start();
        Runner runner2 = new Runner();
        runner2.start();
    }
}

//-----implements Runnable

class Runner implements Runnable{ // interface public void

    @Override
    public void run() {
        // TODO Auto-generated method stub
        for (int i = 0; i < 10; i++)
            System.out.println("Hello " + i);
        try {
            Thread.sleep(100);
        } catch (InterruptedException e) {
            // TODO Auto-generated catch block
            e.printStackTrace();
        }
    }
}

public class App {

    /**
     * @param args
     */
    public static void main(String[] args) {
        // TODO Auto-generated method stub
    }
}
```

```
        Thread t1 = new Thread(new Runner());
        Thread t2= new Thread(new Runner());
        t1.start();
        t2.start();

    }

}
//-----Anonymous class extends Thread

public class App {

    /**
     * @param args
     */
    public static void main(String[] args) {

        Thread t1 = new Thread(new Runnable() { //Anonymous class for interface

            @Override
            public void run() {
                for (int i = 0; i < 10; i++)
                {
                    System.out.println("Hello " + i);
                    try {
                        Thread.sleep(100);
                    } catch (InterruptedException e) {
                        e.printStackTrace();
                    }
                }
            }

        });
        t1.start();
    }

}

//-----UDPServer.java
//home/tovantran/Ctest/UDPServer.java --> 2015-03-14 by ./tv owner: tovantran

//https://systembash.com/a-simple-java-udp-server-and-udp-client/
//ip=localhost port=9876
//package socket.udpserver;

//import java.io.*;
import java.net.*;

class UDPServer
{
    public static void main(String args[]) throws Exception
```

```
{
    DatagramSocket serverSocket = new DatagramSocket(9876);
    byte[] receiveData = new byte[1024];
    byte[] sendData = new byte[1024];
    while(true)
    {
        DatagramPacket receivePacket = new DatagramPacket(receiveData, receiveData.length);
        serverSocket.receive(receivePacket);
        String sentence = new String( receivePacket.getData());
        // convert byte to String
        System.out.println("RECEIVED: " + sentence);
        InetAddress IPAddress = receivePacket.getAddress();
        int port = receivePacket.getPort();
        String capitalizedSentence = sentence.toUpperCase();
        sendData = capitalizedSentence.getBytes();
        DatagramPacket sendPacket =
            new DatagramPacket(sendData, sendData.length, IPAddress, port);
        serverSocket.send(sendPacket);
    }
}

//-----UDPClient.java
//home/tovantran/Ctest/UDPClient.java --> 2015-03-14 by ./tv owner: tovantran

//https://systembash.com/a-simple-java-udp-server-and-udp-client/
//ip=localhost port=9876

//package socket.udpclient;

import java.io.*;
import java.net.*;

class UDPClient
{
    public static void main(String args[]) throws Exception
    {
        BufferedReader inFromUser =
            new BufferedReader(new InputStreamReader(System.in));
        DatagramSocket clientSocket = new DatagramSocket();
        InetAddress IPAddress = InetAddress.getByName("localhost");
        byte[] sendData = new byte[1024];
        byte[] receiveData = new byte[1024];
        for (int i = 0; i < sendData.length; i++){
            sendData[i] = 0x41;
        }
        String sentence = inFromUser.readLine();
        sendData = sentence.getBytes();
        DatagramPacket sendPacket = new DatagramPacket(sendData, sendData.length, IPAddress, 9876);
        clientSocket.send(sendPacket);
        DatagramPacket receivePacket = new DatagramPacket(receiveData, receiveData.length);
```

```
        clientSocket.receive(receivePacket);
        String modifiedSentence = new String(receivePacket.getData());
        System.out.println("FROM UDP SERVER:" + modifiedSentence);
        clientSocket.close();
    }
}

//-----TCPServer.java
//home/tovantran/Ctest/TCPServer.java --> 2015-03-14 by ./tv owner: tovantran

//https://systembash.com/a-simple-java-tcp-server-and-tcp-client/
//package mythread.tcpserver;

import java.io.*;
import java.net.*;

class TCPServer
{
    public static void main(String argv[]) throws Exception
    {
        String clientSentence;
        String capitalizedSentence;
        ServerSocket welcomeSocket = new ServerSocket(6789);
        // ServerSocket only port
        while(true)
        {
            Socket connectionSocket = welcomeSocket.accept();
            BufferedReader inFromClient =
                new BufferedReader(new InputStreamReader(connectionSocket.getInputStream()));
            DataOutputStream outToClient = new DataOutputStream(connectionSocket.getOutputStream());
            clientSentence = inFromClient.readLine();
            System.out.println("Received: " + clientSentence);
            capitalizedSentence = clientSentence.toUpperCase() + '\n';
            outToClient.writeBytes(capitalizedSentence);
        }
    }
}

//-----TCPClient.java
//home/tovantran/Ctest/TCPClient.java --> 2015-03-14 by ./tv owner: tovantran

//https://systembash.com/a-simple-java-tcp-server-and-tcp-client/
//package mythread.tcpclient;

import java.io.*;
import java.net.*;

class TCPClient
{
    public static void main(String argv[]) throws Exception
    {
```

```
String sentence;
String modifiedSentence;
BufferedReader inFromUser = new BufferedReader( new InputStreamReader(System.in));
Socket clientSocket = new Socket("localhost", 6789); //Socket(client) host and port
DataOutputStream outToServer = new DataOutputStream(clientSocket.getOutputStream());
BufferedReader inFromServer = new BufferedReader(new InputStreamReader(clientSocket.getInputStream()))
sentence = inFromUser.readLine();
outToServer.writeBytes(sentence + '\n');
modifiedSentence = inFromServer.readLine();
System.out.println("FROM TCP SERVER: " + modifiedSentence);
clientSocket.close();
}
}
//-----AppSingleThreadedServer.java
//package mythread.tcp.runnable;

import java.net.ServerSocket;
import java.net.Socket;
import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStream;

class SingleThreadedServer implements Runnable{

    protected int          serverPort    = 6789;
    protected ServerSocket serverSocket = null;
    protected boolean       isStopped    = false;
    protected Thread        runningThread= null;

    public SingleThreadedServer(int port){
        this.serverPort = port;
    }

    public void run(){
        synchronized(this){
            this.runningThread = Thread.currentThread();
        }
        openServerSocket();

        while(! isStopped()){
            Socket clientSocket = null;
            try {
                clientSocket = this.serverSocket.accept();
            } catch (IOException e) {
                if(isStopped()) {
                    System.out.println("Server Stopped.") ;
                    return;
                }
            }
        }
    }
}
```

```
        throw new RuntimeException(
            "Error accepting client connection", e);
    }
    try {
        processClientRequest(clientSocket);
    } catch (IOException e) {
        //log exception and go on to next request.
    }
}

System.out.println("Server Stopped.");
}

private void processClientRequest(Socket clientSocket) throws IOException {
    String clientSentence;
    InputStream input = clientSocket.getInputStream();
    OutputStream output = clientSocket.getOutputStream();
    BufferedReader inFromClient =
        new BufferedReader(new InputStreamReader(clientSocket.getInputStream()));
    long time = System.currentTimeMillis();

    clientSentence = inFromClient.readLine();
    System.out.println("FROM CLIENT: " + clientSentence);

    output.write(("HTTP/1.1 200 OK\n\n<html><body>" +
        "Singlethreaded Server: " +
        time +
        "</body></html>").getBytes());

    output.close();
    input.close();
    System.out.println("Request processed time: " + time);
}

private synchronized boolean isStopped() {
    return this.isStopped;
}

public synchronized void stop(){
    this.isStopped = true;
    try {
        this.serverSocket.close();
    } catch (IOException e) {
        throw new RuntimeException("Error closing server", e);
    }
}

private void openServerSocket() {
    try {
        this.serverSocket = new ServerSocket(this.serverPort);
    } catch (IOException e) {

```

```
        throw new RuntimeException("Cannot open port 6789", e);
    }
}

public class AppSingleThreadedServer {
    public static void main(String args[]){
        SingleThreadedServer server = new SingleThreadedServer(6789);
        new Thread(server).start();

        try {
            Thread.sleep(10 * 10000);
        } catch (InterruptedException e) {
            e.printStackTrace();
        }
        System.out.println("Stopping Server");
        server.stop();
    }
}

//-----AppMultiThreadedServer.java
//package mythread.tcp.multithreaded.runnable;

import java.net.ServerSocket;
import java.net.Socket;
import java.io.IOException;

//import mythread.tcp.runnable.SingleThreadedServer;

class MultiThreadedServer implements Runnable{

    protected int          serverPort    = 6789;
    protected ServerSocket serverSocket = null;
    protected boolean      isStopped    = false;
    protected Thread       runningThread= null;

    public MultiThreadedServer(int port){
        this.serverPort = port;
    }

    public void run(){
        synchronized(this){
            this.runningThread = Thread.currentThread();
        }
        openServerSocket();
        while(! isStopped()){
            Socket clientSocket = null;
            try {
                clientSocket = this.serverSocket.accept();
            }
        }
    }
}
```

```
        } catch (IOException e) {
            if(isStopped()) {
                System.out.println("Server Stopped.") ;
                return;
            }
            throw new RuntimeException(
                "Error accepting client connection", e);
        }
        new Thread(
            new WorkerRunnable(
                clientSocket, "Multithreaded Server")
        ).start();
    }
    System.out.println("Server Stopped.") ;
}

private synchronized boolean isStopped() {
    return this.isStopped;
}

public synchronized void stop(){
    this.isStopped = true;
    try {
        this.serverSocket.close();
    } catch (IOException e) {
        throw new RuntimeException("Error closing server", e);
    }
}

private void openServerSocket() {
    try {
        this.serverSocket = new ServerSocket(this.serverPort);
    } catch (IOException e) {
        throw new RuntimeException("Cannot open port 6789", e);
    }
}

}

public class AppMultiThreadedServer {
    public static void main(String args[]){
        MultiThreadedServer server = new MultiThreadedServer(6789);
        new Thread(server).start();

        try {
            Thread.sleep(10 * 10000);
        } catch (InterruptedException e) {
            e.printStackTrace();
        }
        System.out.println("Stopping Server");
    }
}
```



```
        server.stop();
    }
}

//-----AppPoolThreadedServer.java
//package mythread.threadpooled.runnable;

import java.net.ServerSocket;
import java.net.Socket;
import java.io.IOException;
import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;

class ThreadPooledServer implements Runnable {

    protected int serverPort = 6789;
    protected ServerSocket serverSocket = null;
    protected boolean isStopped = false;
    protected Thread runningThread = null;
    protected ExecutorService threadPool = Executors.newFixedThreadPool(10);

    public ThreadPooledServer(int port) {
        this.serverPort = port;
    }

    public void run() {
        synchronized (this) {
            this.runningThread = Thread.currentThread();
        }
        openServerSocket();
        while (!isStopped()) {
            Socket clientSocket = null;
            try {
                clientSocket = this.serverSocket.accept();
            } catch (IOException e) {
                if (isStopped()) {
                    System.out.println("Server Stopped.");
                    break;
                }
                throw new RuntimeException("Error accepting client connection",
                    e);
            }
            this.threadPool.execute(new WorkerRunnable(clientSocket,
                "Thread Pooled Server"));
        }
        this.threadPool.shutdown();
        System.out.println("Server Stopped.");
    }

    private synchronized boolean isStopped() {
```

```
        return this.isStopped;
    }

    public synchronized void stop() {
        this.isStopped = true;
        try {
            this.serverSocket.close();
        } catch (IOException e) {
            throw new RuntimeException("Error closing server", e);
        }
    }

    private void openServerSocket() {
        try {
            this.serverSocket = new ServerSocket(this.serverPort);
        } catch (IOException e) {
            throw new RuntimeException("Cannot open port 8080", e);
        }
    }
}

public class AppThreadPooledServer {
    public static void main(String args[]) {
        ThreadPooledServer server = new ThreadPooledServer(6789);
        new Thread(server).start();

        try {
            Thread.sleep(20 * 100000);
        } catch (InterruptedException e) {
            e.printStackTrace();
        }
        System.out.println("Stopping Server");
        server.stop();
    }
}

//-----WorkerRunnable.java
//home/tovantran/Ctest/JavaThread/WorkerRunnable.java --> 2015-03-17 by ./tv owner: tovantran
//package mythread.threadpooled.runnable;

import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStream;
import java.net.Socket;

public class WorkerRunnable implements Runnable {

    protected Socket clientSocket = null;
    protected String serverText = null;
    String clientSentence;
```

```
    public WorkerRunnable(Socket clientSocket, String serverText) {
        this.clientSocket = clientSocket;
        this.serverText = serverText;
    }

    public void run() {
        try {
            InputStream input = clientSocket.getInputStream();
            OutputStream output = clientSocket.getOutputStream();
            BufferedReader inFromClient =
                new BufferedReader(new InputStreamReader(clientSocket.getInputStream()));
            long time = System.currentTimeMillis();

            clientSentence = inFromClient.readLine();
            System.out.println("FROM CLIENT: " + clientSentence);

            output.write(("HTTP/1.1 200 OK\n\nWorkerRunnable: "
                + this.serverText + " - " + time + "").getBytes());

            output.close();
            input.close();
            System.out.println("Request processed time: " + time);
        } catch (IOException e) {
            // report exception somewhere.
            e.printStackTrace();
        }
    }
}

//home/tovantran/Ctest/JavaThread/ServerEcho.java --> 2015-03-17 by ./tv owner: tovantran
//-----ServerEcho.java
//package mythread.tcp.runnable;

import java.io.BufferedReader;
import java.io.DataOutputStream;
import java.io.IOException;
import java.io.InputStreamReader;
import java.net.ServerSocket;
import java.net.Socket;
import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;

public class ServerEcho {

    public static void main(String[] args) {

        new ServerEcho().startServer();
    }

    public void startServer() {
```

```
final ExecutorService clientProcessingPool = Executors.newFixedThreadPool(10);

Runnable serverTask = new Runnable() {
    @Override
    public void run() {
        try {

            ServerSocket serverSocket = new ServerSocket(6789);
            System.out.println("Waiting for clients to connect...");
            while (true) {
                Socket clientSocket = serverSocket.accept();
                clientProcessingPool.submit(new ClientTask(clientSocket));
            }
        } catch (IOException e) {
            System.err.println("Unable to process client request");
            e.printStackTrace();
        }
    }
};

Thread serverThread = new Thread(serverTask);
serverThread.start();

}

private class ClientTask implements Runnable {
    private final Socket clientSocket;
    String clientSentence;
    String capitalizedSentence;
    private ClientTask(Socket clientSocket) {
        this.clientSocket = clientSocket;
    }

    @Override
    public void run() {

        try {

            System.out.println("Got a client !!!");
            DataOutputStream outToClient = new DataOutputStream(clientSocket.getOutputStream());
            BufferedReader inFromClient =
                new BufferedReader(new InputStreamReader(clientSocket.getInputStream()));
            clientSentence = inFromClient.readLine();
            System.out.println("TCP Server Thread Received: " + clientSentence);
            capitalizedSentence = clientSentence.toUpperCase() + '\n';
            outToClient.writeBytes(capitalizedSentence);
            // Do whatever required to process the client's request

            clientSocket.close();
        } catch (IOException e) {
```

```
        e.printStackTrace();  
    }  
}  
}
```