






Sun Direction in Body Frame
Sun direction (deg)
360
270
180
90
0
0
20
40
60
80
100
120
Pointing Error (0/360 = on target)
Pointing error (deg)
360
315
270
225
180
135
90
45
0
SPINUP
HOLD
TRACK
Time (s)



Z-Axis Body Rate (Gyro)
SPINUP
HOLD
TRACK
Body rate (deg/s)
30
25
20
15
10
5
0
-5
-10
-15
-20
0
20
40
60
80
100
120
Time (s)



Reaction Wheel Speed
Wheel speed (RPM)
Commanded
Measured
300
250
200
150
100
50
0
0
20
40
60
80
100
120
Commanded Torque (magenta = wheel saturated)
Torque cmd (mN·m)
Torque cmd
Saturated
30
25
20
15
10
5
0
-5
-10
Time (s)



Sun Sensor Photodiode Readings
ADC max
+X
+Y
-X
-Y
ADC counts
4500
4000
3500
3000
2500
2000
1500
1000
500
0
20
40
60
80
100
120
Sun Vector Magnitude
sun_mag
1.8
1.6
1.4
1.2
1
0.8
0.6
Time (s)


Magnetometer
Field (μT)
Time (s)
mag_X
mag_Y
|B_xy|


Magnetometer X-Y (hard-iron check)
mag_Y (μT)
mag_X (μT)
Time (s)


Sun Direction vs. Magnetometer Heading
360
270
180
90
0
Angle (deg)
0
20
40
60
80
100
120
Time (s)
Sun direction
Mag heading atan2(Y,X)


Solar Array Direction vs. Measured Sun Direction (0 = body +X at start)
-X face (solar array)
Sun (from sun sensor)
Room-frame angle (deg)
360
315
270
225
180
135
90
45
0
0
20
40
60
80
100
120
KestrelSAT Rotation (integrated gyro)
ψ (deg)
60
40
20
0
-20
-40
-60
-80
0
20
40
60
80
100
120
Time (s)


Calibrated Sun Sensor Channels (1 = calibration "bright")
cap 1.2
Calibrated level
+X (0% at ADC max)
+Y (0% at ADC max)
-X (0% at ADC max)
-Y (1% at ADC max)
Sun Vector Components (direction = atan2(sun_Y, sun_X); sun_X < 0 needed to see 180°)
Component
sun_X = +X - (-X)
sun_Y = +Y - (-Y)
Sun Direction and Pointing Error, with Turn-Direction Flips Marked
Angle (deg)
array axis
Sun direction (body)
Pointing error
Time (s)