



Catmull–Clark subdivision surface

The **Catmull–Clark** algorithm is a technique used in computer graphics to create smooth surfaces by subdivision surface modeling. It was devised by Edwin Catmull and Jim Clark in 1978 as a generalization of bi-cubic uniform B-spline surfaces to arbitrary topology.^[1] In 2005, Edwin Catmull received an Academy Award for Technical Achievement together with Tony DeRose and Jos Stam for their invention and application of subdivision surfaces.



First three steps of Catmull–Clark subdivision of a cube with subdivision surface below (note that the Catmull-Clark bi-cubic interpolation above cannot approach an actual sphere, as a sphere would be quadric).

Contents

Recursive evaluation

Exact evaluation

Software using Catmull–Clark subdivision surfaces

See also

References

Further reading

Recursive evaluation

Catmull–Clark surfaces are defined recursively, using the following refinement scheme:^[1]

Start with a mesh of an arbitrary polyhedron. All the vertices in this mesh shall be called original points.

- For each face, add a *face point*
 - Set each face point to be the *average of all original points for the respective face*
- For each edge, add an *edge point*.
 - Set each edge point to be the *average of the two neighbouring face points and its two original endpoints*
- For each *face point*, add an edge for every edge of the face, connecting the *face point* to each *edge point* for the face.
- For each original point *P*, take the average *F* of all *n* (recently created) face points for faces touching *P*, and take the average *R* of all *n* edge midpoints for (original) edges touching *P*, where each edge midpoint is the average of its two endpoint vertices (not to be confused with new "edge points" above). *Move each original point to the point*

$$\frac{F + 2R + (n - 3)P}{n}.$$

This is the barycenter of *P*, *R* and *F* with respective weights (*n* − 3), 2 and 1.

- Connect each new vertex point to the new edge points of all original edges incident on the original vertex.
- Define new faces as enclosed by edges.

The new mesh will consist only of quadrilaterals, which in general will not be planar. The new mesh will generally look smoother than the old mesh.

Repeated subdivision results in smoother meshes. It can be shown that the limit surface obtained by this refinement process is at least \mathcal{C}^1 at extraordinary vertices and \mathcal{C}^2 everywhere else (when n indicates how many derivatives are continuous, we speak of \mathcal{C}^n continuity). After one iteration, the number of extraordinary points on the surface remains constant.

The arbitrary-looking barycenter formula was chosen by Catmull and Clark based on the aesthetic appearance of the resulting surfaces rather than on a mathematical derivation, although Catmull and Clark do go to great lengths to rigorously show that the method converges to bicubic B-spline surfaces.^[1]

Exact evaluation

The limit surface of Catmull–Clark subdivision surfaces can also be evaluated directly, without any recursive refinement. This can be accomplished by means of the technique of Jos Stam.^[2] This method reformulates the recursive refinement process into a matrix exponential problem, which can be solved directly by means of matrix diagonalization

Software using Catmull–Clark subdivision surfaces

- 3ds Max
- 3D-Coat
- AC3D
- Anim8or
- AutoCAD
- Blender
- Carrara
- CATIA (Imagine and Shape)
- CGAL
- Cheetah3D
- Cinema4D
- Clara.io
- Creo (Freestyle)^[3]
- DAZ Studio, 2.0
- DeleD Community Edition
- DeleD Designer
- Gelato
- Hammer
- Hexagon
- Houdini
- LightWave 3D, version 9
- Makehuman
- Maya
- Metasequoia
- MODO
- Mudbox
- Pixar's OpenSubdiv^{[4][5][6][7][8]}
- PRMan
- Realsoft3D
- Remo 3D
- Shade
- Rhinoceros 3D - Grasshopper 3D Plugin - Weaverbird Plugin
- Silo
- SketchUp - Requires a Plugin.
- Softimage XSI
- Strata 3D CX
- Wings 3D
- Zbrush

See also

- Conway polyhedron notation- A set of related topological polyhedron and polygonal mesh operators.

References

1. Catmull, E.; Clark, J. (1978). "Recursively generated B-spline surfaces on arbitrary topological meshes"http://www.cs.berkeley.edu/~sequin/CS284/PAPERS/CatmullClark_SDSurf.pdf (PDF). *Computer-Aided Design*. **10** (6): 350. doi:10.1016/0010-4485(78)90110-0(<https://doi.org/10.1016%2F0010-4485%2878%2990110-0>)
2. Stam, J. (1998). "Exact evaluation of Catmull-Clark subdivision surfaces at arbitrary parameter values"*Proceedings of the 25th annual conference on Computer graphics and interactive techniques - SIGGRAPH '98*<http://www.dgp.to.onto.edu/people/stam/reality/Research/pdf/sig98.pdf> (PDF). pp. 395–404. doi:10.1145/280814.280945(<https://doi.org/10.1145%2F280814.280945>) ISBN 0-89791-999-8
3. http://www.ptc.com/File%20Library/Community/Academic%20Program/College_Student_Primer_Creo_2.pdf
4. Manuel Kraemer (2014). "OpenSubdiv: Interoperating GPU Compute and Drawing". In Martin Att, Erwin Coumans, George Elkoura, Ronald Henderson, Manuel Kraemer, Jeff Lait, James Reinders. *Multithreading for Visual Effects*.

CRC Press. pp. 163–199. ISBN 978-1-4822-4356-7.

5. <https://www.youtube.com/watch?v=xFZazwvYc5o>
6. <http://www.fxguide.com/featured/pixars-operators-subdiv-v2-a-detailed-look/>
7. <http://on-demand.gputechconf.com/gtc/2014/video/S4856-subdivision-surfaces-industry-standard.mp4>
8. https://www.youtube.com/watch?v=dzII_S-qHQ

Further reading

- Derose, T.; Kass, M.; Truong, T. (1998). "Subdivision surfaces in character animation" *Proceedings of the 25th annual conference on Computer graphics and interactive techniques - SIGGRAPH '98* (PDF). p. 85. doi:10.1145/280814.280826 ISBN 0897919998.
- Loop, C.; Schaefer, S. (2008). "Approximating Catmull-Clark subdivision surfaces with bicubic patches" (PDF). *ACM Transactions on Graphics* **27**: 1. doi:10.1145/1330511.1330519
- Kovacs, D.; Mitchell, J.; Drone, S.; Zorin, D. (2010). "Real-Time Creased Approximate Subdivision Surfaces with Displacements" (PDF). *IEEE Transactions on Visualization and Computer Graphics* **16** (5): 742. doi:10.1109/TVCG.2010.31 PMID 20616390. preprint
- Matthias Nießner, Charles Loop, Mark Meyer Tony DeRose, 'Feature Adaptive GPU Rendering of Catmull-Clark Subdivision Surfaces', *ACM Transactions on Graphics* Volume 31 Issue 1, January 2012, doi:10.1145/2077341.2077347, demo
- Nießner, Matthias ; Loop, Charles ; Greiner, Günther: Efficient Evaluation of Semi-Smooth Creases in Catmull-Clark Subdivision Surfaces Eurographics 2012 Annex: Short Papers (Eurographics 2012, Cagliari). 2012, pp 41–44.
- Wade Brainerd, *Tessellation in Call of Duty: Ghosts* also presented as a SIGGRAPH2014 tutorial[1]
- D. Doo and M. Sabin: *Behavior of recursive division surfaces near extraordinary points*, *Computer-Aided Design*, 10 (6) 356–360 (1978), (doi, pdf)

Retrieved from 'https://en.wikipedia.org/w/index.php?title=Catmull-Clark_subdivision_surface&oldid=820072854

This page was last edited on 12 January 2018, at 22:44.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.