

# TNM087 – Image Processing and Analysis

## Lab 2 –Spatial Filtering

### TASK 1 Preparation

#### Lowpass filtering and derivative operators

The preparation task consists of a few simple problems that should be solved using Matlab. Your answers (in Swedish or English) should be written in the document *Lab\_2.1\_Preparation\_Answers.docx*, where you also insert the required images. To save the images you can use the MATLAB functions `imwrite` or `imsave`. Make sure to save the images in an uncompressed format, such as **.tif** or **.png**.

**Don't scale** the images when inserting them in the word document. Before submitting the answer document on Lisam, first save the document as **.pdf**!

For the preparation tasks you do not need to submit your m-file. However, it is strongly recommended that you save your experiments in an m-file, in case you need to go back and correct anything later. Sometimes, you can also re-use your code in later tasks.

In this task, you are supposed to do a number of spatial filtering tests on a given grayscale test image named *TestPattern.tif*. Start reading this image into MATLAB and scale it on  $[0, 1]$ . (Use for example *imread* followed by *im2double* in MATLAB).

There are a number of MATLAB functions that can be used to filter an image, for example, *filter2*, *conv2*, and *imfilter*. See the lecture notes for Chapter 3 to learn the differences between these functions and how they work.

#### 1) Testing different box filters:

**Problem 1)** Filter the test image (*TestPattern.tif*) with a box kernel of size  $9 \times 9$ . We call the resulting image *Image1*. Insert your result in the answer document. (**HINT:** In the lecture notes you find how to create a box kernel)

**Problem 2)** Filter the test image with a box kernel of size  $21 \times 21$ . We call the resulting image *Image2*. Insert your result in the answer document.

**Problem 3)** Obviously, *Image2* is much more blurred than *Image1*. Does this mean that the  $21 \times 21$  box filter has a lower or higher cutoff frequency than the  $9 \times 9$  box filter kernel? Explain why!

As can be seen in *Image2*, the filtering has introduced visible dark borders in the filtered result.

**Problem 4)** What is the reason for these dark borders? (**HINT:** discussed in the lecture)

**Problem 5)** Filter the test image again with a box kernel of size  $21 \times 21$ . Use an appropriate MATLAB function and filtering to avoid the dark borders. We call the resulting image *Image3*. Insert your result in the answer document.

**Problem 6)** Now, make a highpass filter of the  $21 \times 21$  box filter (which obviously is a lowpass filter). Filter now the test image with your highpass filter kernel. Use an appropriate MATLAB function and filtering to avoid the dark borders. We call the resulting image *Image4*. Insert your result in the answer document.

**Problem 7)** Why is *Image4* so dark? What is the average value of the pixel values in *Image4*? And why? (**HINT:** discussed in the lecture and also in one of the class ("lektion") assignments)

**Problem 8)** Add *Image4* to the original test image, and call the result *Image5*. This operation is called unsharp masking. Insert your result in the answer document.

## 2) Testing Sobel filters and gradient:

The following two Sobel filter kernels are commonly used to perform the first derivative in the  $x$  and  $y$  direction, respectively. If you use these kernels as they are, then you should use **correlation** to perform filtering. You can therefore use the MATLAB function *filter2* (the function *imfilter* can also be used).

$$Sob_x = \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix} \quad Sob_y = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$$

**Problem 9)** Filter the test, i.e. *TestPattern.tif*, image with  $Sob_x$ . We call the resulting image *Image6*. Insert your result in the answer document.

**Problem 10)** Filter the test image with  $Sob_y$ . We call the resulting image *Image7*. Insert your result in the answer document.

The length of the gradient vector is:  $M(x, y) = \|\nabla f\| = \sqrt{g_x^2 + g_y^2}$ , which is an image of the same size as the original image.  $M(x, y)$  is commonly called the gradient image. Remember that, the operation to find the square of these matrices has to be performed **elementwise**.

**Problem 11)** Find the gradient of the test image by using your results in Problem 9 and 10. Call the resulting image *Image8*. Insert your result in the answer document.