

# Computational Intelligence Laboratory

## Lecture 4

# Non-Negative Matrix Factorization

Thomas Hofmann

ETH Zurich – `cil.inf.ethz.ch`

15 March 2019

# Section 1

## Motivation

# Introduction: Topic Models


- ▶ Challenge
  - ▶ given: corpus of text documents (e.g. web pages)
  - ▶ goal: find low-dimensional document representation in **semantic space** of topics or concepts – **aboutness** of documents
  - ▶ also known as **topic models**
- ▶ Approach: predictive model
  - ▶ log-likelihood of predicting words in document
  - ▶ MLE: probabilistic Latent Semantic Analysis (**pLSA**)
  - ▶ Bayesian: Latent Dirichlet Allocation (**LDA**)
  - ▶ related to non-negative matrix decomposition

# Document Representation: Pre-Processing

- ▶ Vocabulary
  - ▶ all “meaningful” words (=terms) in a language
  - ▶ extracted from corpus documents via **tokenization**
  - ▶ large cardinality (e.g.  $\sim 1$ -100 million)
- ▶ Term filtering
  - ▶ exclude **stop words** (“the”, “is”, “at”, “which”, etc.).
  - ▶ exclude infrequent words, misspellings, tokenizer errors, etc.
- ▶ Term normalization
  - ▶ **stemming** (optionally): reduce word to stem/lemma
  - ▶ example: “argue”, “argued”, “argues”, “arguing”, and “argus”  
reduce to the stem “arg”

# Document Representation: Bag-of-Words

- ▶ Bag-of-word Representation
  - ▶ ignore order of words in sentences/document
  - ▶ reduce data to co-occurrence counts
  - ▶ see previous lecture: word context = entire document
  - ▶ document =  $M$ -dimensional vector of counts, very **sparse**!



## Section 2

### Probabilistic LSA

# Probabilistic LSA: Topic Model

- ▶ Topic parameters = word distribution
- ▶ Document = **mixture of topics**
  - ▶  $\neq$  probabilistic assignment
  - ▶ example: document on *soccer world cup 2022 in Dubai*
    - ▶ soccer vocabulary (e.g. “teams”, “play”, “soccer”, “match”)
    - ▶ political vocabulary (e.g. “labor”, “corruption”, “president”)
    - ▶ mixing weights  $\neq$  uncertainty about correct topic
- ▶ Goal: Discover topics in an unsupervised fashion.


# Probabilistic LSA: Two-Stage Sampling

- ▶ Two-stage (hierarchical) sampling:
  - ▶ (1) sample topic for each token
  - ▶ (2) sample token, given sampled topic



- ▶ Model parameters

- ▶ each document = specific mix of topics (colors):  $p(z|d)$
- ▶ each topic (color) = specific distribution of words:  $p(w|z)$





# Probabilistic LSA: Basic Model

- ▶ **Context model:**

occurrence of word  $w$  in context/document  $d$

$$p(w|d) = \sum_{z=1}^K p(w|z)p(z|d)$$

- ▶ identify topics with integers  $z \in \{1, \dots, K\}$  ( $K$ : pre-specified)
- ▶ relative to a fixed “slot” (i.e. fixed position in document)
- ▶ identical distribution for every slot

- ▶ **Conditional independence** assumption (\*)

$$p(w|d) = \sum_z p(w, z|d) = \sum_z p(w|d, z)p(z|d) \stackrel{*}{=} \sum_z p(w|z)p(z|d)$$

- ▶ topics represent regularities common to the entire collection

# Probabilistic LSA: Log-Likelihood

- ▶ Summarize data into co-occurrence counts  $\mathbf{X} = x_{ij}$   
(# occurrences of  $w_j$  in document  $d_i$ )
- ▶ Alternatively: multiset  $\mathcal{X}$  over index pairs  $(i, j)$
- ▶ **Log-likelihood**

$$\ell(\mathbf{U}, \mathbf{V}) = \sum_{i,j} x_{ij} \log p(w_j | d_i) = \sum_{(i,j) \in \mathcal{X}} \log \sum_{z=1}^K \underbrace{p(w_j | z)}_{=: v_{zj}} \underbrace{p(z | d_i)}_{=: u_{zi}}$$

- ▶ two types of parameters:
- ▶  $u_{zi} \geq 0$  such that  $\sum_z u_{zi} = 1$  ( $\forall i$ )
- ▶  $v_{zj} \geq 0$  such that  $\sum_j v_{zj} = 1$  ( $\forall z$ )

# Expectation Maximization for pLSA

- ▶ Missing data  $Q_{zij} \in \{0, 1\}$ :  $w_j$  in  $d_i$  generated via  $z$ ,  $\sum_z Q_{zij} = 1$
- ▶ Variational parameters  $q_{zij} = \Pr(Q_{zij} = 1)$ ,  $\sum_z q_{zij} = 1$
- ▶ Lower bound from Jensen's inequality

$$\log \sum_{z=1}^K q_{zij} \frac{u_{zi} v_{zj}}{q_{zij}} \geq \sum_{z=1}^K q_{zij} [\log u_{zi} + \log v_{zj} - \log q_{zij}]$$

- ▶ Solve for optimal  $q$  (**Expectation Step**)

$$q_{zij} = \frac{u_{zi} v_{zj}}{\sum_{k=1}^K u_{ki} v_{kj}} = \frac{p(w_j|z)p(z|d_i)}{\sum_{k=1}^K p(w_j|k)p(k|d_i)}$$

- ▶  $\implies$  posterior of  $Q_{zij}$  under model

# Expectation Maximization for pLSA (cont'd)

- ▶ Solve for optimal parameters (**Maximization** Step)

$$u_{zi} = \frac{\sum_j x_{ij} q_{zij}}{\sum_j x_{ij}}, \quad v_{zj} = \frac{\sum_i x_{ij} q_{zij}}{\sum_{i,l} x_{il} q_{zil}},$$

- ▶ numerator: simple weighted counts
  - ▶ denominator: ensure proper normalization
- ▶ EM for MLE in pLSA ;-)
  - ▶ guaranteed convergence (cf. mixture models)
  - ▶ **not** guaranteed to find global optimum

# Topics Discovered by pLSA

| "segment 1"  | "segment 2"  | "matrix 1"  | "matrix 2"  | "line 1"  | "line 2"   | "power 1"   | "power 2"  |
|--|--|---|---|---|--|---|--|
| imag<br><b>SEGMENT</b><br>texture<br>color<br>tissue<br>brain<br>slice<br>cluster<br>mri<br>volume | speaker<br>speech<br>recogni<br>signal<br>train<br>hmm<br>source<br>speakerind.<br><b>SEGMENT</b><br>sound | robust<br><b>MATRIX</b><br>eigenvalu<br>uncertain<br>plane<br>linear<br>condition<br>perturb<br>root<br>suffici | manufactur<br>cell<br>part<br><b>MATRIX</b><br>cellular<br>famili<br>design<br>machinepart<br>format<br>group | constraint<br><b>LINE</b><br>match<br>locat<br>imag<br>geometr<br>impos<br>segment<br>fundament<br>recogn | alpha<br>redshift<br><b>LINE</b><br>galaxi<br>quasar<br>absorp<br>high<br>ssup<br>densiti<br>veloc | <b>POWER</b><br>spectrum<br>omega<br>mpc<br>hsup<br>larg<br>redshift<br>galaxi<br>standard<br>model | load<br>memori<br>vlsi<br><b>POWER</b><br>systolic<br>input<br>complex<br>arra<br>present<br>implement |

**Table:** Eight selected topics from a 128 topic decomposition. The displayed word stems are the 10 most probable words in the class-conditional distribution  $p(\text{word}|\text{topic})$ , from top to bottom in descending order.


Hofmann, Thomas. Probabilistic latent semantic indexing. ACM SIGIR Forum. Vol. 51. No. 2. ACM, 2017. (re-print from 1999)

## Section 3

# Latent Dirichlet Allocation

# Generative Document Model

- ▶ Probabilistic LSA: both dimensions of matrix are fixed
- ▶ Generative document model: how to sample **new** document?
- ▶ Co-occurrence matrix: how to sample additional row of  $\mathbf{X}$ ?



- ▶ Need to be able to sample topic weights  $\mathbf{u}_i = (u_{1i}, \dots, u_{Ki})^T$  for a new document
- ▶ Combine with existing  $\mathbf{V}$  to predict new data row

# Latent Dirichlet Allocation (LDA)

- ▶  $\mathbf{u}_i$  is a probability vector, "simplest" (conjugate) distribution = **Dirichlet distribution**

$$p(\mathbf{u}_i|\alpha) \propto \prod_{z=1}^K u_{zi}^{\alpha_z - 1}$$

- ▶ given  $\alpha$  parameters ( $K$  dim.), can generate topic weights
  - ▶ but, we can do more ...
- ▶ Bayesian view: treat  $\mathbf{U}$  as nuisance parameters
  - ▶  $\mathbf{U}$  needs to be averaged out
  - ▶  $\mathbf{V}$  are real parameters,  $\mathbf{U}$  can be re-constructed, if needed
  - ▶ advantages in terms of **model averaging**



# Latent Dirichlet Allocation: Bayesian View

- ▶ LDA model (fixed document length  $l = \sum_j x_j$ )
  - ▶ **multinomial** observation model ( $\mathbf{x}$  = word count vector)

$$p(\mathbf{x}|\mathbf{V}, \mathbf{u}) = \frac{l!}{\prod_j x_j!} \prod_j \pi_j^{x_j}, \quad \pi_j := \sum_z v_{zj} u_z$$

- ▶ Bayesian averaging over  $\mathbf{u}$

$$p(\mathbf{x}|\mathbf{V}, \alpha) = \int p(\mathbf{x}|\mathbf{V}, \mathbf{u}) p(\mathbf{u}|\alpha) d\mathbf{u}$$

- ▶ Generative model
  - ▶ for each  $d_i$ : sample  $\mathbf{u}_i \sim \text{Dirichlet}(\alpha) \implies$  **integrate out**
  - ▶ for each word slots  $w^t$ ,  $1 \leq t \leq l_i \implies$  **iid. = product**
    - ▶ sample topic  $z^t \sim \text{Multi}(\mathbf{u}_i) \implies$  **latent, sum out**
    - ▶ then sample  $w^t \sim \text{Multi}(\mathbf{v}_{z^t}) \implies$  **observable**

# Latent Dirichlet Allocation: Algorithms

- ▶ Learning algorithms
  - ▶ variational expectation maximization
  - ▶ Markov Chain Monte Carlo (MCMC): collapsed Gibbs sampling
  - ▶ distributed, large-scale implementations (100Ms of documents)
  - ▶ (beyond the scope of this lecture...)

Blei, David M., Andrew Y. Ng, and Michael I. Jordan. “Latent dirichlet allocation.” *Journal of Machine Learning Research*, 2003, pp. 993-1022.

# Latent Dirichlet Allocation: Examples

Example from  
Blei, 2012

Figure 1. The intuitions behind latent Dirichlet allocation. We assume that some number of "topics," which are distributions over words, exist for the whole collection (far left). Each document is assumed to be generated as follows. First choose a distribution over the topics (the histogram at right); then, for each word, choose a topic assignment (the colored circle) and choose the word from the corresponding topic. The topics and topic assignments in this figure are illustrative—they are not fit from real data. See Figure 2 for topics fit from data.





Figure 2. Real inference with LDA. We fit a 100-topic LDA model to 17,000 articles from the Journal Science. At left are the inferred topic proportions for the example article in Figure 1. At right are the top 15 most frequent words from the most frequent topics found in this article.



## Section 4

# Non-Negative Matrix Factorization

# Non-Negative Matrix Factorization

- ▶ Count matrix  $\mathbf{X} \in \mathbb{Z}_{\geq 0}^{N \times M}$
- ▶ Non-negative matrix factorization (NMF) of  $\mathbf{X}$ :

$$\mathbf{X} \approx \mathbf{U}^{\top} \mathbf{V}, \quad x_{ij} = \sum_z u_{zi} v_{zj} = \langle \mathbf{u}_i, \mathbf{v}_j \rangle$$

- ▶ constraints on matrix factors  $\mathbf{U}$  and  $\mathbf{V}$ 
  - ▶ non-negativity – as all parameters are probabilities
  - ▶ normalization –  $\mathbf{U}, \mathbf{V}$  are  $L_1$  column-normalized
- ▶ approximation quality measured via log-likelihood
- ▶ dimension reduction:  $N \cdot M \gg (N + M)K - N - M$

# NMF for Quadratic Cost Function

- ▶ pLSA: just one instance of a non-negative matrix factorization
- ▶ Variation: non-negative data  $\mathbf{X}$  with **quadratic** cost function  
= non-negative matrix approximation


$$\min_{\mathbf{U}, \mathbf{V}} J(\mathbf{U}, \mathbf{V}) = \frac{1}{2} \|\mathbf{X} - \mathbf{U}^\top \mathbf{V}\|_F^2.$$

$$\text{s.t. } u_{zi}, v_{zj} \geq 0 \quad (\forall i, j, z) \quad (\text{non-negativity})$$

- ▶ Similar as pLSA, but ...
  - ▶ different sampling model: Gaussian vs. multinomial
  - ▶ different objective: quadratic instead of KL divergence
  - ▶ different constraints (not normalized)

# Part-Based Representation of Faces


- ▶ NMF is useful when modelling non-negative data (e.g. images = non-negative **intensities**)
- ▶ Additive superpositions without cancellations  $\implies$  NMF leads to **part-based representations**
- ▶ vs. vector quantization,  $K$ -means: combination of multiple basis images




*D.D. Lee & H. S. Seung, Learning the parts of objects by non-negative matrix factorization, Nature, 40, 1999.*

# Part-Based Representation of Faces (zoom-in)

NMF



$\times$



$=$

Original





# NMF Algorithm: Quadratic Costs

- ▶ Alternating least squares

- ▶ convex in  $\mathbf{U}$  given  $\mathbf{V}$  and vice versa, but not jointly in  $(\mathbf{U}, \mathbf{V})$
- ▶  $\Rightarrow$  alternate optimization of  $\mathbf{U}$  and  $\mathbf{V}$ , keeping the other fixed
- ▶ **normal equations** in matrix notation

$$(\mathbf{U}\mathbf{U}^\top) \mathbf{V} = \mathbf{U}\mathbf{X}, \quad \text{and} \quad (\mathbf{V}\mathbf{V}^\top) \mathbf{U} = \mathbf{V}\mathbf{X}^\top$$

- ▶ solved via  $QR$ -decomposition or gradient descent
- ▶ project in between alternations – **non-negativity!**

$$u_{zi} = \max\{0, u_{zi}\}, \quad v_{zj} = \max\{0, v_{zj}\}$$

- ▶ More detailed discussion of algorithms for NMF see:

Berry, M.W. et al.: Algorithms and applications for approximate nonnegative matrix factorization. Computational Statistics & Data Analysis, 52(1), 2007, pp.155-173.

# pLSA & NMF: Discussion

- ▶ Matrix factorization obeying non-negativity and (optionally, pLSA) normalization constraints
- ▶ Different cost functions: multinomial likelihood, quadratic loss
- ▶ Iterative optimization (EM algorithm, projected ALS)
- ▶ Interpretability of factors: topics, parts, etc.
- ▶ Wide range of applications