DATA SHEET

HS-1200 - Datasheet

TYPE BALL VALVE

FUNCTION ON-OFF VALVE

Template: DataSheetDigital EN ValvDeslizable Rev2

REV 1

DATE 30/4/2026

SHEET 1/1

GENERAL	100	TAG ADI	**HS-1200**
	101	Revision	1
	102	Revision Reason	Spec
	103	Revision Date	30/4/2026
DOCs	200	TAG (Original)	HS-1200
	201	Template (Datasheet)	PETRO DSD
	202	Doc Type (Original)	-
	203	Doc Number (Original)	-
	204	Hookup	-
LOCATION	300	Process	Polimerization
	301	Subprocess	Discharge
	302	Function	Reactor discharge
	303	Area Classification	ATEX Zone 1/21
	304	P&I	38
FLUID	400	Service	Discharge lane 1
	401	Fluid	Polypropilene + C3H6
	402	Phase	Powder + Gas
	403	Corrosive matter	No
	404	Suspended matter	No

CONDITIONS	410	Vapor Frac	%		0	
	411	Molecular weight	kg/kmol		-	
	412	Dyn. Viscosity at operating temp.	mPa*s		-	
	413	Δp. At flow rate = 0 (valve closed)	bar		-	
		Scenarios		**Min**	**Norm**	**Max**
	414	Flow rate	kg/h	-	3062	-
	415	Inlet Pressure (P1)	bar_g	-	10	-
	416	Differential Pressure (ΔP)	bar	-	8	40
	417	Operating temp.	°C	-	78	110
	418	Density at operating temp.	kg/m3	-	-	-
	419	Cv	-	-	-	-

LINE	500	Line number		100-PP-01-2
	501	Piping class		300B04
	502	DN and PN	in/psi	2"/ 300
	503	Schedule		Sch 40
	504	Material		C-Steel Gr. B
BODY	600	Manufacturer/Type		[M/S (1)]
	601	Type/ways		Ball / 2 ways
	602	Length	mm	-
	603	Facing/ANSI		Flanges RFSF (ASME B 16.5)
	604	DN/PN	in/psi	2" / 300
	605	Body/Flanges Material		ASTM A216 Gr. WCC
	606	Bolts Material		[M/S (1)]
	607	Design temperature	°C	110
	608	Design Pressure	psi	300
	609	Extended stem/Heating jacket		NO / NO

INTERNALS	620	Internals Type		On-Off
	621	Internals Material		A316 SS
	622	Leak Rate		ANSI V or better
	623	Port diameter	mm	-
	624	Guided Ball		-
	625	Flow Characteristic		Open-Close
	626	Seat Material		Metal
	627	Shaft Seal (Type / Material)		PTFE
	628	Body Seal (Type / Material)		
ACTUADOR	700	Manufacturer/Model		M/S (1)
	701	Type		Rack and pinion
	702	Size		M/S (1)
	703	Stroke	mm	M/S (1)
	704	Available Air Pressure (for actuator operatio		5 bar
	705	Air failure		Opens
	706	Pneumatic connection		1/4" NPT
	707	Operating Frequency	cic/min	Control
	708	Delta P tends to (rises/falls)		M/S (1)
POSITIONER	720	TAG Positioner		-
	721	Manufacturer/Type		-
	722	Input		-
	723	Partial Stroke Test		-
	724	Pneumatic connection		-
	725	Electrical connection		-
	726	Enclosure (IP)		-
	727	Explosive Area Certification (EPL)		-
SOLENOID	740	TAG Solenoid		HY1200
	741	Manufacturer/Model		FESTO / MFH-3-1/4
	742	Type		Directional 5/3
	743	Local actuation		-
	744	Coil Power Supply		24 Vdc
	745	Electrical connection		1/2" NPT
	746	Explosive Area Certification (EPL)		M/S (1)
LIMITS	760	TAG Limits		GO+1200 / GO-1200
	761	Manufacturer/Model		[M/S (1)]
	762	Type		[M/S (1)]
	763	Open / Closed / Position Limits		Open-Close Switchs
	764	Power Supply		24 Vdc
	765	Electrical Connection		1/2" NPT
	766	Local Indication		-
	767	Explosive Area Certification (EPL)		M/S (1)
ACC.	800	Air Regulator		YES (67CFR)
	801	Liquid Trap		NO
	802			
	803			

NOTES	900	(1) M/S: Manufacturer Standard
	901	
	902	
	903	
	904	