

```
iot@iot: ~  
[ OK ] Starting Redis Server...  
[ OK ] Starting Update UTPM about System Runlevel Changes...  
[ OK ] Started Redis Server.  
galileo login: root  
root@galileo:~# conmanctl  
conmanctl> enable wifi  
Error wifi: Already enabled  
conmanctl> scan wifi  
Scan completed for wifi  
conmanctl> services  
CCEENACQURP wifi 6817296585ba 47434f454e4147505552_managed_psk  
DIRECT_Fa HP M203 LaserJet wifi 6817296585ba 4449524543542d66612d4850204d323033204c617365724a6574_managed_psk  
JioNetGovt_Engineering wifi 6817296585ba 4a696f4e657440476f76745f4546e67696e656572696e67_managed_none  
JioPrivateNet wifi 6817296585ba 4a696f507269766174654a6574_managed_lee8021x  
AkhilTesh wifi 6817296585ba 416d68696c65726820_managed_psk  
conmanctl> config wifi_0017296585ba_47434f454e4147505552_managed_psk  
conmanctl> agent on  
Agent registered  
conmanctl> connect wifi_6817296585ba_47434f454e4147505552_managed_psk  
Agent RequestInput wifi_6817296585ba_47434f454e4147505552_managed_psk  
Passphrase = [ Type:psk, Requirement:Mandatory ]  
Passphrase? 5dmn@123  
conmanctl> [ 75.657935] wlp1s0: authenticate with a4:2a:95:4a:fe:e0  
[ 75.679421] wlp1s0: send auth to a4:2a:95:4a:fe:e0 (try 1/3)  
[ 75.680515] wlp1s0: authenticated  
[ 75.700165] wlp1s0: associate with a4:2a:95:4a:fe:e0 (try 1/3)  
[ 75.732739] wlp1s0: RX AssocResp from a4:2a:95:4a:fe:e0 (capab=0x431 status=0 aid=1)  
[ 75.776657] wlp1s0: associated  
[ 75.779960] IPv6: ADDRCONF(NETDEV_CHANGE): wlp1s0: link becomes ready  
Connected wifi_6817296585ba_47434f454e4147505552_managed_psk  
conmanctl> exit  
root@galileo:~# ifconfig  
enp8s20f6 Link encap:Ethernet HWaddr 98:4f:ee:05:b8:39  
UP BROADCAST MULTICAST MTU:1500 Metric:1  
RX packets:0 errors:0 dropped:0 overruns:0 frame:0  
TX packets:0 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:0 (0.0 B) TX bytes:980 (980.0 B)  
Interrupt:50 Base address:0x4000  
enp8s20f6:avahi Link encap:Ethernet HWaddr 98:4f:ee:05:b8:39  
inet addr:169.254.6.120 Bcast:169.254.255.255 Mask:255.255.0.0  
UP BROADCAST MULTICAST MTU:1500 Metric:1  
Interrupt:50 Base address:0x4000  
lo  
Link encap:Local Loopback  
inet addr:127.0.0.1 Mask:255.0.0.0  
inet6 addr: ::1/128 Scope:Host  
UP LOOPBACK RUNNING MTU:65536 Metric:1  
RX packets:320 errors:0 dropped:0 overruns:0 frame:0  
TX packets:320 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:0  
RX bytes:23680 (23.1 KiB) TX bytes:23680 (23.1 KiB)  
wlp1s0 Link encap:Ethernet HWaddr 68:17:29:65:85:ba  
inet addr:192.168.1.168 Bcast:192.168.1.255 Mask:255.255.240.0  
inet6 addr: fe80::6a17:29ff:fe65:85ba/64 Scope:Link  
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1  
RX packets:25793 errors:0 dropped:22 overruns:0 frame:0  
TX packets:54 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:2224507 (2.1 MiB) TX bytes:9432 (9.2 KiB)  
root@galileo:~# echo -e '#!/bin/bash\nREPO_PATH=/etc/opkg/iotkit.conf 2> /droot@galileo:~# echo -e '#!/bin/bash\nREPO_PATH=/etc/opkg/iotkit.conf 2> /droot@galileo:~# ^C  
root@galileo:~#
```

















