

The Surface Vault

Quick and easy access to a single asset

The Surface Vault provides a small secured monitored storage enclosure. Storage options include SmartFob, Key, or Direct Entrapment Key. The Surface Vault products provide a secure, monitored asset position located in a locking enclosure that can be mounted on a wall or other suitable structure. Controlled and monitored by an existing access control system or SAM, the vault securely stores a single asset and includes sensors that provide indication of door state and asset presence. When access to the asset is desired, the system is used to unlock the cabinet.



Theory of operation

This solution enables remote monitoring and control over a single asset. It fits a wide variety of applications including emergency access and control, on location, for convenience.

Key product features

- Can connect to an access control system, fire panel, SAM, or any device with a remotely operated relay that can provide sufficient power.
- Time out period after unlock or access granted. The unit locks again if unopened for the time out period.
- Asset presence sensor for remote indication of asset in or out.
- Mechanical key override for asset access should power fail.
- Surface mount.
- Mechanical release after unlocking ensures the door remains closed until the user is ready to access the interior.
- Door sensor for remote indication of cover open or closed.
- LED illuminates to indicate when unlocked or access granted.
- No external fasteners to reduce the risk of tampering.

In practice

Wherever a single key has to stay in a fixed place and be monitored remotely: an emergency key at the entrance, the lift key, the key to a meter cupboard or a plant room. The vault has no software of its own and connects to the system already in place.



SUPPLY THROUGHOUT EUROPE, INSTALLATION IN THE NETHERLANDS AND BELGIUM

DELPHI Sleutelbeheersystemen

Einsteinstraat 3e, 4207 HW Gorinchem, the Netherlands · +31 (0)183 648851
info@sleutelbeheersystemen.nl · sleutelbeheersystemen.nl

Two models

Two Surface Vault models are available: the Key Only model and the Key Ring model.



Key Only model

Direct entrapment via an interchangeable core.



Key Ring model

Cam lock, fob or direct entrapment via an interchangeable core. The key ring allows for up to fifteen keys. Loose access card possible.

Technical specifications

Material Stainless steel, 16 gauge

Power From an external source

Connectivity

- LED +5 VDC standard
- Door solenoid 12 VDC standard
- Door sensor — contact closure
- Asset sensor — contact closure

Dimensions

	KEY RING	KEY ONLY
Width	4 $\frac{5}{16}$ " · 10.9 cm	2 $\frac{5}{16}$ " · 5.9 cm
Height	7 $\frac{5}{8}$ " · 19.4 cm	6 $\frac{1}{8}$ " · 15.6 cm
Depth	2 $\frac{5}{8}$ " · 6.7 cm	2 $\frac{3}{16}$ " · 5.6 cm

Dimensions in inches as given by the manufacturer; centimetres converted and rounded. Dimensions subject to change.



Key Only model in use



Key Ring model in use

SUPPLY THROUGHOUT EUROPE, INSTALLATION IN THE NETHERLANDS AND BELGIUM

DELPHI Sleutelbeheersystemen

Einsteinstraat 3e, 4207 HW Gorinchem, the Netherlands · +31 (0)183 648851
info@sleutelbeheersystemen.nl · sleutelbeheersystemen.nl