

A COMPLICATED AND IMPRESSIVE SOUNDING TITLE THAT IS TOO LONG  
FOR A SINGLE LINE WHILE INCLUDING EVERYTHING

by

David B. Chester

A proposal submitted in partial fulfillment  
of the requirements for the degree

of

MASTER OF SCIENCE

in

Electrical Engineering

Approved:

---

Scott E. Budge, PhD  
Major Professor

---

Jacob Gunther, PhD  
Committee Member

---

Charles M. Swenson, PhD  
Committee Member

UTAH STATE UNIVERSITY  
Logan, Utah

2017

## CONTENTS

|                                     | Page |
|-------------------------------------|------|
| 1 INTRODUCTION .....                | 2    |
| 2 LITERATURE REVIEW .....           | 3    |
| 3 RESEARCH AND DESIGN METHODS ..... | 5    |
| 4 CONCLUSION .....                  | 7    |

here's some stuff i wrote [\[1\]](#)

## CHAPTER 1

### INTRODUCTION

LadarSIM is a robust parametrized simulation tool for time of flight lidar developed at Utah State University's Center for Advanced Imaging Ladar over the past decade and a half. LadarSIM has the flexibility to simulate a wide range of time of flight lidar systems with varying beam and scanner patterns and parametrized transmitters and receivers. These simulated systems can be evaluated using scenarios consisting of user specified terrain, targets, and flight paths. Taking full advantage of the significant work that has gone into creating the LadarSIM software, a simulation of a parametrized Doppler transmitter and receiver will be added to LadarSIM to evaluate the performance of Doppler lidar systems. Utilizing this Doppler lidar simulation capability a trade-off study will be performed to determine the effects of varying laser transmission power, beam divergence, aperture diameter, and FFT size on a Doppler lidar system. These parameters have been selected because of the significant effect they can have on the performance, cost, size, and power consumption of a Doppler lidar system.

It is anticipated that the results of this research will present a clear demonstration of the effects of these parameters on a Doppler lidar system. For each of these parameters it is expected that performance will increase as the value of the parameter is improved but diminishing returns will be evident. Using this data, a designer would have strong guidance in designing the parameters of a Doppler lidar system to meet mission requirements while expending the minimum necessary resources.

## CHAPTER 2

### LITERATURE REVIEW

Adany et al. describe the operation and performance of a simplified homodyne detection scheme. In this scheme a waveform generator drives an electro-optic modulator which modulates an optical signal from a laser. The resulting signal is split into two parts. One part is amplified and sent to the telescope and the other is used as the local oscillator. The returning signal from the telescope is optically mixed with the local oscillator signal and detected by a balanced photodetector. An FFT is then performed on the detected signal to determine detected range and speed. [1]. This scheme is on NASA's Morpheus test vehicle in order to demonstrate it's utility as a potential instrument for planetary landing missions. [2]. Because of its use by NASA the simplified homodyne detection scheme has been selected as the basis of the doppler lidar simulation in LadarSIM.

Adany et al. tested their lidar at ground level at ranges of 50 m and 370 m [1]. The NASA instrument has been tested mounted on a helicopter and the morpheus test vehicle to demonstrate its performance. In the altitude tests the altitude varied from approximately 50 m to 1700 m (pierrottet papers). The Morpheus test vehicle was launched to a 250 m altitude then descended along a 30 degree path to a simulated landing field. These tests provide useful data to compare with simulated results. The results of Adany et al. are particularly interesting because they include a return spectrum from the 370m experiment. The experiments of Adany et al. fall short in that the targets all had relatively good reflectivity and an approximately 90 degree angle incidence therefore there is little to be learned about spectra resulting from non-ideal conditions. The experiments performed by NASA accurately mimic real world circumstances but no data on the resulting spectra is provided and no information on the performance of the system at long ranges. The simulation proposed will therefore provide insight on data which is not readily available, performance information and spectra from non-ideal scenarios. This data will be useful in

making decisions about doppler lidar system characteristics as well as improving detection algorithms for doppler lidar.

## CHAPTER 3

### RESEARCH AND DESIGN METHODS

The goal of this research project is to ascertain and demonstrate the effects of particular parameters on the performance of a Doppler lidar system. The parameters to be studied are laser transmission power, beam divergence, aperture diameter, and FFT size. These parameters have been selected because of their potential effect on the overall performance, cost, power consumption, weight, and computational power of a system. The results of this research will simplify the task of designing or selecting a Doppler lidar system by providing information about where to best allocate resources to achieve performance requirements.

In order to simulate the effects of these characteristics on a Doppler lidar system, a detailed parametrized simulation of Doppler lidar will be added to the LadarSIM lidar simulation software. The updated LadarSIM software will then be used to simulate various Doppler lidar systems with varying transmission power, beam divergence, aperture diameter, and FFT size then the performance of these instruments will be evaluated in a variety of simulated scenarios by calculating and recording the probabilities of detection and false alarm. LadarSIM is a robust and realistic simulator which accurately simulates the real world behavior of a lidar system. After simulating the true measurements of range and velocity of a scenario, LadarSIM simulates the transmission and return of a beam by modeling the interactions of the beam with the atmosphere, target, receiver optics, and electronics to obtain a simulated returned signal. Using this returned signal and models of the noise in the system the probability of detection and false alarm are calculated. For each simulated beam, the probability of detection and false alarm will be recorded with information about the range and angle of incident to the target. This data will be used to compare the performance of Doppler lidar systems with different parameters. The information about the range and angle of incident will be used to compare performance under different conditions.

In order to make the effect of each parameter as evident as possible, each parameter

will be varied and measured while holding the other parameters constant. This will also cut down on the number of simulations because it will not be necessary to simulate every possible combination of parameters to determine the effects of each parameter. However, the parameters of aperture diameter and laser transmission power are directly related. An increase in one will proportionally offset a decrease in the other. This relationship will be studied and the resulting trade-offs presented.



## CHAPTER 4

### CONCLUSION

Doppler lidar is can contribute useful data in determining altitude, speed, and position of a space craft during the landing phase of a mission. Under the Autonomous Landing and Hazard Avoidance Technology (ALHAT) project, NASA has been developing doppler lidar systems to provide this data [3]. It is clear that Doppler lidar will play a role in forthcoming space exploration missions.

In selecting or designing a Doppler lidar an engineer must determine what parameters the system must have in order to meet mission performance requirements. This task will be simplified by the development of the proposed Doppler lidar simulation. This simulation will be added to the existing LadarSIM software. The result will be a robust parametric simulation tool which will be able to simulate the performance of Doppler lidar systems with arbitrary parameters in arbitrary scenarios.

## REFERENCES

- [1] P. Adany, C. Allen, and R. Hui, “Chirped lidar using simplified homodyne detection,” *Journal of Lightwave Technology*, vol. 27, no. 16, pp. 3351–3357, Aug 2009.
- [2] F. Amzajerdian, L. Petway, G. Hines, B. Barnes, D. Pierrottet, and G. Lockard, “Doppler lidar sensor for precision landing on the moon and mars,” in *2012 IEEE Aerospace Conference*, March 2012, pp. 1–7.
- [3] F. Amzajerdian, D. Pierrottet, L. Petwat, G. Hines, B. Barnes, and G. Lockard, “Fiber doppler lidar for precision navigation of space vehicles,” in *Lasers, Sources, and Related Photonic Devices*. Optical Society of America, 2012, p. FTh3.1A.2. [Online]. Available: <http://www.osapublishing.org/abstract.cfm?URI=FILAS-2012-FTh3.1A.2>