



Thoshith R R 250701797-2025-CSE ▾

**T2****Started on** Sunday, 30 August 2026, 11:02 AM**State** Finished**Completed on** Sunday, 30 August 2026, 11:03 AM**Time taken** 31 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is  $\text{SUM } (A[i] * B[i])$  for all `i` is minimum.

**For example:**

| Input | Result |
|-------|--------|
| 3     | 28     |
| 1     |        |
| 2     |        |
| 3     |        |
| 4     |        |
| 5     |        |
| 6     |        |

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int ascending(const void *a, const void *b) {
5      return (*(int *)a - *(int *)b);
6  }
7
8  int descending(const void *a, const void *b) {
9      return (*(int *)b - *(int *)a);
10 }
11
12 int main() {
13     int n;
14     scanf("%d", &n);
15
16     int a[n], b[n];
17
18     for (int i = 0; i < n; i++)
19         scanf("%d", &a[i]);
20
21     for (int i = 0; i < n; i++)
22         scanf("%d", &b[i]);
23
24     qsort(a, n, sizeof(int), ascending);
25     qsort(b, n, sizeof(int), descending);
26
27     long long sum = 0;
28
29     for (int i = 0; i < n; i++)
30         sum += (long long)a[i] * b[i];
31
32     printf("%lld", sum);
33
34     return 0;
35 }
```

|   | Input                                                     | Expected | Got |   |
|---|-----------------------------------------------------------|----------|-----|---|
| ✓ | 3<br>1<br>2<br>3<br>4<br>5<br>6                           | 28       | 28  | ✓ |
| ✓ | 4<br>7<br>5<br>1<br>2<br>1<br>3<br>4<br>1                 | 22       | 22  | ✓ |
| ✓ | 5<br>20<br>10<br>30<br>10<br>40<br>8<br>9<br>4<br>3<br>10 | 590      | 590 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)