



Thoshith R R 250701797-2025-CSE ▾

T2**Started on** Friday, 21 August 2026, 4:17 PM**State** Finished**Completed on** Friday, 21 August 2026, 4:17 PM**Time taken** 28 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: 3

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: 2

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-231 <= nums[i] <= 231 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int majority(int arr[], int low, int high)
4  {
5      if (low == high)
6          return arr[low];
7
8      int mid = (low + high) / 2;
9
10     int left = majority(arr, low, mid);
11     int right = majority(arr, mid + 1, high);
12
13     if (left == right)
14         return left;
15
16     int leftCount = 0, rightCount = 0;
17
18     for (int i = low; i <= high; i++)
19     {
20         if (arr[i] == left)
21             leftCount++;
22         if (arr[i] == right)
23             rightCount++;
24     }
25
26     if (leftCount > rightCount)

```

```
27         return left;
28     else
29         return right;
30 }
31
32 int main()
33 {
34     int n;
35     scanf("%d", &n);
36
37     int arr[n];
38
39     for (int i = 0; i < n; i++)
40         scanf("%d", &arr[i]);
41
42     printf("%d", majority(arr, 0, n - 1));
43
44     return 0;
45 }
```

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)