

SECTIONAL AERONAUTICAL CHART

SCALE 1:500,000

LEGEND Airports having control towers are shown in **blue**, all others in **magenta**. Consult Chart Supplement for details involving airport lighting, navigation aids, and services. For additional symbol information refer to the Chart User's Guide.

AIRPORTS	AIRPORT DATA	AIRPORT TRAFFIC SERVICE AND AIRSPACE INFORMATION	TOPOGRAPHIC INFORMATION
Other than hard-surfaced runways Seaplane Base Hard-surfaced runways 1500 ft. to 8069 ft. in length Hard-surfaced runways greater than 8069 ft., or same multiple runways less than 8069 ft. Open dot within hard-surfaced runway configuration indicates approximate VOR, VOR-DME, or VORTAC location. All recognizable hard-surfaced runways, including those closed, are shown for visual identification. Airports may be public or private. ADDITIONAL AIRPORT INFORMATION Restricted or Private – (Soft surfaced runway, or hard surfaced runway less than 1500' in length.) Use only in emergency, or by specific authorization. Military – Other than hard-surfaced. All military airports are identified by abbreviations AFB, NAS, AAF, etc. For complete airport information, consult DOD FLIP. Heliport Selected Unverified Abandoned-paved, having landmark value, 3000 ft. or greater Ultralight Flight Park Selected Services-fuel available and field attended during normal working hours depicted by use of ticks around basic airport symbol. (Normal working hours are Mon thru Fri 10:00 A.M. to 4:00 P.M. local time. Consult Chart Supplement for service availability at airports with hard-surfaced runways greater than 8069 ft. Rotating airport beacon in operation Sunset to Sunrise	Box indicators FAR 93 Special Air Traffic Rules & Airport Traffic Patterns FSS NO SVFR FAR 91 Location Identifier CT – 118.3 * ATIS 123.8 285 L 72 122 95 RP 23, 34 VFR Advy 125.0 AOE UNICOM Runways with Right Traffic Patterns (public use) RP Special conditions exist - see Chart Supplement ICAO Location indicator shown outside contiguous U.S. FSS – Flight Service Station NO SVFR – Fixed wing special VFR flight is prohibited. CT – 118.3 – Control Tower (CT) primary frequency * – Star indicates operation part-time (see tower frequencies tabulation for hours of operation). C – Indicates Common Traffic Advisory Frequencies (CTAF) ATIS 123.8 – Automatic Terminal Information Service ASOS/AWOS 135.42 – Automated Surface Weather Observing Systems (shown where full-time ATIS is not available). Some ASOS/AWOS facilities may not be located at airports. UNICOM – Aeronautical advisory station VFR Advy – VFR Advisory Service shown where full-time ATIS not available and frequency is other than primary CT frequency. 285 – Elevation in feet L – Lighting in operation sunset to sunrise *L – Lighting limitations exist, refer to Airport/Facility Directory. 72 – Length of longest runway in hundreds of feet; usable length may be less. When information is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting.	Only the controlled and reserved airspace effective below 18,000 ft. MSL are shown on this chart. All times are local. Class B Airspace Class C Airspace (mode C See FAR 91.215/AIM.) Class D Airspace Ceiling of Class D Airspace in hundreds of feet. (A minus ceiling value indicates surface up to but not including that value). Class E (sfc) Airspace Class E Airspace with floor 700 ft. above surface. Class E Airspace with floor 1200 ft. or greater above surface that abuts Class G Airspace. 2400 MSL 4500 MSL Differentiates floors of Class E Airspace greater than 700 ft. above surface. Class E Airspace exists at 1200' AGL unless otherwise designated as shown above. Class E Airspace low altitude Federal Airways are indicated by center line. Intersection - Arrows are directed towards facilities which establish intersection. 132° V 69 Total mileage 169 Class E Airspace low altitude Federal Airways are indicated by center line. Intersection - Arrows are directed towards facilities which establish intersection. T319 TK313 (helicopter only) RNAV waypoint Prohibited, Restricted, and Warning Areas, Canadian Advisory, Danger, and Restricted Areas. Alert Area and MOA - Military Operations Area Special Airport Traffic Area (See FAR Part 93 for details) ADIZ - Air Defense Identification Zone Mode C (See FAR 91.215/AIM.) National Security Area (TRSA) MTR - Military Training Route IR211 MISCELLANEOUS 1° E – Isogonic Line (2010 VALUE) Ultralight Activity Hang Glider Activity Glider Operations Unmanned Aircraft Activity Parachute Jumping Area (See Chart Supplement.) Marine Light NAME (VPXYZ) VFR Waypoints (See Chart Supplement for latitude/longitude).	Roads & Road Markers Railroad Power Transmission Lines Aerial Cable Landmark Feature - stadium, factory, school, golf course, etc. Outdoor Theater Lookout Tower 618 (Elevation Base of Tower) CG Coast Guard Station Race Track Tank-water, oil or gas Oil Well Water Well Mine or Quarry Mountain Pass 11823 (Elevation of Pass) (Pass symbol does not indicate a recommended route or direction of flight and pass elevation does not indicate a recommended clearance altitude. Hazardous flight conditions may exist within and near mountain passes). Perennial Lake Non-Perennial Lake Dams Bridges and Viaducts
RADIO AIDS TO NAVIGATION	COMMUNICATION BOXES	OBSTRUCTIONS	
VHF OMNI RANGE (VOR) VORTAC VOR-DME Non-Directional Radiobeacon (NDB) NDB-DME Other facilities. i.e., FSS Outlet, RCO, etc.	122.1R 122.6 123.6 382 * OAKDALE OAK Underline indicates no voice on this frequency. Crosshatch indicates Shutdown Status Operates less than continuous or On-Request. ASOS/AWOS HIWAS 122.1R FSS radio providing voice communication 122.1R CHICAGO CHI Heavy line box indicates Flight Service Station (FSS). Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada - 121.5, 126.7 and 243.0) are available at many FSSs and are not shown above boxes. All other frequencies are shown. Certain FSSs provide Airport Advisory Service, see Chart Supplement. R - Receive Only. Frequencies above thin line box are removed to NAVDAG site. Other FSS frequencies providing voice communication may be available as determined by altitude and terrain. Consult Chart Supplement for complete information.	1000 ft. and higher AGL below 1000 ft. AGL Group Obstruction Obstruction with high-intensity lights May operate part-time Elevation of the top above mean sea level 2049 (1149) Height above ground Under construction or reported; position and elevation unverified. NOTICE: Guy wires may extend outward from structures.	