

DRIFTER

A memory for your machine.

A dedicated Raspberry Pi vehicle computer for local OBD-II telemetry, drive logging and incident evidence capture.

Built for intermittent symptoms that can disappear before a diagnostic session begins. DRIFTER is a hardware-integrated prototype under active field hardening, not a finished retail appliance.

REFERENCE VEHICLE

2004 Jaguar X-Type 2.5 L V6

ENGINEERING SOURCE: github.com/thotsl4yer69/drifter

A window around the event.

BEFORE

90s

Available rolling context

EVENT

00

Automatic or manual trigger

AFTER

45s

Configured post-event tail

A full pre-event window needs time to accumulate. The available evidence depends on the supported PIDs, the node being powered and the vehicle link remaining available.

Manual capture marks an event the operator notices. Automatic capture is driven by configured rules, alerts or anomaly events. For a controlled demonstration, a manual capture can exercise the evidence path without causing a fault.

Ordered sensor changes help an investigation. They do not, on their own, prove which component caused the problem.

SOURCE: Incident recorder implementation / PR #69

ILLUSTRATION OF CAPTURE SETTINGS. NOT A FIELD RESULT.

A computer, not just an adapter.

01 VEHICLE LINK

An appropriate ELM327 or SocketCAN-class path. Start the first validation with one transport.

02 COMPUTER

Raspberry Pi 5 is the reference compute direction. Linux runs the local vehicle services.

03 VIEW

A display or browser path gives access to onboarding, capture and recovery.

04 RECORD

Storage holds Linux, configuration, drive logs and incident evidence.

05 SUPPLY

The intended vehicle power path must pass repeated cold starts without manual replugging.

SOURCE: docs/BETA_TESTER_GUIDE.md

Repeatability is the point.

The primary field acceptance issue is still open in the reviewed source. The conditions below are targets, not completed results.

10 cold starts	PENDING
----------------	---------

From the intended vehicle supply, without manual replugging.

30 minutes of telemetry	PENDING
-------------------------	---------

Supported RPM, coolant, speed and voltage recorded continuously.

Connection and recovery	PENDING
-------------------------	---------

Prove the adapter and ECU separately; test adapter and display recovery.

Useful incident evidence	PENDING
--------------------------	---------

Produce and inspect an incident bundle; preserve redacted fault evidence.

A result belongs to a vehicle, adapter and software build. Do not turn standards-based OBD-II targeting into a universal compatibility claim.
SOURCE: Field acceptance issue #67

Use the real project name.

DRIFTER VIM — Vehicle Intelligence Module, by
MAZLABZ.

Keep the supplied wordmark proportions. Use ink on paper or the inverse version. Leave at least half a letter-height clear around the mark. Do not stretch, bevel or add a decorative glow.

The media kit includes vector wordmarks, a profile symbol, campaign artwork, an architecture illustration and a recording-time ribbon. These illustrations are not hardware photographs, real telemetry or compatibility evidence.

Use actual field recordings for claims about operation. The website and its design assets do not establish customer numbers, revenue, reliability or passed vehicle tests.

MEDIA / TECHNICAL / FIELD-TESTING ENQUIRIES

mazlabz.ai@gmail.com

SOURCE: PROJECT_STATUS.md

STATUS SNAPSHOT REVIEWED: 26 SEPTEMBER 2026