

P-201A/B LVGO pumparound / product RATED 198 m3/h @ 138 m, dP 10 bar MOTOR 110 kW, API 682 Plan 1122 DES. T 255 C; MAT'L S-6 (CS/12Cr)	P-202A/B HVGO pumparound / product RATED 391 m3/h @ 144 m, dP 10 bar MOTOR 200 kW, API 682 Plan 538 DES. T 345 C; MAT'L A-8 (316)	P-203A/B Slop wax RATED 12 m3/h @ 114 m, dP 8 bar MOTOR 5.5 kW, API 682 Plan 538 DES. T 410 C; MAT'L A-8 (316)	A-201 Lvgo cooler 397 m2 bare; 1 bay(s) 6 m x 12 m, 2 fans DESIGN 9.7 barg / 125 C DUTY 3.10 MW; 2 x 15 kW fans MAT'L CS tubes, Al fins (A-101; CS + inlet ferrules, Ti optional)	A-202 Hvgo Product cooler 361 m2 bare; 1 bay(s) 6 m x 12 m, 2 fans DESIGN 9.7 barg / 125 C DUTY 6.64 MW; 2 x 37 kW fans SHELL: BFW / LP steam / TUBE: Vacuum residue MAT'L CS tubes, Al fins (A-101; CS + inlet ferrules, Ti optional)	E-201 VR / LP steam generator (kettle) 84 m2; 1 shell(s) DESIGN 6 / 20 barg / 310 C; CA 3 mm DUTY 1.78 MW SHELL: BFW / LP steam / TUBE: Vacuum residue MAT'L CS shell / Scr tubes
---	--	---	---	---	--

