


Matematiksel İşlevler, Karakterler ve Dizeler (Mathematical Functions, Characters, and Strings)

Liang, Introduction to Java Programming, Eighth Edition, (c) 2011 Pearson Education, Inc. All rights reserved. 01B2130807

Matematiksel Fonksiyonlar

Java, Math sınıfında, ortak matematiksel işlevleri yerine getirmek için birçok yararlı yöntem sunmaktadır.

Math sınıfı iki faydalı double sabit (constant) sağlar: PI ve E (doğal logaritmaların tabanı). Herhangi bir programda bu sabitleri Math.PI ve Math.E olarak kullanabilirsiniz.

Trigonometrik Yöntemler

Method	*Description*
`sin(radians)`	Returns the trigonometric sine of an angle in radians.
`cos(radians)`	Returns the trigonometric cosine of an angle in radians.
`tan(radians)`	Returns the trigonometric tangent of an angle in radians.
`toRadians(degree)`	Returns the angle in radians for the angle in degrees.
`toDegrees(radians)`	Returns the angle in degrees for the angle in radians.
`asin(a)`	Returns the angle in radians for the inverse of sine.
`acos(a)`	Returns the angle in radians for the inverse of cosine.
`atan(a)`	Returns the angle in radians for the inverse of tangent.

Math.toDegrees(Math.PI / 2)returns90.0

Math.toRadians(30) returns 0.5236 (same as π/6)

Math.sin(0) returns 0.0

Math.sin(Math.toRadians(270)) returns −1.0

Math.sin(Math.PI / 6) returns 0.5

Math.sin(Math.PI / 2) returns 1.0

Math.cos(0) returns 1.0

Math.cos(Math.PI / 6) returns 0.866

Math.cos(Math.PI / 2) returns0

Math.asin(0.5) returns 0.523598333 (same as π/6)

Math.acos(0.5) returns 1.0472 (same as π/3)

Math.atan(1.0) returns 0.785398 (same as π/4)



Üs AlmaYöntemleri (Exponent Methods)

Method	*Description*
`exp(x)`	Returns e raised to power of x (e^x).
`log(x)`	Returns the natural logarithm of x ($\ln(x) = \log_e(x)$).
`log10(x)`	Returns the base 10 logarithm of x ($\log_{10}(x)$).
`pow(a, b)`	Returns a raised to the power of b (a^b).
`sqrt(x)`	Returns the square root of x ($\sqrt{x}$) for $x >= 0$.

Liang, Introduction to Java Programming, Eighth Edition, (c) 2011 Pearson Education, Inc. All rights reserved. 0132130807

Üs Alma İşlemleri (Exponent Operations)

- Math.pow(**2**, **3**), which returns **8.0**
- Math.exp(**3.5**), which returns **33.11545**
- Math.sqrt(**4**), which returns **2.0**
- Math.log(Math.E), which returns **1.0**



Yuvarlama Yöntemleri (The Rounding Methods)

Method	*Description*
`ceil(x)`	*x* is rounded up to its nearest integer. This integer is returned as a double value.
`floor(x)`	*x* is rounded down to its nearest integer. This integer is returned as a double value.
`rint(x)`	*x* is rounded to its nearest integer. If *x* is equally close to two integers, the even one is returned as a double value.
`round(x)`	Returns `(int)Math.floor(x + 0.5)` if *x* is a float and returns `(long)Math.floor(x + 0.5)` if *x* is a double.

Math.ceil(**2.1**) , returns **3.0**
Math.floor(**2.1**) , returns **2.0**
Math.rint(**−2.1**) , returns **−2.0**
Math.round(**2.6f**) , returns **3** // Returns int
Math.round(**2.0**) , returns **2** // Returns long



Minimum, Maksimum ve Mutlak Değer Yöntemleri (The **min**, **max**, and **abs** Methods)

- Abs yöntemi sayının mutlak değerini döndürür (int, long, float veya double)

Math.max(**2**, **3**) returns **3**
Math.min(**2.5**, **4.6**) returns **2.5**
Math.max(Math.max(**2.5**, **4.6**), Math.min(**3**, **5.6**)) returns **4.6**
Math.abs(**−2**) returns **2**
Math.abs(**−2.1**) returns **2.1**



Rastgele Yöntemi (The **random** Method)

Bu yöntem, 0.0'a eşit veya daha büyük ve 1.0'dan küçük bir rasgele çift değer üretir.(**0 <= Math.random() < 1.0**).

(int)(Math.random() * **10**) // 0 ile 9 arasında rastgele bir tamsayı döndürür.

a + Math.random() * b // a + b hariç, a ile a + b arasında rasgele bir sayı döndürür.



Liang, Introduction to Java Programming, Eighth Edition, (c) 2011 Pearson Education, Inc. All rights reserved. 0132130807

Karakter Veri Tipi ve İşlemleri

- Karakter veri türü (char), tek bir karakteri temsil etmek için kullanılır. Bir karakter değişmezi tek tırnak işareti içine alınır.

- **char** letter = '**A**';
- **char** numChar = '**4**';



```
char letter = 'A';
char letter = '\u0041'; // Character A's Unicode is 0041
```

Characters	*Code Value in Decimal*	*Unicode Value*
'0' to '9'	48 to 57	\u0030 to \u0039
'A' to 'Z'	65 to 90	\u0041 to \u005A
'a' to 'z'	97 to 122	\u0061 to \u007A



Karakterleri Karşılaştırma ve Test Etme

'a' < 'b' is true because the Unicode for **'a'** (**97**) is less than the Unicode for **'b'** (**98**).

'a' < 'A' is false because the Unicode for **'a'** (**97**) is greater than the Unicode for **'A'** (**65**).

'1' < '8' is true because the Unicode for **'1'** (**49**) is less than the Unicode for **'8'** (**56**).



Karakter Sınıfındaki Yöntemler

Character sınıfı, java.lang paketinde tanımlanmıştır. (The **Character** class is defined in the **java.lang** package)

Method	*Description*
tter.	`isLetter(ch)` Returns true if the specified character is a le
tter or digit.	`isLetterOrDigit(ch)` Returns true if the specified character is a le
wercase letter.	`isLowerCase(ch)` Returns true if the specified character is a lo
ied character is an uppercase letter.	`isUpperCase(ch)` Returns true if the specif
the specified character.	`toLowerCase(ch)` Returns the lowercase of
the specified character.	`toUpperCase(ch)` Returns the uppercase of

isDigit('a') is false

isLetter('a') is true

isLowerCase('a') is true

isUpperCase('a') is false

toLowerCase('T') is t

toUpperCase('q') is Q



String Tipi

String, bir karakter dizesidir.

String message = **"Welcome to Java"**;




String Nesneleri için Basit Yöntemler

Method	*Description*
`length()`	Returns the number of characters in this string.
`charAt(index)`	Returns the character at the specified index from this string.
`concat(s1)`	Returns a new string that concatenates this string with string `s1`.
`toUpperCase()`	Returns a new string with all letters in uppercase.
`toLowerCase()`	Returns a new string with all letters in lowercase.
`trim()`	Returns a new string with whitespace characters trimmed on both sides.



String' den Karakter Almak

S.charAt (index) yöntemi, s dizesinde belirli bir karakteri almak için kullanılabilir; burada dizin, 0 ile s.length () - 1 arasındadır.



```
String message = "Welcome to Java";
System.out.println("The length of " + message + " is "
+ message.length());

System.out.println( "Welcome".toLowerCase()); //returns
welcome

System.out.println( "Welcome".toUpperCase()); //returns a new
string WELCOME.

System.out.println( message.charAt(0)); //returns the character
W
```

