VIETNAM NATIONAL UNIVERSITY, HO CHI MINH CITY

UNIVERSITY OF SCIENCE

FACULTY OF INFORMATION TECHNOLOGY



Introduction to Machine Learning (CSC14005)

DATA REPORT

CLASSIFYING SIDEWALK OBSTRUCTION IN HO CHI MINH CITY FROM STREET IMAGES

Instructor: Dr. Bùi Tiến Lên

Class: 24KHMT02

Semester I, academic year 2026–2027

Group 11

Lê Nguyễn Quốc Học – 24127044
Bùi Thị Bích Loan – 24127072
Nguyễn Hữu Gia Minh – 24127078
Nguyễn Lê Hoàng Khải – 24127408
Trần Hoàng Phúc – 24127505

Table of Contents

1 Problem introduction **1**

1.1 The machine learning task 1

1.2 Dataset overview 1

2 Data sources and collection methods **2**

2.1 Sources 2

2.2 Collection pipeline 2

2.3 Annotation 3

2.4 Enriching training with blocked examples 4

2.5 Tools and storage formats 4

3 Cleaning and preprocessing **4**

4 Data quality assurance **5**

4.1 Criteria 5

4.2 Manual checks: agreement and adjudication. 6

4.3 Automated checks 7

5 Storage and data management **7**

6 Exploratory data analysis **8**

6.1 Descriptive statistics 8

6.2 Label distributions 10

6.3 Relationships between attributes 11

6.4 Data quality checks. 12

6.5 EDA of image data 15

6.6 Figures accompanying the analysis 16

7 Summary: measured results and remaining work **24**

7.1 What has been measured 24

7.2 What has not been measured or completed 24

7.3 Implications for modelling 25

A Provenance and reproduction **25**

List of Tables

1 Dataset components and final labels (images) . . . 1
2 Annotation assignments . . . 3
3 Cleaning and preprocessing operations . . . 5
4 Main-component pairwise agreement . . . 6
5 Final-label provenance . . . 6
6 Repository data organization . . . 7
7 Data-table inventory . . . 8
8 Panorama brightness: numeric descriptive statistics . . . 9
9 Distance from capture position to street centreline (m) . . . 9
10 Blocked proportions among usable images, 95% intervals, and I shares . . . 10
11 Association with blocked versus passable labels (usable images) . . . 11
12 Validation/test images close to train-side imagery . . . 14
13 Domain-classification AUC . . . 15
14 Image quality: median (IQR) . . . 15
15 Outstanding work and its implications . . . 24
16 EDA scripts and outputs . . . 26

List of Figures

1 Panorama brightness and street distance by group. 17

2 Capture year and creator distributions. 17

3 Label counts by sampling component and split. 18

4 Usable training-set composition before and after enrichment. 18

5 Label composition on the 17 main streets, excluding pilot. 18

6 Obstacle tags on blocked images and reasons for insufficient information. . . . 19

7 Label shares by annotator; enrichment uses individual v1 responses before cross-checks. 19

8 Spearman correlations among numeric metadata attributes. 19

9 Similarity distributions: same position on different days, same street at different positions, and different streets. 20

10 Image positions by split; evaluation streets intersect training streets. 21

11 DINOv2 embedding t-SNE for 5,149 images, coloured by component and label; descriptive illustration only. 21

12 Random main-train examples by label. © Mapillary contributors, CC BY-SA 4.0. 22

13 Additional train examples by sampling stratum; corner labels identify 0, 1 or I. © Mapillary contributors, CC BY-SA 4.0. 22

14 Crop luminance by component and label. 22

15 Crop sharpness on a log scale, by component and label. 23

1. Problem introduction

1.1. The machine learning task

A sidewalk can exist but fail to provide a usable walking route when parked vehicles, goods, furniture or barriers interrupt its continuity. The project builds an image classifier to screen for this condition in street images from Ho Chi Minh City.

The input is one 640×640 image of one side of a sidewalk. Label 0 – Passable means a pedestrian can continue along the near sidewalk; 1 – Blocked means the pedestrian must step into the roadway. Images with insufficient evidence (the near sidewalk is invisible or occluded, or the image is unusable) receive I – Insufficient information and are excluded from model training and evaluation. They remain in the descriptive statistics because they determine the usable yield of the source.

The research question is which model performs best on *streets absent from training*. Splits therefore contain entire streets, and leakage checks are central to the report. Annotators answer: must a pedestrian step into the roadway to continue along the near sidewalk?

1.2. Dataset overview

The three collection components have different sampling designs and are reported separately. Only the main component follows the natural distribution of images along the selected streets.

Table 1: Dataset components and final labels (images)

Component	Images	0	1	I
Main, train (10 streets)	1,839	939	106	794
Main, validation (3 streets)	486	207	35	244
Main, test (4 streets)	674	412	47	215
Pilot, train (3 streets)	150	73	14	63
Additional train images (75 streets)	2,000	819	577	604
Total	5,149	2,450	779	1,920

Source: `data/labels/main_labels_v1.csv`; `data/labels/train_extra_labels_v2.csv`.

Validation and test contain only main images. Pilot images were sampled by score strata of a trial model; additional images were sampled 70% by selector score and 30% randomly from the remainder. Both components enter training only. Validation/test labels are used descriptively, not to tune thresholds or select samples. In the main component, 188/1,746 usable images (10.8%) are blocked; roughly 40% of all images lack sufficient information.

2. Data sources and collection methods

2.1. Sources

The team constructed its own dataset from source imagery rather than adopting an existing labelled dataset. Vietnamese Sidewalk Violation VQA [1] is related, but lacks the coordinates and capture times needed for street-based splitting; none of its images or labels were used. Panoramas and metadata came from the Mapillary Graph API [2]. Streets and contextual points (markets and schools) came from OpenStreetMap [3] through Overpass API. There was no web scraping, questionnaire or survey. Five members annotated images in Label Studio [4].

Mapillary images are licensed CC BY-SA 4.0: © Mapillary contributors, CC BY-SA 4.0. Existing face and licence-plate blurring was retained. Images are not committed to Git. The team has not yet collected its own photographs, although the proposal planned at least 100.

The study covers central Ho Chi Minh City (the former Districts 1, 3, 5, 10, Phú Nhuận and Bình Thạnh), within 10.745–$10.815°$ N and 106.650–$106.725°$ E. The scan on 22 October 2026 found 652,159 panoramas in 1,234 sequences, mainly from `bemaps3_sg`, `phoenix_mapping_front` and `phoenixmap_front`, timestamped 2016, 2023 and 2024. The 2016 timestamps are questionable, as discussed below.

2.2. Collection pipeline

1. Retrieve named OSM streets and contextual points: 7,283 street segments and 6,715 points (`01_osm_streets.py`).
2. Scan panorama metadata in $0.001°$ grid cells: 652,159 images; two small corner cells failed (`02_fetch_mapillary_meta.py`).
3. Assign images to streets within 20 m and within $30°$ of the street axis, excluding alleys: 81.3% can be assigned (`03_rank_streets.py`).
4. Preview 56 streets at 20 positions each; exclude seven canal, bridge or tunnel streets and select 17 (`04_street_preview.py`).
5. Assign entire streets to splits before annotation: 10 train, three validation and four test (`configs/streets_v1.yaml`).
6. Annotate 150 pilot images from three train streets with all five annotators. Fleiss' κ [5] was 0.57 under guide v0; the guide was rewritten as v1 (`10_make_pilot_v2.py`).
7. Collect main images at positions 25 m apart, at most two images per position on different days, capped at 420 per street, excluding pilot positions. Of 3,057 selected panoramas, reject 58 night images and retain 2,999 (`11_collect_main.py`). Subsequent geographic checks identify some nearby pilot/main positions despite this design rule.
8. Annotate, measure agreement and adjudicate; obtain final labels for 3,149 main and pilot images.
9. Add 2,000 train images from 75 new streets, yielding 577 additional blocked images.

Source: `docs/collection_log.md`; scripts in `src/collection/` and `src/labeling/`.

Projection and cropping. Each panorama yields exactly one perspective crop looking to the vehicle's right, $60°$ from travel direction, pitched down $4°$, with $90°$ field of view, 640×640 resolution and JPEG quality 90. Exploratory measurements, not labels, motivated these choices. On 1,166 panoramas, a strict automatic measure found the near sidewalk in 38% of right views and 7% of left views. Left views mostly showed the road, median or opposite sidewalk; consequently, the left sidewalk on one-way streets is underobserved. The $60°/4°$ setting gave the highest near-sidewalk visibility among six combinations (yaw 60/75/90 degrees and downward pitch 4/10 degrees).

Source: `src/analysis/08_side_analysis.py`; `src/analysis/09_crop_param_study.py`; `src/common.py`.

Street splits. Four test streets occupy different areas. Street assignments were determined on 23 October 2026, before main annotation. They are assigned but not yet frozen because train images near validation/test intersections require a decision. Keep the predetermined test streets: the 47 test positives limit evaluation precision and are not a criterion for changing the test set after inspecting its labels.

2.3. Annotation

Humans used guide v1 (`labeling/guide/annotation_guide_v1_draft.md`, whose wording had been agreed). The decision sequence is:

1. Is the image usable? Blur, darkness or overexposure that prevents judgement leads to I.
2. Is the near sidewalk visible? A segment of its edge must fall below the line at three-fifths of image height. Road-only scenes, distant sidewalks, intersections, alley entrances or major occlusion lead to I.
3. Is a continuous path available? If not, choose 1. Moving people and vehicles are not obstacles; only obstacles up to approximately the image midpoint count.

Annotators could give one of four reasons for I, six optional obstacle tags, a difficult/uncertain flag and free-text notes. The interface is `labeling/label_studio/ls_label_config_v1.xml`.

Table 2: Annotation assignments

Component	Images	Assignment
Test	674	Học and Loan independently annotate every image
Validation	486	Minh and Khải independently annotate every image
Main train	1,839	One annotator per image; 276 (15%) independently cross-labelled
Pilot	150	Five annotators under v0; all images subsequently reviewed under v1
Additional train	2,000	400 randomly allocated images per annotator; 203 cross-checked

Annotators did not see street names, splits, model scores or others' responses. Splits were mixed in each project. The main component has all $5 \times 887 = 4,435$ expected annotation records.

Source: `docs/labeling_phase1.md`; assignment CSVs in `data/manifest/`.

2.4. Enriching training with blocked examples

After initial annotation, training had only 120 blocked images, including 14 pilot images. Enrichment targeted the rare class [6] and entered training only.

1. **Selector:** logistic regression on DINOv2 ViT-B/14 embeddings [7], trained on 1,989 train labels (120 positives). Selection used leave-one-street-out comparisons on train labels only. The top 20% contained 22.0% blocked images, versus 13.9% for the previous scorer (difference +8.2 percentage points, 95% CI [4.3, 11.7]) and 5.8% under random sampling.
2. **Streets:** scan 150 unused streets, 30 images each; rank mean selector scores and take the top 75. Reject names matching validation/test streets, including other segments with the same name.
3. **Images:** from 5,035 eligible candidates, select 1,400 highest-scoring images (top_score, score at least 0.61) and 600 random images from the remainder (random). Exclude position centres within 40 m of validation/test; individual-image distances are checked separately below.
4. **Labels:** one human per image, unaware of its sampling stratum.

Scores only select images for humans; they never serve as labels. Targeted selection induces sampling bias [8]. The 30% random remainder stratum measures selector yield on new streets, but is not an unconditional random sample of the full candidate pool. Results always separate enrichment from the main component.

Source: `docs/data_enrichment.md`, sections 7–9; scripts 21, 23 and 24; `data/streets/selector_benchmark.csv`.

2.5. Tools and storage formats

Overpass API and shapely produce OSM JSON; Mapillary, requests and pandas produce metadata Parquet and 2,048-pixel panorama JPEGs. py360convert and Pillow produce crop JPEGs. Manifests are UTF-8 CSV, one row per image. Label Studio runs on AWS with Docker/Caddy; raw exports are JSON and final labels are CSV. Agreement and descriptive statistics use pandas, SciPy and scikit-learn. Torch/Transformers provide DINOv2, CLIP [9] and SegFormer [10] for exploratory selection measurements; embeddings are NPZ. Street configurations are YAML. EDA outputs are CSV, JSON, PDF and JPEG, generated with pandas, SciPy and Matplotlib.

3. Cleaning and preprocessing

Filtering uses rules rather than a model; source data are not overwritten.

Table 3: Cleaning and preprocessing operations

Operation	Method and result
Night images	Filter upper-half panorama brightness around threshold 90 (0–255). Capture hour is unreliable. Reject 58/3,057 main images and 38/5,074 enrichment candidates; one rejected brightness is recorded as exactly 90 after rounding.
Off-street imagery	Require distance at most 20 m and heading within 30 degrees of the street axis; exclude alleys. Assignment yield: 81.3%.
Unjudgeable images	Humans assign I, retaining records but excluding them from modelling: 1,920/5,149 images.
Exact duplicates	Use each panorama once and check crop MD5 hashes.
Near duplicates	Sample positions 25 m apart, at most two capture dates per position. Enrichment also checks dHash [11] within positions, rejecting one pair. Main images are assessed in this report.
Missing values	Images without coordinates or heading cannot be assigned to streets and are excluded earlier. Every annotation requires a primary label.
Transformation	Uniform panorama-to-perspective projection to 640×640. Pixel normalization remains a training-stage operation.
Types	Convert Vietnamese Label Studio strings to 0/1/I; replace 64-bit panorama IDs with anonymous eight-character crop IDs. Capture timestamps remain timezone-aware ISO strings.
Consistency	Collection rejects conflicting street assignments; EDA rechecks keys, splits, streets and coordinates.

Sensitive-content review beyond Mapillary's existing blur and final split freezing remain pending.

Source: `docs/collection_log.md`; collection-status CSV; `docs/data_enrichment.md`.

4. Data quality assurance

4.1. Criteria

Quality criteria are: labels match the operational definition and annotators agree; evaluation retains natural sampling; splits avoid leakage; every image has traceable provenance; images provide sufficient visual evidence; and the rare class has enough examples for meaningful evaluation. Checks combine double annotation, 15% train cross-labelling, Cohen's κ [12], adjudication, street-level splitting, geographic and content comparisons, manifest validation, night filtering and class counts with uncertainty

intervals. The proposal set an agreement threshold of 0.6.

4.2. Manual checks: agreement and adjudication

Table 4: Main-component pairwise agreement

Group	Images	Agreement	3-label κ	0/1 κ
Test (Học–Loan)	674	79%	0.60	0.68
Validation (Minh–Khải)	486	80%	0.64	0.55
Cross-labelled train (10 pairs)	276	78%	0.61	0.56

Binary κ uses only images where both annotators chose 0 or 1 (418 test and 211 validation images). All three groups meet the proposal's threshold for the three-label point estimate; pilot Fleiss' κ under v0 was 0.57. Confidence intervals for κ have not been measured.

Of 1,436 double-labelled images, 303 disagreed: 193 were 0/I, 51 were 1/I and 59 were 0/1. Most disagreement therefore concerned judgeability. **Khải adjudicated all 303 main images and changed 28 labels (9.2%); final labels are those Khải approved.** All 28 changed labels matched one of the original annotators. All 150 pilot images were separately reviewed under v1; Phúc changed three proposed labels, and 29 final labels differ from the v0 majority.

Additional images have one annotator each, so no inter-annotator κ is available for that component. Blocked shares differ (Học 43%, Loan 19%); the original image-independent chi-square calculation gives $p = 4 \times 10^{-15}$, but ignores street dependence and is not decisive evidence. Random allocation suggests possible annotation differences, which require a common independently annotated sample to verify. A second member checked 203 images selected from 264 suspected cases: 186 matched (92%) and 17 changed. This targeted sample does not estimate label noise in all 2,000 images.

Source: `data/labels/main_report/main_report.md`; `docs/labeling_phase1.md`; main/pilot adjudication proposals; `data/labels/train_extra_cross_check.csv`.

Table 5: Final-label provenance

Source code	Images	Meaning
agreed	1,133	Main: two annotators agree
single, main	1,563	One train annotator
adjudicated_proposal	275	Main adjudicator retains proposal
adjudicated_phuc	28	Legacy CSV code; Khải changes the label
pilot_review_proposal	147	Pilot reviewer retains proposal
pilot_review_phuc	3	Pilot reviewer changes proposal
single, enrichment	1,983	Includes 186 matching cross-checks
cross_check	17	Enrichment label changed after cross-check

The legacy code adjudicated_phuc remains for traceability and script compatibility; it does not identify the adjudicator. The team confirmed Khải performed main adjudication. Correcting attribution changes neither labels nor counts. Pilot review is reported separately.

4.3. Automated checks

Collection scripts reject streets already assigned elsewhere, including validation/test base-name matches. Agreement scripts check annotation completeness, duplicate saves and interface version. EDA checks keys, splits, coordinates, outliers, duplicates, similarity and geographic separation; results appear in Section 6.4.

5. Storage and data management

Table 6: Repository data organization

Path	Contents	Git
`configs/streets_v1.yaml`	17 main streets and splits	Yes
`configs/streets_train_extra.yaml`	75 enrichment streets	Yes
`data/manifest/`	Provenance, coordinates, dates, streets, splits, strata and assignments	Yes
`data/labels/main_labels_v1.csv`	3,149 main and pilot final labels	Yes
`data/labels/train_extra_labels_v2.csv`	2,000 enrichment final labels	Yes
`data/labels/*_report/`	Annotation, agreement and adjudication tables	Yes
`data/labels/raw/`	Raw exports containing account emails	No
`data/streets/`	Rankings, selector scores and exploratory results	CSV
`data/raw/`	OSM, metadata, panoramas and embeddings	No
`data/crops/`	Main, pilot and enrichment crops	No
`docs/data_report/`	Reports, EDA tables and figures	Yes

The primary key is the eight-character item; labels join manifests on this key and image paths are `data/crops/<file>`. Images can be reconstructed from panorama IDs and yaw using script 27 or collection scripts. Reconstructed JPEGs differ from server copies: an earlier five-image comparison measured mean differences of 1.35–1.5 grey levels. Label filenames encode versions, older files remain available, original responses remain in Label Studio, and final labels reside in the repository. Tokens and server passwords are in ignored `.env` files.

6. Exploratory data analysis

Statistics separate six groups: natural main train/validation/test, pilot, enrichment top_score, and enrichment random. Pooled results are explicitly identified. Validation/test labels are descriptive only. Unless stated otherwise, 95% proportion intervals are Wilson intervals [13], assuming independent images; within-street dependence can make these too narrow. Important comparisons also use 1,000 street-cluster bootstrap replicates. Validation has only three streets and test four, so their cluster intervals are exploratory.

6.1. Descriptive statistics

Samples, attributes and missingness

Table 7: Data-table inventory

Table	Rows	Columns	Missingness
Main + pilot labels	3,149	8	2,114 missing reasons: 1,833 structural for 0/1; 281 I without reason
Enrichment labels	2,000	11	1,403 missing reasons, including seven I images
Main manifest	2,999	21	None
Pilot manifest	150	21	None; no position-group field
Enrichment manifest	2,000	25	None
Main annotation records	4,435	13	Optional/conditional reason, obstacle and note fields
Enrichment annotation records	2,000	13	Same conditional design

Each image has one label and roughly 20 metadata attributes. Seven numeric attributes cover coordinates, panorama brightness, street distance, travel heading, crop angle and (for enrichment) selector score. Others identify street, split, creator, sequence, capture time, sampling stratum and label provenance. Models take images only; metadata support splitting, provenance and checks.

All retained metadata cells are present because missing coordinates or heading prevent street assignment. The 281 I images without reasons comprise 162 adjudicated images, 63 reviewed pilot images, 55 double-I agreements with different reasons and one singly labelled image. Main-component reason statistics therefore use 1,035/1,253 I images; the primary labels are unaffected.

Source: `tables/inventory_tables.csv`; `tables/inventory_columns.csv`.

Table 8: Panorama brightness: numeric descriptive statistics

Group	n	Mean	Median	Variance	Min	Max	IQR
Main train	1,839	166.8	171.0	448.6	94	231	27.0
Validation	486	154.5	158.5	468.9	91	201	32.0
Test	674	169.4	171.0	564.2	91	249	26.8
Pilot	150	169.2	173.5	573.5	94	236	27.0
Top score	1,400	172.0	176.0	366.8	91	239	19.0
Random	600	172.7	176.0	377.9	94	238	22.3

Brightness is the upper-half panorama mean on a 0–255 scale.

Table 9: Distance from capture position to street centreline (m)

Group	n	Mean	Median	Variance	Min	Max	IQR
Main train	1,839	3.70	3.0	9.67	0.0	20.0	3.40
Validation	486	3.46	3.1	8.53	0.0	18.4	3.08
Test	674	3.54	2.9	9.48	0.0	19.6	3.70
Pilot	150	3.45	2.7	7.98	0.0	17.0	3.58
Top score	1,400	2.87	2.2	6.81	0.0	19.9	2.70
Random	600	2.96	2.3	7.24	0.0	19.8	2.90

No retained panorama has brightness below the night threshold (minimum 91). Validation is darker (median 158.5 versus 171), possibly reflecting its three streets. Street distance is truncated at 20 m by design; enrichment is closer to centrelines, consistent with 71% coming from smaller streets. Selector-score medians are 0.80 (range 0.61–1.00) for top-score images and 0.19 (0.00–0.61) for random-remainder images. Annotation time is strongly right-skewed: medians 3.7 s for main records and 4.5 s for enrichment, maximum 77,451 s from tasks left open. Median is the useful summary; pilot timing is not measured here.

Source: `tables/desc_numeric.csv`. This file also includes coordinates, heading, selector scores and annotation time.

Categorical distributions

Two creators, bemaps3_sg and phoenix_mapping_front, contribute 84% of main images (1,153 and 1,370 of 2,999) and 98% of enrichment, limiting device diversity. Main capture years are 2023 (2,303 images), 2024 (660) and 2016 (36). Across components, all 103 images timestamped 2016 belong to bemaps3_sg and have date 1 January 2016, suggesting a placeholder. Capture hour is unreliable and is not used for filtering. The main component has 17 streets with 86–348 images each (median 150);

enrichment has 75 with 6–157 (median 21). Hoàng Sa and Trường Sa#0 contribute 274 enrichment images (14%).

Source: `tables/cat_distributions.csv`; `tables/tabular_numbers.json`.

6.2. Label distributions

Table 10: Blocked proportions among usable images, 95% intervals, and I shares

Group	All	Blocked/usable [Wilson]	Street bootstrap	I share
Main train	1,839	106/1,045: 10.1% [8.5,12.1]	[7.9,14.1]	43.2%
Validation	486	35/242: 14.5% [10.6,19.5]	[8.2,19.2]	50.2%
Test	674	47/459: 10.2% [7.8,13.4]	[5.7,18.7]	31.9%
Main pooled	2,999	188/1,746: 10.8% [9.4,12.3]	[8.7,13.9]	41.8%
Pilot	150	14/87: 16.1% [9.8,25.2]	[10.0,18.4]	42.0%
Top score	1,400	531/1,018: 52.2% [49.1,55.2]	[47.8,56.6]	27.3%
Random	600	46/378: 12.2% [9.3,15.9]	[8.9,15.3]	37.0%

Usable images have labels 0 or 1. Main imbalance is about eight passable images per blocked image (0:1 ratio 8.3). The ratios for train/validation/test, pilot, top-score and random are respectively 8.9, 5.9, 8.8, 5.2, 0.9 and 7.2. Across all main images including I, blocked share is 6.3% [5.5,7.2]. Split intervals overlap, which does not establish equivalent proportions. Test has only 47 positives and validation 35; street bootstrap uncertainty is large. I consumes 32–50% by split. Pilot and top-score positive rates reflect selection rather than street prevalence. Random-remainder enrichment has a similar observed proportion to main, with overlapping intervals.

After enrichment, training has 2,528 usable images and 697 positives (27.6%, 0:1 ratio 2.6), versus 1,132 usable images and 120 positives (10.6%) beforehand. Enrichment supplies 577/697 positives (83%). This changes training class prevalence relative to validation/test (about 10–15%); report a natural-data-only training comparison and consider class weighting or resampling.

Blocked proportions vary by street, from 7/74 on Lê Văn Sỹ to 15/39 on Hải Thượng Lãn Ông. I shares range from 17% to 83% (Pasteur, a one-way street). Street association supports street-level splitting.

Parked motorcycles are the most common obstacle: 123/188 blocked main images (65%) and 346/577 enrichment images (60%). Goods/stalls account for 32% and 37%, parked cars 4% and 2%; multiple tags per image are allowed. Tags are optional: 13 blocked main and six enrichment images have

none. Pilot obstacle tags are not measured here. Missing-sidewalk reasons dominate I among images with reasons: 880/1,035 main images (85%) and 463/597 enrichment images (78%), followed by occlusion. Blur/darkness/overexposure accounts for 12 and 21 images. Tags are unions from annotation records selecting label 1; stale tags on 0/I records are excluded.

Enrichment blocked shares range from 19% (Loan) to 43% (Học), suggesting potential annotation differences under random allocation, but requiring a common independently annotated sample for confirmation. Main annotator shares are confounded with split because annotators saw different assigned subsets.

Source: `tables/label_counts_by_group.csv`; `tables/train_composition.csv`; `tables/labels_by_street.csv`; `tables/obstacle_tags.csv`; `tables/reasons_I.csv`; `tables/annotator_label_shares.csv`.

6.3. Relationships between attributes

Images are model inputs; metadata associations help identify redundancy and possible shortcut risks. Latitude–longitude Spearman correlation is 0.42 in main and 0.43 in enrichment, reflecting the study area's shape and street directions. Other absolute correlations are at most 0.14 and 0.25 respectively. The maximum VIF is 1.27 (main latitude), with other variables below 1.1: no substantial multicollinearity is evident among the variables tested.

Table 11: Association with blocked versus passable labels (usable images)

Attribute	Main pooled (1,746)	Enrichment (1,396)
Numeric: AUC and street-bootstrap interval (0.5: no discrimination)		
Panorama brightness	0.53 [0.47,0.59]	0.49 [0.45,0.53]
Street distance	0.54 [0.50,0.58]	0.46 [0.43,0.49]
Latitude	0.45 [0.37,0.52]	Interval includes 0.5
Longitude	0.45 [0.35,0.54]	Interval includes 0.5
Selector score	Not available	0.78 [0.75,0.81]
Categorical: bias-corrected Cramér's V [14] (0: no association)		
Street	0.18	0.29
Road type	0.00 (two levels)	0.14 [0.06,0.24]
Creator	0.00	0.03
Capture year	0.02	0.03

Street is the strongest main metadata association, for blocked (V=0.18) and I (V=0.28). Road type has an association in enrichment: in its random remainder, blocked shares are 34/248 (13.7%) on tertiary roads, 4/20 (20%) residential, 3/43 (7.0%) primary and 5/67 (7.5%) secondary. Small groups imply wide intervals; main has only large roads. Main brightness, distance and coordinates show weak discrimination; intervals include 0.5, while creator/year effects are small. Selector AUC 0.78 reflects

enrichment design and is not a permissible model feature or label. In main train alone, longitude AUC is 0.37 [0.28,0.47], with blocked images farther west; only 10 streets make street composition a plausible explanation rather than a geographic rule. CSV p-values assume image independence and can be optimistic; interpretation focuses on effect sizes.

Source: `tables/assoc_numeric.csv`; `tables/assoc_categorical.csv`; Spearman and VIF tables.

6.4. Data quality checks

Validity and consistency

Script 28 reports 71 automated checks: 62 pass and nine fail. It changes no data. All 5,149 IDs are unique; label/manifest joins are one-to-one; split/street assignments match configurations; no street or position-group ID spans splits; no panorama is reused; label values, right-side cropping and licence values are valid. Retained panorama brightness has minimum 91. The failures are documented rather than silently corrected:

- Missing reasons for 281 main/pilot I images and seven enrichment I images, largely due to final-review structure.
- Stale obstacle tags on 285/4,435 main and 119/2,000 enrichment records labelled 0 or I; obstacle statistics use only label-1 records.
- Two enrichment coordinates lie less than 4 m outside the bounding box, consistent with rounded boundaries; retain them.
- One travel bearing is 360.0 rather than in $[0, 360)$; geometrically equivalent to zero.
- 103 capture dates are 1 January 2016; treat them as questionable, not as a filtering/splitting criterion.
- Five pilot images lie within 5 m of main images (minimum 2.9 m); both sides belong to train, so this is not cross-split leakage.
- One rejected-night brightness is recorded as exactly 90 after rounding, so the strict check that all rejected values are below 90 fails.

The missing-reason and stale-tag categories each contribute two failing checks, giving nine failures overall.

Source: `tables/consistency_checks.csv`; `tables/bbox_violations.csv`.

Outliers and unusual observations

Under the $1.5\times$IQR rule [15], main metadata have 81 brightness outliers (63 low, 18 high) and 113 large street distances; enrichment has 113 and 71 respectively. These are distribution tails rather than invalid entries: retained brightness is 91–249 and distance 0–20 m. Among all 5,149 crops, there are 87 luminance outliers (seven low, 80 high), 36 contrast outliers and 115 very-low-sharpness images on the

log scale. In total, 308 images violate at least one image-outlier threshold. There are 128 images with more than 20% overexposed pixels; test has 33 (4.9%), validation 25 (5.1%) and main train 36 (2.0%). Of the 33 test cases, 27 are on Hai Bà Trưng.

Visual contact-sheet observations (not quantitative measurements) suggest the darkest examples mostly show shade, overpasses or overcast conditions; bright examples are overexposed but often still judgeable; blurry examples often show low light or motion. No outliers were removed: unusable cases already receive I, and the remainder reflect real capture conditions.

Night-filter review. The earlier visual review examined all 58 rejected main panoramas and the 58 darkest retained ones. Approximately 48 rejected images were night scenes, nine appeared daytime under dense canopy and one twilight (brightness 68–89). None of the 58 reviewed retained images appeared to be night scenes, although about three were twilight. This does not establish that every retained image is daytime. The nine daytime and one twilight rejections amount to about 0.3% of all 3,057 inputs. The 38 rejected enrichment images have not been reviewed.

Source: `tables/image_outliers.csv`; `tables/image_night_check.csv`; internal contact sheets (not in Git).

Duplicates and near duplicates

No two files share an MD5, no decoded pixel arrays are identical, and no source panorama is repeated among 5,149 images. No pair has 64-bit dHash distance at most four. The nearest cross-split distance is six; visual review found different places with similar bright sky regions. There are 1,709 positions with images from two days (1,363 main, 346 enrichment), always in the same split. Same-position pairs have minimum dHash 12, median 31 (similar to different-street pairs); DINOv2 cosine similarity has median 0.63 and maximum 0.905. Changing vehicles, stalls and lighting support retaining both dates. Neither dHash nor cosine reliably separates the same place from a similar scene; this report therefore does not set a content-based near-duplicate cutoff.

Source: `tables/duplicate_numbers.json`; `tables/dup_population_quantiles.csv`; `tables/dup_pair_counts_aggregated.csv`.

Cross-split leakage

For each validation/test image, content-based nearest neighbours are searched across main train, pilot and enrichment. Nearest cosine similarity has validation median 0.78, maximum 0.909, and test median 0.79, maximum 0.904. The different-train-street reference has median 0.81 and maximum 0.933. Seven validation/test images have similarity at least 0.90 to train images, but are 778–3,585 m away. Visual review of the 20 highest-scoring pairs found different places with similar scenes.

Street splitting does not prevent intersections between streets from different splits.

Table 12: Validation/test images close to train-side imagery

Pair	Min m	< 15 m	< 25 m	< 40 m	< 100 m
Validation (486)–main train	1.5	6	6	14	47
Validation–pilot	17.9	0	1	5	17
Validation–enrichment	41.6	0	0	0	71
Test (674)–main train	7.1	8	18	34	88
Test–pilot	20.9	0	2	4	7
Test–enrichment	34.3	0	0	3	116

Overall, 52/1,160 validation/test images (4.5%) are within 40 m of a train-side image, involving 47 train-side images and 13 intersecting street pairs (for example Hồng Bàng–Nguyễn Trãi, Lý Thường Kiệt–Cách Mạng Tháng Tám, and Hai Bà Trưng–Điện Biên Phủ). The 20 closest pairs (1–14 m) usually face different directions, but some show shared street corners, poles, signs or fences. Content similarity misses these cases: their maximum cosine is only 0.82. One enrichment image is 34.3 m from test: the original 40 m rule applied to 25 m position centres rather than individual images. Of 551 Mapillary sequences, 53 contain both train-side and validation/test imagery; this shares device/capture conditions without necessarily sharing scene content.

Proposed action, not yet applied: remove train-side images within 40 m of validation/test using coordinates alone (at most 47 images), or retain the dataset and additionally report evaluation excluding the 52 nearby validation/test images. Before training, choose and document the geographic policy, save a versioned frozen manifest and rerun affected checks/statistics. Do not replace test streets based on observed positive counts.

Source: `tables/dup_spatial_vt_to_train_side.csv`; `tables/dup_spatial_street_pairs_lt40m.csv`.

How different is enrichment?

A linear domain classifier on DINOv2 embeddings distinguishes image components without using obstruction labels. It uses StandardScaler and balanced logistic regression, five-fold stratified street-grouped cross-validation with three repetitions. The table reports mean fold AUC; fold standard deviations range from 0.02 to 0.08.

Table 13: Domain-classification AUC

Comparison	AUC
Main train–top-score enrichment	0.95
Main train–random enrichment	0.70
Enrichment–validation + test	0.83
Main train–validation + test	0.47
Control: randomly partition main train streets	0.51

The classifier did not detect a main-train versus validation/test domain difference; AUC near 0.5 does not prove equal distributions, especially with 17 streets. Enrichment is distinguishable, including the random remainder (0.70): smaller market-adjacent streets differ from larger evaluation streets. Top-score images are also more homogeneous (mean within-group cosine 0.60 versus 0.49–0.51). The extra 577 positives therefore come from a narrower scene range. The t-SNE visualization [16] illustrates clustering of blocked/top-score images and I images but is not used as inferential evidence.

Source: `tables/dup_domain_classifier_auc.csv`; `tables/duplicate_numbers.json`.

6.5. EDA of image data

Format and resolution

All 5,149 files decode successfully as RGB JPEG, 640×640, with estimated JPEG quality 90. Sizes range from 38.5 to 167.7 KB (median 99.3 KB). Resolution is uniform by design; 2,048-pixel source panoramas limit detail in distant objects.

Image quality

Per-crop measures are mean Rec.601 greyscale luminance (0–255), greyscale standard deviation (contrast), dark-pixel share (< 30), overexposed-pixel share (> 245), Laplacian variance (sharpness), and colourfulness [17].

Table 14: Image quality: median (IQR)

Group	n	Luminance	Contrast	Sharpness	Colourfulness
Main train	1,839	101.9 (31.3)	59.4 (14.1)	494 (254)	25.1 (13.3)
Validation	486	106.7 (36.9)	62.7 (14.1)	560 (354)	26.7 (13.7)
Test	674	104.7 (36.9)	59.3 (14.2)	511 (245)	25.9 (14.0)
Pilot	150	106.6 (38.0)	59.3 (14.0)	487 (244)	24.5 (13.1)
Top score	1,400	91.8 (30.5)	60.1 (13.7)	492 (260)	27.8 (14.3)
Random	600	100.8 (35.2)	58.1 (12.4)	497 (268)	25.7 (13.7)

Across all images, luminance ranges 24.3–242.3, contrast 17.4–96.6, sharpness 22–1,881 and colourfulness 4.8–104.3. Natural main splits, pilot and random enrichment have broadly similar descriptive quality: luminance medians 101–107 and sharpness 487–560. Validation has somewhat higher contrast than train (AUC 0.58 [0.54,0.61]).

Blocked main images are darker than passable images: median luminance 90.9 versus 101.6, AUC 0.37 [0.32,0.41] under the 17-street bootstrap, and dark-pixel shares 18% versus 12%. Obstacles under awnings or trees are a plausible but unverified explanation. Darkness may become a shortcut, to be checked in model error analysis. Top-score enrichment is darker than main train (91.8 versus 101.9), partly reflecting more positives. I images have higher contrast and overexposure than label 0 (AUC 0.67 and 0.65), consistent with more sky and road. Sharpness does not clearly discriminate labels (AUC 0.46–0.59; intervals include 0.5).

Night-filter panorama brightness correlates weakly with crop luminance: Spearman 0.18 [0.09,0.27] in main, 0.31 for the crop's upper half. They measure different regions, so a panorama-level night filter does not guarantee a bright crop. Of 33 I images citing blur/darkness/overexposure (12 main, 21 enrichment), median sharpness ranks at the 3.5th percentile of main and 13th of enrichment. Brightness mixes dark and overexposed images: 36% below percentile 10, 18% above percentile 90. This small sample supports description only.

Source: `tables/image_format_check.csv`; `tables/image_summary_stats.csv`; `tables/image_effect_sizes.csv`; `tables/image_spearman_brightness.csv`; `tables/image_reason_blur_dark_summary.csv`.

6.6. Figures accompanying the analysis

The figures below preserve the original measured plots, numeric annotations and visual encodings. Vector chart labels and captions are translated into English; Vietnamese street and personal names remain unchanged. Image example grids use training images only and retain their original raster annotations. Label meanings are Passable (0), Blocked (1), and Insufficient information (I).




Figure 1: Panorama brightness and street distance by group.




Figure 2: Capture year and creator distributions.




Figure 3: Label counts by sampling component and split.




Figure 4: Usable training-set composition before and after enrichment.




Figure 5: Label composition on the 17 main streets, excluding pilot.




Figure 6: Obstacle tags on blocked images and reasons for insufficient information.




Figure 7: Label shares by annotator; enrichment uses individual v1 responses before cross-checks.




Figure 8: Spearman correlations among numeric metadata attributes.




Figure 9: Similarity distributions: same position on different days, same street at different positions, and different streets.




Figure 10: Image positions by split; evaluation streets intersect training streets.




Figure 11: DINOv2 embedding t-SNE for 5,149 images, coloured by component and label; descriptive illustration only.



Figure 12: Random main-train examples by label. © Mapillary contributors, CC BY-SA 4.0.



Figure 13: Additional train examples by sampling stratum; corner labels identify 0, 1 or I. © Mapillary contributors, CC BY-SA 4.0.




Figure 14: Crop luminance by component and label.




Figure 15: Crop sharpness on a log scale, by component and label.

7. Summary: measured results and remaining work

7.1. What has been measured

The dataset contains 5,149 final-labelled images: 3,229 usable (2,450 passable, 779 blocked) and 1,920 I. Natural main prevalence is 10.8% of usable images (Wilson [9.4,12.3], street bootstrap [8.7,13.9]); validation and test have 35 and 47 positives among 242 and 459 usable images. Enriched training has 697/2,528 positives (27.6%, Wilson [25.9,29.3]), 83% supplied by enrichment. Three-label Cohen's κ is 0.60/0.64/0.61 for test/validation/cross-labelled train. Selector yield among all sampled images is 37.9% [35.4,40.5] in top-score and 7.7% [5.8,10.1] in random remainder (1,400 and 600 images).

No exact duplicates or dHash distances at most four were found; street, position-group and panorama IDs do not cross splits, but 52 evaluation images lie within 40 m of 47 train-side images. Descriptive image-quality measures are broadly close across main splits; blocked images are darker (AUC 0.37 [0.32,0.41]). Enrichment differs from main train (domain AUC 0.95 top-score, 0.70 random). Street has metadata association V=0.18; main road-type V=0.00, while road-type association in enrichment is reported separately. Other main metadata show little evidence of strong label association.

7.2. What has not been measured or completed

Table 15: Outstanding work and its implications

Item	Status and implication
At least 100 team photographs planned in the proposal	Not collected; all images currently come from Mapillary.
Sensitive-content review	Not completed beyond Mapillary's blur; internal sheets still show some identifiable people and plates.
Frozen splits	Pending the policy for 47 train-side images near evaluation intersections. Keep predetermined test streets; 47 positives limit evaluation precision.
Enrichment label-noise rate	Not measured. Targeted cross-checks of 203 suspected cases are not representative; individual blocked shares range 19–43%.
Confidence intervals for κ	Not measured.
1,563 singly labelled main train images	Not re-reviewed; the 15% cross-labelled subset has $\kappa = 0.61$.
Left sidewalks on one-way streets	Underobserved because crops look right; a source limitation.
Unified final-label table	Enrichment and main/pilot remain separate; cross-check cells 263 and 264 await confirmation, retaining original labels.

Item	Status and implication
Explanation for darker blocked images	Unverified; assess in model error analysis.
38 rejected enrichment night images	Not visually reviewed; the 58 rejected main images were reviewed.
Reconstructed versus server crops	Only an earlier five-image comparison (1.35–1.5 grey-level difference); 671 validation/test crops in image EDA were reconstructed.
Pilot annotation timing and obstacle tags	Not included in these statistics.
Pixel normalization and augmentation	Training-stage work, not yet performed.

These are limitations, not claims of completed checks. The report documents a plan rather than changing labels or splits during EDA. Before training, decide and record the geographic exclusion policy, save a fixed manifest and regenerate affected tables. A representative independent enrichment audit, broader reconstruction comparison, sensitive-content review and rejected-enrichment review are still needed; no completion is implied by the editorial corrections.

Source: `docs/unresolved_items.md`; EDA sections above.

7.3. Implications for modelling

Use imbalance-aware metrics (PR-AUC and blocked-class F1), with street-resampled uncertainty. Only 47 test positives limit the ability to distinguish small performance differences. Compare enriched training with training on the natural component alone; consider class weighting or resampling. Check whether models exploit darkness. Resolve train/evaluation intersection proximity before freezing splits.

A. Provenance and reproduction

Every reported number comes from repository data or a reproducible script. Paths beginning `tables/` or `figures/` are relative to `docs/data_report/`. This English edition translates the corrected Vietnamese report's findings, counts and limitations; file names, legacy source codes and proper names remain unchanged.

Table 16: EDA scripts and outputs

Script	Outputs
`src/eda/27_rebuild_missing_crops.py`	Reconstructs missing crops from manifests (671 validation/test crops); reads no labels.
`src/eda/28_eda_tabular.py`	Inventory, label distributions, metadata, associations, consistency checks, `tab_*.pdf` and `tabular_numbers.json`.
`src/eda/29_eda_images.py`	Per-image quality statistics, `img_*` figures, `image_stats.csv` and `image_numbers.json`.
`src/eda/30_eda_duplicates.py`	Duplicates, geography, similarity, domain comparisons, `dup_*` figures and `duplicate_numbers.json`.

Non-EDA sources include the collection log and collection-status CSV (counts and filtering); scripts 08/09 and side-coverage/crop-parameter CSVs (crop decisions); script 19, the main agreement report and labeling-phase log (agreement and adjudication); script 07 and pilot reports; script 21 and selector benchmark; scripts 23/24 and street-scan/enrichment-score CSVs; and script 26, enrichment reports and cross-check CSV (enrichment annotation).

Create a virtual environment and install `requirements.txt`, including PyYAML. Record the actual Python version and `pip freeze` used to regenerate results. Image data are absent from Git: prefer server originals, or configure `MAPILLARY_TOKEN` and reconstruct with script 27, documenting JPEG differences. Scripts 29/30 require `data/crops/`; script 30 requires model downloads and preferably a GPU. Run from the repository root:

```
python src/eda/27_rebuild_missing_crops.py
python src/eda/28_eda_tabular.py
python src/eda/29_eda_images.py
python src/eda/30_eda_duplicates.py
cd docs/data_report
sh make.sh
sh make.sh en
```

The current editorial review independently recounted primary labels and check totals from CSV, but did not rerun pixel/embedding analysis because local crops were unavailable. The original appendix records that three Claude Sonnet agents wrote EDA scripts under a coordinating Claude agent, which independently rechecked headline counts, Wilson intervals, metadata, image measurements on 300 sampled images, hashes, geographic distances and embeddings and inspected contact sheets. Statements described as visual observations refer to those AI contact-sheet observations, not human labels or quantitative measurements. Dataset labels were assigned by humans; Khải performed main adjudication as confirmed by the team.

Only training images are shown in the public example grids. Internal review contact sheets include validation/test crops and are excluded from both the report and Git. Image attribution: © Mapillary contributors, CC BY-SA 4.0.

References

[1] Manh Dung Dao and Thanh Huy Cao. Vietnamese Sidewalk Violation VQA: A question-answering dataset for sidewalk encroachment detection. SE365 course project, University of Information Technology, VNU-HCM, 2026. Dataset card; truy cập 18/10/2026.

[2] Mapillary. An introduction to Mapillary, 2024. Mapillary documentation; truy cập 18/10/2026.

[3] OpenStreetMap contributors. OpenStreetMap, 2026. openstreetmap.org, dữ liệu theo giấy phép ODbL; truy vấn qua Overpass API ngày 22/10/2026.

[4] Maxim Tkachenko, Mikhail Malyuk, Andrey Holmanyuk, and Nikolai Liubimov. Label Studio: Data labeling software, 2020–2022. Phần mềm mã nguồn mở, github.com/heartexlabs/label-studio.

[5] Joseph L. Fleiss. Measuring nominal scale agreement among many raters. *Psychological Bulletin*, 76(5):378–382, 1971.

[6] Josh Attenberg and Foster Provost. Why label when you can search? Alternatives to active learning for applying human resources to build classification models under extreme class imbalance. In *Proceedings of the 16th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2010. doi:10.1145/1835804.1835859.

[7] Maxime Oquab, Timothée Darcet, Théo Moutakanni, et al. DINOv2: Learning robust visual features without supervision, 2023. arXiv:2304.07193.

[8] Sebastian Farquhar, Yarin Gal, and Tom Rainforth. On statistical bias in active learning: How and when to fix it. In *International Conference on Learning Representations (ICLR)*, 2021. arXiv:2101.11665.

[9] Alec Radford, Jong Wook Kim, Chris Hallacy, et al. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, 2021. arXiv:2103.00020.

[10] Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M. Alvarez, and Ping Luo. SegFormer: Simple and efficient design for semantic segmentation with transformers. In *Advances in Neural Information Processing Systems 34 (NeurIPS)*, 2021. arXiv:2105.15203.

[11] Neal Krawetz. Kind of like that, 2013. The Hacker Factor Blog, bài viết mô tả dHash.

[12] Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960.

[13] Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927.

[14] Wicher Bergsma. A bias-correction for Cramér's V and Tschuprow's T. *Journal of the Korean Statistical Society*, 42(3):323–328, 2013.

[15] John W. Tukey. *Exploratory Data Analysis*. Addison-Wesley, 1977.

[16] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9:2579–2605, 2008.

[17] David Hasler and Sabine Süsstrunk. Measuring colorfulness in natural images. In *Human Vision and Electronic Imaging VIII, Proc. SPIE 5007*, pages 87–95, 2003.