Lunar communication inflatable tower mast

"our idea is to develop a compact inflatable tower mast with communication hardware, foldable solar panel that covers the inflated mast. these parts fitted inside a cylindrical lander with three legs that has low reaction force drill system. what makes this different from the existing solutions for lunar communication" *Generated by LeapSpace, Sat Oct 10 2026*

Lunar Communication Concept at a Glance

Key Findings Table

Key finding	Existing baseline	What is different in your concept	Relevant mission context	Citations
Existing lunar communications are dominated by orbital relays, stationary surface terminals, rover systems, and rigid/collapsible deployables	Polar and far-side continuity is usually solved with relay satellites, relay networks, or stationary/mobile relay terminals rather than a compact local tower	Your concept shifts emphasis to a **local elevated surface node** packaged inside the lander instead of relying primarily on orbital infrastructure	Best for local/regional line-of-sight improvement, not full global replacement	[1] [2] [3] [4] [5]
Elevation matters a lot for lunar links	Antenna height strongly affects path loss, visibility, and worksite coverage; deployable towers are used to raise payloads above the lander deck	Your concept combines this elevation benefit with **inflatable high stowage efficiency**	Useful at polar terrain, crater rims, and obstructed local sites	[6] [7] [8] [9]
The main novelty is integration, not just inflation	Prior work shows tower-mounted payloads, vertical solar systems, and separate comm/power buses, but not the same tightly co-packaged arrangement	Inflatable mast + embedded communications + foldable solar cover + cylindrical lander packaging + drill compatibility appear as a distinct combination	Differentiation is system-level rather than component-level	[7] [10] [11] [12] [13]
Inflatable/foldable structures win on packaging efficiency	Inflatable and deployable systems repeatedly show compact stowage and high deployed-to-stowed ratio	Your cylindrical lander concept is especially aligned with those packaging advantages	Strong differentiator for small landers and volume-limited missions	[8] [9] [14] [15] [16]
Reliability is the main trade-off	Inflatable systems face deployment repeatability, wrinkling, rigidization, pressure-loss, creep, and shape-control challenges	Your concept is more compact, but less mature than rigid towers unless hybrid rigidization or bracing is added	Major qualification issue for lunar use	[17] [18] [19] [20] [21] [22]
The drill-lander-mast interface is unusually distinctive	Low-reaction-force drilling, lander stability, and deployable payloads are each studied separately	Few retrieved studies combine them into one coupled architecture, which itself makes your concept unusual	Potential advantage if the drill also anchors or stabilizes the mast	[13] [23] [24] [25] [26]
Survivability is the main technical risk	Dust, micrometeoroids, radiation, plume lofting, puncture, and thermal cycling are major threats to inflatable/deployable hardware	Your concept is differentiated, but also more environmentally fragile than rigid mast alternatives	Needs shielding, rigidization, and dust-aware deployment design	[27] [28] [29] [30] [31]

Direct Answer

What makes your idea different is the **specific integrated architecture** rather than any single element alone. The evidence shows prior lunar work includes deployable towers, relay terminals, orbital relay networks, vertical solar systems, and low-disturbance drilling, but not this exact combination in one compact surface node: an **inflatable mast**, **communications hardware integrated with that mast**, **foldable solar panels covering the mast**, **packaging inside a cylindrical three-leg lander**, and **compatibility with a low-reaction-force drill** [7] [10] [11] [12] [13].

In practical terms, your concept appears most differentiated in five ways:

1. **Higher stowed-volume efficiency** than rigid or telescoping towers because inflatable/foldable systems pack very compactly [8] [14] [15].
2. **Closer coupling of structure, power, and communications** than the more common architecture where antennas, solar arrays, batteries, and thermal hardware are packaged separately [10] [11] [32].
3. **A local elevated node approach** that improves line-of-sight and antenna height on the surface, instead of treating lunar communications mainly as an orbital relay problem [1] [2] [6].
4. **Better fit to small or polar landers** where cylindrical packaging and tight internal volume are major constraints [33] [34] [35].
5. **Potential system-level coupling with anchoring/drilling**, which is not well represented in the retrieved lunar communications literature and could become a real differentiator if the drill stabilizes or emplaces the node [13] [23] [36].

The main caveat is that this does **not** appear to replace orbital relay systems for continuous far-side or persistent polar coverage. The literature supports it more strongly as a **compact local or regional surface infrastructure node** than as a full substitute for networked lunar relay architecture [1] [3] [4] [37].

Confidence level: High - the differentiation claim is strongly supported across multiple source clusters, though exact one-to-one prior-art benchmarking is not available [7] [8] [10] [13].

Study Scope

This report synthesizes the provided literature on: lunar communication architectures, deployable towers and masts, inflatable/foldable structures, integrated power-communications packaging, thermal control, lander-interface constraints, drilling disturbance, and lunar survivability hazards [2] [5] [8] [10] [38]. The evidence base is dominated by concept studies, analytical models, subsystem prototypes, and architecture papers rather than full integrated lunar demonstrations [7] [12] [39] [40] [41].

Assumptions & Limitations

- The evidence does **not** include a directly matched prior system with the same full feature set, so novelty is assessed by synthesis across adjacent technologies rather than exact like-for-like comparison [12] [13] [26].
- The sources do **not** provide integrated quantitative comparisons for mass, deployment time, link-budget gain, or stability advantage for your full architecture [10] [33] [42].
- Much of the retrieved evidence is model-based or subsystem-level, so readiness claims should be treated more cautiously than novelty claims [39] [41] [43].

Suggested Further Research

- Build a **system-level trade study** versus rigid telescoping mast, lander-mounted antenna, and orbital-relay-supported terminal architectures using common mass/volume/link metrics [6] [33].
- Test an **inflation-then-rigidization** or hybrid-braced mast to reduce puncture and thermal-cycling risk [31] [44] [45].
- Run coupled tests of **drilling loads, dust lofting, and mast stability** after deployment [13] [24] [30].
- Study whether the **solar wrap can also act as environmental shielding** against dust, radiation, and micrometeoroid exposure [27] [29] [46].
- Quantify where a **local elevated node** reduces dependence on more expensive orbital relay infrastructure for specific polar scenarios [1] [3] [35].

Full Report

Introduction and Design Question

Your proposed system is a compact lunar surface node: an inflatable tower mast carrying communications hardware, wrapped or covered by foldable solar panels, all stowed inside a cylindrical three-leg lander that also carries a low-reaction-force drill. The core question is not whether each part has precedent, but whether their **combination** changes the design space relative to existing lunar communication solutions [7] [8] [10] [13].

Taken together, the evidence suggests that the concept is most different at the **system architecture level**: it merges elevation, power generation, packaging, and possible anchoring into a single compact deployable node, whereas existing lunar communication approaches usually distribute these functions across orbiters, surface terminals, separate solar hardware, and rigid support structures [2] [11] [38].

Confidence level: High - this framing is directly supported by the cross-source pattern in the provided evidence [1] [7] [8] [26].

Foundational Context

What problem existing lunar communications are trying to solve

Lunar communications architectures are shaped by three recurring constraints: **visibility**, **power**, and **deployment geometry**. At polar and far-side sites, Earth visibility can be intermittent or absent, so many studies prioritize orbital relays or networked nodes for continuity [1] [3] [37]. At the local scale, however, antenna location and height strongly affect path loss and useful coverage over cratered terrain [6]. Surface systems therefore benefit from elevation even when they still depend on orbital backbone links [5] [7].

Why mast height matters

Deployable towers are being studied because raising payloads above the lander deck improves horizon access, line-of-sight, and sometimes solar exposure [7] [34]. This is especially relevant near the poles, where small height gains can materially improve illumination and terrain visibility [34] [35].

Why compact packaging matters

Small landers face tightly coupled mass, power, and volume limits, often around modest onboard power budgets rather than large infrastructure-class systems [33] [47]. Inflatable and foldable structures are attractive in this context because they offer high deployed-to-stowed ratios and reduced launch volume [8] [14] [15].

Where Existing Lunar Communication Architectures Already Solve the Problem

Orbital relay networks and polar coverage

For continuous or near-continuous coverage, especially at the poles and far side, the literature repeatedly favors orbital relay infrastructure. Halo-orbit relay satellites, frozen-orbit constellations, and LunaNet-style architectures are presented as the main solution to Earth-visibility cutoffs and persistent access needs [1] [2] [3] [4]. Some studies even propose heterogeneous multi-node polar networks with mutual backup for reliability and scalability [37].

This creates an important boundary condition for your concept: a single surface mast can improve **local geometry**, but it does not inherently solve the global continuity problem that drives much of lunar communications architecture [1] [4].

Fixed surface nodes and stationary relay terminals

Stationary surface relay terminals are a more direct baseline. The Lunar Surface Relay Terminal is explicitly described as a stationary platform option, and broader lunar comms studies describe central surface wireless nodes linking local assets to Earth via relay or direct links [5]. These systems are closer to your concept functionally, but they are not described as inflatable mast-plus-solar-wrap packages [5].

Rover-mounted and lander-mounted communications

Rover-mounted systems prioritize mobility, while lander-mounted antennas inherit orientation and deck-geometry constraints [48] [49] [50]. A lander-mounted case like ROLSES-1 still operated despite orientation setbacks, illustrating that direct lander integration can work but may suffer from placement and pointing issues [50]. Your concept differs by explicitly trying to escape deck limitations through a deployable elevated mast [7].

Confidence level: High - the distinction between local surface elevation and orbital continuity is strongly evidenced and consistent across sources [1] [5] [6].

Deployable Towers, Inflatable Structures, and the Proposed Mast

What prior tower concepts look like

Deployable lunar towers already exist conceptually. SELTI uses a collapsible carbon-fiber mast with guy wires and a leveler, and is designed to elevate payloads for communication, navigation, sensing, and imaging [7]. Other tower studies analyze guy-wire and spreader-bar configurations to improve tip-mass capacity and deflection behavior [39].

So an elevated surface tower is **not** new. What differs is the tower technology and its packaging/integration strategy [7] [39].

Where inflatables change the trade

Inflatable and foldable structures consistently provide compact stowage, low mass, and large deployed geometry, which fits your cylindrical lander concept very well [8] [9] [14] [15]. Packaging studies suggest rolled or crease-pattern approaches usually give more controlled deployment than classic z-folded booms, while conical rigidizable members can achieve high reliability with low launch volume [19] [20] [51] [52].

The trade-off is that inflatable systems are more sensitive to repeatability, wrinkling, shape control, and long-term stability than rigid deployables [17] [18] [19] [21] [22]. That means your concept's strongest packaging advantage is also its largest engineering burden.

Why your mast is distinct

The retrieved literature supports a strong novelty claim for **co-design**. Prior work separately supports inflatable or deployable structural members, tower-mounted payloads, and vertical/deployable solar systems [7] [10] [53] [54]. But the evidence does not show a clearly established lunar architecture that combines an inflatable mast, comm hardware integrated into that mast, and foldable solar coverage in one compact lander-stowed assembly [10] [11] [12].

This pattern implies your concept is best understood as a **multifunction surface micro-infrastructure node** rather than just "another mast" [7] [10] [53].

Confidence level: High - the novelty is supported mainly as an absence of this specific integrated combination in the retrieved set, while adjacent components are well represented [7] [10] [12].

Power, Thermal Control, and Packaging Integration

Integration of solar and communications

The literature shows mast-based systems supporting power beaming, communication, and vertical solar deployment, but usually as adjacent functions rather than a single physically unified mast-solar-communications package [7] [10]. Batteries and converters are typically treated as separate storage and power-routing subsystems rather than embedded inside the mast package [55] [56] [57].

That makes your solar-wrapped mast distinctive in two ways: it shares structural volume with power generation, and it potentially reduces separate deck-mounted array hardware and associated packaging complexity [11] [32].

Thermal implications

If communications electronics are mast-mounted or enclosed within the deployable package, thermal control becomes critical. Relevant lunar strategies include vertical dust-shedding radiator panels, warm electronics boxes coupled through Variable Conductance Heat Pipes, and thermal storage solutions for multi-day operation [58] [59] [60]. Photovoltaic survival also depends on isolation layers, encapsulation, cover glass, and dust-tolerant protection [46] [61] [62].

Taken together, these findings suggest your design could gain packaging efficiency but may require unusually careful thermal zoning so that solar surfaces, pressure-retaining members, and radios do not create harmful thermal coupling [32] [59].

Mass, volume, and power trade-offs

Small compact landers are volume- and power-constrained, which favors integrated structures if they reduce duplicated packaging and support hardware [33] [47]. More generally, lunar power studies show that architecture choices among elevated solar, storage, cabling, and power transfer strongly affect landed mass [63] [64] [65]. Your concept potentially saves volume and interface complexity, but the sources do not provide a direct quantified mass benefit for your full integrated configuration [10] [33].

Confidence level: Medium - the integration logic is well supported, but quantitative benefit is not directly reported for the exact concept [11] [63].

Lander Interface, Drilling Disturbance, and Lunar Survivability

Lander geometry and cylindrical packaging

The retrieved papers do not directly describe a lander matching your full geometry and payload mix [12] [26] [42]. They do, however, show that touchdown stability is typically kept independent from later payload deployment through dedicated legs, cushioning, and landing optimization [25] [66] [67]. Compact, high-volume, modular architectures are favored, but detailed internal routing of towers, arrays, and drills is not described [12] [26] [68].

So the **gap itself** is part of your differentiation: the mast-lander-drill integration problem appears underexplored [13] [26].

Why low-reaction-force drilling matters here

Low-disturbance drilling becomes more important when delicate deployed hardware is nearby. Self-opposing or balanced drilling can produce attachment forces while managing transverse loads, and lunar drilling studies emphasize that low gravity and vacuum limit allowable drill force [13] [23]. Vibratory excavation can reduce resistance but may loft dust and disturb instruments, which argues for low-disturbance approaches near an inflatable mast or solar cover [24].

This is one of your concept's more unusual differentiators: the drill is not just another payload, but a possible **stability and emplacement subsystem** for the communications node [13] [36].

Survivability risks for an inflatable lunar comms node

This is the hardest part of the concept. Micrometeoroids can cause puncture, tears, and pressure loss; dust causes abrasion, adhesion, contamination, and seal degradation; radiation can degrade materials; landing plume impingement lofts damaging dust; and inflation cycles create creep, deformation, burst, and collapse risks [27] [28] [29] [30] [31].

Several lunar inflatable studies therefore favor hybrid or reinforced concepts that retain packaging benefits while reducing dependence on continuous pressure retention [31] [44] [45]. For your idea, that evidence points toward inflation-assisted deployment followed by rigidization, bracing, or shielding rather than a permanently soft pressure-supported mast [45] [69].

Confidence level: High - survivability concerns are repeatedly and directly supported across multiple sources [22] [27] [30].

Differentiation Assessment

What is genuinely different

The strongest evidence-backed differentiators are:

- **Single-package multifunction integration** of mast, comms, and solar hardware [7] [10] [11].

- **Very high packaging efficiency** enabled by inflatable/foldable deployment inside a compact lander [8] [14] [15].
- **Surface elevation without depending entirely on orbiters**, improving local line-of-sight and terrain clearance [6] [7].
- **Potential coupling to low-disturbance anchoring/emplacement**, which is not common in retrieved lunar comms concepts [13] [23].

What is more incremental than revolutionary

Some aspects align with existing trends rather than departing from them completely:

- Multi-functional lunar infrastructure is already a trend, with communications increasingly linked to navigation, power, and surface support functions [5] [10] [53] [70].
- Elevating payloads above the lander deck is already a known strategy [7].
- Vertical or elevated solar concepts also exist in the lunar power literature [7] [63].

So the concept is **not unprecedented in purpose**, but it is unusual in **how tightly the functions are combined** [10] [11].

What remains unproven

The biggest validation gaps are full-scale deployment reliability, long-duration lunar survival, and the coupled behavior of the mast, lander, solar cover, and drill under real surface operations [13] [30] [39] [41]. The evidence base is stronger for models and partial prototypes than for integrated lunar-qualified systems [7] [40] [43].

Confidence level: High - the distinction between novelty and readiness is clearly supported by the evidence mix [12] [39] [41].

Conclusion

Your idea differs from existing lunar communication solutions mainly because it combines five functions that the literature usually treats separately: **elevated surface communications, inflatable compact deployment, solar integration, cylindrical lander packaging, and low-disturbance emplacement/anchoring** [7] [8] [10] [13]. That makes it look less like a conventional antenna system and more like a **compact surface infrastructure node** [7] [10] [53].

The concept is most compelling where **stowed volume is scarce**, **local terrain blocks line-of-sight**, and **small height gains improve both communications and illumination**, such as compact polar missions [6] [34] [35]. It is less compelling as a replacement for orbital relays, because the literature still treats persistent polar and far-side communications primarily as a relay-network problem [1] [3] [37].

In short: the concept is **architecturally differentiated**, especially in integration and packaging, but its value will depend on proving that the inflatable mast can survive lunar dust, puncture risk, thermal cycling, and nearby drilling operations better than existing rigid alternatives [22] [27] [30].

Overall conclusion confidence: High - the differentiation case is strong; the readiness case remains medium-to-low because integrated lunar validation is limited [12] [39] [43].

References

1. Zhang, L. (2023) From Queqiao to Queqiao-2: The sustainable development of Chinese lunar relay communications satellite. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/85188011524
2. Israel, D.J., Schier, J., Petro, A., (...), Sharma, A. (2021) LunaNet Architecture and Concept of Operations. *16th International Conference on Space Operations*. https://www.scopus.com/pages/publications/105024944772
3. Ely, T.A. (2005) Stable constellations of frozen elliptical inclined lunar orbits. *Journal of the Astronautical Sciences*. https://doi.org/10.1007/bf03546355
4. Ely, T.A., Lieb, E. (2006) Constellations of elliptical inclined lunar orbits providing polar and global coverage. *Journal of the Astronautical Sciences*. https://doi.org/10.1007/BF03256476
5. Scardelletti, M.C., Gasper, M.R., Reinhart, R.C., (...), Turnbull, E.R. (2023) Lunar Surface Network Relay Terminal: A Lunar Communications Platform. *IET Conference Proceedings*. https://doi.org/10.1049/icp.2024.0820
6. Hwu, S.U., Upanavage, M., Sham, C.C. (2008) Lunar surface propagation modeling and effects on communications. *26th AIAA International Communications Satellite Systems Conference, ICSSC*. https://www.scopus.com/pages/publications/77958506237
7. Portmann, V.P., Miller, A.S., Zhang, J.Z., (...), Chin, H.H. (2024) Modeling and Feedback Control for a Guyed, Flexible, Tubular Lunar Tower. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO58975.2024.10521355
8. Zhu, Z., Li, F., Liang, B. (2025) THE ROLE AND DEVELOPMENT OF INFLATABLE STRUCTURES FOR EXTRATERRESTRIAL HABITATIONS. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/083101-0049
9. Grahne, M.S., Cadogan, D.P. (1999) Inflatable solar arrays: Revolutionary technology?. *SAE Technical Papers*. https://doi.org/10.4271/1999-01-2551
10. Williams, H., Crum, R., Ness, R.V., (...), Hell, K. (2023) Lunar Array, Mast, and Power System (LAMPS) for Deployable Lunar Power Provision. *AIAA SciTech Forum and Exposition, 2023*. https://doi.org/10.2514/6.2023-1389
11. Lange, C., Witte, L., Rosta, R., (...), Knapmeyer, M. (2017) A seismic-network mission proposal as an example for modular robotic lunar exploration missions. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2017.02.004

12. Anderson, T. (2021) Architecture Considerations for Crewed Lunar Surface Expeditionary Utility Lander Systems. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO50100.2021.9438196

13. Li, M., Tang, D., Quan, Q., (...), Deng, Z. (2021) Investigation on the ultimate uplift capacity for asteroid exploration in drilling anchoring process: Numerical modelling and DEM simulation. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2021.05.020

14. Cadogan, D., Scheir, C., Dixit, A., (...), Kopf, P. (2006) Intelligent flexible materials for deployable space structures (InFlex). *Collection of Technical Papers - AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference*. https://www.scopus.com/pages/publications/34147121561

15. Criswell, Marvin E., Sadeh, Willy Z., Abarbanel, Jenine (1996) Design and performance criteria for inflatable structures in space. *Proceedings of the International Conference on Engineering, Construction, and Operations in Space*. https://www.scopus.com/pages/publications/0029724305

16. Zirbel, S.A., Lang, R.J., Thomson, M.W., (...), Howell, L.L. (2013) Accommodating thickness in origami-based deployable arrays1. *Journal of Mechanical Design*. https://doi.org/10.1115/1.4025372

17. Zhou, S., Zhou, X. (2014) Development and technical difficulties of deployable space masts. *Zhongguo Kongjian Kexue Jishu/Chinese Space Science and Technology*. https://doi.org/10.3780/j.issn.1000-758X.2014.06.006

18. Wei, H. (2019) The development of space flexible deployable structure technology. *IASS Symposium 2019 - 60th Anniversary Symposium of the International Association for Shell and Spatial Structures; Structural Membranes 2019 - 9th International Conference on Textile Composites and Inflatable Structures, FORM and FORCE*. https://www.scopus.com/pages/publications/85102407329

19. Schenk, M., Viquerat, A.D., Seffen, K.A., Guest, S.D. (2014) Review of inflatable booms for deployable space structures: Packing and rigidization. *Journal of Spacecraft and Rockets*. https://doi.org/10.2514/1.A32598

20. Tsunoda, H., Senbokuya, Y. (2003) Deployment characteristics of rigidizable space inflatable structures. *Space Technology*. https://www.scopus.com/pages/publications/0042925381

21. Tao, Q., Wang, C., Xue, Z., (...), Tan, H. (2016) Wrinkling and collapse of mesh reinforced membrane inflated beam under bending. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2016.08.021

22. Degtyarev, A.V., Lobanov, L.M., Kushnar'ov, A.P., (...), Kaliapin, M.D. (2020) On possibilities for development of the common-sense concept of habitats beyond the Earth. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.02.014

23. Zacny, K., Currie, D., Paulsen, G., (...), Chu, P. (2012) Development and testing of the pneumatic lunar drill for the emplacement of the corner cube reflector on the Moon. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2012.07.025

24. Sun, X., Liu, S., Wen, L., (...), Zhang, R. (2026) Research on low-resistance configuration optimization and excavation performance of a biomimetic scoop for ISRU on the Moon. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2026.05.047

25. Mathavaraj, S., Rajesh, R., Karidhal, R. (2015) Optimization of three dimensional trajectory using legendre pseudo-spectral method for Lunar soft landing. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/84994376758

26. Ramos, E.M., Robertson, B., Diaz, M.J., Mavris, D. (2022) Development of a Lunar Lander Modeling and Simulation Capability. *AIAA Science and Technology Forum and Exposition, AIAA SciTech Forum 2022*. https://doi.org/10.2514/6.2022-0380

27. Glaser, R. (2021) Multi-objective characterization of an inflatable space structure with a quasi-static experimental deflation and finite element analysis. *International Journal of Mechanical Sciences*. https://doi.org/10.1016/j.ijmecsci.2021.106614

28. Wang, X., Huang, Z., Chen, S., (...), Gao, L. (2026) Graphene-enhanced perfluorosilane coating with an ultralow sliding angle prevents lunar dust adhesion. *Chemical Engineering Journal*. https://doi.org/10.1016/j.cej.2026.173181

29. Noor, A.K., Venneri, S.L., Paul, D.B., Hopkins, M.A. (2000) Structures technology for future aerospace systems. *Computers and Structures*. https://doi.org/10.1016/S0045-7949(99)00067-X

30. He, X., He, B., Cai, G. (2012) Simulation of rocket plume and lunar dust using DSMC method. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2011.07.014

31. Dronadula, R., Benaroya, H. (2021) Hybrid lunar inflatable structure. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.10.039

32. Zhang, N., Li, H., Tian, P., (...), Yao, J. (2026) A standardized On-Orbit Replaceable Unit with integrated mechatronic–thermal interface: Design, separation dynamics modeling, and experimental validation. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2026.08.019

33. de Mejanes, N., Pascaud, R., Mazières, V., (...), Pascal, O. (2022) Simulation of the microwave propagation through the plume of a Hall thruster integrated on small spacecraft. *Journal of Applied Physics*. https://doi.org/10.1063/5.0095134

34. Mazarico, E., Neumann, G.A., Smith, D.E., (...), Torrence, M.H. (2011) Illumination conditions of the lunar polar regions using LOLA topography. *Icarus*. https://doi.org/10.1016/j.icarus.2010.10.030

35. Gläser, P., Oberst, J., Neumann, G.A., (...), Robinson, M.S. (2018) Illumination conditions at the lunar poles: Implications for future exploration. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2017.07.006

36. Sherwood, B. (2019) Principles for a practical Moon base. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2019.04.018

37. Liu, S., Li, J. (2020) Analysis and Design of the Communication System for Multi-Probes Joint Lunar Polar Exploration. *Journal of Deep Space Exploration*. https://doi.org/10.15982/j.issn.2095-7777.2020.20191029001

38. Testi, C., Bailey, K., Dousis, S., (...), Bannova, O. (2024) Unique and Novel Inflatable Tower (UNIT) as Critical Infrastructure on the Moon. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/078374-0041

39. Daye, J.G., Lee, A.J., Fernandez, J.M. (2025) Structural Architectures for Imperfect Deployable Lunar Towers. *Journal of Spacecraft and Rockets*. https://doi.org/10.2514/1.A36093

40. Young, A.C., Davids, W.G., Whitney, D.J., (...), Goupee, A.J. (2017) Structural testing and analysis of a braided, inflatable fabric torus structure. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2017.07.004

41. Meguro, A., Shintate, K., Usui, M., Tsujihata, A. (2009) In-orbit deployment characteristics of large deployable antenna reflector onboard Engineering Test Satellite VIII. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2009.03.052

42. Eyer, J., Hervieu, C., Wagener, M., (...), Winter, M. (2021) ALINA-2: Innovations on Planetary Transportation Systems GmbH's Commercial Lunar Lander. *New Space*. https://doi.org/10.1089/space.2020.0005

43. Freeland, R.E., Bilyeu, G.D., Veal, G.R., (...), Carson, D.E. (1997) Large inflatable deployable antenna flight experiment results. *Acta Astronautica*. https://doi.org/10.1016/S0094-5765(98)00057-5

44. Herzig, T., Kömle, N.I., Macher, W., (...), Gläser, P. (2022) Site selection, thermodynamics, environment and life support analysis for the PneumoPlanet inflatable lunar habitat concept. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2022.105595

45. Vasudeva, K., Emami, M.R., Dickinson, C. (2026) Lunar construction: A state-of-the-art survey. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2025.101159

46. Afshar-Mohajer, Nima, Wu, Chang-Yu, Sorloaica-Hickman, Nicoleta (2012) Efficiency determination of an electrostatic lunar dust collector by discrete element method. *Journal of Applied Physics*. https://doi.org/10.1063/1.4739734

47. Baturkin, V. (2005) Micro-satellites thermal control - Concepts and components. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2004.09.003

48. Lin, S.-F., Tsai, J.-R. (2024) Taiwan's lunar payload development and its outsourced transportation services. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/078357-0022

49. Audet, Y., Melman, F.T., Molli, S., (...), Ventura-Traveset, J. (2024) Positioning of a lunar surface rover on the south pole using LCNS and DEMs. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2024.06.022

50. Hibbard, J.J., Burns, J.O. (2025) Commission J: Radio Science from the Moon Lunar Odyssey: ROLSES-1 Data Analysis. *2025 United States National Committee of URSI National Radio Science Meeting, USNC-URSI NRSM 2025 - Proceedings*. https://doi.org/10.23919/USNC-URSINRSM66067.2025.10906823

51. Wei, J.-Z., Tan, H.-F., Sun, H.-W., Du, X.-W. (2010) Simulation and experiment for inflatable control deployment of rolled booms. *Collection of Technical Papers - AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference*. https://doi.org/10.2514/6.2010-2580
52. Palisoc, A.L., Redell, F.H., Andersen, G. (2004) Deployment and Structural Support of Space Membrane Optics System Using Rigidizable Conical Booms. *Engineering Construction and Operations in Challenging Environments Earth and Space 2004: Proceedings of the Ninth Biennial ASCE Aerospace Division International Conference*. https://doi.org/10.1061/40722(153)129
53. Testi, C., Bailey, K., Shah, K., (...), Bannova, O. (2024) DESIGN OF INFLATABLE MULTI-PURPOSE TOWER FOR SUPPORT OF ROBOTIC AND CREWED LUNAR SURFACE OPERATIONS. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/078357-0190
54. Cadogan, D.P., Scarborough, S.E. (2001) Rigidizable materials for use in gossamer space inflatable structures. *19th AIAA Applied Aerodynamics Conference*. https://doi.org/10.2514/6.2001-1417
55. Bahrami, R., Ashenayi, K. (2024) Multi-Port Bi-Directional Converter in Space Applications. *AIAA SciTech Forum and Exposition, 2024*. https://doi.org/10.2514/6.2024-0023
56. Dyer, P., Smith, G., Nelson, G. (2022) EXERGY ANALYSIS OF PHOTOVOLTAICS COUPLED WITH ELECTROCHEMICAL ENERGY STORAGE FOR LUNAR POWER APPLICATIONS. *ASME International Mechanical Engineering Congress and Exposition, Proceedings (IMECE)*. https://doi.org/10.1115/IMECE2022-96993
57. McKinney, C.G., Johnson, L. (2025) Space-Based Solar Power - Enabling Lunar Exploration and Beyond. *AIAA Science and Technology Forum and Exposition, AIAA SciTech Forum 2025*. https://doi.org/10.2514/6.2025-0299
58. El-Genk, M.S., Schriener, T.M. (2011) Long operation life reactor for lunar surface power. *Nuclear Engineering and Design*. https://doi.org/10.1016/j.nucengdes.2011.02.024
59. Ulamec, S., Biele, J., Trollope, E. (2010) How to survive a Lunar night. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2010.09.024
60. Zohuri, Bahman (2020) Application of heat pipe in industry. *Functionality, Advancements and Industrial Applications of Heat Pipes*. https://doi.org/10.1016/B978-0-12-819819-3.00002-X
61. Bush, M.E., Sims, J.D., Erickson, S.S., (...), McMillon-Brown, L. (2025) Space environment considerations for perovskite solar cell operations: A review. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2025.05.025
62. Manyapu, K.K., Peltz, L., De León, P. (2022) Safety considerations for SPIcDER: Spacesuit integrated carbon nanotube dust ejection/removal system. *Journal of Space Safety Engineering*. https://doi.org/10.1016/j.jsse.2021.10.003
63. Marcinkowski, A., Carrio, L., Hilliard, S., (...), Cichan, T. (2023) Lunar Surface Power Architecture Concepts. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO55745.2023.10115621

64. Kerslake, T.W. (2008) Lunar surface-to-surface power transfer. *AIP Conference Proceedings*. https://doi.org/10.1063/1.2845004

65. Freeh, J.E. (2008) Analysis of stationary, photovoltaic-based surface power system designs at the lunar south pole. *Space 2008 Conference*. https://doi.org/10.2514/6.2008-7810

66. Liang, S., Wang, Y., Wang, L., (...), Ji, S. (2019) Landing Process of Lunar Lander Simulated with Coupled DEM-FEM Model. *Chinese Journal of Solid Mechanics*. https://doi.org/10.19636/j.cnki.cjsm42-1250/o3.2018.041

67. Zhao, Q., Lu, C., Hong, Y., (...), Wang, C. (2025) Design and dynamic analysis of landing mechanism for crew lunar vehicles. *Aeronautical Journal*. https://doi.org/10.1017/aer.2025.27

68. Howard, R.L. (2019) A joinable undercarriage to maximize payload (JUMP) lunar lander for Cargo delivery to the lunar surface. *AIAA Propulsion and Energy Forum and Exposition, 2019*. https://doi.org/10.2514/6.2019-4141

69. Wang, Q., Feng, P., Jansen, K., Bao, C. (2024) A novel rigidizable inflatable lunar habitation system: design concept and material characterization. *Materials and Design*. https://doi.org/10.1016/j.matdes.2024.113289

70. Case, C.M. (1991) Utilization of space station freedom pressurized element subsystems for a lunar surface outpost. *4th Space Logistics Symposium, 1991*. https://doi.org/10.2514/6.1991-4127