Lunar lander mast design

"our idea is to develop a compact inflatable composite carbon fiber mast with communication hardware, flexible solar panel that is attached to the inflated mast. these parts fitted inside a cylindrical lander with three legs that has low reaction force drill system to anchor itself on the moon surface and give rigid support . how can we create it adaptable to the climatic conditions of the moon?"
Generated by LeapSpace, Sat Oct 10 2026

Lunar Mast-and-Lander Climate Adaptability at a Glance

Key Findings Table

Key finding	Relevance to your concept	Main evidence
A hybrid mast architecture is the most defensible path: compact deployable/inflatable mast, then post-deployment rigidization plus guy-wire/spreader-bar stabilization	Best balance between stowage efficiency and on-surface stiffness for a cylindrical lander	[1] [2] [3] [4] [5]
The main engineering trade-off is compact packaging versus long-term stiffness and shape stability	Inflatable, coilable, and thin-ply booms pack well, but can lose stiffness through viscoelastic relaxation, thermal deformation, and off-axis sensitivity	[6] [7] [8] [9] [10]
Your three-legged lander should use low-reaction anchoring, not high-thrust rotary drilling	Rotary-percussive, percussive, vibration-assisted, and geometry-optimized anchors reduce required downforce and reaction loads in low gravity	[11] [12] [13] [14] [15] [16]
Tripod leveling and post-landing adjustment are essential, not optional	Lander angle, uneven terrain, and first-leg load concentration strongly affect mast alignment and stability	[4] [17] [18] [19]
Lunar survivability will require mixed passive-active thermal control	Insulation/coatings help, but lunar day heat rejection and night survival usually still need heaters, radiators, louvers, or variable conductance paths	[20] [21] [22] [23] [24]
Material selection for composites and coatings matters strongly under thermal cycling	Epoxy-based systems can microcrack under cycling; cyanate ester systems show better microcrack resistance	[25] [26] [27]
Lunar dust must be treated as a system-level failure driver	Dust can jam joints, wear seals, lower radiator/solar performance, and damage interfaces	[28] [29] [30] [31]

Key finding	Relevance to your concept	Main evidence
Solar blankets and exposed surfaces likely need active dust clearing in addition to passive coatings	Electrodynamic and traveling-wave systems repeatedly show high cleaning effectiveness at low power, though durability under bending is a concern	[32] [33] [34] [35] [36]
Mast-mounted power/comms integration is feasible if treated as a multifunctional subsystem	Prior concepts combine mast, flexible solar, electrical connectors, avionics, and dust-tolerant deployment hardware	[37] [38] [39] [40]

Direct Answer

Yes—your concept can be made adaptable to lunar climatic conditions, but the evidence supports doing it as a **hybrid integrated system**, not as a simple inflatable mast alone. The most evidence-backed architecture is:

1. **Deploy compactly, then rigidize** the mast after inflation/deployment using a composite rigidization approach rather than relying on internal pressure long-term, because inflatable-rigidizable and thermoplastic composite systems support compact stowage but pressure-only or spring-dominated systems can lose stiffness over time [1] [2] [41] [42].
2. Add **guy wires, spreader bars, and a leveling mechanism** so the mast can tolerate lander tilt, dead-load deflection, and payload eccentricity; lunar tower studies repeatedly show this improves payload capacity and pointing stability versus unguyed towers [3] [4] [5] [43].
3. Put the most temperature-sensitive electronics **low in the mast or inside an insulated base enclosure**, and use a combination of **MLI/coatings + heaters + radiator/louver or variable-conductance heat-rejection paths**, because purely passive control is generally insufficient across lunar day-night extremes [20] [21] [22] [23] [24].
4. Use **low-reaction anchoring** integrated into the three legs: rotary-percussive or vibration-assisted drilling with **helical/screw anchors** is more compatible with lunar gravity than high-downforce rotary drilling [11] [13] [14] [44].
5. Design for dust from the start: apply **passive low-adhesion/textured coatings**, protect joints/connectors with **covers or bellows**, and add **active electrodynamic/traveling-wave cleaning** on solar surfaces and perhaps radiators [30] [34] [35] [45] [46] [47].
6. Prefer composite systems with better thermal-cycle durability, especially **cyanate-ester-like matrices over crack-prone epoxies where possible**, and tightly control bolted/clamped thermal interfaces because preload uniformity strongly affects heat transfer in vacuum [25] [48] [49].

Taken together, these findings suggest the best path is a **two-stage system**: rapid inflation/self-erection after landing, followed by **mechanical stabilization, rigidization, anchoring, and thermal-dust conditioning** before full operations begin [4] [19] [30] [37].
Confidence level: High - multiple independent findings across structures, thermal control, anchoring, and dust mitigation converge on this architecture [3] [13] [22] [30] [37].

Study Scope

- **Domain covered:** deployable composite structures, lunar drilling/anchoring, thermal-vacuum survivability, dust mitigation, and integrated lunar power/comms packaging [2] [14] [22] [30] [37].
- **Time span represented:** approximately 2000-2025 across the retrieved studies and reviews [14] [34] [50] [51] [52].
- **Methods represented:** analytical models, finite-element studies, regolith simulant testing, thermal-vacuum tests, component prototypes, and system-concept studies [29] [43] [52] [53] [54].

Assumptions & Limitations

- No single retrieved study validates your **full integrated prototype** with inflatable rigidized mast, flexible solar attached to the mast, comms payload, three-leg anchored lander, and survival through full lunar day-night cycling [55] [56] [57].
- Anchoring evidence is strong for low-reaction methods and helical concepts, but **head-to-head comparisons across all anchor classes** under the same lunar terrain conditions are limited [58] [59].
- Dust-cleaning performance is promising, but **durability on repeatedly bent flexible devices** remains an open issue [36] [60].
- Some conclusions below are system-level inferences assembled from separate structural, thermal, and dust studies rather than one end-to-end demonstration [30] [37] [61].

Suggested Further Research

- Run a **coupled thermal-vacuum-dust deployment test** with mast, flexible solar strips, cables, and anchored tripod in simulant [29] [37] [52].
- Compare **helical, percussive, and hybrid screw-percussive anchors** on the same three-leg lander geometry and tilt cases [13] [44] [62].
- Measure **post-rigidization stiffness retention** after long stowage plus thermal cycling for candidate mast laminates [6] [8] [25].
- Validate **dust mitigation durability** on flexible solar blankets under bending, UV, and vacuum [36] [60].
- Optimize **thermal zoning** of avionics between mast top, mid-span, and insulated base enclosure [22] [38] [48].

Full Report

1. Foundational Context: What “adaptable to lunar climatic conditions” really means

For your system, “adaptable” does not just mean surviving temperature swings. On the Moon, the mast-lander must handle a combined environment of **vacuum, large thermal excursions, abrasive dust, reduced gravity, uneven regolith support, and long night survival constraints** [28] [62] [63]. Those conditions affect different parts of the system in different ways:

- The **mast structure** is threatened by thermal deformation, creep/relaxation after stowage, and lateral instability under eccentric loads [8] [9] [10].
- The **lander foundation** is threatened by low gravity and limited reaction force, making conventional high-downforce drilling unattractive [14] [64].
- The **solar and communications hardware** are threatened by dust accumulation, vacuum thermal bottlenecks, and long hot/cold surface exposure [4] [21] [35].
- The **interfaces**—joints, seals, connectors, cable paths, clamps—are often the most fragile parts under dust and thermal cycling [47] [48] [65].

So the design problem is not only structural deployment. It is the creation of a **multifunctional surface system** whose structure, anchor, thermal control, dust protection, and power/comms routing all reinforce each other [37] [39] [66].

Confidence level: High - this framing is directly supported across all major topic areas in the evidence base [19] [30] [37] [61].

2. System concept and mission-driven architecture

Your proposed architecture—a cylindrical lander with three legs, a compact deployable mast, mast-mounted communications, and flexible solar attached to the mast—is well aligned with prior lunar mast and tower concepts that elevate payloads for line of sight, sensing, and power functions [4] [37] [67]. Mast elevation is especially useful in polar or terrain-obstructed settings where local topography blocks visibility and communications from a low deck height [4] [68] [69].

The strongest system-level lesson is that your concept should be organized as **two nested subsystems**:

- a **deployment subsystem** optimized for compact launch stowage [1] [52] [70]
- an **operational subsystem** optimized for stiffness, thermal survival, and contamination control after landing [3] [22] [30]

This is important because the literature shows a recurring contradiction: the structures that pack best—rollable, inflatable, bistable, thin-ply—are also the ones most exposed to long-term relaxation, shape error, or thermal sensitivity once deployed [6] [7] [8].

Practical implication: do not ask the inflated mast alone to provide final precision support. Let inflation/self-erection provide deployment, then let rigidization, guying, leveling, and anchoring provide operational performance [4] [5] [43].

3. Inflatable composite mast design

3.1 Stowage and deployment

Inflatable-rigidizable masts are attractive because they can achieve very compact stowed dimensions; the InflateSail mast is a clear example of a laminate cylindrical mast that deploys compactly and rigidizes in place [1] [71]. Carbon-reinforced thermoplastic composite systems were specifically investigated for deployable rigidizable structures to reduce shelf-life limits, power demands, and offgassing issues associated with some thermoset approaches [2].

Thin-ply and coilable boom architectures also support compact stowage, but the evidence warns that long stowage causes section-height and stiffness loss through viscoelastic relaxation, and recovery after uncoiling can be incomplete even after extended time [6] [7]. Similarly, stowage and deployment behavior in shape-memory composite booms can lose stored energy and fail to recover full curvature after storage [8].

Design implication: your mast should be treated as a **deploy-then-lock** structure, not a repeatedly flexed operational member [72] [73].

3.2 Rigidization and load-bearing

The evidence supports rigidization methods that do more than rely on pressure retention. Inflatable booms need the outer shell to retain stiffness after deployment, and prior studies moved toward UV-cured or thermally controlled rigidization because spring-tape or residual-strain approaches can lose self-stiffness over time [41] [42]. Thermoplastic composite systems appear promising because they address some shelf-life and handling constraints of thermosets [2].

But rigidization does not eliminate failure risk. Adhesive lap-joint shear, pressure drop beyond gas leakage, thermal deformation, and off-axis sensitivity all appear in the mast literature [1] [10]. This implies your structural qualification must focus heavily on **joints, bonded interfaces, and local reinforcements**, not only mast-wall material [1].

3.3 Geometry and stabilization

For lunar towers, guy wires and spreader bars repeatedly improve tip payload capacity and reduce deflection compared with unguyed references [3] [43]. The SELTI concept is especially relevant because it used a compact self-deploying carbon-fiber mast with guy wires to correct eccentricity and maintain tip orientation, while tolerating lander angle variations up to 12 degrees [4]. Experimental tower work also showed natural lateral deflection under dead load of roughly 5% of boom length, with guy wires significantly reducing deflection and damping oscillations [5].

Recommended mast architecture:

- inflatable/self-erecting central tube for packaging efficiency [1] [4]
- post-deployment rigidization [2] [41]
- secondary guy-wire/spreader-bar stabilization [3] [5]
- integrated level compensation at the mast base [4] [17]

Confidence level: High - multiple direct studies converge on these structural choices [3] [4] [5].

4. Anchoring, leveling, and rigid support on lunar regolith

Your lander cannot assume it will have large reaction mass on the Moon, so the anchor must be **low-WOB (weight-on-bit)** and low reaction by design [14] [64].

4.1 Low-reaction drilling

Rotary-percussive and percussive systems are repeatedly described as lower-downforce options than rotary-only drilling, with much lower interaction forces in regolith [11] [14]. Vibration-assisted drilling can improve penetration rate, though performance depends on tuning amplitude rather than simply maximizing vibration [12]. Percussive excavation and penetration also show major force reductions in simulants, including reports of greater than 50% force reduction and even larger downward-force reductions in compacted regolith conditions [74] [75].

4.2 Anchor type

Helical/screw anchors are especially relevant because they show uplift resistance, lateral resistance, and an installation-torque relationship with soil strength [44] [76] [77]. That means your lander could use anchor insertion not only for fixing itself but also for **subsurface assessment** during installation [76]. Geometry optimization matters: longer anchors, optimized cone apex angles, serrated tines, and self-opposing drill tools all reduce penetration energy or reaction loads [15] [16] [78] [79].

4.3 Leveling and load redistribution

Tripod stability alone is not enough. Active leg systems using lead-screw leveling were proposed to compensate for different shock-absorber deformations and support proper post-landing leveling [17]. Lander touchdown studies show the first-contact leg can take substantially higher loads under inclined landing, so structural load redistribution is important [18]. Anchoring-oriented landing legs have also been proposed with sensing and post-landing ultrasonic drilling functions [19].

Recommended foundation strategy:

1. touchdown on compliant, pressure-distributing footpads [80] [81]
2. sense slope and leg load distribution [18] [19]
3. level using lead-screw or equivalent actuation [17]
4. deploy low-reaction helical/percussive anchor at each leg [13] [44]
5. tension mast guy wires only after anchoring is complete [4] [5]

Taken together, these findings suggest the anchor should be **leg-integrated and staged**, not a separate central drill system.
Confidence level: High - strong convergence across drilling, anchor, and lander-leg studies [11] [17] [19] [44].

5. Thermal, vacuum, and radiation survivability

5.1 Thermal architecture

The thermal evidence strongly favors **mixed passive-active control**. Passive insulation reduces night heat loss, but studies consistently note that heating is still needed for small lunar systems during night [20]. Radiator-plus-louver systems can autonomously regulate electronics temperature during lunar day without powered louver actuation [21]. Variable-conductance heat pipes and related concepts were proposed specifically to keep lunar electronics boxes and batteries within range while throttling heat rejection at night [22] [82].

For your system, the best arrangement is likely a **thermally zoned mast**:

- batteries, processors, and most radios near the insulated warm base [22] [38]
- only low-power RF or antennas higher up the mast [4] [69]
- controlled thermal conduction path from base electronics to radiators [22] [49]

5.2 Material behavior

Composite structures intended for lunar conditions must retain stiffness and dimensional stability roughly across 70 K to nearly 400 K [63]. Matrix choice is crucial: cyanate ester systems resisted thermal-cycle microcracking better than epoxy systems, which developed extensive cracking after relatively few cycles [25]. Graphite/epoxy systems also showed declining strength, stiffness, and CTE with increasing thermal cycles in simulated environments [26] [27].

This does not mean epoxies are unusable, but it does mean your design should favor **thermal-cycle-tolerant resin systems and allowables**, especially at folds, joints, and mast-solar attachment zones [25] [83].

5.3 Thermal interfaces in vacuum

Vacuum thermal contact is especially sensitive to preload and uniformity. Conductance rises strongly with contact pressure, and low-load or nonuniformly clamped joints suffer high constriction resistance [48] [49] [84]. Bolted CFRP-aluminum joints have contact behavior dominated by preload-created sticking regions [85].

Practical implication: for your avionics boxes and mast-base thermal straps, **bolt pattern, preload control, and TIM selection are first-order design variables**, not afterthoughts [48] [86].

5.4 Lunar night survival

The retrieved mission studies consistently treat lunar night as a roughly two-week survival problem [24] [87] [88]. Small systems often avoid full-night survival unless additional energy storage and thermal hardware are added [88] [89]. Therefore, your climate-adaptability strategy must make an early mission choice:

- **Option A:** survive only lunar day and short darkness intervals with modest heater support [89]
- **Option B:** survive full lunar night with larger battery/thermal mass/insulation and much stricter thermal isolation [24] [90]

Confidence level: High - evidence strongly supports passive-active hybrid thermal design and careful material/joint selection [20] [21] [22] [25] [48].

6. Dust and abrasion protection for deployables

Dust is one of the clearest threats to your concept because you have **deployable structure, flexible solar, joints, cables, anchors, and exposed radiators** [28] [29].

6.1 Passive mitigation

Microstructured and treated surfaces can reduce adhesion. Textured aluminum reduced measured dust adhesion by 53% versus polished aluminum, and ion-beam treatment lowered adhesion on silicon and quartz [45] [46]. Coatings on polyimide also showed promising dust-removal behavior in related work [32]. But passive methods have durability limitations under UV, abrasion, and thermal cycling [91] [92].

6.2 Active cleaning

For solar blankets and possibly radiator surfaces, active electrostatic cleaning is the most consistently supported option. Electrodynamic dust shields and traveling-wave cleaners repeatedly show high cleaning effectiveness in vacuum and lunar-like conditions, often above 80-90% and sometimes over 98% in optimized cases, with low power use [32] [33] [35] [93]. The key caution is durability: flexible copper-based EDS devices can crack under repeated bending, and discharge control must be managed [36] [60] [94].

6.3 Interfaces and covers

Dust-tolerant connectors and shielding mechanisms have been prototype-tested in simulant and low-pressure environments [47] [95]. Reviews recommend layered protection using coatings, electrodynamic shielding, and flexible boots/bellows for dusty moving interfaces [30].

Recommended dust strategy by subsystem:

- **solar strips:** passive coating + active EDS/traveling-wave cleaner [34] [35]
- **mast joints/guy-wire hardware:** covers or bellows + minimize exposed sliding contact [30] [31]
- **connectors:** dust-tolerant quick-disconnects or shielded integrated interfaces [47] [96]
- **anchor/drill region:** containment and sacrificial wear design, since active dust generation is unavoidable [29] [30]

Confidence level: High - dust mitigation is one of the most consistent themes in the evidence base [28] [29] [30].

7. Power, communications, and subsystem integration

The evidence is favorable to the idea of a **mast as a multifunctional backbone**. LAMPS-like work explicitly combines vertical mast deployment with flexible solar panels, connectors, actuators, avionics, and dust-tolerant mechanisms for lunar missions [37]. Broader multifunctional spacecraft structure work shows that flexible circuits, integrated avionics, and structural composite panels can reduce harness mass and packaging volume [38] [39] [40].

Flexible solar arrays are attractive because of their high stowage efficiency and favorable power-to-mass properties, using roll-out, Z-fold, fan-fold, or related methods [52] [70] [97]. But the system benefit depends on total added mass from booms, interconnects, protection layers, and deployment hardware [98] [99].

For your application, the evidence suggests that **segmented flexible solar strips** attached along the mast are likely more robust than a single continuous blanket.
Inferred: Low confidence - this follows from the evidence on wrinkle/stress concentration at membrane connections, bending durability concerns in active dust shields, and the general packaging benefits of modular deployment, but it is not directly tested as a lunar mast-solar configuration [60] [98] [100].

8. Recommended design blueprint

A practical evidence-backed configuration would be:

1. **Cylindrical lander bus with three active legs** using compliant footpads and lead-screw leveling [17] [80].
2. **Leg-integrated low-reaction anchors**: helical anchors inserted with rotary-percussive or vibration-assisted drive [13] [44].
3. **Self-erecting inflatable composite mast** stowed in rolled form, deployed after landing, then rigidized [1] [2].
4. **Guy wires with spreader bars** deployed after anchoring to tune mast stiffness and pointing [3] [4].
5. **Thermally insulated warm electronics box** at mast base with heaters plus radiator/louver or variable-conductance rejection [21] [22].
6. **Flexible solar strips** attached to the mast with limited intermediate support and protected cable routing [65] [101].
7. **Layered dust control**: passive coating/texturing, joint covers/bellows, and active electrostatic cleaning on solar-facing surfaces [30] [34] [45].
8. **Composite selection biased toward thermal-cycle durability**, with conservative treatment of joints and bonded regions [1] [25].

9. Validation path

The strongest methodological lesson is that the field relies heavily on partial tests and models, so your biggest opportunity is **coupled system testing** [29] [43] [48] [52] [53].

Minimum qualification sequence:

- deployment and rigidization after representative stowage dwell [6] [8]
- tripod leveling and anchor insertion on sloped simulant [17] [44]

- guy-wire tuning and modal/deflection testing [5]
- thermal-vacuum cycling with mast-mounted electronics and solar attached [37] [54]
- dusty thermal-vacuum operation with active cleaning and connector cycling [29] [36] [47]

Conclusion

The evidence supports your concept as **feasible in principle**, but only if it is implemented as a **hybrid lunar surface system** rather than a simple inflatable mast. The most robust path combines: compact inflatable or coilable deployment, post-deployment rigidization, guyed stabilization, tripod leveling, low-reaction helical/percussive anchoring, mixed passive-active thermal control, and layered dust mitigation [4] [13] [22] [30] [37].

The central design trade-off is clear: the architectures that best fit inside a compact cylindrical lander are also the ones most vulnerable to stiffness loss, thermal distortion, and contamination once deployed [6] [9] [28]. That makes **system integration and environmental qualification** more important than any single material choice [29] [37] [48].

Overall confidence level: High - the specific final configuration is not yet validated end-to-end, but the underlying design directions are strongly and repeatedly supported across the provided structural, anchoring, thermal, dust, and integration evidence [2] [25] [34] [38] [44].

References

1. Viquerat, A., Schenk, M. (2016) Viscoelastic effects in metal-polymer laminate inflatable structures. *3rd AIAA Spacecraft Structures Conference*. https://doi.org/10.2514/6.2016-1221
2. Paesano, A., Cohee, D., Palmese, G.R. (2003) Carbon-fiber reinforced thermoplastic materials for rigidizable space systems. *Journal of Thermoplastic Composite Materials*. https://doi.org/10.1177/0892705703016002866
3. Daye, J.G., Lee, A.J., Fernandez, J.M. (2023) Structural Architectures for Self-Erecting Lunar Towers. *AIAA SciTech Forum and Exposition, 2023*. https://doi.org/10.2514/6.2023-0937
4. Portmann, V.P., Miller, A.S., Zhang, J.Z., (...), Chin, H.H. (2024) Modeling and Feedback Control for a Guyed, Flexible, Tubular Lunar Tower. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO58975.2024.10521355
5. Miller, A.S., Lordos, G., Portman, P., (...), Fernandez, J.M. (2023) Design Development of a Stable, Lightweight, Tall and Self-Deploying Lunar Tower. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO55745.2023.10115592
6. Yapa Hamillage, M.Y., Klimm, W., Kwok, K., Fernandez, J.M. (2024) Shape recovery simulation of viscoelastic thin-ply composite coilable booms. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2023.12.042

7. Lee, A.J., Fernandez, J.M. (2019) Inducing bistability in Collapsible Tubular Mast booms with thin-ply composite shells. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2019.111166
8. Roh, J.-H., Kim, H.-I., Lee, S.-Y. (2015) Viscoelastic effect on unfolding behaviors of shape memory composite booms. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2015.07.095
9. Bai, J.B., Shenoi, R.A., Xiong, J.J. (2017) Thermal analysis of thin-walled deployable composite boom in simulated space environment. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2017.04.022
10. Kajihara, S., Yamashita, S., Sunaga, Y., (...), Iwahori, Y. (2025) Deformation behavior of CFRP bistable open-section cylindrical boom for lunar deployable structure. *Thin-Walled Structures*. https://doi.org/10.1016/j.tws.2025.113651
11. Hao, H., Gao, M., Wu, Y., (...), Yang, Y. (2024) Design, test, and verification of in-situ condition preserved coring and analysis system in lunar-based simulation environment. *International Journal of Mining Science and Technology*. https://doi.org/10.1016/j.ijmst.2024.09.001
12. Chen, J., Liao, H., Yang, B., (...), Yan, Z. (2019) Adaptive modeling of rock crack mechanism during drilling operation based on modified peridynamics. *Engineering Fracture Mechanics*. https://doi.org/10.1016/j.engfracmech.2019.106538
13. Batako, A.D., Babitsky, V.I., Halliwell, N.A. (2004) Modelling of vibro-impact penetration of self-exciting percussive-rotary drill bit. *Journal of Sound and Vibration*. https://doi.org/10.1016/S0022-460X(03)00642-4
14. Zhang, T., Wang, B., Wei, H., (...), Zhao, Z. (2021) Review on planetary regolith-sampling technology. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2021.100760
15. Battsengel, Gal-Erdene, Melkoumian, Noune, Harvey, David, Akmeliawati, Rini (2025) Bioinspired Drilling for Extraterrestrial Applications. *Biomimetics*. https://doi.org/10.3390/biomimetics10110752
16. Li, M., Quan, Q., Tang, D., (...), Deng, Z. (2023) Numerical investigation and optimisation of the anchor rod configuration in a drilling anchor for asteroid exploration. *Applied Mathematical Modelling*. https://doi.org/10.1016/j.apm.2022.12.002
17. Manca, R., Puliti, M., Circosta, S., (...), Amati, N. (2022) Design and Optimization of an Active Leveling System Actuator for Lunar Lander Application. *Actuators*. https://doi.org/10.3390/act11090263
18. Ji, S., Liang, S. (2021) DEM-FEM-MBD coupling analysis of landing process of lunar lander considering landing mode and buffering mechanism. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2021.03.034
19. Zhao, Z., Tao, T., Tang, Z., (...), Liu, B. (2020) Development of a Landing Leg with Active Buffering and Anchoring Functions Applied to the Small Body Landing Mechanism. *2020 IEEE International Conference on Mechatronics and Automation, ICMA 2020*. https://doi.org/10.1109/ICMA49215.2020.9233602

20. Biswas, J., Malzone, P.Q., Rößler, F. (2021) Energy storage selection and operation for night-time survival of small lunar surface systems. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2021.04.042

21. Lazio, T.J.W., MacDowall, R.J., Burns, J.O., (...), Kasper, J. (2011) The Radio Observatory on the Lunar Surface for Solar studies. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2011.07.006

22. Bugby, D.C., Farmer, J.T., O'Connor, B.F., (...), Stouffer, C.J. (2010) Two-phase thermal switching system for a small, extended duration lunar surface science platform. *AIP Conference Proceedings*. https://doi.org/10.1063/1.3326291

23. Farrar, D., Douglas, D.M., Swanson, T., (...), Osiander, R. (2007) MEMS shutters for thermal control - Flight validation and lessons learned. *AIP Conference Proceedings*. https://doi.org/10.1063/1.2437443

24. Lee, J.-J., Kim, K.-H. (2019) A proposal for long-term missions of small lunar rovers using an MLI curtain system. *International Journal of Aerospace Engineering*. https://doi.org/10.1155/2019/7248515

25. Vincent-Bonnieu, K.K., Banks, B.A., Miller, S.K.R., Dever, J.A. (2018) Degradation of spacecraft materials. *Handbook of Environmental Degradation Of Materials: Third Edition*. https://doi.org/10.1016/B978-0-323-52472-8.00029-0

26. Shin, K.-B., Kim, C.-G., Hong, C.-S., Lee, H.-H. (2000) Prediction of failure thermal cycles in graphite/epoxy composite materials under simulated low earth orbit environments. *Composites Part B: Engineering*. https://doi.org/10.1016/S1359-8368(99)00073-6

27. Shin, K.-B., Kim, C.-G., Hong, C.-S., Lee, H.-H. (2001) Thermal distortion analysis of orbiting solar array including degradation effects of composite materials. *Composites Part B:Engineering*. https://doi.org/10.1016/S1359-8368(01)00020-8

28. Colwell, J.E., Batiste, S., Horányi, M., (...), Sture, S. (2007) Lunar surface: Dust dynamics and regolith mechanics. *Reviews of Geophysics*. https://doi.org/10.1029/2005RG000184

29. Kobrick, R.L., Klaus, D.M., Street, K.W. (2011) Defining an abrasion index for lunar surface systems as a function of dust interaction modes and variable concentration zones. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2010.10.010

30. Cannon, K.M., Dreyer, C.B., Sowers, G.F., (...), Schertz, J. (2022) Working with lunar surface materials: Review and analysis of dust mitigation and regolith conveyance technologies. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2022.04.037

31. Thengvall, S.J., Nelson, C.A. (2025) DESIGN OF DUST TOLERANT MECHANISMS FOR LUNAR DOCKING APPLICATIONS. *Proceedings of the ASME Design Engineering Technical Conference*. https://doi.org/10.1115/DETC2025-168476

32. Zheng, J., Sun, L., Long, X., (...), Xie, H. (2025) Electricity generation for lunar bases during construction and operation: Key technologies, challenges and development roadmap. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2025.07.032

33. Kawamoto, H., Miwa, T. (2011) Mitigation of lunar dust adhered to mechanical parts of equipment used for lunar exploration. *Journal of Electrostatics*. https://doi.org/10.1016/j.elstat.2011.04.015

34. Calle, C.I., McFall, J.M., Buhler, C.R., (...), Hogue, M.D. (2008) Development of an active dust mitigation technology for lunar exploration. *Space 2008 Conference*. https://doi.org/10.2514/6.2008-7894

35. Calle, C.I., Buhler, C.R., McFall, J.L., Snyder, S.J. (2009) Particle removal by electrostatic and dielectrophoretic forces for dust control during lunar exploration missions. *Journal of Electrostatics*. https://doi.org/10.1016/j.elstat.2009.02.012

36. Isidori Pacelli, F., Scifoni, L., Schaible, M.J., (...), Romero-Calvo, Á. (2026) Flexible electrodynamic dust shields for lunar missions. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2026.02.023

37. Williams, H., Crum, R., Ness, R.V., (...), Hell, K. (2023) Lunar Array, Mast, and Power System (LAMPS) for Deployable Lunar Power Provision. *AIAA SciTech Forum and Exposition, 2023*. https://doi.org/10.2514/6.2023-1389

38. Phelan, P.T., McDaniel, L.T. (2017) Implementation of an integrated avionics unit for a space vehicle. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO.2017.7943830

39. Jang, T., Soo Oh, D., Kyu Kim, J., (...), Woo Rhee, S. (2011) Development of multi-functional composite structures with embedded electronics for space application. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2010.08.009

40. Rawal, S.P., Barnett, D.M., Martin, D.E. (1998) Thermal management for multifunctional structures [spacecraft electronics]. *Proceedings - 1998 International Conference on Multichip Modules and High Density Packaging*. https://doi.org/10.1109/ICMCM.1998.670767

41. Rastogi, V., Upadhyay, S.H., Singh, K.S. (2024) Self-rigidizable Kapton-SMA conical booms: A comprehensive numerical and experimental study. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2024.01.004

42. Katsumata, Nobuhisa, Kume, Masaru, Higuchi, Ken (2017) Deployment behavior control using cables and bi-shape memory alloy convex tape booms. *Advances in Mechanical Engineering*. https://doi.org/10.1177/1687814017707909

43. Daye, J.G., Lee, A.J., Fernandez, J.M. (2025) Structural Architectures for Imperfect Deployable Lunar Towers. *Journal of Spacecraft and Rockets*. https://doi.org/10.2514/1.A36093

44. Klosky, J.L., Sture, S., Ko, H.-Y., Barnes, F. (1998) Helical anchors for combined anchoring and soil testing in lunar operations. *Space 1998*. https://doi.org/10.1061/40339(206)57

45. Tu, S., Zhang, W., Zhang, L., (...), Feng, J. (2025) Superhydrophobic surfaces exhibiting anti-dust performance: From mechanism, preparation, to applications. *Cell Reports Physical Science*. https://doi.org/10.1016/j.xcrp.2025.103015

46. Kendall, Kevin (2021) Cracking equilibrium means low toughness. *Crack Control*. https://doi.org/10.1016/B978-0-12-821504-3.00004-5

47. Herman, J., Sadick, S., Maksymuk, M., (...), Carlson, L. (2009) Dust-tolerant connector development for lunar surface systems. *AIAA Space 2009 Conference and Exposition*. https://www.scopus.com/pages/publications/77958545937

48. Sponagle, B., Groulx, D. (2016) Measurement of thermal interface conductance at variable clamping pressures using a steady state method. *Applied Thermal Engineering*. https://doi.org/10.1016/j.applthermaleng.2015.12.010

49. Wahid, S.M.S., Madhusudana, C.V., Leonardi, E. (2004) Solid spot conductance at low contact pressure. *Experimental Thermal and Fluid Science*. https://doi.org/10.1016/j.expthermflusci.2003.07.007

50. Zarader, C., Ning, X. (2025) Structural effects of ply-level imperfections and extreme temperatures on bistable ultra-thin composite booms. *Extreme Mechanics Letters*. https://doi.org/10.1016/j.eml.2025.102305

51. Ray, Bankim Chandra (2024) Space applications. *Micro and Nanophased Polymeric Composites*. https://doi.org/10.1016/B978-0-12-818957-3.00013-1

52. Spence, B.R., White, S., LaPointe, M., (...), Merrill, J. (2018) International Space Station (ISS) Roll-Out Solar Array (ROSA) Spaceflight Experiment Mission and Results. *2018 IEEE 7th World Conference on Photovoltaic Energy Conversion, WCPEC 2018 - A Joint Conference of 45th IEEE PVSC, 28th PVSEC and 34th EU PVSEC*. https://doi.org/10.1109/PVSC.2018.8548030

53. Guo, S., Wang, G., Qi, Z., (...), Wu, Z. (2020) A quasi-static model for kinematic analysis of a feed driving mechanism. *Mechanism and Machine Theory*. https://doi.org/10.1016/j.mechmachtheory.2020.103780

54. Lazio, T.J.W., MacDowall, R.J., Burns, J.O., (...), Kasper, J. (2011) The Radio Observatory on the Lunar Surface for Solar studies. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2011.07.006

55. Zhou, Yu, Han, Xinyang, Yu, Chengyi, (...), Chen, Weixing (2024) Design, analysis, and ground deployment test of space deployable mast based on double-layer deployable unit. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*. https://doi.org/10.1177/09544062241238851

56. Lv, Z., Qiu, Z., Yang, W., Shi, Q. (2018) Transient thermal analysis of thin-walled space structures with material uncertainties subjected to solar heat flux. *Thin-Walled Structures*. https://doi.org/10.1016/j.tws.2018.05.023

57. Kondyurin, A., Lauke, B., Vogel, R. (2006) Photopolymerisation of composite material in simulated free space environment at low Earth orbital flight. *European Polymer Journal*. https://doi.org/10.1016/j.eurpolymj.2006.04.018

58. Appana, S., Formoso, O., Ochalek, M., Cheung, K. (2024) Footer Module Systems for Discrete Metamaterials Structure Construction in Lunar Environments. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO58975.2024.10521123

59. Chang, B.C., Bernold, L.E., Lee, T.S. (2010) Experimental study of lunar regolith anchoring forces. *Proceedings of the 12th International Conference on Engineering, Science, Construction, and Operations in Challenging Environments - Earth and Space 2010*. https://doi.org/10.1061/41096(366)127

60. Isidori Pacelli, F., Scifoni, L., Schaible, M.J., (...), Romero-Calvo, Á. (2026) Flexible electrodynamic dust shields for lunar missions. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2026.02.023

61. Read, T.S., Chaudhary, S. (2025) IAF HUMAN SPACEFLIGHT SYMPOSIUM (B3) TABS: Thermally Advanced Bimetallic Substrates Advanced Heat Mitigation/Utilization Techniques. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/083088-0069

62. Jiang, M.J., Zhang, N., Cui, L., (...), Wang, X.X. (2022) Estimation of mechanical parameters of Tongji-1 lunar soil simulant based on cone penetration test. *European Journal of Environmental and Civil Engineering*. https://doi.org/10.1080/19648189.2019.1674697

63. Chua, K.M., Johnson, S.W., Nein, M.E. (1993) Structural concepts for lunar-based astronomy. *Applied Mechanics Reviews*. https://doi.org/10.1115/1.3120362

64. Pitcher, C., Gao, Y. (2015) Analysis of drill head designs for dual-reciprocating drilling technique in planetary regoliths. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2015.07.008

65. Kwan, A.S.K., You, Z., Pellegrino, S. (1993) Active and passive cable elements in deployable/retractable masts. *International Journal of Space Structures*. https://doi.org/10.1177/0266351193008001-204

66. Hicks, M.T., Hashemi, A., Capots, L.H. (2006) HexPak - A deploying structure for high power communications. *Collection of Technical Papers - 24th AIAA International Communications Satellite Systems Conference, ICSSC*. https://www.scopus.com/pages/publications/33845218758

67. Watanabe, K., Higuchi, K., Watanabe, A. (2008) Lunar power tower structure by space inflatable extension. *International Astronautical Federation - 59th International Astronautical Congress 2008, IAC 2008*. https://www.scopus.com/pages/publications/77950497197

68. E, J., Bao, R., Fan, J., (...), Wang, K. (2026) A scenario-driven review of multi-agent cooperation for lunar surface missions. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2026.05.046

69. Sandrasegaran, K., Prag, K. (1999) Planning point-to-multipoint rural radio access networks using expert systems. *Expert Systems with Applications*. https://doi.org/10.1016/s0957-4174(99)00031-7

70. Yang, Tianyang, Mi, Xiang, Zhang, Xiaozhao, (...), Wang, Zhiyi (2027) Deformation of flexible solar arrays induced by substrate dehydration under thermal cycling. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2026.113882

71. Underwood, C., Viquerat, A., Schenk, M., (...), Denis, A. (2019) InflateSail de-orbit flight demonstration results and follow-on drag-sail applications. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2019.05.054

72. Tortorici, D., Sabatini, M., Laurenzi, S. (2024) Numerical simulations and experimental results of the deployment of thin-walled bistable composite booms. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2023.117669

73. Sattari, M., Daye, J.G., Lee, A.J. (2025) Deployment of bistable composite tape springs with non-uniform curvatures. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2025.119235

74. Melenbrink, N., Werfel, J., Menges, A. (2020) On-site autonomous construction robots: Towards unsupervised building. *Automation in Construction*. https://doi.org/10.1016/j.autcon.2020.103312

75. Long-Fox, J.M., Campins, H., Britt, D.T. (2026) A review of technologies for lunar science, exploration, resources, and settlement. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2025.106229

76. Klosky, J.Ledlie, Sture, Stein, Ko, Hon-Yim, Barnes, Frank (1998) Helical anchors for combined anchoring and soil testing in lunar operations. *Proceedings of the International Conference and Exposition on Engineering, Construction, and Operations in Space*. https://www.scopus.com/pages/publications/0031649830

77. Crabtree, J., Klosky, J.L., Gash, R., Miller, D. (2008) Helical anchors: Lateral resistance for shaping the lunar surface. *Earth and Space Conference 2008: Proceedings of the 11th Aerospace Division International Conference on Engineering, Science, Construction, and Operations in Challenging Environments*. https://doi.org/10.1061/40988(323)118

78. Zhang, Y., Wu, R., Long, Z., (...), Zhang, T. (2024) Experimental investigation and theoretical modeling of cutting mechanics using serrated tines in drilling lunar regolith simulant. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2024.06.063

79. Zhang, Y., Zhong, L., Wu, R., (...), Zhang, T. (2025) A two-DOF drilling robot with a suction drill for planetary regolith exploration. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2025.02.014

80. Hao, F., Jiang, M.-J., Sun, D.-A., (...), Wang, C. (2015) Indoor experimental research on bearing behaviour of TJ-1 lunar soil simulant. *Yantu Lixue/Rock and Soil Mechanics*. https://doi.org/10.16285/j.rsm.2015.07.016

81. Zhong, S.-Y., Huang, G.-Q., Qi, S.-C., (...), Yang, J.-Z. (2013) Interface property between soft landing foot pad and simulant lunar soil. *Yantu Lixue/Rock and Soil Mechanics*. https://www.scopus.com/pages/publications/84877259163

82. Anderson, W.G., Hartenstine, J.R., Walker, K.L., Farmer, J.T. (2010) Variable thermal conductance link for Lunar landers and rovers. *8th Annual International Energy Conversion Engineering Conference*. https://www.scopus.com/pages/publications/84856872658

83. Zhang, W., Zhao, L., Zhao, H., (...), Wu, Y. (2026) Damage evolution and electrical performance degradation of flexible solar arrays under hypervelocity impacts. *Solar Energy*. https://doi.org/10.1016/j.solener.2026.114947

84. Ajul, E., Shanmuga Priyan, V.G., Chanda, S., Kanmani Subbu, S. (2025) Experimental investigation and predictive model for Al–SiC metal matrix composite heat sink thermal contact conductance. *International Communications in Heat and Mass Transfer*. https://doi.org/10.1016/j.icheatmasstransfer.2025.109619

85. Sasikumar, A., Guerrero, J.M., Quintanas, A., Costa, J. (2021) Numerical study to understand thermo-mechanical effects on a composite-aluminium hybrid bolted joint. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2021.114396

86. de Mey, G., Pilarski, J., Wöjcik, M., (...), Napieralski, A. (2009) Influence of interface materials on the thermal impedance of electronic packages. *International Communications in Heat and Mass Transfer*. https://doi.org/10.1016/j.icheatmasstransfer.2008.10.016

87. Garrison, M.B., Nguyen, D.H. (2007) Thermal considerations for designing the next lunar lander. *AIP Conference Proceedings*. https://doi.org/10.1063/1.2437438

88. Ulamec, S., Biele, J., Trollope, E. (2010) How to survive a Lunar night. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2010.09.024

89. Haarmann, R., Jaumann, R., Claasen, F., (...), Hofmann, P. (2012) Mobile Payload Element (MPE): Concept study for a sample fetching rover for the ESA Lunar Lander Mission. *Planetary and Space Science*. https://doi.org/10.1016/j.pss.2012.08.008

90. Matsumoto, K., Shinomiya, Y., Hoshino, T., (...), Okada, T. (2004) Night survivaland long stay for Japanese moon landing. *International Astronautical Federation - 55th International Astronautical Congress 2004*. https://www.scopus.com/pages/publications/34249085937

91. Tobosque, P., Núñez, J., Elgueda, A., (...), Carrasco, C. (2025) Modifying the surface roughness of solar glass: A passive mitigation method of soiling. *Sustainable Energy Technologies and Assessments*. https://doi.org/10.1016/j.seta.2025.104447

92. Weiß, Karl-Anders, Klimm, Elisabeth, Kaaya, Ismail (2022) Accelerated aging tests vs field performance of PV modules. *Progress in Energy*. https://doi.org/10.1088/2516-1083/ac890a

93. Kawamoto, H., Hashime, S. (2018) Practical performance of an electrostatic cleaning system for removal of lunar dust from optical elements utilizing electrostatic traveling wave. *Journal of Electrostatics*. https://doi.org/10.1016/j.elstat.2018.05.004

94. Scifoni, L., Isidori Pacelli, F., Schaible, M.J., (...), Romero-Calvo, Á. (2026) Performance of electrodynamic dust shields with functional surface coatings for lunar dust mitigation. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2025.08.057

95. Thengvall, S.J., Li, Y., Nelson, C.A. (2026) Prototyping and Testing of a Dust Protection Mechanism for Lunar Docking Applications. *AIAA Science and Technology Forum and Exposition, AIAA SciTech Forum 2026*. https://doi.org/10.2514/6.2026-0931

96. Letier, P., Siedel, T., Deremetz, M., (...), Gancet, J. (2020) HOTDOCK: Design and validation of a new generation of standard robotic interface for on-orbit servicing. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/85099789761

97. Chang-Díaz, F., Carr, J., Johnson, L., (...), Federica Maffione, P.F. (2019) Solar electric propulsion for human mars missions. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2019.04.039

98. Carr, John A, Thompson, Furman, Bumbalough, Austin (2023) Initial steps towards a robotic solution for the manufacturing and assembly of thin-film space solar arrays. *Flexible and Printed Electronics*. https://doi.org/10.1088/2058-8585/acdae2

99. Mejía-Escobar, M.A., Algora, C. (2025) Surveying the potential of flexible and high-specific-power photovoltaic assemblies and arrays for space applications. *Joule*. https://doi.org/10.1016/j.joule.2025.102194

100. Nowak, P.S., Sadeh, W.Z., Morroni, L.A. (1992) Geometric modeling of inflatable structures for lunar base. *Journal of Aerospace Engineering*. https://doi.org/10.1061/(ASCE)0893-1321(1992)5:3(311)

101. Schmid, M. (1987) EXTENDABLE AND RETRACTABLE MAST AS SUPPORTING TOOL FOR RIGID SOLAR ARRAYS.. *European Space Agency, (Special Publication) ESA SP*. https://www.scopus.com/pages/publications/0023598946