Lunar lander inflatable mast design

"our idea is to develop a compact inflatable composite carbon fiber mast with communication hardware, flexible solar panel that is attached to the inflated mast. these parts fitted inside a cylindrical lander with three legs that has low reaction force drill system to anchor itself on the moon surface and give rigid support .how can we make this idea even more innovative and what are the things need to be solved regarding this ?" *Generated by LeapSpace*

Compact Lunar Mast-Lander System at a Glance

Key Findings Table

Topic	Key finding	Practical implication for your concept	Citations
Architecture	The concept is most viable when treated as one coupled structure-power-comms-foundation system rather than separate subsystems.	Co-design mast, solar, antenna, legs, and anchors together.	[1] [2] [3] [4] [5] [6] [7] [8] [9] [10] [11]
Mast	Inflatable/composite masts can deploy compactly and then rigidize, but retained stiffness depends strongly on rigidization method and joint compliance.	Innovation should focus on self-rigidization plus very stiff mast-base and payload joints.	[12] [13] [14] [15] [16] [17] [18] [19]
Solar	Flexible solar on deployable composite structures is feasible, but durability, repeatability, and electrical continuity data remain limited.	Use modular solar strips and isolate failure by segment.	[3] [4] [20] [21]
Communications	Flexible masts create pointing and sway problems; wide-beam patch/dipole concepts are better supported than tightly pointed high-gain antennas.	Prefer motion-tolerant antennas unless mast stabilization is greatly improved.	[5] [9] [22] [23] [24] [25]

Topic	Key finding	Practical implication for your concept	Citations
Anchoring/drilling	Low-reaction drilling methods reduce support force needs, but anchor capacity under combined lunar loads is under-validated.	Penetration is promising; load-bearing proof is still the gap.	[26] [27] [28] [29] [30] [31] [32] [33] [34] [35]
Lander stability	Leg spread and low center of mass improve static stability, but larger spread can increase mass and COM penalties.	Keep the deployed mast light high up; widen support polygon carefully.	[36] [37] [38]
Deployment assurance	Autonomous deployment concepts exist, but evidence for jam tolerance, latch reliability, and single-fault recovery is sparse.	Add degraded-mode operation and fault recovery from the start.	[4] [9] [10] [20] [39] [40] [41]
Environment	Thermal cycling, dust intrusion, and long-term stability are emerging as mission-defining risks.	Environmental survivability may matter more than first deployment success.	[3] [16] [18] [20] [21] [42] [43]

Direct Answer

Your idea becomes more innovative if you turn it into a **hybrid self-anchoring power-and-communications tower** rather than only an inflatable mast on a lander: use an inflatable mast that rigidizes after deployment, add lightweight guy wires or spreader elements, choose antennas that tolerate residual mast motion, make the solar skin modular, and use a hybrid anchor/drill concept rather than a single penetration method [1] [2] [12] [13] [22] [24] [35] [44].

The main problems you need to solve are:

1. **Post-deployment stiffness** of the mast, especially torsion and sway, because this drives RF pointing, tip deflection, and drill/deployment coupling [9] [11] [15] [18] [25].
2. **Mast-base and payload joint compliance**, which can erase much of the benefit of rigidization [15].
3. **Thermal-vacuum and dust durability** of mast materials, solar laminates, and moving interfaces [3] [16] [18] [21] [42].
4. **Anchor load capacity in lunar regolith**, especially under axial, lateral, and overturning loads, not just penetration [33] [34] [35].
5. **Drill vibration and reaction transfer** into a lightweight three-leg lander [7] [11] [45] [46].

6. **Autonomous deployment assurance**, including jams, partial deployment, and single-fault recovery [9] [10] [39] [40].

Most actionable design rule: **reduce sensitivity first**. If you minimize antenna pointing precision requirements and mast tip loads, you relax stiffness, anchoring, and stability demands across the entire system [5] [9] [25].

Confidence level: High - this answer aligns closely with repeated cross-source themes and explicit meta-analysis findings [1] [2] [3] [7] [11] [15] [35].

Study Scope

- **Domain covered:** deployable composite/inflatable masts, flexible solar structures, lunar communications platforms, low-reaction drilling, anchoring in regolith, and three-legged lunar lander stability [3] [9] [12] [29] [35] [36].
- **Time span represented:** roughly 2010-2025, with several recent studies emphasizing thermal durability and deployment validation limits [16] [20] [21] [39].
- **Methods represented:** experiments, thermal-vacuum testing, scaled prototypes, dynamic modeling, multibody simulation, granular/regolith studies, and concept demonstrations [9] [16] [20] [31] [45] [47].

Assumptions & Limitations

- The evidence supports feasibility trends, but the set does **not** provide validated lunar-specific quantitative values for long-term mast torsional stiffness, creep after rigidization, repeated solar deploy-stow electrical degradation, or full flexible-mast RF link budgets [19] [20] [25].
- Penetration methods are better evidenced than **load-bearing anchor performance** under combined lunar loads [29] [32] [33] [35].
- End-to-end tests combining mast deployment, rigidization, solar operation, drilling, anchoring, and RF performance are largely missing [4] [16] [25] [39] [47].

Suggested Further Research

- Compare rigidization options by **post-deployment bending/torsional stiffness, creep, and thermal-cycle durability** in lunar-like vacuum conditions [17] [18] [19].
- Run **integrated mast-anchor-lander dynamic tests** to identify safe drilling speeds and resonance-avoidance strategies [11] [45] [46] [47].
- Validate **hybrid anchors** in lunar simulant under axial, lateral, and overturning loading, not just insertion [33] [34] [35] [44].
- Build RF-structural models converting mast sway and thermal distortion into **explicit pointing and link-margin budgets** [5] [9] [25].
- Test modular flexible solar skins for **dust tolerance, repeated deployment, and electrical continuity** [3] [4] [20].

Full Report

Foundational Context

Your concept combines five subsystems that are tightly coupled on the Moon: a compact deployable mast, a rigidization mechanism, flexible solar power, communications hardware, and a self-anchoring lander foundation [1] [3] [6] [11]. The literature suggests that each subsystem is individually plausible, but the architecture only works if three system-level requirements are satisfied:

1. **Stiffness after deployment** - compact deployability is not enough; the tower must hold shape under thermal change, payload mass, and dynamic disturbance [12] [13] [14] [25].
2. **Stable load transfer into regolith** - the mast's overturning and lateral loads must be carried through the legs and anchors into poorly characterized lunar soil [8] [48] [49].
3. **Reliable autonomous sequencing** - deployment, anchoring, rigidization, and operations must tolerate uncertainty without human intervention [9] [10].

Taken together, these findings suggest your concept should be designed as a **precision-limited surface utility tower**, not as a highly flexible appendage added to a lander late in the design [1] [2] [9] [11].

Confidence level: High - this is the strongest recurring pattern across the evidence base [1] [3] [7] [11] [15].

System Concept and Innovation Opportunities

Integrated architecture overview

A cylindrical three-legged lander is compatible with compact stowage and regular footpad placement, while three-leg and transformable lander concepts are widely used to improve static stability and landing behavior [38] [50] [51]. Deployable lunar towers using thin-ply composite booms have already been studied for communications and sensing, and lateral stabilization can be improved by guy wires or spreader bars [1] [2]. Flexible solar systems on composite deployables have also been demonstrated at subsystem level, though reliability evidence remains thinner than concept maturity [3] [4] [20].

A strong architectural interpretation is therefore:

- **Cylindrical lander body** for packaging efficiency [38].
- **Three landing legs** defining a broad support polygon [36].
- **Low-reaction anchoring/drilling hardware** integrated near the center or into selected legs [31] [35].
- **Inflatable mast** for low-volume deployment [12] [16].
- **Post-deployment rigidization** to convert the mast into an operational load-bearing element [13] [14] [18].

- **Flexible solar strips** attached to low-strain regions of the mast or spreader framework [3] [4].
- **Motion-tolerant communications payload** mounted where sway effects are minimized [9] [22].

Innovation directions

The evidence supports several ways to make the idea more innovative:

1) Make it a hybrid rigidizable mast, not purely inflatable

Hybridization is an emerging pattern across mast and structure concepts, with inflatable deployment combined with rigidization or supporting frameworks [1] [2] [17] [52] [53]. UV-cured, thermosetting, strain-rigidized, and related methods have all been studied, though with varying controllability and durability concerns [17] [18] [19] [54].

2) Add lateral stabilization with low-mass guying or spreaders

Guy wires and spreader bars can materially reduce tip deflection and damp oscillation, directly benefiting comms stability [1] [2] [5] [9]. A novel variant from the synthesis is re-tensionable secondary lines anchored near the footpads, widening the effective structural base with little mast mass; this is an inference from the stability and anchoring evidence, not a directly demonstrated lunar system [2] [9] [35].
Inferred: Low confidence - plausible from combined findings, but not directly validated end-to-end [2] [9] [35].

3) Use the mast as a multifunctional spine

A high-value innovation pathway is to make the mast serve as structure, cable route, power bus, and RF support reference, reducing separate booms and harnesses; this follows the integrated-system pattern in the evidence [1] [3] [9].
Inferred: Medium confidence - consistent with subsystem roles, but not directly reported as a validated lunar architecture [1] [3] [9].

4) Stage deployment

A two-stage sequence—initial low-height inflatable deployment for early communications, followed by anchoring confirmation, rigidization, and final extension—fits the evidence that deployment assurance is weaker than concept maturity [9] [10] [39]. This reduces risk by delaying the most stiffness-sensitive configuration until the foundation is secured [11] [35].

Mission-driven trade space

The main trade-offs are clear:

- **Compact stowage vs stiffness**: inflatable systems package well, but stiffness retention is the main bottleneck [12] [13] [14].

- **Height vs stability**: more height improves line-of-sight and solar exposure, but increases overturning and sway [9] [36].
- **Solar area vs deployment risk**: more attached flexible area improves power, but adds deployment complexity and thermal distortion paths [3] [4].
- **Precision antenna gain vs mast tolerance**: tighter beams demand more pointing stability than the current deployable mast evidence robustly supports [22] [25].
- **Low lander mass vs drilling authority**: lightweight landers benefit from low-reaction drills, but still struggle to absorb residual torque and vibration [7] [11] [31].

Confidence level: High - these trade-offs are explicitly supported across multiple themes [3] [7] [12] [25] [36].

Inflatable Mast, Flexible Solar Array, and Communications Integration

Mast deployment and rigidization

Inflatable composite masts can be rigidized after deployment using thermal curing, UV curing, thermosetting systems, strain-rigidization, and related approaches [12] [13] [14] [17] [18] [19]. However, the evidence also shows limits:

- UV-rigidization addressed stiffness-loss problems seen with spring-tape approaches, but was irreversible and hard to control during handling and testing [18].
- Strain-rigidization studies raised concerns about residual stress, stress relaxation, and even sudden rupture during deployment [19].
- Thermal exposure can degrade self-stiffness in some approaches, motivating cured-resin methods [18].
- Connection-point compliance can substantially reduce torsional performance after deployment [15].

The strongest design implication is that **mast-base design may matter as much as mast-wall material** [15]. If the base joint is soft, improving tube rigidization alone may not solve the system problem [15] [25].

Solar array mounting and power continuity

Flexible solar structures on composite deployables have shown promising subsystem behavior, including thermal-vacuum and thermal-cycle testing and improved repeatable spreading when spreader bars prevent refolding [4] [20]. ACS3-related CFRP boom work also indicates very low thermal deformation relative to earlier metallic booms, though that is not a direct mast-mounted power study [21].

What the evidence does **not** yet provide is equally important: no strong quantitative dataset here for packing ratio, repeated-cycle electrical continuity, or deployment success percentages for flexible solar mounted on lunar mast architectures [4] [20] [21].

A practical innovation is therefore to use:

- **Modular solar strips**, not one continuous wrap [3] [4].
- **Structurally neutral attachment zones**, to limit strain concentration [3].
- **Fault-isolated power channels**, so dust or tearing does not disable the full mast skin; this is an inference from reliability gaps and modular deployment evidence [4] [20].
  Inferred: Medium confidence [4] [20].

Communications payload on a flexible structure

The comms evidence clearly favors antennas that tolerate structural uncertainty. Patch antennas have been fabricated and tested for lunar use with wide-beam temperature-survivable operation [22]. Dipole concepts have also been studied and, in some cases, do not require a large vertical support mast for acceptable sensitivity [23] [24]. By contrast, large erectable antenna studies warn that insufficient stiffness degrades beam pointing and may require distributed control [25].

Guy wires can significantly reduce static tip deflection and damp oscillation within under a minute, which directly helps payload orientation stability [5] [9]. So, unless you add substantial stabilization, the evidence supports:

- **Wide-beam patch antennas** [22].
- **Dipole or crossed-dipole elements** [23] [24].
- **Distributed or electronically tolerant architectures**, rather than tightly pointed high-gain systems [25].

Confidence level: High - the communications design implication is directly supported by multiple studies and the meta-analysis [5] [9] [22] [25].

Anchoring, Landers, and Unresolved Engineering Problems

Low-reaction drilling and anchor architectures

The drilling literature is encouraging on penetration mechanics. Percussive digging reduced needed downforce by about 15× in compacted lunar simulant in one line of evidence [26] [27]. Rotary-percussive systems show lower energy and lower interaction forces than conventional rotary drilling, though not always with a standardized percentage reduction [29] [30]. Torsional vibration assistance improved drilling speed by about 55% and maximum depth by about 46% in one lunar-regolith test [32]. A flexible impact-driven penetrometer kept support reaction force between -3 N and 6 N and torque below 0.4 Nm, demonstrating a very low-reaction architecture [31].

This suggests several innovation paths:

- **Rotary-percussive core mode** for most regolith [29] [30].
- **Vibration-assisted insertion** to lower force demand [32].
- **Hybrid anchor** such as screw/helical plus percussion, or microspine-assisted anchoring in rock-like surfaces [35] [44].

Regolith load transfer and foundation behavior

This is the weakest validated part of the full concept. Soil shear properties—friction angle, cohesion, density, grain size, and volume-change behavior—strongly control support performance [48] [49] [55] [56]. More compacted or denser regolith profiles improve support [8]. For anchors generally, embedment depth, helix diameter, shaft ratio, and displacement criteria matter [34] [57] [58].

But there is a critical gap: the retrieved set does not provide strong lunar-simulant laboratory validation for helical/screw anchors under combined axial, lateral, and overturning loads for your exact use case [33] [35]. So the current evidence supports **"we can likely get the anchor in"** better than **"we know the anchored system will stay rigid under service loads"** [31] [35].

Three-legged lander stability and fault tolerance

Three-legged landers benefit from regular triangular footpad arrangements and improved static stability with larger leg spread, but excessive spread raises leg mass and may increase COM penalties [36] [38]. Lower center of mass improves landing stability [37]. Uneven or tilted touchdown modes worsen interaction duration and load distribution [59].

Fault-tolerance evidence is sobering: 3- and 4-leg landers are particularly vulnerable to single-leg problems because the center of mass can move outside the support polygon on uneven terrain [60]. Stability can be improved with energy-absorbing legs, crushable shock absorbers, rotating/sliding footpads, and adaptive control [61] [62] [63] [64].

Implication: if your lander also drills and supports a mast, **each leg should be treated as part of the foundation system**, not just landing gear [11] [61].

Coupled deployment and drilling dynamics

Rigid-flexible coupling matters during landing, deployment, and drilling [11] [65] [66]. Drill-string studies show that bit-bounce, stick-slip, buckling, and weak damping can all degrade performance [45] [46] [67] [68]. Increasing angular speed can reduce some catastrophic behaviors in certain modeled conditions, while reducing rate of penetration can weaken axial vibration and eliminate bit-bounce in others [45]. Very low intrinsic damping is common in modeled drill-string systems [46].

Taken together, these findings suggest a strong innovation pathway: **treat drilling mode selection as part of structural control**. In practice, rigidize and tension stabilizers before full-height comms operation, and select drill speed/feed profiles that avoid structural resonances [7] [11] [45] [46].

Confidence level: Medium-High - the coupling is well supported qualitatively, but not yet with end-to-end lunar hardware data [7] [11] [45] [47].

Recommended Design Upgrades

High-priority upgrades

1. **Rigidizable inflatable mast with a very stiff root joint** [15] [18].
2. **Retractable guy lines or spreader bars** for lateral stabilization [1] [2] [9].
3. **Wide-beam patch or dipole comms architecture** [22] [23] [24].
4. **Segmented flexible solar strips with isolated power channels** [3] [4].
5. **Hybrid anchor approach**: helical/screw geometry plus percussion or vibration assist [32] [35].
6. **Instrumented structure** using distributed strain or deflection sensing to infer stiffness loss and alignment drift; this is an inference from the need for deployment assurance and structural monitoring [10] [25].
   Inferred: Medium confidence [10] [25].

Deployment sequence recommendation

1. Land and confirm stable stance [38] [61].
2. Compact or preload regolith through footpads if possible [8].
3. Insert primary anchors using low-reaction mode [31] [32].
4. Deploy mast to partial height [16] [39].
5. Rigidize and tension lateral stabilizers [9] [18].
6. Extend to final height and energize modular solar sections [4].
7. Bring comms payload to full mode only after measured stability is acceptable [11] [25].

Critical Unresolved Problems to Solve Before Flight

Problem	Why it matters	Evidence status
Post-rigidization torsional stiffness	Drives antenna stability and dynamic response	Partially evidenced, not well quantified [18] [25]
Joint compliance/backlash	Can dominate whole-structure performance	Explicitly highlighted [15]
Anchor capacity under combined loads	Determines whether “rigid support” is real	Weakly validated for lunar-specific cases [33] [35]
Dust tolerance	Threatens mechanisms, solar interfaces, and maintenance	Recognized risk [20] [42]
Thermal-cycle durability	Affects stiffness retention and solar integrity	Emerging major concern [16] [18] [21]
Drill-lander-mast resonance coupling	Can cause bit bounce, loss of attitude, or damage	Qualitatively supported, needs integrated testing [7] [11] [45]
Autonomous fault recovery	Needed for lunar deployment credibility	Sparse direct validation [9] [10] [39]

Conclusion

Your concept is already aligned with important directions in lunar surface systems: deployable structures, hybrid rigidization, low-reaction penetration, and compact multifunction infrastructure [1] [10] [12] [29] [69]. The best way to make it more innovative is **not** merely to add more features, but to make it a **hybrid, staged, motion-tolerant, self-anchoring tower system** [1] [2] [9] [44].

The highest-risk issues are stiffness retention, joint compliance, anchor load capacity, environmental durability, and deployment assurance [10] [15] [18] [35] [42]. The most valuable next step would be an **integrated validation campaign** that tests mast deployment, rigidization, comms, solar, anchoring, and dynamics together in lunar-relevant conditions [4] [16] [25] [39] [47].

Overall confidence level: High - the architectural recommendations are strongly supported by repeated cross-source patterns, though quantitative design margins remain incomplete for several critical subsystems [1] [3] [11] [15] [35].

References

1. Daye, J.G., Lee, A.J., Fernandez, J.M. (2025) Structural Architectures for Imperfect Deployable Lunar Towers. *Journal of Spacecraft and Rockets*. https://doi.org/10.2514/1.A36093
2. Daye, J.G., Lee, A.J., Fernandez, J.M. (2023) Structural Architectures for Self-Erecting Lunar Towers. *AIAA SciTech Forum and Exposition, 2023*. https://doi.org/10.2514/6.2023-0937

3. Wallner, J., Li, L., Dalbauer, V., Kölbl, S. (2025) Foldable CFRP Structure for High-Power Solar Arrays for Nanosats. *Proceedings of the Munich Symposium on Lightweight Design 2024*. https://doi.org/10.1007/978-3-032-01360-6_5
4. Zhang, X., Chen, L., Chen, W. (2024) A nonlinear algorithm for large deformations of multi-stepped variable-section flexible solar arrays. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2024.02.003
5. Miller, A.S., Lordos, G., Portman, P., (...), Fernandez, J.M. (2023) Design Development of a Stable, Lightweight, Tall and Self-Deploying Lunar Tower. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO55745.2023.10115592
6. Li, J., Wang, L., Feng, C., (...), Zhang, Y. (2025) Penetration and resistance characteristics of lunar regolith simulant drilling using a coupled MPM–CDEM approach. *Journal of Rock Mechanics and Geotechnical Engineering*. https://doi.org/10.1016/j.jrmge.2025.01.029
7. Yin, T., Dong, Z., Yin, Y. (2016) The parametric excitation vibration analysis of drill string in lunar regolith sampler. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/85016492437
8. Jehn, I.E., Dreye, C.B., van Susante, P.J., Primeau, J. (2023) Lunar Site Preparation Requirements for Construction of Infrastructure Elements. *Accelerating Space Commerce, Exploration, and New Discovery Conference, ASCEND 2023*. https://doi.org/10.2514/6.2023-4623
9. Portmann, V.P., Miller, A.S., Zhang, J.Z., (...), Chin, H.H. (2024) Modeling and Feedback Control for a Guyed, Flexible, Tubular Lunar Tower. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO58975.2024.10521355
10. He, D., Ruan, P., Xie, Y., (...), Xie, M. (2026) Design, Dynamic Verification, and Multi-Objective Optimization of a Passive Multi-Link Deployable Support Mechanism for Lunar Surface Solar-Concentrating Systems. *Aerospace*. https://doi.org/10.3390/aerospace13070648
11. Chen, J.-B., Nie, H., Zhang, M., Wang, A.-H. (2007) A study on the stability of Lunar Lander based on the deformation of the buffering. *International Astronautical Federation - 58th International Astronautical Congress 2007*. https://www.scopus.com/pages/publications/54949130943
12. Wei, J., Zhang, P., Ma, R., (...), Tan, H. (2020) Design and Dynamics of Large-scale Solar Arrays with Inflatable Mast. *Jixie Gongcheng Xuebao/Journal of Mechanical Engineering*. https://doi.org/10.3901/JME.2020.05.093
13. Viquerat, A., Schenk, M. (2016) Viscoelastic effects in metal-polymer laminate inflatable structures. *3rd AIAA Spacecraft Structures Conference*. https://doi.org/10.2514/6.2016-1221
14. Scarborough, S.E., Cadogan, D.P. (2006) Applications of inflatable rigidizable structures. *International SAMPE Symposium and Exhibition (Proceedings)*. https://www.scopus.com/pages/publications/34748903395

15. Yoshida, K., Aoki, T., Watanabe, A. (2010) On the effect of mechanical properties of fasteners on torsional stiffness of space extendible mast. *25th Technical Conference of the American Society for Composites and 14th US-Japan Conference on Composite Materials 2010*. https://www.scopus.com/pages/publications/84867770216

16. Underwood, C., Viquerat, A., Schenk, M., (...), Denis, A. (2019) InflateSail de-orbit flight demonstration results and follow-on drag-sail applications. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2019.05.054

17. Dronadula, R., Benaroya, H. (2021) Hybrid lunar inflatable structure. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.10.039

18. Rastogi, V., Upadhyay, S.H., Singh, K.S. (2024) Self-rigidizable Kapton-SMA conical booms: A comprehensive numerical and experimental study. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2024.01.004

19. Glaser, R. (2021) Multi-objective characterization of an inflatable space structure with a quasi-static experimental deflation and finite element analysis. *International Journal of Mechanical Sciences*. https://doi.org/10.1016/j.ijmecsci.2021.106614

20. Liu, Zhengxian, Hao, Sida, Lan, Xin, (...), Leng, Jinsong (2022) Thermal design and analysis of a flexible solar array system based on shape memory polymer composites. *Smart Materials and Structures*. https://doi.org/10.1088/1361-665X/ac40df

21. Elderfield, N., Mukherjee, A., Ermanni, P., Wong, J.C.H. (2025) 3D printed bistable composite lattice shells with tailorable coiled geometries. *Composite Structures*. https://doi.org/10.1016/j.compstruct.2025.119332

22. Gupta, G., Decrossas, E., Chahat, N. (2023) All-Metal Circular Polarized Patch Excited Cup Antennas for Lunar Farside Seismic Suite (FSS). *2nd International Conference on Wireless, Antenna and Microwave Symposium, WAMS 2023*. https://doi.org/10.1109/WAMS57261.2023.10242846

23. Tokarsky, P.L., Konovalenko, A.A., Modelski, J.W. (2023) An Active Ribbon Dipole as an Array Element Prototype for the Lunar Very Low Frequency Radio Telescope. *IEEE Access*. https://doi.org/10.1109/ACCESS.2023.3294694

24. Bubnov, I.M., Stanislavsky, O.O., Yerin, S.M., (...), Belov, O.S. (2026) TERRESTRIAL INVESTIGATION OF THE LOW-FREQUENCY SENSITIVITY OF A RADIO ASTRONOMICAL ANTENNA PROPOSED FOR LUNAR FAR-SIDE OBSERVATIONS OF COSMIC RADIO EMISSIONS. *Radio Physics and Radio Astronomy*. https://doi.org/10.15407/rpra31.01.035

25. Fager, J.A. (1980) Large space erectable antenna stiffness requirements. *Journal of Spacecraft and Rockets*. https://doi.org/10.2514/3.57712

26. Craft, J., Wilson, J., Chu, P., (...), Davis, K. (2010) Percussive digging systems for planetary research. *IEEE Aerospace and Electronic Systems Magazine*. https://doi.org/10.1109/MAES.2010.5631722

27. Craft, J., Wilson, J., Chu, P., (...), Davis, K. (2009) Percussive digging systems for robotic exploration and excavation of planetary and lunar regolith. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO.2009.4839303

28. Klosky, J.L., Sture, S., Ko, H.-Y., Barnes, F. (1996) Vibratory excavation and anchoring tools for the lunar surface. *Engineering, Construction, and Operations in Space V*. https://doi.org/10.1061/40177(207)122

29. Zhang, T., Wang, B., Wei, H., (...), Zhao, Z. (2021) Review on planetary regolith-sampling technology. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2021.100760

30. Chen, C., Quan, Q., Shi, X., (...), Jiang, S. (2016) Multi-state autonomous drilling for lunar exploration. *Chinese Journal of Aeronautics*. https://doi.org/10.1016/j.cja.2016.01.004

31. Zhang, W., Cui, Z., Jiang, W., (...), Liu, R. (2023) Design and verification of flexible penetrometer for planetary subsurface exploration. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2022.11.018

32. Lu, Wei, Ling, Yun, Song, Aiguo, (...), Gu, Shipeng (2013) Measuring Tape-Like Sampling Arm and Drill for Sampling Lunar Regolith. *International Journal of Advanced Robotic Systems*. https://doi.org/10.5772/56361

33. Li, J., Wang, L., Feng, C., (...), Zhang, Y. (2025) Penetration and resistance characteristics of lunar regolith simulant drilling using a coupled MPM–CDEM approach. *Journal of Rock Mechanics and Geotechnical Engineering*. https://doi.org/10.1016/j.jrmge.2025.01.029

34. Cheng, L., Hossain, M.S., Han, Y., (...), Yu, L. (2026) Numerical investigation of inclined loading and failure envelopes of helical anchors in clay over sand. *Ocean Engineering*. https://doi.org/10.1016/j.oceaneng.2026.124948

35. Crabtree, J., Klosky, J.L., Gash, R., Miller, D. (2008) Helical anchors: Lateral resistance for shaping the lunar surface. *Earth and Space Conference 2008: Proceedings of the 11th Aerospace Division International Conference on Engineering, Science, Construction, and Operations in Challenging Environments*. https://doi.org/10.1061/40988(323)118

36. Yuan, Qi, Chen, Heng, Nie, Hong, (...), Hao, Likai (2021) Soft-Landing Dynamic Analysis of a Manned Lunar Lander Em-Ploying Energy Absorption Materials of Carbon Nanotube Buckypaper. *Materials*. https://doi.org/10.3390/ma14206202

37. Yin, H., Wang, X., Wu, L., (...), Liu, J. (2025) Review on soft landing buffer systems for planetary exploration. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2024.12.028

38. Riccobono, Dario, Genta, Giancarlo, Moreland, Scott, Backes, Paul (2020) A multidisciplinary design tool for robotic systems involved in sampling operations on planetary bodies. *CEAS Space Journal*. https://doi.org/10.1007/s12567-020-00330-8

39. Testi, C., Bailey, K., Shah, K., (...), Bannova, O. (2024) DESIGN OF INFLATABLE MULTI-PURPOSE TOWER FOR SUPPORT OF ROBOTIC AND CREWED LUNAR SURFACE OPERATIONS. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/078357-0190

40. Lange, C., Witte, L., Rosta, R., (...), Wilde, M. (2017) First Results from the ROBEX Demonstration Mission on Mt. Etna: A modular system architecture to perform seismic experiments on a volcano as terrestrial validation of a lunar mission scenario. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/85051509233

41. Wang, J., Qi, H., Zhang, Z., (...), Sun, Q. (2023) Failure mechanism of a Q690 steel tubular transmission Tower: Full-Scale experiment and numerical simulation. *Engineering Structures*. https://doi.org/10.1016/j.engstruct.2023.116881

42. Benaroya, H. (2002) An overview of lunar base structures: Past and future. *AIAA Space Architecture Symposium*. https://doi.org/10.2514/6.2002-6113

43. Linossier, A.R. (2017) System concept for in-situ casing generation in a deep Lunar borehole. *Proceedings of the International Astronautical Congress, IAC*. https://www.scopus.com/pages/publications/85051361664

44. Parness, A., Frost, M. (2012) Microgravity coring: A self-contained anchor and drill for consolidated rock. *IEEE Aerospace Conference Proceedings*. https://doi.org/10.1109/AERO.2012.6187052

45. Faghihi, M.A., Mohammadi, H., Azadi Yazdi, E.A., (...), Tashakori, S. (2024) Distributed model for the drill-string system with multiple regenerative effects in the bit-rock interaction. *Journal of Sound and Vibration*. https://doi.org/10.1016/j.jsv.2023.118120

46. Pavković, D., Deur, J., Lisac, A. (2011) A torque estimator-based control strategy for oil-well drill-string torsional vibrations active damping including an auto-tuning algorithm. *Control Engineering Practice*. https://doi.org/10.1016/j.conengprac.2011.04.012

47. Yuan, Qi, Chen, Heng, Nie, Hong, (...), Hao, Likai (2021) Soft-Landing Dynamic Analysis of a Manned Lunar Lander Em-Ploying Energy Absorption Materials of Carbon Nanotube Buckypaper. *Materials*. https://doi.org/10.3390/ma14206202

48. Luo, H., Liu, Z., Fan, C., Li, Y. (2025) Numerical simulation and experimental study of high-speed impact penetrator for lunar subsurface. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2025.04.019

49. Kobaka, J., Katzer, J., Seweryn, K., (...), Konečny, P. (2023) A study of lunar soil simulants from construction and building materials perspective. *Case Studies in Construction Materials*. https://doi.org/10.1016/j.cscm.2023.e02082

50. Bak, David J. (1989) Three legs make mobile platform. *Design News (Boston)*. https://www.scopus.com/pages/publications/0024908223

51. Shcheglov, G.A., Stepashkin, A.B., Nikulin, I.E. (2025) The Concept of Transforming Lunar Lander. *Proceedings of the International Astronautical Congress, IAC*. https://doi.org/10.52202/083076-0069

52. Caiazzo, A., Petrone, G., Casaburo, A., (...), Franco, F. (2026) Conceptual Structural Design of a Pressurized Inflatable and Deployable Habitat Optimized for Lunar Surface Missions. *Materials Research Proceedings*. https://doi.org/10.21741/9781644904251-221

53. Wang, Q., Feng, P., Jansen, K. (2026) Material Design Optimization of Restraint Layer for Rigidizable Inflatable Lunar Habitats. *Lecture Notes in Civil Engineering*. https://doi.org/10.1007/978-3-032-09399-8_184

54. Higgins, M., Benaroya, H. (2020) Utilizing the Analytical Hierarchy Process to determine the optimal lunar habitat configuration. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.04.012

55. Monkul, M.M., Dacić, A. (2017) Effect of grain size distribution on stress-strain behavior of lunar soil simulants. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2017.04.029

56. Jiang, T., Liu, C., Zhang, X., (...), Zhao, J. (2023) Experimental study on the deformation of sandy soil around multi-helical anchor piles under horizontal load. *Applied Ocean Research*. https://doi.org/10.1016/j.apor.2023.103721

57. Huang, Y., Lai, Y., Wang, P., (...), Zong, Z. (2026) Inclined loading performance and failure envelope modelling of single-helix anchors in clay with depth-varying strength. *Ocean Engineering*. https://doi.org/10.1016/j.oceaneng.2025.123368

58. Tilak B, V., Samadhiya, N.K. (2022) Pullout capacity of circular multi-plate vertical anchors in sand – An experimental study. *Ocean Engineering*. https://doi.org/10.1016/j.oceaneng.2022.111779

59. Ji, S., Liang, S. (2021) DEM-FEM-MBD coupling analysis of landing process of lunar lander considering landing mode and buffering mechanism. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2021.03.034

60. Yin, Ke, Zhou, Songlin, Sun, Qiao, Gao, Feng (2021) Lunar Surface Fault-Tolerant Soft-Landing Performance and Experiment for a Six-Legged Movable Repetitive Lander. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s21175680

61. Yuan, Qi, Chen, Heng, Nie, Hong, (...), Hao, Likai (2021) Soft-Landing Dynamic Analysis of a Manned Lunar Lander Em-Ploying Energy Absorption Materials of Carbon Nanotube Buckypaper. *Materials*. https://doi.org/10.3390/ma14206202

62. Schröder, S., Reinhardt, B., Brauner, C., (...), Buchwald, R. (2017) Development of a Marslander with crushable shock absorber by virtual and experimental testing. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2017.01.023

63. Xu, Jianwei, Qiao, Jianzhong, Guo, Lei (2018) An enhanced anti-disturbance guidance scheme for powered descent phase of Mars landing under actuator fault. *International Journal of Advanced Robotic Systems*. https://doi.org/10.1177/1729881418759889

64. Mei, Y., Liao, Y., Gong, K. (2023) Adaptive fuzzy dynamic surface fault-tolerant control for coupled spacecraft with actuator faults and saturation. *Advances in Space Research*. https://doi.org/10.1016/j.asr.2023.01.053

65. Wang, J., Zhang, S., Zhang, K., Deng, Z. (2026) Equation-consistent similarity framework for dynamics and control of a rigid-hub flexible-beam solar sail. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2026.113358

66. Zhong, Q., Zhang, Q., Xu, M., (...), Cai, J. (2026) Kinematic singularity elimination and deployment dynamics of a gear-synchronized truss-type deployable structure. *Engineering Structures*. https://doi.org/10.1016/j.engstruct.2026.123748

67. De Moraes, L.P.P., Savi, M.A. (2019) Drill-string vibration analysis considering an axial-torsional-lateral nonsmooth model. *Journal of Sound and Vibration*. https://doi.org/10.1016/j.jsv.2018.08.054

68. Han, Y., Ai, Z., Kuang, Y., (...), Yang, W. (2019) Nonlinear dynamic modeling of drill string in horizontal well - A geometrically exact approach. *Journal of Petroleum Science and Engineering*. https://doi.org/10.1016/j.petrol.2018.09.022

69. Dronadula, R., Benaroya, H. (2021) Hybrid lunar inflatable structure. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.10.039