GROUP OF JOLT EXAMPLES




- This template contains four (4) examples of JSON-to-JSON transformation using Jolt
- Each of the examples follows the same flow diagram shown below

Listens for incoming HTTP GET request Replaces any text with a preset JSON-formatted body Uses Jolt to do a JSON-to-JSON transformation on the content Returns a response to the requestor

Created by Marcus Vega

Jolt Transformation Examples Data Flow




KEY ATTRIBUTES

- HandleHttpRequest: Listens for incoming requests.
- ReplaceText: Replaces the flowfile content with a predetermined
 JSON body of text
 - By default, all ReplaceText in this template will contain the same replacement text
- JoltTransformJSON: A JSON-to-JSON transformation takes place using Jolt transformation language
- HandleHttpResponse: Sends a response with the body of the transformed content back to the requestor.

NOTES

- If you have not mapped data using the Jolt Transformation Language before, you might want to start at the process group with the name 'Jolt Transformation 1-to-1' as it is the most basic of the four transformations.
- HandleHttpRequest
 - This processor requires the StandardHttpContextMap to be enabled for it to run
 - The StandardHttpContextMap specified in this processor must be the same StandardHttpContextMap specified in the HandleHttpResponse processor
 - Default endpoint is listed in the label under this processor. The port number will be different for each flow. Example can be seen below.



The label is the large yellow box.

The endpoint is shown within the red square

- JoltTransformJSON
 - There is a green label to the left side of each JoltTransformJSON processor.
 - This label contains a description of what each part of the Jolt spec (the mapping) does.