LICENSEPROOF · DEPENDENCY LICENSE REPORT

License report for acme-video-platform

PROJECT LICENSE	SCAN DATE	PACKAGES
UNLICENSED	2026-07-22T08:37:33.285Z	121 (npm: 104 · pypi: 17)
CONFLICTS	**REVIEW**	**UNKNOWN**
1	1	1
TOOL VERSION	**DATA VERSION**	
0.3.0	2026.07.21.2	

> **1 license conflict requires attention before distribution.**

Informational license categorization — not legal advice.

Executive summary

This report covers 121 packages resolved from the npm and PyPI dependency trees of acme-video-platform, whose declared project license is UNLICENSED.

1 package was flagged as a license conflict against the project license. 1 package was flagged for manual review. 1 could not be confidently identified. The remaining 118 raised no flags.

Among the packages whose license was identified, the most restrictive category present is strong copyleft.

Findings

Packages that raised a flag against the project license, most restrictive first. Clean packages are listed in the full inventory below.

Conflict (1)

CONFLICT **ffmpeg-static@5.3.0** npm direct · production dependency

License	GPL-3.0-or-later	Category	strong copyleft
Confidence	high	Source	metadata
Dependency	via ffmpeg-static		

This package is under a strong-copyleft license (e.g. GPL/AGPL). Distributing it as part of a closed-source product can require releasing your own source code under the same terms. Flagged as CONFLICT for a proprietary project.

Review (1)

REVIEW **certifi@2026.7.22** pypi transitive · production dependency

License	MPL-2.0	Category	weak copyleft
Confidence	high	Source	metadata
Dependency	via requests → certifi		

This package is under a weak-copyleft license (e.g. LGPL/MPL). Obligations typically depend on whether you modify the package or merely link/import it dynamically. Flagged for REVIEW, not automatic CONFLICT.

Unknown (1)

UNKNOWN **colorama@0.4.6** pypi transitive · production dependency

License	UNKNOWN	Category	unknown
Confidence	low	Source	none
Dependency	via click → colorama		

LicenseProof could not confidently identify this package's license. Unknown does not mean safe — flagged for manual REVIEW.

Full inventory

Every scanned package, ordered by status then name. Matches the JSON report ordering.

All 121 packages

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
ffmpeg-static	5.3.0	npm	GPL-3.0-or-later	strong copyleft	high	metadata	CONFLICT
certifi	2026.7.22	pypi	MPL-2.0	weak copyleft	high	metadata	REVIEW
colorama	0.4.6	pypi	UNKNOWN	unknown	low	none	UNKNOWN
@derhuerst/http-basic	8.2.4	npm	MIT	permissive	high	metadata	CLEAN
@types/node	10.17.60	npm	MIT	permissive	high	metadata	CLEAN
accepts	1.3.8	npm	MIT	permissive	high	metadata	CLEAN
agent-base	6.0.2	npm	MIT	permissive	high	metadata	CLEAN
annotated-types	0.7.0	pypi	MIT	permissive	medium	classifier	CLEAN
array-flatten	1.1.1	npm	MIT	permissive	high	metadata	CLEAN
asynckit	0.4.0	npm	MIT	permissive	high	metadata	CLEAN
axios	1.18.1	npm	MIT	permissive	high	metadata	CLEAN
body-parser	1.20.6	npm	MIT	permissive	high	metadata	CLEAN
buffer-from	1.1.2	npm	MIT	permissive	high	metadata	CLEAN
bytes	3.1.2	npm	MIT	permissive	high	metadata	CLEAN
call-bind-apply-helpers	1.0.2	npm	MIT	permissive	high	metadata	CLEAN
call-bound	1.0.4	npm	MIT	permissive	high	metadata	CLEAN
caseless	0.12.0	npm	Apache-2.0	permissive	high	metadata	CLEAN
chalk	5.6.2	npm	MIT	permissive	high	metadata	CLEAN

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
charset-normalizer	3.4.9	pypi	MIT	permissive	high	metadata	CLEAN
click	8.4.2	pypi	BSD-3-Clause	permissive	high	expression	CLEAN
combined-stream	1.0.8	npm	MIT	permissive	high	metadata	CLEAN
concat-stream	2.0.0	npm	MIT	permissive	high	metadata	CLEAN
content-disposition	0.5.4	npm	MIT	permissive	high	metadata	CLEAN
content-type	1.0.5	npm	MIT	permissive	high	metadata	CLEAN
cookie	0.7.2	npm	MIT	permissive	high	metadata	CLEAN
cookie-signature	1.0.7	npm	MIT	permissive	high	metadata	CLEAN
cors	2.8.6	npm	MIT	permissive	high	metadata	CLEAN
dayjs	1.11.21	npm	MIT	permissive	high	metadata	CLEAN
debug	4.4.3	npm	MIT	permissive	high	metadata	CLEAN
debug	2.6.9	npm	MIT	permissive	high	metadata	CLEAN
debug	4.4.3	npm	MIT	permissive	high	metadata	CLEAN
delayed-stream	1.0.0	npm	MIT	permissive	high	metadata	CLEAN
depd	2.0.0	npm	MIT	permissive	high	metadata	CLEAN
destroy	1.2.0	npm	MIT	permissive	high	metadata	CLEAN
dunder-proto	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
ee-first	1.1.1	npm	MIT	permissive	high	metadata	CLEAN
encodeurl	2.0.0	npm	MIT	permissive	high	metadata	CLEAN
env-paths	2.2.1	npm	MIT	permissive	high	metadata	CLEAN
es-define-property	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
es-errors	1.3.0	npm	MIT	permissive	high	metadata	CLEAN

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
es-object-atoms	1.1.2	npm	MIT	permissive	high	metadata	CLEAN
es-set-tostringtag	2.1.0	npm	MIT	permissive	high	metadata	CLEAN
escape-html	1.0.3	npm	MIT	permissive	high	metadata	CLEAN
etag	1.8.1	npm	MIT	permissive	high	metadata	CLEAN
express	4.22.2	npm	MIT	permissive	high	metadata	CLEAN
finalhandler	1.3.2	npm	MIT	permissive	high	metadata	CLEAN
follow-redirects	1.16.0	npm	MIT	permissive	high	metadata	CLEAN
form-data	4.0.6	npm	MIT	permissive	high	metadata	CLEAN
forwarded	0.2.0	npm	MIT	permissive	high	metadata	CLEAN
fresh	0.5.2	npm	MIT	permissive	high	metadata	CLEAN
function-bind	1.1.2	npm	MIT	permissive	high	metadata	CLEAN
get-intrinsic	1.3.0	npm	MIT	permissive	high	metadata	CLEAN
get-proto	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
gopd	1.2.0	npm	MIT	permissive	high	metadata	CLEAN
has-symbols	1.1.0	npm	MIT	permissive	high	metadata	CLEAN
has-tostringtag	1.0.2	npm	MIT	permissive	high	metadata	CLEAN
hasown	2.0.4	npm	MIT	permissive	high	metadata	CLEAN
http-errors	2.0.1	npm	MIT	permissive	high	metadata	CLEAN
http-response-object	3.0.2	npm	MIT	permissive	high	metadata	CLEAN
https-proxy-agent	5.0.1	npm	MIT	permissive	high	metadata	CLEAN
iconv-lite	0.4.24	npm	MIT	permissive	high	metadata	CLEAN
idna	3.18	pypi	BSD-3-Clause	permissive	high	expression	CLEAN

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
inherits	2.0.4	npm	ISC	permissive	high	metadata	CLEAN
ipaddr.js	1.9.1	npm	MIT	permissive	high	metadata	CLEAN
lodash	4.18.1	npm	MIT	permissive	high	metadata	CLEAN
markdown-it-py	4.2.0	pypi	MIT	permissive	medium	classifier	CLEAN
math-intrinsics	1.1.0	npm	MIT	permissive	high	metadata	CLEAN
mdurl	0.1.2	pypi	MIT	permissive	medium	classifier	CLEAN
media-typer	0.3.0	npm	MIT	permissive	high	metadata	CLEAN
merge-descriptors	1.0.3	npm	MIT	permissive	high	metadata	CLEAN
methods	1.1.2	npm	MIT	permissive	high	metadata	CLEAN
mime	1.6.0	npm	MIT	permissive	high	metadata	CLEAN
mime-db	1.52.0	npm	MIT	permissive	high	metadata	CLEAN
mime-types	2.1.35	npm	MIT	permissive	high	metadata	CLEAN
ms	2.1.3	npm	MIT	permissive	high	metadata	CLEAN
ms	2.1.3	npm	MIT	permissive	high	metadata	CLEAN
ms	2.0.0	npm	MIT	permissive	high	metadata	CLEAN
ms	2.1.3	npm	MIT	permissive	high	metadata	CLEAN
negotiator	0.6.3	npm	MIT	permissive	high	metadata	CLEAN
object-assign	4.1.1	npm	MIT	permissive	high	metadata	CLEAN
object-inspect	1.13.4	npm	MIT	permissive	high	metadata	CLEAN
on-finished	2.4.1	npm	MIT	permissive	high	metadata	CLEAN
parse-cache-control	1.0.1	npm	BSD-3-Clause	permissive	medium	license-file	CLEAN
parseurl	1.3.3	npm	MIT	permissive	high	metadata	CLEAN
path-to-regexp	0.1.13	npm	MIT	permissive	high	metadata	CLEAN

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
progress	2.0.3	npm	MIT	permissive	high	metadata	CLEAN
proxy-addr	2.0.7	npm	MIT	permissive	high	metadata	CLEAN
proxy-from-env	2.1.0	npm	MIT	permissive	high	metadata	CLEAN
pydantic	2.13.4	pypi	MIT	permissive	high	expression	CLEAN
pydantic-core	2.46.4	pypi	MIT	permissive	high	expression	CLEAN
pygments	2.20.0	pypi	BSD-2-Clause	permissive	high	expression	CLEAN
python-dotenv	1.2.2	pypi	BSD-3-Clause	permissive	high	metadata	CLEAN
qs	6.15.3	npm	BSD-3-Clause	permissive	high	metadata	CLEAN
range-parser	1.2.1	npm	MIT	permissive	high	metadata	CLEAN
raw-body	2.5.3	npm	MIT	permissive	high	metadata	CLEAN
readable-stream	3.6.2	npm	MIT	permissive	high	metadata	CLEAN
requests	2.34.2	pypi	Apache-2.0	permissive	high	metadata	CLEAN
rich	15.0.0	pypi	MIT	permissive	high	metadata	CLEAN
safe-buffer	5.2.1	npm	MIT	permissive	high	metadata	CLEAN
safer-buffer	2.1.2	npm	MIT	permissive	high	metadata	CLEAN
send	0.19.2	npm	MIT	permissive	high	metadata	CLEAN
serve-static	1.16.3	npm	MIT	permissive	high	metadata	CLEAN
setprototypeof	1.2.0	npm	ISC	permissive	high	metadata	CLEAN
side-channel	1.1.1	npm	MIT	permissive	high	metadata	CLEAN
side-channel-list	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
side-channel-map	1.0.1	npm	MIT	permissive	high	metadata	CLEAN

PACKAGE	VERSION	ECOSYSTEM	LICENSE	CATEGORY	CONFIDENCE	SOURCE	STATUS
side-channel-weakmap	1.0.2	npm	MIT	permissive	high	metadata	CLEAN
statuses	2.0.2	npm	MIT	permissive	high	metadata	CLEAN
string_decoder	1.3.0	npm	MIT	permissive	high	metadata	CLEAN
toidentifier	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
type-is	1.6.18	npm	MIT	permissive	high	metadata	CLEAN
typedarray	0.0.6	npm	MIT	permissive	high	metadata	CLEAN
typing-extensions	4.16.0	pypi	PSF-2.0	permissive	high	expression	CLEAN
typing-inspection	0.4.2	pypi	MIT	permissive	high	expression	CLEAN
unpipe	1.0.0	npm	MIT	permissive	high	metadata	CLEAN
urllib3	2.7.0	pypi	MIT	permissive	high	expression	CLEAN
util-deprecate	1.0.2	npm	MIT	permissive	high	metadata	CLEAN
utils-merge	1.0.1	npm	MIT	permissive	high	metadata	CLEAN
uuid	9.0.1	npm	MIT	permissive	high	metadata	CLEAN
vary	1.1.2	npm	MIT	permissive	high	metadata	CLEAN
zod	3.25.76	npm	MIT	permissive	high	metadata	CLEAN

Methodology & limitations

How licenses were resolved, what confidence means, and known limitations

How each package's license is resolved

LicenseProof reads only files already present on disk from the scanned project and its installed dependencies. It never contacts a network, registry, or remote service. The two ecosystems use different resolution orders:

npm packages

The first step that yields a license wins (later steps are not consulted):

1. **Declared metadata** — the `license` field in the package's `package.json`, parsed as an SPDX id or expression (OR / AND / WITH preserved). Confidence: high. npm's `UNLICENSED` convention is not treated as an SPDX id and falls through.
2. **License file** — the text of an on-disk `LICENSE` / `COPYING` file, matched by fingerprint against known license texts. Confidence: medium for a close match, low for a modified or partial match.
3. **README mention** — a `License:` line near the top of the README. Confidence: low.
4. **Unknown** — no signal resolved; the package is reported as `UNKNOWN` and flagged for review. Unknown does not mean safe.

PyPI packages

The metadata signals are read together so a disagreement between them can be surfaced; the on-disk steps run only when no metadata signal resolved:

1. **License-Expression** — the PEP 639 `License-Expression` metadata field. Confidence: high.
2. **License** — the legacy `License` metadata field, used when no `License-Expression` is present. Confidence: high.
3. **Trove classifiers** — the `License ::` classifiers, mapped to a representative SPDX id. Confidence: medium (classifiers are coarser than an explicit id — e.g. "BSD License" cannot distinguish BSD-2 from BSD-3).
4. **License file** — on-disk license text, fingerprint-matched. Confidence: medium / low, as for npm.
5. **README mention** — a `License:` line. Confidence: low.
6. **Unknown** — reported as `UNKNOWN`, flagged for review.

When a PyPI package's declared license field and its Trove classifiers resolve to different licenses (and not merely to different variants of the same license family), the package is additionally flagged for review as an internal metadata inconsistency.

What the confidence levels mean

- **high** — the license came from an explicit, declared SPDX id or expression in package or project metadata.
- **medium** — the license was inferred from a close license-file text match or from a coarse Trove classifier.

- **low** — the license came from a modified/partial license-file match, a README mention, or could not be determined at all (Unknown).

Limitations

- The category assigned to each license is an informational classification, not a legal determination of your obligations.
- Only declared and detectable license signals are used. No manual legal review is performed, and no upstream registry is consulted (the tool runs fully offline).
- Dependency paths are enumerated up to a cap; a "+at least N other paths" note is a floor, not an exact total.
- A package's resolved license reflects the metadata and files present on disk at scan time; it is not verified against any external source of truth.
- Unknown does not mean safe — it means the license could not be identified confidently and needs a human to look.

Not legal advice

This report is an informational license categorization produced by automated analysis of declared package metadata and license files. It is not legal advice and is not a substitute for review by qualified counsel.

`LicenseProof 0.3.0 · reference data 2026.07.21.2 (SPDX license list e4c1f27) · scanned 2026-07-22T08:37:33.285Z`

This report is an informational license categorization produced by automated analysis of declared package metadata and license files. It is not legal advice and is not a substitute for review by qualified counsel.