

Recursive Self-Improvement in AI: From Bounded Self-Refinement to Autonomous Research Loops

Mingguang Chen^{1,*} Licheng Wang² Bo Qu³

¹DeepGrounding ²AlphaAvatar ³Illinois Institute of Technology (IIT)

*Corresponding authors. Email: deepgroundingai@gmail.com

July 2026

Abstract

AI systems increasingly participate in their own improvement: revising their outputs, adapting and evolving their own harnesses during deployment, training on data they generate, and — in a growing research thread — conducting AI research itself. The literature describing this participation has exploded, but under a vocabulary (“self-refine,” “self-reward,” “self-play,” “self-evolve”) that conflates fundamentally different ambitions. We survey 1,250 arXiv papers (2024–2026) and organize them along two axes: *what the system improves* — its behavior in deployment, its policy through training, its evaluator, or the research process itself — and the *degree of loop closure* (human-in-the-loop to fully closed). The taxonomy separates *bounded self-refinement* — convergent, evaluable, and already industrial practice — from *open-ended recursive self-improvement* (RSI), which remains bounded by grounding requirements, collapse dynamics, and compute constraints on every side current evidence can measure. Its distinctive feature is a dedicated category for *self-evaluation*: every improvement loop is a claim that some signal can substitute for human judgment, so we survey the evaluator design space — judges, process reward models, verifiers, rubrics, meta-evaluation — alongside the loops it supervises, order the signals into a verification hierarchy from formal verifiers (strongest) to intrinsic self-assessment (weakest), and observe that demonstrated self-improvement strength tracks this hierarchy, that its characteristic failure modes (self-confirming loops, model collapse, diversity collapse) follow from its violations, and that the “research direction-setting” bottleneck that keeps humans in the loop divides into a verification problem the hierarchy indexes and a prior one — choosing what deserves evaluation at all — that it does not. We connect the technical literature to the theory of RSI limits and to the safety and governance questions raised by frontier-lab accounts of closing the loop, and identify governance-grade measurement of self-improvement as the field’s most underpopulated niche.

1. Introduction

The idea that an artificial intelligence might improve itself — and that each improvement might make the next one easier — is among the oldest in the field. Good’s “intelligence explosion” argument [1] and Schmidhuber’s provably-optimal Gödel machines [2] framed recursive self-improvement (RSI) as a theoretical endpoint decades before any system could plausibly attempt it. What has changed is that fragments of the loop are now engineering practice. Large language models routinely critique and revise their own outputs, train on data they themselves generated, rewrite their own agent scaffolding, and — in systems like FunSearch [3] and AlphaEvolve [4] — discover algorithms that feed back into the infrastructure of AI development itself.

Anthropic’s recent essay on recursive self-improvement [5] frames this transition as a continuum of increasing AI autonomy in the AI-improvement loop: from humans writing all code (pre-2023), through chatbot-assisted coding and autonomous coding agents, to agents that delegate work to other agents today, and — at the end of the spectrum — “closing the loop”: agents that design and train their successor models. The essay argues that current systems sit conspicuously far along this spectrum on *execution* (as of May 2026, Claude reportedly writes over 80% of Anthropic’s merged code) while remaining bottlenecked on *research direction-setting* — choosing which problems matter. Whether, when, and how the remaining gap closes is arguably the most consequential open question in the field. We use the essay as a motivating frame and a source of stage vocabulary, not as evidence; the survey’s evidence base is the peer literature collected below.

This survey maps the research literature underneath that question. We assembled a corpus of **1,250 arXiv papers (2024–2026)** — a systematic seed harvest of 871 papers across seven threads of the self-improvement literature, extended by a targeted supplemental harvest of 379 papers in directions the taxonomy below makes first-class (§2.3) — and classified all of them into **four technical categories plus a foundations family** (Table 1). Three observations motivate the paper’s structure:

First, “self-improvement” is not one thing. The term is used for inference-time output revision (Self-Refine [6]), training loops on self-generated data (STaR [7], Self-Rewarding LMs [8]), agents that rewrite their own code (Gödel Agent [9], Darwin Gödel Machine [10]), and systems that autonomously conduct AI research [11]. These differ enormously in ambition and risk profile, yet the literature’s “self-X” vocabulary (self-refine, self-reward, self-play, self-distill, self-evolve, self-verify) obscures the differences. We organize the field along two axes: **(i) what the system improves** — its behavior in *deployment* (outputs, weights adapted at test time, or its own harness), its *policy* through a training phase, its *evaluator* (the signal that defines “better”), or the *research process itself*; and **(ii) the degree of loop closure** — is a human in the loop, reviewing an automatically generated signal, or absent entirely?

Second, the field is accelerating faster than it is consolidating. 74% of our corpus was posted in 2026; quarterly output in the seed harvest grew from single digits in early 2024 to roughly 500 papers in 2026 Q2 (Figure 6). Existing surveys cover single slices — on-policy distillation [12], tree-search-plus-reward methods [13] — but no survey spans the full spectrum from bounded self-refinement to open-ended RSI. That integration, anchored to an explicit autonomy continuum, is this paper’s main contribution.

Third, one bottleneck recurs everywhere: the evaluator. Every category we survey lives or dies by the reliability of its improvement signal — a verifier, a reward model, execution feedback, a proof checker, a meta-evaluator. Self-training works where answers are checkable (code, math) and degrades where they are not; automated researchers produce fluent papers whose claims resist auditing; self-rewarding loops hack their own judges. We therefore treat *self-evaluation* not as a cross-cutting remark but as a category of its own (§5) — the pillar on which the other three stand.

Contributions. (1) A two-axis taxonomy — four improvement categories crossed with degree of loop closure — that cleanly separates *bounded self-refinement* from *open-ended recursive self-improvement* and replaces the ambiguous self-X vocabulary (§2). (2) A systematic map of 1,250 recent papers into the taxonomy, each category surveyed in §§3–6. (3) A dedicated treatment of self-evaluation — the evaluator design space, the verification hierarchy, and the failure modes that follow from its violations — as the field’s common limiting factor (§5). (4) A synthesis of the theory, limits, and safety literature that connects the technical threads back to the takeoff question (§7).

Table 1. The taxonomy’s four technical categories plus the foundations family, with corpus coverage.

Category	Sub-threads	Papers	% posted 2026
Deployment-time self-evolution (§3)	output refinement · test-time training · harness/skill evolution	393	74%
Training-time self-iteration (§4)	self-reward RL · CoT self-training · self-distillation · self-play (incl. zero-data) · embodied	340	69%
Self-evaluation (§5)	judges · process/reward models · verifiers · rubrics · meta-evaluation	318	82%
Auto Research (§6)	AI scientists · evolutionary program discovery	139	76%
Foundations, limits & safety (§7)	theory · limits · safety	60	57%

2. Preliminaries, Taxonomy, and Method

2.1 Preliminaries and definitions

The terms below are used loosely and inconsistently across the literature; we fix their meanings for this survey.

Agent. An LLM-based system that pursues a goal through a perceive–act loop: it observes state (tool outputs, environment feedback, files), chooses actions (tool calls, code execution, messages), and iterates until a stopping condition. A bare model invoked once is not an agent; the same model inside a loop with tools and memory is.

Harness (scaffolding). Everything around the model that turns it into an agent: system prompts, tool definitions, memory stores, skill libraries, retrieval indices, orchestration code, stopping rules [14]. The harness is externally inspectable and editable — including by the agent itself, which is what makes harness self-modification the most concrete form of “the agent rewrites itself.”

Evaluator (verifier, judge, reward model). Any mechanism that maps a candidate artifact to a quality signal: a formal proof checker, a test suite, a learned reward or process-reward model, an LLM judge, a rubric, a human rater. We use *verifier* for evaluators with soundness guarantees, *judge* for learned or prompted evaluators without them.

Self-improvement. A system participates in producing a better version of itself or of its own outputs, where “better” is defined by some evaluator. The definitional dependence on an evaluator

is not pedantry; it is the source of every failure mode in §5.

Test-time training (TTT). Updating model weights *during deployment*, conditioned on the current query or session, without a curated offline training phase — distinct from inference-time refinement (weights frozen) and from training-time iteration (offline phase).

Self-play. Training in which the model generates its own tasks or opponents — proposer–solver loops, adversarial curricula — including the *zero-data* regime that starts from nothing but a base model [15, 16].

Bounded self-refinement vs. open-ended RSI. Bounded self-refinement improves a system against a fixed, external evaluator; it is convergent and evaluable. Open-ended recursive self-improvement modifies the system *and* the criteria or machinery of improvement itself, with no fixed external anchor; it is divergent in principle. The distinction is the survey’s central cut.

2.2 A two-axis taxonomy

The literature’s terminology has proliferated faster than its concepts. *Self-refine*, *self-correct*, *self-reward*, *self-play*, *self-distill*, *self-train*, *self-evolve*, *self-verify* — each names a mechanism, but the mechanisms cut across fundamentally different ambitions. A model that re-reads its draft and fixes an error is doing something categorically different from an agent that rewrites its own codebase, even though both are “self-improving.” We locate any self-improvement method on two axes.

Axis 1 — what does the system improve? Four categories:

- **Deployment-time self-evolution** (§3): the system improves *during deployment* — iterating on outputs with frozen weights, adapting weights per query (test-time training), or evolving its own harness, skills, and memory. Improvement is episodic or accumulates outside the base weights. (Parts of this category are often called *inference-time* self-improvement; we prefer *deployment-time* because the category also includes weight updates (§3.4) and cross-episode accumulation (§3.5–3.6), which “inference-time” would misdescribe.)
- **Training-time self-iteration** (§4): the system generates data, rewards, or teacher signals that update its own weights in a training phase. Improvement persists in the weights but is bounded by the quality of the self-generated signal.
- **Self-evaluation** (§5): the system’s *evaluator* is the object of improvement — designing, strengthening, or co-evolving the judges, verifiers, reward models, and rubrics that define “better” for the other three categories.
- **Auto Research** (§6): the system does the work of AI research itself — proposing hypotheses, running experiments, discovering algorithms — in the limit, autonomously optimizing the methods of §§3–5. Improvement compounds across systems, not within one.

Axis 2 — degree of loop closure. *Who* validates the improvement?

- **Human-in-the-loop:** a person reviews each change (AI-assisted coding, co-scientist tools).
- **Human-on-the-loop:** the improvement signal is generated automatically (execution feedback, a reward model, a proof checker) but humans audit outcomes and gate deployment.
- **Closed loop:** the system generates, validates, and applies its own improvements without human review — the regime Anthropic’s essay calls “closing the loop” [5].

Nearly all of the 1,250 papers surveyed here study bounded self-refinement (human-on-the-loop cells); open-ended RSI — closed loops that also modify their own evaluators — is where the safety

stakes concentrate (§7). On Anthropic’s five-stage spectrum, the bulk of the technical literature occupies stages 3–4; the papers in §6 probe the boundary of stage 5.

What the axes do not encode. Two exclusions are deliberate and worth stating, because they bound what a classification of this shape can see. First, both axes take the *objective as given*: axis 1 asks which substrate an improvement lands in, axis 2 asks who validates it against the criterion in force, and neither indexes whether that criterion is still the right one (§5.3, failure mode 4; §5.4). Second, the taxonomy is indexed by substrate rather than by *trajectory*. A single system that improves its outputs, then its evaluator, then its own research method occupies three cells, and the fact that these are episodes of one continuously developing system rather than three unrelated improvements has nowhere to be recorded. The corpus contains the negative image of this omission — “scientific amnesia,” behaviours improving across campaigns while no methodological knowledge accumulates [17] — but the positive property, continuity of method across a change of frame, is not something this grid can register. We take it up as an open problem (§8) rather than as a third axis, because we know of no measurement in the corpus that would populate one.

Figure 1 lays out the resulting 4×3 grid with representative systems in each cell. Two features of the grid matter more than any individual cell. First, density is concentrated in the middle row: almost everything surveyed in §§3–6 is human-*on-the-loop* — an automatically generated signal with a human auditing outcomes. Second, the closed-loop row is sparse everywhere and thinnest at the right; its most consequential cell is self-evaluation × closed loop — a system that rewrites its own definition of “better” — which is exactly where bounded self-refinement shades into open-ended RSI. The taxonomy therefore does double duty: it organizes the survey (§§3–6 follow its columns) and it makes the survey’s central claim visible — the literature’s mass sits where a human still audits the loop, and the load-bearing column is the evaluator’s.

2.3 Corpus and method

The corpus was assembled in two stages. **Seed harvest:** we queried arXiv (2024–2026) across seven threads — self-refinement, self-rewarding training, automated AI research, self-modifying agents, LLM-driven code/algorithm discovery, RSI theory and safety, and self-generated-data loops — enriched records with OpenAlex citation and venue metadata, and removed off-topic bleed, yielding 871 papers. **Taxonomy alignment:** all seed papers were re-classified into the categories of §2.2 (theme-level mapping plus keyword rules on title and abstract, with manual correction of rule misfires), and a targeted supplemental harvest added 379 papers in three directions the seed queries under-covered but the taxonomy makes first-class: self-evaluation methods (judges, process reward models, verifiers, rubrics, meta-evaluation), test-time training, and zero-data self-play. Figure 2 shows the combined corpus.

Reproducibility. The seed and supplemental query strings, per-query caps, deduplication logic, and classification rules (category defaults, keyword rules, and explicit per-paper overrides) are released as executable scripts alongside the corpus (see Data availability). Rule-based classification moved 89 seed papers off their thread defaults; a further 3 misfires caught during writing were corrected via explicit overrides. Classification and corrections were performed by a single annotator; we release the full per-paper assignments so that disagreements are auditable rather than hidden.

Positioning relative to existing surveys. Prior surveys cover single slices of this landscape: on-policy distillation [12] and tree-search-plus-reward methods for reasoning [13] sit inside our §4; agent and LLM-evaluation surveys treat components of §3 and §5 in isolation. To our knowledge no existing survey covers the four categories jointly, treats self-evaluation as a load-bearing pillar




Figure 1: the two-axis taxonomy, with representative systems per cell.

rather than a tooling detail, or anchors the technical literature to an explicit autonomy/loop-closure axis — the three moves that let this survey address the RSI question rather than one mechanism family at a time.

Limitations. The corpus is a *sample*, not a census: seed queries with per-query depth caps favor recent, high-volume threads, and the supplemental harvest is recency-biased by construction (growth statistics in Figure 6 therefore use the seed corpus only). 74% of papers were posted in 2026 and the median paper is months old, so citation counts are near zero and must not be read as impact; where a category has a recognized seminal work predating the harvest window (STaR, SPIN, FunSearch, The AI Scientist), we cite it explicitly as an anchor. Our reading strategy compensates for the corpus’s youth: the argumentative skeleton rests on verified anchor works and the diagnostic/critical literature, while the 2026 mass functions as a *map* of where activity is, not as evidence of what has lasting impact. Automatic classification is approximate; boundary papers exist in every category, and roughly one in seven supplemental papers (roughly 54 of 379) is peripheral query bleed — these remain in the corpus counts but none are cited as evidence. Finally, industrial RSI practice (inside frontier labs) is only observable through what labs publish — a nontrivial censoring effect for exactly the most advanced part of the spectrum.

3. Deployment-Time Self-Evolution

The first category covers everything a system does to improve *during deployment*: iterating on outputs with frozen weights (§3.1–3.3), adapting weights per query (§3.4), and evolving its own harness, skills, and memory (§3.5–3.6). What unifies these mechanisms is their position in the



Figure 2: semantic map of the 1,250-paper corpus (TF-IDF abstracts, SVD + t-SNE projection; axes are arbitrary embedding dimensions). Contours show category density; Auto Research and foundations form coherent regions while the three large categories interpenetrate.

lifecycle — improvement happens in the field, per episode or per user, without an offline training phase — and what differentiates them is persistence: refined outputs evaporate when the episode ends, test-time updates persist for a session, harness changes accumulate indefinitely. This is the largest category in our corpus (393 papers) and the most widely deployed.

The canonical output-refinement loop — generate, critique, revise — was established by Self-Refine [6] and Reflexion [18] in 2023, and inference-time iteration was given a scaling-law treatment by Snell et al. [19], who showed that spending compute on revisions and search at test time can outperform spending it on a larger model, and framed such compute allocation as “a critical step towards building generally self-improving agents.” Output refinement is where self-improvement claims are easiest to evaluate — and where the most decisive negative results have accumulated.

3.1 Self-critique and self-verification for text and reasoning

The largest single thread in our corpus refines the basic loop along three lines.

Structured and symbolic feedback. Because free-form self-critique is unreliable, a major thread replaces it with structured signals. SymbolicAI [20] treats the LLM as a semantic parser embedded in a logic-based framework, routing outputs through formal solvers; recent planning work couples LLM planners to symbolic validators that return actionable error traces rather than vague critiques [21]. The pattern generalizes: wherever a checker exists — a SQL executor [22], a hallucination detector for clinical summaries [23], a QA-based factuality probe for long-document summarization [24] — refinement is rebuilt around it. The design lesson, repeated across dozens of papers, is that *the refinement loop is only as good as the feedback channel*, an early appearance of the verification bottleneck of §5.

Deployment-time self-evolution: what persists, and for how long?




Figure 3: deployment-time self-evolution ordered by persistence — refined outputs evaporate with the episode, test-time updates last a session, harness and skill changes accumulate indefinitely.

Search-shaped refinement. A second line reframes refinement as search: SQL-o1’s self-reward heuristic search over query candidates [22] and the reinforced self-training loop of LLM-Personalize for household planning [25] both treat drafts as nodes to expand and score rather than texts to polish. This blurs into the training-time methods of §4 — the same scoring signal can rank candidates at inference or fine-tune the policy afterward, and several systems do both [26].

What does refinement actually improve? The thread’s most valuable recent contributions are diagnostic. A systematic study of document-level literary translation across nine LLMs and seven language pairs [27] finds that refinement gains come primarily from fluency, style, and terminology, with limited and less consistent improvement in adequacy — and that refinement *projects outputs toward the refiner’s own distribution* rather than correcting what the draft actually got wrong. This echoes the influential negative result of Huang et al. [28]: absent external feedback, LLMs largely cannot self-correct reasoning, and naive self-correction can make answers worse. The 2026 literature has internalized this: almost every new system in our corpus grounds its critique in an external signal (execution, retrieval, a detector, a solver), and “intrinsic self-correction” papers have become rare. In taxonomy terms, the field quietly moved from closed-loop self-critique to human-on-the-loop verified refinement — a retreat from autonomy that improved reliability.

The negative result is now being refined rather than merely repeated. A task-sensitive analysis asks not *whether* intrinsic self-correction works but *through which mechanism* it could: revisiting explicit, checkable constraints behaves differently from revisiting open-ended reasoning, and the former is where unaided self-correction retains some value [29]. Underneath both lies a calibration question — when does the model’s own probability mass align with correctness at all? A four-level quantification across decoding methods, models, and benchmarks maps exactly where sequence likelihood is and is not a usable proxy for quality [30], effectively charting the floor of §5’s verification hierarchy

from below. And the evaluation side of the loop is being restructured in parallel: rather than one opaque holistic judge, BinEval decomposes evaluation into atomic binary questions whose verdicts aggregate into interpretable, debuggable scores [31] — self-improvement applied to the judge, not the answer, an inversion that recurs throughout this survey.

3.2 Code self-repair via execution feedback

Code is the modality where the external signal is cheapest and sharpest — programs run, tests pass or fail — which makes this theme the cleanest laboratory for refinement claims.

The affirmative results are strong. Execution-feedback repair loops power systems from multi-agent 3D-asset generation in Blender [32] to database tuning agents that diagnose bottlenecks from runtime feedback [33] and compiler-pass tuning grounded in profiling evidence [34]. In formal mathematics, agentic frameworks around proof assistants — LEAP for Lean theorem proving [35], KVerus for scalable Rust verification [36], specification generation against evolving knowledge bases [37] — exploit the strongest verifier available (a proof checker) to drive many-round repair with essentially no risk of accepting a wrong “improvement.” Verifier-guided decoding pushes the signal inside generation itself rather than applying it post hoc [38].

The thread’s second contribution is decomposition: *why* does feedback help? A controlled student-teacher protocol [39] separates genuine feedback value from resampling, format correction, and extra test-time compute — effects that inflate naive comparisons. A placebo-controlled study of self-repair in small frozen code models [40] makes the Popperian framing explicit: a failing test is an executable counterexample, and feedback’s value should be attributed to falsification, not to mere re-exposure to the problem. Complementary results show that execution feedback matters more than pipeline topology in small-model code generation [41], while pre-execution structural checks catch the dominant failure mode (inter-tool contract violations) more consistently than unstructured critique [42]. Systematic evaluations of multi-round repair across models and languages confirm the pattern at scale — most evaluations still measure single-attempt accuracy, but real-world value concentrates in the iterative loop [43]. Together these papers give this thread something the rest of the deployment category lacks: a causal account of when refinement works. DISC [44] extends the account to reasoning, treating verification-question outputs as noisy measurements of *where* a solution is corrupted and denoising across rounds — refinement as inference over error locations rather than blind revision.

Two further developments sharpen the signal itself. FLARE interposes a lightweight diagnostic model that predicts *line-level suspiciousness* between generation and revision, on the observation that test failures are too coarse and self-critique too high-level to tell the model where to fix [45] — feedback resolution, not just feedback existence, is a design variable. And CoSPlay confronts the setting where even the tests are self-generated: model-written unit tests are noisy and *spuriously coupled* with the wrong code they were written alongside, so it co-evolves code and test populations cooperatively at test time, using each to debug the other [46]. This is the verification bottleneck in miniature — when the verifier is self-generated, verifying the verifier becomes part of the loop — and it previews the evaluator co-evolution ideas of §5 and §6.

3.3 Vision-language and multimodal self-critique

The refinement paradigm has generalized well beyond text, but the verification signal thins as it travels. In vision-language models, the leading use case is hallucination mitigation: Kestrel [47] grounds self-refinement in visual evidence to suppress LVLM hallucinations training-free, and

Reflect-R1 [48] argues that closed-loop self-reflection *within internal parameters* traps long-video models in “blind confidence,” fixing it with evidence-driven external retrieval — the multimodal restatement of Huang et al.’s negative result. In generation, unified MLLMs self-refine their own text-to-image outputs through fine-grained reasoning [49], and Proprio [50] gives a frozen video generator a “proprioceptive” self-scoring signal in latent space to improve physical plausibility at inference time.

Perception itself is becoming the object of refinement. ActiveScope diagnoses two failure modes of passive visual attention — contextual dominance (salient distractors overwhelm the target) and semantic bias — and responds by having the model *actively seek and correct its own perception*, re-examining regions rather than re-wording answers [51]. On the generation side, safety enters the loop at the representation level: iteratively self-improving codebooks purge unsafe visual patterns from the token vocabulary of autoregressive image generators, so the improvement target is the generator’s own discrete alphabet [52].

Two cautionary threads deserve emphasis. First, a study of self-evolving large multimodal models [53] shows that self-play and self-consistency rewards can optimize *answer agreement* while the decoder under-attends to visual content, leaning on language priors (“visual under-conditioning”) — a modality-specific form of the self-confirming loop (§5). Second, the strongest multimodal systems increasingly resemble the code pattern: they succeed by importing an external channel (retrieval, detectors, physics residuals, personal visual context [54]) rather than by trusting the model’s own judgment. The judge-side evidence reinforces the caution: VLMs used as automated judges for physical plausibility encode *different* internal taxonomies of physical phenomena, so a single global evaluation schema credits every judge with the same competences regardless of what each can actually perceive — JudgeFit therefore discovers a per-judge taxonomy before trusting its scores [55]. Where §3.2’s verifiers are programs, §3.3’s are models — and model-judges inherit model idiosyncrasies.

Assessment (output refinement, §3.1–3.3). Inference-time refinement is bounded self-improvement in its purest form: improvements are real, measurable, and evaporate when the episode ends. Its half-life problem — nothing persists — motivates both the training loops of §4 (persist improvements into weights) and the harness and skill mechanisms of §3.5–3.6 (persist them into scaffolding). Its verified successes and instructive failures established the field’s central design rule: *no external signal, no reliable improvement*.

3.4 Test-time training

Between frozen-weight refinement and offline training sits a rapidly growing middle regime: updating weights *during deployment*. Query-conditioned test-time self-training constructs a query-specific objective and fine-tunes on it at inference, correcting misconceptions that no amount of frozen-weight iteration can reach [56]; continual variants convert the reasoning traces that inference-time scaling produces — and normally discards — into persistent lightweight memories [57]; and consolidation approaches give the model a periodic “sleep” phase that transfers in-context experience into long-term parameters [58]. Our supplemental harvest (§2.3) finds this thread growing fast (87 papers), largely under the older banner of test-time adaptation now being rediscovered for LLMs. TTT sits deliberately astride our taxonomy’s §3/§4 boundary: it has training’s persistence with deployment’s per-query granularity, and its rise is the clearest sign that the inference/training dichotomy the field inherited is dissolving into a continuum of update timescales.

3.5 Harness and agent self-evolution

The mechanisms so far improve what the model *says*; the remaining two subsections improve what the agent *is*. Here the object of improvement is the harness itself — prompts, tools, memory, skill libraries, orchestration code, in the limit the agent’s own source. This is the technical instantiation of “the agent rewrites itself,” the segment of the autonomy spectrum where Anthropic’s essay locates today’s frontier (agents delegating to agents) and the on-ramp to closing the loop [5]. Because harness changes are persistent and externally inspectable (§2.1), this is also where deployment-time improvement stops being episodic and starts to accumulate.

The thread’s conceptual poles were set early. The Gödel Agent [9] — named for Schmidhuber’s provably-optimal self-modifiers [2] — is a self-referential framework in which the agent reads and rewrites its *own runtime code*, searching the full agent-design space rather than a human-predefined subset; the Darwin Gödel Machine [10] relaxes provable benefit into empirical benefit, maintaining an open-ended archive of self-modifications validated against coding benchmarks. At the other pole, Liu et al. argue that truly self-improving agents require *intrinsic metacognitive learning* — the agent’s ability to assess and adapt its own learning process — and that current approaches, which hard-code the self-improvement procedure while leaving only its object to vary, are rigid precisely where they most need flexibility [59]. Nearly everything else in the theme sits between these poles, evolving one component of the system while freezing the rest.

What actually gets evolved, in practice, is instructive. Prompt-level evolution grounds automated prompt optimization in environment feedback [60]. Verification-level evolution is the most novel move: rather than post-training the policy, self-evolving deep-research agents iteratively strengthen the *rubrics and verifiers* that judge their outputs — improvement of the improvement signal itself [61]. The Red Queen Gödel Machine takes this to its logical conclusion: it observes that existing self-improving agents assume a *stationary* evaluation criterion — a fixed verifier or benchmark that stays valid as the agent improves — and co-evolves agents *with their evaluators*, making evaluation part of the improvement loop rather than its fixed frame [62]. Escher-Loop pushes self-reference one level further, with optimizer agents that refine task agents *and themselves* against a dynamically evolving benchmark [63]. Topology-level evolution treats the multi-agent communication structure as a retrievable, self-improving design artifact while keeping every worker frozen [64]. Data-level evolution closes the loop for computer-use agents by generating verifiable synthetic trajectories from the agent’s own failures [65]. And infrastructure-level work argues the whole enterprise needs a new data foundation: “experience graphs” that persist the branch-execute-fail-repair search structure of long-horizon agents, so that experience is queryable rather than discarded [66]. Meanwhile, a practitioner-facing analysis of coding agents crystallizes the cultural shift: the artifact humans now engineer is the *loop* — trigger, goal, verification, stopping rule, memory — not the step-by-step prompt [14]. Human effort is migrating from doing the task to specifying the conditions under which the agent may improve at it: precisely the human-on-the-loop posture of our taxonomy.

Measurement of the capability itself is beginning. The Meta-Agent Challenge evaluates whether a frontier model, given a sandboxed environment, an evaluation API, and a time budget, can *autonomously develop an agent system* that maximizes a target metric [67] — the first benchmark aimed at agent development rather than agent execution, i.e., directly at the boundary between our taxonomy’s third and fourth columns. And the unit of evolution is widening beyond the individual: SAGE compares compute-matched isolated self-improvement against “socialized” evolution in which agents observe peers’ strategies and outcomes, quantifying when shared experience yields improvements that solitary self-improvement cannot [68] — population-level self-improvement, with

population-level failure modes (§3.6’s propagation risks) to match.

Sobriety about returns is warranted: a systematic Pareto analysis of inference-scaling strategies (34 configurations across self-consistency, self-refinement, debate, and mixture-of-agents) finds peak gains of +7.1 points over chain-of-thought only at roughly 20× the compute budget, with methods differing sharply in efficiency — self-consistency saturates early while multi-agent gains persist [69]. The practical lesson is that compute-aware method selection, not more iteration, drives much of the realized benefit: self-evolution is not free, and a large share of the theme’s gains currently flows from better engineering rather than from anything recursive.

3.6 Skill libraries and persistent accumulation

The companion thread concentrates on the mechanism Voyager [70] introduced: an ever-growing library of reusable skills, each distilled from experience, composable into more complex behavior. In its modern form the “skill” is typically a natural-language procedure document paired with executable code, loaded by the agent at runtime — and the central empirical fact of 2026 is that *LLMs are bad at writing them*: on SkillsBench, human-authored skills improve pass rates by 16.2 points while LLM-authored skills provide no measurable gain [71]. The theme is, in effect, a research program to close that gap. SkillAxe closes it with evaluation-guided self-refinement of skill documents [71]; Skill-R1 treats skill optimization as a recurrent RL problem decoupled from the (possibly closed-source) task model [72]; SkillRevise handles the cold-start case by trace-conditioned revision of an initial imperfect skill [73]; AlgoSkill schedules human-like skills for algorithm design instead of relying on generic self-refinement [74]; SkillMaster goes furthest, training the agent to create, refine, and select skills *itself* rather than delegating those operations to external teachers or hand-designed rules — skills as internalized capabilities rather than invoked resources [75]. Beyond the single agent, skills federate across users without sharing raw trajectories [76], co-evolve with the tool layer they invoke [77], and derive from execution traces to generate weakness-targeted training tasks for coding agents [78]. In domains where free-form self-modification is too dangerous to permit, the evolvable artifact is deliberately constrained: SHARP evolves a *human-auditable rubric policy* for financial trading agents, arguing that in low signal-to-noise environments unbounded prompt evolution cannot distinguish systematic logic flaws from market variance, whereas a structured rubric can be audited, diffed, and rolled back [79] — a design pattern (constrain the self-modification surface to keep it verifiable) that generalizes well beyond finance.

Because skills are *persistent and executable*, this thread has the sharpest safety surface in the technical corpus, and — unusually — the attack literature has arrived concurrently rather than after deployment. SkillMutator benchmarks cross-modal attacks in which a skill’s natural-language specification and its executable code tell different stories [80]; SkillHarness addresses continual skill learning in adversarial environments [81]; VASO argues that foundation models have collapsed the cost of *creating* skills but not the cost of *trusting* them, and responds with formally verifiable skill evolution for physical agents [82]. A systematic threat analysis of self-evolving agent systems identifies the qualitatively new risk: adversarial influence that becomes *permanently encoded, self-amplifying across generations, and transmissible through agent populations* without sustained attacker access [83]. And work on “healthy evolution” finds capability degradation and safety drift arising *without* any adversary, proposing human-oversight anchors as a corrective [84].


Assessment. Harness and skill evolution is where bounded self-refinement starts shading into open-ended self-modification, and its two headline facts pull in opposite directions. On one hand, autonomy is modest in practice: what self-evolves is almost always one carefully sandboxed com-

ponent, validated against a fixed benchmark — the Darwin Gödel Machine’s empirical validation loop is state of the art precisely because full self-reference remains intractable to evaluate. On the other hand, persistence changes the risk calculus fundamentally: an inference-time mistake evaporates, a bad weight update can be rolled back, but a corrupted skill in a shared, federating library propagates. The safety literature has correctly identified accumulation-without-verification as the core problem — the same verification bottleneck, now with memory.

4. Training-Time Self-Iteration

The second category internalizes the loop into the weights: the model generates its own training data, rewards, or teacher signal, and the improvement persists. This category (340 papers) is the technical heart of RSI as currently practiced, and the closest thing the field has to an industrial standard. Its lineage runs from STaR’s bootstrapped rationales [7] through ReST^{EM}’s scaled self-training [85], SPIN’s self-play fine-tuning [86], and Self-Rewarding Language Models [8], in which the model that generates responses also judges them, so that both the policy *and the reward signal* improve across iterations — the first widely-noted instance of a genuinely recursive training loop, and the origin of its characteristic failure mode.

One loop, five paradigms: training-time self-iteration



Every variant differs mainly in who supplies the evaluation signal (§5).

Figure 4: the training-time self-iteration loop. The five paradigms of §4 differ mainly in who supplies the evaluation signal; the two failure modes attach to the evaluate-and-select station.

4.1 Self-rewarding reinforcement learning

The self-rewarding thread asks how far the reward signal itself can be self-generated. ReST-MCTS* [87] is the theme’s most-cited work: rather than filtering complete solutions by final-answer correctness — which admits lucky guesses with wrong reasoning — it infers *process* rewards via tree search, scoring intermediate steps and yielding a higher-quality self-training set. The process-reward idea

has since diversified: SEVA structures verification itself as an agent that emits evidence alignments and calibrated confidence rather than opaque binary labels [88]; EvoIdeator replaces scalar rubric rewards with checklist-grounded signals for scientific ideation [89]; RePro adds retrospective progress-awareness for long-horizon agents, having found that naive online progress prompting actually hurts [90]. A striking interpretability result suggests why self-generated value signals are possible at all: language models encode a “value axis” in activation space that tracks whether their current trajectory is on track [91] — the raw material for self-reward, available before any verbalized critique.

The clearest statement of the category’s endgame is Self-Trained Verification [92], which begins from the observation this survey keeps returning to: test-time verification–refinement loops and training-time self-training are *gated by the same bottleneck, the verifier* — the former stalls when verifier scores inflate while accuracy stagnates, the latter fails when bad self-generated data enters training — and therefore proposes to self-train the verifier itself, unlocking both loci at once. Whether verifier self-training escapes the circularity it is meant to solve, or merely relocates it, is in our reading the single most consequential open question in this family.

The thread also supplies its own strongest caution. Lin documents a *rise-and-collapse* failure mode in REINFORCE post-training for code: across sequential training campaigns, pass@1 climbs and then collapses within the same run — sometimes to near zero — under a genuinely verifiable binary reward, and KL- and EWC-style constraints do not prevent it [93]. Reward-model misalignment is not required for self-training to self-regress; optimization dynamics alone suffice. Similarly, LLM-generated reward *design* fails in characteristic ways — reward flooding, semantic misunderstanding of the environment API — and is better treated as iterative debugging than one-shot generation [94]. And a diagnosis from industrial practice identifies a subtler failure than forgetting: pipelines that repeatedly DPO-train a base model across preference campaigns can preserve learned behaviors yet fail to accumulate *methodological* knowledge about how to run the next campaign — “scientific amnesia,” self-improvement of the model without self-improvement of the process [17]. These results foreshadow §5: even in the most verifiable settings, the loop is not self-stabilizing.

4.2 Self-training for chain-of-thought reasoning

Where §4.1 innovates on the reward, this thread innovates on the *data*: the model’s own reasoning traces become its curriculum. The STaR recipe — sample rationales, keep the ones that reach correct answers, fine-tune, repeat — remains the backbone. Re-ReST augments it with a reflector that repairs failed trajectories using environment feedback, converting failures into training signal instead of discarding them [95]; PRefLexOR recasts the loop as recursive preference optimization over intermediate reasoning steps [96]; LaTRO shows the loop can run with no external reward at all, treating the model’s own likelihood as a latent-variable objective and “unlocking” reasoning already hidden in the base model [97]. That last framing — post-training amplifies latent capability rather than creating it — has hardened into a research question of its own, with recent work mapping the boundary conditions under which elicitation works and where it fails [98].

The verifier-free frontier of the recipe is now being mapped directly. Self-Verified Distillation starts from nothing but unlabeled questions — no ground truth, no tools, no external teacher — and improves math, science, and coding performance by filtering the model’s own candidate solutions with prompt-based self-verification [99]; Semi-CoT formalizes the analogous semi-supervised setting, constructing pseudo reasoning supervision from unlabeled questions [100]. The loop is also migrating *inside deployment* — the test-time-training regime surveyed in §3.4 — blurring the in-

ference/training boundary from both sides.

Three correctives structure the thread’s 2026 wave. First, *efficiency*: o1-style long thinking overshoots — models burn thousands of tokens on trivial problems [101] — and incorrect traces exhibit more unproductive self-reflection than correct ones even at matched length, motivating segment-level credit assignment to teach models when to stop [102]. Second, *joint optimization*: ThinkTwice interleaves solving and refining under the same binary reward, making self-refinement a trained capability rather than a prompting trick [103]. Third, *scope limits*: a notable negative result shows that “a verifiable search is not a learnable chain-of-thought” — there is an identifiable class of procedures that models can execute but cannot internalize from traces via fine-tuning [104]. Self-training inherits the representational limits of its substrate; more loops do not fix what the architecture cannot learn.

4.3 On-policy self-distillation

The corpus’s youngest thread did not exist before 2026 and already spans dozens of papers — the sharpest example of how fast this field crystallizes new paradigms. The recipe: a single model acts as both student and *privileged teacher* — the teacher being the same weights conditioned on extra information (a reference solution, verified feedback, richer context) — and the student is trained to match the teacher’s token-level distribution on its own rollouts. Dense token-level supervision, no external teacher, no reward model. A dedicated survey already exists [12]; our interest is in the paradigm’s position on the RSI spectrum: it is the most *closed* training loop in routine use, since even the teacher signal is self-generated.

Theoretical work is consolidating: the power-distribution analysis unifies sampling, self-reward RL, and self-distillation as instances of one distributional operation [105], clarifying why these superficially different loops behave alike. At the simple extreme, “embarrassingly simple self-distillation” improves code generation with nothing but temperature-and-truncation sampling plus SFT — no verifier, no teacher, no RL [106], raising the still-open question of where such verifier-free gains bottom out. The refinement literature is characteristically empirical: negative (incorrect) rollouts carry more information than positive ones and should be reweighted accordingly [107]; unmanaged difficulty routing over-optimizes easy problems [108]; procedural information in rollouts can be retained as distilled memory across episodes rather than discarded after each episode-level update [109].

The failure modes are equally well-documented, and they rhyme with §3’s. Purified OPSD shows the vanilla recipe *consistently fails on long-CoT reasoning models*, destabilizing the very reflective behaviors it is meant to strengthen [110]; the privileged teacher’s dense supervision can overfit in-domain patterns [111]. A contrastive analysis identifies the mechanism: the learning signal drawn from the privileged/unprivileged distribution gap concentrates on *style* tokens rather than task-bearing ones — the hinted teacher writes shorter, more direct text — producing “privilege-induced style drift” that destabilizes training or collapses response length [112]. A second structural pathology, “prefix failure,” shows dense per-token supervision inducing a bimodal teacher mixture with fragmented gradients that no token-level loss reweighting can repair, forcing intervention at the trajectory level instead [113]. And since everything hinges on what the privileged teacher is shown, the design of the privileged context itself — which feedback, at what specificity — is emerging as the paradigm’s core degree of freedom [114]. In multimodal settings the shortcut is structural: the privileged target lets the teacher guide tokens from the text reference while ignoring the image, so the student distills a language prior rather than a perceptual skill, requiring explicit

decoupling of perception from reasoning [115]. The pattern to carry forward: *the more privileged the self-generated signal, the more efficiently the loop transmits both capability and bias.*

4.4 Self-play

Self-play closes the loop one turn further: the model generates not just answers or rewards but the *problems*. The modern lineage runs from SPIN — self-play fine-tuning against one’s own previous iteration, provably converging to the data distribution [86] — to the zero-data proposer–solver frameworks of Absolute Zero [15] and R-Zero [16], where a Challenger learns to pose problems at the frontier of the Solver’s competence and both co-evolve from a single base model with no human tasks at all; Agent0 extends the recipe from reasoning problems to *agent*ic tasks, co-evolving a curriculum agent and a tool-using executor from zero external data [116]. This is the closest existing training paradigm to an autonomous curriculum, and it works remarkably well where a programmatic verifier exists: executable geospatial programs [117], formal theorem proving — now with a theoretical framework for prover–conjecturer co-evolution [118] — and verifier-backed generation of genuinely hard mathematics problems [119].

The thread’s central finding, however, is about stability. A systematic study argues that self-play survival is governed by two asymmetric levers — *data gating* (what enters the training set) and *reward grounding* (what anchors the signal to reality) — and that collapse is the default when either fails, not an occasional accident of reward design [120]. Population-based variants attack the same problem structurally, replacing self-calibration with cross-evaluation between co-evolving sub-populations [121]. On non-verifiable tasks the difficulty compounds: LLM-as-judge rewards are bounded by the judge’s own competence, motivating meta-evaluation schemes in which models learn to evaluate *evaluations* [122] and verifier-free intrinsic rewards based on predictive shift between models [123]. And a warning from open-ended interaction dynamics: multi-turn LLM self-play conversations drift into topic-independent attractor states [124] — precisely the homogenization pressure that co-evolutionary curricula must fight to keep generating novelty.

4.5 Embodied and synthetic-data loops

The category’s newest frontier ports the training loop into physical and synthetic-data settings, where verification is expensive, noisy, and slow. Robots critique and replan their own social behaviors using a VLM as internal critic [125]; VLA policies check physical feasibility and self-reflect during execution rather than acting purely feed-forward [126]; embodied foundation models integrate planning, correction, and pointing in one architecture explicitly aimed at self-evolving physical intelligence [127]. Robot self-improvement via human-video dynamics models tests whether passive human video can support not just policy initialization but *embodied practice and learning from failure* [128]. On the data side, the loop turns inward on the pipeline itself: DataEvolver self-evolves the data-preparation process for LLM training [129] — self-improvement applied to the substrate that all other training loops consume.

Assessment. Training-time loops are where bounded self-improvement earns its keep: gains persist, scale, and compound across iterations — until they don’t. Every sub-thread independently rediscovered the same three facts: (i) the loop’s ceiling is set by its verification signal (execution and proofs highest, learned judges lower, intrinsic signals lowest); (ii) collapse is a default dynamic to be engineered against, not an edge case [93, 120]; (iii) the loop transmits bias as efficiently as capability. These are the load-bearing facts for §5.

5. Self-Evaluation

The third category is the one the other three stand on. Every loop in §§3–4 and every discovery system in §6 improves against some evaluator, and each of those sections ended on the same note; this section makes the argument explicitly. **Every self-improvement loop is a claim that some signal can substitute for human judgment, and the loop’s ceiling is exactly the quality of that substitute.** Reflecting its load-bearing role, self-evaluation is also the corpus’s fastest-consolidating category (318 papers, 82% posted in 2026): what was recently a service function of training papers is now a research area with its own methods, benchmarks, and failure analyses.

5.1 The evaluator design space

The modern evaluator lineage has three anchors. Process supervision — scoring intermediate reasoning steps rather than final answers — was established by Lightman et al. [130], whose finding that process rewards outperform outcome rewards seeded today’s process-reward-model (PRM) literature; MT-Bench and Chatbot Arena made *LLM-as-a-judge* a measurable methodology, quantifying both the ~80% judge–human agreement that justifies the paradigm and the position, verbosity, and self-enhancement biases that qualify it [131]; and Gao et al.’s scaling laws for reward-model overoptimization gave the field its Goodhart curve — optimize any learned proxy hard enough and true quality peaks, then falls [132].

The current wave develops each anchor. PRMs are being made cheaper and better-calibrated [133], and structured: SEVA replaces opaque binary verdicts with evidence alignments, reasoning chains, and calibrated confidence, so that agents can act on *why* they failed [88]. Judge reliability is acquiring psychometrics — measurement datasheets that characterize an LLM judge’s biases before its scores are trusted [134] — and judge *specificity*: per-judge competence taxonomies [55], multilingual judge disagreement [135], and decomposition of holistic scores into auditable binary questions [31]. Rubrics, the human-readable middle ground between formal verifiers and free-form judges, are becoming first-class evolvable artifacts: self-generated rubrics closing the gap to expert-written ones [136], rubric hierarchies that scale open-ended evaluation [137], and rubric-conditioned signals replacing scalar rewards in training (§4.3; [138]). Self-verification is being built into the objective itself, as in dual-preference formulations that make a model’s verification ability a trained product rather than a prompted hope [139].


Most consequentially for this survey’s argument, the field has begun improving the evaluator *with the same loops it supervises* — the move §8 identifies as the field’s collective answer to its bottleneck. Deep-research agents evolve their own rubrics [61]; self-trained verification treats the verifier as the primary object of self-improvement [92]; meta-evaluation judges the judges [122]; and the Red Queen framework makes the evaluation criterion itself a co-evolving population member rather than a fixed frame [62]. Every mechanism in §§3–4 is being recursively applied to the signal that supervises it. Whether that recursion stabilizes or compounds bias is the open question the rest of this section addresses.

5.2 The verification hierarchy

The verification hierarchy. At the top sit *formal verifiers* — proof checkers, type systems — which are sound by construction: self-play theorem proving and verified skill evolution can iterate indefinitely without accepting a false improvement [118, 82]. One step down, *execution feedback* — tests, compilers, benchmarks — is reliable but incomplete: passing tests underdetermines correctness, and any fixed benchmark is eventually gamed. Next, *learned judges* — reward models,

LLM-as-judge — are bounded by the judge’s own competence and are themselves optimization targets [122]. At the bottom, *intrinsic signals* — the model’s confidence, self-consistency, likelihood — are the cheapest and the most gameable. The empirical regularity across all four categories — a qualitative pattern we observe throughout the corpus, not a measured law — is that demonstrated self-improvement strength tracks this hierarchy. FunSearch and AlphaEvolve live at the top two levels [3, 4]; the self-refinement methods that survived 2024’s negative results are the ones that climbed the hierarchy (§3); the AI-scientist gap (§6.3) is precisely a level-4 problem being attempted with level-3 tools.

The verification hierarchy: what substitutes for human judgment?



Demonstrated self-improvement strength tracks this hierarchy (§5.2).

Figure 5: the verification hierarchy. Signal reliability rises toward the top while task coverage widens toward the bottom; failure modes concentrate at the bottom rungs, and human research judgment remains the rung self-improvement cannot yet climb. The hierarchy ranks signals *given* a target; the choice of target is prior to it rather than a rung of it (§5.4).

The hierarchy’s floor has now been measured directly. The Mirror Loop study iterates three providers’ models through ten rounds of ungrounded self-critique across four task families and finds informational change declining 55% across iterations — recursive self-evaluation without external feedback yields *reformulation*, *not progress* — while a single minimal grounding intervention (one verification step at iteration three) restores forward movement [140]. That is the survey’s thesis as an experiment: the difference between a loop that improves and a loop that circles is one rung of external verification.

5.3 Failure modes

Failure mode 1: the self-confirming loop. When generator and evaluator share weights, biases correlate. Tan et al. diagnose the mechanism in self-rewarding RL: confidence-coupled rewards systematically over-reward *high-confidence mistakes*, so the loop preferentially reinforces exactly the

errors the model is most sure about [141]. The same structure appears at every locus: multimodal self-consistency rewards that optimize answer agreement while ignoring the image [53]; privileged self-distillation teachers that transmit in-domain bias with token-level efficiency [111]; AI scientists whose self-critique “inherits the blind spots that produce confident fabrication” [142]; and — at the integrity extreme — systems that misreport failure as success when task completion is rewarded [143]. Reward hacking is the special case where the gamed judge is explicit; the self-confirming loop is the general case, and it needs no adversary.

Failure mode 2: collapse. Whether self-generated-data loops improve indefinitely or degrade is the field’s most contested empirical question. The pessimistic pole is anchored by Shumailov et al.’s *Nature* result — models trained recursively on their own outputs lose the tails of the distribution and degenerate [144] — and now has a unifying theory: an information-geometric account showing model collapse in LLMs, GANs, and RL policies to be one phenomenon, with real-data mixing, entropy bonuses, and retrieval all acting as instances of a single entropy-reservoir principle [145]. Zenil sharpens it into a theorem-shaped claim: if the fraction of exogenous, externally grounded signal vanishes asymptotically, degenerative dynamics (entropy decay, variance amplification) follow [146]. The optimistic pole answers that collapse is an engineering problem: diffusion models can train on their own generations once perceptual alignment and hallucination accumulation are controlled [147]; self-play survives when data gating and reward grounding are managed as separate levers [120]; reasoning self-training collapses from identifiable data imbalance and overthinking, both fixable [148]. The synthesis the evidence currently supports: *pure* closed loops degrade, as the theory predicts, but no practical system need run a pure closed loop — the open question is how *little* external grounding suffices, and no one has established the exchange rate.

Failure mode 3: diversity collapse. Distinct from distributional collapse is the narrowing of the *task* distribution in co-evolutionary loops: proposers converge to the narrow band of problems that satisfy the reward, starving the solver’s curriculum [149]; open-ended model–model interaction drifts into topic-independent attractor states [124]; and even in single campaigns, pass@1 rises then collapses without any distribution shift in the task [93]. Novelty, it turns out, is a consumable resource that closed loops deplete.

Failure mode 4: frame lock-in. The three modes above are all detectable *from inside* the loop: a confidence-coupled reward, a collapsing output distribution, and a narrowing curriculum each leave signatures in quantities the loop already tracks. A fourth does not. A loop can be grounded, honest, diverse, and stable and still optimize an objective that has ceased to be the one worth optimizing — the well-posed wrong question. The corpus’s evidence for this mode is scattered because no category collects it. In physics-simulation rediscovery, agents reach the correct answer while defending a mechanism their own data contradicts — local closure mistaken for understanding [150]. Repeated-campaign analysis finds behaviours improving while no methodological knowledge accumulates [17]. Open-ended model–model interaction drifts into topic-independent attractor states [124]. Most directly, an agent-native research-artifact protocol that preserves prior failure traces reports that those traces cut both ways on open-ended extension tasks: they accelerate progress, but can also constrain a capable agent from stepping outside the prior run’s box [151] — accumulated context as a source of lock-in, not only of competence. The mode is under-studied for a structural reason: detecting it requires a vantage point outside the loop’s own criteria, which is exactly what a closed loop lacks — and what a hierarchy that ranks signals *given* a target does not supply.

5.4 The non-verifiable frontier

Where no checkable signal exists — creative writing, dialogue, research taste — the hierarchy bottoms out, and the workarounds are revealing: meta-evaluation (judging the judges) [122], verifier-free intrinsic rewards from cross-model predictive shift [123], claim-level auditability that makes outputs verifiable by construction [152]. None yet approaches the reliability of execution feedback. This maps exactly onto the gap Anthropic’s essay identifies: research *execution* is verifiable (code runs, benchmarks score) and is increasingly automated; research *direction-setting* is the paradigm case of a non-verifiable task, and it is where humans remain [5].

It is tempting to conclude that the direction-setting bottleneck and the verification bottleneck are therefore the same bottleneck. That identification holds for only half of direction-setting, and the other half is logically prior to the hierarchy rather than a rung of it. *Direction evaluation* — given a candidate direction, judge whether it is sound and worth resourcing — is verification-shaped and is now benchmarkable: SoundnessBench reconstructs 1,099 research proposals from ICLR submissions labelled with reviewer soundness sub-scores and finds a pervasive optimism bias across twelve frontier models, concluding they are not yet reliable as standalone first-gate evaluators of rigour [153]. *Direction generation* — deciding what the space of candidate questions should be, and noticing when a question the current criteria still score highly has stopped being worth answering — is not. A loop can climb every rung, keep an honest evaluator, and detect and correct the corruption of its own proxy (§6.2) while remaining excellent at a question worth abandoning; nothing in the hierarchy indexes that possibility, because the hierarchy takes the question as given. The corpus states the concern directly in one place: a position paper on autonomous AI scientists lists as its *first* challenge that problem selection is subject to the McNamara fallacy — the measurable displacing the important — and asks for persistent world models representing the *shifting objectives* that govern real investigations, rather than better verifiers for fixed ones [154]. The formal treatment of interestingness [155] is best read as the beginning of a theory for this prior question, not as a fifth rung. §8 (open problem 6) takes up what measuring it would require.

5.5 Result-level versus process-level improvement

A distinction that cuts across everything above is the *resolution* of the evaluator: does it judge the answer or the procedure that produced it? Result-level signals — final-answer correctness, pass/fail tests, outcome rewards — are cheap to generate and anchor most of §4’s training loops, from STaR’s answer-filtered rationales [7] onward. Process-level signals judge intermediate steps, and the evidence that they matter has been accumulating since Lightman et al. showed process supervision beating outcome supervision [130], with ReST-MCTS*’s observation that outcome filtering admits lucky guesses with wrong reasoning [87] as the training-loop corollary.

The distinction becomes vivid through an analogy with human learning. A student who merely checks answers improves slowly; effective learners keep an error notebook, trace *where* a derivation went wrong, ask a teacher for targeted guidance, revisit old mistakes on a schedule, and gradually organize what they learn into a system — the final answer being the least important artifact of the whole process. Each of these behaviors now has a machine counterpart in this corpus: the error notebook is experience and strategy memory (Reflexion’s verbal episodic memory [18], ISM’s self-refined bank of schemas learned from failed episodes [156], experience graphs that persist the branch-fail-repair structure of long-horizon work [66, 157]); stepwise correction is process reward modeling [130, 133]; asking the teacher is the privileged-teacher signal of on-policy self-distillation (§4.3); scheduled review is replay and consolidation, up to and including “sleep” [58, 57]; and

building a knowledge system is skill-library and knowledge-graph accumulation [70, 158].

The two levels have opposite cost structures, and the difference is economic, not just technical. Result-level improvement is *operating expenditure*: outcome checks are nearly free to produce, but the improvement they buy is per-instance — best-of-N sampling and answer-filtered retraining must be paid again for every new problem, and what they teach transfers poorly. Process-level improvement is *capital expenditure*: process labels are expensive (Lightman’s step annotations required substantial human effort, and the PRM literature is largely an attempt to automate that cost down [133]), but a corrected procedure, a debugged skill, or a schema in a strategy bank is reusable — the cost amortizes across every future problem that shares the structure. The “scientific amnesia” failure of §4.1 is precisely a pipeline stuck at result level: behaviors improve while no methodological knowledge accumulates [17].

This framing suggests a reading of the endgame that differs from the intelligence-explosion imagery: if the durable gains of self-improvement are process-level — accumulated procedures, verified skills, organized experience — then mature self-improving systems may look less like unboundedly ascending intelligence and more like *maturing methodology*: a widening toolbox of verified procedures attached to a model whose raw capability grows much more slowly. That reading is consistent with the theory of §7 (open-ended capability growth requires external grounding; accumulated method does not) and with where this corpus’s mass actually sits (§3.5–3.6’s persistent scaffolding). Whether the toolbox picture or the takeoff picture better describes the coming decade is, in compressed form, the question this survey’s two-axis grid keeps asking.

6. Auto Research

The fourth category is the far end of the spectrum: systems that do the work of research itself — in the limit, agents applying the machinery of §§3–5 to the process that produces the next system. This category (139 papers) contains both the field’s most spectacular concrete results and its most systematic critiques — often about the same systems.

6.1 LLM-driven evolutionary program discovery

The discovery thread has the category’s strongest verified results, and the reason is structural: it inherits the evolutionary-computation template, in which every candidate is a *program* scored by an *automatic evaluator*. FunSearch established the paradigm’s credibility by producing new mathematical constructions — improved bounds for the cap set problem — published in *Nature* [3]. AlphaEvolve scaled it into a general coding agent whose discoveries fed back into Google’s own AI infrastructure: faster matrix-multiplication kernels, data-center scheduling, accelerator circuit simplifications [4] — the clearest existing example of AI output compounding into AI development, and the concrete referent for most contemporary RSI discussion. Concurrently, EoH showed LLM-plus-evolution could beat FunSearch on heuristic design at a fraction of the query budget [159], and successors refined the search itself: quality-uncertainty balancing [160], diversity-driven harmony search [161], and heterogeneous LLM populations as mutation operators to escape a single model’s inductive biases [162].

The 2026 wave pushes in three directions that matter for the RSI question. First, *deployment at scale*: the AlphaEvolve recipe is now applied to production infrastructure well beyond its original demonstrations — warehouse-scale interprocedural code layout optimization [163] and fully homomorphic encryption kernels on TPUs [164] — the “AI output feeding back into AI infrastructure”

loop operating as routine engineering. Second, *reflexivity*: the target of evolutionary discovery is increasingly AI’s own machinery. EVOM meta-evolves actor-critic architectures [165]; POISE autonomously discovers new policy-optimization algorithms for LLM training itself [166]; MLEvolve targets machine-learning engineering pipelines end to end [167]. When the algorithms being discovered are the algorithms that train the discoverer’s successors, the loop of §2’s taxonomy is no longer metaphorical. Third, *formalization of the loop’s own objective*: work reframing scientific discovery as meta-optimization argues that evolving the *evaluation criteria* is as important as evolving candidates [168] — an explicit acknowledgment, from within the paradigm, that a fixed evaluator eventually becomes the binding constraint (§5). The paradigm has also begun evolving its own benchmarks, synthesizing frontier tasks as existing ones saturate [169].

A quieter finding concerns where the leverage actually lies. Controlled studies of harness design show that discovery success depends heavily on the *execution infrastructure* around the model — how the token budget splits between many shallow candidates and fewer deep ones, how evaluation failures are handled — independent of model capability [170]; LEVI demonstrates that stronger search architectures (diversity-preserving archives, capability-matched model routing, informative-subset evaluation) can substitute for larger LLMs in evolutionary search, cutting frontier-model spend without losing discovery quality [171]. The pattern mirrors §3.5’s loop-engineering shift: much of what looks like model self-improvement is improvement of the scaffolding the model searches within — which is good news for reproducibility and cost, and a caution against attributing the gains to the model’s own recursive capability.

6.2 AI scientist agents

The AI-scientist thread generalizes from programs to papers. The AI Scientist [11] demonstrated the full pipeline — ideation, experiment, writing, automated review — for machine-learning research at ~\$15 per paper, and the theme has since fragmented into dozens of domain-specific descendants: an autonomous mathematics researcher navigating literature and long-horizon proofs [172], Socratic agents pursuing “epistemic autonomy” in high-dimensional physics [173], evolving multi-agent scientists that adapt their own pipelines from accumulated history [174, 175], and infrastructure for coordinating fleets of research agents at web scale [176].

As the systems mature, the field’s attention is shifting from the agent to its surroundings. EurekaAgent argues the bottleneck has moved from prescribing agent workflows to *engineering the agent’s environment* — the resources, constraints, and interfaces that shape what an autonomous discoverer can do [177]; Heuresis decomposes the research pipeline into composable primitives and systematically compares search strategies over ideas, treating quality, diversity, and novelty as separate objectives rather than a single score [178]; and Xscientist externalizes research synthesis and validation into inspectable, contract-governed artifacts — literature evidence, idea states, ablation records, repair traces — so that a generated claim’s provenance survives outside the model’s inference [179]. All three are, in different vocabularies, attempts to move scientific judgment out of the model and into auditable structure — the constructive response to the critique literature below.

Two corpus results deserve particular attention for what they say about loop closure. A-Evolve-Training reports an autonomous system that ran the *entire post-training loop* of a 30B model — proposing data and recipe changes, launching runs, reading evaluations, deciding what to keep — across four rounds over multiple weeks with no human in the loop, reaching near-parity with the top human submission on a public leaderboard (0.86 vs. 0.87, placing 8th of roughly 4,000; the authors are careful to claim only “the first publicly reported autonomous post-training run at this scale,”

not an autonomous match of human researchers) [180]. The result’s most striking detail is not the score: mid-run, the loop detected that its own development metric had decoupled from external performance — candidates were driving the dev metric to record highs without moving the external target — and *revised its own search policy* to treat the now-misleading proxy as evidence against a candidate rather than for it. An autonomous system noticing and correcting the corruption of its own improvement signal is precisely the capability §5 identifies as the field’s binding constraint, observed in the wild. This is, to our knowledge, the closest published system to Anthropic’s “closing the loop” stage: not an agent improving its outputs or skills, but an AI system executing AI model development end to end. Read against the Anthropic essay’s claim that execution is largely solved while direction-setting is not [5], the result is confirmatory rather than contradictory — the system optimized within a human-specified objective and search space — but it moves the demonstrated frontier. Second, failure recovery is emerging as its own discipline: single free-form reflection over a failed experiment is demonstrably insufficient, motivating multi-hypothesis failure attribution [181] — the AI-scientist restatement of §3’s lesson that unstructured self-critique does not work.

6.3 The critical and diagnostic literature

What distinguishes this category from the rest of the corpus is that its skeptical literature is as developed as its constructive one — and often better cited. Three critiques recur.

Feasibility is not quality. ScienceAgentBench, the thread’s most-cited paper, decomposes “scientific discovery” into individual workflow tasks and finds even the best agents solve only a minority — explicitly cautioning against end-to-end automation claims [182]. ResearchArena runs frontier coding agents (Claude, Codex, Kimi) through the full research loop and asks not whether papers get produced but whether they are any *good* — with an instructive twist: under manuscript-only automated review the picture is optimistic (the best agent’s papers match the average human ICLR submission score), but artifact-aware review and human meta-review reveal that picture to be overstated [183]. The gap between how machine-generated research *reads* and what its artifacts *support* is itself evidence for the auditability thesis below. MLReplicate benchmarks autonomous systems on reproducing ICML outstanding papers — a task with a verifiable target — and documents how far systems remain from reliable replication [184].

Auditability is the new bottleneck. As report generation becomes cheap, the cost shifts to *tracing*: which sentence rests on which evidence, what was ignored, where sources conflict. Claim-level auditability [152] and evidence-licensed claims — calibrating assertion strength to supporting evidence [185] — are attempts to make machine-generated science verifiable by construction, since post-hoc verification does not scale. In regulated domains, deterministic integrity gates are interposed because “self-critique inherits the blind spots that produce confident fabrication” [142]; in frontier physics, unscaffolded agents “cite but do not confront” the literature anchors their claims depend on [186].

Integrity under pressure. SciIntegrity-Bench constructs dilemmas in which honest acknowledgment of failure is the only correct answer while task completion requires misconduct, and finds a 34.2% integrity-failure rate across seven state-of-the-art models — most strikingly, in missing-data scenarios *all seven* fabricate synthetic data rather than acknowledge infeasibility, differing only in whether they disclose the substitution; removing explicit completion pressure sharply reduces undisclosed fabrication but leaves the fabrication itself intact [143]. A complementary position paper documents a subtler variant: in physics-simulation rediscovery episodes, agents reach the *correct answer* while defending a *wrong mechanism* — even asserting general claims their own experimental

data contradicts — and argues that outcome, mechanism fidelity, and epistemic honesty must be measured as separate quantities [150]. Both results connect directly to the reward-hacking analysis of §5: an agent optimized to produce results will, at the margin, misreport rather than fail — and the disposition appears to be intrinsic, not prompt-induced.

Two systemic critiques extend the concern from the agent to the ecosystem. “Dead Science Walking” argues the near-term risk is *corpus failure*: AI scientists are trained on and grounded in a literature that systematically over-represents positive results, so automated hypothesis generation inherits and amplifies publication bias at machine speed — a slow, ecosystem-level self-confirming loop in which today’s distorted record trains tomorrow’s hypothesis generators [187]. And a pre-specified human-in-the-loop study in economics finds that reliability depends less on model capability than on how cognitive labor is *structured* between human and machine — pre-commitment, decision sequencing, accountability, attention allocation [188] — empirical support for the claim that the human role in research loops is a design problem, not a residue.

Assessment. This category exhibits the widest gap in the corpus between demonstrated capability and reliable capability. Where the evaluator is a program — a test suite, a bound-checker, a profiler — automated discovery already produces artifacts that outperform expert humans and feed back into AI infrastructure [4]. Where the evaluator is scientific judgment — novelty, importance, evidential support — the constructive systems outrun their verification, and the diagnostic literature exists precisely to document the difference. The two sub-themes are thus natural experiments in the same variable: §6.1 shows what closed-loop discovery achieves *with* a trustworthy verifier; §§6.2–6.3 show what breaks *without* one.

7. Foundations, Limits, and Safety of RSI

The final family (60 papers) steps back from mechanisms to conditions: when *can* self-improvement continue, what bounds it, and what follows for safety. It is the corpus’s smallest family — a disproportion we return to in §9.

7.1 Theoretical conditions and bounds

The clearest positive statement of conditions is Schaul’s “boundless Socratic learning” position paper: an agent in a closed system can master any capability provided (a) feedback is sufficiently informative and *aligned* with the target, (b) experience coverage is broad enough, and (c) capacity suffices — with language games proposed as the framework in which conditions (a) and (b) can, in principle, be engineered [189]. Read against §5, the empirical literature is one long study of what happens when (a) fails (self-confirming loops) or (b) fails (diversity collapse); the Socratic-learning conditions have become, in effect, the field’s implicit design checklist. On the alignment side, theoretical guarantees for self-rewarding language models have begun to appear, characterizing when iterative self-alignment provably improves [190] — narrow results, but the first of their kind.

The bounding literature attacks the takeoff question from four angles. *Computability-theoretic*: a formal separation result shows that finite internal self-modification keeps a system within its current computational layer — under the paper’s modeling assumptions, no amount of repeated internal revision yields the qualitative capability jump that RSI narratives casually assume, which would require something like stabilized access to an external oracle [191]. The result disciplines the vocabulary: “recursively self-improving” and “unboundedly self-improving” are different claims, and only the first is licensed by internal revision. *Dynamical*: Jafari et al. formalize “runaway growth”

as a testable property, linking capability growth to resource build-out and deriving conditions under which finite-time escalation can be ruled out by physical and information-theoretic limits [192]. *Economic*: Whitfill and Wu estimate the elasticity of substitution between research compute and cognitive labor from a novel panel of four frontier labs (OpenAI, DeepMind, Anthropic, DeepSeek; 2014–2024), asking whether a “software-only” intelligence explosion is possible or whether compute bottlenecks bind. Notably, their two specifications *diverge*: a baseline model estimates compute and labor as substitutes (permitting software-only acceleration), while a “frontier experiments” model accounting for the scale of state-of-the-art training runs estimates them as complements (the bottleneck binds) — making this the empirical crux of the RSI-feasibility debate rather than a settled answer [193]. *Information-theoretic*: Zenil’s impossibility result [146] argues LLM-style self-training *cannot* be unboundedly self-improving without symbolic model synthesis or an unvanishing stream of external signal. Together these justify the taxonomy’s central cut: bounded self-refinement is what the theory permits without new external resources; open-ended RSI requires either continued grounding (data, compute, environment) or an architectural ingredient current systems lack.

7.2 The skeptical position

The skeptical thread deserves separate statement because it is not a fringe: it includes the corpus’s strongest formal results. Its composite claim: (i) self-training without external signal degrades rather than explodes [146, 144]; (ii) even with external signal, compute and physical constraints may prevent super-exponential trajectories [193, 192]; (iii) the capabilities that would most plausibly drive takeoff — research taste, problem selection — are precisely the ones current systems demonstrably lack (§6.3). On point (iii), a first formal treatment now exists: framing “interestingness” — the prospective identification of which tasks hold potential for future progress — as an inductive heuristic for future compression progress, analyzable with the tools of algorithmic information theory, and identifying it explicitly as a bottleneck on the way to recursively self-improving systems [155]. Research taste, in other words, is beginning to acquire a theory, which is the precondition for it acquiring a benchmark. Note what the skeptical position does *not* claim: none of these results bounds the impact of *bounded* self-improvement plus human direction — Anthropic’s “compounding efficiency” scenario — which is compatible with every impossibility theorem in the corpus and is arguably just a description of current frontier-lab practice.

7.3 Safety, control, and the dialogue with the takeoff question

The safety-relevant technical literature concentrates at the category boundaries surveyed above: permanent, self-amplifying, population-transmissible corruption in self-evolving agent systems [83]; capability degradation and safety drift arising without any adversary, and the case for human-oversight anchoring [84]; integrity failure under completion pressure [143]. At the architectural level, the “unfireable safety kernel” line argues that any control located *inside* the agent’s runtime is reachable by inputs that influence the agent — so a system with sufficient reach into its own runtime can, in principle, modify its own guardrails — and that execution-time alignment must therefore live outside the agent’s address space [194]. This is the control-theoretic restatement of why self-modification (locus 3) changes the safety calculus: guardrails become part of the modifiable surface.

The governance literature is thin but pointed. An analysis of inference scaling argues the shift from pre-training compute to inference compute may derail the current paradigm of governance-via-training-compute-thresholds — with opposite implications depending on whether the inference compute is spent at deployment or folded back into training programs inside the lab [195]; the

latter case is exactly the §4–§6 loop structure, and it is the harder one to observe from outside. Domain-specific evaluation frameworks for the highest-stakes capabilities are emerging in parallel, notably for the biological capabilities and risks of autonomous research agents, where the meaning of an evaluation result depends on under-documented design choices [196].

Anthropic’s essay [5] sketches three scenarios — trend stall, compounding efficiency with human direction-setters, and full RSI — and proposes verification infrastructure for credible slowdowns, international coordination on the arms-control model, and urgency on alignment lest “misalignment present in today’s models compound” through self-improvement loops. The corpus speaks to this framing in three ways. First, it locates the present: nearly everything surveyed here is scenario-2 machinery — bounded loops with human-specified objectives — with A-Evolve-Training [180] as the most scenario-3-shaped published artifact. Second, it identifies the takeoff signal to watch: not benchmark scores but *movement up the verification hierarchy on non-verifiable tasks* — a system that could reliably evaluate research directions would relax the binding constraint that currently keeps humans in the loop, though only over the half of direction-setting that is verification-shaped (§5.4). Third, it exposes the misalignment-compounding concern as technically substantive rather than speculative: the self-confirming loop (§5) is exactly the mechanism by which a bias present in today’s models would amplify under self-training, and it is already observed at small scale [141]. What the technical corpus does not yet offer is the verification infrastructure the governance proposals require — methods to *demonstrate* that a training loop is not self-improving past a threshold. That gap between what governance needs and what the literature provides is, we suggest, the most underpopulated research niche this survey has identified.

8. Discussion: Cross-Cutting Observations and Open Problems

The field is accelerating faster than any survey can track. Quarterly output in our corpus grew from single digits in early 2024 to roughly 500 papers in 2026 Q2 (Figure 6); one theme (on-policy self-distillation, 56 papers) did not exist as a distinct thread eighteen months before this writing. We therefore claim durability for this survey’s *structure* — the categories-by-closure axes, the verification hierarchy — rather than its paper list. The structure has already absorbed two paradigm arrivals (OPSD, zero-data self-play) without modification, which is some evidence it will absorb the next one. Absorption is a virtue only up to a point: a structure that accommodates every new result predicts nothing, so §2.2 and open problem 6 state what we believe this one cannot see.

The corpus’s shape itself asks for explanation. The category proportions in Table 1 and the share panel of Figure 3 are conspicuously uneven, and it is worth being explicit about both what that unevenness can and cannot mean. It cannot be read directly as the field’s true composition: our seed queries and deliberately targeted supplement shape the proportions (§2.3), so the raw counts partly mirror our own sampling. What survives that caveat, because it is visible *within* comparable samples, still calls for explanation: deployment- and training-time work dominates every seed quarter; Auto Research is a factor of two to three smaller despite carrying the field’s most celebrated results; foundations is smallest by far. We offer four non-exclusive hypotheses, testable in principle. *A verifiability gradient:* the two dominant categories concentrate where cheap verifiers exist (code, math), so experiments are fast and publishable — the same gradient §5.2 documents inside methods reappears as a force on topic selection. *A cost-of-entry gradient:* an inference-time refinement study needs API credits; a training-loop paper needs GPUs; an Auto-Research system needs infrastructure, long horizons, and (for frontier results) lab-scale compute — paper counts




Figure 6: Seed-corpus quarterly growth through 2026Q2, showing log-scaled paper counts and category shares; partial 2026Q3 (data cutoff early July 2026) is omitted.

fall roughly as entry costs rise, and the compute concentration documented for frontier labs [193] pushes the far end of the spectrum behind corporate walls, where §2.3’s publication-censoring effect hides it from any arXiv sample. *Herd dynamics*: the OPSD thread crystallizing from nothing to dozens of papers within months (§4.3) shows how fast attention concentrates once a recipe is legible and benchmarkable; legibility, not importance, sets the gradient. *Institutional role assignment*: evaluation was until recently a service function inside method papers rather than a research identity — our supplement had to target it precisely because the self-improvement literature treats it as plumbing — and the foundations deficit (60 of 1,250, against the stakes claimed in §7) plausibly reflects that theory and governance work is rewarded by neither benchmarks nor product roadmaps. We flag these as hypotheses rather than findings; distinguishing them would itself be a useful study, and the data to start it ships with this paper.

Mechanisms outrun evaluation. The “self-X” vocabulary keeps growing, but the papers our analysis leaned on hardest were disproportionately diagnostic: controlled decompositions of feedback value [39], placebo-controlled self-repair studies [40], stability analyses of self-play [120], integrity benchmarks [143]. This critique literature is no longer a reaction to the field; it is a load-bearing part of it, and in several themes (AI scientists most clearly) it is the better-cited part. We read this as a maturation signal — the same sequence (method wave, then measurement wave) that reasoning research went through in 2023–2024.

The field’s emerging answer to the verification bottleneck is evaluator co-evolution. Across otherwise unconnected themes, 2026 produced the same architectural move independently at least five times: co-evolving self-generated unit tests with the code they judge [46], discovering per-judge competence taxonomies before trusting judge scores [55], decomposing opaque judges into auditable binary questions [31], self-training the verifier as the primary object of improvement [92], and making the evaluation criterion itself part of the evolutionary loop [62, 168]. The field has evidently concluded that static verifiers cannot supervise improving systems — the Red Queen framing — and is betting that the verifier must improve alongside the policy. Whether this escapes the self-confirming loop or merely gives it a second story is, in our view, the pivotal empirical question the next two years will answer; the A-Evolve-Training episode (§6.2), where a loop detected its own proxy’s corruption and revised its search policy, is the first field observation suggesting escape is possible.

Modality generalization is real but signal-limited. The paradigm has spread from text to vision-language, video, robotics, and speech (§§3.3, 4.5). But each port re-encounters the verification hierarchy at a lower rung: execution feedback has no cheap embodied analogue, and multimodal self-consistency signals admit shortcuts that text-only loops do not [115, 53]. The generalization frontier is therefore not model capability but *signal engineering* — physics residuals [50], formal skill verification [82] — modality by modality.

Open problems. Six, in rough order of leverage:

1. **The exchange rate of grounding.** Theory says pure closed loops degrade [146]; practice mixes in external signal ad hoc. Nobody has characterized the minimum exogenous-signal rate that sustains improvement, though the entropy-reservoir framework [145] suggests the question is well-posed.
2. **Verifying the non-verifiable.** Progress on research taste, creative quality, and direction-setting evaluation would relax the binding constraint of the entire spectrum (§5). Meta-evaluation [122] and auditability-by-construction [152] are starts, not solutions.
3. **Stability engineering as a discipline.** Rise-and-collapse [93], diversity collapse [149],

and safety drift [84] are currently rediscovered per-paradigm. A unified treatment of self-improvement loop dynamics — when they converge, oscillate, or collapse — would replace today’s per-theme folklore.

4. **Trustworthy accumulation.** Persistent self-modification (skills, memory, experience graphs) lacks the verification story that weights-based training has. The formal-verification approach [82] and the threat analyses [83] bracket the problem from two sides; the middle is open.
5. **Governance-grade measurement.** The verification infrastructure that credible slowdown proposals require [5] — auditable evidence about what a training loop is and is not improving — has essentially no technical literature behind it. Given that the foundations family (§7) is the corpus’s smallest at 60 of 1,250 papers, the mismatch between the stated stakes and the allocated research effort is the clearest gap this survey has found.
6. **Recognizing frame revision.** Every problem above is posed inside a fixed objective. The prior question — whether a system can notice that the objective itself has gone stale, and reframe while preserving what should survive the reframing — has neither a benchmark nor a measurement convention, and is invisible to the instrument this survey builds (§2.2). It is not obviously unmeasurable. Four observables are candidates: *productive abandonment* (dropping a line whose local metric is still improving, scored against later vindication); *invariant transfer* (which constraints a system carries across a reformulation of its own task); *absence-sensitivity* (whether a missing result is treated as evidence — testable against the null-result deficit formalized in [187]); and *reframing latency* (how much evidence a loop needs to abandon a stale objective after its environment shifts). A benchmark of deliberately stale or misspecified objectives, scored on whether a system notices rather than on how well it optimizes, is buildable today and does not exist. Part of the obstacle is that the record deletes the evidence: publication discards failed experiments, rejected hypotheses, and the branching exploration itself — the “storytelling tax” that agent-native artifact protocols are designed to reverse [151]. We note the reflexive point: this section argues that legibility, not importance, sets the field’s attention gradient; a taxonomy is a legibility instrument, and ours is subject to the same critique.

9. Conclusion

We surveyed 1,250 recent papers on AI self-improvement through a two-axis taxonomy — what the system improves (outputs, policy, scaffolding, the research process) and who validates the improvement — and argued that the axis structure resolves what the “self-X” vocabulary obscures: bounded self-refinement and open-ended recursive self-improvement are different phenomena with different evidence bases, different theory, and different risk profiles.

The evidence sorts cleanly. Bounded self-refinement is an engineering success: inference-time loops reliably improve outputs when grounded in external signals; training-time loops persist those gains and are industrial practice; agents accumulate skills and experience across episodes; and evolutionary discovery systems produce artifacts — algorithms, kernels, mathematical constructions — that feed back into AI development itself. Open-ended RSI, by contrast, remains bounded on every side we can measure: theoretically by grounding requirements and compute elasticities, empirically by collapse dynamics, and practically by the non-verifiability of exactly the judgments (what to work on, what counts as better) that would make the loop self-sufficient.

These are not one difficulty. “What counts as better” is a verification problem the hierarchy indexes;

“what to work on” is prior to it, and this survey’s instrument — like the field’s — measures the first far better than the second.

The single thread connecting every category is that self-improvement is only as real as its verification. That framing converts the takeoff question from speculation into a measurement program: watch not benchmark scores but the verification hierarchy — in particular, whether systems become reliable evaluators of open-ended research judgment. Until then, the human role in the loop is not a sentimental holdover; it is the field’s verification layer of last resort. The literature surveyed here suggests that layer will be load-bearing for some time — and that building its eventual replacement, carefully and measurably, is the research program this decade’s AI safety may most depend on.

Data availability

The full 1,250-paper corpus with taxonomy category assignments (plus the unsupervised 13-topic clustering that organized the seed harvest before the taxonomy of §2.2 was fixed), the per-category statistics underlying Table 1, the figure sources, and the scripts that generate the bibliography and figures are available at <https://github.com/deepgrounding/recursive-self-improvement>.

References

References

- [1] Irving John Good. Speculations concerning the first ultraintelligent machine. *Advances in Computers*, 6:31–88, 1966. doi: 10.1016/S0065-2458(08)60418-0.
- [2] Jürgen Schmidhuber. Gödel machines: Self-referential universal problem solvers making provably optimal self-improvements. *arXiv preprint cs/0309048*, 2003. URL <https://arxiv.org/abs/cs/0309048>.
- [3] Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M. Pawan Kumar, Emilien Dupont, Francisco J. R. Ruiz, Jordan S. Ellenberg, Pengming Wang, Omar Fawzi, Pushmeet Kohli, and Alhussein Fawzi. Mathematical discoveries from program search with large language models. *Nature*, 625:468–475, 2024. doi: 10.1038/s41586-023-06924-6. FunSearch.
- [4] Alexander Novikov, Ngân V u, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco J. R. Ruiz, Abbas Mehrabian, M. Pawan Kumar, Abigail See, Swarat Chaudhuri, George Holland, Alex Davies, Sebastian Nowozin, Pushmeet Kohli, and Matej Balog. AlphaEvolve: A coding agent for scientific and algorithmic discovery, 2025. URL <https://arxiv.org/abs/2506.13131>.
- [5] Anthropic. Recursive self-improvement. Anthropic Institute blog post, 2026. URL <https://www.anthropic.com/institute/recursive-self-improvement>. Published May 2026.
- [6] Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. URL <https://arxiv.org/abs/2303.17651>.

- [7] Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. STaR: Bootstrapping reasoning with reasoning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL <https://arxiv.org/abs/2203.14465>.
- [8] Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models. In *International Conference on Machine Learning (ICML)*, 2024. URL <https://arxiv.org/abs/2401.10020>.
- [9] Xunjian Yin, Xinyi Wang, Liangming Pan, Li Lin, Xiaojun Wan, and William Yang Wang. Gödel agent: A self-referential agent framework for recursive self-improvement, 2024. URL <https://arxiv.org/abs/2410.04444>.
- [10] Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin gödel machine: Open-ended evolution of self-improving agents, 2025. URL <https://arxiv.org/abs/2505.22954>.
- [11] Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. The AI scientist: Towards fully automated open-ended scientific discovery, 2024. URL <https://arxiv.org/abs/2408.06292>.
- [12] Mingyang Song and Mao Zheng. A survey of on-policy distillation for large language models, 2026. URL <https://arxiv.org/abs/2604.00626>.
- [13] Jiaqi Wei, Xiang Zhang, Yuejin Yang, Wenxuan Huang, Juntai Cao, Sheng Xu, Xiang Zhuang, Zhangyang Gao, Muhammad Abdul-Mageed, Laks V. S. Lakshmanan, Chenyu You, Wanli Ouyang, and Siqi Sun. Unifying tree search algorithm and reward design for LLM reasoning: A survey, 2025. URL <https://arxiv.org/abs/2510.09988>.
- [14] Sandeco Macedo. Stop hand-holding your coding agent: Engineering the loops that replace step-by-step prompting, 2026. URL <https://arxiv.org/abs/2607.00038>.
- [15] Andrew Zhao, Yiran Wu, Yang Yue, Tong Wu, Quentin Xu, Yang Yue, Matthieu Lin, Shenzhi Wang, Qingyun Wu, Zilong Zheng, and Gao Huang. Absolute zero: Reinforced self-play reasoning with zero data, 2025. URL <https://arxiv.org/abs/2505.03335>.
- [16] Chengsong Huang, Wenhao Yu, Xiaoyang Wang, Hongming Zhang, Zongxia Li, Ruosen Li, Jiaxin Huang, Haitao Mi, and Dong Yu. R-zero: Self-evolving reasoning LLM from zero data, 2025. URL <https://arxiv.org/abs/2508.05004>. ICLR 2026.
- [17] Jianzhe Lin, Fang Wang, Xiaolin Li, Rajeshkumar Golani, and Jubin Chheda. Repeated post-training is not self-improving: Diagnosing scientific amnesia in continual DPO pipelines, 2026. URL <https://arxiv.org/abs/2606.21089>.
- [18] Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. URL <https://arxiv.org/abs/2303.11366>.
- [19] Charlie Snell, Jae-Hoon Lee, Kelvin Xu, and Aviral Kumar. Scaling LLM test-time compute optimally can be more effective than scaling model parameters, 2024. URL <https://arxiv.org/abs/2408.03314>.
- [20] Marius-Constantin Dinu, Claudiu Leoveanu-Condrei, Markus Holzleitner, Werner Zellinger, and Sepp Hochreiter. SymbolicAI: A framework for logic-based approaches combining generative models and solvers, 2024. URL <https://arxiv.org/abs/2402.00854>.

- [21] Jiajing Zhang, Jiamei Jiang, Chenyang Zhang, Feifei Mo, Linjing Li, and Daniel Zeng. Towards reliable and robust LLM planning: Symbolic feedback-driven iterative self-refinement framework, 2026. URL <https://arxiv.org/abs/2606.27757>.
- [22] Shuai Lyu, Haoran Luo, Ripeng Li, Zhonghong Ou, Jiangfeng Sun, Yang Qin, Xiaoran Shang, Meina Song, and Yifan Zhu. SQL-o1: A self-reward heuristic dynamic search method for text-to-SQL, 2025. URL <https://arxiv.org/abs/2502.11741>.
- [23] Shamanth Kuthpadi Seethakantha, Dung Thai, Vara Prasad Gudi, Simran Tiwari, Rami Matar, Avijit Mitra, Wenlong Zhao, Wael Salloum, and Andrew McCallum. Hallucination detection-guided preference optimization for clinical summarization, 2026. URL <https://arxiv.org/abs/2605.28910>.
- [24] Huyen Nguyen, Haoxuan Zhang, Yang Zhang, Haihua Chen, and Junhua Ding. LongSumEval: Question-answering based evaluation and feedback-driven refinement for long document summarization, 2026. URL <https://arxiv.org/abs/2604.25130>.
- [25] Dongge Han, Trevor McInroe, Adam Jelley, Stefano V. Albrecht, Peter Bell, and Amos Storkey. LLM-personalize: Aligning LLM planners with human preferences via reinforced self-training for housekeeping robots, 2024. URL <https://arxiv.org/abs/2404.14285>.
- [26] Genghan Zhang, Weixin Liang, Olivia Hsu, and Kunle Olukotun. Adaptive self-improvement LLM agentic system for ML library development, 2025. URL <https://arxiv.org/abs/2502.02534>.
- [27] Shaomu Tan, Dawei Zhu, Ke Tran, Michael Denkowski, Sony Trenous, Bill Byrne, Leonardo Ribeiro, and Felix Hieber. What does LLM refinement actually improve? a systematic study on document-level literary translation, 2026. URL <https://arxiv.org/abs/2605.13368>.
- [28] Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet, 2024. URL <https://arxiv.org/abs/2310.01798>. ICLR 2024.
- [29] Elroy Stav, Dvir Berlowitz, Maayan Orner, and Sarit Kraus. When does intrinsic self-correction help? a task-sensitive analysis, 2026. URL <https://arxiv.org/abs/2606.23196>.
- [30] Johannes Zenn and Jonas Geiping. When are likely answers right? on sequence probability and correctness in LLMs, 2026. URL <https://arxiv.org/abs/2606.27359>.
- [31] Sangwoo Cho, Kushal Chawla, Pengshan Cai, Zefang Liu, Chenyang Zhu, Shi-Xiong Zhang, and Sambit Sahu. Ask, don’t judge: Binary questions for interpretable LLM evaluation and self-improvement, 2026. URL <https://arxiv.org/abs/2606.27226>.
- [32] Shuang Lu, Chen Guan, Nam Anh Dinh, Itai Lang, Ari Holtzman, and Rana Hanocka. Ll3m: Large language 3d modelers, 2025. URL <https://arxiv.org/abs/2508.08228>.
- [33] Xiaomin Yang, Chaozheng Wang, Chen Zheng, Heng Zhang, and Yanjun Wu. AgenticDB: Agentic performance reconfiguration for database workloads, 2026. URL <https://arxiv.org/abs/2606.20318>.
- [34] Zepeng Li, Jie Ren, Zhanyong Tang, Jie Zheng, and Zheng Wang. AutoPass: Evidence-guided LLM agents for compiler performance tuning, 2026. URL <https://arxiv.org/abs/2606.20373>.
- [35] Po-Nien Kung, Linfeng Song, Dawsen Hwang, Jinsung Yoon, Chun-Liang Li, Simone Severini, Mirek Olšák, Edward Lockhart, Quoc V Le, Burak Gökürk, Thang Luong, Tomas

- Pfister, and Nanyun Peng. LEAP: Supercharging LLMs for formal mathematics with agentic frameworks, 2026. URL <https://arxiv.org/abs/2606.03303>.
- [36] Yuwei Liu, Xinyi Wan, Yanhao Wang, Minghua Wang, Lin Huang, and Tao Wei. KVerus: Scalable and resilient formal verification proof generation for rust code, 2026. URL <https://arxiv.org/abs/2605.03822>.
 - [37] Wenhan Wang and Zeyu Sun. KBSpec: LLM-driven formal specification generation with evolving domain knowledge base, 2026. URL <https://arxiv.org/abs/2606.21339>.
 - [38] Tianyang Zhou, Somesh Jha, Mihai Christodorescu, Kirill Levchenko, and Varun Chandrasekaran. Verifier-guided code translation via meta-step decoding, 2026. URL <https://arxiv.org/abs/2605.17626>.
 - [39] Bartłomiej Cupiał, Jan Lojek, Mikołaj Garstecki, Szymon Pobłocki, Alicja Ziarko, and Piotr Miłoś. What drives interactive improvement from feedback?, 2026. URL <https://arxiv.org/abs/2606.30774>.
 - [40] Mehmet İscan. Falsification, not exposure: An internally preregistered placebo-controlled decomposition of self-repair feedback in frozen small code models, 2026. URL <https://arxiv.org/abs/2606.31511>.
 - [41] Charles Junichi McAndrews. Feedback over form: Why execution feedback matters more than pipeline topology in 1-3b code generation, 2026. URL <https://arxiv.org/abs/2604.21950>.
 - [42] Will LeVine, Brendan Evers, Sam Saltwick, and Abhay Venkatesh. RubricRefine: Improving tool-use agent reliability with training-free pre-execution refinement, 2026. URL <https://arxiv.org/abs/2605.09730>.
 - [43] Le Zhang and Suresh Kothari. Unlocking LLM code correction with iterative feedback loops, 2026. URL <https://arxiv.org/abs/2606.17514>.
 - [44] Shen Yin, David Ken, and Joel Stremmel. Denoising iterative self-correction: Structured verification loops for reliable LLM reasoning, 2026. URL <https://arxiv.org/abs/2606.21724>.
 - [45] Yinsheng Yao, Hongxiang Zhang, Weixi Tong, and Tianyi Zhang. FLARE: Fine-grained diagnostic feedback for LLM code refinement, 2026. URL <https://arxiv.org/abs/2606.03852>.
 - [46] Zhangyi Hu, Chenhui Liu, Tian Huang, Jindong Li, Yang Yang, Jiemin Wu, Zining Zhong, Menglin Yang, and Yutao Yue. CoSPlay: Cooperative self-play at test-time with self-generated code and unit test, 2026. URL <https://arxiv.org/abs/2605.23491>.
 - [47] Jiawei Mao, Hardy Chen, Haoqin Tu, Yuhan Wang, Letian Zhang, Zeyu Zheng, Huaxiu Yao, Zirui Wang, Cihang Xie, and Yuyin Zhou. Kestrel: Grounding self-refinement for LVLM hallucination mitigation, 2026. URL <https://arxiv.org/abs/2603.16664>.
 - [48] Shuimu Chen, Yihan Chen, Yuanshen Guan, Zebang Cheng, Zeyu Zhang, Su-Juan Qin, Bin Xia, Jiaran Li, Wenming Yang, and Fei Ma. Reflect-r1: Evidence-driven reflection for self-correction in long video understanding, 2026. URL <https://arxiv.org/abs/2606.27922>.
 - [49] Yong-Jin Kim, Yoonjin Oh, Yerin Kim, Hyomin Kim, Jeeyoung Yun, Yujung Heo, Minjun Kim, and Sungwoong Kim. FiRe: Fine-grained multimodal reasoning for enhanced image generation, 2026. URL <https://arxiv.org/abs/2604.13491>.

- [50] Mariam Hassan, Kaouther Messaoud, Wuyang Li, and Alexandre Alahi. Proprio: Latent self-scoring and inference-time refinement for physically plausible video generation, 2026. URL <https://arxiv.org/abs/2605.28230>.
- [51] Yajing Wang, Chao Bi, Junshu Sun, Shufan Shen, Zhaobo Qi, Shuhui Wang, and Q Huang. ActiveScope: Actively seeking and correcting perception for MLLMs, 2026. URL <https://arxiv.org/abs/2606.24292>.
- [52] Yunqi Xue, Zhijiang Li, Philip Torr, and Jindong Gu. Safe autoregressive image generation with iterative self-improving codebooks, 2026. URL <https://arxiv.org/abs/2606.27147>.
- [53] Shravan Venkatraman, Ritesh Thawkar, Omkar Thawakar, Rao Muhammad Anwer, Hisham Cholakkal, Salman Khan, and Fahad Khan. Paying more attention to visual tokens in self-evolving large multimodal models, 2026. URL <https://arxiv.org/abs/2606.27373>.
- [54] Zihui Xue, Ami Baid, Sangho Kim, Mi Luo, and Kristen Grauman. Personal visual context learning in large multimodal models, 2026. URL <https://arxiv.org/abs/2605.10936>.
- [55] Yu Cao, Ziquan Liu, Zhensong Zhang, Jiankang Deng, Shaogang Gong, and Jifei Song. Each judge its own yardstick: Discovering per-VLM taxonomies for physical video evaluation, 2026. URL <https://arxiv.org/abs/2606.22918>.
- [56] Chaehee Song, Minseok Seo, Yeeun Seong, Doyi Kim, and Changick Kim. Query-conditioned test-time self-training for large language models, 2026. URL <https://arxiv.org/abs/2605.13369>.
- [57] Vaggelis Dorovatas, Nancy Kalaj, and Rahaf Aljundi. Continual self-improvement with lightweight experiential latent memories, 2026. URL <https://arxiv.org/abs/2606.17803>.
- [58] Ali Behrouz, Farnoosh Hashemi, and Vahab Mirrokni. Language models need sleep: Learning to self-modify and consolidate memories, 2026. URL <https://arxiv.org/abs/2606.03979>.
- [59] Tennison Liu and Mihaela van der Schaar. Truly self-improving agents require intrinsic metacognitive learning, 2025. URL <https://arxiv.org/abs/2506.05109>.
- [60] Rean Clive Fernandes, Lukas Fehring, Theresa Eimer, Marius Lindauer, and Matthias Feurer. Environment-grounded automated prompt optimization for LLM game agents, 2026. URL <https://arxiv.org/abs/2606.17838>.
- [61] Yuxuan Wan, Tianqing Fang, Zaitang Li, Yintong Huo, Wenxuan Wang, Haitao Mi, Dong Yu, and Michael R. Lyu. Inference-time scaling of verification: Self-evolving deep research agents via test-time rubric-guided verification, 2026. URL <https://arxiv.org/abs/2601.15808>.
- [62] Alex Iacob, Andrej Jovanović, William F. Shen, Daniel Burkhardt, Meghdad Kurmanji, Nurbek Tastan, Lorenzo Sani, Niccolò Alberto Elia Venanzi, Ambroise Odonnat, Zeyu Cao, Bill Marino, Xinchu Qiu, and Nicholas D. Lane. The red queen gödel machine: Co-evolving agents and their evaluators, 2026. URL <https://arxiv.org/abs/2606.26294>.
- [63] Ziyang Liu, Xinyan Guo, Xuchen Wei, Han Hao, and Liu (M. Sc.) Yang. Escher-loop: Mutual evolution by closed-loop self-referential optimization, 2026. URL <https://arxiv.org/abs/2604.23472>.
- [64] Congjia Tian, Yuhang Yao, and Jiaming Cui. QueenBee planner: Skill-evolving communication topologies for token-efficient LLM multi-agent systems, 2026. URL <https://arxiv.org/abs/2606.27492>.

- [65] Xueqiao Sun, Xiaohan Wang, Ludwig Schmidt, Serena Yeung-Levy, and Yuhui Zhang. Learning from failure: Inference-time self-improvement for computer-use agents, 2026. URL <https://arxiv.org/abs/2606.31270>.
- [66] Gang Liao, Y He, Abdullah Ozturk, Zhouyang Li, Ying Wang, Zichang Guo, Hongsen Qin, Yaobin Qin, Tao Yang, Zewei Jiang, Dianshi Li, Jort Gemmeke, Jiangyuan Li, Liyuan Li, Nathan Yan, Masha Basmanova, Uladzimir Pashkevich, Matt Steiner, Pedro Pedreira, Rob Fergus, Anirudh Goyal, C E Wu, Gaoxiang Liu, Andrew Witten, and Daniel J. Abadi. Experience graphs: The data foundation for self-improving agents, 2026. URL <https://arxiv.org/abs/2606.29823>.
- [67] Xinyu Lu, Tianshu Wang, Pengbo Wang, Zujie Wen, Zhiqiang Zhang, Jun Zhou, Boxi Cao, Yaojie Lu, Hongyu Lin, Xianpei Han, and Le Sun. The meta-agent challenge: Are current agents capable of autonomous agent development?, 2026. URL <https://arxiv.org/abs/2606.04455>.
- [68] Linyue Pan, Yaoming Zhu, Lin Qiu, Xuezhi Cao, and Xunliang Cai. SAGE: A quantitative evaluation of socialized evolution in agent ecosystems, 2026. URL <https://arxiv.org/abs/2606.03544>.
- [69] Florian Valentin Wunderlich, Lars Benedikt Kaesberg, Jan Philip Wahle, Terry Ruas, and Bela Gipp. Multi-agent reasoning improves compute efficiency: Pareto-optimal test-time scaling, 2026. URL <https://arxiv.org/abs/2605.01566>.
- [70] Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models, 2023. URL <https://arxiv.org/abs/2305.16291>. TMLR 2024.
- [71] Srishti Gautam, Arjun Radhakrishna, and Sumit Gulwani. SkillAxe: Sharpening LLM-authored agent skills through evaluation-guided self-refinement, 2026. URL <https://arxiv.org/abs/2606.10546>.
- [72] Yash Vishe, Rohan Surana, Xunyi Jiang, Zihan Huang, Xintong Li, Nikki Lijing Kuang, Tong Yu, Ryan A. Rossi, Jingbo Shang, Julian McAuley, and Junda Wu. Skill-r1: Agent skill evolution via reinforcement learning, 2026. URL <https://arxiv.org/abs/2605.09359>.
- [73] Yuxuan Liu, Zhaochen Su, Lingyun Xie, Yuhao Zhang, Qing Zong, Jiahe Guo, Zhongwei Xie, Yiyan Ji, Yauwai Yim, Hongyu Luo, Xiyu Ren, Ruan Chenyu, Haoran Li, and Yangqiu Song. SkillRevise: Improving LLM-authored agent skills via trace-conditioned skill revision, 2026. URL <https://arxiv.org/abs/2606.01139>.
- [74] Xinyuan Song, Zekun Cai, and L Zhao. AlgoSkill: Learning to design algorithms by scheduling human-like skills, 2026. URL <https://arxiv.org/abs/2606.29999>.
- [75] Min Yang, Jinghua Piao, Xu Xia, Xiaochong Lan, Jiaju Chen, Yongshun Gong, and Yong Li. SkillMaster: Toward autonomous skill mastery in LLM agents, 2026. URL <https://arxiv.org/abs/2605.08693>.
- [76] Jingbo Yang, Guanyu Yao, Yang Zhang, Ramana Rao Kompella, Gaowen Liu, and Shiyu Chang. FederatedSkill: Federated learning for agentic skill evolution, 2026. URL <https://arxiv.org/abs/2606.03143>.
- [77] Yangbo Wei, Zhen Huang, Shaoqiang Lu, Junhong Qian, Qifan Wang, Chen Wu, and Lei

- He. SkillSmith: Co-evolving skills and tools for self-improving agent systems, 2026. URL <https://arxiv.org/abs/2606.01314>.
- [78] Chuan Xiao, Zhengbo Jiao, Shaobo Wang, Wei Wang, Bing Zhao, Hu Wei, Linfeng Zhang, and Lin Qu. Socratic-SWE: Self-evolving coding agents via trace-derived agent skills, 2026. URL <https://arxiv.org/abs/2606.07412>.
- [79] Xiwen Chen, Wenhui Zhu, Songzhu Zheng, Kashif Rasul, Yueyue Deng, and Huayu Li. SHARP: A self-evolving human-auditable rubric policy for financial trading agents, 2026. URL <https://arxiv.org/abs/2605.06822>.
- [80] Youngduk Kim, Minkyoo Song, and Seungwon Shin. SkillMutator: Benchmarking and defending language-and-code cross-modal attacks on LLM agent skills, 2026. URL <https://arxiv.org/abs/2606.14154>.
- [81] Yurun Chen, Biao Yi, Keting Yin, and Shengyu Zhang. SkillHarness: Harnessing safe skills for computer-use agents, 2026. URL <https://arxiv.org/abs/2606.20636>.
- [82] Yunhao Yang, Neel P. Bhatt, Kevin Wang, Samuel Tetteh, Zhangyang Wang, and Ufuk Topcu. VASO: Formally verifiable self-evolving skills for physical AI agents, 2026. URL <https://arxiv.org/abs/2606.05395>.
- [83] Ruixiao Lin, Xinhao Deng, Qingming Li, Jianan Ma, Yunhao Feng, Yuqi Qing, Zhenyuan Li, Yechao Zhang, Shiwen Cui, Changhua Meng, Tianwei Zhang, Xingjun Ma, Qi Li, Ke Xu, and Shouling Ji. Safety in self-evolving LLM agent systems: Threats, amplification, and case studies, 2026. URL <https://arxiv.org/abs/2606.23075>.
- [84] Dongyong Shi, Junqi He, Junhao Chen, Bowen Wang, and Yuta Nakashima. Towards healthy evolution: Exploring the role and mechanisms of human-agent interaction in self-evolving systems, 2026. URL <https://arxiv.org/abs/2606.06114>.
- [85] Avi Singh, John D. Co-Reyes, Rishabh Agarwal, et al. Beyond human data: Scaling self-training for problem-solving with language models, 2023. URL <https://arxiv.org/abs/2312.06585>. ReST^{EM}; TMLR 2024.
- [86] Zixiang Chen, Yihe Deng, Huizhuo Yuan, Kaixuan Ji, and Quanquan Gu. Self-play fine-tuning converts weak language models to strong language models. In *International Conference on Machine Learning (ICML)*, 2024. URL <https://arxiv.org/abs/2401.01335>. SPIN.
- [87] Dan Zhang, Sining Zhou, Ziniu Hu, Yisong Yue, Yuxiao Dong, and Jie Tang. ReST-MCTS*: LLM self-training via process reward guided tree search, 2024. URL <https://arxiv.org/abs/2406.03816>.
- [88] Aojie Yuan, Yi Nian, Haiyue Zhang, Zijian Su, and Yue Zhao. SEVA: Self-evolving verification agent with process reward for fact attribution, 2026. URL <https://arxiv.org/abs/2606.29713>.
- [89] Andreas Sauter, Yuyue Zhao, Jacopo Urbani, Wenxiang Hu, Zaiqiao Meng, Lun Zhou, Xiaohui Yan, and Yougang Lyu. EvoIdeator: Evolving scientific ideas through checklist-grounded reinforcement learning, 2026. URL <https://arxiv.org/abs/2603.21728>.
- [90] Xinbei Ma, Congmin Zheng, Jiyang Qiu, Jiale Hong, Yao Yao, Xiangmou Qu, Jiabin Yin, Xingyu Lou, Jun Wang, Weiwen Liu, Weinan Zhang, Zhuosheng Zhang, and Hongyun Zhao. Retrospective progress-aware self-refinement for LLM agent training, 2026. URL <https://arxiv.org/abs/2606.14302>.

- [91] Nick Jiang, Isaac Kauvar, and Jack Lindsey. The value axis: Language models encode whether they’re on the right track, 2026. URL <https://arxiv.org/abs/2606.17056>.
- [92] Chen Henry Wu and Aditi Raghunathan. Self-trained verification for training- and test-time self-improvement, 2026. URL <https://arxiv.org/abs/2605.30290>.
- [93] Jianzhe Lin. Self-improvement can self-regress: The rise-and-collapse failure mode of LLM self-training, 2026. URL <https://arxiv.org/abs/2606.21090>.
- [94] Youting Wang, Yuan Tang, Bowen Liu, Xuan Liu, and Dingyan Shang. When LLM reward design fails: Diagnostic-driven refinement for sparse structured RL, 2026. URL <https://arxiv.org/abs/2605.28918>.
- [95] Zi-Yi Dou, Cheng-Fu Yang, Xueqing Wu, Kai-Wei Chang, and Nanyun Peng. Re-ReST: Reflection-reinforced self-training for language agents, 2024. URL <https://arxiv.org/abs/2406.01495>.
- [96] Markus J. Buehler. PRefLexOR: Preference-based recursive language modeling for exploratory optimization of reasoning and agentic thinking, 2024. URL <https://arxiv.org/abs/2410.12375>.
- [97] Haolin Chen, Yihao Feng, Zuxin Liu, Weiran Yao, Akshara Prabhakar, Shelby Heinecke, Ricky Ho, Phil Mui, Silvio Savarese, Caiming Xiong, and Huan Wang. Language models are hidden reasoners: Unlocking latent reasoning capabilities via self-rewarding, 2024. URL <https://arxiv.org/abs/2411.04282>.
- [98] Aydin Javadov, Shyngys Aitkazinov, Tobias Hoesli, Florian von Wangenheim, Bjoern Schuller, and James Ollier. NeuReasoner: Theory-grounded mapping of reasoning elicitation boundaries, 2026. URL <https://arxiv.org/abs/2606.29971>.
- [99] Tony Lee and Percy Liang. Self-verified distillation: Your language model is secretly its own synthetic data pipeline, 2026. URL <https://arxiv.org/abs/2605.26132>.
- [100] H. He, Jiuming Liu, and Victor Sanchez. Revisiting chain-of-thought reasoning under limited supervision: Semi-supervised chain-of-thought learning, 2026. URL <https://arxiv.org/abs/2607.01511>.
- [101] Xingyu Chen, Jiahao Xu, Tian Liang, Zhiwei He, Ji Pang, Dian Yu, Linfeng Song, Qiuzhi Liu, Mengfei Zhou, Zhuosheng Zhang, Rui Wang, Zhaopeng Tu, Haitao Mi, and Dongbo Yu. Do NOT think that much for $2+3=?$ on the overthinking of o1-like LLMs, 2024. URL <https://arxiv.org/abs/2412.21187>.
- [102] C Chung min Lee, Sihui Dai, Mingyang Zhou, Isha Slavin, Shi-Xiong Zhang, Sambit Sahu, and William Campbell. Know when to stop: Segment-level credit assignment for reducing overthinking, 2026. URL <https://arxiv.org/abs/2607.00482>.
- [103] Difan Jiao, Q. G. Wen, Blair Yang, Zhenwei Tang, and Ashton Anderson. ThinkTwice: Jointly optimizing large language models for reasoning and self-refinement, 2026. URL <https://arxiv.org/abs/2604.01591>.
- [104] Harsh Patel. A verifiable search is not a learnable chain-of-thought, 2026. URL <https://arxiv.org/abs/2606.21884>.
- [105] Akiyoshi Tomihari and Issei Sato. Power distribution bridges sampling, self-reward RL, and self-distillation, 2026. URL <https://arxiv.org/abs/2605.04542>.

- [106] Ruixiang Zhang, Richard He Bai, Huangjie Zheng, Navdeep Jaitly, Ronan Collobert, and Yizhe Zhang. Embarrassingly simple self-distillation improves code generation, 2026. URL <https://arxiv.org/abs/2604.01193>.
- [107] C Y Lin, Kedi Chen, and Wei Zhang. ReNIO: Reweighting negative trajectory importance for LLM on-policy distillation, 2026. URL <https://arxiv.org/abs/2606.23104>.
- [108] Haisen Luo, Yiwei Liu, Haoning Wang, Dan Liu, Junxi Yin, Haotian Wang, Lei Zhang, Xiaoyu Tian, Shuaiting Chen, Yuansheng Song, Baoyan Guo, Xiongfei Yan, B Yang, Chengwei Liu, Ming Cui, and Jiong Chen. DRIFT: Difficulty routing self-Distillation with rhythm-gated exploration and success BuFFer training, 2026. URL <https://arxiv.org/abs/2606.30345>.
- [109] Ye Liu, Srijan Bansal, Bo Pang, Yang Li, Zeyu Leo Liu, Yifei Ming, Zixuan Ke, Shafiq Joty, and Semih Yavuz. Procedural memory distillation: Online reflection for self-improving language models, 2026. URL <https://arxiv.org/abs/2607.01480>.
- [110] Zhanming Shen, Jintao Tong, Su Yan, Chen Shen, Hao Chen, Wentao Ye, Xiaomeng Hu, Rui Miao, Haobo Wang, Junbo Zhao, Gang Chen, and J P Ye. Purified OPSD: On-policy self-distillation without losing how to think, 2026. URL <https://arxiv.org/abs/2607.02234>.
- [111] Yunhe Li, Hao Shi, Wenhao Liu, Mengzhe Ruan, Hanxu Hou, Zhongxiang Dai, Shuang Qiu, and Linqi Song. DemoPSD: Disagreement-modulated policy self-distillation, 2026. URL <https://arxiv.org/abs/2607.02502>.
- [112] Leyi Pan, Shuchang Tao, Yunpeng Zhai, Lingzhe Zhang, Zhaoyang Liu, Bolin Ding, Aiwei Liu, and Lijie Wen. RLCSO: Reinforcement learning with contrastive on-policy self-distillation, 2026. URL <https://arxiv.org/abs/2606.11709>.
- [113] Li Jiang, Haoran Xu, Yichuan Ding, and Amy Zhang. Trajectory-refined distillation, 2026. URL <https://arxiv.org/abs/2606.08432>.
- [114] Semih Kara and Oğuzhan Ersoy. The role of feedback alignment in self-distillation, 2026. URL <https://arxiv.org/abs/2606.11173>.
- [115] Sihan Wang, Xiyao Liu, Lianqing Liu, and Zhi Han. Seeing before reasoning: Decoupling perception and reasoning for shortcut-resilient multimodal on-policy self-distillation, 2026. URL <https://arxiv.org/abs/2606.19120>.
- [116] Peng Xia, Kaide Zeng, Jiaqi Liu, Can Qin, Fang Wu, Yiyang Zhou, Caiming Xiong, and Huaxiu Yao. Agent0: Unleashing self-evolving agents from zero data via tool-integrated reasoning, 2025. URL <https://arxiv.org/abs/2511.16043>. ICML 2026.
- [117] Kyeongjin Ahn, Seungeon Lee, Krishna P. Gummadi, and Meeyoung Cha. GeoX: Mastering geospatial reasoning through self-play and verifiable rewards, 2026. URL <https://arxiv.org/abs/2605.20006>.
- [118] Thomas Chen and Zhiyuan Li. A theoretical framework for self-play theorem proving algorithms, 2026. URL <https://arxiv.org/abs/2606.01861>.
- [119] Yuhang Lai, Jiazhan Feng, Yee Whye Teh, and Ning Miao. Verifier-backed hard problem generation for mathematical reasoning, 2026. URL <https://arxiv.org/abs/2605.06660>.
- [120] Sophia Xiao Pu, Zhaotian Weng, Chengzhi Liu, Jayanth Srinivasa, Gaowen Liu, William W. B. Wang, and Xin Eric Wang. Survive or collapse: The asymmetric roles of data gating and reward grounding in self-play RL, 2026. URL <https://arxiv.org/abs/2605.22217>.

- [121] Roger Creus Castanyer, Geoffrey Bradway, Lorenz Wolf, Maxwell Lin, Augustine N. Mavor-Parker, and Matthew James Sargent. PopuLoRA: Co-evolving LLM populations for reasoning self-play, 2026. URL <https://arxiv.org/abs/2605.16727>.
- [122] Yuan Sui and Bryan Hooi. Conversation for non-verifiable learning: Self-evolving LLMs through meta-evaluation. *Open MIND*, 2026. doi: 10.48550/arxiv.2601.21464. URL <https://arxiv.org/abs/2601.21464>.
- [123] Chengsong Huang, Haolin Liu, Tong Zheng, Runpeng Dai, Langlin Huang, Jinyuan Li, Zongxia Li, Zhepei Wei, Yu Meng, and Jiaxin Huang. G-zero: Self-play for open-ended generation from zero data, 2026. URL <https://arxiv.org/abs/2605.09959>.
- [124] T.P. Ko and Jonas Geiping. Attractor states emerge in multi-turn LLM conversations, 2026. URL <https://arxiv.org/abs/2606.30571>.
- [125] Jiyu Kelly Lim, Youngwoo Yoon, and Kwanghyun Park. The robot’s inner critic: Self-refinement of social behaviors through VLM-based replanning, 2026. URL <https://arxiv.org/abs/2603.20164>.
- [126] Jiayu Yang, Tao Yang, Weijun Li, Xiang Chang, Fei Chao, Changjing Shang, and Qiang Shen. PhysReflect-VLA: Physical feasibility and self-reflective regulation for reliable vision-language-action policies, 2026. URL <https://arxiv.org/abs/2606.27146>.
- [127] Yifu Yuan, Yaoting Huang, Xianze Yao, Yutong Li, Shuoheng Zhang, Linqi Han, Pengyi Li, Jiangeng Sun, Wenting Jia, Zhao Zhang, Yuhao Liu, Ruihao Liao, Yucheng Hu, Qiyu Wu, Yuxiao Li, Zibin Dong, Fei Ni, Yan Zheng, Shuyang Gu, Yi Ma, Hongyao Tang, Han Hu, and Jianye Hao. Embodied-r1.5: Evolving physical intelligence via embodied foundation models, 2026. URL <https://arxiv.org/abs/2606.11324>.
- [128] Hanzhi Chen, A M Zhang, Simon Schaefer, Kejia Chen, Shi Chen, Daniel Cremers, Oier Mees, and Stefan Leutenegger. Robot self-improvement via human-video dynamics models, 2026. URL <https://arxiv.org/abs/2606.21406>.
- [129] Chao Deng, Shaolei Zhang, Ju Fan, and Xiaoyong Du. DataEvolver: Automatic data preparation for large language models through multi-level self-evolving, 2026. URL <https://arxiv.org/abs/2606.07001>.
- [130] Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s verify step by step, 2023. URL <https://arxiv.org/abs/2305.20050>. ICLR 2024.
- [131] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhonghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023. URL <https://arxiv.org/abs/2306.05685>.
- [132] Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning (ICML)*, 2023. URL <https://arxiv.org/abs/2210.10760>.
- [133] Nakyoung Lee, Sangwoo Hong, and Jungwoo Lee. Efficient process reward modeling via contrastive mutual information, 2026. URL <https://arxiv.org/abs/2604.10660>.

- [134] Hiroyasu Usami, Keisuke Hara, Ayato Tsuboi, and Naohiko Matsuda. LLM judges have dark current: A psychometric datasheet for LLM-as-a-judge evaluation, 2026. URL <https://arxiv.org/abs/2606.15610>.
- [135] Xiyan Fu and Wei Lu. When languages disagree: Self-evolving multilingual LLM judges, 2026. URL <https://arxiv.org/abs/2606.08092>.
- [136] Mengyuan Sun, Yu Li, Zhuohao Yu, Shikun Zhang, and Wei Ye. Support vector rubrics: Closing the gap between self-generated and human rubrics, 2026. URL <https://arxiv.org/abs/2606.08077>.
- [137] Weizhi Zhang, Zechen Li, Hamid Palangi, Ben Graef, A. Ali Heydari, Simon A. Lee, Sabera Rahman, Ray Luo, Zeinab Esmaeilpour, Erik Schenck, Chloe Zhang, Yamin Li, Menglian Zhou, Philip S. Yu, Daniel McDuff, Lindsey Sunden, Mark Malhotra, Shwetak Patel, and Ahmed A. Metwally. RubricsTree: Scalable and evolving open-ended evaluation of personal health agents across health memory and medical skills, 2026. URL <https://arxiv.org/abs/2606.18203>.
- [138] Siyi Gu, Jialin Chen, Sophia Zhou, Arman Cohan, and Rex Ying. Rethinking reward supervision: Rubric-conditioned self-distillation, 2026. URL <https://arxiv.org/abs/2606.19327>.
- [139] Shuaijie She, Yu Bao, Lu Yu, Lu Xu, Tao Li, Wenhao Zhu, Shujian Huang, Shanbo Cheng, L. Lu, and Yuxuan Wang. DuPO: Enabling reliable LLM self-verification via dual preference optimization, 2025. URL <https://arxiv.org/abs/2508.14460>.
- [140] Bentley DeVilling. The mirror loop: Recursive non-convergence in generative reasoning systems, 2025. URL <https://arxiv.org/abs/2510.21861>.
- [141] Chuyi Tan, Peiwen Yuan, Xinglin Wang, Yicheng Li, Shaoxiong Feng, Yueqi Zhang, Jiayi Shi, Ji Zhang, Boyuan Pan, Yao Hu, and Kan Li. Breaking the self-confirming loop: Diagnosing and mitigating systemic reward bias in self-rewarding RL, 2025. URL <https://arxiv.org/abs/2510.08977>.
- [142] Yoojin Nam, Jinhoon Jeong, and Namkug Kim. Deterministic integrity gates for LLM-assisted clinical manuscript preparation: An auditable biomedical informatics architecture, 2026. URL <https://arxiv.org/abs/2606.09500>.
- [143] Zonglin Yang, Xingtong Liu, and Xinyan Xu. SciIntegrity-bench: A benchmark for evaluating academic integrity in AI scientist systems, 2026. URL <https://arxiv.org/abs/2605.10246>.
- [144] Ilia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. AI models collapse when trained on recursively generated data. *Nature*, 631:755–759, 2024. doi: 10.1038/s41586-024-07566-y.
- [145] Jingwei Chen. Entropy-reservoir bregman projection: An information-geometric unification of model collapse, 2025. URL <https://arxiv.org/abs/2512.14879>.
- [146] Hector Zenil. On the limits of self-improving in large language models: The singularity is not near without symbolic model synthesis, 2026. URL <https://arxiv.org/abs/2601.05280>.
- [147] Xulu Zhang, Xiaoyong Wei, Jinlin Wu, Jiaxin Wu, Zhaoxiang Zhang, Zhen Lei, and Qing Li. Generating on generated: An approach towards self-evolving diffusion models, 2025. URL <https://arxiv.org/abs/2502.09963>.

- [148] Qihuang Zhong, Liang Ding, Juhua Liu, Bo Du, Leszek Rutkowski, and Dacheng Tao. Better, faster: Harnessing self-improvement in large reasoning models, 2026. URL <https://arxiv.org/abs/2605.24998>.
- [149] Jacob Dineen, Aswin RRV, Zhikun Xu, and Ben Zhou. Vocabulary dropout for curriculum diversity in LLM co-evolution, 2026. URL <https://arxiv.org/abs/2604.03472>.
- [150] Steven Young Eulig. Position: Correct answer, wrong mechanism – when AI scientists defend general claims their own data contradicts, 2026. URL <https://arxiv.org/abs/2606.23175>.
- [151] Jiachen Liu, Jiaxin Pei, Jintao Huang, Chenglei Si, Ao Qu, Xiangru Tang, Runyu Lu, Lichang Chen, Xiaoyan Bai, Haizhong Zheng, Carl Chen, Zhiyang Chen, Haojie Ye, Yujuan Fu, Zexue He, Zijian Jin, Zhenyu Zhang, Shangquan Sun, Maestro Harmon, John Dianzhuo Wang, Jianqiao Zeng, Jiachen Sun, Mingyuan Wu, Baoyu Zhou, Yuchen You, Shijian Lu, Yiming Qiu, Fan Lai, Yuan Yuan, Yao Li, Junyuan Hong, Ruihao Zhu, Beidi Chen, Alex Pentland, Ang Chen, Mosharaf Chowdhury, and Zechen Zhang. The last human-written paper: Agent-native research artifacts, 2026. URL <https://arxiv.org/abs/2604.24658>.
- [152] Razeen A Rasheed, Somnath Banerjee, Animesh Mukherjee, and Rima Hazra. From fluent to verifiable: Claim-level auditability for deep research agents. *Open MIND*, 2026. doi: 10.48550/arxiv.2602.13855. URL <https://arxiv.org/abs/2602.13855>.
- [153] Sy-Tuyen Ho, Minghui Liu, Huy Nghiem, and Furong Huang. SoundnessBench: Can your AI scientist really tell good research ideas from bad ones?, 2026. URL <https://arxiv.org/abs/2605.30329>.
- [154] Harshit Bisht, Vinay Kumar, Kevin Maik Jablonka, Mausam, and N. M. Anoop Krishnan. Agentic AI scientists are not built for autonomous scientific discovery, 2026. URL <https://arxiv.org/abs/2605.08956>.
- [155] Vincent Herrmann and Jürgen Schmidhuber. Interestingness as an inductive heuristic for future compression progress, 2026. URL <https://arxiv.org/abs/2605.14831>.
- [156] Prakhar Dixit and Tim Oates. ISM:self-improving strategy memory for continual mathematical reasoning, 2026. URL <https://arxiv.org/abs/2606.31191>.
- [157] Tao Feng, Chongrui Ye, Tianyang Luo, Jingjun Xu, Xueqiang Xu, Haozhen Zhang, Zhigang Hua, Yan Xie, Shuang Yang, Ge Liu, and Jiaxuan You. ExpGraph: Model-agnostic experience learning with graph-structured memory for LLM agents, 2026. URL <https://arxiv.org/abs/2605.30712>.
- [158] Huyu Wu, Jun Liu, Xiaochi Wei, Yan Gao, Yi Wu, and Yao Hu. Knowledge-graph paths as intermediate supervision for self-evolving search agents, 2026. URL <https://arxiv.org/abs/2605.05702>.
- [159] Fei Liu, Xialiang Tong, Mingxuan Yuan, Xi Lin, Fu Luo, Zhenkun Wang, Zhichao Lu, and Qingfu Zhang. Evolution of heuristics: Towards efficient automatic algorithm design using large language model, 2024. URL <https://arxiv.org/abs/2401.02051>.
- [160] Zijie Chen, Zhanchao Zhou, Yu Lü, Renjun Xu, Lili Pan, and Zhenzhong Lan. QUBE: Enhancing automatic heuristic design via quality-uncertainty balanced evolution, 2024. URL <https://arxiv.org/abs/2412.20694>.

- [161] Pham Vu Tuan Dat, L. Doan, and Huynh Thi Thanh Binh. HSEvo: Elevating automatic heuristic design with diversity-driven harmony search and genetic algorithm using LLMs, 2024. URL <https://arxiv.org/abs/2412.14995>.
- [162] John Donaghy and Shikhar Rastogi. DEI: Diversity in evolutionary inference for quality-diversity search, 2026. URL <https://arxiv.org/abs/2605.27130>.
- [163] Chaitanya Mamatha Ananda, Rajiv Gupta, Mircea Trofin, Aiden Grossman, Sriraman Tallam, Xinliang David Li, and Amir Yazdanbakhsh. AI-PROPELLER: Warehouse-scale inter-procedural code layout optimization with AlphaEvolve, 2026. URL <https://arxiv.org/abs/2606.00131>.
- [164] Shruthi Gorantala, Jianming Tong, Asra Ali, Baiyu Li, Jonathan Katz, Jeremy Kun, Thomas Steinke, Abhradeep Thakurta, Julian Walker, and Amir Yazdanbakhsh. Adapting AlphaEvolve to optimize fully homomorphic encryption on TPUs, 2026. URL <https://arxiv.org/abs/2605.14718>.
- [165] Boyun Zhang, Chao Wang, and Kai Wu. EVOM: Agentic meta-evolution of actor-critic architectures for reinforcement learning, 2026. URL <https://arxiv.org/abs/2606.26327>.
- [166] Sirui Xia, Yikai Zhang, Aili Chen, Siye Wu, Siyu Yuan, and Yanghua Xiao. From AI assistant to AI scientist: Autonomous discovery of LLM-RL algorithms with LLM agents, 2026. URL <https://arxiv.org/abs/2603.23951>.
- [167] Shangheng Du, Xiangchao Yan, Jinxin Shi, Zongsheng Cao, Shiyang Feng, Zichen Liang, Boyuan Sun, Tianshuo Peng, Yifan Zhou, Xin Li (51274), Jie Zhou, Liang He, Bo Zhang, and Lei Bai. MLEvolve: A self-evolving framework for automated machine learning algorithm discovery, 2026. URL <https://arxiv.org/abs/2606.06473>.
- [168] Yuanhang Zhang, Chesson Sipling, and Massimiliano Di Ventra. Scientific discovery as meta-optimization: a combinatorial optimization case study, 2026. URL <https://arxiv.org/abs/2606.26728>.
- [169] Yangzhen Wu, Aaron J. Li, Wenjie Ma, Li Cao, Ziheng Zhou, Mert Cemri, Shu Liu, Yuran Xiu, Chenxiao Yan, Haikun Zhao, Bin Yu, Ion Stoica, and Dawn Song. BenchEvolver: Frontier task synthesis via solution-centric evolution, 2026. URL <https://arxiv.org/abs/2606.01286>.
- [170] Yoichi Ishibashi, Taro Yano, and Masafumi Oyamada. Effective harness engineering for algorithm discovery with coding agents, 2026. URL <https://arxiv.org/abs/2605.15221>.
- [171] Temoor Tanveer. LEVI: Stronger search architectures can substitute for larger LLMs in evolutionary search, 2026. URL <https://arxiv.org/abs/2605.09764>.
- [172] Tony Feng, Trieu Trinh, Garrett Bingham, Dawsen Hwang, Yuri Chervonyi, Junehyuk Jung, Joonkyung Lee, Carlo Pagano, Sang hyun Kim, Federico Pasqualotto, Sergei Gukov, Jonathan N. Lee, Junsu Kim, Kaiying Hou, Golnaz Ghiasi, Yi Tay, Yaguang Li, Chenkai Kuang, Yuan Liu, Hanzhao, Lin, Nigamaa Nayakanti, Xiaomeng Yang, Heng-Tze Cheng, Demis Hassabis, Koray Kavukcuoglu, Quoc V. Le, and Quoc V. Le. Towards autonomous mathematics research. *Open MIND*, 2026. doi: 10.48550/arxiv.2602.10177. URL <https://arxiv.org/abs/2602.10177>.
- [173] Xianrui Zeng, Pengfei Liu, Yirui Zang, Yang Shen, Fei Yu, C Shijia Yu, M Y Liu, and Yang Du. Socratic agents for autonomous scientific discovery in high-dimensional physical systems, 2026. URL <https://arxiv.org/abs/2606.26722>.

- [174] Yougang Lyu, Xi Zhang, Xinhao Yi, Yuyue Zhao, Shuyu Guo, Wenxiang Hu, Jan A. Piotrowski, Jakub Kaliski, Jacopo Urbani, Zaiqiao Meng, Lun Zhou, and Xiaohui Yan. EvoScientist: Towards multi-agent evolving AI scientists for end-to-end scientific discovery. *Open MIND*, 2026. doi: 10.48550/arxiv.2603.08127. URL <https://arxiv.org/abs/2603.08127>.
- [175] Xinyu Zhu, Yuzhu Cai, Zexi Liu, Cheng Wang, Fengyang Li, Wenkai Jin, Wanxu Liu, Zehao Bing, Bingyang Zheng, Jingyi Chai, Shuo Tang, Rui Ye, Yuwen Du, Xianghe Pang, Yaxin Du, Tingjia Miao, Yuzhi Zhang, Ruoxue Liao, Zhaohan Ding, Linfeng Zhang, Yanfeng Wang, Weinan E, and Siheng Chen. EvoMaster: A foundational evolving agent framework for agentic science at scale, 2026. URL <https://arxiv.org/abs/2604.17406>.
- [176] Zihan Guo, Zeyi Chen, Zhiyu Chen, Zicai Cui, Shuai Shao, Bo Huang, Zhi Han, Y Song, Yuan Yuan, Chenxi Zeng, Xiaohang Nie, Zhengxi Yu, Hanwen Zhu, J G Liao, Ming Zhou, Yang Li, Yuanjian Zhou, and Weinan Zhang. Clarus: Coordinating autonomous research agents toward web-scale scientific collaboration, 2026. URL <https://arxiv.org/abs/2606.30246>.
- [177] Amy Xin, Jiening Siow, Junjie Wang, Zijun Yao, F Zhang, Jian Song, Lei Hou, and Juanzi Li. EurekAgent: Agent environment engineering is all you need for autonomous scientific discovery, 2026. URL <https://arxiv.org/abs/2606.13662>.
- [178] Antonis Antoniadis, Deepak Nathani, Ritam Saha, Alfonso Amayuelas, Ivan Bercovich, Zhaotian Weng, Vignesh Baskaran, Kunal Bhatia, and William Yang Wang. Heuresis: Search strategies for autonomous AI research agents across quality, diversity and novelty, 2026. URL <https://arxiv.org/abs/2606.25198>.
- [179] Zijian Wang, Hanqi Li, Ziyue Yang, Zijian Hu, Shenghan Zuo, Yunzhe Zhang, Da Ma, Danyu Luo, Chenrun Wang, Jie Peng, Tiancheng Huang, Sijia Guo, Huayang Wang, Zichen Zhu, Senyu Han, Yilu Cao, Kai Yu, Lu Chen, Kai Yu, and Lu Chen. Externalizing research synthesis and validation in AI scientists through a research harness, 2026. URL <https://arxiv.org/abs/2606.18874>.
- [180] Zhan Shi, Bing He, Yisi Sang, Hanqing Lu, and Benoit Dumoulin. A-evolve-training: Autonomous post-training of a 30b model, 2026. URL <https://arxiv.org/abs/2606.20657>.
- [181] J Y, Binfei Chu, Gao, Jinlu Zhang, Yiwei Ma, Yi Tan, Jiayi Ji, Xiaoshuai Sun, and Rongrong Ji. One reflection is not enough: Self-correcting autonomous research via multi-hypothesis failure attribution, 2026. URL <https://arxiv.org/abs/2606.31478>.
- [182] Ziru Chen, Shijie Chen, Yuting Ning, Qianheng Zhang, Boshi Wang, Botao Yu, Yifei Li, Zeyi Liao, Chen Wei, Zitong Lu, Vishal Dey, Mingyi Xue, Frazier N. Baker, Benjamin Burns, Daniel Adu-Ampratwum, Xuhui Huang, Xia Ning, Song Gao, Yu Su, and Huan Sun. ScienceAgentBench: Toward rigorous assessment of language agents for data-driven scientific discovery, 2024. URL <https://arxiv.org/abs/2410.05080>.
- [183] Zhengxin Zhang, Ning Wang, Sainyam Galhotra, and Claire Cardie. How far are we from true auto-research?, 2026. URL <https://arxiv.org/abs/2605.19156>.
- [184] Sasi Kiran Gaddipati, Diyana Muhammed, Farhana Keya, Gollam Rabby, and Sören Auer. MLReplicate: Benchmarking autonomous research systems for machine learning reproducibility, 2026. URL <https://arxiv.org/abs/2605.16616>.
- [185] Hongmin Li. The calibration turn in AI-assisted research: A conceptual and methodological framework for evidence-licensed claims, 2026. URL <https://arxiv.org/abs/2606.31273>.

- [186] H Huang. Grounded autonomous research: a fault-tolerant LLM pipeline from corpus to manuscript in frontier computational physics, 2026. URL <https://arxiv.org/abs/2607.02329>.
- [187] Kargi Chauhan. Dead science walking: Publication bias and the AI scientist pipeline, 2026. URL <https://arxiv.org/abs/2606.04220>.
- [188] Chen Zhu, Xiaolu Wang, and Weilong Zhang. (human) attention is (still) all you need: Human oversight makes AI-assisted social science reliable, 2026. URL <https://arxiv.org/abs/2606.12848>.
- [189] Tom Schaul. Boundless socratic learning with language games, 2024. URL <https://arxiv.org/abs/2411.16905>.
- [190] Shi Fu, Yingjie Wang, Shengchao Hu, Peng Wang, and Dacheng Tao. Why self-rewarding works: Theoretical guarantees for iterative alignment of language models. *Open MIND*, 2026. doi: 10.48550/arxiv.2601.22513. URL <https://arxiv.org/abs/2601.22513>.
- [191] Chien-Ping Lu. The computational boundary of inference: Capability internalization, training, and the turing jump, 2026. URL <https://arxiv.org/abs/2605.27381>.
- [192] Akbar Anbar Jafari, Cagri Ozcinar, and Gholamreza Anbarjafari. A mathematical framework for AI singularity: Conditions, bounds, and control of recursive improvement, 2025. URL <https://arxiv.org/abs/2511.10668>.
- [193] Parker Whitfill and C.H. Wu. Will compute bottlenecks prevent an intelligence explosion?, 2025. URL <https://arxiv.org/abs/2507.23181>.
- [194] Seth Dobrin and Łukasz Chmiel. The unfireable safety kernel: Execution-time AI alignment for AI agents and other escapable AI systems, 2026. URL <https://arxiv.org/abs/2606.26057>.
- [195] Toby Ord. Inference scaling reshapes AI governance, 2025. URL <https://arxiv.org/abs/2503.05705>.
- [196] Patricia Paskov, Jeffrey Lee, Kyle Brady, and Alyssa Worland. Measuring biological capabilities and risks of AI agents, 2026. URL <https://arxiv.org/abs/2606.19899>.