



SAP

Design Studio

tutorialspoint

SIMPLY EASY LEARNING

www.tutorialspoint.com



<https://www.facebook.com/tutorialspointindia>



<https://twitter.com/tutorialspoint>

About the Tutorial

SAP Design Studio can be defined as an Application Development Tool for creating advanced level Dashboards using SAP BW, HANA and Universe Data Sources. These interactive dashboards can be accessed on mobile devices like iPad, mobile phones, and tablets.

This Design Studio can also create applications that allow you to interact with data by applying different components like filters, drill down to dimensions and aggregated data detailed analysis, etc.

This is an introductory tutorial that covers the basics of SAP Design Studio and how to handle its various components and sub-components.

Audience

This tutorial will be extremely useful for professionals who aim to understand the basics of SAP Design Studio and implement it in practice. It is especially going to help professionals who are associated with Universe Data Sources, SAP Business Warehouse and HANA (High-Performance Analytic Appliance).

Prerequisites

It is a straightforward tutorial and the readers can easily understand the concepts explained here with a basic knowledge of how an organization deals with their application development tools and advanced dashboards. However, it will help if you have some prior exposure to HANA, SAP BW, SAP BusinessObjects BI Platform.

It will also be an additional help if the reader has a basic knowledge on how to interact with data by applying different components like filters, aggregated data detailed analysis, user interface components and applications, etc.

Copyright & Disclaimer

© Copyright 2016 by Tutorials Point (I) Pvt. Ltd.

All the content and graphics published in this e-book are the property of Tutorials Point (I) Pvt. Ltd. The user of this e-book is prohibited to reuse, retain, copy, distribute or republish any contents or a part of contents of this e-book in any manner without written consent of the publisher.

We strive to update the contents of our website and tutorials as timely and as precisely as possible, however, the contents may contain inaccuracies or errors. Tutorials Point (I) Pvt. Ltd. provides no guarantee regarding the accuracy, timeliness or completeness of our website or its contents including this tutorial. If you discover any errors on our website or in this tutorial, please notify us at contact@tutorialspoint.com

Table of Contents

About the Tutorial.....	i
Audience	i
Prerequisites	i
Copyright & Disclaimer.....	i
Table of Contents	ii
1. SAP DESIGN STUDIO – OVERVIEW	1
Design Studio Terminology.....	1
Roadmap of SAP Design Studio	4
2. SAP DESIGN STUDIO – KEY FEATURES.....	5
3. SAP DESIGN STUDIO – HOW TO LOGON	7
4. SAP DESIGN STUDIO – NAVIGATION	8
Welcome Page	8
Design Studio Navigation Views	9
Maintaining Settings in the Design Tool	13
5. SAP DESIGN STUDIO: CREATE AN APPLICATION.....	14
How to Create a New Analysis Application?	14
How to Set a Layout for a Component?	17
6. SAP DESIGN STUDIO – ADD DATA SOURCE	19
7. SAP DESIGN STUDIO – HANA CONNECTIVITY.....	22
How to Create a New Connection?.....	23

8.	SAP DESIGN STUDIO – SETTING UP BOOKMARKS	26
	Loading Bookmarks Using Scripting.....	26
	Loading Bookmarks Using URL	26
	Listing Bookmarks	27
	Saving and Sharing Bookmarks.....	28
	Deleting Bookmarks	28
9.	SAP DESIGN STUDIO – WORKING WITH DATA SOURCES.....	30
	How to Add More Dimensions in the Data Source?	31
10.	SAP DESIGN STUDIO – CONNECT TO A UDS.....	34
	How to Add Universe as a Data Source?	34
11.	SAP DESIGN STUDIO – EXPORTING DATA	39
12.	SAP DESIGN STUDIO – HANA MODE INTERACTIVE	42
	Connect to a Streaming Data Source	42
	Create a Time-Based Line on Real Time Streaming.....	44
13.	SAP DESIGN STUDIO – WORKING WITH INFO CHARTS.....	46
	Info Chart Feeding Panel	46
	Changing the Visualization Type.....	47
14.	SAP DESIGN STUDIO – WORKING WITH FILTERS.....	51
	Setting up an Analytic Component as a Filter	51
	Adding a Dimension Filter	52
	Editing a Filter	55
	Removing filter.....	56
15.	SAP DESIGN STUDIO – GEOMAP	57

16. SAP DESIGN STUDIO – EXPORTING AN APPLICATION	60
17. SAP DESIGN STUDIO – EXPORTING AS TEMPLATES.....	63
18. SAP DESIGN STUDIO – VISUALIZATION TEMPLATES.....	67
Creating Visualizations	67
Renaming a Visualization	68
19. SAP DESIGN STUDIO – CUSTOM DASHBOARDS	69
Sharing Dashboards	70
20. SAP DESIGN STUDIO – REFRESH A DOCUMENT	71
Refresh a Document in Web/Mobile (BW)	71

1. SAP Design Studio – Overview

SAP BusinessObjects Design Studio can be defined as an **Application Development Tool** for creating advanced level Dashboards using SAP BW, HANA and Universe Data Sources. These interactive dashboards can be accessed on mobile devices like iPad, mobile phones, and tablets.

To create applications and advanced Dashboards you don't need any knowledge of HTML and UI5 programming and you can subset of Java scripts and bookmarks for application development.

SAP Design Studio can be used with following data sources:

- SAP Business Warehouse (BW)
- SAP HANA
- SAP BusinessObjects BI Platform

It allows you to **design applications** and enter data manually in Crosstabs or you can also add data using planning objects while using SAP BW as the backend system. Applications developed in Design Studio can have real time connection to SAP HANA or the Business Warehouse System.

Using **SAP BusinessObjects Design Studio SDK**, you can also add 3rd party custom components in your application. These components can get data from different data sources to create interactive visualizations. Apart from this, SDK components can also act as data source for other SDK components.

Design Studio Terminology

Design Studio allows application developers to **create and edit applications** that are saved in the XML format. These applications contain interactive dashboards and advance data visualizations by using charts, crosstabs, etc. and alias of data source.


Data Source and Binding

You can create applications using different components like charts, crosstabs and data source alias. A Data source alias is defined as an instance of SAP BW or HANA data source. If you want to see the list of components that are used in an application, you can check this in outline view of Design tool.

Data Binding

To use different components like charts, crosstabs you need to bind the data from data source alias to these components. Data binding defines the simple mapping of data to components in application. When data in data alias is changed, Design Studio automatically updates all the components that are bound to that data alias.

To see the data binding relationship between components and data sources, you can go to the outline view.



In SAP BusinessObjects Design Studio, you can create applications that allow you to interact with data by applying different components like filters, drill down to dimensions and aggregated data detailed analysis, etc.


To enable users to interact with data, you need to add UI components in the application.

Example

You can create a Radio button on top of the chart to visualize the data for different regions in a sales analysis.

You can set an event with each button in a user interactive application. To see the list of all available components, you can navigate to Properties view of the Design Studio. All the events are defined in the script editor where you can mention the action to take place when an application user triggers a specific event.

The scripting language used in the script editor is a subset of Java script and you can define multiple sequences of API methods call.




Apart from scripting properties, there are various other properties that are defined in the Properties view. Some of the properties are common for all the components however a few are specific.

Example

Display properties define theme applied, position of message, message window, etc. and other properties of application. Layout property defines the positioning of the following components in an application:


- Top Margin
- Left Margin
- Right Margin
- Width
- Height



Roadmap of SAP Design Studio

Here is the roadmap of the SAP Design Studio along with its release month and year.

- SAP BusinessObjects Design Studio 1.4 Released Date: Nov, 2014
- SAP BusinessObjects Design Studio 1.5 Released Date: May, 2015
- SAP BusinessObjects Design Studio 1.6 Released Date: Dec, 2015



2. SAP Design Studio – Key Features

As per the Design Studio roadmap strategy, the following are the key features that are covered in the latest version of the SAP BusinessObjects Design Studio 1.6 SP2.

Features for the End-Users

- Resizable, movable dialogs
- Display scaling factors in Info Chart
- Waterfall Info Charts

Features for the Analyst

- Ad hoc currency conversion
- Build virtual hierarchy of stacked dimensions
- Cascading Filter for Universe and CSV as Data
- Source

Features for the Designer, Developer, and Administrators

- New standard components, e.g. Dialog, Filter Bar, Link, MultiLine Text Input, Switch, Progress Bar (SAP Fiori Library).
- Info Chart Enhancements
- Initial View Editor: Simple Calculations
- Designer UI Enhancement: Compact Palette View

Resizable, movable Dialog

- New component available in SAP Fiori library
- Container component
- Free defined buttons for dialog footer
- Movable, resizable and full screen maintained in property sheet

Displaying Scaling Factors in Info Chart

- Showing data label including scaling factor with Tooltips.

Waterfall Info Chart

- New chart type
- Semantic coloring (e.g. Negative, Positive and Total)
- Configurable connection line
- "Set as Total" possible in design time.

Adhoc Currency Conversion


- New API for opening currency conversion dialog
- Conversion based on target currency and conversion type defined in SAP BW backend
- Can be added as custom entry in context menu

Filter Bar

- New component in SAP Fiori library
- End user can select dimension filters to show and set filter value
- Toggle button to show or hide filter bar
- Defining "On Toggle" event via API

3. SAP Design Studio – How to Logon

To open SAP BusinessObjects Design Studio, go to **Start -> All Programs -> SAP Business Intelligence -> SAP BusinessObjects Design Studio -> Design Studio**



In the Logon to SAP BusinessObjects BI Platform dialog box, type in your user name and password for the BI Platform. When Design Studio is launched first time, you need to enter the following details:

- Host Name
- Port into the Web Service URL
- Select the authentication.
- Click OK

When you want to use SAP BW as backend, in the logon to SAP NetWeaver dialog box, select BW system from the drop down list and enter the system details and the username as well as the password.


In a similar way, you can also logon to SAP HANA dialog box, enter username and password for the HANA system.

4. SAP Design Studio – Navigation

In this chapter, we will discuss regarding the various navigation functions when you open SAP Business Objects Design Studio.

Welcome Page

When you open SAP BusinessObjects Design Studio, you land on the welcome page first. It consists of different sections, which are as follows:



Design Studio at the Top

SAP BusinessObjects Design Studio enables application designers to create analysis applications and dashboards for browsers and mobile devices on top of BW, SAP HANA, and Universe data sources.



Getting Started

This section allows you to access the help material to make you familiar with the tool and you can go through the video which will help you in how to document the tutorial guide to learn key features, concepts, and tasks of the Design Studio.



Other features include:

- **Create New:** This can be used to create a new analysis application.
- **Recently Used:** This can be used to access recently opened analysis applications in Design Studio.

Useful Links

This allows you to find useful information and access SAP Community Network, SAP Idea Place and SAP Help Portal.



Design Studio Navigation Views


When you start to create a new analysis application, you can see the following views in the Design Studio user interface:

Components View

This view provides you with a list of all the components that you can use to create a new analysis application. You can drag and drop different components in the layout to create the content of that application.

These components are grouped in different folders:

- **Analytic Components:** You can use different analytic components like charts and cross tabs.
- **Basic Components:** This folder contains basic components like check box, date field, image, input field, list box, etc.
- **Container Component:** This allows you to group and structure the content of an application.




Outline View

This view gives you a hierarchical structure of all objects in the currently active application. It consists of all the data sources and all the UI components.




Properties View

This shows the properties of the currently active object in an analysis application. It displays the property of the currently selected object in an outline view tree node or in the component editor.




Error Log View

This is used to display general errors related to system or messages for script validation.



Problems View


This is used to display the problem in scripting during the design time, when you save the application.



Layout Editor


For each application, an editor is opened that contains components for the application. When you make any changes to a component in editor area, it automatically reflects these changes to other views in the Design tool.

If you resize a component in the editor, it automatically changes the layout values under the Properties view of the Design tool. The same applies to the Outline and other views.



Maintaining Settings in the Design Tool

This is used to define the settings for a Design tool in the Preferences tab. To open the Preferences dialog box, go to **Tool -> Preferences -> Application Design**.



Storage of Applications and Images

Application files and images are stored in a folder on the BI platform. It is also possible to use images and logos in the analysis application from the internet.

- **Analysis Applications History:** The analysis applications history in the Application menu is persisted in your cache file – **<home directory>\sap\com.sap.ip.bi\cache**.
- **Data Source History:** The data source history in the Add Data Source dialog box is persisted in – **<home directory>\sap\com.sap.ip.bi\cache**.

5. SAP Design Studio – Create an Application

You can create new analysis applications in SAP Design Studio. SAP provides a list of predefined templates that are suitable to open in web browsers or mobile platform. You can select from a list of predefined templates and the system creates a copy of this template.

How to Create a New Analysis Application?

To create a new analysis application, navigate to **Application -> New**.




A new application dialog box opens, you can then enter the following fields:

- Name of the Application
- Description


Template Category

It is used to define the target device. When you want to create an analysis application for a desktop browser or a mobile device. When you can also change the type of your application by going to the Application properties view.



Click the Next button. Select the template for a new application as per the template category. You can also select a blank template to create an empty application.


You can also see a brief description of each template just below the template name as shown in the following screenshot.



Click the Finish button. You can add components from the component view to the editor area.

In the Components view, click on a component -> Drag and drop the component of your choice into the editor area.

Drag and drop the component of your choice into the Layout folder of the Outline view.



Enter a text in the filter text box at the top of the Components view, if you want to filter for a certain component.




The next step is to specify and change the properties of the components you have added to the application.

Click on a component in the editor area. Then you can click on a component in the Layout folder of the Outline view.

The properties of this component are available for editing under the Properties view. In the Properties view, click on the property you want to change. A field can have different values as per type:

- Numeric: Like for layout properties
- String: Like for caption, etc.
- Boolean: Like True/ false from drop down like for Style, etc. and
- Dialog box.


For a few special property types, you can open a dialog box by clicking on the value tab.



How to Set a Layout for a Component?

While setting layout for a component, you can adhere to the following points:

There are three properties that specify the position and size of a component in an application:



Margin (Top, bottom, left, right)

- **Width:** This tells the distance to the left margin and distance to the right margin along the horizontal axis.
- **Height:** This tells the distance to the top margin and the distance to the bottom margin along the vertical axis.

To allow relative resizing of the components as per the web browser, you need to set any of these three properties to automatic.




Please note that you cannot set all the three properties to automatic mode.


6. SAP Design Studio – Add Data source

In this chapter, we will discuss on how to add a data source in the design studio.


To add a data source, go to the **Outline View -> Data Sources folder**.




Right-click on the **folder -> New**




It will open the add data source wizard. To add a connection, click on the Browse tab and select the connection.



Once you select the connection, data source option will be enabled. Go to **Browse -> Search tab and enter the data source name.**




The data source alias is automatically assigned. Click on the OK button. Then the data source is added to the outline pane.




7. SAP Design Studio – HANA Connectivity

To allow SAP HANA connectivity, you can use the existing backend connections to Design Studio. Go to **Tool -> Preferences**.




In next window, **Application Design -> Backend connections**




How to Create a New Connection?


To create a new connection to SAP HANA using HDB ODBC drivers, click on the icon to add a connection.



In the ODBC Data Source Administrator, go to **System DSN** -> click on **Add**.




In a new window, you have to search for the HDB ODBC database drivers. These drivers get installed when you install SAP HANA client.




Click the Finish button.

In a new window, you need to enter the following details of the HANA system.

- Enter the Host name
- Port Number (3xx15, xx-instance number)
- User name and Password and click OK.



You can check the connectivity by clicking on the **Connect** button -> **Connection Successful**. To see the new connection, click on Reload connection. To use the connection, you may need to reopen the Design Studio.



8. SAP Design Studio – Setting Bookmarks

When you create an analysis application in the Design Studio, you can create bookmarks for reusability and flexibility. Bookmarks can be created for the snapshot of the full application or a part of it. There are three types of bookmarks that can be used in Design Studio:

- Standard
- Fragment
- Portable fragment

When an application developer wants to serialize the state of entire application, standard bookmark can be used. To use a selected part of an application, a fragment or portable fragment bookmark is used.

Loading Bookmarks Using Scripting

To load a bookmark in running analysis application, you can use scripting method.

To load a standard bookmark, you can use the following format:

```
Bookmark.loadBookmark(id);
```

Now to select a bookmark id, you can select from the drop down list.

```
var id = DROPDOWN_1.getSelectedValue();  
Bookmark.loadBookmark(id);
```

To load a fragment bookmark, you can use the following scripting method.

```
Bookmark.FragmentBookmark.loadBookmark(id)
```

To load a portable fragment bookmark, you can use the following scripting method.

```
Bookmark.PortableFragmentBookmark.loadBookmark(id)
```

Loading Bookmarks Using URL

You can also load bookmarks shared by other application user via a URL in the browser bar. All the bookmarks that are shared via a URL can't be directly added to the user lists of that bookmark.

You can bookmark the shared analysis application and that bookmark is then listed when calling the script method.

```
Bookmark.getAllBookmarks()
Bookmark.FragmentBookmark.getAllBookmarkInfos()
Bookmark.PortableFragmentBookmark.getAllBookmarkInfos(groupIdentifier)
```

You can also save the URL to browser favorites.

Listing Bookmarks

You can use the scripting API to allow application users to retrieve a list of their own bookmarks at runtime. The following script methods are used, depending on the type of bookmark involved.

How to List Standard Bookmarks?

The returned array contains a list of BookmarkInfo object types. A BookmarkInfo object contains BookmarkId id, String name and String text. Both the String name and BookmarkId id refers to the bookmark id. The string text refers to the bookmark title. Any selection component like a Dropdown box or a List box can be populated with the array returned from the Bookmark.getAllBookmarks(); method.

```
var array = Bookmark.getAllBookmarks();
array.forEach(function(element, index)
{ DROPDOWN_1.addItem(element.name, element.text);
});
```

How to List Fragment Bookmarks?

You can list the fragment bookmarks to return the list of all fragment bookmarks for an analysis application:

```
var array = Bookmark.FragmentBookmark.getAllBookmarkInfos();
array.forEach(function(element, index)
{ DROPDOWN_1.addItem(element.id, element.title);
});
```

How to List Portable Fragment Bookmarks for all the Applications?

You can use the following scripting method.

```
Bookmark.PortableFragmentBookmark.getAllBookmarkInfos();
```

This returns a list of all portable fragment bookmarks specified by the Group Identifier parameter. You can populate the Fragment Gallery with all portable fragment bookmarks created by the user using the **FragmentGallery_1.addItem();** scripting method.

```
var array =
Bookmark.PortableFragmentBookmark.getAllBookmarkInfos("groupIdentifier");
FRAGMENTGALLERY_1.addItem(array);
```

Saving and Sharing Bookmarks

In SAP Design Studio, an application user can save their bookmarks using the API scripting. You can save standard bookmarks with a unique title mentioned by the users.

You can use the following script to save a standard bookmark.

```
var id = Bookmark.saveBookmark();
var id = Bookmark.saveBookmark("title")
```

You can also save a fragment bookmark using the following method.

```
var fragInfo = Bookmark.FragmentBookmark.saveBookmark(ContainerComponent);
```

You can use method an Optional **BookmarkInfo toOverWrite** – to overwrite an existing fragment bookmark.

Sharing a Bookmark

Application designers can also share their bookmarks using a scripting method. You can run the following scripting method as per the type of the bookmark.

To share a standard bookmark, you can apply: **Bookmark.shareBookmark(String URL)** scripting method.

To share a fragment bookmark, you can apply:

Bookmark.FragmentBookmark.shareBookmark(String URL) scripting method.

To share a portable fragment bookmark, you can apply:

Bookmark.PortableFragmentBookmark.shareBookmark(String URL) scripting method.

Deleting Bookmarks

In SAP Design Studio, each bookmark owns a parent application. When you delete a parent application, its child bookmarks are deleted. To delete these bookmarks, you can use scripting API methods.

The following scripts can be used as per the bookmark type.

How to Delete Standard Bookmarks?

You can use the following script to allow the application user to delete their own standard bookmarks.

```
Bookmark.deleteBookmark(id);  
Bookmark.deleteAllBookmarks();
```

How to delete Fragment Bookmarks?

You can use the following script to allow the application user to delete their own fragment bookmarks.

```
Bookmark.FragmentBookmark.deleteBookmark(id);  
Bookmark.FragmentBookmark.deleteAllBookmarks();
```

How to delete Portable Fragment Bookmarks?


The following scripting method is used to allow the application user to delete their own portable fragment bookmarks.

```
Bookmark.PortableFragmentBookmark.deleteBookmark(id)  
Bookmark.PortableFragmentBookmark.deleteAllBookmarks(groupIdentifier)
```


9. SAP Design Studio – Working with Data Sources

In SAP Design studio, you can work with data sources, edit the initial view of data source, add dimensions and measures to crosstabs and charts, etc.

We have added the following data source under the Outline view of the Design Studio.



To edit an initial view of the data source, right click on the **Data Source Name -> Edit Initial View**.



In the next window, you can see a list of all the dimensions and measures in the data source.

Edit Initial View of DASSET - DS_1

Columns

- Measures
 - Quantity
 - Number of Records

Rows

- Company code - OCOMP_CODE

Live Preview (8 data cells)

Company code	Quantity	Number of Records
1000	1000	0.000
3000	3000	0.000
#	Not assigned	0.000
Overall Result	0.000	3

How to Add More Dimensions in the Data Source?

You can also add more dimensions and measures by dragging objects from the left pane to the Rows and columns box.

Edit Initial View of DASSET - DS_1

Columns

- Measures
 - Quantity
 - Number of Records

Rows

- Company code - OCOMP_CODE
- Asset class - DASSET_CLAS

Live Preview (8 data cells)

Company code	Asset class	Quantity	Number of Records
1000	1000	Not assigned	0.000
3000	3000	Not assigned	0.000
#	Not assigned	Not assigned	0.000
Overall Result		0.000	3

You can also change the order of dimensions and measures. You can select the dimension and drag it up or down as per the requirement. Data in the crosstab also changes as per the selection.

Edit Initial View of DASSET - DS_1

Columns: Measures

Rows: Asset class - DASSET_CLAS, Company code - OCOMP_CODE

Live Preview (8 data cells):

Asset class	Company code	Quantity	Number of Records
Not assigned	1000	1000	0.000
	3000	3000	0.000
	#	Not assigned	0.000
	Result	0.000	3

You can also remove the extra columns from the crosstab. Select the column from the dimension/measures and move it to the left pane.

Edit Initial View of DASSET - DS_1


Columns: Measures

Rows: Asset class - DASSET_CLAS, Company code - OCOMP_CODE

Live Preview (8 data cells):

Asset class	Company code	Quantity	Number of Records
Not assigned	1000	1000	0.000
	3000	3000	0.000
	#	Not assigned	0.000
	Result	0.000	3


Once you remove the extra column, data in the crosstab will also change accordingly.



Asset class	Company code	Quantity
Not assigned	1000	0.000
Not assigned	3000	0.000
#	Not assigned	0.000
Result		0.000

You can also perform various other functions on the selected values, some of which are:

- Decimal places
- Scaling
- Calculate Total As
- Sort




Asset class	Company code	Quantity
Not assigned	1000	0.000
Not assigned	3000	0.000
#	Not assigned	0.000
Result		0.000

10. SAP Design Studio – Connect to a UDS


You should connect to BI platform to add data source to a new analysis application in Design Studio. You have to connect to BI platform at the time of login.

To connect to a **Universe Data Source (UDS)**, go to the Data Source folder under Outline in a new analysis application – **Right click -> Add Data Source**.




How to Add Universe as a Data Source?


Let us see how to add Universe as a data source. Click on Browse tab against Connection in the Add Data Source window.



Select **eFashion.unx** file to add a connection. You can also filter the connection from the available list.




The next step is to edit the query panel. For this, you have to click on the Edit query specification.




Add the dimensions and measures to result objects. You can expand each of these folders in the left pane and add objects to dimensions and measures.

Once you select all the objects, click on the OK button of the query panel. This query will be added to the add data source window. Click on OK to add this to the Data source folder under the Outline view.




To edit the initial view, right click on the **Data Source -> Edit Initial View**. The measures will be added to the preview tab directly.



Add the dimensions selected in the query to Row tab.

In the following screenshot, we have added State and Category to come with measure values. You can apply formatting to measure values.

Click OK and then click on Create Cross tab.



A Cross tab has been added to the editor area and this is how you can connect to the Universe Data Source.

The screenshot displays the SAP Design Studio interface. On the left, the 'Components' pane shows a tree structure under 'Test_New_Ana' with 'Data Sources' containing 'eFashion.univ - DS_1'. The 'Outline' pane shows a 'CROSSTAB_1 - DS_1' object. The main editor area shows a cross-tab visualization with the following data:


State	Category	Sold at (unit price)	Sales revenue	Quantity
California	2 Pocket shirts	196.42	229,420.10	
	Belts,bags,wallets	157.27	297,074.20	
	Bermudas	171.07	16,080.70	
	Boatwear	163.57	54,468.60	
	Cardigan	153.13	160,477.60	
	Casual dresses	141.80	65,229.10	
	Day wear	122.08	157,236.90	
	Dry wear	212.12	45,606.10	
	Evening wear	140.91	315,782.20	
	Fancy fabric	167.39	40,508.90	
Full length	191.04	49,287.60		
Hair accessories	189.86	45,567.20		

On the right, the 'Properties' pane shows the configuration for the cross-tab:


- General:** Name: CROSSTAB_1, Type: Crosstab, Visible: true.
- Data Binding:** Data Source: DS_1.
- Optimization for Low:** Pixel-Based Sort: false, Row Limit: 20, Column Limit: 20.
- User Interactivity:** Selection Type: None, Selectable Area: All, Enable Hover: true, Hierarchy Navig.: true, Sorting Enabled: true, Column Resizing: true, Horizontal Head: false, Horizontal Scroll: false, Context Menu: true.
- Display:** No additional properties available.

11. SAP Design Studio – Exporting Data


We have a crosstab in SAP Design Studio Editor and we want to **export the data from a Crosstab to Microsoft Excel**. Add a button from the basic components to the Editor as shown in the following screenshot.



Under Display, add Text – **Export to Excel**.




Go to Event and add a script as shown in the following screenshot.




Script to export to Excel

```
APPLICATION.export(ExportType.EXCEL_xlsx,[(CROSTAB_1)]);
```



Now execute the application using the arrow mark at the top. Once it is run, click on Export to Excel.






Click on Open or Save to open the excel sheet or to save the sheet to your system.

State	Category	Sold at (unit price)	Sales revenue	Quantity sold	Margin	Discount
California	2 Pocket shirts	196.42	229,420.10	1,168.00	80,782.60	0.00
California	Belts,bags,wallets	157.27	297,074.20	1,889.00	112,598.30	0.00
California	Bermudas	171.07	16,080.70	94.00	5,415.80	0.00
California	Boatwear	163.57	54,468.60	333.00	24,125.00	0.00
California	Cardigan	153.13	160,477.60	1,048.00	53,123.20	0.00
California	Casual dresses	141.80	65,229.10	460.00	21,769.70	0.00
California	Day wear	122.08	157,236.90	1,288.00	58,353.70	0.00
California	Dry wear	212.12	45,606.10	215.00	20,231.60	0.00
California	Evening wear	140.91	315,782.20	2,241.00	132,871.90	0.00
California	Fancy fabric	167.39	40,508.90	242.00	17,486.50	0.00
California	Full length	191.04	49,287.60	258.00	19,581.50	0.00
California	Hair accessories	189.86	45,567.20	240.00	13,007.80	0.00
California	Hats, gloves, scarves	131.97	337,326.20	2,556.00	129,747.90	0.00
California	Jackets	150.01	52,352.30	349.00	16,950.70	0.00
California	Jeans	191.50	53,811.80	281.00	20,753.90	0.00
California	Jewelry	158.72	1,018,829.10	6,419.00	391,240.70	0.00
California	Long lounge pants	169.86	32,102.80	189.00	13,377.80	0.00
California	Long sleeve	163.80	252,581.30	1,542.00	100,011.70	0.00
California	Lounge wear	146.96	106,249.80	723.00	37,655.90	0.00
California	Mini city	185.84	25,646.40	138.00	9,018.30	0.00
California	Night wear	241.82	9,914.70	41.00	3,952.30	0.00
California	Outdoor	161.61	57,857.40	358.00	22,091.60	0.00
California	Pants	218.20	9,382.60	43.00	5,052.50	0.00
California	Party pants	135.18	254,672.10	1,884.00	84,694.20	0.00


12. SAP Design Studio – HANA Mode Interactive

The SAP Design Studio starts locally and it is possible to change the setting to SAP HANA mode by going to **Tools -> Preferences**.

In Application Design, you need to select SAP HANA as the design mode instead of local and you can use SAP HANA as the data source to design applications.



You need to restart and when in the start-up mode change it to Design Studio. Once you click on OK, it will ask you to restart the Design Studio.




You can add a data source using SAP HANA connection now.


Connect to a Streaming Data Source

Streaming data sources in SAP allows you to create visualization on real time data in the Design Studio. To connect to a streaming data source, you should have real time package installed and Design Studio 1.4.


You can download these from SAP Marketplace. To install Real time package, go to **Tools -> Install Extension to Design Studio**.



You can check real time functionality by going to the Help tab.



Along with the real time package, you need SAP Enterprise streaming package **ESP SP9**.




Create a Time-Based Line on Real Time Streaming

Time based line charts can handle null values if there is break in data as compared to the standard line charts.


Your streaming data source is also configured and connected to ESP.




Add your chart component to the editor area in the Design Studio.



Drag the data source to the chart as shown in the following screenshot.



You can go to the chart type to select Additional charts from the drop down list.




13. SAP Design Studio – Working with Info Charts

Info charts can be found in SAP Design Studio under the Analytic components. This is a new feature available in the Design Studio 1.6. You can configure info charts independently of the initial view. When you configure info charts, dimensions from the data sources is bound to specific chart areas.

You can have two dimensions in a row in the Info chart which was not possible in normal charts in the Design Studio.

Info charts can be considered as the main component for creating new Dashboards in the Design Studio 1.6 however other chart types are also available.



Info Chart Feeding Panel

You can configure Info charts like other charts in the Chart editor. You have to drag the chart component to the canvas and add a data source from the outline view. When you assign a data source, a chart is created as per the values.

To configure an info chart, you have to go to the chart configuration properties. You can perform the following functions in the properties tab.


- Change the dimension by dragging to each group. The available group depends on the chart type selected for the Info chart.
- You can also change measure the assignment in the chart type.
- You can also change the chart type.

Features

Chart type picker and chart feeding panels are two features that you can use with Info Chart. The feeding panel is a component that allows you to bind dimensions and measures with chart area.

You can configure the chart at run time and dimensions and measure changes as per binding.

Chart type picker allows you to select the chart type which is suitable. Chart type picker works with both charts and info charts.



To add chart type picker, it is available under the list of basic components.

Note: Info Charts also support the scripting method that are used in the Chart component regarding selection and behavior.

Changing the Visualization Type


To analyze the data in different ways, you can select different visualizations. Select a different visualization type from the dropdown arrow to the right of a group within the Chart Type Picker palette.

Your visualization type changes accordingly to render your data in a different way.


Conditional Formatting

You can use Conditional formatting to change the chart appearance when a specified condition is met. This feature allows you to add conditional formatting rules to measures or dimensions in chart components. These rules change the chart appearance when a specific condition is met.

To apply conditional formatting to a chart, select the chart component and go to the Properties tab.




Click on the browse button, a new window will open. Select New rule to add a new rule for conditional formatting.



Choose New Rule -> A New Rule dialog box opens.

In the Name textbox, enter a title to identify your new conditional formatting rule.



Within the Rule Description area of the Conditional Formatting dialog box, select either Measure or Dimension Member from the dropdown list. The dropdown list is populated from the data set you have applied to your chart.


You can apply to the following data set to your chart.

Select one of the following:

- is equal to
- is greater than
- is less than


Enter the value to be assigned to the new rule.

Within the Preview area of the dialog box, choose the Format button to assign a color to your rule. Choose a color from the pre-defined color picker or define a custom color by choosing the Define Custom Colors button.



The 'Edit Rule' dialog box is shown. It has a 'Name' field at the top. Below it is the 'Rule Description' section, which contains a 'Measure' dropdown menu, a 'Discount' dropdown menu, an 'is equal to' dropdown menu, and a text field containing '100000'. A green arrow points to the 'Rule Description' label. Below the 'Rule Description' section is a 'Preview' section. In the preview, there is a red bar and a 'Format...' button. A green arrow points to the 'Format...' button. At the bottom right are 'OK' and 'Cancel' buttons.

Click OK.




14. SAP Design Studio – Working with Filters

Filters are used to limit the data in visualization in SAP Design Studio. You can create different types of filters and use analytic components and basic components to set up filters.

Setting up an Analytic Component as a Filter

To set an analytic component as a filter, you need to enable the selection that allows the user to select the individual component.



Select **Analytic component -> Properties Pane**, under **Events Enable -> True**. Go to Onset to add a script to this event. You can use the **setFilter** script method to set the filter.

In the script, you need to select the Data source, scripting method, dimension and value.



```
DS.setFilter("00_Sold_To",  
CROSSTAB.getSelectedMember("00_Sold_To").internalkey);
```



Save the application and run it locally. Select the Sold to Party component.



You can also set up a basic component as filter in the similar manner.

Adding a Dimension Filter

To add a dimension filter, select a filter from the analytic components and drag it to the canvas area.

Components

type filter text

Analytic Components

Dimension Filter ←

Filter Line

Basic Components

Button

Chart Type Picker

Container Components

Grid Layout

Pagebook

Outline

type filter text

Test_Analysis

Data Sources


eFashion.unx - DS 1

Category ▲	Lines ▲	Sales revenue ▲	Quantity sold ▲	Margin ▲
2 Pocket shirts	Shirt Waist	492 1,072,995.70	5,442.00	378,570.30
	Total	1,072,995.70	5,442.00	378,570.30
Belts,bags,wallets	Accessories	1,642,491.90	10,894.00	609,188.20
	Total	1,642,491.90	10,894.00	609,188.20
Bermudas	City Trousers	105,170.90	617.00	34,181.40
	Total	105,170.90	617.00	34,181.40
Boatwear	Jackets	245,044.40	1,487.00	110,169.50
	Total	245,044.40	1,487.00	110,169.50
Cardigan	Sweaters	921,793.80	6,135.00	289,717.90
	Total	921,793.80	6,135.00	289,717.90
Casual dresses	Dresses	382,702.80	2,646.00	129,478.70
	Total	382,702.80	2,646.00	129,478.70


Select a dimension

Go to the Properties tab of the **Dimension filter** -> **Data Binding**. Then Under Data Binding, select a data source.

Go to dimension, and select the dimension on which you want to apply the filter.




Select the Data source and dimension as shown in the following screenshot and then save the application.



Once the application is saved, then you can run the application locally.






The screenshot shows a web browser window with the URL `http://localhost:50175/aad/zen?APPLICATION=Ad...`. The main content is a table with the following data:

Category	Lines	Sales revenue	Quantity sold	Margin
2 Pocket shirts	Shirt Waist	1,072,995.70	5,442.00	378,570.30
	Total	1,072,995.70	5,442.00	378,570.30
Belts,bags,wallets	Accessories	1,642,491.90	10,894.00	609,188.20
	Total	1,642,491.90	10,894.00	609,188.20
Bermudas	City Trousers	105,170.90	617.00	34,181.40
	Total	105,170.90	617.00	34,181.40
Boatwear	Jackets	245,044.40	1,487.00	110,169.50
	Total	245,044.40	1,487.00	110,169.50
Cardigan	Sweaters	921,793.80	6,135.00	289,717.90
	Total	921,793.80	6,135.00	289,717.90
Casual dresses	Dresses	382,702.80	2,646.00	129,478.70
	Total	382,702.80	2,646.00	129,478.70

To the right of the table is a dimension filter for 'Category' with a dropdown arrow. A green arrow points to this filter.

Click on the dimension Filter and you will be prompted to select a dimension value from the available list. You can also go to the range tab to put a start and end value.



The screenshot shows the 'Category' dimension filter dialog. It has a 'Back' button, an 'Apply' button, and two tabs: 'Selection' and 'Range'. A green arrow points to the 'Selection' tab. Below the tabs is a 'Select Members' section with a search bar and a list of categories. A green arrow points to the 'Bermudas' row in the list.

Text	Key	
2 Pocket shirts	2 Pocket shirts	<input type="checkbox"/>
Belts,bags,wallets	Belts,bags,wallets	<input type="checkbox"/>
Bermudas	Bermudas	<input type="checkbox"/>
Boatwear	Boatwear	<input type="checkbox"/>
Cardigan	Cardigan	<input type="checkbox"/>
Casual dresses	Casual dresses	<input type="checkbox"/>
Day wear	Day wear	<input type="checkbox"/>
Dry wear	Dry wear	<input type="checkbox"/>
Evening wear	Evening wear	<input type="checkbox"/>
Fancy fabric	Fancy fabric	<input type="checkbox"/>
Full length	Full length	<input type="checkbox"/>
Hair accessories	Hair accessories	<input type="checkbox"/>

Once you select the dimension, data in component is filter accordingly. To apply the filter settings, click on the Apply button.

The screenshot shows a data table on the left and a 'Select Members' dialog on the right. The table displays sales data categorized by clothing items. The dialog allows selecting members for the 'Category' dimension.

Category	Lines	Sales revenue	Quantity sold	Margin
2 Pocket shirts	Shirt Waist	1,072,995.70	5,442.00	378,570.30
	Total	1,072,995.70	5,442.00	378,570.30
Belts,bags,wallets	Accessories	1,642,491.90	10,894.00	609,188.20
	Total	1,642,491.90	10,894.00	609,188.20
Bermudas	City Trousers	105,170.90	617.00	34,181.40
	Total	105,170.90	617.00	34,181.40
Boatwear	Jackets	245,044.40	1,487.00	110,169.50
	Total	245,044.40	1,487.00	110,169.50
Total		3,065,702.90	18,440.00	1,132,109.40

The 'Select Members' dialog shows a list of categories with checkboxes. The 'Category' dimension is selected, and the 'Apply' button is highlighted.

Editing a Filter

To edit a filter in SAP Design Studio, go to the Outline tab and under the Layout folder. There you can see a list of all the filters that are applied in an application. To edit an application, select the filter you want to edit.

The screenshot shows the 'Outline' tab on the left, displaying a tree structure of the application components. The 'Layout' folder is expanded, showing 'DIMENSIONFILTER_3 - DS_1' selected. The data table on the right shows sales data for 'Casual dresses'.

Casual dresses	Total	382,702.80
Select a dimension		

Go to the Properties tab of the selected filter and make changes as required. Save the changes that you have made and run the application to reflect the changes.

The screenshot shows a data table on the left and a Properties panel on the right. The table has columns for 'Category', 'Sales', and 'Margin'. The Properties panel is for a filter named 'DIMENSIONFILTER_3'.

Category	Sales	Margin
5,442.00	378,570.30	
5,442.00	378,570.30	
10,894.00	609,188.20	
10,894.00	609,188.20	
617.00	34,181.40	
617.00	34,181.40	
1,487.00	110,169.50	
1,487.00	110,169.50	
6,135.00	289,717.90	
6,135.00	289,717.90	
2,646.00	129,478.70	
2,646.00	129,478.70	

Property	Value
General	
Name	DIMENSIONFILTER_3
Type	Dimension Filter
Visible	<input checked="" type="checkbox"/> true
Data Binding	
Data Source	DS_1
Target Data Source	
Dimension	OBJ_508
Display	
CSS Class	
Dimension Name	<input checked="" type="checkbox"/> true
Display Mode	Filter List
Member Display	Text and Key
Popup Width	350
Popup Height	500
Popup Position	Default
Popup is Modal	<input checked="" type="checkbox"/> false
Remove Redundant	<input checked="" type="checkbox"/> false
Auto Apply	<input checked="" type="checkbox"/> false

Removing filter

To remove a filter in an analysis application, go to **Outline View -> Layout**. Select the filter you want to remove. Right click and you will get all the following options.

The screenshot shows the Outline View on the left and a data table on the right. The Outline View shows a tree structure with 'Test_Analysis' selected. A context menu is open over 'DIMENSIONFILTER_2' in the 'Layout' folder.

Casual dresses	Total	382,702.80	2,646.00	129,478.70
Select a dimension				

- Copy
- Paste
- Rename
- Delete**
- Hide
- Find References

Click on **Delete** to delete the selected filter as shown in the above screenshot.

You can also Copy, rename or check reference of each filter in an analysis application from here.

15. SAP Design Studio – Geomap

In SAP Design Studio, you can use a Geomap to display different layers of geographical information. These Geomaps are available under the Analytic components and can be added by simply dragging them to the canvas.


As per the Geomap properties and scripting defined in the Geomap component, each layer shows different data as per the user interaction. To use Geomaps, the data source should contain countries, regions, longitudes, etc.

The screenshot displays the SAP Design Studio interface. On the left, the 'Components' pane shows 'Analytic Components' with 'Geo Map' highlighted. Below it, the 'Outline' pane shows a tree structure for 'Test_Analysis' including 'Data Sources', 'Planning Objects', 'Layout', and 'Technical Components'. The 'Layout' section contains 'CROSSTAB_2 - DS_2', 'DIMENSIONFILTER_3 - DS_1', and 'GEO_MAP_1'. The main canvas area shows a world map with a blue pin labeled 'LAYER_1 Location' in North America. Above the map is a table with the following data:

State	Sales revenue	Quantity sold	Margin	Discount
California	7,479,569.30	46,074.00	2,972,909.90	1,299,909.73
Colorado	2,060,275.20	12,787.00	806,149.20	343,370.47
DC	2,961,949.90	18,744.00	1,153,001.40	582,601.15
Florida	1,879,158.50	11,267.00	777,281.10	187,349.56
Illinois	3,022,658.40	17,976.00	1,254,092.70	273,716.60
Massachusetts	1,382,386.60	7,676.00	511,692.00	244,389.31

On the right side of the map, there is a 'Category' dropdown menu. The map itself includes zoom controls (+, -) and a scale bar at the bottom right.

To start with Geomaps, drag the Geomap from analytic components to the Canvas area and add the data source to the Outline view. The data source added will also reflect under **Additional Properties -> Data Source**.




Go to Edit Initial view of the data source, you need to select only one Geo dimension under Rows and measures under column tab.

You can select the Geo Map in the layout pane. In the Properties tab, enter the URL for your selected basemap in the Basemap URL property. It is also an option to leave this blank, if no basemap is required.




The Map Legend Visible property is set to true by default. If you wish to hide the legend on all your Geo Map layers, you can set this property value to false.

You can also add or remove layers to a Geomap. This can be done by using Add layer button in the Geomap.



A new layer Id is added for each layer, you can select the Data source and measure values.




To remove a layer, you need to click on the cross button at the top right corner under Additional Properties.


16. SAP Design Studio – Exporting an Application

In SAP Design Studio, you can also export your analysis applications to the local machine or to a network shared drive. This allows you to export the source code to send to SAP for resolving errors or to use on a different BI platform. You can also perform regular backup of your analysis application using export options.

To export an application, select the application and then click on Export under Application tab at the top. If your application is not saved, you will be prompted to save the application.



You can select any other application by clicking on the Browse button. By default, it shows the open analysis application.




To have the MIME objects example – images or CSS files which are referenced in the application or exported, you should keep the Export referenced files checkbox activated.

The system analyzes the selected application and auto-detects all MIME objects referenced by the application. If you have MIME files that the system cannot auto-detect, choose Add File... and then select the required files.

Click on Next.

To select the target folder on your local PC or on a network share, click on Browse.

You can change the default name of the ZIP file, enter the required name under the ZIP File Name.




The default name of the ZIP file is the name of the application suffixed with a timestamp as shown in above screenshot.


17. SAP Design Studio – Exporting as Templates

In SAP Design Studio, you can use your analytic application to be used as the template for other application designers.

To export an application as a template, **Select Application -> Application Tab- > Export as Template.**



You can select any other application by clicking on the browse button. By default, it shows the open analysis application.




To have the MIME objects example – images or CSS files which are referenced in the application, exported, keep the Export referenced files checkbox activated.


The system analyzes the selected application and auto-detects all MIME objects referenced by the application. If you have MIME files that the system cannot auto-detect, choose Add File... and select the required files.

Click the Next button.

Select the template folder or network drive. Enter the **Template Name -> Select the Template Category** from – Desktop, iPad, iPhone as shown in the following screenshot.



You can also add your own categories by going to **Configure Categories -> Preferences**. To add a new template category, click on the Add button and then you can Enter the new category name.



Template Caption is used to enter the name of the template to be displayed in the New Application dialog box.

Note: This name is case-sensitive.

Under Template Description, you can describe the content and purpose of your template.

This description is displayed in the New Application dialog box and can help other application designers identify which template to select.

Click Finish.

You can find the new template in the selected folder with the **content.biapp** file and an **.info file** with the template description.

Printing an Application to a browser

You can also print your analysis application to a web browser in the SAP Design Studio. This feature is not supported when you use SAP Design Studio mobile solution.

To print an analysis application to browser, select the component to call Print function. This will print your analysis application to your web browser.

18. SAP Design Studio – Visualization Templates

In SAP Design Studio, you can create custom dashboards using visualization templates representing data from different data sources. You can use SAP BW or SAP HANA as the data source.

Open the online self-service data discovery and visualization application. In next window you will be prompted to connect to a recently used query or a data source.

You can select from the following two options:

- You can select recently used queries to select a query from a list of all the queries you have already used till date.
- You can also select a system to select the data source and the query you want to assign to your dashboard, if there are no recently used queries listed.

Select Next and OK.


The default Visualize page opens, displaying the measure and dimensions from your selected data source.

Creating Visualizations

Go to Visualize page, drag and drop dimensions to the rows or columns area.


The default visualization in the layout area changes automatically to reflect your dimension selection and the created visualization is automatically saved to the gallery.

Select the member you want to display to the X-axis and the Y-axis.



Renaming a Visualization

You can rename the visualizations according to the queries that are used to create them. To rename a visualization select the cogwheel at the top under the Visualize tab as shown in the following screenshot.



You can select Rename to change the name of the title.


Restore Default Title – This can be used to restore the title to default as per the query.

19. SAP Design Studio – Custom Dashboards


You can create number of visualizations and add them to the gallery and they can be used to create dashboards by arranging them in a story under the Compose tab.

This allows you to create a custom dashboard, you can change the data sources and visualization also gets changed in the Visualize tab.

Go to the Compose page at the top, the gallery shows all the current visualizations. To create custom dashboards, drag and drop the visualizations from the gallery to the layout area.




To create a new custom dashboard, select the New Story button.



You can add title to your dashboard and then click on Create.

Sharing Dashboards

You can share the dashboards as bookmarks with other users. You can also export them to PDF format as shown in the following screenshot.



20. SAP Design Studio – Refresh a Document

To refresh a document in Design Studio, a request is sent via the Web browser or a mobile client. The following are the key steps involved in data refresh:

Step 1: To perform a refresh on Design Studio document, the user sends an HTTP request to the web browser or the mobile client to the web application server. The web application server forwards this request to the Central Management Server (CMS) to find the analysis application. The CMS server is also responsible to check if the user has access to refresh the document or not.

Step 2: A request is sent to Analysis application server to get the current data for Design Studio document. An Analysis application service gets the current data from SAP HANA using the JDBC driver.

Step 3: The Analysis application service creates the document with the latest data from SAP HANA and send it back to the Web Application server.

Step 4: The last step is that Web application server converts the data to HTML format and send it to web browser or mobile client where Design document refresh data is displayed.

Refresh a Document in Web/Mobile (BW)

To refresh a Design Studio document is the same in SAP BW except that the refresh is performed using a BICS connection on a RFC call as compared to HANA using JDBC drivers.

To refresh a document in the Design Studio in web/mobile on BW, a request is sent via the Web browser or a mobile client.

The following are the key steps involved in data refresh:

Step 1: To perform a refresh on the Design Studio document, the user sends a HTTP request to the web browser or a mobile client from the web application server. The web application server forwards this request to the Central Management Server to find the analysis application. The CMS server is also responsible to check if the user has access to refresh the document or not.

Step 2: A request is sent to the Analysis application service hosted on the Adaptive server to get the current data for Design Studio document. An Analysis application service gets the current data from the SAP NetWeaver BW system using the Remote function to call RFC and BICS Business Intelligence Consumer Service Connectivity.

Step 3: The Analysis application service creates the document with the latest data from SAP HANA and sends it back to the Web Application Server.

Step 4: The last step is that Web application server converts the data to HTML format and send it to the web browser or the mobile client where the Design document refresh data is displayed.