



Data Preprocessing

——Discretization and Concept Hierarchy Generation——

徐华

清华大学 计算机系 智能技术与系统国家重点实验室

xuhua@tsinghua.edu.cn

1

Data Preprocessing



- ◉ About data
- ◉ Why preprocess the data?
- ◉ Descriptive data summarization
- ◉ Data cleaning
- ◉ Data integration and transformation
- ◉ Data reduction
- ◉ Discretization and concept hierarchy generation
- ◉ Summary

2



Discretization and Concept hierarchy




Discretization

- ◆ reduce the number of values for a given continuous attribute by dividing the range of the attribute into intervals. Interval labels can then be used to replace actual data values, e.g. salary, price, age

Concept hierarchies

- ◆ reduce the data by collecting and replacing low level concepts (such as numeric values for the attribute age) by higher level concepts (such as young, middle-aged, or senior) place-street-city-country



(i) Binary split



(ii) Multi-way split



3

Discretization and Concept Hierarchy Generation for Numeric Data



- Binning (see sections before)
- Histogram analysis (see sections before)
- Clustering analysis (see sections before)
- Entropy-based discretization
- Segmentation by natural partitioning



4

Entropy-Based Discretization



- samples S , S is partitioned into two intervals S_1 and S_2 using boundary T , the information gain(信息增益) after partitioning is

$$I(S, T) = \frac{|S_1|}{|S|} \text{Entropy}(S_1) + \frac{|S_2|}{|S|} \text{Entropy}(S_2)$$

- Calculated based on class distribution of the samples in the set. Given m classes, the entropy of S_1 is

$$\text{Entropy}(S_1) = - \sum_{i=1}^m p_i \log_2(p_i)$$

where p_i is the probability of class i in S_1

- The boundary that minimizes the entropy function over all possible boundaries is selected as a binary discretization
- The process is recursively applied to partitions obtained until some stopping criterion is met
- Such a boundary may reduce data size and improve classification accuracy

5



Interval Merge by χ^2 Analysis



- Merging-based (bottom-up) vs. splitting-based methods
- Merge: Find the best neighboring intervals and merge them to form larger intervals recursively
- ChiMerge
 - Initially, each distinct value of a numerical attr. A is considered to be one interval
 - χ^2 tests are performed for every pair of adjacent intervals
 - Adjacent intervals with the least χ^2 values are merged together
 - This merge process proceeds recursively until a predefined stopping criterion is met (such as significance level, max-interval, max inconsistency, etc.)

6



Segmentation by Natural Partitioning




- A simply 3-4-5 rule can be used to segment numeric data into relatively uniform, “natural” intervals.
 - ◆ If an interval covers 3, 6, 7 or 9 distinct values at the most significant digit(最高有效位), partition the range into 3 equi-width intervals
 - ◆ If it covers 2, 4, or 8 distinct values at the most significant digit, partition the range into 4 intervals
 - ◆ If it covers 1, 5, or 10 distinct values at the most significant digit, partition the range into 5 intervals

7



Example of 3-4-5 Rule



8



Concept Hierarchy Generation for Categorical Data



- ◉ Specification of a partial ordering of attributes explicitly at the schema level by users or experts
 - ◆ street < city < state < country
- ◉ Specification of a portion of a hierarchy by explicit data grouping
 - ◆ {Urbana, Champaign, Chicago} < Illinois
- ◉ Specification of a set of attributes.
 - ◆ System automatically generates partial ordering by analysis of the number of distinct values
 - ◆ E.g., street < city < state < country
- ◉ Specification of only a partial set of attributes
 - ◆ E.g., only street < city, not others

9



Automatic Concept Hierarchy Generation



- ◉ Some concept hierarchies can be automatically generated based on the analysis of the number of distinct values per attribute in the given data set
 - ◆ The attribute with the most distinct values is placed at the lowest level of the hierarchy
 - ◆ Note: Exception—weekday, month, quarter, year



10



Summary



- ◉ Data preparation or preprocessing is a big issue for both data warehousing and data mining
- ◉ Descriptive data summarization is needed for quality data preprocessing
- ◉ Data preparation includes
 - ◆ Data cleaning and data integration
 - ◆ Data reduction and feature selection
 - ◆ Discretization
- ◉ A lot of methods have been developed but data preprocessing still an active area of research

11



References



- ◉ D. P. Ballou and G. K. Tayi. Enhancing data quality in data warehouse environments. *Communications of ACM*, 42:73-78, 1999
- ◉ T. Dasu and T. Johnson. *Exploratory Data Mining and Data Cleaning*. John Wiley & Sons, 2003
- ◉ T. Dasu, T. Johnson, S. Muthukrishnan, V. Shkapenyuk. [Mining Database Structure; Or, How to Build a Data Quality Browser](#). *SIGMOD' 02*.
- ◉ H.V. Jagadish et al., Special Issue on Data Reduction Techniques. *Bulletin of the Technical Committee on Data Engineering*, 20(4), December 1997
- ◉ D. Pyle. *Data Preparation for Data Mining*. Morgan Kaufmann, 1999
- ◉ E. Rahm and H. H. Do. Data Cleaning: Problems and Current Approaches. *IEEE Bulletin of the Technical Committee on Data Engineering*. Vol.23, No.4
- ◉ V. Raman and J. Hellerstein. *Potters Wheel: An Interactive Framework for Data Cleaning and Transformation*, *VLDB' 2001*
- ◉ T. Redman. *Data Quality: Management and Technology*. Bantam Books, 1992
- ◉ Y. Wand and R. Wang. Anchoring data quality dimensions ontological foundations. *Communications of ACM*, 39:86-95, 1996
- ◉ R. Wang, V. Storey, and C. Firth. A framework for analysis of data quality research. *IEEE Trans. Knowledge and Data Engineering*, 7:623-640, 1995

12





Thanks !

