



User Manual of IoTDB-Quality

Author: Data Quality Group

Institute: School of Software, Tsinghua University

Date: April 15, 2021

Contents

1	Get Started	1
1.1	Introduction	1
1.2	Comparison	1
1.3	Q&A	2
2	Data Profiling	3
2.1	Distinct	3
2.2	Histogram	4
2.3	Integral	5
2.4	Mad	7
2.5	Median	9
2.6	Mode	10
2.7	Percentile	11
2.8	Sample	13
2.9	Skew	15
2.10	Spread	16
2.11	Stddev	17
3	Data Quality	19
3.1	Completeness	19
3.2	Consistency	21
3.3	Timeliness	23
3.4	Validity	26
4	Data Repairing	29
4.1	Fill	29
4.2	TimestampRepair	29
4.3	ValueRepair	29
5	Data Matching	32
5.1	Cov	32
5.2	DTW	32
5.3	Pearson	32
5.4	SeriesAlign	32
5.5	SeriesSimilarity	32
5.6	ValueAlign	32

6	Anomaly Detection	33
6.1	KSigma	33
6.2	LOF	34
6.3	Range	34
7	Complex Event Processing	36
7.1	AND	36
7.2	EventMatching	36
7.3	EventNameRepair	36
7.4	EventTag	36
7.5	EventTimeRepair	36
7.6	MissingEventRecovery	36
7.7	SEQ	36

Chapter 1 Get Started

1.1 Introduction

1.1.1 What is IoTDB-Quality

Apache IoTDB (Internet of Things Database) is a data management system for time series data, which can provide users specific services, such as, data collection, storage and analysis.

For applications based on time series data, data quality is vital. **IoTDB-Quality** is IoTDB User Defined Functions (UDF) about data quality, including data profiling, data quality evaluation and data repairing. It effectively meets the demand for data quality in the industrial field.

1.1.2 Quick Start

1. Download the JAR with all dependencies and the script of registering UDF.
2. Copy the JAR package to `ext\udf` under the directory of IoTDB system.
3. Run `sbin\start-server.bat` (for Windows) or `sbin\start-server.sh` (for Linux or MacOS) to start IoTDB server.
4. Copy the script to the directory of IoTDB system and run it to register UDF.

1.2 Comparison

1.2.1 InfluxDB

InfluxDB is a popular time series database. InfluxQL is its query language, some of whose universal functions are related to data profiling. The comparison is shown below. *Native* means this function has been the native function of IoTDB and *Built-in UDF* means this function has been the built-in UDF of IoTDB.

Data profiling functions of IoTDB-Quality	Univeral functions of InfluxQL
<i>Native</i>	COUNT()
Distinct	DISTINCT()
Integral	INTEGRAL()
<i>Native</i>	MEAN()
Median	MEDIAN()
Mode	MODE()
Spread	SPREAD()
Stddev	STDDEV()
<i>Native</i>	SUM()
<i>Built-in UDF</i>	BOTTOM()
<i>Native</i>	FIRST()
<i>Native</i>	LAST()
<i>Native</i>	MAX()
<i>Native</i>	MIN()
Percentile	PERCENTILE()
Sample	SAMPLE()
<i>Built-in UDF</i>	TOP()
Histogram	HISTOGRAM()
Mad	
Skew	

1.3 Q&A

1.3.1 Is the name of UDF case sensitive

The name of UDF is not case sensitive. Users can choose uppercase, lowercase or mixed case according to their own habits.

Chapter 2 Data Profiling

2.1 Distinct

2.1.1 Usage

This function returns all unique values in time series.

Name: DISTINCT

Input Series: Only support a single input series. The type is arbitrary.

Output Series: Output a single series. The type is the same as the input.

Note:

- The timestamp of the output series is meaningless. The output order is the same as the appearing order of values.
- Missing points and null points in the input series will be ignored, but `NaN` will not.

2.1.2 Examples

Input series:

Time	root.test.d2.s2
[2020-01-01T08:00:00.001+08:00]	Hello
[2020-01-01T08:00:00.002+08:00]	hello
[2020-01-01T08:00:00.003+08:00]	Hello
[2020-01-01T08:00:00.004+08:00]	World
[2020-01-01T08:00:00.005+08:00]	World

SQL for query:

```
select distinct(s2) from root.test.d2
```

Output series:

Time	distinct(root.test.d2.s2)
[1970-01-01T08:00:00.001+08:00]	Hello
[1970-01-01T08:00:00.002+08:00]	hello
[1970-01-01T08:00:00.003+08:00]	World

2.2 Histogram

2.2.1 Usage

This function is used to calculate the distribution histogram of a single column of numerical data.

Name: HISTOGRAM

Input Series: Only supports a single input sequence, the type is INT32 / INT64 / FLOAT / DOUBLE

Parameters:

- **start** : The lower limit of the requested data range, the default value is -Double.MAX_VALUE.
- **end** : The upper limit of the requested data range, the default value is Double.MAX_VALUE, and the value of start must be less than or equal to end.
- **count** : The number of buckets of the histogram, the default value is 1. It must be a positive integer.

Output Series: The value of the bucket of the histogram, where the lower bound represented by the i -th bucket (index starts from 1) is $start + (i - 1) \cdot \frac{end - start}{count}$ and the upper bound is $start + i \cdot \frac{end - start}{count}$.

Note:

- If the value is lower than **start**, it will be put into the 1st bucket. If the value is larger than **end**, it will be put into the last bucket.
- Missing points, null points and **NaN** in the input series will be ignored.

2.2.2 Examples

Input series:

Time root.test.d1.s1	
[2020-01-01T00:00:00.000+08:00]	1.0
[2020-01-01T00:00:01.000+08:00]	2.0
[2020-01-01T00:00:02.000+08:00]	3.0
[2020-01-01T00:00:03.000+08:00]	4.0
[2020-01-01T00:00:04.000+08:00]	5.0
[2020-01-01T00:00:05.000+08:00]	6.0
[2020-01-01T00:00:06.000+08:00]	7.0
[2020-01-01T00:00:07.000+08:00]	8.0
[2020-01-01T00:00:08.000+08:00]	9.0
[2020-01-01T00:00:09.000+08:00]	10.0
[2020-01-01T00:00:10.000+08:00]	11.0
[2020-01-01T00:00:11.000+08:00]	12.0
[2020-01-01T00:00:12.000+08:00]	13.0

2020-01-01T00:00:13.000+08:00	14.0
2020-01-01T00:00:14.000+08:00	15.0
2020-01-01T00:00:15.000+08:00	16.0
2020-01-01T00:00:16.000+08:00	17.0
2020-01-01T00:00:17.000+08:00	18.0
2020-01-01T00:00:18.000+08:00	19.0
2020-01-01T00:00:19.000+08:00	20.0
+-----+-----+	

SQL for query:

```
select histogram(s1, "start"="1", "end"="20", "count"="10") from root.test.d1
```

Output series:

Time histogram(root.test.d1.s1, "start"="1", "end"="20", "count"="10")	
+-----+-----+	
1970-01-01T08:00:00.000+08:00	2
1970-01-01T08:00:00.001+08:00	2
1970-01-01T08:00:00.002+08:00	2
1970-01-01T08:00:00.003+08:00	2
1970-01-01T08:00:00.004+08:00	2
1970-01-01T08:00:00.005+08:00	2
1970-01-01T08:00:00.006+08:00	2
1970-01-01T08:00:00.007+08:00	2
1970-01-01T08:00:00.008+08:00	2
1970-01-01T08:00:00.009+08:00	2
+-----+-----+	

2.3 Integral

2.3.1 Usage

This function is used to calculate the integration of time series, which equals to the area under the curve with time as X-axis and values as Y-axis.

Name: INTEGRAL

Input Series: Only support a single input numeric series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **unit**: The unit of time used when computing the integral.

The value should be chosen from "1S", "1s", "1m", "1H", "1d"(case-sensitive), and each represents taking one millisecond / second / minute / hour / day as 1.0 while calculating the area and integral.

Output Series: Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the integration.

Note:

- The integral value equals to the sum of the areas of right-angled trapezoids consisting of each two adjacent points and the time-axis.

Choosing different `unit` implies different scaling of time axis, thus making it apparent to convert the value among those results with constant coefficient.

- Missing points, null points and `NaN` in the input series will be ignored. The curve or trapezoids will skip these points and use the next valid point.

2.3.2 Examples

2.3.2.1 Default Parameters

With default parameters, this function will take one second as 1.0.

Input series:

Time root.test.d1.s1	
[2020-01-01T00:00:01.000+08:00]	1
[2020-01-01T00:00:02.000+08:00]	2
[2020-01-01T00:00:03.000+08:00]	5
[2020-01-01T00:00:04.000+08:00]	6
[2020-01-01T00:00:05.000+08:00]	7
[2020-01-01T00:00:08.000+08:00]	8
[2020-01-01T00:00:09.000+08:00]	NaN
[2020-01-01T00:00:10.000+08:00]	10

SQL for query:

```
select integral(s1) from root.test.d1 where time <= 2020-01-01 00:00:10
```

Output series:

Time integral(root.test.d1.s1)	
[1970-01-01T08:00:00.000+08:00]	57.5

Calculation expression:

$$\frac{1}{2}[(1+2) \times 1 + (2+5) \times 1 + (5+6) \times 1 + (6+7) \times 1 + (7+8) \times 3 + (8+10) \times 2] = 57.5$$

2.3.2.2 Specific time unit

With time unit specified as "1m", this function will take one minute as 1.0.

Input series is the same as above, the SQL for query is shown below:

```
select integral(s1, "unit"="1m") from root.test.d1 where time <= 2020-01-01 00:00:10
```

Output series:

Time	integral(root.test.d1.s1)
1970-01-01T08:00:00.000+08:00	0.958

Calculation expression:

$$\frac{1}{2 \times 60} [(1+2) \times 1 + (2+5) \times 1 + (5+6) \times 1 + (6+7) \times 1 + (7+8) \times 3 + (8+10) \times 2] = 0.958$$

2.4 Mad

2.4.1 Usage

The function is used to compute the exact or approximate median absolute deviation (MAD) of a numeric time series. MAD is the median of the deviation of each element from the elements' median.

Take a dataset $\{1, 3, 3, 5, 5, 6, 7, 8, 9\}$ as an instance. Its median is 5 and the deviation of each element from the median is $\{0, 0, 1, 2, 2, 2, 3, 4, 4\}$, whose median is 2. Therefore, the MAD of the original dataset is 2.

Name: MAD

Input Series: Only support a single input series. The data type is INT32 / INT64 / FLOAT / DOUBLE.

Parameter:

- **error**: The relative error of the approximate MAD. It should be within [0,1] and the default value is 0. Taking **error**=0.01 as an instance, suppose the exact MAD is a and the approximate MAD is b , we have $0.99a \leq b \leq 1.01a$. With **error**=0, the output is the exact MAD.

Output Series: Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the approximate MAD.

Note: Missing points, null points and NaN in the input series will be ignored.

2.4.2 Examples

2.4.2.1 Exact Query

With the default `error` (`error=0`), the function queries the exact MAD.

Input series:

Time	root.test.s0
[2021-03-17T10:32:17.054+08:00]	0.5319929
[2021-03-17T10:32:18.054+08:00]	0.9304316
[2021-03-17T10:32:19.054+08:00]	-1.4800133
[2021-03-17T10:32:20.054+08:00]	0.6114087
[2021-03-17T10:32:21.054+08:00]	2.5163336
[2021-03-17T10:32:22.054+08:00]	-1.0845392
[2021-03-17T10:32:23.054+08:00]	1.0562582
[2021-03-17T10:32:24.054+08:00]	1.3867859
[2021-03-17T10:32:25.054+08:00]	-0.45429882
[2021-03-17T10:32:26.054+08:00]	1.0353678
[2021-03-17T10:32:27.054+08:00]	0.7307929
[2021-03-17T10:32:28.054+08:00]	2.3167255
[2021-03-17T10:32:29.054+08:00]	2.342443
[2021-03-17T10:32:30.054+08:00]	1.5809103
[2021-03-17T10:32:31.054+08:00]	1.4829416
[2021-03-17T10:32:32.054+08:00]	1.5800357
[2021-03-17T10:32:33.054+08:00]	0.7124368
[2021-03-17T10:32:34.054+08:00]	-0.78597564
[2021-03-17T10:32:35.054+08:00]	1.2058644
[2021-03-17T10:32:36.054+08:00]	1.4215064
[2021-03-17T10:32:37.054+08:00]	1.2808295
[2021-03-17T10:32:38.054+08:00]	-0.6173715
[2021-03-17T10:32:39.054+08:00]	0.06644377
[2021-03-17T10:32:40.054+08:00]	2.349338
[2021-03-17T10:32:41.054+08:00]	1.7335888
[2021-03-17T10:32:42.054+08:00]	1.5872132
.....	

Total line number = 10000

SQL for query:

```
select mad(s0) from root.test
```

Output series:

Time	mad(root.test.s0)
[1970-01-01T08:00:00.000+08:00]	0.6806197166442871

By setting `error` within $(0,1]$, the function queries the approximate MAD.

SQL for query:

Output series:

Time <code>mad(root.test.s0, "error"="0.01")</code>	
1970-01-01T08:00:00.000+08:00	0.6806616245859518

The function is used to compute the approximate median of a numeric time series.

Name: MEDIAN

Parameter:

- Output Series:** Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the approximate median.

Input series:

Time root.test.s0	
2021-03-17T10:32:17.054+08:00	0.5319929
2021-03-17T10:32:18.054+08:00	0.9304316
2021-03-17T10:32:19.054+08:00	-1.4800133
2021-03-17T10:32:20.054+08:00	0.6114087
2021-03-17T10:32:21.054+08:00	2.5163336

```
[2021-03-17T10:32:22.054+08:00] -1.0845392|
[2021-03-17T10:32:23.054+08:00]  1.0562582|
[2021-03-17T10:32:24.054+08:00]  1.3867859|
[2021-03-17T10:32:25.054+08:00] -0.45429882|
[2021-03-17T10:32:26.054+08:00]  1.0353678|
[2021-03-17T10:32:27.054+08:00]  0.7307929|
[2021-03-17T10:32:28.054+08:00]  2.3167255|
[2021-03-17T10:32:29.054+08:00]  2.342443|
[2021-03-17T10:32:30.054+08:00]  1.5809103|
[2021-03-17T10:32:31.054+08:00]  1.4829416|
[2021-03-17T10:32:32.054+08:00]  1.5800357|
[2021-03-17T10:32:33.054+08:00]  0.7124368|
[2021-03-17T10:32:34.054+08:00] -0.78597564|
[2021-03-17T10:32:35.054+08:00]  1.2058644|
[2021-03-17T10:32:36.054+08:00]  1.4215064|
[2021-03-17T10:32:37.054+08:00]  1.2808295|
[2021-03-17T10:32:38.054+08:00] -0.6173715|
[2021-03-17T10:32:39.054+08:00]  0.06644377|
[2021-03-17T10:32:40.054+08:00]  2.349338|
[2021-03-17T10:32:41.054+08:00]  1.7335888|
[2021-03-17T10:32:42.054+08:00]  1.5872132|
.....
Total line number = 10000
```

SQL for query:

```
select median(s0, "error"="0.01") from root.test
```

Output series:

Time	median(root.test.s0, "error"="0.01")
[1970-01-01T08:00:00.000+08:00]	1.021884560585022

2.6 Mode

2.6.1 Usage

This function is used to calculate the mode of time series, that is, the value that occurs most frequently.

Name: MODE

Input Series: Only support a single input series. The type is arbitrary.

Output Series: Output a single series. The type is the same as the input. There is only one data point in the series, whose timestamp is 0 and value is the mode.

Note:

- If there are multiple values with the most occurrences, the one that appears first will be output.
- Missing points and null points in the input series will be ignored, but `NaN` will not.

2.6.2 Examples

Input series:

	Time root.test.d2.s2
[1970-01-01T08:00:00.001+08:00]	Hello
[1970-01-01T08:00:00.002+08:00]	hello
[1970-01-01T08:00:00.003+08:00]	Hello
[1970-01-01T08:00:00.004+08:00]	World
[1970-01-01T08:00:00.005+08:00]	World
[1970-01-01T08:00:01.600+08:00]	World
[1970-01-15T09:37:34.451+08:00]	Hello
[1970-01-15T09:37:34.452+08:00]	hello
[1970-01-15T09:37:34.453+08:00]	Hello
[1970-01-15T09:37:34.454+08:00]	World
[1970-01-15T09:37:34.455+08:00]	World

SQL for query:

```
select mode(s2) from root.test.d2
```

Output series:

	Time mode(root.test.d2.s2)
[1970-01-01T08:00:00.000+08:00]	World

2.7 Percentile

2.7.1 Usage

The function is used to compute the approximate quantile of a numeric time series. A quantile is value of element in the certain rank of the sorted series.

Name: PERCENTILE

Input Series: Only support a single input series. The data type is INT32 / INT64 / FLOAT / DOUBLE.

Parameter:

- **rank** : The rank percentage of the quantile. It should be [0,1] and the default value is 0.5. For instance, a quantile with **rank** =0.5 is the median.
- **error** : The rank error of the approximate quantile. It should be within (0,1) and the default value is 0.01. For instance, a 0.5-quantile with **error** =0.01 is the value of the element with rank percentage 0.49~0.51.

Output Series: Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the approximate percentile.

Note: Missing points, null points and **NaN** in the input series will be ignored.

2.7.2 Examples

Input series:

Time root.test.s0	
[2021-03-17T10:32:17.054+08:00]	0.5319929
[2021-03-17T10:32:18.054+08:00]	0.9304316
[2021-03-17T10:32:19.054+08:00]	-1.4800133
[2021-03-17T10:32:20.054+08:00]	0.6114087
[2021-03-17T10:32:21.054+08:00]	2.5163336
[2021-03-17T10:32:22.054+08:00]	-1.0845392
[2021-03-17T10:32:23.054+08:00]	1.0562582
[2021-03-17T10:32:24.054+08:00]	1.3867859
[2021-03-17T10:32:25.054+08:00]	-0.45429882
[2021-03-17T10:32:26.054+08:00]	1.0353678
[2021-03-17T10:32:27.054+08:00]	0.7307929
[2021-03-17T10:32:28.054+08:00]	2.3167255
[2021-03-17T10:32:29.054+08:00]	2.342443
[2021-03-17T10:32:30.054+08:00]	1.5809103
[2021-03-17T10:32:31.054+08:00]	1.4829416
[2021-03-17T10:32:32.054+08:00]	1.5800357
[2021-03-17T10:32:33.054+08:00]	0.7124368
[2021-03-17T10:32:34.054+08:00]	-0.78597564
[2021-03-17T10:32:35.054+08:00]	1.2058644
[2021-03-17T10:32:36.054+08:00]	1.4215064
[2021-03-17T10:32:37.054+08:00]	1.2808295
[2021-03-17T10:32:38.054+08:00]	-0.6173715
[2021-03-17T10:32:39.054+08:00]	0.06644377
[2021-03-17T10:32:40.054+08:00]	2.349338
[2021-03-17T10:32:41.054+08:00]	1.7335888
[2021-03-17T10:32:42.054+08:00]	1.5872132
.....	
Total line number = 10000	

SQL for query:

```
select percentile(s0, "rank"="0.2", "error"="0.01") from root.test
```

Output series:

Time	percentile(root.test.s0, "rank"="0.2", "error"="0.01")
[1970-01-01T08:00:00.000+08:00]	0.1801469624042511

2.8 Sample

2.8.1 Usage

This function is used to sample the input series, that is, select a specified number of data points from the input series and output them. Currently, two sampling methods are supported: **Reservoir sampling** randomly selects data points. All of the points have the same probability of being sampled. **Isometric sampling** selects data points at equal index intervals.

Name: SAMPLE

Input Series: Only support a single input series. The type is arbitrary.

Parameters:

- **method**: The method of sampling, which is 'reservoir' or 'isometric'. By default, reservoir sampling is used.
- **k**: The number of sampling, which is a positive integer. By default, it's 1.

Output Series: Output a single series. The type is the same as the input. The length of the output series is **k**. Each data point in the output series comes from the input series.

Note: If **k** is greater than the length of input series, all data points in the input series will be output.

2.8.2 Examples

2.8.2.1 Reservoir Sampling

When **method** is 'reservoir' or the default, reservoir sampling is used. Due to the randomness of this method, the output series shown below is only a possible result.

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:01.000+08:00]	1.0
[2020-01-01T00:00:02.000+08:00]	2.0

2020-01-01T00:00:03.000+08:00	3.0
2020-01-01T00:00:04.000+08:00	4.0
2020-01-01T00:00:05.000+08:00	5.0
2020-01-01T00:00:06.000+08:00	6.0
2020-01-01T00:00:07.000+08:00	7.0
2020-01-01T00:00:08.000+08:00	8.0
2020-01-01T00:00:09.000+08:00	9.0
2020-01-01T00:00:10.000+08:00	10.0
+-----+-----+	

SQL for query:

```
select sample(s1, 'method'='reservoir', 'k'='5') from root.test.d1
```

Output series:

	Time sample(root.test.d1.s1, "method"="reservoir", "k"="5")
+-----+-----+	
2020-01-01T00:00:02.000+08:00	2.0
2020-01-01T00:00:03.000+08:00	3.0
2020-01-01T00:00:05.000+08:00	5.0
2020-01-01T00:00:08.000+08:00	8.0
2020-01-01T00:00:10.000+08:00	10.0
+-----+-----+	

2.8.2.2 Isometric Sampling

When `method` is 'isometric', isometric sampling is used.

Input series is the same as above, the SQL for query is shown below:

```
select sample(s1, 'method'='isometric', 'k'='5') from root.test.d1
```

Output series:

	Time sample(root.test.d1.s1, "method"="isometric", "k"="5")
+-----+-----+	
2020-01-01T00:00:01.000+08:00	1.0
2020-01-01T00:00:03.000+08:00	3.0
2020-01-01T00:00:05.000+08:00	5.0
2020-01-01T00:00:07.000+08:00	7.0
2020-01-01T00:00:09.000+08:00	9.0
+-----+-----+	

2.9 Skew

2.9.1 Usage

This function is used to calculate the population skewness.

Name: SKEW

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Output Series: Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the population skewness.

Note: Missing points, null points and `NaN` in the input series will be ignored.

2.9.2 Examples

Input series:

Time root.test.d1.s1	
[2020-01-01T00:00:00.000+08:00]	1.0
[2020-01-01T00:00:01.000+08:00]	2.0
[2020-01-01T00:00:02.000+08:00]	3.0
[2020-01-01T00:00:03.000+08:00]	4.0
[2020-01-01T00:00:04.000+08:00]	5.0
[2020-01-01T00:00:05.000+08:00]	6.0
[2020-01-01T00:00:06.000+08:00]	7.0
[2020-01-01T00:00:07.000+08:00]	8.0
[2020-01-01T00:00:08.000+08:00]	9.0
[2020-01-01T00:00:09.000+08:00]	10.0
[2020-01-01T00:00:10.000+08:00]	10.0
[2020-01-01T00:00:11.000+08:00]	10.0
[2020-01-01T00:00:12.000+08:00]	10.0
[2020-01-01T00:00:13.000+08:00]	10.0
[2020-01-01T00:00:14.000+08:00]	10.0
[2020-01-01T00:00:15.000+08:00]	10.0
[2020-01-01T00:00:16.000+08:00]	10.0
[2020-01-01T00:00:17.000+08:00]	10.0
[2020-01-01T00:00:18.000+08:00]	10.0
[2020-01-01T00:00:19.000+08:00]	10.0

SQL for query:

```
select skew(s1) from root.test.d1
```

Output series:

Time	skew(root.test.d1.s1)
[1970-01-01T08:00:00.000+08:00]	-0.9998427402292644

2.10 Spread

2.10.1 Usage

This function is used to calculate the spread of time series, that is, the maximum value minus the minimum value.

Name: SPREAD

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Output Series: Output a single series. The type is the same as the input. There is only one data point in the series, whose timestamp is 0 and value is the spread.

Note: Missing points, null points and `NaN` in the input series will be ignored.

2.10.2 Examples

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	NaN

SQL for query:

```
select spread(s1) from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

Time	spread(root.test.d1.s1)
[1970-01-01T08:00:00.000+08:00]	26.0]

2.11 Stddev

2.11.1 Usage

This function is used to calculate the population standard deviation.

Name: STDDEV

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Output Series: Output a single series. The type is DOUBLE. There is only one data point in the series, whose timestamp is 0 and value is the population standard deviation.

Note: Missing points, null points and `NaN` in the input series will be ignored.

2.11.2 Examples

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:00.000+08:00]	1.0]
[2020-01-01T00:00:01.000+08:00]	2.0]
[2020-01-01T00:00:02.000+08:00]	3.0]
[2020-01-01T00:00:03.000+08:00]	4.0]
[2020-01-01T00:00:04.000+08:00]	5.0]
[2020-01-01T00:00:05.000+08:00]	6.0]
[2020-01-01T00:00:06.000+08:00]	7.0]
[2020-01-01T00:00:07.000+08:00]	8.0]
[2020-01-01T00:00:08.000+08:00]	9.0]
[2020-01-01T00:00:09.000+08:00]	10.0]
[2020-01-01T00:00:10.000+08:00]	11.0]
[2020-01-01T00:00:11.000+08:00]	12.0]
[2020-01-01T00:00:12.000+08:00]	13.0]
[2020-01-01T00:00:13.000+08:00]	14.0]
[2020-01-01T00:00:14.000+08:00]	15.0]
[2020-01-01T00:00:15.000+08:00]	16.0]

[2020-01-01T00:00:16.000+08:00]	17.0
[2020-01-01T00:00:17.000+08:00]	18.0
[2020-01-01T00:00:18.000+08:00]	19.0
[2020-01-01T00:00:19.000+08:00]	20.0

+	+	+
---	---	---

SQL for query:

```
select stddev(s1) from root.test.d1
```

Output series:

+	+	+
	Time stddev(root.test.d1.s1)	
+	+	+
1970-01-01T08:00:00.000+08:00	5.7662812973353965	
+	+	+

Chapter 3 Data Quality

3.1 Completeness

3.1.1 Usage

This function is used to calculate the completeness of time series. The input series are divided into several continuous and non overlapping windows. The timestamp of the first data point and the completeness of each window will be output.

Name: COMPLETENESS

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **window**: The number of data points in each window. The number of data points in the last window may be less than it. By default, all input data belongs to the same window.

Output Series: Output a single series. The type is DOUBLE. The range of each value is [0,1].

Note: Only when the number of data points in the window exceeds 10, the calculation will be performed. Otherwise, the window will be ignored and nothing will be output.

3.1.2 Examples

3.1.2.1 Default Parameters

With default parameters, this function will regard all input data as the same window.

Input series:

Time root.test.d1.s1	
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0

[2020-01-01T00:00:28.000+08:00]	126.0]
[2020-01-01T00:00:30.000+08:00]	NaN]
+-----+	

SQL for query:

```
select completeness(s1) from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

+-----+	
	Time completeness(root.test.d1.s1)
+-----+	
[2020-01-01T00:00:02.000+08:00]	0.875]
+-----+	

3.1.2.2 Specific Window Size

When the window size is given, this function will divide the input data as multiple windows.

Input series:

+-----+	
	Time root.test.d1.s1
+-----+	
[2020-01-01T00:00:02.000+08:00]	100.0]
[2020-01-01T00:00:03.000+08:00]	101.0]
[2020-01-01T00:00:04.000+08:00]	102.0]
[2020-01-01T00:00:06.000+08:00]	104.0]
[2020-01-01T00:00:08.000+08:00]	126.0]
[2020-01-01T00:00:10.000+08:00]	108.0]
[2020-01-01T00:00:14.000+08:00]	112.0]
[2020-01-01T00:00:15.000+08:00]	113.0]
[2020-01-01T00:00:16.000+08:00]	114.0]
[2020-01-01T00:00:18.000+08:00]	116.0]
[2020-01-01T00:00:20.000+08:00]	118.0]
[2020-01-01T00:00:22.000+08:00]	120.0]
[2020-01-01T00:00:26.000+08:00]	124.0]
[2020-01-01T00:00:28.000+08:00]	126.0]
[2020-01-01T00:00:30.000+08:00]	NaN]
[2020-01-01T00:00:32.000+08:00]	130.0]
[2020-01-01T00:00:34.000+08:00]	132.0]
[2020-01-01T00:00:36.000+08:00]	134.0]
[2020-01-01T00:00:38.000+08:00]	136.0]
[2020-01-01T00:00:40.000+08:00]	138.0]
[2020-01-01T00:00:42.000+08:00]	140.0]
[2020-01-01T00:00:44.000+08:00]	142.0]
[2020-01-01T00:00:46.000+08:00]	144.0]
[2020-01-01T00:00:48.000+08:00]	146.0]

[2020-01-01T00:00:50.000+08:00]	148.0
[2020-01-01T00:00:52.000+08:00]	150.0
[2020-01-01T00:00:54.000+08:00]	152.0
[2020-01-01T00:00:56.000+08:00]	154.0
[2020-01-01T00:00:58.000+08:00]	156.0
[2020-01-01T00:01:00.000+08:00]	158.0

SQL for query:

```
select completeness(s1, "window"="15") from root.test.d1 where time <= 2020-01-01 00:01:00
```

Output series:

Time completeness(root.test.d1.s1, "window"="15")
[2020-01-01T00:00:02.000+08:00] 0.875
[2020-01-01T00:00:32.000+08:00] 1.0

3.2 Consistency

3.2.1 Usage

This function is used to calculate the consistency of time series. The input series are divided into several continuous and non overlapping windows. The timestamp of the first data point and the consistency of each window will be output.

Name: CONSISTENCY

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **window**: The number of data points in each window. The number of data points in the last window may be less than it. By default, all input data belongs to the same window.

Output Series: Output a single series. The type is DOUBLE. The range of each value is [0,1].

Note: Only when the number of data points in the window exceeds 10, the calculation will be performed. Otherwise, the window will be ignored and nothing will be output.

3.2.2 Examples

3.2.2.1 Default Parameters

With default parameters, this function will regard all input data as the same window.

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0]
[2020-01-01T00:00:03.000+08:00]	101.0]
[2020-01-01T00:00:04.000+08:00]	102.0]
[2020-01-01T00:00:06.000+08:00]	104.0]
[2020-01-01T00:00:08.000+08:00]	126.0]
[2020-01-01T00:00:10.000+08:00]	108.0]
[2020-01-01T00:00:14.000+08:00]	112.0]
[2020-01-01T00:00:15.000+08:00]	113.0]
[2020-01-01T00:00:16.000+08:00]	114.0]
[2020-01-01T00:00:18.000+08:00]	116.0]
[2020-01-01T00:00:20.000+08:00]	118.0]
[2020-01-01T00:00:22.000+08:00]	120.0]
[2020-01-01T00:00:26.000+08:00]	124.0]
[2020-01-01T00:00:28.000+08:00]	126.0]
[2020-01-01T00:00:30.000+08:00]	NaN]

SQL for query:

```
select consistency(s1) from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

Time	consistency(root.test.d1.s1)
[2020-01-01T00:00:02.000+08:00]	0.9333333333333333]

3.2.2.2 Specific Window Size

When the window size is given, this function will divide the input data as multiple windows.

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0]
[2020-01-01T00:00:03.000+08:00]	101.0]
[2020-01-01T00:00:04.000+08:00]	102.0]
[2020-01-01T00:00:06.000+08:00]	104.0]
[2020-01-01T00:00:08.000+08:00]	126.0]
[2020-01-01T00:00:10.000+08:00]	108.0]
[2020-01-01T00:00:14.000+08:00]	112.0]

[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	NaN
[2020-01-01T00:00:32.000+08:00]	130.0
[2020-01-01T00:00:34.000+08:00]	132.0
[2020-01-01T00:00:36.000+08:00]	134.0
[2020-01-01T00:00:38.000+08:00]	136.0
[2020-01-01T00:00:40.000+08:00]	138.0
[2020-01-01T00:00:42.000+08:00]	140.0
[2020-01-01T00:00:44.000+08:00]	142.0
[2020-01-01T00:00:46.000+08:00]	144.0
[2020-01-01T00:00:48.000+08:00]	146.0
[2020-01-01T00:00:50.000+08:00]	148.0
[2020-01-01T00:00:52.000+08:00]	150.0
[2020-01-01T00:00:54.000+08:00]	152.0
[2020-01-01T00:00:56.000+08:00]	154.0
[2020-01-01T00:00:58.000+08:00]	156.0
[2020-01-01T00:01:00.000+08:00]	158.0
+-----+-----+	

SQL for query:

```
select consistency(s1,"window"="15") from root.test.d1 where time <= 2020-01-01 00:01:00
```

Output series:

Time consistency(root.test.d1.s1, "window"="15")	
+-----+-----+	
[2020-01-01T00:00:02.000+08:00]	0.9333333333333333
[2020-01-01T00:00:32.000+08:00]	1.0
+-----+-----+	

3.3 Timeliness

3.3.1 Usage

This function is used to calculate the timeliness of time series. The input series are divided into several continuous and non overlapping windows. The timestamp of the first data point and the timeliness of each window will be output.

Name: TIMELINESS

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **window** : The number of data points in each window. The number of data points in the last window may be less than it. By default, all input data belongs to the same window.

Output Series: Output a single series. The type is DOUBLE. The range of each value is [0,1].

Note: Only when the number of data points in the window exceeds 10, the calculation will be performed. Otherwise, the window will be ignored and nothing will be output.

3.3.2 Examples

3.3.2.1 Default Parameters

With default parameters, this function will regard all input data as the same window.

Input series:


Time root.test.d1.s1	
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	NaN

SQL for query:

```
select timeliness(s1) from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

Time timeliness(root.test.d1.s1)	
[2020-01-01T00:00:02.000+08:00]	0.9333333333333333



3.3.2.2 Specific Window Size

When the window size is given, this function will divide the input data as multiple windows.

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0]
[2020-01-01T00:00:03.000+08:00]	101.0]
[2020-01-01T00:00:04.000+08:00]	102.0]
[2020-01-01T00:00:06.000+08:00]	104.0]
[2020-01-01T00:00:08.000+08:00]	126.0]
[2020-01-01T00:00:10.000+08:00]	108.0]
[2020-01-01T00:00:14.000+08:00]	112.0]
[2020-01-01T00:00:15.000+08:00]	113.0]
[2020-01-01T00:00:16.000+08:00]	114.0]
[2020-01-01T00:00:18.000+08:00]	116.0]
[2020-01-01T00:00:20.000+08:00]	118.0]
[2020-01-01T00:00:22.000+08:00]	120.0]
[2020-01-01T00:00:26.000+08:00]	124.0]
[2020-01-01T00:00:28.000+08:00]	126.0]
[2020-01-01T00:00:30.000+08:00]	NaN]
[2020-01-01T00:00:32.000+08:00]	130.0]
[2020-01-01T00:00:34.000+08:00]	132.0]
[2020-01-01T00:00:36.000+08:00]	134.0]
[2020-01-01T00:00:38.000+08:00]	136.0]
[2020-01-01T00:00:40.000+08:00]	138.0]
[2020-01-01T00:00:42.000+08:00]	140.0]
[2020-01-01T00:00:44.000+08:00]	142.0]
[2020-01-01T00:00:46.000+08:00]	144.0]
[2020-01-01T00:00:48.000+08:00]	146.0]
[2020-01-01T00:00:50.000+08:00]	148.0]
[2020-01-01T00:00:52.000+08:00]	150.0]
[2020-01-01T00:00:54.000+08:00]	152.0]
[2020-01-01T00:00:56.000+08:00]	154.0]
[2020-01-01T00:00:58.000+08:00]	156.0]
[2020-01-01T00:01:00.000+08:00]	158.0]

SQL for query:

```
select timeliness(s1, "window"="15") from root.test.d1 where time <= 2020-01-01 00:01:00
```

Output series:

Time	timeliness(root.test.d1.s1, "window"="15")
[2020-01-01T00:00:02.000+08:00]	0.9333333333333333
[2020-01-01T00:00:32.000+08:00]	1.0

3.4 Validity

3.4.1 Usage

This function is used to calculate the Validity of time series. The input series are divided into several continuous and non overlapping windows. The timestamp of the first data point and the Validity of each window will be output.

Name: VALIDITY

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **window**: The number of data points in each window. The number of data points in the last window may be less than it. By default, all input data belongs to the same window.

Output Series: Output a single series. The type is DOUBLE. The range of each value is [0,1].

Note: Only when the number of data points in the window exceeds 10, the calculation will be performed. Otherwise, the window will be ignored and nothing will be output.

3.4.2 Examples

3.4.2.1 Default Parameters

With default parameters, this function will regard all input data as the same window.

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0

2020-01-01T00:00:16.000+08:00	114.0
2020-01-01T00:00:18.000+08:00	116.0
2020-01-01T00:00:20.000+08:00	118.0
2020-01-01T00:00:22.000+08:00	120.0
2020-01-01T00:00:26.000+08:00	124.0
2020-01-01T00:00:28.000+08:00	126.0
2020-01-01T00:00:30.000+08:00	NaN
+-----+-----+	

SQL for query:

```
select Validity(s1) from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

+-----+-----+	
	Time validity(root.test.d1.s1)
+-----+-----+	
2020-01-01T00:00:02.000+08:00	0.8833333333333333
+-----+-----+	

3.4.2.2 Specific Window Size

When the window size is given, this function will divide the input data as multiple windows.

Input series:

+-----+-----+	
	Time root.test.d1.s1
+-----+-----+	
2020-01-01T00:00:02.000+08:00	100.0
2020-01-01T00:00:03.000+08:00	101.0
2020-01-01T00:00:04.000+08:00	102.0
2020-01-01T00:00:06.000+08:00	104.0
2020-01-01T00:00:08.000+08:00	126.0
2020-01-01T00:00:10.000+08:00	108.0
2020-01-01T00:00:14.000+08:00	112.0
2020-01-01T00:00:15.000+08:00	113.0
2020-01-01T00:00:16.000+08:00	114.0
2020-01-01T00:00:18.000+08:00	116.0
2020-01-01T00:00:20.000+08:00	118.0
2020-01-01T00:00:22.000+08:00	120.0
2020-01-01T00:00:26.000+08:00	124.0
2020-01-01T00:00:28.000+08:00	126.0
2020-01-01T00:00:30.000+08:00	NaN
2020-01-01T00:00:32.000+08:00	130.0
2020-01-01T00:00:34.000+08:00	132.0
2020-01-01T00:00:36.000+08:00	134.0
2020-01-01T00:00:38.000+08:00	136.0

[2020-01-01T00:00:40.000+08:00]	138.0
[2020-01-01T00:00:42.000+08:00]	140.0
[2020-01-01T00:00:44.000+08:00]	142.0
[2020-01-01T00:00:46.000+08:00]	144.0
[2020-01-01T00:00:48.000+08:00]	146.0
[2020-01-01T00:00:50.000+08:00]	148.0
[2020-01-01T00:00:52.000+08:00]	150.0
[2020-01-01T00:00:54.000+08:00]	152.0
[2020-01-01T00:00:56.000+08:00]	154.0
[2020-01-01T00:00:58.000+08:00]	156.0
[2020-01-01T00:01:00.000+08:00]	158.0
+-----+-----+	

SQL for query:

```
select Validity(s1,"window"="15") from root.test.d1 where time <= 2020-01-01 00:01:00
```

Output series:

+-----+-----+	
	Time validity (root.test.d1.s1, "window"="15")
+-----+-----+	
[2020-01-01T00:00:02.000+08:00]	0.8833333333333333
[2020-01-01T00:00:32.000+08:00]	1.0
+-----+-----+	

Chapter 4 Data Repairing

4.1 Fill

4.2 TimestampRepair

4.3 ValueRepair

4.3.1 Usage

This function is used to repair the value of the time series. Currently, two methods are supported: **Screen** is a method based on speed threshold, which makes all speeds meet the threshold requirements under the premise of minimum changes; **LsGreedy** is a method based on speed change likelihood, which models speed changes as Gaussian distribution, and uses a greedy algorithm to maximize the likelihood.

Name: VALUEREPAIR

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

Parameters:

- **method** : The method used to repair, which is 'Screen' or 'LsGreedy'. By default, Screen is used.
- **minSpeed** : This parameter is only valid with Screen. It is the speed threshold. Speeds below it will be regarded as outliers. By default, it is the median minus 3 times of median absolute deviation.
- **maxSpeed** : This parameter is only valid with Screen. It is the speed threshold. Speeds above it will be regarded as outliers. By default, it is the median plus 3 times of median absolute deviation.
- **center** : This parameter is only valid with LsGreedy. It is the center of the Gaussian distribution of speed changes. By default, it is 0.
- **sigma** : This parameter is only valid with LsGreedy. It is the standard deviation of the Gaussian distribution of speed changes. By default, it is the median absolute deviation.

Output Series: Output a single series. The type is the same as the input. This series is the input after repairing.

Note: **NaN** will be filled with linear interpolation before repairing.

4.3.2 Examples

4.3.2.1 Repair with Screen

When `method` is 'Screen' or the default, Screen method is used.

Input series:

Time	root.test.d2.s1
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	100.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	NaN

SQL for query:

```
select valuerespair(s1) from root.test.d2
```

Output series:

Time	valuerespair(root.test.d2.s1)
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	106.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0

[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	128.0
+-----+	

4.3.2.2 Repair with LsGreedy

When `method` is 'LsGreedy', LsGreedy method is used.

Input series is the same as above, the SQL for query is shown below:

```
select valuerepair(s1,'method'='LsGreedy') from root.test.d2
```

Output series:

+-----+	
	Time valuerepair(root.test.d2.s1, "method"="LsGreedy")
+-----+	
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	106.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	128.0
+-----+	

Chapter 5 Data Matching

5.1 Cov

5.2 DTW

5.3 Pearson

5.4 SeriesAlign

5.5 SeriesSimilarity

5.6 ValueAlign

Chapter 6 Anomaly Detection

6.1 KSigma

6.1.1 Usage

This function is used to detect distribution anomaly of time series. According to k parameter, the function judges if a input value is an extreme value beyond k-sigma, aka distribution anomaly, and a new time series of anomaly will be output.

Name: KSIGMA

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

- **k**:how many times to multiply on standard deviation to define extreme value.

Output Series: Output a single series. The type is DOUBLE.

Note: Only when k is larger than 0, the anomaly detection will be performed. Otherwise, nothing will be output.

6.1.2 Examples

6.1.2.1 Assigning k

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	0.0
[2020-01-01T00:00:03.000+08:00]	50.0
[2020-01-01T00:00:04.000+08:00]	100.0
[2020-01-01T00:00:06.000+08:00]	150.0
[2020-01-01T00:00:08.000+08:00]	200.0
[2020-01-01T00:00:10.000+08:00]	200.0
[2020-01-01T00:00:14.000+08:00]	200.0
[2020-01-01T00:00:15.000+08:00]	200.0
[2020-01-01T00:00:16.000+08:00]	200.0
[2020-01-01T00:00:18.000+08:00]	200.0
[2020-01-01T00:00:20.000+08:00]	150.0
[2020-01-01T00:00:22.000+08:00]	100.0
[2020-01-01T00:00:26.000+08:00]	50.0
[2020-01-01T00:00:28.000+08:00]	0.0
[2020-01-01T00:00:30.000+08:00]	NaN

SQL for query:

```
select ksigma(s1,"k"="1.0") from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

Time	ksigma(root.test.d1.s1,"k"="3.0")
2020-01-01T00:00:02.000+08:00	0.0
2020-01-01T00:00:03.000+08:00	50.0
2020-01-01T00:00:26.000+08:00	50.0
2020-01-01T00:00:28.000+08:00	0.0

6.2 LOF

6.2.1 Usage

This function is used to detect density anomaly of time series. According to k-th distance calculation parameter and local outlier factor (lof) threshold, the function judges if a set of input values is an density anomaly, and a bool mark of anomaly values will be output.

Name: LOF

Input Series: Multiple input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

- **k**: use the k-th distance to calculate lof.
- **threshold**: sets of values of lof larger than this threshold will be recognized as outlier. Lof larger than 1 indicates density near the set of value is below nearby sets, which is likely to be an outlier.

Output Series: Output a single series. The type is BOOLEAN.

Note: Incomplete rows will be ignored. They are neither calculated nor marked as anomaly.

6.2.2 Examples

6.2.2.1 Assigning k

6.2.2.2 Assigning k and threshold

6.3 Range

6.3.1 Usage

This function is used to detect range anomaly of time series. According to upper bound and lower bound parameters, the function judges if a input value is beyond range, aka range anomaly, and a new time series of anomaly will be output.

Name: RANGE

Input Series: Only support a single input series. The type is INT32 / INT64 / FLOAT / DOUBLE.

- `lower_bound`: lower bound of range anomaly detection.
- `upper_bound`: upper bound of range anomaly detection.

Output Series: Output a single series. The type is DOUBLE.

Note: Only when `upper_bound` is larger than `lower_bound`, the anomaly detection will be performed. Otherwise, nothing will be output.

6.3.2 Examples

6.3.2.1 Assigning Lower and Upper Bound

Input series:

Time	root.test.d1.s1
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:03.000+08:00]	101.0
[2020-01-01T00:00:04.000+08:00]	102.0
[2020-01-01T00:00:06.000+08:00]	104.0
[2020-01-01T00:00:08.000+08:00]	126.0
[2020-01-01T00:00:10.000+08:00]	108.0
[2020-01-01T00:00:14.000+08:00]	112.0
[2020-01-01T00:00:15.000+08:00]	113.0
[2020-01-01T00:00:16.000+08:00]	114.0
[2020-01-01T00:00:18.000+08:00]	116.0
[2020-01-01T00:00:20.000+08:00]	118.0
[2020-01-01T00:00:22.000+08:00]	120.0
[2020-01-01T00:00:26.000+08:00]	124.0
[2020-01-01T00:00:28.000+08:00]	126.0
[2020-01-01T00:00:30.000+08:00]	NaN

SQL for query:

```
select range(s1,"lower_bound"="101.0","upper_bound"="125.0") from root.test.d1 where time <= 2020-01-01 00:00:30
```

Output series:

Time	range(root.test.d1.s1,"lower_bound"="101.0","upper_bound"="125.0")
[2020-01-01T00:00:02.000+08:00]	100.0
[2020-01-01T00:00:28.000+08:00]	126.0

Chapter 7 Complex Event Processing

7.1 AND

7.2 EventMatching

7.3 EventNameRepair

7.4 EventTag

7.5 EventTimeRepair

7.6 MissingEventRecovery

7.7 SEQ