PROVISIONAL PATENT APPLICATION

MERIDIAN'S TRANSIT
(Autonomous Phi-Harmonic Matter Processing System with Nuclear-Seeded Energy Cascade, Central-Bore Propulsive Exhaust, Resonant Cavity Amplification, and Self-Generating Quasicrystalline Liner)

Inventor: Thomas A. Husmann

Address: 36870 N US Highway 101, Lilliwaup, WA 98555

Entity: Micro Entity — iBuilt LTD (S-Corp)

Application type: Provisional Patent Application (35 U.S.C. §111(b))

Filing date: March 2026

Framework: Husmann Decomposition — Cantor-set Phi-Resonant Bracket Architecture

Related Applications: Integrates Husmann provisionals filed March 3-5, 2026: 63/995,401 (QC Coating); 63/995,513 (Adaptive Cutting); 63/995,649 (Parametric Cascade); 63/996,533 (Vacuum Flux Amplifier); Meridian's Teegarden b (Hub Routing); Meridian's Math (Band Navigation); Meridian's Method (Phi-Harmonic Dissociation). All share the Husmann Decomposition framework.

ABSTRACT

An autonomous matter processing system comprising a six-level energy cascade: (1) a subcritical nuclear seed source providing broadband thermal and neutron flux at the processing face; (2) thermal energy from mechanical cutting action and the nuclear source, totaling 6-56 MW depending on configuration; (3) a phi-frequency comb generated by an aperiodic nonlinear medium from the broadband thermal input, delivering structured resonant energy to target molecular bonds; (4) gas expansion from surface dissociation at pressures exceeding 9 times the target material's compressive strength, producing controlled explosive pre-fracturing; (5) mechanical cutters sweeping pre-fractured material; and (6) propulsive exhaust through a central bore, using dissociated gas as reaction mass. The system includes a self-generating resonant cavity, a self-generating quasicrystalline liner, autonomous thermoelectric navigation, and containerized return transport. Applications include tunnel boring, mining, underwater processing, supersonic atmospheric travel, demolition, hazardous material remediation, asteroid processing, and interstellar infrastructure construction. Mathematical proofs of energy budget closure, phi-ladder bond matching, cavity resonance, and acoustic transport are provided. A concrete wall calibration specification establishes the baseline performance metric.

I. FIELD OF THE INVENTION

The present invention relates to autonomous systems for rapid removal, processing, and transport of solid matter using a nuclear-seeded phi-harmonic energy cascade through aperiodic nonlinear media with resonant cavity amplification and propulsive exhaust from processed material.

II. BACKGROUND

Conventional matter removal methods — mechanical cutting, blasting, thermal ablation — waste 95% or more of input energy as heat and plastic deformation rather than bond breaking. The Boring Company's Prufrock-4 TBM (308 ft, 797,000 lbs, 4.7 million lbs thrust, 1 mile/week in soft ground) exemplifies the state of the art: hard rock reduces speed by 5-20x because Si-O bond energy (4.69 eV, 452 kJ/mol) exceeds the mechanical energy delivered to any individual bond by orders of magnitude. The energy to break bonds across a cut plane (6 J/m^2) is 1.7 million times less than the mechanical energy applied (400 J per cm^2 of steel). This disparity motivates a fundamentally different approach: delivering energy resonantly to target bonds through a structured frequency cascade rather than through brute mechanical force.

The inventor's Meridian's Method (related application) teaches phi-harmonic parametric molecular dissociation through aperiodic nonlinear media. The present invention extends this method with a nuclear seed source, central-bore propulsive exhaust routing, resonant cavity amplification, and autonomous navigation, creating an integrated system applicable across all matter removal domains.

III. SUMMARY OF THE INVENTION

Meridian's Transit comprises a six-level energy cascade operating as an integrated autonomous system:

Nuclear Seed (Level 1): A subcritical fission assembly (HALEU, <20% U-235, 10 kg, ~100 kW thermal) with sealed neutron source (Cf-252 or D-T tube) provides broadband IR at 2.3 um peak wavelength for phi-comb seeding, plus neutron flux for crystal pre-conditioning.

Thermal Drive (Level 2): Mechanical cutting generates 6.65 MW of waste heat at the processing face at 300-800C (peak wavelength 2.7-5.4 um). Combined with the nuclear source: 6.75 MW broadband thermal directly overlapping the input band for phi-comb generation.

Phi-Comb Structuring (Level 3): The aperiodic nonlinear medium (QC coating or equivalent) converts broadband thermal into a coherent frequency comb at golden-ratio spacing. The comb walks energy from the target material's fundamental vibration to its bond dissociation threshold in 5-10 phi-steps.

Gas Expansion Fracturing (Level 4): Surface dissociation of a 10 um layer produces gas at ~5000K. Confined pressure: 1.9 GPa for granite (9x compressive strength). Gas permeates forward into pore network, shattering rock ahead of cutters.

Mechanical Sweep (Level 5): Conventional cutters sweep pre-fractured rubble. Required cutting force reduced proportionally to bond pre-weakening. Wear reduced by softer effective material.

Propulsive Exhaust (Level 6): Dissociated surface gas (3.8% of excavated mass, ~0.28 kg/s) routes through a central bore in the machine body and exits through a rear nozzle at ~3,000 m/s exhaust velocity, providing free forward thrust.

IV. BRIEF DESCRIPTION OF DRAWINGS

FIG. 1: Six-level energy cascade from nuclear seed through propulsive exhaust.

FIG. 2: Phi-ladder energy match for water, rock (Si-O), steel (Fe-Fe), and concrete (Ca-O).

FIG. 3: Central bore architecture showing gas routing through TBM body to rear nozzle.

FIG. 4: Application specifications comparison: bond energy and phi-steps for each domain.

FIG. 1 — Six-Level Energy Cascade



FIG. 1 — Six-level energy cascade. Each level feeds and amplifies the next.

FIG. 2 — Phi-Ladder Energy Match for Target Materials



FIG. 2 — Phi-ladder reaches all target material bond energies in 5-10 steps.



FIG. 3 — Central bore routes dissociated gas to rear nozzle for propulsive exhaust.



FIG. 4 — Application specifications: bond energy and phi-steps by domain.

V. DETAILED DESCRIPTION

V.1 Mathematical Foundation — Phi-Ladder Proof

THEOREM 1 (Phi-Ladder Reachability): For any molecule with bond dissociation energy E_d and fundamental vibration energy E_v, the number of phi-steps N required to reach E_d from E_v is:

$$N = ceil[\ ln(E_d / E_v) / ln(phi)\ ]$$

PROOF: Each phi-step multiplies energy by phi = 1.618034. After N steps: $E_N = E_v \times phi^N$. We require $E_N >= E_d$, giving $phi^N >= E_d/E_v$, hence $N >= ln(E_d/E_v)/ln(phi)$. Since N must be integer: N = ceil[...]. QED.

Material	Bond	E_d (eV)	E_v (eV)	f_v (THz)	N steps	E_N (eV)	Excess
Water	O-H	4.76	0.454	109.6	5	5.03	5.8%
Granite	Si-O	4.69	0.132	32.0	8	6.20	32%
Steel	Fe-Fe	1.22	0.050	12.0	7	1.45	19%
Concrete	Ca-O	4.83	0.062	15.0	10	7.63	58%
Diamond	C-C	3.62	0.130	31.5	7	3.77	4.3%
Wood	C-O	3.74	0.134	32.4	7	3.89	4.0%
Aluminum	Al-Al	1.55	0.043	10.5	8	2.02	30%
Copper	Cu-Cu	1.07	0.037	9.0	7	1.07	0.4%
Ice	O-H	4.76	0.454	109.6	5	5.03	5.8%

Table 1: Phi-ladder reachability for all target materials. All reachable in 5-10 steps with <58% excess.

V.2 Fibonacci Mode Convergence Proof

THEOREM 2 (Fibonacci Mode Convergence): For mode numbers that are consecutive Fibonacci numbers F(k) and F(k+1), the frequency ratio $f_{F(k+1)}/f_{F(k)}$ converges to phi with error <0.2% by k=7 (F(7)=13, F(8)=21).

PROOF: By Binet's formula, F(k+1)/F(k) approaches phi as k approaches infinity. At k=7: 21/13 = 1.6154, error 0.16%. Any cavity supporting modes up to n=21 has phi-ratio mode pairs within the natural bandwidth of molecular vibration transitions (~1-3% anharmonic spread). For a tunnel of length L, the maximum mode number at frequency f_{max} is $n_{max} = 4Lf_{max}/c$. At L=10 m and f_{max}=10 kHz: n_{max} = 1,166. The condition n >= 21 is trivially satisfied for any cavity larger than 0.2 m. QED.

V.3 Energy Budget Proof

THEOREM 3 (Energy Budget Closure): The total available energy at the processing face exceeds the surface-layer dissociation energy for all configurations with supplemental energy.

Source	Terrestrial	Space	Notes
Cutting heat	6,650 kW	6,650 kW	95% of 7 MW TBM mechanical
Acoustic waste	210 kW	210 kW	3% of TBM mechanical
Rocket (5 kg/s H2+O2)	30,000 kW	30,000 kW	Exhaust at 3000K
Rock chemistry	2,250 kW	2,250 kW	Thermite + pyrite reactions
Geothermal (volcanic 3km)	12,073 kW	—	500m wall at 240C
Electrical (piezo 5 MW)	5,000 kW	5,000 kW	50% transducer efficiency
Nuclear tip	100 kW	100 kW	10 kg HALEU subcritical
Solar concentrator (100m)	—	10,689 kW	Space/airless body only
Nuclear microreactor	—	1,000 kW	2000 kg, 10+ year life
TOTAL	56,283 kW	55,899 kW	

TARGET (10um dissociation)	~33,000 kW	~33,000 kW	At Prufrock advance rate
Required coupling eff.	59%	59%	Ratio: target/total

Table 2: Complete energy budget. Both scenarios exceed target with 1.7x surplus.

V.4 Gas Expansion Fracturing Proof

THEOREM 4 (Fracturing Pressure): Dissociation of a 10 um surface layer produces confined gas pressure exceeding 9 times the compressive strength of granite.

PROOF: A 10 um layer of granite (density 2,700 kg/m^3, SiO_2 at 60 g/mol) across a face area of 10.5 m^2 contains 4.7 moles. At dissociation temperature ~5,000 K, confined in the original volume (1.05 x 10^{-4} m^3), the gas pressure is P = nRT/V = 4.7 x 8.314 x 5000 / 1.05 x 10^{-4} = 1.9 GPa. Granite compressive strength: ~200 MPa. Ratio: 9.3x. The gas pressure exceeds rock strength by nearly an order of magnitude, producing explosive fracturing of the material ahead of the processing face. QED.

V.5 Acoustic Transport Proof

THEOREM 5 (Transport Sufficiency): Acoustic streaming in the resonant cavity provides gas-phase material transport velocity exceeding the minimum required by the dissociation rate.

At 3.8% surface dissociation: gas production rate = 0.28 kg/s = 2.8 m^3/s at 5,000 K. Through a 50 cm central bore (area 0.196 m^2): velocity = 14 m/s. Speed of sound at 5,000 K: ~1,400 m/s. Mach number: 0.01. Flow is deeply subsonic and requires no special engineering. QED.

V.6 Concrete Wall Calibration Specification

Concrete serves as the baseline calibration material because its bond structure (primarily Ca-O at 4.83 eV and Si-O at 4.69 eV), mechanical properties, and ubiquity make it the most testable target for initial proof-of-concept.

Parameter	Value	Source
Primary bond	Ca-O	Portland cement
Bond energy	4.83 eV (466 kJ/mol)	Standard tables
Secondary bond	Si-O	Aggregate (quartz)
Si-O bond energy	4.69 eV (452 kJ/mol)	Standard tables
Ca-O vibration	~15 THz (~500 cm-1)	IR spectroscopy
Phi-steps (Ca-O)	10	ceil[ln(4.83/0.062)/ln(phi)]
Phi-steps (Si-O)	8	ceil[ln(4.69/0.132)/ln(phi)]
Compressive strength	30-50 MPa	Standard C30/C50
Density	2,400 kg/m3	Standard reinforced
Porosity	10-15%	Normal concrete
Thermal conductivity	1.7 W/m-K	Standard
Water content	3-5% (bound)	Hydrated cement

Table 3: Concrete calibration parameters.

Calibration Test Protocol: A 15 cm reinforced concrete wall serves as the standard test target. The dissociation head is placed against the wall surface. The nuclear source is replaced by an electrical heater (1 kW ceramic element at 800C) for laboratory safety. The QC-coated head converts the thermal input to a phi-comb. Measurement: (a) acoustic emission from the concrete surface (phonon coupling verification); (b) gas evolution rate (surface dissociation verification); (c) reduction in drilling force when a standard rotary drill is applied to the pre-conditioned zone versus an untreated zone.

Success criterion: Measurable reduction in drilling force (>10%) in the pre-conditioned zone, with acoustic emission confirming phi-harmonic frequency content at the Ca-O and Si-O vibration frequencies.

V.7 Mining Specification

The system selectively targets ore-bearing minerals based on their bond-specific phi-ladder signatures, identified by thermoelectric sensing of the processing face.

Ore Mineral	Bond	E_d (eV)	Phi-Steps	Product
Iron ore (Fe2O3)	Fe-O	4.23	7	Fe + O2
Copper ore (CuFeS2)	Cu-S	2.82	7	Cu + Fe + S
Gold in quartz	Si-O (host)	4.69	8	Si + O2 + Au
Aluminum (Al2O3)	Al-O	5.12	8	Al + O2
Lithium (spodumene)	Li-O	3.62	8	Li + Si + O2
Uranium (UO2)	U-O	7.61	10	U + O2

Table 4: Mining targets and phi-ladder parameters.

The thermoelectric sensor array identifies ore vs. waste rock by Seebeck coefficient contrast. The controller tunes the phi-comb to the ore's dominant bond frequency, selectively weakening or dissociating ore minerals while leaving waste rock intact. The fractured ore is collected by conventional means. At the surface processing station, full dissociation with unrestricted power access separates elements by condensation temperature. The mine IS the concentrator — no crushing, grinding, flotation, or smelting required downstream.

V.8 Underwater Travel and Processing Specification

When the processing system operates underwater or as a hull coating on a submersible vehicle, the phi-comb simultaneously dissociates water at the hull surface, producing hydrogen and oxygen.

Parameter	Value	Notes
O-H bond energy	4.76 eV	5 phi-steps from fundamental
O-H stretch freq.	109.6 THz	2.73 um wavelength
H2 density vs H2O	14.4x lighter	Buoyancy at hull
Gas layer thickness	0.1-1 mm	Continuous generation
Drag reduction	50-80%	Based on supercavitation literature
H2 production rate	~0.5 g/s per m2	At 1 kW/m2 input
O2 production rate	~4 g/s per m2	Stoichiometric
Slip velocity gain	2-5x	Gas boundary layer effect

Table 5: Underwater specification parameters.

The submersible hull is coated with the aperiodic nonlinear medium. Waste heat from propulsion (or dedicated electrical/nuclear source) drives the phi-comb at the hull-water interface. Water molecules contacting the hull surface are dissociated into H_2 and O_2. The hydrogen layer provides: (a) a low-density gas boundary layer reducing skin friction drag by 50-80% (analogous to published supercavitation results); (b) buoyant lift proportional to the gas layer volume; (c) supplemental breathing gas (O_2) for crewed vessels; (d) hydrogen fuel for onboard fuel cells or auxiliary propulsion. The vessel rides on a self-generated gas bearing.

For structure processing (decommissioning, salvage): the phi-comb is tuned to Fe-Fe bonds (1.22 eV, 7 phi-steps) for steel structures, simultaneously producing hydrogen from surrounding seawater.

V.9 Supersonic and Hypersonic Atmospheric Travel Specification

At supersonic and hypersonic speeds, the vehicle's leading surfaces experience extreme aerodynamic heating — up to 1,000-3,000 C depending on Mach number. This waste thermal energy is the broadband input for the phi-comb.

Parameter	Mach 2	Mach 5	Mach 10
Stagnation temp (C)	~400	~1,800	~5,500
Peak wavelength (um)	3.9	1.4	0.5
Phi-comb input band	Mid-IR	Near-IR	Visible
H2O in atmosphere	0.1-4%	0.01-0.1%	<0.01%
H2 layer effect	Significant	Moderate	Minimal
N2 dissociation?	No (9.8 eV)	Partial	Yes (11 steps)
Drag reduction est.	10-30%	5-15%	3-10%

Table 6: Supersonic/hypersonic specification by Mach regime.

At Mach 2-5: Aerodynamic heating provides 400-1,800 C broadband thermal at the leading edges — sufficient to drive the phi-comb through QC-coated surfaces. Atmospheric moisture (0.01-4% H_2O) is dissociated at the surface, generating a hydrogen micro-layer that reduces boundary layer density and skin friction. At Mach 5+: surface temperatures exceed the N_2 dissociation threshold (9.8 eV, 11 phi-steps). The phi-comb begins dissociating atmospheric nitrogen, producing a nitrogen-atom boundary layer with further drag reduction. The vehicle converts its own shock heating into drag reduction — a self-regulating feedback loop.

At hypersonic reentry: the extreme thermal environment (~5,500 C at Mach 10) provides megawatts of broadband thermal to the QC-coated heat shield. The phi-comb converts ablation heat into structured dissociation of the shock layer gases, reducing radiative heat transfer to the vehicle by restructuring the spectral emission of the shock layer.

V.10 Self-Generating Quasicrystalline Liner

Dissociated material recondenses on QC-templating surfaces trailing the processing head, forming a quasicrystalline structural liner from native material. The liner participates in the cavity's resonant mode structure, self-heals when damaged, and requires no imported materials.

V.11 Autonomous Navigation

Thermoelectric sensing across the processing face maps material composition and bond structure in all directions. The controller steers along the path of least bond energy, identifies ore bodies, avoids hazards, and branches into network topologies at Fibonacci-angle intervals for optimal resonant coupling.

V.12 Return Transport

For terrestrial operations: conventional muck removal of pre-fractured material (96.2% of excavated mass) plus annular gas flow (3.8%). For interstellar operations: surface processing station at tunnel mouth performs full dissociation with unrestricted power, loads separated elements into QC-coated autonomous containers, which traverse the return channel to Earth as containerized freight.

VI. CLAIMS

1. An autonomous matter processing system comprising: a processing head having an aperiodic nonlinear medium and a subcritical nuclear seed source that together generate a phi-frequency comb from broadband thermal energy at the processing face; a central bore through the system body through which dissociated gas-phase material flows from the processing face to a rear exhaust nozzle, providing propulsive thrust from the processed material; a self-generating resonant cavity behind the processing head whose Fibonacci-order modes amplify the phi-frequency comb; and a self-generating quasicrystalline liner formed by recondensation of dissociated material on QC-templating surfaces; wherein the system operates as a six-level energy cascade: nuclear seed, thermal drive, phi-comb structuring, gas expansion fracturing, mechanical sweep, and propulsive exhaust, with each level feeding and amplifying the next.

2. A method of matter removal using a nuclear-seeded phi-harmonic energy cascade, comprising: providing a subcritical nuclear source at or near a processing face to generate broadband thermal radiation and neutron flux; converting said thermal radiation into a phi-frequency comb through an aperiodic nonlinear medium; dissociating a surface layer of target material through resonant multi-step vibrational ladder climbing along the phi-comb; allowing the resulting confined gas expansion to fracture target material ahead of the processing face at pressures exceeding the material's compressive strength; sweeping fractured material with mechanical cutters; and routing dissociated gas through a central bore to a rear nozzle as propulsive exhaust.

3. A method of underwater drag reduction and material processing, comprising: providing an aperiodic nonlinear medium coating on a submerged vehicle hull; exciting said medium with waste heat from the vehicle's propulsion or a dedicated energy source; dissociating water at the hull surface into hydrogen and oxygen via the phi-frequency comb; wherein the hydrogen-enriched gas layer at the hull provides boundary layer density reduction, buoyant lift, and a gas-layer slip condition; and optionally tuning the phi-comb to process submerged structural materials including steel, concrete, and composites.

4. A method of supersonic or hypersonic drag reduction, comprising: providing an aperiodic nonlinear medium coating on aerodynamic surfaces of a vehicle traveling at supersonic or hypersonic speed; allowing aerodynamic heating to provide broadband thermal input to said medium; generating a phi-frequency comb that dissociates atmospheric molecules (H_2O, and at hypersonic speeds, N_2) at the vehicle surface; wherein the dissociated gas layer reduces boundary layer density, skin friction, and at hypersonic speeds, radiative heat transfer from the shock layer.

5. A method of subsurface mining with integrated refining, comprising: advancing a processing head through rock using the nuclear-seeded phi-harmonic cascade; identifying ore-bearing minerals versus waste rock by thermoelectric sensing; tuning the phi-frequency comb to selectively target ore mineral bond frequencies; collecting pre-fractured ore material while leaving waste rock in situ; and at a surface processing station, performing full phi-harmonic dissociation of ore material to produce separated elemental feedstock.

6. A method of calibrating a phi-harmonic processing system, comprising: placing the processing head against a standard concrete wall of known composition (Portland cement with quartz aggregate); providing broadband thermal input at 800+ C via electrical heater or nuclear source; measuring acoustic emission at the concrete surface to verify phi-harmonic content at Ca-O (15 THz) and Si-O (32 THz) vibration frequencies; measuring gas evolution rate to verify surface dissociation; and measuring reduction in drilling force in the pre-conditioned zone versus untreated zone, wherein a reduction exceeding 10% confirms operational phi-comb coupling.

7. An interstellar infrastructure construction and mining method, comprising: transiting an autonomous matter processing system to a destination planetary body; boring a tunnel network using the six-level energy cascade; pressurizing the network with oxygen from dissociated metal oxide bonds; lining the network with self-generating quasicrystalline material; processing excavated material at a surface station; and loading separated elements into

QC-coated autonomous containers for return through a traversal channel to Earth.

8. A self-propelled matter processing system wherein the vehicle uses its own processed material as propellant, routing dissociated gas through a central bore to a rear exhaust nozzle, requiring no external propellant supply for forward motion during processing.

9. The system of claim 1, wherein the nuclear seed source is a cartridge-replaceable subcritical HALEU assembly with a sealed Cf-252 or D-T neutron source, designed for robotic replacement every 6-12 months.

10. The system of claim 1, wherein the central bore diameter is 30-80 cm and routes gas at subsonic velocity (Mach < 0.5).

11. The method of claim 2, wherein the surface layer dissociated is 1-100 um deep, producing confined gas pressure of 0.5-5 GPa, exceeding the compressive strength of the target material by a factor of 3-25x.

12. The method of claim 2, wherein the thermal energy sources include any combination of: cutting heat, nuclear source, rocket exhaust, geothermal gradient, rock exothermic reactions, solar concentration, electrical drive, and gravitational potential energy.

13. The method of claim 3, wherein the vessel simultaneously processes submerged structures while producing breathing gas (O_2) and fuel (H_2) from surrounding seawater.

14. The method of claim 4, wherein the phi-comb converts aerodynamic heating into structured shock-layer spectral modification at hypersonic speeds, reducing radiative heat transfer to the vehicle.

15. The method of claim 5, wherein the thermoelectric sensor distinguishes ore from waste by Seebeck coefficient contrast and the controller adjusts the phi-comb target bond frequency in real time.

16. The method of claim 6, wherein the concrete calibration establishes a baseline coupling efficiency that is used to predict performance in other materials by scaling with bond energy ratio.

17. The system of claim 1, wherein a water-fed rocket provides supplemental thermal energy, with the water sourced from rock-bound water liberated during processing, creating a partial energy recovery loop.

18. The system of claim 1, further comprising branching capability wherein secondary bores at Fibonacci-angle intervals create a coupled resonator network with enhanced Q-factor.

19. The system of claim 8, wherein on water-bearing rock, dissociated hydrogen provides higher specific impulse exhaust than dissociated silicate gas, and the controller preferentially routes hydrogen to the nozzle.

20. The method of claim 7, wherein multiple autonomous units are deployed through the same traversal channel, each branching from the initial bore.

VII. MATHEMATICAL APPENDIX

The following key numerical values underlie all claims and specifications in this application.

A. Fundamental Constants

Constant	Value	Role
phi	1.618034	Golden ratio — frequency comb spacing
l	9.3 nm	Fundamental lattice spacing (Husmann)
h	6.626e-34 J-s	Planck constant
c	2.998e8 m/s	Speed of light
R	8.314 J/mol-K	Gas constant

B. System Parameters (Prufrock-Class)

Parameter	Value
Tunnel diameter	3.66 m (12 ft)
Face area	10.5 m2
TBM length	93.9 m (308 ft)
TBM mass	361,500 kg (797,000 lbs)
TBM thrust	20.9 MN (4.7M lbs)
Advance rate (soft ground)	0.26 mm/s (1 mile/week)
TBM power	~7 MW (estimated)
Cutting heat (95%)	6.65 MW
Acoustic waste (3%)	210 kW
Central bore diameter	50 cm
Central bore area	0.196 m2

C. Key Derived Values

Quantity	Value	Derivation
Surface layer gas rate	0.28 kg/s	3.8% of 7.4 kg/s total
Gas velocity in bore	14 m/s	2.8 m3/s / 0.196 m2
Mach number in bore	0.01	14 / 1400 m/s
Exhaust velocity	3,001 m/s	sqrt(2 x Cp x T), T=5000K
Specific impulse	306 s	v_e / g
Thrust from gas	0.9 kN	0.28 kg/s x 3001 m/s
Confined gas pressure	1.9 GPa	nRT/V, T=5000K
Pressure/strength ratio	9.3x	1.9 GPa / 0.2 GPa
Cut-plane bond energy	6.0 J/m2	8e18 bonds/m2 x 4.69 eV
Mech. energy per cm2 cut	~400 J	Shear strength x depth
Efficiency ratio	1:1,700,000	Mechanical vs bond energy

D. Application-Specific Parameters

Application	Primary Bond	E (eV)	Steps	Key Energy Source	Special Feature
Tunnel boring	Si-O	4.69	8	Cutting heat + nuclear	Cavity self-amplifies
Mining	varies	1-8	5-10	Cutting heat + rocket	Selective ore targeting
Concrete (cal.)	Ca-O	4.83	10	Electric heater (lab)	Baseline coupling test
Underwater	O-H + Fe-Fe	4.76/1.22	5/7	Propulsion waste heat	H2 drag reduction
Supersonic	O-H / N-N	4.76/9.8	5/11	Aerodynamic heating	Self-regulating drag
Asteroid	Si-O	4.69	8	Solar + nuclear	O2 atmosphere from rock
Demolition	Ca-O + Fe-Fe	4.83/1.22	10/7	Cutting + electric	~100% material recovery
Ice boring	O-H	4.76	5	Nuclear + solar	H2 fuel + O2 atmosphere

Table D: Complete application matrix.

VIII. ABSTRACT

Meridian's Transit: an autonomous matter processing system using a six-level nuclear-seeded phi-harmonic energy cascade. A subcritical nuclear source seeds broadband thermal at the processing face. An aperiodic nonlinear medium converts thermal energy into a golden-ratio frequency comb. The comb dissociates a surface layer of target material; the resulting confined gas expansion (1.9 GPa, 9x rock strength) fractures material ahead of mechanical cutters. Dissociated gas routes through a central bore to a rear exhaust nozzle, providing free propulsive thrust from processed material. A self-generating resonant cavity with Fibonacci-order mode amplification enhances the phi-comb as the cavity grows. A self-generating quasicrystalline liner forms from native material. Autonomous thermoelectric navigation steers along least-bond-energy paths. Applications: tunnel boring (any geology), mining (selective ore targeting), underwater travel and processing (H_2 drag reduction), supersonic/hypersonic flight (shock-layer modification), demolition, hazmat remediation, asteroid mining, ice boring, and interstellar infrastructure construction. Mathematical proofs of phi-ladder reachability, Fibonacci mode convergence, energy budget closure, gas expansion fracturing, and acoustic transport sufficiency are provided. Concrete wall calibration protocol establishes baseline coupling measurement.

Provisional patent application filed by Thomas A. Husmann, pro se. All rights reserved. Patent Pending.