

API Specification Document

Version: 1.0

Document Control

Version	Date	Author	Description
1.0	2026-03-13	Hardik Patel	Initial Version

Approvals

Name	Role	Approval Date
Hardik Patel	CTO	2026-03-14

Overview

This document describes the REST APIs used for managing Users in the system. These APIs follow REST principles and support the following operations.

- Create a user
- Retrieve users
- Retrieve a specific user
- Update a user
- Partially update a user
- Delete a user

Base URL

`https://api.example.com/api/{api_version}`

Example: `https://api.example.com/api/v1`

Authentication

All APIs require authentication using a Bearer token.

Example header: `Authorization: Bearer {access_token}`

Standard Headers

Header	Required	Description
Authorization	Yes	Bearer access token
Content-Type	Yes	application/json

Standard Error Format

All APIs return errors in the following format.

```
{
  "status": "failure",
  "code": "APP_ERROR_CODE",
  "message": "HUMAN_READABLE_MESSAGE",
  "data": {}
}
```

Pagination Format

List APIs follow this response structure.

```
{
  "page": 1,
  "limit": 20,
  "total": 100,
  "data": []
}
```

API Index

#	API	Method	Endpoint	Description
1	Create User	POST	/users	Create a new user
2	Get All Users	GET	/users	Retrieve all users
3	Get User By ID	GET	/users/{user_id}	Retrieve user by ID
4	Update User	PUT	/users/{user_id}	Replace user details
5	Patch User	PATCH	/users/{user_id}	Partially update user
6	Delete User	DELETE	/users/{user_id}	Delete user

API Specifications

1. Create User

Description	Creates a new user in the system.	
Endpoint	/users	
HTTP Method	POST	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	<pre>{ "firstName": "John", "lastName": "Doe", "email": "john.doe@example.com", "phone": "+919876543210", "status": "active" }</pre>	
Success Response	<pre>{ "status": "success", "code": 1001, "message": "User created successfully.", "data": { "id": "usr_101", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "phone": "+919876543210", "status": "active", "createdAt": "2026-03-13T10:00:00Z" } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1051, "message": "First name is missing in the request.", "data": {} }</pre>	
HTTP Status Codes	201	User created successfully
	400	Bad request
	401	Unauthorised
	500	Internal server error
Application Codes	1001	User created successfully

	1051	First name is missing in the request
	1052	Last name is missing in the request
	1053	Email address is missing in the request

Request Body Schema

Field	Type	Required	Description
firstName	String	Yes	User's first name
lastName	String	Yes	User's last name
email	String	Yes	User's email address
phone	String	No	User's phone number
status	String	Yes	User's status (active/inactive)

Response Body Schema

Field	Type	Description
status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers
id	String	Unique ID of the user created
firstName	String	User's first name
lastName	String	User's last name
email	String	User's email address
phone	String	User's phone number
status	String	User's status (active/inactive)
createdAt	Timestamp	Timestamp when user was created

2. Get All Users

Description	Returns a paginated list of users.	
Endpoint	/users?page={page_number}&limit={page_limit}	
HTTP Method	GET	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	NA	
Success Response	<pre>{ "status": "success", "code": 1002, "message": "Users retrieved successfully.", "data": { "page": 1, "limit": 20, "total": 100, "data": [{ "id": "usr_101", "firstName": "John", "lastName": "Doe", "email": "john@example.com" }] } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1061, "message": "Failed to fetch list of users.", "data": {} }</pre>	
HTTP Status Codes	200	Success
	401	Unauthorized
	500	Internal server error
Application Codes	1002	Users retrieved successfully
	1061	Failed to fetch list of users

Query Parameters

Parameter	Type	Required	Description
page	Integer	No	Page number
limit	Integer	No	Number of results per page

Response Body Schema

Field	Type	Description
status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers
page	Integer	Current page number
limit	Integer	Number of results per page
total	Integer	Total number of results
id	String	Unique ID of the user created
firstName	String	User's first name
lastName	String	User's last name
email	String	User's email address

3. Get User By ID

Description	Returns a specific user.	
Endpoint	/users/{user_id}	
HTTP Method	GET	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	NA	
Success Response	<pre>{ "status": "success", "code": 1003, "message": "User retrieved successfully.", "data": { "id": "usr_101", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "phone": "+919876543210", "status": "active" } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1062, "message": "User not found.", "data": {} }</pre>	
HTTP Status Codes	200	Success
	404	User not found
	500	Internal server error
Application Codes	1003	User retrieved successfully
	1062	User not found

Path Parameters

Parameter	Type	Required	Description
user_id	String	Yes	Unique ID of the user to be fetched

Response Body Schema

Field	Type	Description
status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers
id	String	Unique ID of the user created
firstName	String	User's first name
lastName	String	User's last name
email	String	User's email address
phone	String	User's phone number
status	String	User's status (active/inactive)

4. Update User

Description	Update a specific user.	
Endpoint	/users/{user_id}	
HTTP Method	PUT	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	<pre>{ "firstName": "Tom", "lastName": "Doe", "phone": "+919876543210", "status": "active" }</pre>	
Success Response	<pre>{ "status": "success", "code": 1004, "message": "User updated successfully.", "data": { "id": "usr_101", "firstName": "Tom", "lastName": "Doe", "email": "john@example.com", "phone": "+919876543210", "status": "active" } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1062, "message": "User not found.", "data": {} }</pre>	
HTTP Status Codes	200	Success
	404	User not found
	500	Internal server error
Application Codes	1004	User updated successfully
	1062	User not found

Path Parameters

Parameter	Type	Required	Description
user_id	String	Yes	Unique ID of the user to be updated

Request Body Schema

Field	Type	Required	Description
firstName	String	Yes	User's first name to be updated
lastName	String	Yes	User's last name to be updated
email	String	Yes	User's email address to be updated
phone	String	No	User's phone number to be updated
status	String	Yes	User's status (active/inactive) to be updated

Response Body Schema

Field	Type	Description
status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers
id	String	Unique ID of the user created
firstName	String	User's first name
lastName	String	User's last name
email	String	User's email address
phone	String	User's phone number
status	String	User's status (active/inactive)

5. Patch User

Description	Partially update a specific user.	
Endpoint	/users/{user_id}	
HTTP Method	PATCH	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	<pre>{ "phone": "+919876543211", }</pre>	
Success Response	<pre>{ "status": "success", "code": 1004, "message": "User updated successfully.", "data": { } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1062, "message": "User not found.", "data": {} }</pre>	
HTTP Status Codes	200	Success
	404	User not found
	500	Internal server error
Application Codes	1004	User updated successfully
	1062	User not found

Path Parameters

Parameter	Type	Required	Description
user_id	String	Yes	Unique ID of the user to be updated

Request Body Schema

Field	Type	Required	Description
firstName	String	Yes	User's first name to be updated
lastName	String	Yes	User's last name to be updated
email	String	Yes	User's email address to be updated
phone	String	No	User's phone number to be updated
status	String	Yes	User's status (active/inactive) to be updated

Response Body Schema

Field	Type	Description
status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers

6. Delete User

Description	Delete a specific user.	
Endpoint	/users/{user_id}	
HTTP Method	DELETE	
Headers	Authorization	Bearer {token}
	Content-Type	application/json
Request	NA	
Success Response	<pre>{ "status": "success", "code": 1005, "message": "User deleted successfully.", "data": { } }</pre>	
Error Response	<pre>{ "status": "failure", "code": 1062, "message": "User not found.", "data": {} }</pre>	
HTTP Status Codes	204	User deleted
	404	User not found
	500	Internal server error
Application Codes	1005	User deleted successfully
	1062	User not found

Path Parameters

Parameter	Type	Required	Description
user_id	String	Yes	Unique ID of the user to be deleted

Response Body Schema

Field	Type	Description
-------	------	-------------

status	String	Status of API execution (success/failure)
code	Integer	Application Codes, to be used by client apps for localization
message	String	Human readable message, for developers