

Advanced Java CompletableFuture Features: Introducing Completion Stage Methods

Douglas C. Schmidt

d.schmidt@vanderbilt.edu

www.dre.vanderbilt.edu/~schmidt



Professor of Computer Science


**Institute for Software
Integrated Systems**

**Vanderbilt University
Nashville, Tennessee, USA**



Learning Objectives in this Part of the Lesson

- Understand advanced features of completable futures, e.g.
 - Factory methods initiate async computations
 - Completion stage methods chain together actions to perform async result processing & composition



Completion Stage Methods Chain Actions Together

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing

Interface `CompletionStage<T>`

All Known Implementing Classes:

`CompletableFuture`

```
public interface CompletionStage<T>
```

A stage of a possibly asynchronous computation, that performs an action or computes a value when another `CompletionStage` completes. A stage completes upon termination of its computation, but this may in turn trigger other dependent stages. The functionality defined in this interface takes only a few basic forms, which expand out to a larger set of methods to capture a range of usage styles:

- The computation performed by a stage may be expressed as a `Function`, `Consumer`, or `Runnable` (using methods with names including *apply*, *accept*, or *run*, respectively) depending on whether it requires arguments and/or produces results. For example, `stage.thenApply(x -> square(x)).thenAccept(x -> System.out.print(x)).thenRun(() -> System.out.println())`. An additional form (*compose*) applies functions of stages themselves, rather than their results.
- One stage's execution may be triggered by completion of a single stage, or both of two stages, or either of two stages. Dependencies on a single stage are arranged using methods with prefix *then*. Those triggered by completion of *both* of two stages may *combine* their results or effects, using correspondingly named methods. Those triggered by *either* of two stages make no guarantees about which of the results or effects are used for the dependent stage's computation.

See docs.oracle.com/javase/8/docs/api/java/util/concurrent/CompletionStage.html

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
                ("846122553600669882"),
    new BigInteger
        ("188027234133482196"),
    false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
                ::toMixedString)
    ...
```

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result

*Create an unreduced
big fraction variable*

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
        ::toMixedString)
    ...
```

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
                ("846122553600669882"),
    new BigInteger
        ("188027234133482196"),
    false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

*Create a supplier lambda
variable that will reduce
the big fraction*

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
                ::toMixedString)
    ...
```

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
                ("846122553600669882"),
              new BigInteger
                ("188027234133482196"),
              false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
                ::toMixedString)
    ...
```

This factory method will asynchronously reduce the big fraction supplier lambda

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
        ::toMixedString)
    ...
```

*thenApply()'s action is
triggered when future from
supplyAsync() completes*

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result
- Methods can be chained together "fluently"

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
        ::toMixedString)
    .thenAccept(System.out::println);
```

thenAccept()'s action is triggered when future from thenApply() completes

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
 - A dependent action runs on a completed async call result
 - Methods can be chained together "fluently"
 - Each method registers a lambda action to apply

REGISTER

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
        ::toMixedString)
    .thenAccept(System.out::println);
```


Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result
- Methods can be chained together "fluently"
 - Each method registers a lambda action to apply
 - A lambda action is called only after previous stage completes successfully

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

CompletableFuture



```
.supplyAsync(reduce)
.thenApply(BigFraction
    ::toMixedString)
.thenAccept(System.out::println);
```



This is what is meant by "chaining"

Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing
- A dependent action runs on a completed async call result
- Methods can be chained together "fluently"
 - Each method registers a lambda action to apply
 - A lambda action is called only after previous stage completes successfully

```
BigFraction unreduced = BigFraction
    .valueOf(new BigInteger
        ("846122553600669882"),
        new BigInteger
            ("188027234133482196"),
        false); // Don't reduce!
```

```
Supplier<BigFraction> reduce = () ->
    BigFraction.reduce(unreduced);
```

```
CompletableFuture
    .supplyAsync(reduce)
    .thenApply(BigFraction
        ::toMixedString)
    .thenAccept(System.out::println);
```



Action is "deferred" until previous stage completes & fork-join thread is available

Completion Stage Methods Chain Actions Together

- Use completion stages to avoid blocking a thread until the result *must* be obtained



Completion Stage Methods Chain Actions Together

- Use completion stages to avoid blocking a thread until the result *must* be obtained, e.g.
- Try not to call `join()` or `get()` unless absolutely necessary



Servers may avoid blocking completely, whereas clients may need `join()` sparingly


Completion Stage Methods Chain Actions Together

- Use completion stages to avoid blocking a thread until the result *must* be obtained, e.g.
 - Try not to call `join()` or `get()` unless absolutely necessary
 - The goal is to improve responsiveness



Completion Stage Methods Chain Actions Together

- A completable future can serve as a "completion stage" for async result processing



<<Java Class>>	
G CompletableFuture<T>	
•	CompletableFuture()
•	cancel(boolean):boolean
•	isCancelled():boolean
•	isDone():boolean
•	get()
•	get(long,TimeUnit)
•	join()
•	complete(T):boolean
•	supplyAsync(Supplier<U>):CompletableFuture<U>
•	supplyAsync(Supplier<U>,Executor):CompletableFuture<U>
•	runAsync(Runnable):CompletableFuture<Void>
•	runAsync(Runnable,Executor):CompletableFuture<Void>
•	completedFuture(U):CompletableFuture<U>
•	thenApply(Function<?>):CompletableFuture<U>
•	thenAccept(Consumer<? super T>):CompletableFuture<Void>
•	thenCombine(CompletionStage<? extends U>,BiFunction<?>):CompletableFuture<V>
•	thenCompose(Function<?>):CompletableFuture<U>
•	whenComplete(BiConsumer<?>):CompletableFuture<T>
•	allOf(CompletableFuture[]<?>):CompletableFuture<Void>
•	anyOf(CompletableFuture[]<?>):CompletableFuture<Object>

Juggling is a good analogy for completion stages!

End of Advanced Java CompletableFuture Features: Introducing Completion Stage Methods