

Streaming Bayes GFlowNets



Tiago da Silva, Daniel Augusto de Souza, Diego Mesquita

Keywords — GFlowNets, Variational Bayesian inference

I. Background: GFlowNets

GFlowNets are amortized algorithms for sampling from distributions over compositional objects, i.e., over objects that can be sequentially constructed from an initial state through the application of simple actions (e.g., graphs via edge-addition).




Figure 1: An illustration of the state graph as a DAG on \mathcal{S} .

To accomplish this, we learn a forward $p_F(\tau)$ and backward $p_B(\tau|x)$ policies on a state graph (illustrated above) such that

$$Z p_F(\tau) = p_B(\tau|x) R(x), \quad (1)$$

in which R is the unnormalized distribution of interest and Z is its partition function. If this condition is satisfied for each τ ,

$$p_\tau(x) = \sum_{\tau \leadsto x} p_F(\tau) \propto R(x), \quad (2)$$

ensuring that the correctness of the generative process.

II. Streaming Bayes GFlowNets

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim aequale doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguere possit, augeri amplificarique non possit. At etiam Athenis, ut e patre audiebam facere et urbane Stoicos irridere, statua est in quo a nobis philosophia defensa et collaudata est, cum id, quod maxime placeat, facere possimus, omnis.




Figure 2: Streaming amortized inference with SB-GFlowNets.

We introduce Streaming Bayes GFlowNets (SB-GFlowNets) as a general-purpose tool for streaming Bayesian inference over discrete spaces. Our model leverages a GFlowNet as a surrogate prior when updating the current posterior approximation based on new data, thereby avoiding to repeatedly process old data and significantly accelerating training convergence in a streaming setting.

Linear preference learning with integer-valued features.




Figure 3: SB-GFlowNets accurately sample from the posterior distribution over the utility in integer-valued preference learning.

Streaming Bayesian structure learning with DAG-GFlowNets.




Figure 4: SB-GFlowNets accurately sample from an evolving belief distribution in a structure learning setting.

Online Bayesian phylogenetic inference.




Figure 5: SB-GFlowNet's probability mass associated to the true phylogenetic tree increases as we observe more sequences.

		Model		
		GFlowNet	SB-GFlowNet	% ↑
# of leaves	7	2846.88 s	1279.68 s	0%
	9	3779.11 s	1714.49 s	-2%
	11	4821.74 s	2303.99 s	0%

SB-GFlowNets achieve faster training convergence than conventional GFlowNets in a streaming context — while maintaining a comparable performance in terms of the TV distance (right column).
(Results averaged across 3 runs.)