

ADVANCED NETWORK SECURITY AND ARCHITECTURES

METI

Report Module 2 [EN]

Authors:

José Oliveira (103771)

Afonso Mendes (116024)

Tiago Videira (116069)

jose.novais.oliveira@tecnico.ulisboa.pt

afonsofmenDES@tecnico.ulisboa.pt

tiago.g.videira@tecnico.ulisboa.pt

Group 3

Contents

1	Introduction	2
2	IKEv1 with Pre-Shared Keys	3
3	IKEv1 with Digital Signatures	4
3.1	Introduction	4
3.2	Topology Overview	4
3.3	PKI Installation Verification	4
3.3.1	CA Configuration and Certificate (RA)	4
3.3.2	Router Certificates (R1)	5
3.3.3	RSA Public Keys (R1 and R2)	6
3.3.4	Summary	8
3.4	SCEP Enrollment Analysis	8
3.4.1	CA Certificate Retrieval	8
3.4.2	Certificate Enrollment Request	9
3.5	Encrypted ICMP Traffic Analysis	10
3.6	ISAKMP and SA Re-establishment Analysis	12

1 Introduction

2 IKEv1 with Pre-Shared Keys

3 IKEv1 with Digital Signatures

3.1 Introduction

This section describes the configuration and analysis of IPSec VPN using IKEv1 with digital certificates (PKI-based authentication using SCEP). The objective is to replace pre-shared keys with RSA signatures issued by a Certification Authority (CA).

3.2 Topology Overview

RA operates as the Certification Authority (CA) and NTP server. R1 and R2 establish an IPSec tunnel authenticated using RSA signatures and certificates obtained through SCEP enrollment.

3.3 PKI Installation Verification

The Certification Authority (CA) and router certificates were verified using IOS show commands.

3.3.1 CA Configuration and Certificate (RA)

The CA is configured on router RA and operates in automatic enrollment mode.

```
RA#show crypto pki server
Certificate Server myCA:
  Status: enabled
  State: enabled
  Server's configuration is locked (enter "shut" to unlock it)
  Issuer name: cn=saarCA
  CA cert fingerprint: 46CB9C10 CC370311 8CFCB545 E4DD2F58
  Granting mode is: auto
  Last certificate issued serial number (hex): 1
  CA certificate expiration timer: 16:17:23 UTC May 14 2029
  CRL NextUpdate timer: 22:17:23 UTC May 15 2026
  Current primary storage dir: nvram:
  Database Level: Minimum - no cert data written to storage
```

The CA certificate installed on RA confirms that RA is acting as a trusted root authority:

```
RA#show crypto ca certificate
CA Certificate
  Status: Available
  Certificate Serial Number (hex): 01
  Certificate Usage: Signature
  Issuer:
    cn=saarCA
  Subject:
```

```
cn=saarCA
Validity Date:
  start date: 16:17:23 UTC May 15 2026
  end   date: 16:17:23 UTC May 14 2029
Associated Trustpoints: myCA
Storage: nvram:saarCA#1CA.cer
```

The detailed certificate view confirms RSA key usage and X.509 extensions:

```
RA#show crypto ca certificate verbose
CA Certificate
Status: Available
Version: 3
Certificate Serial Number (hex): 01
Certificate Usage: Signature
Issuer:
  cn=saarCA
Subject:
  cn=saarCA
Validity Date:
  start date: 16:17:23 UTC May 15 2026
  end   date: 16:17:23 UTC May 14 2029
Subject Key Info:
  Public Key Algorithm: rsaEncryption
  RSA Public Key: (1024 bit)
Signature Algorithm: MD5 with RSA Encryption
Fingerprint MD5: 46CB9C10 CC370311 8CF5B545 E4DD2F58
Fingerprint SHA1: 0B6BF47E F0932FC1 54A33FA8 4C1F48D1 80083958
X509v3 extensions:
  X509v3 Key Usage: 86000000
    Digital Signature
    Key Cert Sign
    CRL Signature
  X509v3 Subject Key ID: 42BD5391 0D07D957 6CC26630 AABA09E4 A93162E2
  X509v3 Basic Constraints:
    CA: TRUE
  X509v3 Authority Key ID: 42BD5391 0D07D957 6CC26630 AABA09E4 A93162E2
  Authority Info Access:
Associated Trustpoints: myCA
Storage: nvram:saarCA#1CA.cer
```

3.3.2 Router Certificates (R1)

R1 successfully enrolled with the CA and received both the CA certificate and its own identity certificate:

```
R1#show crypto pki certificates
```

Certificate

Status: Available
Certificate Serial Number (hex): 03
Certificate Usage: General Purpose
Issuer:
 cn=saarCA
Subject:
 Name: R1
 Serial Number: 9S08DYF8WAKSOLHEG3ZVL
 hostname=R1+serialNumber=9S08DYF8WAKSOLHEG3ZVL
Validity Date:
 start date: 16:33:16 UTC May 15 2026
 end date: 16:33:16 UTC May 15 2027
Associated Trustpoints: myTrustpoint

The CA certificate is also stored locally to validate the trust chain:

CA Certificate

Status: Available
Certificate Serial Number (hex): 01
Certificate Usage: Signature
Issuer:
 cn=saarCA
Subject:
 cn=saarCA
Validity Date:
 start date: 16:17:23 UTC May 15 2026
 end date: 16:17:23 UTC May 14 2029
Associated Trustpoints: myTrustpoint

3.3.3 RSA Public Keys (R1 and R2)

The RSA public keys generated on R1 and R2 are extracted using the following IOS command:

```
show crypto key mypub rsa
```

R2 RSA Public Key:

```
R2#show crypto key mypub rsa
% Key pair was generated at: 16:32:05 UTC May 15 2026
Key name: R2
Key type: RSA KEYS
Storage Device: private-config
Usage: General Purpose Key
Key is not exportable.
Key Data:
```

```
30819F30 OD06092A 864886F7 OD010101 05000381 8D003081 89028181 00C337FE
B0DAEE4D 444B0AF7 A19A73B3 2D2FCD5E 27E09095 3017E393 2F27F7AA 581894E6
5E7F50B3 0454ACF2 FD1E8E24 F91125DD 6D611D93 611D70AD 36C59F6F EAEE003C
7704B6DB 41D9A165 27252864 17170DA2 F38A68D4 46C91133 36DBCBC5 B09AD90E
0F05531B F7ABB4A5 0B954C0F 389C2195 3DE377FF 7FE63FB3 B02DF189 35020301
0001
```

% Key pair was generated at: 16:57:46 UTC May 16 2026

Key name: R2.server

Key type: RSA KEYS

Temporary key

Usage: Encryption Key

Key is not exportable.

Key Data:

```
307C300D 06092A86 4886F70D 01010105 00036B00 30680261 00A38B5F B33F29E4
E5E30AFB 512084C9 0A89E015 BCA1569A C10C686B B79BD8EC C3C25CAD 6EE74C8F
C891E5FF 1B042503 710EC940 65712523 377F2776 77CDC4C0 D7D61754 57C88063
19BF191B F48130CC 327EF733 1F877D95 5CB74450 AEEF7E99 45020301 0001
```

R1 RSA Public Key:

R1#show crypto key mypub rsa

% Key pair was generated at: 16:31:43 UTC May 15 2026

Key name: R1

Key type: RSA KEYS

Storage Device: private-config

Usage: General Purpose Key

Key is not exportable.

Key Data:

```
30819F30 OD06092A 864886F7 OD010101 05000381 8D003081 89028181 00DF87BB
11BD33EE C4E9DF4A C2FF2CCB 2ECCEFF9 713AAA45 633ADE4A C188109E 88680D67
FBOA2F20 67257007 79DB3616 75D5459A 4898DE69 E74E80BA 77C993E8 A4B70D41
00D1D2FB E37BF0E3 89C8BEEE 9830712E 8A4C13DC E30C5C72 D72FEDF2 A221F6DB
9A1A1B8F 9A69BC61 3700CA1B B66DB044 72F24609 E0C1FE8D 24D1B3DA DD020301
0001
```

% Key pair was generated at: 16:57:42 UTC May 16 2026

Key name: R1.server

Key type: RSA KEYS

Temporary key

Usage: Encryption Key

Key is not exportable.

Key Data:

```
307C300D 06092A86 4886F70D 01010105 00036B00 30680261 0095CC14 73EE9BA8
1B0A40A6 E3EE90C1 BC2FAADF 2D532270 160D9039 C19C40CA 6A4E54B5 BAB8892C
D266AE9A 53210F58 876755F6 381C44B6 5D71F57F 35705BC5 3E8D9746 61833A6A
DB5E740B 8A22A486 83EE7AFA ACAB3798 27D03FC2 7C6EA875 FD020301 0001
```

Both routers generate 1024-bit RSA key pairs used for digital signature authentication during IKEv1 Phase 1.

3.3.4 Summary

The outputs confirm that:

- RA is correctly configured as a trusted CA (myCA).
- R1 has successfully obtained a signed X.509 certificate from the CA.
- The certificate chain is self-signed at the CA level.
- RSA key pairs are generated locally on each router and are bound to X.509 certificates issued by the CA for IKEv1 authentication using digital signatures.
- Both R1 and R2 possess locally generated RSA key pairs used for authentication and certificate binding in IKEv1.

3.4 SCEP Enrollment Analysis

SCEP (Simple Certificate Enrollment Protocol) is used to automate certificate distribution between routers and the CA using HTTP.

The enrollment process consists of:

- CA certificate request
- CA certificate response
- Router certificate request
- Router certificate issuance

3.4.1 CA Certificate Retrieval

Initially, R1 requests the CA certificate using the SCEP `GetCACert` operation over HTTP.

Time	Source IP	Source Port	Destination IP	Destination Port	Protocol	Length	Info
41.93.199538	200.1.1.1	224.0.0.5	OSPF	94 Hello Packet			
42.93.563621	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet			
43.95.110005	200.1.1.1	200.1.1.10	TCP	60 19426 - 80 [SYN] Seq=0 Win=4128 Len=0 MSS=1460			
44.95.124859	200.1.1.10	200.1.1.1	TCP	60 80 - 19426 [SYN, ACK] Seq=0 Ack=1 Win=4128 Len=0 MSS=1460			
45.125.125787	200.1.1.10	200.1.1.10	TCP	60 19426 - 80 [ACK] Seq=1 Ack=1 Win=4128 Len=0			
46.95.126857	200.1.1.1	200.1.1.10	HTTP	211 GET /cgi-bin/pkiclient.exe?operation=GetCACert&message=myTrustpoint HTTP/1.0			
47.95.134954	200.1.1.10	200.1.1.1	TCP	60 80 - 19426 [ACK] Seq=1 Ack=158 Win=3971 Len=0			
48.95.145088	200.1.1.10	200.1.1.1	TCP	310 80 - 19426 [ACK] Seq=1 Ack=158 Win=3971 Len=256 [TCP segment of a reassembled PDU]			
49.95.145161	200.1.1.10	200.1.1.1	HTTP	603 HTTP/1.1 200 OK (application/x-x509-ca-cert)			
50.95.146222	200.1.1.1	200.1.1.10	TCP	60 19426 - 80 [ACK] Seq=158 Ack=807 Win=7195 Len=0			
51.95.147128	200.1.1.1	200.1.1.10	TCP	60 19426 - 80 [FIN, PSH, ACK] Seq=158 Ack=807 Win=7195 Len=0			
52.95.148580	200.1.1.10	200.1.1.1	TCP	60 36405 - 80 [SYN] Seq=0 Win=4128 Len=0 MSS=1460			
53.95.155158	200.1.1.10	200.1.1.1	TCP	60 80 - 19426 [ACK] Seq=807 Ack=159 Win=3971 Len=0			
54.95.155211	200.1.1.10	200.1.1.1	TCP	60 80 - 36405 [SYN, ACK] Seq=0 Ack=1 Win=4128 Len=0 MSS=1460			
55.95.156565	200.1.1.1	200.1.1.10	TCP	60 36405 - 80 [ACK] Seq=1 Ack=1 Win=4128 Len=0			
56.95.157423	200.1.1.1	200.1.1.10	HTTP	211 GET /cgi-bin/pkiclient.exe?operation=GetCACaps&message=myTrustpoint HTTP/1.0			
57.95.165271	200.1.1.10	200.1.1.1	TCP	60 80 - 36405 [ACK] Seq=1 Ack=158 Win=3971 Len=0			
58.95.165334	200.1.1.10	200.1.1.1	TCP	310 80 - 36405 [ACK] Seq=1 Ack=158 Win=3971 Len=256 [TCP segment of a reassembled PDU]			
59.95.165348	200.1.1.10	200.1.1.1	HTTP	112 HTTP/1.1 200 OK (application/x-pki-message)			
60.95.166484	200.1.1.1	200.1.1.10	TCP	60 36405 - 80 [ACK] Seq=158 Ack=316 Win=7686 Len=0			
61.95.167437	200.1.1.1	200.1.1.10	TCP	60 36405 - 80 [FIN, PSH, ACK] Seq=158 Ack=316 Win=7686 Len=0			
62.95.175347	200.1.1.10	200.1.1.1	TCP	60 80 - 36405 [ACK] Seq=316 Ack=159 Win=3971 Len=0			
63.95.185428	ca:01:16:60:00:00	ca:01:16:60:00:00	LOOP	60 Reply			

Hypertext Transfer Protocol
HTTP/1.1 200 OK
Date: Fri, 15 May 2026 16:29:14 GMT
Server: cisco-IOS
Content-Type: application/x-x509-ca-cert
Expires: Fri, 15 May 2026 16:29:14 GMT
Last-Modified: Fri, 15 May 2026 16:29:14 GMT
Cache-Control: no-store, no-cache, must-revalidate
Pragma: no-cache
Accept-Ranges: none

[HTTP response 1/1]
[Time since request: 0.018384000 seconds]
[Request in frame: 46]
[Request URI: http://200.1.1.10/cgi-bin/pkiclient.exe?operation=GetCACert&message=myTrustpoint]
File Data: 511 bytes

Media Type
Media type: application/x-x509-ca-cert (511 bytes)

Figure 1: SCEP GetCACert request and CA certificate response

The CA replies with an HTTP 200 OK message containing an X.509 CA certificate with media type `application/x-x509-ca-cert`. This certificate allows R1 to establish trust with the Certification Authority before certificate enrollment.

3.4.2 Certificate Enrollment Request

After establishing trust with the CA, R1 performs certificate enrollment using the SCEP `PKIOperation` request.

169	330.534670	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet	
170	333.552158	ca:01:16:00:00:00	CDP/VTP/DTP/PagP/UD..	CDP	349 Device ID: RA Port ID: FastEthernet0/0	
171	335.184788	ca:01:16:00:00:00	ca:01:16:00:00:00	LOOP	60 Reply	
172	335.756061	200.1.1.1	224.0.0.5	OSPF	94 Hello Packet	
173	336.711505	200.1.1.1	200.1.1.10	TCP	60 55472 -> 80 [SYN] Seq=0 Win=4128 Len=0 MSS=1460	
174	336.730971	200.1.1.10	200.1.1.1	TCP	60 80 -> 55472 [SYN, ACK] Seq=0 Ack=1 Win=4128 Len=0 MSS=1460	
175	336.731861	200.1.1.1	200.1.1.10	TCP	60 55472 -> 80 [ACK] Seq=1 Ack=1 Win=4128 Len=0	
176	336.732806	200.1.1.1	200.1.1.10	TCP	1514 55472 -> 80 [ACK] Seq=1 Ack=1 Win=4128 Len=1460 [TCP segment of a reassembled PDU]	
177	336.740658	200.1.1.10	200.1.1.1	TCP	60 80 -> 55472 [ACK] Seq=1 Ack=1461 Win=2668 Len=0	
178	336.740715	200.1.1.10	200.1.1.1	TCP	60 [TCP Window Update] 80 -> 55472 [ACK] Seq=1 Ack=1461 Win=4128 Len=0	
+	179	336.743055	200.1.1.1	HTTP	907 GET /cgi-bin/pkiclient.exe?operation=PKIOperation&message=MIIF7QYJKoZIhvcNAQcCoIIF3jCCBdoCAQE	
+	180	336.750752	200.1.1.10	200.1.1.1	TCP	310 80 -> 55472 [ACK] Seq=1 Ack=2314 Win=3275 Len=256 [TCP segment of a reassembled PDU]
+	181	336.901694	200.1.1.10	200.1.1.1	TCP	1259 80 -> 55472 [ACK] Seq=257 Ack=2314 Win=3275 Len=1205 [TCP segment of a reassembled PDU]
+	182	336.904198	200.1.1.1	200.1.1.10	TCP	60 55472 -> 80 [ACK] Seq=2314 Ack=1462 Win=6539 Len=0
+	183	336.904245	200.1.1.1	200.1.1.10	TCP	60 [TCP Window Update] 55472 -> 80 [ACK] Seq=2314 Ack=1462 Win=8000 Len=0
+	184	336.911797	200.1.1.10	200.1.1.1	TCP	166 80 -> 55472 [ACK] Seq=1462 Ack=2314 Win=3275 Len=112 [TCP segment of a reassembled PDU]
+	185	336.911885	200.1.1.10	200.1.1.1	HTTP	71 HTTP/1.1 200 OK (application/x-pki-message)
+	186	336.916080	200.1.1.1	200.1.1.10	TCP	60 55472 -> 80 [ACK] Seq=2314 Ack=1592 Win=7871 Len=0
+	187	336.916127	200.1.1.1	200.1.1.10	TCP	60 55472 -> 80 [FIN, PSH, ACK] Seq=2314 Ack=1592 Win=7871 Len=0
+	188	336.918179	200.1.1.10	200.1.1.1	TCP	60 80 -> 55472 [ACK] Seq=1592 Ack=2315 Win=3275 Len=0
+	189	339.758848	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet
+	190	340.502206	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60 Reply
+	191	344.963500	200.1.1.1	224.0.0.5	OSPF	94 Hello Packet
+	192	345.184696	ca:01:16:00:00:00	ca:01:16:00:00:00	LOOP	60 Reply

Response Phrase: OK
Date: Fri, 15 May 2026 16:33:16 GMT\r\n
Server: cisco-IOS\r\n
Content-Type: application/x-pki-message\r\n
Expires: Fri, 15 May 2026 16:33:16 GMT\r\n
Last-Modified: Fri, 15 May 2026 16:33:16 GMT\r\n
Cache-Control: no-store, no-cache, must-revalidate\r\n
Pragma: no-cache\r\n
Accept-Ranges: none\r\n
\r\n
[HTTP request 1/1]
[Time since request: 0.16883000 seconds]
[\[Request in frame: 179\]](#)
[Request URI [truncated]: http://200.1.1.10/cgi-bin/pkiclient.exe?operation=PKIOperation&message=MIIF7QYJKoZIhvcNAQcCoIIF3jCCBdoCAQExCzAJBgUrDgMCGGUAMICvgYJKoZI%0Ahvfv
File Data: 1297 bytes

Media Type
Media type: application/x-pki-message (1297 bytes)

Figure 2: SCEP PKIOperation certificate enrollment request

The HTTP request contains a PKCS#10 certificate signing request (CSR) encoded in the message field. The CSR includes the router identity and its RSA public key, allowing the CA to generate a signed X.509 certificate for R1.

The captured HTTP messages show certificate exchange between R1 and the CA. The content-type field indicates certificate payload transfer (.crt).

Using Wireshark, the packet containing the issued certificate was identified by filtering HTTP traffic and locating the response message with a **Media Type** indicating a certificate object. The packet was then selected, and the certificate data was extracted by right-clicking on the relevant field and choosing *Export Packet Bytes*. The file was saved with a .crt extension, which allows it to be decoded as an X.509 certificate.

packet.crt	
saarCA	
Identity:	saarCA
Verified by:	saarCA
Expires:	14/05/2029
Details	
Subject Name	
CN (Common Name):	saarCA
Issuer Name	
CN (Common Name):	saarCA
Issued Certificate	
Version:	3
Serial Number:	01
Not Valid Before:	2026-05-15
Not Valid After:	2029-05-14
Certificate Fingerprints	
SHA1:	0B 6B F4 7E F0 93 2F C1 54 A3 3F A8 4C 1F 48 D1 80 08 39 58
MD5:	46 CB 9C 10 CC 37 03 11 8C FC B5 45 E4 DD 2F 58
Public Key Info	
Key Algorithm:	RSA
Key Parameters:	05 00
Key Size:	1024
Key SHA1 Fingerprint:	BD 39 CD 1B 6D A4 0C CF 6A 75 25 4D A0 C5 53 AE 85 8D 41 C9
Public Key:	30 81 89 02 81 81 00 A3 6A 1F EA 2A 1C B5 81 9D E4 BF CA 59 FD D2 76 17 CF 05 D2 AD 94 AD 74 EA BC 27 C2 45 7C 45 6D 2F C0 5E D9 DC B2 30 B8 51 67 9A 20 38 40 55 A2 9C D0 F8 9C 75 46 D2 0A 07 70 82 66 58 58 3D 5E 2E 18 FE FB 94 81 ED 2F A0 95 67 EB A4 97 AA 82 BC 13 CD C3 5B 9E 22 F9 DC ED 01 75 92 5A EB 61 25 E1 2A 38 33 83 A3 47 76 59 8F 0F 02 03 01 00 01
Basic Constraints	
Certificate Authority:	Yes
Max Path Length:	Unlimited
Critical:	Yes
Key Usage	
Usages:	Digital signature $\rightarrow$ Certificate signature $\rightarrow$ Revocation list signature
Critical:	Yes
Extension	
Identifier:	2.5.29.35
Value:	30 16 80 14 42 BD 53 91 0D 07 D9 57 6C C2 66 30 AA BA 09 E4 A9 31 62 E2
Critical:	No
Subject Key Identifier	
Key Identifier:	42 BD 53 91 0D 07 D9 57 6C C2 66 30 AA BA 09 E4 A9 31 62 E2
Critical:	No
Signature	

Figure 3: HTTP packet carrying the issued X.509 certificate (.crt file export in Wireshark)

The exported certificate represents the CA-signed identity certificate for R1. It contains the subject information, the public key corresponding to R1, and the digital signature generated by the CA, which validates its authenticity within the PKI infrastructure.

3.5 Encrypted ICMP Traffic Analysis

After configuring IPsec with RSA-signature authentication, connectivity between PC1 and PC2 was successfully verified using ICMP echo requests (ping).

Traffic was captured on the public network between R1 and R2 while the ping operation was performed.

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60	Reply
2	3.889135	200.1.1.10	224.0.0.5	OSPF	94	Hello Packet
3	5.482695	ca:01:16:60:00:00	ca:01:16:60:00:00	LOOP	60	Reply
4	6.320045	2.2.2.2	1.1.1.1	ESP	166	ESP (SPI=0xb87d2aab)
5	7.009428	1.1.1.1	2.2.2.2	ESP	166	ESP (SPI=0x147d646a)
6	7.269011	200.1.1.1	224.0.0.5	OSPF	94	Hello Packet
7	8.171183	2.2.2.2	1.1.1.1	ESP	182	ESP (SPI=0xb87d2aab)
8	8.188890	1.1.1.1	2.2.2.2	ESP	182	ESP (SPI=0x147d646a)
9	8.221515	2.2.2.2	1.1.1.1	ESP	182	ESP (SPI=0xb87d2aab)
10	8.239182	1.1.1.1	2.2.2.2	ESP	182	ESP (SPI=0x147d646a)
11	8.282182	2.2.2.2	1.1.1.1	ESP	182	ESP (SPI=0xb87d2aab)
12	8.299668	1.1.1.1	2.2.2.2	ESP	182	ESP (SPI=0x147d646a)
13	8.322552	2.2.2.2	1.1.1.1	ESP	182	ESP (SPI=0xb87d2aab)
14	8.339979	1.1.1.1	2.2.2.2	ESP	182	ESP (SPI=0x147d646a)
15	8.362850	2.2.2.2	1.1.1.1	ESP	182	ESP (SPI=0xb87d2aab)
16	8.380385	1.1.1.1	2.2.2.2	ESP	182	ESP (SPI=0x147d646a)
17	10.028466	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60	Reply
18	13.658516	200.1.1.10	224.0.0.5	OSPF	94	Hello Packet
19	15.485532	ca:01:16:60:00:00	ca:01:16:60:00:00	LOOP	60	Reply
20	15.847636	2.2.2.2	1.1.1.1	ESP	166	ESP (SPI=0xb87d2aab)
21	16.864505	200.1.1.1	224.0.0.5	OSPF	94	Hello Packet
22	17.007888	1.1.1.1	2.2.2.2	ESP	166	ESP (SPI=0x147d646a)
23	20.042916	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60	Reply


```

▶ Frame 7: 182 bytes on wire (1456 bits), 182 bytes captured (1456 bits) on interface -, id 0
▶ Ethernet II, Src: ca:01:16:60:00:00 (ca:01:16:60:00:00), Dst: 0c:35:d9:73:00:00 (0c:35:d9:73:00:00)
▼ Internet Protocol Version 4, Src: 2.2.2.2, Dst: 1.1.1.1
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  ▶ Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 168
    Identification: 0x011d (285)
  ▶ Flags: 0x00
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 254
    Protocol: Encap Security Payload (50)
    Header Checksum: 0xb501 [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 2.2.2.2
    Destination Address: 1.1.1.1
  ▼ Encapsulating Security Payload
    ESP SPI: 0xb87d2aab (3095210667)
    ESP Sequence: 61

```

Figure 4: Encrypted IPSec traffic observed between R1 and R2

The Wireshark capture shows that the ICMP packets exchanged between PC1 and PC2 are not visible in plaintext on the public network. Instead, the packets appear encapsulated using ESP (Encapsulating Security Payload).

The ESP packets contain encrypted payload data, preventing direct inspection of the original ICMP echo request and echo reply contents. Only the external IP header remains visible, showing communication between the tunnel endpoints (R1 and R2).

This confirms that IPSec is correctly providing:

- **Confidentiality** through payload encryption
- **Integrity protection** through ESP authentication
- **Secure tunnel encapsulation** between the two sites

The observed ESP traffic corresponds to the IPSec transform-set configuration:

```
crypto ipsec transform-set myTSet esp-aes esp-sha-hmac
```

AES is used for encryption while SHA-HMAC is used for integrity verification.

3.6 ISAKMP and SA Re-establishment Analysis

To analyze tunnel re-establishment, the IPSec Security Associations (SAs) were manually cleared using:

```
clear crypto session
```

While capturing traffic on the public network, new ISAKMP exchanges were observed as the routers negotiated fresh IPSec Security Associations.

1 0.000000	1.1.1.1	2.2.2.2	ESP	166 ESP (SPI=0x37bfac13)
2 1.087267	2.2.2.2	1.1.1.1	ESP	166 ESP (SPI=0x3aa0a0ef)
3 1.968939	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet
4 4.571026	200.1.1.1	224.0.0.5	OSPF	94 Hello Packet
5 5.111299	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60 Reply
6 5.470172	ca:01:16:60:00:00	ca:01:16:60:00:00	LOOP	60 Reply
7 7.109808	ca:01:16:60:00:00	CDP/VTP/DTP/PagP/UD...	CDP	349 Device ID: RA Port ID: FastEthernet0/0
8 8.201714	1.1.1.1	2.2.2.2	ISAKMP	118 Informational
9 8.203333	1.1.1.1	2.2.2.2	ISAKMP	134 Informational
10 8.217971	2.2.2.2	1.1.1.1	ISAKMP	134 Informational
11 8.888812	1.1.1.1	2.2.2.2	ISAKMP	210 Identity Protection (Main Mode)
12 8.901438	2.2.2.2	1.1.1.1	ISAKMP	150 Identity Protection (Main Mode)
13 8.907525	1.1.1.1	2.2.2.2	ISAKMP	414 Identity Protection (Main Mode)
14 8.931954	2.2.2.2	1.1.1.1	ISAKMP	434 Identity Protection (Main Mode)
15 8.968150	1.1.1.1	2.2.2.2	ISAKMP	742 Identity Protection (Main Mode)
16 9.012585	2.2.2.2	1.1.1.1	ISAKMP	742 Identity Protection (Main Mode)
17 9.031615	1.1.1.1	2.2.2.2	ISAKMP	230 Quick Mode
18 9.054747	2.2.2.2	1.1.1.1	ISAKMP	230 Quick Mode
19 9.072084	1.1.1.1	2.2.2.2	ISAKMP	102 Quick Mode
20 9.073561	1.1.1.1	2.2.2.2	ESP	150 ESP (SPI=0x59df71ad)
21 9.084887	2.2.2.2	1.1.1.1	ESP	150 ESP (SPI=0x08155835)
22 9.087434	1.1.1.1	2.2.2.2	ESP	166 ESP (SPI=0x59df71ad)
23 9.105426	2.2.2.2	1.1.1.1	ESP	150 ESP (SPI=0x08155835)
24 9.105619	2.2.2.2	1.1.1.1	ESP	166 ESP (SPI=0x08155835)
25 9.109976	1.1.1.1	2.2.2.2	ESP	150 ESP (SPI=0x59df71ad)
26 9.110573	1.1.1.1	2.2.2.2	ESP	262 ESP (SPI=0x59df71ad)
27 9.125696	2.2.2.2	1.1.1.1	ESP	182 ESP (SPI=0x08155835)
28 9.127906	1.1.1.1	2.2.2.2	ESP	134 ESP (SPI=0x59df71ad)
29 9.128484	1.1.1.1	2.2.2.2	ESP	150 ESP (SPI=0x59df71ad)
30 9.145928	2.2.2.2	1.1.1.1	ESP	166 ESP (SPI=0x08155835)
31 9.145991	2.2.2.2	1.1.1.1	ESP	134 ESP (SPI=0x08155835)
32 9.148997	1.1.1.1	2.2.2.2	ESP	166 ESP (SPI=0x59df71ad)
33 11.649739	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet
34 11.661379	1.1.1.1	2.2.2.2	ESP	150 ESP (SPI=0x59df71ad)
35 11.680534	2.2.2.2	1.1.1.1	ESP	150 ESP (SPI=0x08155835)
36 13.733941	1.1.1.1	2.2.2.2	ESP	182 ESP (SPI=0x59df71ad)
37 13.754607	2.2.2.2	1.1.1.1	ESP	182 ESP (SPI=0x08155835)
38 14.254637	200.1.1.1	224.0.0.5	OSPF	94 Hello Packet
39 15.160283	0c:35:d9:73:00:00	0c:35:d9:73:00:00	LOOP	60 Reply
40 15.468087	ca:01:16:60:00:00	ca:01:16:60:00:00	LOOP	60 Reply
41 16.248445	2.2.2.2	1.1.1.1	ESP	150 ESP (SPI=0x08155835)
42 16.264702	1.1.1.1	2.2.2.2	ESP	150 ESP (SPI=0x59df71ad)
43 18.238626	1.1.1.1	2.2.2.2	ESP	166 ESP (SPI=0x59df71ad)
44 18.409561	2.2.2.2	1.1.1.1	ESP	166 ESP (SPI=0x08155835)
45 20.827957	200.1.1.10	224.0.0.5	OSPF	94 Hello Packet

▶ Frame 1: 166 bytes on wire (1328 bits), 166 bytes captured (1328 bits) on interface -, id 0

Figure 5: ISAKMP exchanges after clearing crypto sessions

After the existing SAs were deleted, R1 and R2 initiated a new IKEv1 Phase 1 negotiation using ISAKMP messages over UDP port 500.

The captured exchange shows the following operations:

- ISAKMP SA proposal negotiation
- Exchange of nonces and Diffie-Hellman values
- Certificate exchange between peers

- RSA digital signature authentication
- Establishment of a new ISAKMP Security Association
- Negotiation of IPsec Phase 2 parameters
- Creation of new IPsec SAs for ESP traffic

The certificate-based authentication process relies on the X.509 certificates previously obtained from the CA through SCEP enrollment.

During authentication, each router validates:

- The peer certificate authenticity
- The CA signature
- The RSA signature generated during IKE authentication

Successful validation allows the tunnel to be securely re-established without the use of pre-shared keys.

The re-established IPsec tunnel was confirmed by successful encrypted ICMP communication between PC1 and PC2 after the negotiation process completed.