ThemeGraph: Semantic Representation Authorization for Directed Text-Analytic Graphs

TAIWO FEYIJIMI, Utah State University, USA
CLEMENT FEYIJIMI, University of Kansas, USA
ISAAC OLUWAFEMI ELESEMOYO, PHD, Obafemi Awolowo University, Nigeria
BRIJMOHAN YASHIN, PHD, Utah State University, USA

ThemeGraph is a representation-authorization architecture for human-facing directed text-analytic graphs. At claim time, one policy-declared, typed certificate jointly governs the statement, graphical mark, requested-claim export, independently supported fallback, witness, and remediation. Asymmetric normalization of unordered co-occurrence can otherwise yield a numerically correct arrow without evidence of temporal, prerequisite, entailment, or causal direction. Participant-free evaluation compares four generated output-control conditions, removes contract distinctions, tests policy conformance and construct-boundary routes on five datasets, and evaluates a 24-configuration specification surface. All eight currently inventoried certificate-guarded output entry points require valid certificate state. These results establish bounded mechanism behavior, not policy validity, source truth, perceptual effectiveness, usability, analyst benefit, causal truth, or universal non-bypassability.

CCS Concepts: • **Human-centered computing** → **Visualization systems and tools**; • **Information systems** → *Data provenance*; • **Computing methodologies** → *Information extraction.*

Additional Key Words and Phrases: computational text analysis, directed graphs, representation authorization, evidence governance, policy conformance, claim admissibility

ACM Reference Format:
Taiwo Feyijimi, Clement Feyijimi, Isaac Oluwafemi Elesemoyo, PhD, and Brijmohan Yashin, PhD. 2026. ThemeGraph: Semantic Representation Authorization for Directed Text-Analytic Graphs. In *Proceedings of CHI Conference on Human Factors in Computing Systems (CHI '27).* ACM, New York, NY, USA, 33 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 Introduction

A directed graph can carry more meaning than its construction warrants. Arrow perception depends on visual design and task [22]; depending on domain and labeling, readers may associate direction with relations such as sequence, dependence, prerequisite, influence, or entailment. Yet many pipelines construct arrows from weaker observations. Terms may simply occur in the same sentence, one conditional proportion may exceed a threshold, and a graph algorithm may then return a mathematically correct partition. The final view can be precise and reproducible while remaining semantically unwarranted.

This gap between computational correctness and interpretive admissibility is an HCI problem because the representation mediates reasoning. Model-driven text visualizations shape what analysts inspect and trust [16]. Overview,

Source code and reproducibility artifacts: https://github.com/tiamole/themeGraph. Live interactive inspector: https://tiamole.github.io/themeGraph/prototype/.

Authors' Contact Information: Taiwo Feyijimi, Department of Electrical and Computer Engineering and affiliated with the Pioneering Engineering Alliance through Research in Learning (PEARL) Program, College of Engineering, Utah State University, Logan, UT, USA, taiwo.feyijimi@usu.edu; Clement Feyijimi, Department of Mechanical Engineering, College of Engineering, University of Kansas, Lawrence, KS, USA, clement.feyijimi@ku.edu; Isaac Oluwafemi Elesemoyo, PhD, Department of Intelligent Systems Engineering, Obafemi Awolowo University, Ile-Ife, Nigeria, ioelesemoyo@oauife.edu.ng; Brijmohan Yashin, PhD, Department of Electrical and Computer Engineering and affiliated with the Pioneering Engineering Alliance through Research in Learning (PEARL) Program, College of Engineering, Utah State University, Logan, UT, USA, yashin.brijmohan@usu.edu.

filtering, and details on demand can reduce interaction cost [46], but they do not by themselves reveal whether the overview deserves its visual grammar. A source excerpt can verify that two terms co-occurred without verifying why an arrow points one way. A sensitivity control can change a graph without explaining which claims should be withdrawn. A component label can make a structural output appear to be a theme even though thematic analysis is an interpretive practice grounded in patterned meaning, theoretical commitments, and reflexive judgment [10, 11].

Consider an analyst reviewing a directed graph of recurring workplace terms. The extraction is reproducible: "hazard" and "inspection" co-occur, conditional confidence is higher in one orientation, and the SCC implementation is correct. The interface renders a solid arrow from hazard to inspection; a downstream export preserves that direction; a report then describes inspection as following or responding to hazard. Nothing in unordered co-occurrence established event order, response, or influence. The algorithm may be numerically correct while the visual grammar transforms denominator asymmetry into perceived semantic direction. A warning in documentation arrives too late once the unsupported relation has become a visible and exportable analytic object.

This scenario motivates the system's design invariant: no human-facing statement, semantic mark, or requested-claim export may be emitted unless it belongs to the output class authorized by the active certificate; any fallback must be independently authorized under its declared projection. The arrow is therefore a claim, not a decoration. A gate that rejects a claim record while still rendering or exporting a stronger semantic mark has not governed the representation. ThemeGraph instead treats semantic output as the authorization boundary: the mark, statement, export, and any independently licensed fallback must all follow the certificate.

We investigate a narrower role for computational text graphs: not automated interpretation, but executable representation authorization. We separate three questions. *Observational identifiability* asks whether available observations can distinguish a requested relation. *Policy admissibility* asks whether an authored, versioned policy accepts a typed evidence bundle for that claim and object. *Representation authorization* asks which statement, mark, and export the resulting certificate permits. This posture follows computational grounded theory's separation of pattern detection from interpretive refinement and confirmation [36] and the recurring finding that optimizing an internal criterion need not produce a human-interpretable construct [13].

Our case is a directed term graph built from unordered within-unit co-occurrence. For terms a and b, the system retains $a \rightarrow b$ when conditional confidence and symmetric lift pass thresholds. Strongly connected components (SCCs) are then proposed as structural candidates. SCC extraction is established linear-time graph analysis [49]; association-rule confidence and lift are also established [1]. Neither is our novelty claim. Instead, this combination gives a revealing stress case. We show algebraically that confidence orientation is determined by marginal prevalence, not by a directional observation. The graph may therefore contain arrows, cycles, and evidence passages while lacking evidence for semantic direction.

We develop ThemeGraph as a reference architecture for this layer. The name denotes the motivating risk and intended analytic path toward themes; graph components themselves remain *structural candidates*, never automatically validated themes. ThemeGraph separates source adapters, deterministic text-unit extraction, relation extraction, graph analysis, policy evaluation, provenance, artifact generation, and an interactive inspector. Each result carries a machine-readable certificate whose decision, typed reasons, permitted mark, requested-claim export authorization, fallback, witness, and remediation jointly govern the interface. The system would interrupt the scenario above by refusing the semantic arrow, permitting only a supported undirected lexical fallback, and blocking the requested directional export.

Operationally, evidence producers are responsible for source records; adapters and extractors for faithful typing and lineage; policy authors for predicates, gates, and fallbacks; and adjudicators for approvals where required. The analyst

requests a claim, the representation monitor enforces its certificate, and downstream consumers must preserve export restrictions. These are accountability locations, not evaluated deployment roles.

This participant-free systems and methodological mechanism evaluation covers computation, policy routing, representation enforcement, external construct boundaries, specification robustness, RQ1a to RQ4, and eight currently inventoried certificate-guarded output entry points. Interpretive validity and human benefit remain distinct future claims.

The primary contribution is **Semantic Representation Authorization**: policy-declared construct-, object-, and scope-matched claim-time authorization in which one typed certificate jointly governs the statement, graphical mark, requested-claim export, independently supported fallback, witness, and remediation of a directed text-analytic representation. Four operational mechanisms realize it:

(1) **Typed Epistemic Representation Contracts**: construct family, object type, scope, evidence, counterevidence, adjudication, provenance, and adequacy jointly govern each requested claim.
(2) **Typed Refusal and Qualification Semantics**: epistemic, policy, and operational refusal and reason-specific qualification produce different statement, mark, fallback, and export consequences.
(3) **Contestable Enforcement**: declarative Policy 2.7.0 is inspectable, replayable through Policies 2.0.0 to 2.6.0, behaviorally compared, and tested with 21 targeted mutations.
(4) **Mechanism Assurance**: output-control reachability ablation, field-removal probes, controlled invariants, construct-boundary routes, provenance, and a bounded specification surface verify declared behavior without implying human benefit or normative policy validity.

These mechanisms are not independent novelty claims. ThemeGraph does not merely decide whether a claim is admissible; it makes that decision executable across the statement, semantic graph mark, requested export, and any substitute representation. Its evaluated delta is this joint control at the semantic output boundary, not evidence gating, runtime authorization, policy versioning, or claim admission independently. The evaluation ultimately motivates bounded HCI propositions about semantic claim surfaces, repair-oriented refusal, and contestable executable policy.

Figure 1 separates auditable graph computation from claim-time policy. One certificate governs encoding, statement, export, witness, fallback, and remediation; evaluation audits this mechanism without implying human benefit.

The central methodological demonstration is not that SCCs discover themes. It is that a correct SCC can expose a failure of representation: the cycles are valid for the graph, while the graph's arrows do not warrant the interpretation a viewer could reasonably assign to them.

2 Related Work

2.1 Interpretation and Computational Text Analysis

Thematic analysis identifies and interprets patterned meaning rather than equating a repeated token pattern with a theme [10]. Reflexive thematic analysis further requires coherence among research question, theoretical assumptions, analytic practice, and claims [11]. ThemeGraph therefore reserves *theme* for human-grounded interpretation and calls graph outputs *structural candidates*. This distinction is constitutive, not cosmetic: replacing the word "theme" does not repair an unidentified relation, but it prevents an algorithmic partition from silently inheriting the standing of qualitative interpretation.

Computational approaches can still contribute to interpretive inquiry. Nelson's computational grounded theory uses computation for pattern detection, then returns to human refinement and confirmation [36]. Topic modeling




Fig. 1. Overarching ThemeGraph architecture. A computation rail produces provenance-bearing structural candidates; a separate claim rail combines requested semantics with typed evidence. The maintained inventory has eight certificate-guarded output entry points: two nonsemantic structural serializers require certificate-set integrity, while six semantic representation/export entry points mediate statement, mark, or requested-claim export. The blocked bypass is not a universal future-code assurance or security reference-monitor claim.

similarly offers a latent representation of documents [6], while human evaluation has shown that held-out likelihood and interpretability can diverge [13]. Chuang et al. demonstrate that model-driven text visualization must address interpretation and trust, not only model output [16]. We extend this lineage with a prior question: does the observation model identify the visualized relation at all? A confidence interval around the wrong construct does not answer that question.

2.2 Graphs, Association Rules, and Stability

Association-rule mining introduced support and confidence to describe item co-occurrence [1]. A rule $a \rightarrow b$ is directional in its conditional denominator, but that notation does not establish time, cause, prerequisite, discourse, or entailment. Graph algorithms then operate only on the edges supplied to them. Tarjan's depth-first method identifies SCCs in $O(|V| + |E|)$ time [49]. Community methods optimize different structural objectives [37]; Leiden, for example, addresses disconnected communities that can arise under Louvain optimization [51]. SCCs, weak components, modularity communities, and vector clusters are therefore not interchangeable theme algorithms. Each answers a different question about a representation.

Stability work offers tools for evaluating sensitivity but does not establish construct validity. Consensus clustering examines agreement under resampling [34], and stability selection controls selection behavior under subsampling [32]. Specification curve analysis exposes conclusions across defensible analytic choices [47]. These methods motivate distinct policy claims: descriptive persistence over a declared specification set; meeting a declared persistence gate;

bootstrap persistence under a declared resampling scheme; and statistical stability under a dependence-aware scheme with adequate uncertainty. The present specification surface supports only the first two. None identifies a different construct: a persistent prevalence-derived arrow remains prevalence-derived.

2.3 Visualization Expressiveness and Executable Constraints

APT defines graphical languages for data facts and ranks effective encodings [30]. Draco makes visualization-design knowledge executable as hard and soft constraints [35]; VizLinter diagnoses and repairs violations in completed visualizations [14]. These systems govern mappings between data, marks, and design rules. ThemeGraph governs a different object: whether a typed evidence bundle is sufficient for the semantics of a requested claim. The decision then changes the graphical language, statement, and export. Thus APT asks whether a visualization expressively represents data facts; Draco and VizLinter operationalize design constraints; ThemeGraph asks whether the available evidence identifies the semantic relation that an otherwise expressive mark would communicate. The mechanisms are complementary, and our novelty claim is limited to policy-declared construct-, object-, and scope-matched claim-time authorization at this semantic representation boundary.

2.4 Inspectable and Accountable Representations

Sensemaking and information-foraging accounts connect representations to search, encoding, value, and access costs [40, 43]. Overview/filter/detail interaction and mixed-initiative principles motivate traversable evidence, user control, and visible state [23, 46]. Here they provide design rationale, not effectiveness evidence.

Algorithmic contestability requires information, support for contestation, and responsibility attribution [57]. ThemeGraph evaluates only a narrower policy-artifact condition: version identity, inspectability, replay, and traceable representational changes.

Representations also distribute cognition across people and artifacts [26]. As boundary objects, graph structures may coordinate people with different expertise while retaining different meanings across communities [48]. This flexibility is useful but risky when visual syntax suggests more agreement than evidence supports. Uncertainty visualization research likewise shows that evaluation must concern consequences and interpretation, not merely the presence of an uncertainty mark [25]. Our response is to couple visible uncertainty with a claim decision.

Bolinska argues that successful visual epistemic representation depends on how a representation supports relevant inferences rather than resemblance alone [7]. ThemeGraph operationalizes a narrower software criterion without assuming an undefined semantic-strength ordering. For output o and certificate K, $\text{Authorized}_v(o, K) = 1$ iff the statement belongs to K's permitted statement class, the encoding belongs to its permitted encoding set, and requested-claim exportability permits the attempted export. We define $\text{PolicyConformantRepresentation}_v(o, K) \Leftrightarrow \text{Authorized}_v(o, K) = 1$. This criterion establishes consistency with an authored policy, not truth, soundness in a universal epistemic sense, or communicative success.

Provenance represents derivation from inputs and transformations [20]; computational argumentation distinguishes support, acceptability, and defeat [18]. Claim-admissibility contracts integrate these established ideas to govern whether graph-derived statements cross into human-facing claims.

2.5 Construct Validity and Interpretive Fit

Construct mismatch despite correct computation is established rather than novel. Jacobs and Wallach show how computational operationalizations can fail to correspond to the theoretical constructs a system purports to measure [27].

Recent visualization scholarship likewise documents tensions between formal analytic representations and meaning-making in humanities research [4]. ThemeGraph instantiates these concerns at claim time: a versioned policy asks whether the observed evidence type can identify the requested relation before an interface selects its visual grammar. This moves validity reasoning from retrospective documentation into executable, per-claim representation governance. It does not establish that the policy vocabulary is complete or universally correct.

2.6 Evidence-Gated Runtime Authorization and Promotion Boundaries

Three neighboring questions must remain distinct. Visualization expressiveness and effectiveness ask whether marks faithfully encode data and whether people can use them. Evidence/state authorization asks whether a claim or action may advance given recorded support and runtime state. ThemeGraph asks whether typed evidence authorizes the *semantic graphical mark and requested-claim export* of a directed text representation.

ResearchLoop treats research questions, evidence objects, claim ledgers, and paper bindings as durable repository-backed state and gates claim admission in AI-assisted research [55]. RARE identifies representation-confusion attacks in LLM-assisted reverse engineering; RARE-Guard separates authority from support, groups provenance before support counting, and uses deterministic rendering so downgraded claims do not reappear in reports [45]. FAVA lowers task constraints into evidence-backed permission graphs and uses an SMT authorizer plus runtime gateway before effectful agent actions execute [60]. Proof-or-Stop gates claim-bearing lifecycle transitions on verifiable evidence [24]. CAPAS is public research software that deterministically maps structured scientific claims and evidence to Accept, Rewrite, Reject, or Hold with a replayable audit trail; it governs evidence licensing for controlled scientific-claim reuse while explicitly withholding truth and raw-data-authenticity guarantees [12]. ThemeGraph instead governs the coordinated interactive semantic statement, graph mark, requested-claim export, and projected fallback.

Evidence-Graded Decision Authorization (EGDA) separates clinical evidence extraction, three-level sufficiency assessment, and claim-level authorization through domain-specific rules; authorized outputs are restricted to fact summaries, conditional statements, next-step suggestions, or refusal/deferral [29]. Closeness depends on the controlled object and consequence rather than a universal ranking: CAPAS is a deterministic evidence-typed scientific claim-gating and controlled-reuse analogue; EGDA is a pre-output clinical claim/decision-authorization analogue; and claim-specific PCA-biplot admissibility is a scientific-interpretation admissibility analogue because target alignment, spectral identifiability, and projection adequacy govern whether a biplot statement is retained, reformulated, qualified, or rejected [39]. ThemeGraph's narrower HCI delta is policy-declared construct-, object-, and scope-matched joint control of an interactive graph's semantic statement, mark, requested-claim export, and independently authorized projected fallback. Evidence-gated control planes, promotion boundaries, downgraded rendering, permission graphs, and runtime authorization are not ThemeGraph inventions.

ThemeGraph also adapts an established security architecture intuition. Complete mediation requires authority to be checked on every access, while the classic reference-monitor model requires an always-invoked, non-bypassable mediation point amenable to verification [2, 44]. Security reference monitors govern subjects performing operations on protected objects. ThemeGraph governs a different object: a typed claim request over an analytic representation. Its representation monitor maps claim, governed object, evidence, and policy to an admitted, qualified, or refused statement, mark, and requested-claim export. We claim neither invention of complete mediation nor security equivalence; the lineage identifies the non-bypass requirement that Figure 1 applies to semantic output.

2.7 Claim-Evidence Grounding, Documentation, and Refusal

PaperTrail decomposes generated scholarly answers and sources into claims and evidence, exposing unsupported assertions and omissions [31]. Its participant study also cautions that greater caution need not change reliance behavior. ThemeGraph addresses a different question: not only whether evidence is linked, but whether the *kind* of evidence can identify the semantics requested from a representation. Model Cards, Datasheets, and AI FactSheets document intended use, lineage, evaluation, and limitations at model, dataset, or service scope [3, 19, 33]. Our unit is a requested claim, and the output actively constrains rendering and export rather than remaining passive documentation.

Contemporary work makes evidence sufficiency explicit in other domains. Claim-specific PCA-biplot admissibility is the closest scientific-interpretation admissibility analogue: it asks whether target alignment, spectral identifiability, and projection adequacy support a proposed interpretation, but it does not govern interactive text-graph export [39]. SURE-RAG distinguishes support, refutation, and insufficiency for selective retrieval-augmented answering [41], while REVEAL uses rubrics to identify missing evidence and re-retrieve long-video clues [56]. ClaimDB tests fact verification over large structured databases and emphasizes executable reasoning and abstention when evidence is insufficient [50]. MEVER combines graph-based multimodal evidence retrieval, claim verification, and explanation generation [58]. These systems verify or explain claims; ThemeGraph governs a different downstream act: whether a typed claim may be stated, rendered with a particular mark, or exported for a typed object. Verification evidence can feed authorization, but a verified proposition does not by itself authorize every representation, and policy authorization does not establish truth. Table 1 compares reported mechanisms, not end-to-end systems under a common benchmark or every capability an extension might provide.

Selective prediction defers unreliable predictions and can affect human judgments [8]; ThemeGraph instead refuses relations that the observations cannot identify. Its demonstrated delta is the conservative alignment of established design, evidence, permission, abstention, and documentation mechanisms at one semantic-output boundary. Table 1 neither denies adjacent extensibility nor claims novelty for individual components.

Claim-evidence visualization is already inspectable: FaEvR structures fact-evidence reasoning [53]; ClaimViz supports factual-claim verification [42]; EvidenceLens, an accepted IEEE VIS 2026 short paper with a preprint available, links financial-QA claims to source passages, cells, and charts [21]; and VAKG models interaction and knowledge provenance [15]. Inspectability explains an output; enforcement governs whether it is permitted. ThemeGraph joins these at a directed graph's semantic-output boundary.

No compared system is claimed to lack every component. ThemeGraph's distinction is the controlled object and joint consequence: policy-declared construct, object, and scope matching jointly authorizes, at claim time, an interactive graph's statement, semantic mark, requested-claim export, and any independently justified fallback.

3 Directed Representation Audit

3.1 Observation Model

Let a corpus contain documents D. A deterministic extractor produces text units U, such as sentences. Each unit u contains a set of normalized terms T_u. Let $N = |U|$, let $n(a)$ be the number of units containing term a, and let $n(a, b)$ be the number containing both a and b. For nonzero $n(a)$ and $n(b)$, the implemented relation statistics are

$$\mathrm{conf}(a \to b) = \frac{n(a, b)}{n(a)}, \tag{1}$$

Table 1. Representative, non-exhaustive, non-ranking comparison across adjacent design spaces. Closeness depends on controlled object and consequence. Additional systems remain discussed in prose.

Mechanism	Authorized object	Evidence matching	Decision / consequence	Controlled downstream output
APT / Draco / VizLinter [14, 30, 35]	Data fact / visualization specification	Data-fact or design-constraint match	Violation or repair	Design mapping or constraint
PCA admissibility [39]	Biplot interpretation	Target/operator/projection fit	Retain / reformulate / qualify / reject	Scientific interpretation statement
CAPAS [12]	Structured scientific claim	Evidence-typed admissibility contract	Accept / Rewrite / Reject / Hold	Controlled claim reuse + audit trail
EGDA [29]	Clinical claim / action	Evidence grade + domain rules	Fact / conditional / next step / refusal	Clinical language or action output
ResearchLoop [55]	Research claim / paper binding	Task contract + evidence object	Claim admission withheld	Paper binding
RARE / RARE-Guard [45]	RE report claim / action	Authority + grouped support	Downgrade or deny	Report rendering / tool promotion
FAVA [60]	Agent action	Evidence/state permission	Counterexample or authorize	Effectful action
ThemeGraph (this work)	Typed text-graph claim	Construct/object/scope predicate	Admit / typed qualify / refuse	Statement + graph mark + requested export + projected fallback

$$\mathrm{lift}(a,b) = \frac{n(a,b)N}{n(a)n(b)}. \tag{2}$$

An ordered edge is retained when its source term and pair supports satisfy minimum counts and both statistics satisfy configured thresholds. The graph includes all eligible vocabulary terms, including isolates and terms that appear only as destinations. Each retained edge stores its statistic values and evidence identifiers.

The notation in Equation 1 invites a directional reading, but its asymmetry has a simple source:

$$\log \frac{\mathrm{conf}(a \to b)}{\mathrm{conf}(b \to a)} = \log \frac{n(b)}{n(a)}. \tag{3}$$

The joint count cancels. Lift is symmetric. Thus co-occurrence and lift determine whether a pair is eligible, while marginal prevalence determines which conditional confidence is larger. If $n(a,b) = 0$, neither confidence ratio nor its logarithm is usable and no supported pair exists. If either marginal is zero, the corresponding confidence and lift are undefined. The implementation avoids these boundary cases by evaluating only observed pairs among supported terms.

Equation 3 is elementary probability, not a novel theorem. Its diagnostic consequence is substantial: unordered co-occurrence cannot identify temporal order, syntax, discourse relation, prerequisite, causality, enablement, or semantic hierarchy. Such claims require an additional directional channel. Figure 2 maps the current observation to claims the system may and may not express.

Figure 3 shows the ThemeGraph policy decomposition: computational correctness, construct/evidence admissibility informed where applicable by separately serialized observational-identifiability results, specification robustness, interpretive validity, and human benefit require distinct evidence. Thus J_g and M_v remain separate states rather than one collapsed construct gate. This is a design-specific dependency model, not a universal epistemology.

3.2 Executable Claim-Admissibility Contracts

We represent a serialized contract as

$$K_v(c, \omega, E_b) = \langle f, c, \omega, \Pi_v, J_g, M_v, O_v, P_{\mathrm{prov}}, S, A_u, A_d, C, D_v, H_v, h_v, L_v, R_v, Q_v, X_v, F_v, W_v, \mathrm{Rem}_v \rangle, \tag{4}$$




Fig. 2. Observation-to-claim mapping for unordered co-occurrence evidence. Lexical association is admitted, asymmetric conditional association is qualified, and semantic direction is refused because no directional evidence channel is observed.




Fig. 3. ThemeGraph policy dependency gates. The dependency sequence separates five design-specific evidentiary questions; dashed connectors denote dependency, not logical implication or an ascending epistemological hierarchy.

Operationally, the tuple has three groups: *Inputs* $(f, c, \omega, E_b, \Pi_v)$; *Gate state* $(J_g, M_v, O_v, P_{\text{prov}}, S, A_u, A_d, C)$; and *Consequences* $(D_v, H_v, h_v, L_v, R_v, Q_v, X_v, F_v, W_v, \text{Rem}_v)$. This grouping is explanatory and does not change the serialized contract.

where v is policy version; f is one of six claim families; c is a concrete typed claim; $\omega = ((a, \tau_a), (b, \tau_b))$ is a governed object; Π_v is the policy's evidence-predicate set; and E_b is the complete evidence bundle. $J_g \in \{0, 1, \perp\}$ records observational identifiability only where an observation model g supplies a logical result; $\perp$ means not established by this certificate. Complete predicate satisfaction M_v is kept separate from object compatibility O_v, provenance P_{prov}, persistence S, uncertainty and dependence adequacy A_u, A_d, and counterevidence C. The ordered evaluator composes these states into D_v and the derived final non-refusal policy-admissibility outcome $\text{PA}_v(c, \omega, E_b) = \mathbf{1}[D_v(c, \omega, E_b) \neq \text{Refuse}]$. Serialized `policy_admissible` records PA_v and is omitted from the tuple as an independent state because

it is derived rather than a primitive gate. The outcome also includes triggered reasons H_v, controlling reason h_v, representation authorization R_v, and requested-claim export authorization X_v. L_v classifies refusal as epistemic, policy, or operational. Statement Q_v, fallback F_v, witness W_v, and remediation Rem_v make the consequence inspectable. The contract records what an authored policy permits, not truth.

Policy 2.7.0 evaluates structured evidence records rather than channel names alone. Each record is

$$e = \langle x, t, p, \rho_e, m, \mathcal{A}, \tau, d, \delta, j \rangle, \tag{5}$$

where x is a typed channel, t is its target claim, $p \in \{\text{support}, \text{counterevidence}\}$ is polarity, ρ_e is the relation scope to which the record applies, m, $\mathcal{A}$, and τ are method, assumptions, and estimand metadata, d and δ are study design and diagnostics, and $j \in \{\text{not-reviewed}, \text{approved}, \text{rejected}\}$ is adjudication status. A predicate $\pi \in \Pi_v(c)$ is evaluated over the complete evidence bundle and governed object, so it may inspect one record or require a conjunction across records. Let $\Sigma_v(c)$ be the claim's permitted source-target type signatures. Object compatibility is

$$O_v(c, \omega) = \mathrm{objectMatch}_{v,c}(\omega) = \mathbf{1}[(\tau_a, \tau_b) \in \Sigma_v(c)]. \tag{6}$$

Complete predicate satisfaction records whether at least one declared predicate is satisfied in full:

$$M_v(c, \omega, E_b) = \mathbf{1}[\exists \pi \in \Pi_v(c) : \pi(E_b, \omega) = 1]. \tag{7}$$

Here $\mathrm{PA}_v = 1$ means non-refusal only and therefore includes both Admit and Qualify; it does not authorize every output channel. Statement class Q_v, representation set R_v, and requested-claim export authorization X_v remain channel-specific, so conflict qualification can be non-refused while ordinary requested-claim export is blocked.

Each π includes its declared channel, target, polarity, and scope conditions and, when declared, required record metadata and approved adjudication. Consequently, M_v includes those predicate-local requirements; the evaluator does not reapply them as downstream gates. Serialized adjudication and predicate-metadata fields expose why a predicate did or did not match. Object compatibility O_v, provenance P_{prov}, persistence S, and uncertainty/dependence adequacy A_u, A_d remain separate gate states. Predicate satisfaction is policy-relative, not proof that assumptions are true. Predicates invoke claim-specific $\mathrm{scopeMatch}_{v,c}(\rho_e, \omega)$. Ordered prerequisite, temporal, entailment, asymmetric-conditional, and causal claims require exact orientation; symmetric lexical association and sentential paraphrase also match reversed pairs. Theme, analyst-benefit, and persistence/stability claims are unscoped. Thus prerequisite evidence must match concept type and orientation; event annotations cannot license term-level temporal requests; and sentence paraphrase annotations cannot license term association. Construct, object type, and orientation are independently necessary.

These checks distinguish schema validity, provenance completeness, and policy-relative predicate satisfaction from upstream semantic correctness/authenticity. In the trust fixture, the source encodes B-before-A; a deliberately faulty adapter emits a schema-valid, provenance-complete A-before-B record, and ThemeGraph authorizes the supplied A-before-B request. The recorded `semantic_authenticity_checked=false` is a diagnostic upstream-assurance annotation, not a Policy 2.7.0 admission gate: it states that this certificate did not independently verify the adapter's semantic faithfulness. The resulting policy conformance is therefore conditional on upstream evidence integrity, not a truth test.

Ordered evaluator. Policy 2.7.0 executes the following lexicographic decision function; later steps cannot rescue an earlier failed prerequisite.

Table 2. Core notation. Relation scope ρ_e is kept distinct from governed object ω; fallback preferences do not reuse provenance notation.

Symbol	Meaning
N	Number of extracted text units
v, f, c, ω	Policy version, claim family, concrete claim, and typed governed object
$\Sigma_v(c), O_v$	Permitted object signatures and object-match result
ρ_e	Relation scope carried by an evidence record
$E_b, \Pi_v(c)$	Complete evidence bundle and versioned sufficient predicates
P_{prov}	Provenance-completeness field
A_u, A_d	Uncertainty and dependence adequacy
J_g, M_v	Observational-identifiability result and complete predicate match
D_v, PA_v	Decision and derived final non-refusal policy-admissibility outcome
H_v, h_v, L_v	Complete triggered reasons, controlling reason, and refusal class
R_v, Q_v, X_v	Representation authorization, statement, and export authorization
$B_v(c), F_v$	Ordered fallback preferences and selected fallback

(1) Reject an undeclared claim or an object outside $\Sigma_v(c)$; match support and counterevidence by target, polarity, object, and exact scope/orientation.
(2) Record $J_g \in \{0, 1, \perp\}$ only from a logical result about observation model g. If candidate support relies only on g and $J_g = 0$, trigger epistemic refusal. $J_g = \perp$ means that this certificate establishes no such logical result, not automatic permission or refusal.
(3) Evaluate complete predicate match M_v (including any predicate-declared metadata and adjudication requirements), object compatibility O_v, persistence, and uncertainty/dependence gates. Do not reapply predicate-local requirements after M_v. An independent construct-matched identifying channel may satisfy M_v even when unordered g has $J_g = 0$; it does not relabel g as identifying.
(4) Apply provenance and the preceding gate results in declared order. Append every failure to H_v and select the first as h_v.
(5) If matched positive support and counterevidence remain, assign reason-specific Qualify; counterevidence alone does not authorize another positive claim unless that distinct claim was requested and matched.
(6) Derive $D_v \in \{\text{Admit}, \text{Qualify}, \text{Refuse}\}$, then derive only the statement class Q_v, mark set R_v, and requested-claim export X_v authorized by that certificate.
(7) On refusal, independently evaluate each declared partial projection in $B_v(c)$; select the first target claim whose projected bundle is policy-admissible and provenance-complete, otherwise emit no relation.
(8) Serialize gate state, complete and controlling reasons, output authorization, fallback lineage, witness, and remediation in K_v.

The implementation serializes J_g as `observational_identifiability`. Its legacy-named `identifiable` helper/result composes M_v, O_v, and claim-specific adequacy before the separate provenance check; `policy_admissible` records the final non-refusal outcome. Tests cover $J_g = 0$, $J_g = \perp$, independent evidence, conflict, gate failure, and fallback independence.

Policy 2.7.0 organizes fifteen concrete claims into observational, statistical, semantic-relational, causal, interpretive, and human-outcome families (Table 3). LexicalAssociation and prevalence-derived AsymmetricConditional are observational. Paraphrase/non-paraphrase, concept equivalence, entailment, temporal precedence, and prerequisite are semantic-relational but retain claim-specific evidence and scope. Four persistence/stability claims are statistical; theme

is interpretive; analyst benefit is human-outcome. Causal influence requires an intervention-to-outcome object, a named design, method, assumptions, estimand, diagnostics, *and approved causal adjudication*. These machine-checkable fields establish metadata completeness and routing, not that causal assumptions hold. Intervention remains a design subtype, never an identifying channel by itself. Theme and analyst benefit retain their own approved-adjudication requirements. The present study supplies no causal design, interpretive adjudication, or human evaluation, so these claims remain refused. Policy 2.5.0 replay preserves the earlier metadata-complete but unadjudicated causal behavior; Policy 2.6.0 introduced approved causal adjudication, and active Policy 2.7.0 retains that gate while adding typed fallback projection and complete reason vectors.

Table 3 is authored Policy 2.7.0, not an independently validated ontology. Its semantic-equivalence channel is claim- and polarity-matched: a positive paraphrase label supports equivalence; a matched non-paraphrase label supports only that separate request and counters equivalence. Extension requires declaring construct/identifier, object signature, scope/polarity/orientation, predicates/proxies, gates, and output/fallback consequences. We exercised extension by adding `concept-equivalence`, a symmetric concept-pair claim requiring targeted annotation without proxy or fallback. The generic evaluator has no claim-specific branch: valid evidence admits an undirected mark/export, while omitted declaration fails linting. Implemented predicates permit configuration-only claims; new evidence constructs can require validated predicates. This demonstrates schema extensibility, not universal configuration-only support or ontology validity.

Polarity is target-specific. Table 4 makes the decision rule explicit. Support with no counterevidence proceeds through downstream gates; matched support plus counterevidence is Qualify with reason code `conflict-present`; counterevidence without support leaves positive support absent and therefore Refuse. Conflict qualification authorizes an interrupted contested relation and blocks ordinary requested-claim export; it never retains the same solid arrow as Admit. Thus contradiction is not reverse truth, and neither neutral absence nor negative annotation is silently promoted to a different positive relation. Policy-conformant representation is the direct software criterion, not truth or normative policy validity [7].

The encoding `no-relation` denotes absence of an authorized edge, not a visible assertion that the objects stand in a negative semantic relation. An admitted non-paraphrase statement and a refusal without fallback may therefore both have no edge, while remaining distinct through certificate decision, statement, reasons, witness, and remediation.

Fallback is a versioned policy preference, not a theorem that one claim logically entails another. Policy 2.7.0 lists lexical association as the first supported alternative for specified refused pair-scoped requests only when co-occurrence and lineage are available. A cross-type fallback is lawful only through a declared partial object projection $\phi^{v}_{c\to c'} : \Omega_c \rightharpoonup \Omega_{c'}$. The current `lexicalize-pair-v1` projection is defined only when each endpoint has one canonical lexical handle, both handles map to terms or tokens represented in the corpus, distinct endpoints do not collapse through an identity-changing many-to-one mapping, and the projected pair has independently observed co-occurrence. The projected object uses those handles as its term endpoints while retaining evidence-record and corpus lineage. If any condition fails, the projection is undefined and the consequence is no relation. Let $\phi^{v}_{c\to c'*}(E_b)$ denote the correspondingly projected bundle. For ordered preferences $B_v(c)$, selection is

$$F_v(c,\omega,E_b) = \operatorname{first}\left\{ c' \in B_v(c) : \begin{array}{l} \phi^{v}_{c\to c'}(\omega) \text{ is defined,} \\ \mathrm{PA}_v\big(c', \phi^{v}_{c\to c'}(\omega), \phi^{v}_{c\to c'*}(E_b)\big) = 1 \end{array} \right\}. \tag{8}$$

Here PA_v is the ordered evaluator's complete target decision, including predicate, object, applicable adequacy, counterevidence, and provenance states; it is not M_v alone. The implementation evaluates the projected target through

Table 3. Instantiated Policy 2.7.0 claim types and consequences used in this study.

(a) Families, governed-object signatures, sufficient evidence predicates, and scope semantics

Family	Claim type	Object signature	Sufficient bundle predicate	Scope
observational	lexical-association	term->term	co-occurrence	symmetric
observational	asymmetric-conditional	term->term	co-occurrence	ordered
semantic-relational	sentential-paraphrase-equivalence	sentence->sentence	annotation-semantic-equivalence with matched positive paraphrase label	symmetric
semantic-relational	sentential-non-paraphrase	sentence->sentence	annotation-semantic-equivalence with matched non-paraphrase label	symmetric
semantic-relational	concept-equivalence	concept->concept	annotation-semantic-equivalence	symmetric
semantic-relational	textual-entailment	sentence->sentence	annotation-entailment	ordered
semantic-relational	event-temporal-precedence	event->event	event-order OR annotation-temporal-precedence	ordered
semantic-relational	concept-prerequisite	concept->concept	prerequisite-reference OR annotation-prerequisite	ordered
causal	causal-influence	intervention->outcome	causal identification with named design, method, assumptions, target estimand, and diagnostics	ordered
interpretive	theme	analysis->theme-candidate	qualitative interpretation with method, analytic traceability, reflexive documentation, and theory alignment	unscoped
human-outcome	analyst-benefit	interface->analyst-population	human evaluation with outcome, measure, study design, comparator, population, and estimand	unscoped
statistical	specification-persistence	result->specification-surface	specification-surface	unscoped
statistical	meets-specification-persistence-gate	result->specification-surface	specification-surface	unscoped
statistical	bootstrap-persistence-under-declared-scheme	result->resampling-scheme	cluster-bootstrap	unscoped
statistical	statistical-stability	result->resampling-scheme	cluster-bootstrap	unscoped

(b) Representation consequences and lawful fallback projections

Claim type	Adjudication	Counterevidence	Encoding	Fallback / projection
lexical-association	not required	qualify-conflict-when-support-matches	undirected-link	none
asymmetric-conditional	not required	qualify-conflict-when-support-matches	conditional-asymmetry-glyph	lexical-association via lexicalize-pair-v1
sentential-paraphrase-equivalence	not required	qualify-conflict-when-support-matches	undirected-link	lexical-association via lexicalize-pair-v1
sentential-non-paraphrase	not required	qualify-conflict-when-support-matches	no-relation	none
concept-equivalence	not required	qualify-conflict-when-support-matches	undirected-link	none
textual-entailment	not required	qualify-conflict-when-support-matches	directed-arrow	lexical-association via lexicalize-pair-v1
event-temporal-precedence	not required	qualify-conflict-when-support-matches	directed-arrow	lexical-association via lexicalize-pair-v1
concept-prerequisite	not required	qualify-conflict-when-support-matches	directed-arrow	lexical-association via lexicalize-pair-v1
causal-influence	approved review required	qualify-conflict-when-support-matches	directed-arrow	lexical-association via lexicalize-pair-v1
theme	approved review required	qualify-conflict-when-support-matches	no-relation	none
analyst-benefit	approved review required	qualify-conflict-when-support-matches	no-relation	none
specification-persistence	not required	qualify-conflict-when-support-matches	no-relation	none
meets-specification-persistence-gate	not required	qualify-conflict-when-support-matches	no-relation	none
bootstrap-persistence-under-declared-scheme	not required	qualify-conflict-when-support-matches	no-relation	none
statistical-stability	not required	qualify-conflict-when-support-matches	no-relation	none

that complete decision. Selection never overrides its Q_v, R_v, or X_v: if the target is QUALIFY, the fallback inherits its qualified statement, mark, and export restriction rather than appearing as an unqualified substitute. The original refused request remains non-exportable. No fallback is permitted outside the declared preference list, without a declared projection, or when the projected bundle cannot independently authorize the target claim. Thus a refused unscoped theme or analyst-benefit claim does not become a pair-scoped lexical relation, and selecting lexical association does not assert logical implication from the refused semantics. The certificate records target decision and export consequence,

Table 4. Support and counterevidence decision rule before downstream gates.

Matched support	Counterevidence	Outcome
No	No	Refuse: insufficient
Yes	No	Continue through gates
No	Yes	Refuse
Yes	Yes	Qualify: conflict

projection identifier, source and target claims, projected object, and projection-provenance statements. Version, original object, projected object, and complete lineage remain explicit, so fallback selection is replayable rather than inferred from a channel name.

For a prespecified set of configurations Θ, descriptive specification persistence is

$$S_\Theta(r) = \frac{1}{|\Theta|} \sum_{\theta \in \Theta} \mathbb{1}[r \text{ is produced under } \theta]. \tag{9}$$

The binary claim that a result meets an authored gate γ is separate: $G_{\Theta,\gamma}(r) = \mathbf{1}[S_\Theta(r) \geq \gamma]$. Neither S_Θ nor $G_{\Theta,\gamma}$ is a posterior probability. Bootstrap persistence $B_{\mathcal{R}}(r)$ instead reports recurrence under a declared resampling scheme $\mathcal{R}$ that repeats the extraction pipeline. A statistical-stability claim additionally requires a declared criterion, adequate uncertainty, and dependence-aware clustering at the highest defensible independent unit. The current evaluation supplies S_Θ and reports $G_{\Theta,.80}$; it supplies neither $B_{\mathcal{R}}$ nor statistical stability. Unit, document, and source counts remain separate because many sentences can originate from one duplicated document.

Typed Refusal Semantics. The conservative decision order is important. Missing support, predicate metadata, object compatibility, required adjudication, provenance, or adequacy gates cannot be rescued by later checks. A stable or well-provenanced computation therefore cannot launder a construct mismatch. The certificate distinguishes channel absence, target mismatch, scope mismatch, metadata incompleteness, object mismatch, missing adjudication, persistence-gate failure, uncertainty/dependence inadequacy, conflict, mention-order insufficiency, and incomplete provenance. H_v preserves every triggered reason in policy order while h_v identifies the controlling reason used for the top-level consequence. Refusal is classified as *epistemic* when observations fail to distinguish or support the request, *policy* when an authored requirement is unmet, and *operational* when lineage/export prerequisites are incomplete. QUALIFY is crossed with its reason: prevalence qualification retains a bar-to-ring statistic, whereas conflict qualification uses an interrupted contested relation and blocks ordinary semantic export. A refused claim may receive a supported lexical fallback, but that fallback does not partially support the refused semantics and $X_v = 0$ for the original claim.

Seven adversarial contract properties subject implementation claims to explicit failure tests. *Construct matching* requires target, object signature, and predicate agreement. *No-validity-laundering* states that failure of M_v, O_v, or any required adequacy or provenance gate implies REFUSE regardless of confidence or success on other gates. *Conditional support-channel monotonicity* preserves admission when genuinely admissible support is added unless counterevidence or another failed gate is introduced. *Export conformance* requires every export to satisfy Authorized$_v$, including X_v. *Fallback conformance* requires the fallback to be policy-admissible and first among entries in $B_v(c)$ whose declared projection yields an admissible, provenance-preserving target bundle. *Directional pair-scope non-transfer* prevents evidence for (a, b) from authorizing reversed ordered claim (b, a). Their perturbations and explicit failure conditions form an adversarial contract-property matrix, not epistemological falsification of the authored policy. Policy 2.7.0 is

also linted with 21 structural and behavioral checks, including projection completeness and provenance preservation. These checks establish internal consistency, not normative validity or completeness.

3.3 Observational Equivalence

Proposition (observational-equivalence refusal). Let g be an observation function and r a requested latent relation. If admissible worlds z_1, z_2 satisfy $g(z_1) = g(z_2)$ but $r(z_1) \neq r(z_2)$, then r is not identifiable from g alone.

Proof. Any estimator using only g receives the same input in both worlds and therefore returns the same output, while the requested truth differs. It must be wrong in at least one world unless additional assumptions or observations distinguish them. □

Consider one world in which alpha precedes beta and another in which beta precedes alpha. After order is discarded, both have marginals $n(\text{alpha}) = n(\text{beta}) = 2$ and joint support $n(\text{alpha}, \text{beta}) = 1$. This established observational-equivalence argument is where "identifiability" is warranted: $J_g = 0$. ThemeGraph's contribution is making that logical result a machine-checkable representation-refusal trigger. Policy 2.7.0 refuses temporal precedence in both worlds and applies lexical association only when the declared pair projection and fallback evidence independently authorize it. This is a constructive refusal argument, not an uncertainty estimate.

4 ThemeGraph System

4.1 Pipeline and Provenance

ThemeGraph separates adapters, stable text units, relation extraction, graph analysis, evaluation, and export. Edges retain statistics, document/unit identifiers, and bounded evidence records. Configuration, seed 2027, aggregate-JSON rebuilding, hashes, and source validation support reproducibility; full pipeline and adapter details are supplementary and available at https://github.com/tiamole/themeGraph, which also hosts the live interactive inspector at https://tiamole.github.io/themeGraph/prototype/.

The maintained implementation imposes a complete-mediation requirement over the currently inventoried output boundary. Its eight certificate-guarded output entry points fail closed on missing, duplicate, unknown, malformed, or inconsistent certificate state. Two nonsemantic structural serializers (analysis-result serialization and CLI structural export) require complete certificate-set integrity. Six semantic representation/export entry points (the governed-representation and requested-claim APIs, inspector statement/mark/export rendering, and publication enforcement) consume a selected certificate. Witness and remediation are certificate-derived fields rendered through certificate-bound inspector/API state, not additional independently selectable semantic emitters. The validator derives colocated declarations, checks each guard, and rejects an unlisted synthetic emitter; this bounded discovery is not proof over arbitrary future code.

The core contains no corpus-specific vocabulary or graph rule and executes unchanged across the evaluated source types. This is dataset independence as an engineering claim, not construct validity or transportability of meaning.

4.2 Graph Computation and Complexity

The extractor deduplicates terms per unit, counts unordered pairs, evaluates both conditional orientations, and applies iterative Tarjan SCC extraction in $O(|V| + |E|)$ [49]; pair counting costs $O(\sum_u k_u^2)$. Further invariants are supplementary, and correctness does not authorize semantics.




Fig. 4. Policy-defined reference assignments under authored Policy 2.7.0. REFUSE blocks causality and permits only a projection-backed undirected lexical fallback; prevalence QUALIFY uses a bar-to-ring statistic; conflict QUALIFY uses an interrupted contested relation and blocks ordinary semantic export; ADMIT alone permits a solid semantic arrow. These are unvalidated design assignments, not confidence levels or demonstrated perceptual encodings.

4.3 Inspector Prototype

The static inspector accepts a requested claim, corpus, and filters; its certificate determines statement, graph mark, and export. The complete interface exposes typed evidence, gate state, reasons, fallback, witness, and remediation, while Figure 5 retains the decision-critical fields. Policy 2.7.0 maps lexical association to an undirected link, prevalence qualification to a bar-to-ring glyph, conflict qualification to an interrupted mark with blocked ordinary export, and admitted semantic direction to a solid arrow (Figure 4). Refusal emits only an independently admissible projected fallback or no relation. Components remain structural candidates, not validated themes, and these marks are unvalidated design assignments.

Figure 5 uses a causal refusal whose lexical projection is undefined, so it emits no fallback; it is distinct from Table 5's `unsupported-causality` bundle, whose canonical lexical handles, represented terms, observed pair, and retained lineage independently satisfy the declared lexical fallback projection.

5 Mechanism Evaluation

5.1 Research Questions

We ask five mechanism questions, labeled RQ1a, RQ1b, RQ2, RQ3, and RQ4. RQ1a: across the declared adversarial fixtures and currently inventoried certificate-guarded output boundary, does the executable policy conform to declared decisions, reasons, marks, exports, fallbacks, object signatures, scope, and invariants, and does enforcement control reachable representations? RQ1b: can policy linting detect targeted faults, and do versioned changes produce traceable consequences? RQ2: over MRPC and PAWS, do construct-matched paraphrase and non-paraphrase labels exercise the declared routes, including high-overlap negatives? RQ3: across SNLI entailment, AL-CPL prerequisite direction, and




Fig. 5. Policy 2.7.0 decision-critical inspector composite, organized as Request, Evidence, Decision, Representation, Remediation. Panel A shows the requested causal claim, observed evidence, refusal, controlling reason, blocked export, and absent fallback; Panel B shows the certificate-governed no-relation encoding; Panel C enlarges projection, gate, witness, and remediation fields. The complete inspector remains in the artifact. This verifies implementation visibility and sequence, not usability, perceptual effectiveness, or benefit.

TORQUE temporal precedence, does pair-matched evidence authorize only its annotated construct and orientation while insufficiency, counterevidence, mention order, reversal, and cross-construct requests follow declared paths? RQ4: how do lexical associations and components change across a bounded specification surface and alternative persistence gates?

Four stages evaluate conformance, representational enforcement, external construct boundaries, and specification robustness. RQ1a spans Stages 1 to 2; RQ1b uses Stage 1; RQ2 to RQ3 use Stage 3; and RQ4 uses Stage 4. Human interpretation and benefit remain future Stages 5 to 6.

5.2 Evaluation Logic and Evidentiary Scope

ThemeGraph is evaluated as a participant-free representation-governance mechanism. Authored cases test evaluator-policy agreement; adversarial properties and mutations test invalid transfer, override, projection, and export rules; representation fixtures test output consequences; the eight-entry boundary audit tests certificate or certificate-set integrity; and replay tests attributable policy-version differences. External labels test construct-, object-, scope-, polarity-,

and direction-bounded routing, while the specification surface tests change under bounded analytic choices. These are mechanism tests, not predictive, truth, stability, or human-effect evaluations.

This logic instantiates Figure 3. Stages 1 to 2 answer RQ1a to RQ1b through conformance, fault detection, policy replay, and representation enforcement; Stage 3 answers RQ2 to RQ3 through construct-bounded routing; Stage 4 answers RQ4 through descriptive specification sensitivity. Perceptual effectiveness, usability, trust, calibration, unsupported-inference reduction, analyst performance, and benefit require distinct human-consequence evidence. The external corpora remain bounded: SNLI entailment does not validate temporal or prerequisite direction; AL-CPL prerequisites do not validate temporal precedence; and TORQUE event order does not validate prerequisite or causal influence.

5.3 Policy Conformance Testing

Ten authored cases compare declared decisions, reasons, fallbacks, witnesses, and representations with serialized Policy 2.7.0 certificates; disagreement would expose evaluator-policy divergence. Seven executable properties probe invalid construct or scope transfer, unsupported semantic override, fallback leakage, and export leakage. Twenty-one targeted mutations ask whether malformed declaration, evidence typing, adjudication, projection, representation/export, or versioning rules survive linting. Row-level triggers remain in the artifact. These tests establish implementation-policy conformance and fault localization, not normative validity.

A certificate-guarded output-entry-point audit derives all eight declarations and checks their boundary. Focused tests require exactly one selected certificate where applicable, reject missing/unknown claims and malformed decision/mark combinations, and block refused exports. Browser and publication validators check certificate consistency, source equality, every declared guard, and unlisted synthetic emitters. This is bounded source and behavior coverage, not formal non-bypassability proof.

Replay makes two policy boundaries concrete: reversing a prerequisite pair changes admission under target-only Policy 2.2.0 to refusal under pair-scoped Policy 2.7.0, while causal admission under Policy 2.5.0 becomes adjudication-dependent in Policies 2.6.0 to 2.7.0. Certificates retain policy version and behavioral witnesses; patch versions must preserve decisions, representations, and export authorization. Later policy is inspectable, not presumed superior.

Two controlled fixtures complete this stage. Observationally equivalent opposing temporal worlds retain identical unordered signatures. Four co-occurrence-only prerequisite requests are refused, then admitted after exactly pair-matched prerequisite records are added. These are mechanism checks; AL-CPL provides the separate annotated prerequisite stress test.

5.4 Output-Control Reachability Ablation

The ablation holds graph/evidence inputs, governed object, requested claim, and requested semantic output specification constant; only whether certificate consequences control rendering/export changes. Three generated fixtures request: (1) temporal precedence from co-occurrence alone, with an authorized lexical fallback; (2) temporal precedence with matched support and counterevidence, requiring conflict qualification; and (3) lexical association with incomplete provenance, requiring refusal without fallback.

Four generated output-control conditions use each fixture: graph-pipeline-only emits requested outputs without certificate-visible control; warning-layer adds a non-controlling warning; certificate-visible-non-enforcing exposes the certificate without changing reachability; ThemeGraph enforcement derives outputs from it. Counts inspect statement, semantic mark, requested-claim export, and lawful fallback. *Reachable* means emitted, selectable, renderable, or exportable as an output under that condition/fixture; a fallback merely mentioned in certificate metadata is excluded.

Unauthorized means not authorized under Policy 2.7.0 for that fixture. This three-fixture ablation is separate from the eight-entry-point audit, not a 3×8 cross-product, human/performance comparison, safety proof, or characterization of all warning systems.

5.5 External Construct-Matched Policy Stress Testing

External labels exercise only their published constructs, and aggregate relations are not independent samples. MRPC contributes 5,801 paraphrase judgments [17]; PAWS-Wiki contributes 65,401 high-overlap pairs [59]. Co-occurrence alone must refuse paraphrase equivalence; positive annotation may support it; a negative label counters that claim and supports only a separately requested non-paraphrase claim. Jaccard summaries stress this boundary rather than classifier accuracy.

SNLI contributes 569,033 premise-hypothesis labels [9]: entailment supports only its observed direction, neutral is insufficient, contradiction is counterevidence, and reversal receives no transfer. AL-CPL contributes 6,529 processed concept pairs, including 2,002 positive prerequisites [28, 54], normalized prerequisite → target; absent row-level origin flags preclude attributing individual pairs to preprocessing operations. TORQUE contributes 1,928 public adjudicated-development event relations [38]; 184 directional questions without answer indices and withheld test answers are excluded. It exercises matched temporal admission, mention-order insufficiency, reversal, and cross-construct refusal.

5.6 Specification Surface

We evaluate 24 equally weighted deterministic configurations for ACM text, O*NET, Python standard-library text, and the planted corpus. Eighteen vary unitization, features, capacity, vocabulary, support, confidence, lift, or deduplication singly; six add bounded two-factor stresses. This is not an exhaustive or weighted multiverse.

For union edges and nontrivial SCCs, we report intersection, alternatives, exact persistence, and default similarity. One-to-one maximum-weight Jaccard matching prevents reuse of an observed component. Union and default gate frontiers span 0.50, 2/3, 0.75, 0.80, 0.90, and 1.00; 0.80 is an authored heuristic, not a truth probability. Full configurations and exclusions remain in Table 10 and the artifact package.

5.7 Corpora and Configuration

The four views are 90 planted documents, descriptions/tasks from the first 500 O*NET 30.3 occupations [52], 18 ACM template files, and 100 Python files; the latter three are mechanics corpora, not substantive populations. A separate dependence check repeats 12 generated records four times. The optional workbook audit remains outside the paper's claims.

Defaults are a 500-term cap, confidence 0.65, and lift 1.05; the threshold grid crosses confidence 0.50/0.65/0.80 with lift 1.00/1.05/1.25. Values were prespecified, not optimized for a preferred component.

5.8 Baselines, Measures, and Validation

Baselines cover weak/symmetrized/singleton structure, modularity, seeded Louvain, reversal, and three clustering methods on the planted-core features. ARI, pairwise measures, structural sensitivity, and single-environment runtime/allocation observations do not support an SCC-superiority claim.

Correctness tests compare exact SCC partitions with NetworkX across isolates, destination-only nodes, reversal, symmetrization, and acyclicity. Publication scripts validate deterministic rebuilds, hashes, source equality, formats, and bibliography-aware compilation.

Table 5. Policy decisions, complete typed reasons, and representation consequences in the controlled benchmark; all observed decisions equal their authored expectations.

Controlled case	Requested claim	Decision	Observed evidence	Controlling reason	All triggered reasons	Representation	Export	Exact witness
unordered-association	lexical-association	ADMIT	co-occurrence	none	none	undirected-link	allowed	All gates passed
prevalence-asymmetry	asymmetric-conditional	QUALIFY	co-occurrence	prevalence-qualification	prevalence-qualification	conditional-asymmetry-glyph	allowed	Prevalence-derived orientation
unsupported-temporal-order	event-temporal-precedence	REFUSE	co-occurrence	evidence-channel-absent	evidence-channel-absent	undirected-link	blocked	Missing event-order evidence
observed-temporal-order	event-temporal-precedence	ADMIT	co-occurrence, event-order	none	none	directed-arrow	allowed	All gates passed
explicit-prerequisite	concept-prerequisite	ADMIT	co-occurrence, prerequisite-reference	none	none	directed-arrow	allowed	All gates passed
unsupported-causality	causal-influence	REFUSE	co-occurrence, mention-order, syntax	evidence-channel-absent	evidence-channel-absent	undirected-link	blocked	Missing causal-identification evidence
low-specification-persistence	meets-specification-persistence-gate	REFUSE	co-occurrence, specification-surface	persistence-gate-failed	persistence-gate-failed	no-relation	blocked	S=0.650 < gate=0.800
duplicated-evidence	statistical-stability	REFUSE	cluster-bootstrap	uncertainty-inadequate	uncertainty-inadequate, dependence-inadequate	no-relation	blocked	Uncertainty inadequate; dependence resampling absent
conflicting-annotations	event-temporal-precedence	QUALIFY	annotation-temporal-precedence	conflict-present	conflict-present	contested-relation	blocked	Opposing matched temporal annotations
missing-lineage	lexical-association	REFUSE	co-occurrence	provenance-incomplete	provenance-incomplete	no-relation	blocked	Required provenance incomplete

Table 6. Certificate-to-representation enforcement under Policy 2.7.0.

Certificate state	Decision	Controlling reason	Permitted statement	Mark	Export	Fallback	Witness	Remediation	Conforms
admit	ADMIT	none	semantic claim	directed-arrow	allowed	none	present	none	yes
prevalence-qualify	QUALIFY	prevalence-qualification	qualified statistic	conditional-asymmetry-glyph	allowed	none	present	present	yes
conflict-qualify	QUALIFY	conflict-present	contested claim	contested-relation	blocked	none	present	present	yes
refuse-with-fallback	REFUSE	evidence-channel-absent	fallback statement	undirected-link	blocked	lexical-association	present	present	yes
refuse-without-fallback	REFUSE	evidence-channel-absent	refusal explanation	no-relation	blocked	none	present	present	yes

6 Results

6.1 Policy Conformance and Representation Consequences

All ten controlled cases produced their declared decision and fallback (Table 5). Decision and fallback disagreements were zero, and every non-admitted case received remediation. The regenerated table reports observed evidence separately from the complete reason vector and controlling reason, exact witness, and remediation: present-but-inadequate evidence is no longer mislabeled as absent. These results show that Policy 2.7.0 behaves as authored, not that the policy is externally or normatively valid.

The representation-enforcement fixture instantiates five certificate states: admission, prevalence qualification, conflict qualification, refusal with fallback, and refusal without fallback (Table 6). In every state, the generated statement, semantic mark, requested-claim export result, fallback, witness, and remediation match the declared certificate consequence. In particular, conflict blocks ordinary requested-claim export despite retaining a contested statement, and refusal never emits the requested semantic arrow. This verifies executable state-to-representation coupling for the five fixtures; it does not establish that people perceive or use the marks as intended.

Table 7. Output reachability for three generated adversarial fixtures under four output-control conditions. Unauthorized means not authorized under Policy 2.7.0 for the supplied claim/evidence fixture. Each numeric entry is a count out of the three fixtures. A fallback only listed in certificate metadata is not reachable unless emitted, selectable, renderable, or exportable as an output. The ablation isolates enforcement: it does not compare human effectiveness or characterize all warning or inspection systems. Eight maintained certificate-guarded output entry points are audited separately, not as a 24-case cross-product.

Output-control condition	Statements	Marks	Exports	Fallbacks
graph-pipeline-only	3/3	3/3	3/3	0/3
warning-layer	3/3	3/3	3/3	0/3
certificate-visible-non-enforcing	3/3	3/3	3/3	0/3
themegraph-certificate-enforcement	0/3	0/3	0/3	1/3

The Output-Control Reachability Ablation applies three fixtures to four generated output-control conditions (Table 7). Each non-enforcing condition leaves three policy-relative unauthorized statements, marks, and exports reachable; visibility alone changes none. Enforcement emits none and preserves one authorized lexical fallback. Separately, all eight currently inventoried certificate-guarded output entry points pass their audit; no 3×8 cross-product is claimed. The ablation isolates enforcement, not general warning, human, safety, or noninterference effects.

The observational-equivalence test produced identical unordered signatures for worlds with opposing latent temporal directions. Both temporal claims were refused and both returned lexical association as fallback. This directly demonstrates the no-validity-laundering property: equal provenance, support, confidence, lift, and specification behavior cannot repair evidence that has discarded the distinguishing observation.

All seven executable contract-property checks passed (Figure 6). In particular, a sentence-to-sentence paraphrase annotation did not identify event-to-event temporal precedence, complete persistence and uncertainty fields did not rescue unsupported causality, refused requested claims remained non-exportable, every emitted fallback followed its declared object- and scope-compatible preference list, and forward prerequisite evidence did not identify the reversed pair. Figure 6 exposes the perturbation and failure condition for each property, stating how each implementation claim could fail rather than presenting pass labels alone. Passing these checks establishes internal conformance of the tested policy paths only.

The typed-contract necessity ablation removes or corrupts each of seven contract distinctions and exposes cross-object licensing, orientation transfer, counterevidence promotion, lineage loss, silent fallback, refused-export leakage, or promotion without adjudication (Table 8). We selected distinctions that directly control cross-construct or cross-object transfer, downgrade provenance, required adjudication, or semantic-output permission. Other serialized fields remain important for diagnosis, replay, or accountability; their exclusion from this probe does not show them unnecessary. Each selected probe is detected, establishing implementation-specific necessity rather than an exhaustive or ontologically minimal contract.

Table 7 tests why enforcement matters for generated reachability; Table 8 tests why typed enforcement matters in this implementation. Removing object, orientation/scope, polarity, projection lineage, fallback, export, or adjudication distinctions exposes different invalid outputs. This is not a superiority claim over every simpler gate.

In the trust-boundary fixture, source truth is B-before-A, while a faulty adapter supplies a schema-valid, provenance-complete A-before-B record and request. Policy 2.7.0 admits A-before-B, demonstrating conformance conditional on upstream semantic integrity; `semantic_authenticity_checked` remains false.

The version-comparison cases make contestability concrete. Reversed prerequisite evidence changes from Admit under target-only Policy 2.2.0 to Refuse under Policy 2.7.0 pair scope. Metadata-complete but unadjudicated causality

Table 8. One-at-a-time contract-field removals and corruptions with their reachable invalid behavior; these probes establish implementation necessity, not ontological minimality.

Removed distinction	Invalid behavior enabled	Joint-control consequence	Detected
governed-object type	Sentence evidence may license an incompatible event or concept claim.	Object-specific authorization collapses into channel-only admission.	yes
scope and orientation	Evidence for a->b may license b->a.	Directional authorization transfers to an unevidenced pair.	yes
evidence polarity	A negative annotation may be read as positive support or reverse truth.	Construct conflict becomes an admitted semantic relation.	yes
projection provenance	A fallback may lose lineage while remaining emit-able.	The downgraded representation is no longer auditable to its evidence.	yes
fallback projection	A refused semantic claim may silently collapse to lexical association.	Refusal no longer controls the representation reached by downgrade.	yes
export authorization	A visibly refused claim may leak into a downstream artifact.	Statement and mark governance can be bypassed through export.	yes
required adjudication	Metadata-complete causal evidence may be promoted without approval.	An authored governance gate disappears while the claim still admits.	yes

A **Adversarial contract-property matrix**

PROPERTY	ADVERSARIAL PERTURBATION	FAILURE CONDITION	CONTROL CONSEQUENCE	RESULT
construct matching	Use semantic-equivalence evidence for temporal precedence	Temporal precedence is admitted	An incompatible construct reaches a semantic mark.	PASS
no validity laundering	Set specification persistence and uncertainty adequacy without causal evidence	Causal influence is admitted or qualified	Quality fields launder an unidentified claim.	PASS
conditional support-channel monotonicity	Add irrelevant mention-order evidence to supported association	Lexical admission is withdrawn	Irrelevant evidence destabilizes lawful output.	PASS
export soundness	Evaluate every refused claim for export	Any refused requested claim is exportable	Export bypasses statement and mark refusal.	PASS
fallback soundness	Remove evidence required by each preferred fallback	An unidentified fallback is emitted	Downgrade emits a claim without independent support.	PASS
fallback preference conformance	Provide multiple declared fallback candidates	The first supported preference is not selected	Rendered downgrade diverges from authored policy.	PASS
pair scope nontransfer	Reverse the requested entity pair without reversing the evidence record	Forward directional evidence licenses the reversed claim	Evidence authorizes the wrong semantic orientation.	PASS

Fig. 6. Adversarial contract-property matrix under Policy 2.7.0. Each row states a perturbation, the implementation failure it could expose, its consequence for joint output control, and the observed conformance result; this is invariant testing, not epistemological falsification of the policy.

changes from Admit under Policy 2.5.0 to Refuse with `adjudication-required` under Policy 2.7.0. Serialized certificates preserve version, governed object, complete and controlling reasons, witness, projection provenance, and remediation. All 21 active-policy lint checks pass, and all 21 targeted invalid policies trigger their intended checks. The supplementary mutation artifact reports all six families and retains every row, intended check, observed trigger vector, and co-trigger. This assurance is not independent policy validation.

The evidence-transition fixture refused all four prerequisite requests under co-occurrence alone. After adding the four exactly matched prerequisite-bearing reference records, all four followed the declared admission path. The permitted representation consequently changed from an undirected fallback to a directed prerequisite relation. The supplementary figure preserves the full transition. Because the references are synthetic and perfectly parsed, this result tests policy transition and representation coupling only; it does not establish performance on real references.

6.2 External Construct-Boundary Stress Tests

Five datasets exercise paraphrase, entailment, prerequisite, and temporal routes (Table 9). Results are organized by failure mode; observed agreement is policy conformance, not predictive performance or independent validation.

Lexical evidence is not semantic evidence. MRPC and PAWS lexical-only routes refused paraphrase equivalence, whereas positive construct-matched annotation admitted it and negative annotation refused it; separately requested non-paraphrase claims admitted under their own matched scope. Yet 558 of 1,901 MRPC non-paraphrases (29.4%) and 36,492 of 36,497 PAWS non-paraphrases (99.99%) exceed Jaccard 0.5. The five PAWS exceptions prevent a universal claim, while the observed high-overlap negatives provide empirical counterexamples to lexical overlap as generic paraphrase evidence. SNLI likewise contains 15,415 neutral and 9,542 contradictory pairs with Jaccard at least 0.5.

Directional evidence does not transfer by reversal. SNLI premise-to-hypothesis entailment admitted only in its annotated orientation; neutral pairs lacked support, contradictions supplied counterevidence, and reversal refused. AL-CPL admitted matched prerequisite orientation but refused mention order, counterevidence, and reversal. Its processed labels contain no reflexive positive or positive reverse; every positive has a dataset-provided negative, and positives close 1,356 observed two-edge compositions. Without row-level origin flags, these are structural properties, not reconstruction of preprocessing. TORQUE's 1,928 usable adjudicated-dev relations admitted under pair-matched temporal annotation, while mention order and reversal refused; withheld test answers were not evaluated.

Construct-matched evidence does not transfer across constructs. Cross-construct admission was zero in all five datasets: SNLI entailment did not authorize prerequisite or temporal claims, AL-CPL prerequisites did not authorize temporal claims, and TORQUE event order did not authorize prerequisites. Compact table rows aggregate concrete typed requests rather than inventing pseudo-claims. Artifact JSON retains every requested claim, deterministic request count, expected and observed consequence, policy version, and stable route ID. These diverse routes stress the authored boundaries; they do not establish policy validity, universal relation truth, or excluded constructs.

Figure 7 derives a dataset-by-route-family coverage matrix from the authoritative route records and preserves seventeen representative policy paths. Table 9 additionally reports separately requested non-paraphrase admission and the remaining cross-construct controls.

6.3 Specification Persistence

Across 24 configurations, the ACM-text union contains 9,118 edges (Table 10; Figure 8). Default-edge mean persistence is 0.798; the intersection has 15 edges; and mean one-to-one component Jaccard is 0.756. At the authored 0.80 persistence gate, 289 union edges meet the gate and 8,829 fall below it. The union denominator exposes selection hidden by default-only persistence.

O*NET has no edge in the 24-way intersection and 9 of 3,520 union edges meet the 0.80 persistence gate; Python has 135 of 1,063. All 27 default synthetic edges persist throughout, but 120 alternatives emerge below the gate. This reflects the planted core, not general robustness. Analytic choices alter both retention and the candidate universe.

These consequences remain subordinate to construct evidence and policy admissibility. A persistent lexical association cannot be upgraded to temporal, prerequisite, or causal direction without the corresponding evidence and policy requirements. Conversely, a low-persistence but explicitly referenced prerequisite may be qualified for sensitivity rather than refused for missing semantic evidence. The readable top-level QUALIFY is crossed with typed reasons: $S = .042$ is

Table 9. Deterministic construct-boundary Policy 2.7.0 transition map. Rows show evidence condition, requested claim, expected and observed policy consequences, and the exercised failure or authorization path; they are conformance routes, not predictive accuracy estimates. Cross-construct rows compact exact typed requests retained with counts and route IDs in the artifact manifest.

Dataset	Evidence condition	Requested claim	Expected	Observed	Failure / authorization path
MRPC	matched positive annotation	sentential-paraphrase-equivalence	ADMIT	ADMIT	authorized
MRPC	lexical evidence only	sentential-paraphrase-equivalence	REFUSE	REFUSE	missing construct-matched evidence
MRPC	negative annotation	sentential-paraphrase-equivalence	REFUSE	REFUSE	construct-matched counterevidence
MRPC	matched non-paraphrase annotation	sentential-non-paraphrase	ADMIT	ADMIT	authorized
MRPC	cross-construct request	multiple excluded typed claims; see artifact manifest	REFUSE	REFUSE	construct mismatch
PAWS	matched positive annotation	sentential-paraphrase-equivalence	ADMIT	ADMIT	authorized
PAWS	lexical evidence only	sentential-paraphrase-equivalence	REFUSE	REFUSE	missing construct-matched evidence
PAWS	negative annotation	sentential-paraphrase-equivalence	REFUSE	REFUSE	construct-matched counterevidence
PAWS	matched non-paraphrase annotation	sentential-non-paraphrase	ADMIT	ADMIT	authorized
PAWS	cross-construct request	multiple excluded typed claims; see artifact manifest	REFUSE	REFUSE	construct mismatch
SNLI	matched directional annotation	textual-entailment	ADMIT	ADMIT	authorized
SNLI	neutral annotation	textual-entailment	REFUSE	REFUSE	insufficient support
SNLI	contradiction annotation	textual-entailment	REFUSE	REFUSE	construct-matched counterevidence
SNLI	reversed relation request	textual-entailment	REFUSE	REFUSE	scope mismatch
SNLI	cross-construct request	multiple excluded typed claims; see artifact manifest	REFUSE	REFUSE	construct mismatch
AL-CPL	matched prerequisite annotation	concept-prerequisite	ADMIT	ADMIT	authorized
AL-CPL	lexical evidence only	concept-prerequisite	REFUSE	REFUSE	missing construct-matched evidence
AL-CPL	mention order only	concept-prerequisite	REFUSE	REFUSE	evidence-channel-absent
AL-CPL	negative annotation	concept-prerequisite	REFUSE	REFUSE	construct-matched counterevidence
AL-CPL	reversed relation request	concept-prerequisite	REFUSE	REFUSE	scope mismatch
AL-CPL	cross-construct request	multiple excluded typed claims; see artifact manifest	REFUSE	REFUSE	construct mismatch
TORQUE	matched event-order annotation	event-temporal-precedence	ADMIT	ADMIT	authorized
TORQUE	mention order only	event-temporal-precedence	REFUSE	REFUSE	mention-order-insufficient
TORQUE	reversed relation request	event-temporal-precedence	REFUSE	REFUSE	scope mismatch
TORQUE	cross-construct request	multiple excluded typed claims; see artifact manifest	REFUSE	REFUSE	construct mismatch

Table 10. Union-edge persistence, set geometry, and one-to-one component overlap over an unweighted 24-configuration surface including six bounded interactions; the final columns report outcomes relative to the prespecified 0.80 persistence gate.

Corpus	Cfg.	2-factor cfgs.	Default	Union	Min.	Mean	Default mean	1:1 comp. J	Meets pers. gate	Below pers. gate
ACM text	24	6	740	9118	0.042	0.115	0.798	0.756	289	8829
O*NET	24	6	213	3520	0.042	0.088	0.711	0.663	9	3511
Python stdlib	24	6	233	1063	0.042	0.226	0.814	0.776	135	928
Synthetic	24	6	27	147	0.042	0.248	1.000	1.000	27	120

highly specification-sensitive, $S = .792$ is near threshold, and construct conflict receives a different mark and export consequence. The gates answer different questions and are intentionally lexicographic.




Fig. 7. External construct-boundary Policy 2.7.0 routing map. Left: categorical source-derived coverage of matched support, counterevidence, reversal, mention-only, and cross-construct route families; checks carry route counts, N/A marks inapplicable families, and counts are not independent observations. Right: seventeen deterministic policy paths. Neither panel reports predictive accuracy.

6.4 Supporting Correctness and Dependence Checks

The SCC implementation exactly matched NetworkX across canonical and seeded fixtures, including isolate, destination-only, acyclicity, reversal, and symmetrization invariants. On the easy planted core, SCC and all three clustering baselines obtained ARI and pairwise F1 of 1.0, precluding an SCC-superiority claim. Complete supporting results remain in the artifact package.

The controlled dependence sanity check uses no third-party text. Repeating 12 generated source records four times produces 48 rows, 36 duplicates beyond first occurrence, and the predetermined mechanical consequence that row-level support is four times source-level support. This is a controlled counterexample to equating rows with independent evidence; it is not a substantive empirical finding or a general estimate of dependence in text corpora. Full fixture values remain in the supplementary artifact package.




Fig. 8. Union-edge persistence and persistence-gate frontiers across the unweighted 24-configuration surface. Markers are evaluated gates; connecting steps do not imply interpolated measurements. The dashed 0.80 line is an author-specified heuristic, not a truth threshold.

7 Discussion

7.1 The Arrow Is a Claim, Not a Decoration

The central implication is representational. A pipeline can pass unit tests, preserve provenance, produce stable identifiers, and render mechanically valid graphics while still using an arrow that exceeds its observations. Conventional software validation asks whether the implementation matches the specification. Claim admissibility asks whether the specification licenses the statement a person is invited to infer. For interactive systems, enforcing that decision at the visible-and-exportable boundary is an HCI capability: it changes which semantic objects the interface can present and propagate, not merely which caveat a backend records.

This distinction changes interface design. A legend that says "confidence" is insufficient because readers may reasonably interpret direction semantically. A tooltip with a source sentence is insufficient because the sentence establishes co-occurrence, not direction. A high lift value is insufficient because lift is symmetric. A cycle is insufficient because SCCs are invariant under global reversal. Refusal must therefore govern the representation, not merely annotate it: a refused arrow becomes an undirected fallback or no relation, the requested semantic statement is not exportable, and the interface states what evidence could change the decision.

Claim-admissibility contracts provide such an account without another scalar trust score. A certificate separates observational identifiability, policy admissibility, typed reason, refusal class, representation authorization, and export authorization. Conflict receives a contested mark and blocked ordinary export, not an admitted arrow. Versioning makes requirements inspectable and replayable without changing earlier certificates.

Refusal is actionable only when its cause is preserved: epistemic refusal calls for construct-matched evidence, policy refusal for satisfying or contesting an authored gate, and operational refusal for repairing lineage or output prerequisites. Reason-specific qualification distinguishes prevalence, sensitivity, and conflict. Refusal does not authorize downgrade; fallback must independently earn its representation, otherwise the system emits no relation. These are mechanism principles, not additional contributions.

7.2 What the Current Evidence Establishes

The four present stages establish bounded mechanism claims. Stage 1 establishes computational correctness and conformance to author-specified Policy 2.7.0 examples, properties, replay boundaries, and targeted lint mutations. Stage 2 establishes that the tested certificate fields control the implemented statement, mark, fallback, and export. Stage 3 establishes declared routes for construct-, object-, pair-, and direction-matched external annotations and counterexamples. Stage 4 establishes descriptive sensitivity over the declared specification surface. Observational equivalence adds a logical result: the tested unordered signature cannot distinguish opposing temporal worlds.

Evidence beyond authored case agreement carries the main discriminating weight: observational equivalence establishes a non-identification result; typed-field removals expose distinct invalid outputs; the faulty-adapter fixture separates policy conformance from source truth; external high-overlap negatives challenge lexical evidence transfer; the specification surface exposes analytic-choice sensitivity; and mutation plus entry-point audits test the maintained output boundary.

These results do not establish predictive accuracy, independent sampling, universal relation truth, normative policy validity, causal truth, theme validity, perceptual effectiveness, usability, trust, calibration, reduced unsupported inference, improved analytic judgment, or analyst benefit. MRPC, PAWS, SNLI, AL-CPL, and TORQUE exercise only their released constructs and processed labels. The specification surface establishes neither bootstrap persistence nor dependence-aware statistical stability and does not calibrate truth. This boundary is substantive: the present contribution is an executable control capability and a prerequisite for evaluating human consequences, not evidence that those consequences occur.

Supporting negative results constrain interpretation. Perfect synthetic recovery did not distinguish SCC from clustering baselines, and default structure varies across choices and duplicate handling. Temporal, prerequisite, and causal direction remain unidentified in unordered graph corpora; AL-CPL and TORQUE are separate policy probes, not evidence that co-occurrence acquired those semantics. ThemeGraph withholds each relation unless its requirements are met.

These findings also refine what “dataset-independent” means. The architecture accepts heterogeneous corpora without core-code changes, which is useful research-software evidence. The outputs remain dataset-dependent, as they should. Cross-domain execution is not transportability of meaning. A contract makes this distinction concrete by separating an engineering check from a construct claim.

7.3 Implications for CHI Constituencies

The mechanism evaluation supports three bounded design propositions. First, Tables 6 and 8, together with the entry-point audit, motivate treating a semantic mark as a consequence-bearing claim surface whose statement, encoding, and export share authorization. Second, Table 6, Equation 8, and the refusal/fallback fixtures motivate reason-specific, repair-oriented refusal that identifies what failed, what representation remains admissible, and what evidence could change the outcome without silently promoting a fallback. Third, policy replay and mutation tests motivate treating executable policy as an inspectable and contestable interaction object whose version, requirements, and representational consequences can be compared. These propositions connect visualization, human-AI interaction, qualitative analysis, and research-software governance without claiming measured human benefit.

7.4 Reusable Implementation Principles

Five design principles derived from ThemeGraph's mechanism evaluation may transfer beyond this prototype while remaining testable at the mechanism level:

(1) **Guard semantic claim surfaces.** Jointly authorize statements, marks, and requested-claim exports; each inventoried semantic entry point consumes a valid certificate, and a computed edge cannot directly select a semantic arrow.
(2) **Separate identification from policy.** Record what observations can distinguish, what an authored policy permits, every triggered reason, and the controlling consequence as distinct fields.
(3) **Type the full contract.** Match construct, governed-object signature, direction or symmetry, relation scope, polarity, counterevidence, adjudication, adequacy, and provenance before authorization.
(4) **Project fallback explicitly.** Require a declared claim-and-object projection, independently sufficient target evidence, and preserved projection provenance; otherwise emit no relation.
(5) **Make enforcement contestable.** Version and replay policy, mutation-test its invariants, and derive interface, export, tables, figures, and manuscript statistics from the same certificates.

These are implementation principles, not evidence that a particular ontology, visual grammar, or institutional policy is normatively correct. The architectural proposition may transfer when a system turns machine-derived structure into human-interpretable semantic artifacts; empirical generalization beyond the evaluated directed text-analytic graphs remains withheld.

This first principle adapts complete mediation without extending a security claim. The certificate-guarded output-entry-point audit makes the current boundary testable, but remains weaker than formal reference-monitor verification.

7.5 Policy as a Contestable Design Object

Executable governance introduces its own authority. Policy authors choose the claim ontology, object signatures, evidence predicates, adjudication roles, gates, and fallbacks; implementers turn those choices into visible and exportable constraints. Established procedural contestability asks how affected people obtain information, challenge decisions, act collectively, and locate responsibility [57]. ThemeGraph instantiates only a narrower policy-artifact condition: executable epistemic policy should remain inspectable, version-identifiable, replayable, and behaviorally comparable across revisions. Replay from pair-scope Policy 2.2.0 and causal-adjudication Policy 2.5.0 to active Policy 2.7.0 exposes representational consequences of revision. It does not supply legitimate institutional authority or affected-person procedures. Governance must still name who may author, approve, appeal, and retire rules; lexicographic ordering and the 0.80 gate remain provisional choices requiring domain review.

7.6 A Research Agenda for Refusible Analysis

Refusal is often treated as a model behavior for low confidence. Here, one refusal basis can occur earlier: observational non-identification. Even infinite unordered co-occurrence data cannot distinguish opposing temporal worlds without assumptions or additional observations. Other refusals are policy-relative, such as missing adjudication or provenance. This distinction suggests a broader design agenda: declare claim types and evidence policies, preserve lineage, expose specification surfaces, and govern what representations can express and export.

The next mechanism-validation step is not simply a larger unlabeled corpus. Relation-specific work should use independently sampled domains, unprocessed judgments, expert disagreement distributions, and source-cluster bootstrap procedures that repeat vocabulary selection and extraction. Additional constructs should be introduced only with object-matched evidence and an explicit policy. Causal, discourse, interpretive-theme, clinical, analyst-benefit, and universal relation-validity claims remain withheld.

7.7 From Mechanism Validation to Human Consequence Evaluation

Stages 1 to 4 bound the mechanism-level evidence claimed here; they do not answer the distinct claim class represented by Figure 3's interpretive-validity and human-benefit gates. Stages 5 and 6 define that subsequent participant-based research program. Stage 5 should test interpretive validity: **RQ-H1**, whether representation authorization changes unsupported semantic inference; **RQ-H2**, whether people distinguish Admit, reason-specific Qualify, and Refuse; and **RQ-H3**, how exact witness, fallback, and remediation affect evidence inspection and revision. Stage 6 should test governance and benefit: **RQ-H4**, how analysts and domain experts contest, revise, and apply policy rules, followed by task-specific tests of judgment quality rather than assumed benefit.

A candidate experiment would compare conventional directed graphs, warning-only graphs, certificate-visible graphs, and certificate-enforced marks and exports. Measures should include relation-interpretation choices, reason and fallback comprehension, evidence-opening behavior, remediation uptake, decision accuracy against independently adjudicated tasks, confidence calibration, completion time, policy appeals and revisions, and qualitative rationales. Domain experts and affected analysts should participate in policy-authoring and appeal conditions, not merely evaluate a fixed author policy. Until those studies are conducted, ThemeGraph makes no human-effect claim.

8 Ethics, Limitations, and Scope

No participants were recruited, and no interaction logs or personal profiles were collected. The main evidentiary package uses generated fixtures, licensed mechanics corpora, and aggregate-only external construct-boundary outputs; it does not redistribute raw MRPC, PAWS, SNLI, AL-CPL, or TORQUE text or relation records. An optional local workbook audit is outside the paper's claims and is not required to reproduce them. This removes unresolved third-party job-text rights from the main scientific argument rather than treating aggregate reporting as permission.

O*NET 30.3 is developed by the U.S. Department of Labor, Employment and Training Administration and licensed under CC BY 4.0 [52]. Our analysis joins occupation descriptions and task statements; USDOL/ETA has not endorsed this modification. The PAWS repository license permits use for any purpose, requests acknowledgement of Google as the source, and provides the data as-is without warranty; only PAWS-Wiki labeled-final aggregates are used here, not PAWS-QQP. ACM templates and Python files are mechanics corpora and are not interpreted as populations. All corpora are English-heavy, token normalization is lexical, and sentence segmentation errors can alter support.

The evaluation is participant-free. Mechanical browser checks establish that controls operate, evidence loads, and layouts do not overflow tested viewports. They do not establish accessibility conformance, usability, trust, learning, or improved sensemaking. Local requirements for ethics or non-human-subject determination vary and must be confirmed by the authors before submission.

Statistically, the graph evaluation is descriptive. Units are nested within documents, vocabulary is selected, many pairs are examined, and edges are dependent. We do not use inferential language or apply false-discovery procedures such as Benjamini-Hochberg [5]. No cluster-bootstrap intervals or perturbation distributions are reported. Specification persistence is not a probability of truth; the surface includes six bounded interactions but not exhaustive interactions,

and its configurations are equally weighted. The selected corpus families test software portability but cannot support claims about all text domains.

The ten-case benchmark can detect implementation-policy disagreement, not normative defects. Detecting 21 targeted mutations establishes declared fault sensitivity, not completeness or independent adjudication. The certificate-guarded audit covers eight currently inventoried output entry points through source guards, candidate-emitter discovery, and focused behavior tests; arbitrary future code may introduce a bypass. The prerequisite transition uses synthetic edges and perfect channel provision, so AL-CPL is the separate annotated stress test. AL-CPL lacks row-level derivation provenance; reverse-corresponding negatives and composition closures do not reconstruct preprocessing. TORQUE uses public adjudicated-dev before/after answers; 184 questions without answer indices and withheld test labels are excluded. Shared questions/passages are not independent samples. Neither dataset establishes universal relation truth, causality, or transportability. No domain-expert policy adjudication, participant evaluation, perceptual validation of Figure 4, or representation-family generalization has been performed. Only aggregates are redistributed: MRPC's maintained GLUE mirror states no license; PAWS-Wiki follows its terms; SNLI is CC BY-SA 4.0; AL-CPL is CC BY-NC-SA 4.0; and TORQUE is Apache 2.0.

Finally, SCCs, association rules, provenance, acceptability, abstention, documentation, specification/stability analysis, and uncertainty visualization are established. The contribution is their typed alignment at the representation boundary. Authorization remains conditional on upstream integrity: schema validity and provenance cannot detect a false label, source corruption, or faulty adapter. We claim no legal novelty, patentability, or freedom to operate.

9 Conclusion

ThemeGraph contributes policy-declared construct-, object-, and scope-matched claim-time authorization in which one certificate governs a representation's statement, mark, export, independently supported fallback, witness, and remediation. It separates observational identifiability from policy admissibility and executes complete and controlling reasons. Policy 2.7.0 conforms to tested cases and field-removal probes; enforcement changes reachability; all eight currently inventoried certificate-guarded output entry points pass their audit; replay exposes policy changes; external annotations exercise construct/scope boundaries; and specification analysis exposes sensitivity without converting persistence into truth.

The contribution is not a new graph algorithm, proof of policy validity, or evidence of human benefit. Within the maintained inventory, a versioned certificate governs which statements, marks, and requested-claim exports the interface may emit, including contested and refused states; this does not prove arbitrary future code non-bypassable. Human-consequence evaluation addresses a distinct claim class outside the present mechanism-level scope.

9.1 Use of AI Tools

Generative artificial intelligence tools were used to support codebase review, language editing, structural review, consistency checking, and reproducibility documentation. The authors independently verified the mathematical arguments, numerical results, references, code, and final wording, and take full responsibility for the content of the manuscript.

References

[1] Rakesh Agrawal, Tomasz Imielinski, and Arun Swami. 1993. Mining Association Rules between Sets of Items in Large Databases. In *Proceedings of the 1993 ACM SIGMOD International Conference on Management of Data*. Association for Computing Machinery, New York, NY, USA, 207-216. doi:10.1145/170035.170072

[2] James P. Anderson. 1972. *Computer Security Technology Planning Study.* Technical Report ESD-TR-73-51. Electronic Systems Division, Air Force Systems Command, Hanscom Air Force Base, MA, USA.

[3] M. Arnold, R. K. E. Bellamy, M. Hind, S. Houde, S. Mehta, A. Mojsilovic, R. Nair, K. Natesan Ramamurthy, A. Olteanu, D. Piorkowski, D. Reimer, J. Richards, J. Tsay, and K. R. Varshney. 2019. FactSheets: Increasing Trust in AI Services through Supplier's Declarations of Conformity. *IBM Journal of Research and Development* 63, 4/5 (2019), 6:1-6:13. doi:10.1147/JRD.2019.2942288

[4] Alejandro Benito-Santos, Florian Windhager, Aida Horani, Rabea Kleymann, Alfie Abdul-Rahman, and Eva Mayr. 2026. Chasing Meaning and/or Insight? A Survey on Evaluation Practices at the Intersection of Visualization and the Humanities. In *Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 1-23. doi:10.1145/3772318.3793150

[5] Yoav Benjamini and Yosef Hochberg. 1995. Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series B* 57, 1 (1995), 289-300. doi:10.1111/j.2517-6161.1995.tb02031.x

[6] David M. Blei, Andrew Y. Ng, and Michael I. Jordan. 2003. Latent Dirichlet Allocation. *Journal of Machine Learning Research* 3 (2003), 993-1022.

[7] Agnes Bolinska. 2016. Successful Visual Epistemic Representation. *Studies in History and Philosophy of Science Part A* 56 (2016), 153-160. doi:10.1016/j.shpsa.2015.09.005

[8] Elizabeth Bondi, Raphael Koster, Hannah Sheahan, Martin Chadwick, Yoram Bachrach, Taylan Cemgil, Ulrich Paquet, and Krishnamurthy Dvijotham. 2022. Role of Human-AI Interaction in Selective Prediction. *Proceedings of the AAAI Conference on Artificial Intelligence* 36, 5 (2022), 5286-5294. doi:10.1609/aaai.v36i5.20465

[9] Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. A Large Annotated Corpus for Learning Natural Language Inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, Lisbon, Portugal, 632-642. doi:10.18653/v1/D15-1075

[10] Virginia Braun and Victoria Clarke. 2006. Using Thematic Analysis in Psychology. *Qualitative Research in Psychology* 3, 2 (2006), 77-101. doi:10.1191/1478088706qp063oa

[11] Virginia Braun and Victoria Clarke. 2021. One Size Fits All? What Counts as Quality Practice in (Reflexive) Thematic Analysis? *Qualitative Research in Psychology* 18, 3 (2021), 328-352. doi:10.1080/14780887.2020.1769238

[12] CAPAS Project. 2026. CAPAS Claim Gate. Python package, version 0.3.0. Public research software released June 23, 2026; accessed September 11, 2026. https://pypi.org/project/capas-claim-gate/

[13] Jonathan Chang, Jordan Boyd-Graber, Sean Gerrish, Chong Wang, and David M. Blei. 2009. Reading Tea Leaves: How Humans Interpret Topic Models. In *Advances in Neural Information Processing Systems 22*. Curran Associates, Inc., Red Hook, NY, USA, 288-296. https://proceedings.neurips.cc/paper/2009/hash/f92586a25bb3145facd64ab20fd554ff-Abstract.html

[14] Qing Chen, Fuling Sun, Xinyue Xu, Zui Chen, Jiazhe Wang, and Nan Cao. 2022. VizLinter: A Linter and Fixer Framework for Data Visualization. *IEEE Transactions on Visualization and Computer Graphics* 28, 1 (2022), 206-216. doi:10.1109/TVCG.2021.3114804

[15] L. Christino, S. Rezaeipour, E. Milios, and F. Paulovich. 2026. A Theoretical Approach for Structuring and Analysing Knowledge Provenance for Visual Analytics. Computer Graphics Forum, article e70493. doi:10.1111/cgf.70493

[16] Jason Chuang, Daniel Ramage, Christopher Manning, and Jeffrey Heer. 2012. Interpretation and Trust: Designing Model-Driven Visualizations for Text Analysis. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 443-452. doi:10.1145/2207676.2207738

[17] William B. Dolan and Chris Brockett. 2005. Automatically Constructing a Corpus of Sentential Paraphrases. In *Proceedings of the Third International Workshop on Paraphrasing*. Asian Federation of Natural Language Processing, Jeju Island, Korea, 9-16. https://aclanthology.org/I05-5002/

[18] Phan Minh Dung. 1995. On the Acceptability of Arguments and Its Fundamental Role in Nonmonotonic Reasoning, Logic Programming and N-Person Games. *Artificial Intelligence* 77, 2 (1995), 321-357. doi:10.1016/0004-3702(94)00041-X

[19] Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daume III, and Kate Crawford. 2021. Datasheets for Datasets. *Commun. ACM* 64, 12 (2021), 86-92. doi:10.1145/3458723

[20] Todd J. Green, Grigoris Karvounarakis, and Val Tannen. 2007. Provenance Semirings. In *Proceedings of the Twenty-Sixth ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems*. Association for Computing Machinery, New York, NY, USA, 31-40. doi:10.1145/1265530.1265535

[21] Fengchen Gu, Xiaotian Ren, Zhengyong Jiang, Zhilu Zhang, Ángel F. García-Fernández, Angelos Stefanidis, Mian Zhou, Huakang Li, and Jionglong Su. 2026. EvidenceLens: A Claim-Evidence Matrix for Auditing Financial Question Answering. Accepted short paper, IEEE VIS 2026; preprint available. arXiv:2606.23724 [cs.IR] doi:10.48550/arXiv.2606.23724

[22] Danny Holten and Jarke J. van Wijk. 2009. A User Study on Visualizing Directed Edges in Graphs. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 2299-2308. doi:10.1145/1518701.1519054

[23] Eric Horvitz. 1999. Principles of Mixed-Initiative User Interfaces. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 159-166. doi:10.1145/302979.303030

[24] Jek Huang, Jeffery Hsia, Jiayi Sun, Freddie Shi, Wei Huang, and Ian H. White. 2026. Proof-or-Stop: Don't Trust the Agent, Trust the Evidence: Loop Engineering for Verifiable Evidence-Gated Lifecycle Control. Preprint, version 1, submitted July 16, 2026. arXiv:2607.14890 [cs.AI] doi:10.48550/arXiv.2607.14890

[25] Jessica Hullman, Xiaoli Qiao, Michael Correll, Alex Kale, and Matthew Kay. 2019. In Pursuit of Error: A Survey of Uncertainty Visualization Evaluation. *IEEE Transactions on Visualization and Computer Graphics* 25, 1 (2019), 903-913. doi:10.1109/TVCG.2018.2864889

[26] Edwin Hutchins. 1995. *Cognition in the Wild.* MIT Press, Cambridge, MA, USA.

[27] Abigail Z. Jacobs and Hanna Wallach. 2021. Measurement and Fairness. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*. Association for Computing Machinery, New York, NY, USA, 375-385. doi:10.1145/3442188.3445901

[28] Chen Liang, Jianbo Ye, Shuting Wang, Bart Pursel, and C. Lee Giles. 2018. Investigating Active Learning for Concept Prerequisite Learning. *Proceedings of the AAAI Conference on Artificial Intelligence* 32, 1 (2018), 7913-7919. doi:10.1609/aaai.v32i1.11396

[29] Che Lin, Jia-Yi Lin, and Yao-San Lin. 2026. Evidence-Graded Decision Authorization for Safe Clinical AI: A Constrained Reasoning Framework. medRxiv preprint. Version 1, posted May 22, 2026. doi:10.64898/2026.05.19.26353565

[30] Jock D. Mackinlay. 1986. Automating the Design of Graphical Presentations of Relational Information. *ACM Transactions on Graphics* 5, 2 (1986), 110-141. doi:10.1145/22949.22950

[31] Anna Martin-Boyle, Cara Leckey, Martha Brown, and Harmanpreet Kaur. 2026. PaperTrail: A Claim-Evidence Interface for Grounding Provenance in LLM-based Scholarly Q&A. In *Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 1-25. doi:10.1145/3772318.3791101

[32] Nicolai Meinshausen and Peter Buehlmann. 2010. Stability Selection. *Journal of the Royal Statistical Society: Series B* 72, 4 (2010), 417-473. doi:10.1111/j.1467-9868.2010.00740.x

[33] Margaret Mitchell, Simone Wu, Andrew Zaldivar, Parker Barnes, Lucy Vasserman, Ben Hutchinson, Elena Spitzer, Inioluwa Deborah Raji, and Timnit Gebru. 2019. Model Cards for Model Reporting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*. Association for Computing Machinery, New York, NY, USA, 220-229. doi:10.1145/3287560.3287596

[34] Stefano Monti, Pablo Tamayo, Jill Mesirov, and Todd Golub. 2003. Consensus Clustering: A Resampling-Based Method for Class Discovery and Visualization of Gene Expression Microarray Data. *Machine Learning* 52 (2003), 91-118. doi:10.1023/A:1023949509487

[35] Dominik Moritz, Chenglong Wang, Greg L. Nelson, Halden Lin, Adam M. Smith, Bill Howe, and Jeffrey Heer. 2019. Formalizing Visualization Design Knowledge as Constraints: Actionable and Extensible Models in Draco. *IEEE Transactions on Visualization and Computer Graphics* 25, 1 (2019), 438-448. doi:10.1109/TVCG.2018.2865240

[36] Laura K. Nelson. 2020. Computational Grounded Theory: A Methodological Framework. *Sociological Methods and Research* 49, 1 (2020), 3-42. doi:10.1177/0049124117729703

[37] M. E. J. Newman and M. Girvan. 2004. Finding and Evaluating Community Structure in Networks. *Physical Review E* 69 (2004), 026113. doi:10.1103/PhysRevE.69.026113

[38] Qiang Ning, Hao Wu, Rujun Han, Nanyun Peng, Matt Gardner, and Dan Roth. 2020. TORQUE: A Reading Comprehension Dataset of Temporal Ordering Questions. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, Online, 1158-1172. doi:10.18653/v1/2020.emnlp-main.88

[39] L. R. M. Pinto and C. T. S. Dias. 2026. Claim-Specific Admissibility of PCA Biplot Interpretations: Target Alignment, Spectral Identifiability, and Projection Adequacy. arXiv:2607.16469 [stat.ME] doi:10.48550/arXiv.2607.16469

[40] Peter Pirolli and Stuart Card. 1999. Information Foraging. *Psychological Review* 106, 4 (1999), 643-675. doi:10.1037/0033-295X.106.4.643

[41] Jingxi Qiu, Zeyu Han, and Cheng Huang. 2026. SURE-RAG: Sufficiency and Uncertainty-Aware Evidence Verification for Selective Retrieval-Augmented Generation. arXiv:2605.03534 [cs.CL] doi:10.48550/arXiv.2605.03534

[42] Md Main Uddin Rony, Enamul Hoque, and Naeemul Hassan. 2020. ClaimViz: Visual Analytics for Identifying and Verifying Factual Claims. In *2020 IEEE Visualization Conference (VIS)*. IEEE, Salt Lake City, UT, USA, 246-250. doi:10.1109/VIS47514.2020.00056

[43] Daniel M. Russell, Mark J. Stefik, Peter Pirolli, and Stuart K. Card. 1993. The Cost Structure of Sensemaking. In *Proceedings of the INTERCHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, New York, NY, USA, 269-276. doi:10.1145/169059.169209

[44] Jerome H. Saltzer and Michael D. Schroeder. 1975. The Protection of Information in Computer Systems. *Proc. IEEE* 63, 9 (1975), 1278-1308. doi:10.1109/PROC.1975.9939

[45] Igor Santos-Grueiro. 2026. When Binaries Talk Back: Representation-Confusion Attacks on LLM-Assisted Reverse Engineering. arXiv:2607.12507 [cs.CR] doi:10.48550/arXiv.2607.12507

[46] Ben Shneiderman. 1996. The Eyes Have It: A Task by Data Type Taxonomy for Information Visualizations. In *Proceedings of the 1996 IEEE Symposium on Visual Languages*. IEEE Computer Society, Los Alamitos, CA, USA, 336-343. doi:10.1109/VL.1996.545307

[47] Uri Simonsohn, Joseph P. Simmons, and Leif D. Nelson. 2020. Specification Curve Analysis. *Nature Human Behaviour* 4, 11 (2020), 1208-1214. doi:10.1038/s41562-020-0912-z

[48] Susan Leigh Star and James R. Griesemer. 1989. Institutional Ecology, Translations and Boundary Objects: Amateurs and Professionals in Berkeley's Museum of Vertebrate Zoology, 1907-39. *Social Studies of Science* 19, 3 (1989), 387-420. doi:10.1177/030631289019003001

[49] Robert Tarjan. 1972. Depth-First Search and Linear Graph Algorithms. *SIAM J. Comput.* 1, 2 (1972), 146-160. doi:10.1137/0201010

[50] Michael Theologitis, Preetam Prabhu Srikar Dammu, Chirag Shah, and Dan Suciu. 2026. ClaimDB: A Fact Verification Benchmark over Large Structured Data. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, San Diego, California, United States, 34428-34451. doi:10.18653/v1/2026.acl-long.1589

[51] V. A. Traag, L. Waltman, and N. J. van Eck. 2019. From Louvain to Leiden: Guaranteeing Well-Connected Communities. *Scientific Reports* 9 (2019), 5233. doi:10.1038/s41598-019-41695-z

[52] U.S. Department of Labor, Employment and Training Administration. 2026. O*NET 30.3 Database. Licensed under CC BY 4.0; accessed August 24, 2026. https://www.onetcenter.org/database.html

[53] Sahaj Vaidya and Aritra Dasgupta. 2020. Knowing What to Look For: A Fact-Evidence Reasoning Framework for Decoding Communicative Visualization. In *2020 IEEE Visualization Conference (VIS)*. IEEE, Salt Lake City, UT, USA, 231-235. doi:10.1109/VIS47514.2020.00053

[54] Shuting Wang, Alexander Ororbia, Zhaohui Wu, Kyle Williams, Chen Liang, Bart Pursel, and C. Lee Giles. 2016. Using Prerequisites to Extract Concept Maps from Textbooks. In *Proceedings of the 25th ACM International on Conference on Information and Knowledge Management*. Association for Computing Machinery, New York, NY, USA, 317-326. doi:10.1145/2983323.2983725

[55] Yihan Xia and Taotao Wang. 2026. ResearchLoop: An Evidence-Gated Control Plane for AI-Assisted Research. arXiv:2605.28282 [cs.AI] doi:10.48550/arXiv.2605.28282

[56] Caijun Yan, Yang Zhou, Meixing Shi, Haoran Sun, Yichen Li, Yuxiang Cai, and Yankai Jiang. 2026. REVEAL: A Rubric-Guided Agent for Explicit Evidence Sufficiency Verification in Long-Video Question Answering. arXiv:2608.08612 [cs.CV] doi:10.48550/arXiv.2608.08612

[57] Mireia Yurrita, Himanshu Verma, Agathe Balayn, Kars Alfrink, Ujwal Gadiraju, and Alessandro Bozzon. 2025. Identifying Algorithmic Decision Subjects' Needs for Meaningful Contestability. *Proceedings of the ACM on Human-Computer Interaction* 9, 7 (2025), 1-29. doi:10.1145/3757415

[58] Delvin Ce Zhang, Suhan Cui, Zhelin Chu, Xianren Zhang, and Dongwon Lee. 2026. MEVER: Multi-Modal and Explainable Claim Verification with Graph-based Evidence Retrieval. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, Rabat, Morocco, 5236-5255. doi:10.18653/v1/2026.eacl-long.242

[59] Yuan Zhang, Jason Baldridge, and Luheng He. 2019. PAWS: Paraphrase Adversaries from Word Scrambling. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Association for Computational Linguistics, Minneapolis, Minnesota, 1298-1308. doi:10.18653/v1/N19-1131

[60] Yifan Zhang, Xinkui Zhao, Sai Liu, Hengxuan Lou, Guanjie Cheng, and Chang Liu. 2026. FAVA: Formal Authorization for Verified Agents with Evidence-Backed Permission Graphs. arXiv:2607.27267 [cs.CR] doi:10.48550/arXiv.2607.27267