


# Deep Learning for Seismic Data Classification in Full-Waveform Inversion

Congyue Cui<sup>1</sup>, Chao Song<sup>1</sup>

1. Department of Geosciences, Princeton University, Princeton, NJ, 08540, USA

E-mail: ccui@princeton.edu

chaosong@princeton.edu



COS424 2019 Final Project


## Motivation

### What is our goal?

- We are using **FWI** with *seismograms* to image the *internal structure of the Earth*.
- FWI implementation needs a lot of, but only *good* data.
- High-frequency *surface wave* is messing up our data selection algorithm, so current algorithm has to discard some data that might still be useful.
- We hope *deep neural networks* classification could detect the similarity in data and synthetics unseen by humans to obtain more data.

### What is a *seismogram*?

- An *earthquake* represents the shaking of the surface of the Earth, resulting from the sudden energy release of fault slip underground the Earth that creates *seismic waves*.
- A *seismogram* is the time variant wiggles recorded at the seismic measuring station, a proxy of seismic waves.




### What is FWI?

- Process from seismograms (*data*) to unknown structures (*models*) is called *inversion*.
- To fully exploit the information in data, Full-Waveform Inversion (FWI) was proposed.
- It tries to iteratively minimize the difference between the observed and synthetic seismograms.
- FWI is getting popular only recently due to the development of high-performance computing to deal with the massive computations.

## Method

### What is ResNet and Why?

- deep residual network* (ResNet) is one kind of *convolutional neural network* (CNN).
- CNN is a deep neural network involving convolution, inspired by the biological connectivity between animal neuron resembling.
- CNNs have already many successful applications in *Seismology*, one kind of time series analysis.



- An similar architecture of ResNet in *Seismology* could be like above, but has not been tried yet in previous researches.

## Data and Implementation

### Data Description


- Use ObspyDMT to retrieve, process and manage seismic data<sup>[3]</sup>
- All data used comes from IRIS (Incorporated Research Institutions for Seismology) Data Services<sup>[4]</sup>
- Z component of 20,000 seismograms in total; each 30-min long; 50-s low-pass filtered; down-sampled from 18,000 to 1024.
- Use the time-frequency misfit between the observed and synthetic seismogram<sup>[5]</sup> as the proxy to label our data in the train and test set

$$\chi_e^2(u_i^0, u_i) := \int_{\mathbb{R}^2} W_e^2(t, \omega) [| \tilde{u}_i(t, \omega) | - | \tilde{u}_i^0(t, \omega) |]^2 dt d\omega$$

$$\chi_p^2(u_i^0, u_i) := \int_{\mathbb{R}^2} W_p^2(t, \omega) [\phi_i(t, \omega) - \phi_i^0(t, \omega)]^2 dt d\omega$$

### Implementation


- Refer to the basic CNN API in Keras<sup>[6]</sup> and some time series analysis ideas in Fawaz et al. (2019)<sup>[7]</sup>
- Grows the network by continuously adding more data and epochs to learn incrementally<sup>[8]</sup>
- One-hot encoding; 11 layers including 9 convolutional layers in 3 blocks, 1 global average pooling layer and 1 softmax classifier layer.
- In each block, fixed 64 (128, 128) filters in each conv layer, which equals to the number of extracted features; preceded by batch normalization and ReLU activation; mini-batch size is 16 (256)



### Evaluation Metrics

- Compare the results with the selection (labeling) algorithm.
- Identify contradictory results (Fourier analysis and manual verification).
- Add the seismogram to the inversion and check strange patterns (one of the ways we find out false positives in our current algorithm).

## Result



## Discussion

### Data-preprocessing

- Data volume (more data in both train and test set)
- Diversity (more types of bad observation or even synthetics)
- Label credibility (is the current labelling algorithm reliable, could be tricky to quantify)
- Other representations (Wavelet Transform; ...)

### Architecture

- Mini-batch size (size of data fed into the network every time)
- Learning rate (cause tradeoff between accuracy and time cost)
- Feature size (number of extracted features in each convolutional layer)
- Depth (add more layers)

### Other methods

- FCNN (fully-connected neural networks)
- SVM (support vector machine)
- RF (random forests and ensemble learning)

## Conclusion

- Using automated Resnet classification is feasible for data selection during the data processing stage before FWI.
- Resnet has achieved an acceptable accuracy in finding qualified data for FWI, and its performance is already better than our previous algorithm.
- Several parameters in architecture design, such as mini-batch size, number of features and network depth, can be further optimized and so does the input itself, i.e. data-preprocessing.
- Although this project is rather preliminary, it might illuminate a broader application of ResNet in the future of Seismology, given the big data era is coming.

## Reference

- He, Kaiming, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. "Deep residual learning for image recognition." In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770-778. 2016.
- He, Kaiming, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. "Identity mappings in deep residual networks." In *European conference on computer vision*, pp. 630-645. Springer, Cham, 2016.
- <https://github.com/kasra-hosseini/obsipyDMT>
- <http://ds.iris.edu/ds/>
- Fichtner, Andreas. *Full seismic waveform modelling and inversion*. Springer Science & Business Media, 2010.
- [https://keras.io/examples/cifar10\\_resnet/](https://keras.io/examples/cifar10_resnet/)
- <https://github.com/hfawaz/dl-4-tsc>
- Xiao, Tianjun, Jiayang Zhang, Kuiyuan Yang, Yuxin Peng, and Zheng Zhang. "Error-driven incremental learning in deep convolutional neural network for large-scale image classification." In *Proceedings of the 22nd ACM international conference on Multimedia*, pp. 177-186. ACM, 2014.