tianocore

UEFI & EDK II TRAINING

EDK II Open Board Platform Design for Intel Architecture (IA)

tianocore.org

LESSON OBJECTIVE

- Introduce Minimum Platform Architecture (MPA)
- Explain the EDK II Open board platforms infrastructure & focus areas
- Describe Intel® FSP with the EDK II open board platforms

Reference: Minimum Platform Architecture Specification

DESIRED USE CASES

– Open Source EDK II Platforms

Developers need a way to turn on and off of a feature.

Developers need a way to get platform configuration data.

Developers need to do porting work from an existing board to a new board.

Why can’t the platform tree structures bear more similarity?

tianocore

INTRODUCING
Minimum Platform Architecture

GOALS

Minimum Platform Architecture (MPA)

Structured	Enable developers to consistently navigate code, boot flow, and the functional results
Approachable	Enable developers to quickly produce a baseline that is extensible with minimal UEFI or EDK II knowledge
Portable	Minimize coupling between common, silicon, platform, board, and feature packages
Reusable	Enable large granularity binary reuse (FV binaries)
Testable	Enable validating the correctness of a port

Design open source EDK II Intel Architecture firmware

WHY?

Code Convergence & Consistency

System firmware (BIOS) is the largest payload in the IFWI binary image

Platform implementation is ~2-3 **million** lines+ of “C” code

Technology complexity increasing, strains firmware implementation solutions

Limited firmware engineering resources

Copy + Paste + Modify = Human Errors

tianocore

Why Move to Open Source?

Goal:

- Enable improvements in quality and security for Intel products
- Enable vertically integrated open solutions

Benefits:

- Allow improved customer engagements
- Builds transparency and trust
- Reduce overhead to transition from internal to external
- Deploy fixes across the ecosystem more rapidly

Easier to access, understand, fix & optimize means improved product quality

MinPlatform + Intel® Firmware Support Package (Intel® FSP)



Intel Open Platform Firmware Stack - Minimum Platform

Consistent boot flows and interfaces
Approachable across the ecosystem
Scalable from pre-silicon to derivatives

What are Minimum Platform Stages?



Stages reflect firmware development lifecycle and how a system bootstraps itself

tianocore

Four Focus Areas



- Staged Minimal Baseline
- Feature ON/OFF
  - Debug
  - I/O Devices
  - User Interface
  - . . .

- Staged
- Defined PCD
- Policy Hob/PPI/Protocol

- Staged
- GPIO
- SIO
- ACPI

tianocore

Tree Structure



Organization

Common	• No direct HW requirements
Platform	• Enable a specific platform's capabilities.
Board	• Board specific code
Silicon	• Hardware specific code
Features	• Advanced features of platform functionality that is non-essential for "basic OS boot"



Package Organization Example



MinPlatformPkg	• Common - Boot flow, well defined interfaces
BoardModulePkg	• Board - Generic board functionality (e.g. CMOS access code) – staging to EDK II
XxxOpenBoardPkg	• Platform Xxx* - board-specific details: GPIOs, memory config, audio verb tables, etc.
XxxSiliconPkg	• Silicon - Hardware specific code for Xxx
YyyFeaturePkg	• Features – Advanced functional features

*Where Xxx would be an open platform: `KabyLakeOpenBoardPkg`, `WhiskeyLakeOpenBoardPkg`, etc.

MPA Dependency Rules



Key
Bottom shapes can only depend on shapes above them
`YyyFeaturePkg` – represents multiple feature package instances that are mutually exclusive to each other

BoardAbc – directory for `OpenBoardPkg.dsc`

Open Source EDK II Workspace

```
MyWorkSpace/
     edk2/
       - "edk2 Common"
     edk2-platforms/
       Platform/ "Platform"
          Intel/
            MinPlatformPkg/"Platform"
            BoardModulePkg/"Sharable"
            XxxOpenBoardPkg/ "Platform"
               BoardX/ "Board"
       Silicon/ "Silicon"
          Intel/
            XxxSiliconPkg/
     edk2-non-osi/
       Silicon/
          Intel/
     FSP/"Silicon"
        . . ./
```

Common

Platform

Board

Silicon



Open Board Tree Structure

```
edk2/ https://github.com/tianocore/edk2                    ← Common
  . . .
edk2-platform/ https://github.com/tianocore/edk2-platforms
  Platform/
      Intel/                                               ← Common (sharable)
          BoardModulePkg                                   ← Platform (family)
          KabylakeOpenBoardPkg
             KabylakeRvp3                                  ← Board (instance)
          MinPlatformPkg                                   ← Platform
  Silicon/
      Intel/
          KabylakeSiliconPkg                               ← Silicon
          . . .
  Features/Intel
            AdvancedFeaturePkg                             ← Features
edk2-non-osi/ https://github.com/tianocore/edk2-non-osi
    Silicon/
      Intel/                                               ← Silicon
          KabylakeSiliconBinPkg
          PurleySiliconBinPkg
FSP/  https://github.com/IntelFsp/FSP                      ← Silicon
      KabylakeFspBinPkg
```



Directory Description

edk2-platform: EDK II repo includes open source platform code

- Platform folder: contains the platform specific modules by architecture
  - BoardModulePkg: generic board functionality (board Lib interfaces)
  - MinPlatformPkg: generic platform instance to control the boot flow.
  - <Generation>OpenBoardPkg: the silicon generation specific board package. All of the boards based upon this silicon generation can be located here.
- Silicon folder: contains the silicon specific modules.
  - <Generation>SiliconPkg: the silicon generation specific silicon package.
- Features/Intel folder: contains Advanced features packages.
  - <XxxFeature>Pkg: package and modules for advanced features

edk2-non-osi: EDK II repo for platform modules in binary format (ex: silicon init binaries).

- <Generation>SiliconBinPkg: It is the silicon generation specific binary package. For example, CPU Microcode or the silicon binary FVs.

Ideally, Only `<Generation>OpenBoardPkg` needs updating

FSP Directory Description

FSP: repo for Intel® Firmware Support Package (FSP) binaries

Platform folder Pkg: Each FSP project will be hosted in a separate directory

- ApolloLakeFspBinPkg Intel® Atom™ processor E3900 product family
- . . .
- CoffeeLakeFspBinPkg - 8th Generation Intel® Core™ processors and chipsets (formerly Coffee Lake and Whiskey Lake)
- KabylakeFspBinPkg 7th Generation Intel® Core™ processors and chipsets
  - Include
    - FSP UPD structure and related definitions used with EDK II build
  - Doc - Integration Guide .PDF documentation
  - FSP.fd - Binary to be included with flash device image
  - FSP.bsf - Configuration File with IDE configuration tool

FSP each project based on Intel Architecture

Board Package Structure

MinPlatformPkg

```
MinPlatformPkg /
  <Basic Common Driver>/
  Include /
  Library /
  PlatformInit /
```

Platform Common Driver

Where:

- **<Basic Common Driver>**: The basic features to support OS boot, such as ACPI, flash, and FspWrapper. It also includes the basic security features such as Hardware Security Test Interface (HSTI).
- **Include**: The include file as the package interface. All interfaces defined in MinPlatformPkg.dec are put to here.
- **Library**: It only contains feature independent library, such as PeiLib. If a library is related to a feature, this library is put to <Feature>/Library folder, instead of root Library folder.
- **PlatformInit**: The common platform initialization module. There is PreMemPEI, PostMemPEI, DXE and SMM version. These modules control boot flow and provide some hook point to let board code do initialization.

Board Module Package Structure

BoardModulePkg

```
BoardModulePkg /
  Include /
  Library /
    BiosIdLib /
    CmosAccessib /
    PlatformCmosAccessLibNull /
```

Board Generic Functionality

Where:

- **Include**: The include file as the package interface. All interfaces defined in BoardModulePkg.dec are put to here.
- **Library**: It only contains board generic features as independent library, such as BiosIdLib and Cmos Access Lib

Open Board Package Structure

<Generation>OpenBoardPkg

```
<Generation>OpenBoardPkg /
  <BasicCommonBoardDrivers>/
  Include /
  Library /
  Features /
     <AdvancedCommonBoardDrivers> /
  <BoardX> /
     Include/
     Library/
     <BoardSpecificDriver> /
     OpenBoardPkg.dsc
     OpenBoardPkg.fdf
```

Where:

- <BasicCommonBoardDrivers> and <AdvancedCommonBoardDrivers> designate a board generation specific feature. They need to be updated when we enable a board generation.
- <Board> contains all the board specific settings. If we need to port a new board in this generation, copy the <Board> folder and update the copy's settings

Advanced Feature Package

```
Features/Intel /
  XxxFeaturePkg /
     Include /
     Library /
     Readme.md
```

The advanced features, domains such as SMBIOS table, IPMI, User Interface, Power Management

Where:

Include: The **include** file as the package interface.
Library: Implementation of feature as a library.
Readme.md : Describes the purpose and scope of the feature package with a list of dependencies

One Feature, One directory Guideline

Use a hierarchical layout , KabylakeOpenBoardPkg example

```
KabylakeOpenBoardPkg /
  Acpi /
    BoardAcpiDxe  /
  FspWrapper /
    Library /
    PeiFspPolicyUpdateLib /
  Include /
  KabylakeRvp3
  Library /
    BaseEcLib /
    BaseGpioExpanderLib /
    PeiI2cAccessLib /
  Policy /
```

```
KabylakeRvp3 / (cont.)
  Include /
  Library /
  OpenBoardPkg.dsc
  OpenBoardPkg.fdf
```

Only put the basic features into the root directory

tianocore

Features



- Staged Minimal Baseline
- Feature ON/OFF
  - Debug
  - I/O Devices
  - User Interface
  - . . .

tianocore

Feature Selection

There are three phases of feature selection



Minimum	Manage Stage I-V options
Advanced Feature Selection	Add rich feature sets (Stage VI)
Optimization	Remove undesired features (Stage VII)

Select features through build, prune in binary

Minimum Platform Feature Selection



Minimum Platform

- Minimum feature selection should be exclusively implemented as Platform Configuration Database (PCD)
- Required PCD are identified in the MPA specification
- PCDs:
  - Declared with defaults in DEC files in different packages
  - Modified in DSC file for the board, if different than the default value

Silicon – FSP Integration from <Generation>FspBinPkg documentation package

All initial porting features selection should be done this way

Advanced Feature Selection

Advanced features implement DSC and FDF files that you can include in your board DSC and FDF files in the correct spots

OpenBoardPkg.dsc File

. . .

<End-of-File>

!include YyyAdvancedPkg.dsc

OpenBoardPkg.fdf File

FV Advanced Pre-Mem

!include YyyAdvancedPkgPreMem.fdf

FV Advanced Post-Mem

!include YyyAdvancedPkgPostMem.fdf

FV Advanced Late

!include YyyAdvancedPkgLate.fdf

FV Advanced ← (Pre-mem + Post-mem + Late)

Optimization Feature Selection

Minimum Platform takes advantage of UEFI and EDK II features to enable feature selection to be done by post-processing the built binaries

Essentially, after your system is functioning well, you can remove features using the FMMT tool to remove the drivers that are included as you build up the desired functionality

For example, if you need UEFI Shell during power-on, testing, etc. But you don't want it for final product. Minimum Platform architecture makes it easy to locate and remove the shell by post-processing the image

Link for FMMT Tool



Full Customization Feature Selection



Feature modifications only at the Board / Platform DSC

Preferred modifications at Board (e.g. `BoardAbc`)



BoardAbc – directory for `OpenBoardPkg.dsc`

tianocore

Features Build Enabled

Platform-Board Build Scripts



Many platforms have a script (Python or bash) to pre & post process the EDK II build process: Build Script

Example: Invoked from the `edk2-platforms/Platform/Intel`

```
python build_bios.py –p <Board-name>
```

uses config file `build.cfg` from the `<Board-name>` directory

Configuration Files:

- edk2-platforms/Platform/Intel/build.cfg - default settings
- Default settings are under the DEFAULT_CONFIG section
- Override the `edk2-platforms/Platform/Intel/. . ./build.cfg` settings from each board in board specific directory

Example Build Config File



Kabylake example of Board specific settings:

`<workspace>/edk2-platforms/Platform/Intel/KabylakeOpenBoardPkg/\KabylakeRvp3/ build_config.cfg`

```
[CONFIG]
WORKSPACE_PLATFORM_BIN = WORKSPACE_PLATFORM_BIN
EDK_SETUP_OPTION =
openssl_path =
PLATFORM_BOARD_PACKAGE = KabylakeOpenBoardPkg
PROJECT = KabylakeOpenBoardPkg/KabylakeRvp3
BOARD = KabylakeRvp3
FLASH_MAP_FDF = KabylakeOpenBoardPkg/Include/Fdf/FlashMapInclude.fdf
PROJECT_DSC = KabylakeOpenBoardPkg/KabylakeRvp3/OpenBoardPkg.dsc
BOARD_PKG_PCD_DSC =
KabylakeOpenBoardPkg/KabylakeRvp3/OpenBoardPkgPcd.dsc
ADDITIONAL_SCRIPTS =
KabylakeOpenBoardPkg/KabylakeRvp3/build_board.py
PrepRELEASE = DEBUG
SILENT_MODE = FALSE
...
```

Platform name & path to `build.cfg` file under `[PLATFORMS]`

Minimum Platform Stage Selection

Platform Firmware Boot Stage PCD :

OpenBoardPkgPcd.dsc




```
[PcdsFixedAtBuild]
  #
  # Please select BootStage here.
  # Stage 1 - enable debug (system deadloop after debug init)
  # Stage 2 - mem init (system deadloop after mem init)
  # Stage 3 - boot to UEFI shell only
  # Stage 4 - boot to OS
  # Stage 5 - boot to OS with security boot enabled
  # Stage 6 – Add Advanced features
  gMinPlatformPkgTokenSpaceGuid.PcdBootStage|4
```

Minimum Platform Stage Selection

Stage selection allows developers to bring up a system in a familiar matter:

- Set to Stage I. Boot, verify serial debug capability, ready for silicon debug
- Set to Stage II. Boot, verify memory and silicon functionality
- Set to Stage III. Boot, verify board porting from shell: devices, GPIO, etc
- Set to Stage IV. Boot, verify ACPI porting, MADT, DSDT methods, etc.

Developers can exercise functionality gradually.

Verification at each stage

Required set of PCDs in MPA Spec



Link to Required PCDs according to stages

- Flash Map Config
- Debug Config
- Intel® FSP Config
- Post Memory FV
- UEFI FV
- Driver Related

- Memory Type Information
- OS FV
- Security Flash Map
- Stage 5 Features
- Advanced Feature FV

Build Control Files



DSC files

control what gets compiled and linked

FDF files

control what gets put in the system FLASH image

Where are the DSC & FDF files?

Kabylake Open Board

```
Platform/Intel/KabyLakeOpenBoardPkg/

  KabyLakeRvp3/


    OpenBoardPkgPcd.dsc      ← Modify PCD Here
    OpenBoardPkgBuildOption.dsc
    OpenBoardPkg.dsc         ← Add Features Here

    FlashMapInclude.fdf
    OpenBoardPkg.fdf         ← Add Features Here
```

```
/edk2-platforms/Platform/
  Intel/MinPlatformPkg/
    Include/
      Fdf/
      Dsc/

/edk2-platforms/Features/
  Intel/YyyAdvancedPkg/
    Include/
      Fdf/
      Dsc/
```

`OpenBoardPkgPcd.dsc` File Controls if feature ON or OFF

Example Kabylake Configuration .DSC file

```
[PcdsFixedAtBuild]
  #
  # Please select BootStage here.
  # Stage 1 - enable debug (system deadloop after debug init)
  # Stage 2 - mem init (system deadloop after mem init)
  # Stage 3 - boot to shell only
  # Stage 4 - boot to OS
  # Stage 5 - boot to OS with security boot enabled
  #
  gMinPlatformPkgTokenSpaceGuid.PcdBootStage|4

[PcdsFeatureFlag]
  gMinPlatformPkgTokenSpaceGuid.PcdStopAfterDebugInit|FALSE
  gMinPlatformPkgTokenSpaceGuid.PcdStopAfterMemInit|FALSE
  gMinPlatformPkgTokenSpaceGuid.PcdBootToShellOnly|FALSE
  gMinPlatformPkgTokenSpaceGuid.PcdUefiSecureBootEnable|FALSE
  gMinPlatformPkgTokenSpaceGuid.PcdTpm2Enable|FALSE

!if gMinPlatformPkgTokenSpaceGuid.PcdBootStage >= 1
  gMinPlatformPkgTokenSpaceGuid.PcdStopAfterDebugInit|TRUE
!endif
```

Link to OpenBoardPkgPcd.dsc Confg .dsc file

Link to EDK II DSC Spec.

Example Kabylake .FDF file

```
[FV.FvPreMemory]
INF UefiCpuPkg/SecCore/SecCore.inf
INF MdeModulePkg/Core/Pei/PeiMain.inf
!include $(PLATFORM_PACKAGE)/Include/Fdf/CorePreMemoryInclude.fdf
INF $(PLATFORM_PACKAGE)/PlatformInit/PlatformInitPei/PlatformInitPreMem.inf
INF IntelFsp2WrapperPkg/FspmWrapperPeim/FspmWrapperPeim.inf
INF $(PLATFORM_PACKAGE)/PlatformInit/SiliconPolicyPei/SiliconPolicyPeiPreMem.inf
[FV.FvPostMemoryUncompact]
!include $(PLATFORM_PACKAGE)/Include/Fdf/CorePostMemoryInclude.fdf
# Init Board Config PCD
INF $(PLATFORM_PACKAGE)/PlatformInit/PlatformInitPei/PlatformInitPostMem.inf
INF IntelFsp2WrapperPkg/FspsWrapperPeim/FspsWrapperPeim.inf
INF $(PLATFORM_PACKAGE)/PlatformInit/SiliconPolicyPei/SiliconPolicyPeiPostMem.inf
!if gSiPkgTokenSpaceGuid.PcdPeiDisplayEnable == TRUE
FILE FREEFORM = 4ad46122-ffeb-4a52-bfb0-518cfca02db0 {
SECTION RAW = $(PLATFORM_FSP_BIN_PACKAGE)/SampleCode/Vbt/Vbt.bin
SECTION UI = "Vbt"
}
FILE FREEFORM = 7BB28B99-61BB-11D5-9A5D-0090273FC14D {
SECTION RAW = MdeModulePkg/Logo/Logo.bmp
}
```

Link to Kabylake .FDF

Link to EDK II FDF Spec

tianocore

Configuration



- Staged
- Defined PCD
- Policy Hob/PPI/Protocol

tianocore

Configuration Options

There might be many sources of platform configuration data.

- PI PCD
- Configuration Block
- CMOS
- UEFI Variable
- Global NVS
- MACRO
- FSP UPD- Silicon Policy Hob/PPI/ Protocol
- Platform signed data blob

MPA Configuration Options

Platform configuration data for Minimum Platform

PI PCD	• The PI PCD could be static data fixed at build time or dynamic data updatable at runtime.
FSP UPD- Silicon Policy Hob/PPI/ Protocol	• FSP UPD can be static default configuration, or a dynamic updatable UPD. It is policy data constructed at runtime or it can be a hook for silicon code
Global NVS	• ACPI region, passes configuration from C code to ASL code.

TIP: Use PCD Instead of UEFI Variable

UEFI Variable

```
//
// Get config from setup variable
//
VarDataSize = sizeof (SETUP_DATA);
Status = GetVariable (
    L"Setup",
    &gSetupVariableGuid,
    NULL,
    &VarDataSize,
    &mSystemConfiguration
);
```

PCD

```
//
// Get setup configuration from PCD
//
CopyMem (
    &mSystemConfiguration,
    PcdGetPtr (PcdSetupConfiguration),
    sizeof(mSystemConfiguration)
);
```

PCD Syntax Review

PCD defined in the DEC file from any package

```
[Guids.common]
PcdTokenSpaceGuidName={0x914AEBE7, 0x4635, 0x459b, { 0xAA, . . .}}

. . .
[Pcds...]
PcdTokenSpaceGuidName.PcdTokenName|Value[|DatumType[|MaxSize]]|Token
```

PCD usage listed in INF file for module

```
[…Pcd…]
PcdTokenSpaceGuidName.PcdTokenName|[Value]
```

Value of PCD set in OpenBoardPkg...dsc

```
[Pcds...]
PcdTokenSpaceGuidName.PcdTokenName|Value[|DatumType[|MaximumDatumSize]]
```

How to Map PCD to Configuration Data

Using “Callback” mechanism to convert PCD to Configuration data

Platform driver should use `PcdGet()` to retrieve policy data, and `PcdSet()` to update policy data.



Source Open_Source_IA_Firmware_Platform_Design_Guide_in_EFI_Developer_Kit_II.pdf Fig 7.

“C” Data Structure as PCDs

Example: AdvancedFeaturePkg.dec for SMBIOS type 0 data structure

```
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation| \
        {0x0}|SMBIOS_TABLE_TYPE0|0x80010000 {
    <HeaderFiles>
       IndustryStandard/SmBios.h
    <Packages>
       MdePkg/MdePkg.dec
       AdvancedFeaturePkg/AdvancedFeaturePkg.dec
}
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.Vendor|0x1
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosVersion|0x2
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosSegment|0xF000
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosReleaseDate|0x3
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosSize|0xFF
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosCharacteristics.\
     PciIsSupported|1
gAdvancedFeaturePkgTokenSpaceGuid.PcdSmbiosType0BiosInformation.BiosCharacteristics.\
     PlugAndPlayIsSupported|1
```

Example of DSC xRef (.DEC & .h)

Purley Pkg DEC File

```
## gEfiSetupVariableGuid
OemSkuTokenSpaceGuid.PcdSetupData|{0x0}|\
SYSTEM_CONFIGURATION|0x000F0001 {
<HeaderFiles>
      Guid/SetupVariable.h
    <Packages>
      MdePkg/MdePkg.dec
      PurleyRcPkg/RcPkg.dec
      PurleySktPkg/SocketPkg.dec
      LewisburgPkg/PchRcPkg.dec
      PurleyOpenBoardPkg/PlatPkg.dec
  }
```

"C" SetupVariable.h File

```
. . .
   UINT8    FanPwmOffset;
   UINT8    WakeOnLanSupport;
   UINT8    Use1GPageTable;
   UINT8    CloudProfile;
} SYSTEM_CONFIGURATION;
```

StructureConfig.DSC File

```
gOemSkuTokenSpaceGuid.PcdSetupData.\
CloudProfile|0x0

gOemSkuTokenSpaceGuid.PcdSetupData.\
Use1GPageTable|0x1

gOemSkuTokenSpaceGuid.PcdSetupData.\
FanPwmOffset|0x0

gOemSkuTokenSpaceGuid.PcdSetupData.\
WakeOnLanSupport|0x0

. . .
```

Configuration Multi-SKU PCD – Board ID

DSC File – SKU Set at BUILD time

```
. . .
SKUID_IDENTIFIER = ?

[SkuIds]
0|DEFAULT
4|BoardX
0x42|BoardY

[PcdsDynamicDefault.common.BoardX]
gBoardModuleTokenSpaceGuid.PcdGpioPin|0x8
gBoardModuleTokenSpaceGuid.PcdGpioInitValue|\
        {0x00, 0x04, 0x02, 0x04, ...}

[PcdsDynamicDefault.common.BoardY]
gBoardModuleTokenSpaceGuid.PcdGpioPin|0x4
gBoardModuleTokenSpaceGuid.PcdGpioInitValue|\
        {0x00, 0x02, 0x01, 0x02, ...}
```

SKU PCD Set Dynamically

```
BoardXBoardDetect( VOID)
{
. . .
  if (LibPcdGetSku () != 0) {
    return EFI_SUCCESS;
  }
  if (IsBoardX ()) {
     LibPcdSetSku (BoardIdIsBoardX);
     ASSERT (LibPcdGetSku() ==
                BoardIdIsBoardX);
  }
  return EFI_SUCCESS;
}
```

Default Stores PCD – for Configuration

DSC File –

```
. . .
VPD_TOOL_GUID = 8C3D856A-9 . . .

[DefaultStores]
0|STANDARD
1|MANUFACTURING
2|SAFE


[PcdsDynamicExVpd.common.DEFAULT]
  gEfiMdeModulePkgTokenSpaceGuid.PcdNvStoreDefaultValueBuffer|*
[PcdsDynamicEx.common.DEFAULT.STANDARD]
  gOemSkuTokenSpaceGuid.PcdSetupData.CloudProfile|0x0
  gOemSkuTokenSpaceGuid.PcdSetupData.Use1GPageTable|0x1
[PcdsDynamicEx.common.DEFAULT.MANUFACTURING]
  gOemSkuTokenSpaceGuid.PcdSetupData.CloudProfile|0x1
  gOemSkuTokenSpaceGuid.PcdSetupData.Use1GPageTable|0x0
```

- Special PCD to support the default stores concept in UEFI specification
- Can be Dynamically set

Silicon Policy Data Flow Guidelines

Silicon Module Provides Default Silicon Policy Data

- `Typedef` data structure

Board Module Updates the Silicon Policy Data

- PCD database, Setup Variable, Binary Blob, etc.

Example: FSP policy in MinPlatformPkg



Update Silicon Policy example

KabylakeOpenBoardPkg/FspWrapper/Library/PeiSiliconPolicyUpdateLibFsp

```
EFI_STATUS
EFIAPI
PeiFspSaPolicyUpdatePreMem (
IN OUT FSPM_UPD *FspmUpd
)
{
VOID *Buffer;
// Override MemorySpdPtr
CopyMem((VOID *)(UINTN)\
 FspmUpd->FspmConfig.MemorySpdPtr00,\
 (VOID *)(UINTN)PcdGet32 (PcdMrcSpdData), \
 PcdGet16 (PcdMrcSpdDataSize));
CopyMem((VOID *)(UINTN)\
 FspmUpd->FspmConfig.MemorySpdPtr10,\
 (VOID *)(UINTN)PcdGet32 (PcdMrcSpdData),\
 PcdGet16 (PcdMrcSpdDataSize));
```

```
 •   •   •
// Updating Dq Pins Interleaved,Rcomp Resistor &
// Rcomp Target Settings

 Buffer = (VOID *) (UINTN) PcdGet32 \
          (PcdMrcRcompTarget);
  if (Buffer) {
    CopyMem ((VOID *)\
      FspmUpd->FspmConfig.RcompTarget, \
      Buffer, 10);
  }
  return EFI_SUCCESS;
}
```

Link to file: PeiSaPolicyUpdatePrMem.c

Dynamically Set Defaults

The Default Store PCD is also a dynamic PCD.

During boot, the board initialization code checks the boot mode and selects the default store.

This step must be after SetSku. Otherwise, the default setting may be wrong.

```
...
if (NeedDefaultConfig()) {
PcdSet16S (PcdSetNvStoreDefaultId, 0x0);
}
```

tianocore

Board Porting



- Staged
- GPIO
- SIO
- ACPI

Staged Approach by Features

- Platform Firmware Boot Stage PCD

PCD Variable:

`gPlatformModuleTokenSpaceGuid.PcdBootStage`

Stage 1	enable debug
Stage 2	memory initialization
Stage 3	boot to UEFI shell only
Stage 4	boot to OS
Stage 5	boot to OS w/ security enabled
Stage 6	Advanced Feature Selection
Stage 7	Performance Optimizations

PCD Is tested within .FDF to see which modules to include

tianocore

Minimum Platform + Intel® FSP Boot Flow
- Staged Approach



Stages Organize the MPA Specification



tianocore

Staged Approach by Features

- Firmware Volume



Modules organized by Firmware Volumes according to the different boot stages

UEFI Firmware Volumes (FV) - Review

Platform Initialization - Firmware Volume

- Basic storage repository for data and code is the Firmware Volume (FV)
- Each FV is organized into a file system, each with attributes
- One or more Firmware File Sections (FFS) files are combined into a FV
- Flash Device may contain one or more FVs.
- .FDF file controls the layout → .FD image(s)



PI Spec Vol 3

tianocore

Standardize FV By Stages

Pre-Memory	• FvPreMemory – The PEIM dispatched before the memory initialization. Also included FSP - FV
Post Memory	• FvPostMemory – The PEIM dispatched after the memory initialization. Also included FSP - FV
UEFI Boot	• FvUefiBoot – The DXE driver supporting UEFI boot, such as boot to UEFI shell.
OS Boot	• FvOsBoot – The DXE driver supporting UEFI OS boot, such as UEFI Windows.
Security	• FvSecurity – The security related modules, such as UEFI Secure boot, TPM etc.
Advanced	• FvAdvanced – The advanced feature modules, such as UEFI network, IPMI etc.

FSP Firmware Volumes
– created Pre-Build

```
MyWorkSpace/
     edk2/
       - “edk2 Common”
     edk2-platforms/
       Platform/Intel “Platform”
          KabyLakeOpenBoardPkg/
            include/fdf \
               FlashMapInclude.fdf
            BoardXPkg/ “Board”
       Silicon/ “Silicon”
          Intel/MinPlatformPkg/
     edk2-non-osi/
       Silicon/Intel/
     FSP/
      BoardXPkg
         Fsp.fd
```

Fsp.fd Rebased for FVs

FvFspT
- – Temp Memory

FvFspM
- -> FvPreMemorySilicon

FvFspS
- -> FvPostMemorySilicon

Pre-Build w/
`RebaseAndPatchFspBinBaseAddress.py`

tianocore

FSP APIs in FSP Binary

Using Intel® FSP w/ EDK II: PDF



Boot Flow with FSP API Mode

5 APIs for FSP



Source: Using the Intel® FSP with EDK II (2.0) Fig 4.

FSP 2.1 Dispatch Mode Boot Flow

`gIntelFsp2WrapperTokenSpaceGuid.PcdFspModeSelection` 0 - dispatch, 1 – API



FSP Spec 2.1

tianocore

PLATFORM HOOKS

Using EDK II Libraries

EDK II Libraries w/ Platform Hooks

DSC maps library class to library-instances

Syntax in DSC file

```
[libraryclasses]
  LibraryClassName|Path/To/LibInstanceNameInstance1.inf
```

Search INF files for string: “**LIBRARY_CLASS =**”

tianocore

Library Classes Section in DSC

DebugLib class example

Library Class Section

```
[LibraryClasses]
    DebugLib|MdePkg/Library/BaseDebugLibNull/BaseDebugLibNull.inf
    ...
[LibraryClasses.common.DXE_CORE]
    ...
    DebugLib|IntelFrameworkModulePkg/Library/PeiDxeDebugLibReportStatusCode/
            PeiDxeDebugLibReportStatusCode.inf
    ...
[LibraryClasses.common.DXE_SMM_DRIVER]
    DebugLib|MdePkg/Library/BaseDebugLibNull/BaseDebugLibNull.inf
```

Components Section

```
[Components]
   ...
MyPath/MyModule.inf {
<LibraryClasses>
    DebugLib|MdePkg/Library/BaseDebugLibSerialPort.inf
}
```

Platform Initialization Board Hook Modules

```
MinPlatformPkg/
  Include/
    Library/
      BoardnitLib.h
  Library/
  . . .
  PlatformInit/
    PlatformInitPei/
      PlatformInitPreMem/
      PlatformInitPostMem/
    PlatformInitDxe/
    PlatformInitSmm/
```

```
BoardDetect()
BoardDebugInit()
BoardBootModeDetect()
BoardInitBeforeMemoryInit()
BoardInitBeforeTempRamExit()
BoardInitAfterTempRamExit()
BoardInitAfterMemoryInit()
BoardInitBeforeSiliconInit()
```

PEI

```
BoardInitAfterPciEnumeration()
BoardInitReadyToBoot()
BoardInitEndOfFirmware()
```

DXE

Platform Initialization Board Hook Modules

```
MinPlatformPkg/
   . . .
   PlatformInit/
    PlatformInitPei/
     PlatformInitPreMem/
```

```
PlatformInitPreMem/
   BoardDetect()
   BoardDebugInit()
   BoardBootModeDetect()
   BoardInitBeforeMemoryInit()
. . .
Notify call back
   BoardInitAfterMemoryInit()
```

PEI

```
     PlatformInitPostMem/
```

```
PlatformInitPostMem/
   BoardInitBeforeSiliconInit()
. . .
   BoardInitAfterSiliconInit()
```

How to find the Platform Hooks: Process of Porting

Check the Board/Platform .FDF file layout

Investigate the FDF then DSC files

Porting process per stage find and update platform hooks

1. Locate FVs for each stage
2. Modules for each FV contents
3. Module Locations
4. Platform Porting Libraries per Module
5. Update the Hook Function for Board



Also check the reference platform BUILD directory

tianocore

How to search for Libraries in the Workspace

1. Search the workspace .DSC files for the string of the library
2. Open the .DSC files associated with the open board platform project
3. Determine which Library is used and that should have the build path in the workspace
4. DSC file will have similar to:

```
SomeLib|Path_to_the_Library_used.inf
```

5. Verify the instance used from the `Build` directory

Platform Initialization Board Hook Modules - Stage 1

```
MinPlatformPkg/
  Include/
    Library/
      BoardInitLib.h ←— // hooks
  Library/
  . . .
  PlatformInit/
    PlatformInitPei/
      PlatformInitPreMem/
```

```
BoardDetect()
BoardDebugInit()
BoardBootModeDetect()
BoardInitBeforeMemoryInit()
```

Platform folder `PlatformInit` controls the platform initialization flow

Link: BoardInitLib.h

Example Hook - Board Detection

-Kabylake example

```
MinPlatformPkg/
  . . .
  PlatformInit/
    PlatformInitPei ->
      PlatformInitPreMem.c
        BoardDetect()
KabylakeOpenBoardPkg/
  . . .
  KabylakeRvp3/
    Library/
      BoardInitLib ->
        PeiBoardInitPreMemLib.c
          BoardDetect()
        PeiKabylakeRvp3Detect.c
          KabylakeRvp3BoardDetect()
```

Uses PCD Library calls to set / get Board SKU for Storing Board ID

`LibPcdGetSku()` & `LibPcdSetSku()`

`KabylakeRvp3BoardDetect()` function reads Board ID from embedded controller (EC) using the LPC bus

`LibPcdSetSku()` stores Board ID

`LibPcdGetSku()` used from that point on

Minimum Platform Architecture Summary



- Staged Minimal Baseline
- Feature ON/OFF
  - Debug
  - I/O Devices
  - User Interface
  - . . .

- Staged
- Defined PCD
- Policy Hob/PPI/Protocol

- Staged
- GPIO
- SIO
- ACPI

tianocore

SUMMARY

- Minimum Platform Architecture (MPA) is an Open source Intel platform code base for use with EDK II
- EDK II Minplatform's infrastructure focus areas: Tree, Features, Configuration & Porting
- MinPlatform uses Intel® FSP for processor, silicon and memory init & uses silicon policy guildlines for data flow


Questions?

Return to Main Training Page

Return to Training Table of contents for next presentation link


tianocore

tianocore

BACK UP

Basic Boot Components



Board default setup variable data



Board Detection and Initialization Flow