

Motion Estimation

— BMA

Dr. Xigun Lu

College of Computer Science

Zhejiang University

Outline

- Optical Flow (Pixel-level)
 - What is optical flow?
 - Lucas-Kanade algorithm (LK) ^[2]
 - Horn-Schunck algorithm (HS) ^[3]
- BMA (Block-level)
 - The principle of BMA
 - Full search scheme
 - Three step search ^[4]
 - New three step search ^[5]
 - Four step search ^[6]
 - Diamond search scheme ^[7]


Outline

- Optical Flow (Pixel-level)
 - What is optical flow?
 - Lucas-Kanade algorithm (LK) [2]
 - Horn-Schunck algorithm (HS) [3]
- BMA (Block-level)
 - The principle of BMA
 - Full search scheme
 - Three step search [4]
 - New three step search [5]
 - Four step search [6]
 - Diamond search scheme [7]

Correlation in Video Frames




To remove the **temporal redundancy** between successive frames.



The Principle of BMA

- For each image-block, find the best matching block in the previously **encoded** frame.
 - Motion vector
 - The DCT transform coefficients of the **residual** signal will be transmitted.



Block-matching: Error Measure

- Mean Square Error (MSE)

$$MSE = \frac{1}{I * J} \sum_{i=1}^I \sum_{j=1}^J [f(i, j) - g(i - dx, j - dy)]^2$$

- Mean of the Absolute frame Difference (MAD)

$$MAD = \frac{1}{I * J} \sum_{i=1}^I \sum_{j=1}^J |f(i, j) - g(i - dx, j - dy)|$$

- Sum of Absolute Difference (**SAD**)

$$SAD = \sum_{i=1}^I \sum_{j=1}^J |f(i, j) - g(i - dx, j - dy)|$$

Generally, $I = J = 16$

Full Search Method

- Search every point in the searching window
 - Matching: $(2w+1)^2$
 - For each matching, the error computation: $N \times N$
 - If $w=16$ (the default search range in MPEG-1/2/4), the total number of search points will be 1089.

References

- [1] G. Johansson, “Visual perception of biological motion and a model for its analysis”, *Perception and Psychophysics*, vol.14, 201-211, 1973.
- [2] B. Lucas and T. Kanade, “An iterative image registration technique with an application to stereo vision,” in Proc. of *International Joint Conf. On Artificial Intelligence*, pp.674-679, 1981.
- [3] B. Horn and B. Schunck, “Determining optical flow,” *Artificial Intelligence*, 17:185-203, 1981.
- [4] T. Koga, K. Iinuma, A. Hirano, Y. Iijima, and T. Ishiguro, “Motion compensated interframe coding for video conferencing,” *Proceedings of national Telecommunications conference*, New Orleans, LA, pp.G5.3.1–G5.3.5, Dec. 1981.
- [5] R. Li, B. Zeng, and M. L. Liou, “A new three-step algorithm for block motion estimation,” *IEEE Trans. On Circuits and Systems for Video Technology*, 4(4): 438-442, 1994.
- [6] L.-M. Po and W.-C. Ma, “A novel four-step search algorithm for fast block motion estimation,” *IEEE Trans. On Circuits and Systems for Video Technology*, 6(3): 313-317, 1996.
- [7] S. Zhu and K.-K. Ma, “A new diamond search algorithm for fast block-matching motion estimation,” *IEEE Trans. On Image Processing*, 9(2): 287-290, 2000.

Thank You!

Dr. Xigun Lu

xqlu@zju.edu.cn