# BIRDB: Towards Secure and Efficient Encrypted Search for Encrypted Databases

*Anonymous Submission #59*

***Abstract*—The escalating concerns surrounding the security of data outsourced to untrusted cloud servers have driven significant advancements in *Encrypted Databases* (EDB). EDBs provide secure storage, search, and processing of encrypted data while ensuring the confidentiality of search metadata. However, existing approaches face challenges in achieving both efficient encrypted search and metadata confidentiality. One line of work constructs cryptographic indexes on property-preserving ciphertexts for efficient searches but suffers from a substantial increase in index size and inadvertent metadata leakage. The other line of work resorts to scanning the entire dataset to hide metadata, resulting in significant overhead for encrypted search.**

**We present BIRDB, the first high-performance and metadata-hiding encrypted database. At the core of BIRDB lies a new *boolean information retrieval* technique, enabling logarithmic search complexity on ciphertexts within a searchable index structure. The boolean nature of the index provides two crucial advantages: (1) lossless index compression through linear approximation and (2) seamless integration with efficient private information retrieval (PIR) protocols. This integration allows computationally expensive query-independent computations to be shifted to an offline phase, leading to sublinear computation during the query-specific online phase, all while ensuring metadata protection. Extensive evaluations demonstrate the superiority of BIRDB, achieving up to 15.2X higher query throughput, occupying 1018X less space, and providing robust metadata protection compared to existing notable EDB solutions.**

## I. INTRODUCTION

The popularity of cloud computing has prompted numerous organizations to adopt cloud storage services like DropBox [31] and Onedrive [84] for their scalability and rich query capabilities [9], [47], [85]. However, this increased reliance has also raised significant security concerns. For example, a recent data breach resulted in the exposure of personal information belonging to 237,000 US government employees [1]. Samsung has leaked its confidential source code, where employees had uploaded it to ChatGPT for solutions [7]. TikTok has also faced accusations of compromising user privacy, particularly regarding the data of over 150 million US citizens uploaded to the cloud [8].

Recently, *Encrypted Databases* (EDBs) have emerged as a reliable solution for confidential computing on the public cloud. EDBs store data exclusively in encrypted form without storing decryption keys, ensuring data confidentiality against privileged database administrators and external attackers (in short, *adversaries*). To facilitate secure and efficient query processing on large and continuously expanding encrypted datasets, EDBs must incorporate searchable and compact indexes, similar to traditional insecure databases like MySQL [60]. More importantly, EDBs must utilize oblivious algorithms to safeguard search metadata, preventing adversaries from extracting sensitive information about the encrypted data from index access footprints [24], [33], [89].





**Fig. 1:** Compared to an EDB that uses only end-to-end encryption shown in **(a)**∼**(c)**, a metadata-hiding EDB in **(d)** disguises intended index operations with dummy operations, effectively preventing adversaries from determining which index node is being accessed, ensuring enhanced confidentiality protection.

Consider an example of how an adversary can exploit search access patterns to exfiltrate data and how an EDB would benefit from metadata protection [27]. Figure 1 depicts an EDB server that stores a search index, typically a binary search tree (BST) or its variants, that maps an encrypted keyword to its file. The adversary first observes a series of plaintext queries and their respective index operations shown in (a)∼(b). In this example, it observes two point lookup queries retrieving files containing the keywords 'cat' and 'dog' and their respective search paths. By repeating this process, the adversary can learn the keyword linked to every index node; subsequently, when a user submits a confidential query with an encrypted search keyword ('⋆' in (c)), the adversary can deduce the keyword without requiring decryption keys based on the search path and the specific index node accessed, causing unexpected data leakage. An EDB with metadata protection employs oblivious algorithms that incorporate dummy accesses **(d)**, to conceal the actual search access patterns, thus mitigating the search pattern vulnerability.

A commonly employed approach to achieve both searchability and metadata protection is the use of Oblivious RAM (ORAM) [32], [66], [77]. ORAM-based methods enable cryptographic concealment of read/write operations on servers while keeping search accesses confidential. Several academic studies have proposed incorporating a BST within ORAM as a

Network and Distributed System Security (NDSS) Symposium 2024
26 February - 1 March 2024, San Diego, CA, USA
ISBN 1-891562-93-2
https://dx.doi.org/10.14722/ndss.2024.24059
www.ndss-symposium.org

straightforward technique [30], [37], [75]. However, despite the polylogarithmic asymptotic complexity of ORAM in relation to the size of the index, the practical implementation of ORAM schemes remains prohibitively expensive. This is primarily due to the requirement of executing all oblivious computations within a single query-processing stage [27], [66].

As an alternative, the second line of work leverages specific cryptographic tools to maintain either searchability or metadata privacy. Specifically, CryptDB [68] and its variants [41], [80] use property-preserving encryption algorithms [18], [10]. These algorithms maintain determinism and ordering of encrypted data, enabling the construction of BSTs with logarithmic search complexity. However, these approaches tend to overlook metadata security. Additionally, they often suffer from unexpectedly poor query performance due to the substantial increase in the size of encrypted index nodes because this surged index size necessitates a higher reliance on I/O expensive external storage solutions such as disks [34], [46].

To hide search access pattern and address the challenge of increased encrypted index size, HELibDB [25] employs Fermat's Little Theorem [83] to directly assess the equivalence of homomorphically encrypted data [35], [91], eliminating the need for index construction. However, this direct evaluation necessitates linearly scanning a large amount of encrypted data and consumes substantial bandwidth due to multi-round communication requirements. Another approach, OO-PIR [57], preprocesses the database into multiple chunks, where each online query retrieves an entire chunk as dummy operations to conceal the accessed data. Although costly oblivious operations are moved to an offline phase, it still requires scanning each chunk to test the membership of the queried data, resulting in a significant decrease in performance.

Overall, the development of an EDB that can achieve efficiency (logarithmic search complexity), compactness (constant space for indexing regardless of the total stored data), and metadata-hiding is still an open problem and highly desirable.

Drawing inspiration from existing Boolean Information Retrieval (BIR) protocols developed for document retrieval [12], [52], our key observation is that the *membership* information has significant potential to achieve all the aforementioned properties simultaneously. Specifically, we identify two distinct benefits of membership information. First (searchability), it provides a new approach to enable search on ciphertexts by replacing traditional numerical comparisons in BSTs with membership tests. Second (compactness), the boolean characteristic of membership information allows for the integration of advanced compression techniques [49], [53]. This addresses the inherent inefficiency of indexing ciphertexts as the storage space required for indexing ciphertexts can be reduced. Third (metadata-hiding), this approach aligns well with recent advancements in two-phase PIR [42], [57], where the database is preprocessed using boolean operations. Overall, this indicates compatibility and potential synergy of using one boolean abstraction to achieve all properties in a unified manner.

This paper introduces BIRDB[1], the first seachable and compact encrypted database with metadata protection. At the core of BIRDB is a novel secure and compact index called

[1]BIRDB stands for **B**oolean **I**nformation **R**etrieval based E**DB**.





**Fig. 2:** BIRDB's fundamental concept revolves around leveraging Boolean information to construct a searchable and compact index that incorporates an oblivious PIR protocol.

BINDEX. Unlike previous approaches that employ ORAM-based or cryptographic methods resulting in uncompressible indexes due to random noise introduced during encryption, BINDEX utilizes efficient one-way functions (OWF), such as SHA-256 [40], to transform data into computationally-irreversible ciphertexts within a membership-preserving data structure. The membership information associated with these ciphertexts is then leveraged for searching, while the boolean nature of index nodes allows for compressibility.

Figure 2 illustrates the fundamental concept of BINDEX. In this process, each item undergoes transformation using OWFs to generate *cipher identifiers*. These identifiers are organized within a carefully designed data structure that preserves membership information. Notably, even with knowledge of these identifiers, a computational bounded adversary cannot reverse-engineer the original plaintext because of the inherent guarantees provided by OWFs [40].

To achieve searchability, all cipher identifiers are positioned at the bottom layer of the index, and BINDEX is constructed by recursively combining them into a data structure resembling a Merkle tree. Each inner node in the structure represents the union of its child identifiers. The searchability is facilitated by BINDEX propagating the membership information of identifiers from the bottom layer to the root. This enables efficient top-down binary search by testing the membership of the queried item in each node. This search mechanism resembles the behavior of a BST commonly used in plaintext databases but without the need for numerical comparisons on plaintext values.

A key performance challenge of BINDEX lies in the space efficiency. Specifically, if the identifiers in index nodes are stored uncompressed, the space consumption would theoretically be proportional to the size of the dataset. Moreover, the unique leaf-to-root membership propagation, which enables searching without plaintexts, amplifies the space occupancy even further. This is due to the fact that inner nodes in BINDEX need to maintain the membership information of all child nodes, resulting in an exponentially growing index size.

To address this challenge, BIRDB implements a compact index design that incorporates lossless compression techniques for the top-level index nodes containing a significant amount of membership information from child nodes. Taking inspiration from the recent advancements in the field of linear approximation model [48], [49], [53], BIRDB apply offsets to represent the boolean information of large BINDEX nodes

and employ linear approximation with corrections to map the keys in the input set to their respective positions, resulting in compressed nodes with constant space occupancy. By doing so, the performance penalty arising from the expanded index on ciphertext is significantly reduced, making BIRDB's queries can run at high performance without compromising accuracy or security.

The boolean nature of BINDEX allows for seamless integration with state-of-the-art Private Information Retrieval (PIR) protocols, ensuring efficient metadata security. In practice, BINDEX is constructed and deployed on both an online EDB server and an offline server (e.g., a replica of the EDB). The offline server performs database preprocessing to generate auxiliary hints, which are then leveraged during the online phase to provide efficient responses to user queries with sublinear computation and communication [26], [57]. This integration is seamless because the preprocessing step also relies on boolean operations, typically XOR. The integration between BINDEX and the PIR protocol is mutually beneficial, as the searchable BINDEX accelerates the PIR process, while the PIR protocol ensures metadata hiding for BINDEX.

We implemented BIRDB on CryptDB's codebase [68]. BIRDB's modular architecture allows for the transparent deployment of decoupled index and storage optimizations with reasonable engineering efforts. To evaluate its performance, we compared BIRDB against CryptDB [68], HElibDB [25], and OO-PIR [57], which are two efficient EDBs for oblivious information retrieval, within the same system. We conducted evaluations using a typical workload from previous studies [92]. Evaluation shows that:

• BIRDB demonstrates high efficiency. BIRDB exhibits up to 33.5% lower query latency and 5.1X higher throughput than HElibDB, as well as up to 3.8% lower latency and 2.3X higher throughput than OO-PIR. These performance gains can be attributed to the logarithmic complexity and compactness of BINDEX (§VI).

• BIRDB offers compactness. In terms of storage space, a compressed BINDEX occupies approximately 1018X less space than an uncompressed version while maintaining the same query accuracy (§VI).

Our main contribution is BINDEX, the first high-performance and compact index on ciphertexts. BIRDB makes the first effective attempt to use boolean information for constructing a searchable and compressable index, and seamlessly integrates with state-of-the-art PIR protocol that preprocesses database using boolean operations, in one unified system. BIRDB has potential to be deployed in many safety-critical applications, including privacy-preserving video streaming [67], [88], password manager [36], recommendation [43], [72], and anonymous messaging [45], [71]. BIRDB is open-sourced and its code is released on github.com/ndss24p59/BirDB.

In the rest of this paper: §II introduces background; §III gives an overview of BIRDB; §IV describes BIRDB's design; §V covers BIRDB's security analysis; §VI shows our evaluation; §VII discusses related work and §VIII concludes.

| System | Data Confidentiality | Metadata Security | Sublinear Complexity | Compact Index | General Purpose |
|---|---|---|---|---|---|
| MySQL [60] | ✗ | ✗ | ✓ | ✓ | ✓ |
| CryptDB [68] | ✓ | ✗ | ✓ | ✗ | ✓ |
| HElibDB [25] | ✓ | ✓ | ✗ | ✓ | ✓ |
| Dory [28] | ✓ | ✓ | ✗ | ✗ | ✗ |
| OO-PIR [57] | ✓ | ✓ | ✗ | ✗ | ✓ |
| Titanium [57] | ✓ | ✓ | ✗ | ✗ | ✓ |
| **BIRDB** | ✓ | ✓ | ✓ | ✓ | ✓ |

**TABLE I:** Characterization of representative EDBs.

## II. BACKGROUND

In this section, we aim to highlight the importance of meeting three key properties - *searchability*, *compactness*, and *metadata protection* - in encrypted databases (compared in Table I). Understanding the significance of these properties will provide motivation for our design of BIRDB.

### A. Toward efficient server-side search

In response to growing security concerns about data leakage, enterprises like Keybase [5], PreVeil [6], SpiderOak [2], Sync [3], and Tresorit [4] have emerged, offering encrypted storage services to ensure user data confidentiality. These companies have expressed a need for server-side search functionality on encrypted data, in a way similar to conventional plaintext databases like MySQL [60]. However, none of these companies currently support server-side search, as their development efforts have been hindered by performance or the disclosure of search access patterns.

One straightforward yet inefficient way to enable search on encrypted data is to download the entire database. However, this approach is impractical due to the significant bandwidth consumption and client-side storage resources required. Thus although it provides the highest level of security, no existing industrial solution utilizes this approach.

To enable efficient server-side search on encrypted data, extensive academic research has explored the use of specific cryptographic tools, such as property-preserving encryption, as seen in the case of CryptDB [68]. The core concept behind this approach is to preserve the determinism and maintain the order of encrypted data, thereby allowing for the direct construction of an index (typically a BST [23]) on top of the encrypted data with logarithmic search complexity.

**The need for compacting index.** Despite extensive efforts to achieve efficient search performance, evaluations have shown that the actual performance often falls short of theoretical (i.e., logarithmic) expectations. The primary reason for this discrepancy is that the performance bottleneck does not lie in the binary search itself. Instead, it is the I/O operations to external storage that significantly degrade the overall performance. This is particularly true when dealing with substantial data volumes that cannot be indexed and fit within the limited main memory, compounded by the fact that encryption algorithms typically expand ciphertext size linearly [11], [78].

Therefore, in the context of EDB, achieving high performance necessitates not only sublinear (logarithmic) search complexity but also effective compression techniques. By ensuring sublinear search complexity, the search operations can be executed efficiently, while compression helps mitigate the impact of I/O operations and reduces the storage requirements.

### B. Toward efficient metadata protection

**Private Information Retrieval (PIR).** The initial concept of Private Information Retrieval (PIR) was introduced by Chor et al. [61], allowing clients to retrieve specific objects from an untrusted server-managed database without revealing the accessed object. PIR protocols aim to minimize communication costs, achieving sublinear complexity relative to the database size. Modern PIR deployment models include multi-server PIR [29], [51], [54], [56], where the database is replicated across non-colluding servers for enhanced fault tolerance. Alternatively, single-server PIR protocols [58], [59], [64] are computationally more demanding but avoid non-collusion assumptions through cryptographic hardness assumptions. These advancements provide a range of options for secure and private information retrieval, considering efficiency, security assumptions, and deployment requirements.

Oblivious RAM (ORAM) is a traditional PIR technique known for concealing access patterns during interactions with untrusted servers [65], [76], however, it is not suitable for our setting due to its impractical performance penalty. ORAM protocols achieve access pattern obfuscation through techniques like oblivious data shuffling and path encryption. Researchers have also proposed various ORAM variants like Titanium [24] and Dory [27] to improve performance and scalability while preserving data privacy [20], [39], [70], [74], [75]. However, ORAM-based techniques still suffer from the drawback of processing the entire database with linear computation for every query, resulting in significant performance penalties.

**Two-phase PIR on the boolean information.** Many research efforts have been put on improving the performance of ORAM by introducing preprocessing techniques [17], [26], [73], [90]. Preprocessing involves shifting the inevitable PIR computation to a query-independent offline phase and generating auxiliary data or hints along the way. This approach aims to make the computational cost of online query processing, with the assistance of these hints, sublinear to the database size.

Two recent PIR protocols, namely the Corrigan-Gibbs and Kogan scheme (CK) [26], and the Shi, Aqeel, Chandrasekaran, and Maggs scheme (SACM) [73], operate on the boolean information to enable a two-phase design. Notably, the CK protocol [26] presents a two-server PIR construction that stores $\mathcal{O}(\sqrt{n})$ bits at the client and achieves $\mathcal{O}(\sqrt{n})$ server computation for online queries. The fundamental idea behind CK is the reflexivity of XOR operations. The CK protocol divides the database into random chunks, and the user preserves a preprocessed hint $h = p \oplus s$, where $p$ represents the desired value to be queried and $s$ is obtained by querying a random chunk of the database. Through this approach, the user can ultimately obtain $p = h \oplus s$ using its hint and queried random result, with correctness guaranteed by the reflexivity property (i.e., $p \oplus s \oplus s = p$).

### C. Opportunities

Based on the survey results discussed above, we have identified several opportunities to address the challenge of practical yet secure encrypted search:

• Traditional cryptographic approaches are not capable of simultaneously achieving both searchability and compactness.





**Fig. 3:** BIRDB's architecture for searchable, compact, and metadata-hiding encrypted database built on the two-phase PIR.

Hence, there is a strong need for an alternative approach that offers a more flexible and practical index design, even if it entails sacrificing some degree of confidentiality. This trade-off is crucial to ensure the compactness of the encrypted search system, making it efficient for real-world applications.

• Boolean information has shown significant advancements in efficient metadata protection and holds great potential for implementation in an encrypted search index.

These opportunities serve as the basis for BIRDB's design.

## III. Overview

### A. System model

Same as [27], in BIRDB, the database items are divided into partitions, each managed by a different group of EDB servers. Multiple partitions can exist in a query system, and execution across partitions occurs in parallel.

**Entities.** For a single partition (depicted in Figure 3), we adopt the two-phase PIR model, specifically the CK protocol introduced by Corrigan-Gibbs and Kogan [26]. In our setup, a single partition consists of two servers deployed on the public cloud: an offline server (usually a replica) responsible for database preprocessing to generate runtime hints for PIR, and an online server (master) handling user queries. These servers are *semi-honest*, in the sense that they do not collude but have an interest in learning which objects the client is accessing from the database. Concretely, BIRDB's architecture for a single partition includes the following entities:

• **Users:** Multiple users interact with the BIRDB replica to obtain hints and send search queries (e.g., point lookup) to the BIRDB master for information retrieval. Each user needs to store a *salt*, a randomly generated 128-bit key, used for salting and recovering the original data during offline preprocessing to ensure confidentiality.

• **Master:** The BIRDB master processes user queries by searching BINDEX sublinearly and performing sublinear PIR computations. The master also ensures that the $l$ replicas have a consistent view of the database state, and users know which servers to contact. In line with [27], we employ $l = 2$ in our implementation.

• **Replicas:** The BIRDB replica conducts database preprocessing to generate runtime *hints*, ensuring metadata-hiding during

information retrieval while keeping the computation required on the master sublinear.

Similar to [27], BIRDB does not provide availability if servers refuse to provide services. However, it is important to note that cloud providers are typically incentivized to ensure availability by either bringing the failed server back online or replacing it promptly [27], [47], [85].

**Data model.** To exemplify BIRDB's design, we employ the NoSQL key-value data model for its simplicity. However, it's important to note that BIRDB is highly extensible and can be applied to other data models transparently, including structured relational data models and unstructured key-value pairs. This is made possible by the unclustered architecture on which BIRDB is built, as discussed in [60], which decouples BIRDB's encrypted search index from the underlying storage.

Similar to previous works [57], [68], BIRDB replicates the database $D$ across both the offline and online servers. The database consists of two confidential columns, each containing $n$ keys or values (items). Each item has a size of $b$ bits. Before sending values to the replicas, users encrypt them using their salts to ensure confidentiality during preprocessing. The preprocessed results, also known as hints, can later be recovered by the user using the respective salts. The correctness of this process is guaranteed by the reflexivity property of XOR on boolean operations, as we will explain in §IV.

In line with typical PIR systems [27], [57], the value column in database $D$ is treated as an array, where $D[i]$ represents the $i$-th value in D. The notation $[x, y]$ is used to denote the set of consecutive integers from $x$ to $y$, inclusive. For simplicity, when $x$ = 1, the notation $[y]$ is used to represent the set $\{1, ..., y\}$.

**PIR model** (two-phase PIR [26])**.** BIRDB is built on the two-phase PIR which typically comprises four algorithms (`Prep`, `Query`, `Resp`, `Recov`). These algorithms are defined as follows in the setup of BIRDB over a database $D$ of $n$ items:

• `Prep`$(D) \rightarrow h$: this algorithm is executed by BIRDB replicas for each user. It takes the database $D$ as input and outputs a hint $h$. The hint $h$ consists of three parts: randomly partitioned chunks, filters for chunks, and parities for chunks.

• `Query`$(h, i) \rightarrow q_i$: this algorithm is executed by each user. It takes the hint $h$ and the desired query index $i$ as input and outputs a query $q_i$.

• `Resp`$(D, q_i) \rightarrow r_i$: this algorithm is executed by the BIRDB master. It takes a query $q_i$ from users as input and outputs a response $r_i$.

• `Recov`$(h, r_i) \rightarrow d_i$: this algorithm is executed by each user. It takes as input a hint $h$ from a replica and a response $r_i$ from the master, and outputs the desired data object $d_i$.

These four algorithms work together to enable the metadata-hiding retrieval of specific data objects in BIRDB, ensuring that the access patterns and queried data remain concealed from the untrusted servers.

### B. Threat model

In line with recent cloud-based EDBs [24], [27], [57], [68], we assume semi-honest database servers, in the sense that these servers do not collude but are interested in learning the plaintext data and the accessed items. Adversaries, denoted as $\mathcal{A}$, can include database administrators and privileged insiders who can perform passive attacks such as cipher analysis [19] and dictionary attack [21] to extract plaintext information. We rely on the security of one-way functions (OWFs) like SHA-256 [40], assuming that $\mathcal{A}$ is computationally incapable of reversing OWFs or compromising cryptographic encryption keys. These assumptions form the foundation for ensuring the confidentiality of both the data and metadata in BIRDB's encrypted data during encrypted search.

We assume that users are always honest and do not engage in collusion with any servers. While access control mechanisms [62] and blacklists [82] can be used to prevent corrupted clients, we do not consider them within the scope of this work. Additionally, similar to prior research [27], we assume that the underlying storage engine is maliciously secure. This ensures that servers can retrieve the correct data from the underlying storage by detecting rollback and fork attacks, which have been extensively studied in previous storage works [22], [79], [50].

**Out-of-scope attacks.** We make the assumption that servers do not engage in active attacks such as modifying, dropping, or replaying queries, and that they adhere to BIRDB's protocol. Mitigations exist to authenticate queries and ensure query integrity on plaintext data under active attacks, but addressing integrity under active attacks on encrypted data remains an open problem that we leave for future work [87], [94]. Furthermore, we assume a fixed size for items, which eliminates size leakage. It is challenging to prevent size leakage efficiently without extensive padding to the largest file size (which is costly) or relying on trusted hardware (which requires trust in a third-party vendor). However, mitigations such as partial padding and delayed accessing, where different file chunks are downloaded at different times, can be employed [63], [81].

**BIRDB's guarantees.** BIRDB's confidentiality guarantee ensures that all index keys are irreversible, in the sense that if $\mathcal{A}$ is a computationally bounded adversary, $\mathcal{A}$ is infeasible to reverse the encrypted index keys and retrieve the original records in plaintext. These guarantees are facilitated by BIRDB's index, which effectively achieves high-performance encrypted search with logarithmic complexity and compactness. Formally, we have the following theorem (proved in §V) that captures BIRDB's security:

**Theorem 1.** *Given that the one-way functions (OWFs) used in index construction is mathematically irreversible, and assuming that the $\epsilon$-approximate linear models and the two-phase PIR scheme of Corrigan-Gibbs and Kogan [26] are secure against passive attacks, the* BIRDB *encrypted database is secure in the presence of a computationally bounded adversary.*

### C. System goals and approaches

At a high level, our goal is to achieve searchability, compactness, and metadata protection for encrypted search, while maintaining the confidentiality of both data and metadata. To accomplish this, our key weapon is a new boolean information retrieval (BIR) technique that allows us to achieve all of these objectives simultaneously. Below, we provide a brief overview of the approaches to achieve these desirable features in EDBs.





**Fig. 4:** BIRDB employs boolean information for logarithmic encrypted search by testing membership in index branches and finally comparing every bit at leaf nodes.

**Goal 1: Logarithmic encrypted search.** Enabling search functionality on encrypted data is crucial for efficient retrieval of specific items without the requirement of decrypting the entire dataset. To address this challenge, our key idea is to replace conventional numerical comparison operations at index branches with secure boolean membership tests. By incorporating secure boolean information into an orchestrated searchable data structure, we can enable encrypted searches with a logarithmic time complexity.

Figure 4 exemplifies our encrypted search method named BINDEX. This approach involves converting database items into boolean information using cryptographic one-way functions (OWFs), such as SHA-256. Drawing inspiration from the Bloom Filter [14], BINDEX employs a membership-preserving data structure to maintain the membership of the OWF-transformed items, which are represented as binary strings (e.g., '⋆' is represented as '1100'). These binary strings serve as leaf nodes positioned at the lowest index layer, while the inner nodes at higher levels are the *unions* of their child nodes. Each inner node performs an *OR* gate computation on the boolean entries of its child nodes to generate its own boolean information. To search for a specific item, BINDEX compares the '1' bits of the item at each index branch, starting from the root, to ensure a match for every '1' bit. At the leaf node, BINDEX compares each entry, including '0' bits, to ensure an exact match with the queried item.

**Goal 2: Compact index with constant overhead.** Although achieving logarithmic search complexity (**Goal 1**) is important, it is not sufficient to ensure high performance. This is because as the inner node size of BINDEX grows exponentially when reaching the index root, it becomes challenging to store a large number of index nodes in primary storage. As a result, more nodes are shifted to the secondary storage, which incurs costly I/O operations and hampers performance.





**Fig. 5:** Based on the boolean information, BIRDB compacts giant index nodes to optimize I/O efficiency and achieve high performance.





**Fig. 6:** The third goal of metadata-hiding in BIRDB is achieved through the utilization of two-phase PIR. BINDEX, which accomplishes **Goals 1 and 2**, accelerates the PIR process, while PIR ensures the metadata confidentiality of BINDEX.

Figure 5 illustrates our approach to compact BINDEX and achieve constant query time and space occupancy. The core idea is that BINDEX's membership information only needs to store the positions of the '1' bits, while the numerous '0' bits are left irrelevant. Taking inspiration from the recent new family of linear approximation model [48], [49], [53], we propose to use *offsets* to represent the boolean information (specifically, the positions of '1' bits). We then compact these offsets using piece-wise linear functions that map the position in the array to the corresponding offset [34]. For instance, we can utilize two linear functions, defined by only two slopes and intercepts, to represent the offset array belonging to a BINDEX node in Figure 5. Consequently, the implementation of this compacted structure requires constant time and space, regardless of the total number of stored items.

**Goal 3: End-to-end metadata protection.** To effectively conceal metadata and eliminate the leakage of search access patterns, we implement BIRDB using the CK protocol introduced by Corrigan-Gibbs and Kogan [26]. The CK protocol is a cutting-edge two-phase PIR protocol that offloads query-independent computations to a preprocessing phase, resulting in sublinear computation for online queries.

Figure 6 demonstrates the integration with two-phase PIR discussed in §III-B. Specifically, the process consists of a preprocessing phase and a query phase. During the preprocessing phase, the BIRDB replica divides the database into random chunks. For each chunk of keys, it computes the parity of the corresponding values and builds filters for each chunk (❶). In the query phase, the user searches for their desired query item by testing its membership in each chunk's filter. Once the target chunk is found, the user deletes the intended query item (❷). The BIRDB master then searches the database using BINDEX based on the query items and computes the parity of the searched values (❸ and ❹). Finally, the user recovers the result by XORing the returned parity with the parity of the original chunk (❺). The correctness of this process is ensured by the reflexivity of XOR on boolean operations; BIRDB accelerates the PIR process using BINDEX (§IV-C).

Overall, by utilizing one core concept of boolean information retrieval, we construct a search index with logarithmic complexity using OWFs. Furthermore, we compact the index by employing linear approximation techniques. Finally, we ensure the concealment of search metadata by leveraging the

reflexivity of XOR on boolean operations. Hence, we address all three essential properties: searchability, compactness, and metadata-hiding, in a unified manner.

## IV. Protocol Description

### A. Desiging an encrypted search index

We first establish the foundation for constructing BIRDB's encrypted search index and subsequently delve into the details of index construction and search methods.

**Preliminaries**. The underlying searchable data structure in BIRDB is based on the Bloom filter [14], a compact data structure designed for efficient membership testing. The Bloom filter operates by utilizing a single set to store the hash values of all items. Specifically, a Bloom filter $B$ is represented by an $m$-bit array and employs $k$ independent and uniformly distributed OWFs, i.e., cryptographic hash functions $\{H_k\}$. Each hash function maps an item to an index in the Bloom filter array. To insert an item $x$ into the filter, we compute its hash using $\{H_k\}$ and set all the bits at the corresponding indices in $B$ to 1. For testing whether an item $y$ is a member of the set, we again hash $y$ using $\{H_k\}$. If any of the bits at the corresponding indices in $B$ are 0, then $y$ is definitely not in the set (i.e., zero false negatives). Conversely, if all the bits at the corresponding indices in $B$ are 1, $y$ is considered to have a high probability of being in the set, albeit with a small configurable false positive rate [14].

**Challenges and opportunities**. As mentioned above, traditional Bloom filters offer valuable information regarding the *membership* of data for tests. In addition to this, we have observed two key characteristics of Bloom filters that make them promising for encrypted search applications. Firstly, a Bloom filter is *monolithic* in nature, meaning that all items are assigned to a single boolean set. This characteristic allows for efficient item membership tests related to data existence. Secondly, a Bloom filter ensures data *confidentiality* by utilizing one-way functions (OWFs) to transform original plaintexts into hash values of items. The use of OWFs makes the Bloom filter computationally irreversible, effectively hiding the original plaintexts. This security property relies on the assumption of the one-wayness of cryptographic hash functions, which has been extensively studied in prior research [14].

However, despite the valuable membership property and data confidentiality offered by a Bloom filter, the monolithic nature limits its functionality to supporting only membership tests by indicating whether an item (hash) is present in a set. Consequently, Bloom filters alone are not capable of functioning as an index for efficiently searching encrypted data. We observe two significant benefits of using Bloom filters for encrypted search:

• **Security for indexing**. In encrypted search, users do not require the encrypted index keys to be decryptable, as they are used solely for searching corresponding values. Therefore, the utilization of one-way functions (OWFs) to efficiently transform plaintexts into computationally irreversible ciphertexts is sufficient. OWFs provide the necessary security for the index keys without the need for decryption.

• **Compactness**. The boolean nature of Bloom filters allows for the application of cutting-edge compression techniques specifically designed for boolean data. Leveraging these techniques can lead to significant compression gains in the encrypted search index. This is particularly advantageous as traditional encrypted search indexes, such as Order-Preserving Encryption (OPE)-based indexes, are not easily compressible [68], [27]. By reducing the index size through compression, the encrypted search system can benefit from improved performance by avoiding the drawbacks associated with large index sizes and potential performance penalties. We introduce the details of BIRDB compression in §IV-B.

**Algorithm 1:** Minifilter-based encrypted search

```
1  Function PointSearch(root, key) do
2      if isLeaf(root) then
           ▽ Every corresponding bit should match
3          if key.rft = root.rft        ▷ Minifilter comparison
4           then
5              return root
       ▽ In inner nodes, every '1' bit should match
6      if isInner(root) then
7          if left_minifilter.contain(key) then
8              return PointSearch(root.left, key)
9          if right_minifilter.contain(key) then
10             return PointSearch(root.right, key)
11         return NULL                  ▷ Key is non-existent
12 Function RangeSearch(root, [key1, key2]) do
13     left ← PointSearch(root, key1)
14     right ← PointSearch(root, key2)
15     while left.next != right do
16         value[] ← left.next      ▷ Retrieve sorted leaf nodes
17     return value
```

**Approach.** To construct the encrypted search index, we modify the traditional monolithic Bloom filter by decomposing it into a collection of *minifilters*. Each minifilter is responsible for storing the hash (in bits) of a single item. In other words, a mini-filter represents a Bloom filter dedicated to an individual data item, where only one item (hash) is assigned to the set.

The minifilters are recursively organized to form a searchable index known as BINDEX. These minifilters have a fixed array size $m$, and are arranged in a Merkle-tree structure. Each minifilter is stored at a leaf node of the tree, representing an index key. The index keys, such as `"1100"` for record '⋆' in Figure 4, are sorted based on their plaintext key order. The values of the inner nodes, which include all nodes except the leaf nodes, are determined through an element-wise $OR$ gate computation on the minifilters of their child nodes. Let's consider an inner node with $l$ child nodes, denoted as $Cn$. For each bit (array entry) in the minifilter of the inner node, its value is computed as follows: $Sub_{in}[i] = Cn_1[i]$ *or ... or* $Cn_l[i]$ , for all i in the range $[0, m]$. Note that, in the construction of BINDEX, only the leaf nodes in the minifilter tree store actual values, such as record addresses. The inner nodes serve the primary purpose of indexing, facilitating tree traversal for efficient search operations.

**Design rationale.** The searchability of BINDEX is achieved through the membership-preserving property of the minifilters. Specifically, when any entry in a child node's minifilter is set to `"1"`, the $OR$ gate computation guarantees that the corresponding entry in its parent node's minifilter will also contain a `"1"` bit. For example, in Figure 4, the first entry of the minifilter for '⋆' is `"1"` while the first entry of the minifilter for '♣' is `"0"`. As a result, the first entry of their parent node's minifilter is computed as $1\ OR\ 0 = 1$.





**Fig. 7:** The construction and a running example that show our compact design for BINDEX. **Step 1** extracts an original BINDEX node into offset representation wherein the $i$th entry is the position of the $i$th '1' bit. In **Step 2**, we uses the Piece-wise Linear Approximation model [34] to compact and search the extracted offset array.

The BINDEX design ensures that if an item exists in a minifilter node, it must also exist in its parent node. In other words, the membership information is propagated to higher-level index nodes. This novel observation, utilized by BINDEX, allows for efficient top-down logarithmic tree traversal based on the membership information. Furthermore, the irreversible confidentiality provided by OWFs directly carries over to the construction of minifilters. By testing the membership of query items in the minifilter nodes, BINDEX eliminates the need for plaintext comparisons typically found in traditional binary search trees (BSTs).

**Using BINDEX for encrypted searches.** Algorithm 1 outlines the process of an encrypted point query through BINDEX, which involves generating a minifilter for the query item and traversing BINDEX to locate the corresponding value. BIRDB performs minifilter comparisons at each inner node to verify the membership of each `"1"` bit in the query item's minifilter. The traversal continues until reaching the leaf nodes, where the match of every bit confirms the presence of a unique index key.

The point search method can be extended to handle range queries. By transforming the range boundaries into minifilters, BINDEX locates two matched leaf nodes using the same method as point queries. All values between these leaf nodes are then returned, akin to the retrieval process in a B$^+$-tree.

### *B. Compacting* BINDEX *for efficient encrypted search*

**A core index challenge: size and cost.** Despite BINDEX's efficient tree-based index structure, which facilitates logarithmic search complexity, achieving a low search complexity alone is insufficient for achieving high-performance encrypted search. The reason is two fold. Firstly, as the total number of items increases, each BINDEX node experiences exponential growth in membership information storage due to the membership propagation design (§IV-A). Consequently, the index size significantly expands, adversely affecting search efficiency. Secondly, even in a static setting, the false positive issue, attributed to the fundamental nature of Bloom filters, further amplifies the size of each minifilter node.

To illustrate, let's consider a database with $2^{20}$ static items and the user aims for a low false positive rate of $1 \times 10^{-3}$, same as the configuration in [86], each minifilter in BINDEX would need to be approximately 1.79MB in size using the formula in Bloom filter theory [14]. Consequently, the entire BINDEX would require a substantial amount of storage space, around 3.57TB, which is unaffordable. The significant increase in space occupancy compared to a plaintext database index results in a notable performance decline due to expensive I/O operations involving secondary storage such as disks.

**Algorithm 2:** Encrypted search on a compressed minifilter

**Input parameter:**
  $A$ ▷ Sorted offset array of a minifilter node
  $\epsilon$ ▷ Error bound of PGM (typically $\epsilon = 1$)
  $levels$ ▷ Level of compacted BINDEX
  $k$ ▷ The query item for search
**Function** `Query`$(k, A, \epsilon, levels)$ **do**
  $pos \leftarrow f_r(k), where\ r \leftarrow levels[0][0]$
  **while** $i \leq size(levels)$ **do**
    $lo \leftarrow max\{pos - \epsilon, 0\}$
    $hi \leftarrow min\{pos + \epsilon, size(levels)\}$
    $s \leftarrow []$
    **while** $s' \in levels[i][lo, hi]$ **do**
      **if** $s'.key \leq k$ **then**
        $s \leftarrow s'$
    $t \leftarrow right\ most\ segment\ of\ s$
    $pos \leftarrow \lfloor min\{f_s(k), f_t(t.key)\}\rfloor$
  $lo \leftarrow max\{pos - \epsilon, 0\}$
  $hi \leftarrow min\{pos + \epsilon, size(A)\}$
  $return\ binary\ search\ for\ k\ in\ A[lo, hi]$

Facing this challenge, our contention is that relying solely on achieving theoretical logarithmic search complexity is insufficient for achieving high-performance encrypted search, even though it represents a significant improvement over linear search methods [25], [28]. Instead, an encrypted search index should adopt a compact design to ensure that the overall query performance remains manageable and cost-effective.

**The compact design.** As depicted in Figure 7, during index construction, BINDEX preserves light index nodes and compacts giant index nodes that exceed a user-defined memory budget $B$ using two steps below.

• **Step 1 (From bits to offsets).** Recall that in BINDEX, each index node (i.e., minifilter) is represented as a one-item Bloom filter (§IV-A), which is a bit array consisting of only '0' and '1' bits. However, only the '1' bits contain informative data since membership tests only involve checking if all '1' bits are present in a filter. Thus in **step 1**, we extract the positions of all '1' bits from the filter, creating a new offset array. This extraction process allows us to discard unnecessary bits and avoid wasting primary storage resources.

• **Step 2 (Linear Approximation using PGM [34]).** Although **step 1** reduces the size of giant BINDEX nodes, the size still increases exponentially with the total number of records $n$. Fortunately, we find that the cutting-edge compression technique known as Piece-wise Linear Approximation, particularly the PGM [34], is highly suitable for further compressing the extracted offset array in our specific setting.

Specifically, the PGM is a data structure that addresses the linear approximation problem in a multiset of sorted keys within an array $A$, drawn from a universe $U$. PGM is parametric with an integer $\epsilon$ and employs piece-wise linear approximation models to learn a mapping that returns a position for a given key $k \in U$, which is within $\epsilon$ distance from the

correct position in $A$. The fundamental concept behind PGM is that a single linear model, or *segment*, may not be sufficient to $\epsilon$-approximate the positions of all keys in $U$. Therefore, PGM employs a sequence of segments, each requiring constant space (two floats and one key) and constant query time to provide the $\epsilon$-approximate position of $k$ in $A$. To construct each segment, PGM reduces the piece-wise linear $\epsilon$-approximation problem to constructing the convex hull of a set of points using a streaming algorithm. This algorithm operates in linear time and space, generating the minimum number of $\epsilon$-approximate segments. We refer to [38], [55], [69] for more on the convex algorithm.

Once the prepared segments, such as the two linear functions shown in Figure 5, are available, the next step is to identify the $\epsilon$-approximate segment responsible for estimating the approximate position of a query item. To achieve this, PGM begins with the sequence constructed over the entire input array $A$. It then extracts the first key (indicated by red keys in Figure 7) from $A$ that falls within the coverage of each segment. Subsequently, another linear model is constructed using this reduced set of keys. This recursive process continues until convergence to a single segment. Following the recursive construction, the $\epsilon$-approximate positions returned by the segments can be converted into exact positions through a binary search within a range of $\pm\epsilon$ keys in $A$. This binary search operation has a time complexity logarithmic to $\epsilon$, regardless of the total number of records in BINDEX's offset array.

**Running example.** Figure 7 provides a running example of searching a compressed BINDEX node using Algorithm 2. Each accessed node in the search path is highlighted in blue. We assume the compressed BINDEX has an error bound $\epsilon = 1$ and the key being searched is $k = 83$.

The search begins from the root segment $s' = l_0[0][0]$. The next position, $\lfloor fs'(k) \rfloor = \lfloor k * sl_0 + ic_0 \rfloor$, is computed to be 1 for the next level. The search then proceeds to locate $k$ within the range $[1-\epsilon, 1+\epsilon]$ in $l_1$, considering the keys [2, 29, 72]. It is determined that the next segment for the search is $s'' = l_1[2]$ because $k > 72$. Finally, the position for the next (leaf) level, $l_2$, which represents the extracted offset array, is computed by evaluating $\lfloor fs''(k) \rfloor = 8$. Consequently, a binary search is performed to search for $k$ within the range $[8-\epsilon, 8+\epsilon]$ in $l2$. Ultimately, it is found that $k$ is located at position 9 since $A[9]$ = 83.

In the compacted BINDEX, Algorithm 2 functions as the internal search mechanism for `minifilter.contain(`$k$`)` in Algorithm 1. Combined, they constitute the complete end-to-end encrypted search algorithm of BIRDB.

### C. Seamless integrating BINDEX with PIR

Our metadata-hiding solution builds on the two-phase PIR scheme of Corrigan-Gibbs and Kogan [26]. We start by describing the CK protocol and then we decribe our approach to seamlessly integrate BINDEX with it.

**Overview of the CK protocol.** As described in §II-B, the CK protocol comprises two phases: an offline preprocessing phase conducted on BIRDB's replica, and an online query processing phase involving BIRDB's master. The offline preprocessing phase is independent of the specific item that the user wants to query and involves the `Prep` step. This phase is performed on BIRDB's replica and includes the necessary preparations for the PIR search process. In the online query processing phase, which depends on the specific item being queried, the interactions occur between BIRDB's master (who has no knowledge of the preprocessed hints generated by the replica) and the user. This phase consists of the `Query`, `Resp`, and `Recov` steps, where the user submits the query, the master provides the corresponding response, and the necessary recovery actions are taken.

- `Prep(`$D$`)` $\rightarrow h$. The replica divides all index keys of the database items into $\sqrt{n}\log n$ independent random sets, denoted as $S_1$, ..., $S_{\sqrt{n}\log n}$, where each set contains $\sqrt{n}$ keys sampled uniformly at random. For each set $S_i$, the replica computes its parity, $P_i$, where $p_i = \oplus_{t \in S_i} D[t]$ for $i \in [1, \sqrt{n}\log n]$. Each parity is uniformly padded to $b$ bits. In short, a parity $p_i$ for set $s_i$ is the XOR of all items in D referenced by the keys in $S_i$. The replica sends the hint $h = \{(S_1, P_1), ..., (S_{\sqrt{n}\log n}, P_{\sqrt{n}\log n})\}$ to the user.

- `Query(`$h$`,`$i$`)` $\rightarrow q_i$. The user generates a query for retrieving an item with index key $i$ (i.e., D[i]). The user selects a set $S$ from the hint $h$ such that $i \in S$ (the corresponding parity is $P_S$). The user then removes $i$ from set $S$ with a high probability (i.e., $1 - \frac{\sqrt{n}-1}{n}$); otherwise, it removes a randomly chosen key from $S \backslash \{i\}$. The query $q_i$ is transformed to the resulting set $S^*$, which has a size of $\sqrt{n} - 1$. The user sends $q_i$ to the master.

- `Resp(`$D$`,`$q_i$`)` $\rightarrow r_i$. The master computes the PIR, $r_i = \oplus_{t \in S^*} D[t]$, where $S^*$ is the query set received from the user. The master sends $r_i$ back to the user.

- `Recov(`$h$`,`$r_i$`)` $\rightarrow d_i$. Using the parity $P_S$ obtained during the `Query` step, the user recovers the real desired query item $D[i]$ by computing $d_i = P_S \oplus r_i$.

To ensure security against a semi-honest online server, the CK protocol incorporates a cheap *refresh* operation after each query. This operation involves the user generating a new set with $\sqrt{n}-1$ new random keys and obtaining the corresponding parity $P_{new}$ from the replica. The user then adds the previously queried key $k$ to the new set and updates the parity by XORing the key's parity with $P_{new}$. This refresh operation prevents the server from deducing search access patterns by comparing sets in multiple queries.

**Accelerating PIR with BINDEX.** The PIR process in the CK protocol effectively conceals search metadata and safeguards user privacy from a semi-honest server. However, a significant drawback is that the CK protocol requires linear time complexity during the membership test (i.e., the `Query` step) and database search step (i.e., the `Resp`) step.

We observe that the core principle of the CK protocol, which leverages the reflexivity of XOR operations on boolean information, can be seamlessly incorporated into BIRDB due to their shared basis in boolean information retrieval. By leveraging this common concept, we can construct efficient (logarithmic complexity and compact) encrypted search indexes on the keys, facilitating rapid membership tests and database searches; further, we can employ the CK protocol to the values, enabling the PIR process to conceal search metadata. In this way, BIRDB simutaneously enables high-performance and metadata-hiding encrypted search in a unified

manner.

The end-to-end query workflow operates in the following manner. After constructing the BINDEX on the user's side, the user submits the chosen OWFs and salted values using $b$-bit one-time pads (same as the parity) to the BIRDB replica. These OWFs are then used by the replica to construct Bloom filters for each random subset during the `Prep` step; those salted values can later be recovered by the user in the `Recov` step by XORing the corresponding salts owing to the reflexivity property. By doing so, we facilitate efficient membership tests in the subsequent `Query` step, allowing users to quickly determine whether a key is present in a set or not with a complexity of $\mathcal{O}(1)$. In the `Resp` step, the BIRDB master employs the compacted BINDEX to search and retrieve items (Algorithm 1 and Algorithm 2). This operation has a logarithmic time complexity and ensures compactness to reduce I/O costs. Subsequently, the user locally recovers the results and obtains the desired item.

## V. PERFORMANCE AND SECURITY ANALYSIS

### A. Proof Sketch of Security

BIRDB's security is established through two key lemmas: **Lemma 1** demonstrates the impossibility for an adversary $\mathcal{A}$ to access plaintexts, while **Lemma 2** proves $\mathcal{A}$'s inability to detect the metadata of the specific item being searched. These lemmas collectively form the proof for **Theorem 1**, affirming BIRDB's security.

**Lemma 1** (data confidentiality)**.** Given an item with its key (minifilter) $mf$, value $v$, and a set of cryptographic hash functions $H$, it is infeasible for both the BIRDB master and replica to find any input $x$ such that $H(x) = mf$ and reverse the mapping to obtain $v$.

***Proof.*** We prove this lemma from three perspectives. Firstly, the key (minifilter), as defined in §IV-A, guarantees the irreversibility of plaintext. This is achieved through the use of one-way functions (OWFs) [14], [27] (i.e., $H$), which provide one-wayness, making it computationally infeasible for any adversary to reverse the transformation of OWF-encoded data. Additionally, $v$ is obfuscated through a one-time pad that is known only to the client, ensuring its irreversibility (§IV-C).

For the second aspect regarding the semi-honest master and replica, the security against the replica is ensured by its lack of knowledge regarding the specific items being queried. The replica remains unaware of the queried items, safeguarding the confidentiality of the search process (§IV-C). Thirdly, security against the master relies on two crucial factors. Firstly, the user's queried subset is uniformly random and remains unknown to the master. This prevents the master from obtaining any information about the user's specific query. Secondly, it is assumed that the two servers involved in the process do not collude (§III-B). By combining these properties, neither the master nor the replica can discover any input $x$ satisfying $H(x) = rf$ and successfully reverse the plaintext of $v$.

**Lemma 2** (metadata confidentiality)**.** Assuming the semi-honest behavior of the master and replica, and their non-collusion, BIRDB ensures complete concealment of specific items that a user fetches.

***Proof.*** **Lemma 2** directly follows from the implementation of the underlying CK protocol within the two-server Private Information Retrieval (PIR) setting [26].

### B. High performance

**Vanilla BINDEX.** In the original uncompressed version of BINDEX, we can achieve a time complexity of $\mathcal{O}(\log N)$ for encrypted search. The inner comparison of minifilter nodes takes $\mathcal{O}(\log N)$ time, where $N$ is the total number of records. The leaf node comparison takes $\mathcal{O}(m)$ time, where $m$ is the bit length of the minifilters. Therefore, the overall time complexity is $\mathcal{O}(\log n)$+$\mathcal{O}(m)$. Since $m \ll n$, the actual time complexity of the uncompressed BINDEX is $\mathcal{O}(\log n)$.

**Compressed BINDEX.** For the compact version of BINDEX, the average-case time complexity worsens to $\mathcal{O}(\log^2 N)$. This is because the original BINDEX directly computes the positions using OWFs, achieving $\mathcal{O}(1)$ time complexity for each minifilter testing. However, in the compressed version of BINDEX, each minifilter requires a logarithmic search among the segments (or linear models), resulting in $\mathcal{O}(\log n)$ time complexity for each minifilter node's membership test. Hence, the overall time complexity for the compacted BINDEX is $\mathcal{O}(\log^2 N)$.

## VI. EVALUATION

**Testbed.** The experiments were conducted on a cluster of lab machines, each featuring a 2.60GHz Intel E5-2690 V3 CPU, 64GB memory, 40Gbps NIC, and 24 cores. All nodes, including users, master, and the replica, were executed within Docker containers. The average ping latency between the nodes was set at 0.17ms with the aid of Linux traffic control [13].

**Baseline.** We utilized WiredTiger [44], a prominent NoSQL Key-Value storage engine, to implement all of our baseline systems. WiredTiger is widely employed in industrial MongoDB deployments, making it an appropriate default choice. Our comparative analysis involved three state-of-the-art baseline approaches: HElibDB [25], an imperative oblivious database developed by IBM, which employs Fermat's Little Theorem for comparison on homomorphic encrypted data. However, each query in HElibDB necessitates processing the entire database for metadata protection. We also incorporated the CK [26] two-server OO-PIR protocol, known for its exceptional performance. The CK protocol moves query-independent computation to an offline preprocessing phase. Lastly, we assessed a version of BIRDB without compression, denoted as UC-BIRDB in subsequent evaluations. Although UC-BIRDB maintains logarithmic search complexity through our implementation of a boolean information-based index structure (§IV-A), it exhibits a significantly larger size due to lack of compression.

**Workload and default setting.** We adopted the same NoSQL key-value workload as CK OO-PIR. This involved generating a range of keys and values with fixed sizes, specifically ranging from $2^{10}$ to $2^{20}$. The key size was set at 8 bytes, while the value size was set at 64 bytes. Unless specified for the scalability study, our evaluations were conducted on a default dataset of $2^{20}$ key-value pairs. We used point lookup queries for experiments. Each experiment was executed for a duration of 60 seconds, and the results were collected during

| BIRDB's results (in milliseconds) | | | | | | |
|---|---|---|---|---|---|---|
| **EDB size (# = $2^x$)** | **10** | **12** | **14** | **16** | **18** | **20** |
| **P0: Prep** (Replica) | 0.23 | 0.38 | 0.6 | 0.69 | 1.07 | 1.41 |
| **P1: Query** (User) | 0.12 | 0.81 | 1.26 | 2.87 | 3.47 | 4.6 |
| **P2: Refresh** (User & Replica) | 0.84 | 1.36 | 1.55 | 2.29 | 3.91 | 5.44 |
| **P3: Response** (Master) | 0.17 | 0.22 | 0.51 | 0.86 | 1.12 | 1.65 |
| **P4: Recover** (User) | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 |
| **End-to-end** ($\sum_1^4 P_i$) | 1.17 | 2.43 | 3.36 | 6.06 | 8.54 | 11.74 |

**TABLE II:** End-to-end latency breakdown of BIRDB.

| OO-PIR's results (in milliseconds) | | | | | | |
|---|---|---|---|---|---|---|
| **EDB size (# = $2^x$)** | **10** | **12** | **14** | **16** | **18** | **20** |
| **P0: Prep** (Replica) | 0.11 | 0.27 | 0.49 | 0.56 | 0.89 | 1.3 |
| **P1: Query** (User) | 2.5 | 2.41 | 3.93 | 4.87 | 6.54 | 7.81 |
| **P2: Refresh** (User & Replica) | 0.82 | 1.35 | 1.51 | 2.23 | 3.8 | 5.34 |
| **P3: Response** (Master) | 1.45 | 2.81 | 3.48 | 4.64 | 5.31 | 6.25 |
| **P4: Recover** (User) | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 |
| **End-to-end** ($\sum_1^4 P_i$) | 4.81 | 6.61 | 8.96 | 11.78 | 15.69 | 19.45 |

**TABLE III:** End-to-end latency breakdown of CK's OO-PIR.

the middle 30 seconds (i.e., 15s to 45s) to mitigate any potential disturbances caused by system start-up or cool-down. Our extensive evaluation focused on addressing the following research questions:

- How efficient is BIRDB compared to baselines?
- What is the communication cost of BIRDB?
- Can BIRDB scale efficiently?
- How sensitive is BIRDB to compression error bound?

### A. End-to-end Performance

We evaluated the end-to-end query performance of BIRDB and baselines. We measured latency as the user-perceived response time, while throughput was quantified at the server side (specifically, the BIRDB master). The results, as illustrated in Figure 8, demonstrated that BIRDB exhibited a mean latency that was 5.29 times lower than that of HElibDB. This notable difference can be attributed to BIRDB's new encrypted search approach of BINDEX, which enables logarithmic search complexity. In contrast, HElibDB necessitates linear scans to search for equivalent encrypted data, resulting in significantly longer latency for database queries.

Furthermore, BIRDB achieved a mean latency that was 1.57 times lower than that of OO-PIR. This performance advantage can be attributed to two key factors. Firstly, BIRDB employs Bloom filters during the `Query` step, resulting in a time complexity of $\mathcal{O}(1)$ for membership tests (§IV-C). In contrast, OO-PIR requires $\mathcal{O}(n)$ linear scans of the entire database items. Although this moderately increases BIRDB's communication costs (as shown in Figure 9), it allows BIRDB to achieve higher efficiency along the performance-critical path of the database. Secondly, in the `Response` step, BIRDB's BINDEX reduces the search complexity of OO-PIR from $\mathcal{O}(n)$ to $\mathcal{O}(\log n)$, further contributing to its superior performance.

In terms of query throughput, BIRDB achieved up to 45 times higher throughput than baselines. Furthermore, BIRDB achieved a 1.17 times higher throughput than UC-BIRDB, primarily due to its significantly reduced storage consumption and fewer costly I/O operations to secondary storage. This empirical result aligns with our theoretical evaluation (§III-C),






**Fig. 8:** Throughput and latency comparison among different metadata-hiding baselines, each equipped with $2^{20}$ items.




(a) Scalability on datasets (b) Communication costs

**Fig. 9:** (a) Scalability evaluation with varying dataset sizes on all metadata-hiding baselines. (b) Online communication costs for CK OO-PIR, BIRDB, and uncompressed BIRDB.

which suggests that achieving both low search complexity and compact indexing is essential for achieving high performance in the encrypted search domain.

**Breakdown.** To gain insights into the low latency and moderate overhead of BIRDB, we meticulously recorded the time required for each step of the query workflows in BIRDB and OO-PIR. The breakdown of these timings can be found in Table II for BIRDB and Table III for OO-PIR.

The latency of both BIRDB and OO-PIR increases as the size of the database grows. However, BIRDB incurs additional preprocessing overhead due to the construction of filters using OWF computations. Fortunately, this overhead is not on the critical path. For both BIRDB and OO-PIR, the online query process consists of two parts: querying an item to the online server and simultaneously refreshing the used set to the offline server. The logic applied by both servers is identical, involving a sublinear number of XOR operations relative to the database size, resulting in low costs. In the refresh step, BIRDB incurs slightly higher latency than OO-PIR due to the reconstruction of filters to achieve $\mathcal{O}(1)$ complexity in the `Query` step. The `Query` and `Response` steps are two additional time-consuming stages in the overall encrypted search process, and BIRDB significantly reduces the associated overhead compared to OO-PIR. This reduction is the primary reason for BIRDB's higher performance.

In summary, BIRDB outperformed all baseline approaches with up to 5.29 times lower latency and up to 45 times higher throughput. It achieved these improvements while maintaining metadata-hiding capabilities, same as all baselines. The communication costs of BIRDB were moderately higher (around 1.65 times) compared to the most efficient baseline (OO-PIR). However, considering the gains in latency and throughput, these increased communication costs were deemed acceptable. Additionally, we observed that achieving both low search





**Fig. 10:** Sensitivity analysis of compressing BIRDB using different PGM error bounds $\epsilon$.

complexity and compact indexing is crucial for achieving high performance in the encrypted search domain. While this concept is commonly practiced in industrial database development, to the best of our knowledge, we are the first to propose and validate it in the context of security.

### B. Scalability

**Scale to larger datasets**. We conducted evaluations of the baselines using key-value datasets of varying sizes, ranging from $2^{10}$ to $2^{20}$. Figure 9(a) depicts the latency scaling of BIRDB, which exhibits a logarithmic pattern consistent with our complexity analysis discussed in §V-B. As the dataset size increases, both BIRDB and OO-PIR experienced a moderate increase in latency. In contrast, HElibDB demonstrated significantly higher latency, attributable to its requirement to perform linear scans of the entire dataset. In contrast, BIRDB and OO-PIR leverage offline preprocessing to move query-independent computation, as evidenced in Table II and Table III. Furthermore, BIRDB exhibited lower latency compared to UC-BIRDB, confirming the enhanced performance achieved by the compressed encrypted search index, as demonstrated in the end-to-end evaluation presented in Figure 8.

### C. Sensitivity

**Larger error bound, higher cost.** We conducted evaluations to assess the sensitivity of compacting BINDEX with different error bounds (i.e., $\epsilon$). Figure 7 illustrates that as the error bound increases, the size of the index decreases significantly and eventually converges, while the mean search (point lookup) time increases. This behavior can be attributed to the fact that a larger error bound results in fewer segments (linear models) being used to index the offsets derived from the original BINDEX's boolean information (§IV-B). Consequently, more entries in the final leaf layer require a binary search. This explains the reduced index size associated with a larger error bound due to the application of fewer segments. Furthermore, the increased search time is a result of fewer segments, as the final binary search at the leaf layer requires more time due to the larger error bound.

## VII. Discussion

### A. Limitations

BIRDB has two major limitations. Firstly, the BINDEX is not updateable, which means that when the underlying database changes (e.g., through update queries), it requires significant modifications to the search data structure. This includes changes to the layout of BINDEX, the creation of new linear models for compression, and the generation of new chunks for incremental PIR. Finding a satisfactory solution to address this limitation remains an open problem.

Secondly, BINDEX is designed to support searching on a single attribute, making it unsuitable for databases that require searching across multiple attributes, such as graph databases [15], [16]. While BIRDB can handle disjunctive queries by independently searching on the BINDEX of each attribute, it is unable to handle conjunctive queries without integrating BINDEX with multidimensional indexes like $k-d$ tree [93]. Exploring the integration of BINDEX with multidimensional indexes is an interesting future work.

### B. Lessons Learned

Based on our theoretical proof and empirical evaluation, we have reached the conclusion that relying solely on logarithmic search complexity is insufficient for achieving high-performance encrypted search. Instead, an encrypted search index should incorporate a compact design similar to traditional insecure databases, which ensures cost-effective I/O operations. By combining the features of low complexity and compactness, an encrypted database can ultimately achieve high-performance query processing.

## VIII. Conclusion

We introduce BIRDB, the first encrypted database that efficiently supports encrypted queries while ensuring provable data and metadata confidentiality. BIRDB is built upon the concept of boolean information retrieval, which enables the construction of a secure and efficient index called BINDEX. BINDEX utilizes data membership tests for achieving logarithmic-complexity encrypted searches and employs linear approximation for compression while preserving searchability. Furthermore, BIRDB seamlessly integrates with a two-phase PIR scheme, ensuring metadata hiding. Extensive evaluations conducted on NoSQL workload demonstrate that BIRDB exhibits high efficiency and scalability compared to existing baselines. We have open-sourced BIRDB, and its source code is available at github.com/ndss24p59/BirDB.

## References

[1] "Data breaches - updated list," https://tech.co/news/data-breaches-updated-list, accessed on June 2, 2023.

[2] "Spideroak," 2007, website: https://spideroak.com/.

[3] "Sync," 2011, website: https://www.sync.com/.

[4] "Tresorit," 2011, website: https://tresorit.com/.

[5] "Keybase," 2014, website: https://keybase.io/.

[6] "Preveil," 2015, website: https://www.preveil.com/.

[7] (2023, May 20) Chatgpt confirms data breach. [Online]. Available: https://securityintelligence.com/articles/chatgpt-confirms-data-breach/

[8] (2023, May 15) Tiktok data breach timeline. [Online]. Available: https://firewalltimes.com/tiktok-data-breach-timeline/

[9] H. Abu-Libdeh, L. Princehouse, and H. Weatherspoon, "Racs: a case for cloud storage diversity," in *Proceedings of the 1st ACM symposium on Cloud computing*, 2010, pp. 229–240.

[10] R. Agrawal, J. Kiernan, R. Srikant, and Y. Xu, "Order preserving encryption for numeric data," in *Proceedings of the 2004 ACM SIGMOD international conference on Management of data*, 2004, pp. 563–574.

[11] R. R. Al-Dahhan, Q. Shi, G. M. Lee, and K. Kifayat, "Survey on revocation in ciphertext-policy attribute-based encryption," *Sensors*, vol. 19, no. 7, p. 1695, 2019.

[12] M. B. Aliyu, "Efficiency of boolean search strings for information retrieval," *American Journal of Engineering Research*, vol. 6, no. 11, pp. 216–222, 2017.

[13] W. Almesberger *et al.*, "Linux network traffic control—implementation overview," 1999.

[14] F. Angius, M. Gerla, and G. Pau, "Bloogo: Bloom filter based gossip algorithm for wireless ndn," in *Proceedings of the 1st ACM workshop on Emerging Name-Oriented Mobile Networking Design-Architecture, Algorithms, and Applications*, 2012, pp. 25–30.

[15] R. Angles, "A comparison of current graph database models," in *2012 IEEE 28th International Conference on Data Engineering Workshops*. IEEE, 2012, pp. 171–177.

[16] R. Angles and C. Gutierrez, "Survey of graph database models," *ACM Computing Surveys (CSUR)*, vol. 40, no. 1, pp. 1–39, 2008.

[17] A. Beimel, Y. Ishai, and T. Malkin, "Reducing the servers computation in private information retrieval: Pir with preprocessing," in *Advances in Cryptology—CRYPTO 2000: 20th Annual International Cryptology Conference Santa Barbara, California, USA, August 20–24, 2000 Proceedings 20*. Springer, 2000, pp. 55–73.

[18] M. Bellare, M. Fischlin, A. O'Neill, and T. Ristenpart, "Deterministic encryption: Definitional equivalences and constructions without random oracles," in *Advances in Cryptology–CRYPTO 2008: 28th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 17-21, 2008. Proceedings 28*. Springer, 2008, pp. 360–378.

[19] J. Black, P. Rogaway, and T. Shrimpton, "Black-box analysis of the block-cipher-based hash-function constructions from pgv," in *Crypto*, vol. 2442. Springer, 2002, pp. 320–335.

[20] D. Boneh, D. Mazieres, and R. A. Popa, "Remote oblivious storage: Making oblivious ram practical," 2011.

[21] L. Bošnjak, J. Sreš, and B. Brumen, "Brute-force and dictionary attack on hashed real-world passwords," in *2018 41st international convention on information and communication technology, electronics and microelectronics (mipro)*. IEEE, 2018, pp. 1161–1166.

[22] M. Brandenburger, C. Cachin, M. Lorenz, and R. Kapitza, "Rollback and forking detection for trusted execution environments using lightweight collective memory," in *2017 47th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*. IEEE, 2017, pp. 157–168.

[23] N. G. Bronson, J. Casper, H. Chafi, and K. Olukotun, "A practical concurrent binary search tree," *ACM Sigplan Notices*, vol. 45, no. 5, pp. 257–268, 2010.

[24] W. Chen, T. Hoang, J. Guajardo, and A. A. Yavuz, "Titanium: A metadata-hiding file-sharing system with malicious security," *Cryptology ePrint Archive*, 2022.

[25] H. E. L. Contributors, "Helib: Homomorphic encryption library," https://github.com/homenc/HElib, 2021.

[26] H. Corrigan-Gibbs and D. Kogan, "Private information retrieval with sublinear online time," in *Advances in Cryptology–EUROCRYPT 2020: 39th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Zagreb, Croatia, May 10–14, 2020, Proceedings, Part I 39*. Springer, 2020, pp. 44–75.

[27] E. Dauterman, E. Feng, E. Luo, R. A. Popa, and I. Stoica, "Dory: An encrypted search system with distributed trust," in *Proceedings of the 14th USENIX Conference on Operating Systems Design and Implementation*, 2020, pp. 1101–1119.

[28] ——, "Dory: An encrypted search system with distributed trust," in *14th USENIX Symposium on Operating Systems Design and Implementation (OSDI 20)*, 2020, pp. 1101–1119.

[29] D. Demmler, A. Herzberg, and T. Schneider, "Raid-pir: practical multi-server pir," in *Proceedings of the 6th edition of the ACM Workshop on Cloud Computing Security*, 2014, pp. 45–56.

[30] J. Doerner and A. Shelat, "Scaling oram for secure computation," in *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, 2017, pp. 523–535.

[31] I. Dropbox, "Dropbox," *http://www. dropbox. com*, 2014.

[32] B. Fan, D. G. Andersen, M. Kaminsky, and M. D. Mitzenmacher, "Cuckoo filter: Practically better than bloom," in *Proceedings of the 10th ACM International on Conference on Emerging Networking Experiments and Technologies (CoNEXT)*, 2014, pp. 75–88. [Online]. Available: https://dl.acm.org/doi/10.1145/2674005.2674994

[33] C.-I. Fan, S.-Y. Huang, and W.-C. Hsu, "Encrypted data deduplication in cloud storage," in *2015 10th Asia Joint Conference on Information Security*. IEEE, 2015, pp. 18–25.

[34] P. Ferragina and G. Vinciguerra, "The pgm-index: a fully-dynamic compressed learned index with provable worst-case bounds," *Proceedings of the VLDB Endowment*, vol. 13, no. 8, pp. 1162–1175, 2020.

[35] C. Fontaine and F. Galand, "A survey of homomorphic encryption for nonspecialists," *EURASIP Journal on Information Security*, vol. 2007, pp. 1–10, 2007.

[36] P. Gasti and K. B. Rasmussen, "On the security of password manager database formats," in *Computer Security–ESORICS 2012: 17th European Symposium on Research in Computer Security, Pisa, Italy, September 10-12, 2012. Proceedings 17*. Springer, 2012, pp. 770–787.

[37] C. Gentry, K. A. Goldman, S. Halevi, C. Julta, M. Raykova, and D. Wichs, "Optimizing oram and using it efficiently for secure computation," in *Privacy Enhancing Technologies: 13th International Symposium, PETS 2013, Bloomington, IN, USA, July 10-12, 2013. Proceedings 13*. Springer, 2013, pp. 1–18.

[38] A. Gogolou, T. Tsandilas, T. Palpanas, and A. Bezerianos, "Progressive similarity search on time series data," in *BigVis 2019-2nd International Workshop on Big Data Visual Exploration and Analytics*, 2019.

[39] O. Goldreich and R. Ostrovsky, "Software protection and simulation on oblivious rams," *Journal of the ACM (JACM)*, vol. 43, no. 3, pp. 431–473, 1996.

[40] S. Gueron, S. Johnson, and J. Walker, "Sha-512/256," in *2011 Eighth International Conference on Information Technology: New Generations*. IEEE, 2011, pp. 354–358.

[41] M. He, J. Zhang, G. Zeng, and S. M. Yiu, "A privacy-preserving multi-pattern matching scheme for searching strings in cloud database," in *2017 15th Annual Conference on Privacy, Security and Trust (PST)*. IEEE, 2017, pp. 293–29 309.

[42] A. Henzinger, M. M. Hong, H. Corrigan-Gibbs, S. Meiklejohn, and V. Vaikuntanathan, "One server for the price of two: Simple and fast single-server private information retrieval," *Cryptology ePrint Archive*, 2022.

[43] Y. Himeur, A. Sayed, A. Alsalemi, F. Bensaali, A. Amira, I. Varlamis, M. Eirinaki, C. Sardianos, and G. Dimitrakopoulos, "Blockchain-based recommender systems: Applications, challenges and future opportunities," *Computer Science Review*, vol. 43, p. 100439, 2022.

[44] S. Idreos and M. Callaghan, "Key-value storage engines," in *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*, 2020, pp. 2667–2672.

[45] P. Jiang, Q. Wang, J. Cheng, C. Wang, L. Xu, X. Wang, Y. Wu, X. Li, and K. Ren, "Boomerang:{Metadata-Private} messaging under hardware trust," in *20th USENIX Symposium on Networked Systems Design and Implementation (NSDI 23)*, 2023, pp. 877–899.

[46] M. Johnson, P. Ishwar, V. Prabhakaran, D. Schonberg, and K. Ramchandran, "On compressing encrypted data," *IEEE Transactions on Signal Processing*, vol. 52, no. 10, pp. 2992–3006, 2004.

[47] S. Kamara and K. Lauter, "Cryptographic cloud storage," in *Financial Cryptography and Data Security: FC 2010 Workshops, RLCPS, WECSR, and WLC 2010, Tenerife, Canary Islands, Spain, January 25-28, 2010, Revised Selected Papers 14*. Springer, 2010, pp. 136–149.

[48] T. Kraska, A. Beutel, E. H. Chi, J. Dean, and N. Polyzotis, "The case for learned index structures," in *Proceedings of the 2018 International Conference on Management of Data*. ACM, 2018. [Online]. Available: https://dl.acm.org/doi/10.1145/3183713.3196909

[49] T. Kraska, A. Beutel, E. H. Chi, J. Dean, N. Polyzotis, and L. Zhu, "Consistency guarantees for parallel incremental data processing," in *Proceedings of the 2019 International Conference on Management of Data*. ACM, 2019, pp. 1271–1288. [Online]. Available: https://dl.acm.org/doi/10.1145/3299869.3319882

[50] T. K. Kuppusamy, V. Diaz, and J. Cappos, "Mercury:{Bandwidth-Effective} prevention of rollback attacks against community reposito-

ries," in *2017 USENIX Annual Technical Conference (USENIX ATC 17)*, 2017, pp. 673–688.

[51] K. Kurosawa, "How to correct errors in multi-server pir," in *Advances in Cryptology–ASIACRYPT 2019: 25th International Conference on the Theory and Application of Cryptology and Information Security, Kobe, Japan, December 8–12, 2019, Proceedings, Part II*. Springer, 2019, pp. 564–574.

[52] A. H. Lashkari, F. Mahdavi, and V. Ghomi, "A boolean model in information retrieval for search engines," in *2009 International Conference on Information Management and Engineering*. IEEE, 2009, pp. 385–389.

[53] C. Li, W. Ma, and L. Qin, "Efficient and accurate approximate query processing on data warehouses with learned indexes," in *Proceedings of the 2019 International Conference on Management of Data*. ACM, 2019, pp. 1717–1734. [Online]. Available: https://dl.acm.org/doi/10.1145/3299869.3319886

[54] S. Li and M. Gastpar, "Converse for multi-server single-message pir with side information," in *2020 54th Annual Conference on Information Sciences and Systems (CISS)*. IEEE, 2020, pp. 1–6.

[55] Z. Li, J. Guo, H. Li, T. Wu, S. Mao, and F. Nie, "Speed up similarity search of time series under dynamic time warping," *IEEE Access*, vol. 7, pp. 163 644–163 653, 2019.

[56] H.-Y. Lin, S. Kumar, E. Rosnes, A. G. i Amat, and E. Yaakobi, "Multi-server weakly-private information retrieval," *IEEE Transactions on Information Theory*, vol. 68, no. 2, pp. 1197–1219, 2021.

[57] Y. Ma, K. Zhong, T. Rabin, and S. Angel, "Incremental {Offline/Online}{PIR}," in *31st USENIX Security Symposium (USENIX Security 22)*, 2022, pp. 1741–1758.

[58] S. J. Menon and D. J. Wu, "Spiral: Fast, high-rate single-server pir via fhe composition," in *2022 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2022, pp. 930–947.

[59] M. H. Mughees, H. Chen, and L. Ren, "Onionpir: Response efficient single-server pir," in *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, 2021, pp. 2292–2306.

[60] A. MySQL, "Mysql," 2001.

[61] F. Olumofin and I. Goldberg, "Revisiting the computational practicality of private information retrieval," in *International Conference on Financial Cryptography and Data Security*. Springer, 2011, pp. 158–172.

[62] S.-C. Park and M.-S. Lee, "A survey of access control models in database management systems," *Journal of Computing Science and Engineering*, vol. 9, no. 2, pp. 57–78, 2015.

[63] S. Patel, G. Persiano, K. Yeo, and M. Yung, "Mitigating leakage in secure cloud-hosted data structures: Volume-hiding for multi-maps via hashing," in *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, 2019, pp. 79–93.

[64] G. Persiano and K. Yeo, "Limits of preprocessing for single-server pir," in *Proceedings of the 2022 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*. SIAM, 2022, pp. 2522–2548.

[65] B. Pinkas and T. Reinman, "Oblivious ram revisited," in *Advances in Cryptology–CRYPTO 2010: 30th Annual Cryptology Conference, Santa Barbara, CA, USA, August 15-19, 2010. Proceedings 30*. Springer, 2010, pp. 502–519.

[66] B. Pinkas and T. Schneider, "Oblivious ram: Improved lower bounds and optimal constructions," in *Proceedings of the 31st Annual International Cryptology Conference (CRYPTO)*, 2009, pp. 502–519. [Online]. Available: https://link.springer.com/chapter/10.1007/978-3-642-03356-8_28

[67] R. Poddar, G. Ananthanarayanan, S. Setty, S. Volos, and R. A. Popa, "Visor: Privacy-preserving video analytics as a cloud service," in *Proceedings of the 29th USENIX Conference on Security Symposium*, 2020, pp. 1039–1056.

[68] R. A. Popa, C. M. Redfield, N. Zeldovich, and H. Balakrishnan, "Cryptdb: Protecting confidentiality with encrypted query processing," in *Proceedings of the twenty-third ACM symposium on operating systems principles*, 2011, pp. 85–100.

[69] I. Popivanov and R. J. Miller, "Similarity search over time-series data using wavelets," in *Proceedings 18th international conference on data engineering*. IEEE, 2002, pp. 212–221.

[70] L. Ren, C. Fletcher, A. Kwon, E. Stefanov, E. Shi, M. Van Dijk, and S. Devadas, "Constants count: Practical improvements to oblivious {RAM}," in *24th {USENIX} Security Symposium ({USENIX} Security 15)*, 2015, pp. 415–430.

[71] T. Shen, J. Jiang, Y. Jiang, X. Chen, J. Qi, S. Zhao, F. Zhang, X. Luo, and H. Cui, "Daenet: making strong anonymity scale in a fully decentralized network," *IEEE Transactions on Dependable and Secure Computing*, vol. 19, no. 4, pp. 2286–2303, 2021.

[72] T. Shen, J. Qi, J. Jiang, X. Wang, S. Wen, X. Chen, S. Zhao, S. Wang, L. Chen, X. Luo *et al.*, "{SOTER}: Guarding black-box inference for general neural networks at the edge," in *2022 USENIX Annual Technical Conference (USENIX ATC 22)*, 2022, pp. 723–738.

[73] E. Shi, W. Aqeel, B. Chandrasekaran, and B. Maggs, "Puncturable pseudorandom sets and private information retrieval with near-optimal online bandwidth and time," in *Advances in Cryptology–CRYPTO 2021: 41st Annual International Cryptology Conference, CRYPTO 2021, Virtual Event, August 16–20, 2021, Proceedings, Part IV 41*. Springer, 2021, pp. 641–669.

[74] E. Shi, T.-H. H. Chan, E. Stefanov, and M. Li, "Oblivious ram with o ((logn) 3) worst-case cost." in *Asiacrypt*, vol. 7073. Springer, 2011, pp. 197–214.

[75] E. Stefanov, M. v. Dijk, E. Shi, T.-H. H. Chan, C. Fletcher, L. Ren, X. Yu, and S. Devadas, "Path oram: an extremely simple oblivious ram protocol," *Journal of the ACM (JACM)*, vol. 65, no. 4, pp. 1–26, 2018.

[76] E. Stefanov, E. Shi, and D. Song, "Towards practical oblivious ram," *arXiv preprint arXiv:1106.3652*, 2011.

[77] E. Stefanov, M. van Dijk, E. Shi, and R. A. Popa, "Path oram: An extremely simple oblivious ram protocol," in *Proceedings of the 2013 ACM SIGSAC Conference on Computer and Communications Security (CCS)*, 2013, pp. 299–310. [Online]. Available: https://dl.acm.org/doi/10.1145/2508859.2516661

[78] D. Stehlé and R. Steinfeld, "Faster fully homomorphic encryption," in *Advances in Cryptology-ASIACRYPT 2010: 16th International Conference on the Theory and Application of Cryptology and Information Security, Singapore, December 5-9, 2010. Proceedings 16*. Springer, 2010, pp. 377–394.

[79] E. Tsyrklevich and B. Yee, "Dynamic detection and prevention of race conditions in file accesses," in *12th USENIX Security Symposium (USENIX Security 03)*, 2003.

[80] S. L. Tu, M. F. Kaashoek, S. R. Madden, and N. Zeldovich, "Processing analytical queries over encrypted data," 2013.

[81] J. Wang, S.-F. Sun, T. Li, S. Qi, and X. Chen, "Practical volume-hiding encrypted multi-maps with optimal overhead and beyond," in *Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security*, 2022, pp. 2825–2839.

[82] Z. Wang, R. Hu, T. Yu, and C. Chen, "Design and implementation of a database client blacklist mechanism," in *2019 International Conference on Computing, Communications and Intelligence Systems (ICCCIS)*. IEEE, 2019, pp. 71–74.

[83] E. W. Weisstein, "Fermat's little theorem," *https://mathworld. wolfram. com/*, 2004.

[84] K. Wilson and K. Wilson, "Onedrive," *Everyday Computing with Windows 8.1*, pp. 71–74, 2015.

[85] J. Wu, L. Ping, X. Ge, Y. Wang, and J. Fu, "Cloud storage as the infrastructure of cloud computing," in *2010 International conference on intelligent computing and cognitive informatics*. IEEE, 2010, pp. 380–383.

[86] P. Wu, J. Ning, J. Shen, H. Wang, and E.-C. Chang, "Hybrid trust multi-party computation with trusted execution environment," in *The Network and Distributed System Security (NDSS) Symposium*, 2022.

[87] Y. Xia, X. Yu, M. Butrovich, A. Pavlo, and S. Devadas, "Litmus: Towards a practical database management system with verifiable acid properties and transaction correctness," in *Proceedings of the 2022 International Conference on Management of Data, Philadelphia, PA, USA*, 2022, pp. 12–17.

[88] H. Xu, Z. Cai, D. Takabi, and W. Li, "Audio-visual autoencoding for privacy-preserving video streaming," *IEEE Internet of Things Journal*, vol. 9, no. 3, pp. 1749–1761, 2021.

[89] K. Xue, W. Chen, W. Li, J. Hong, and P. Hong, "Combining data owner-side and cloud-side access control for encrypted cloud storage," *IEEE Transactions on Information Forensics and Security*, vol. 13, no. 8, pp. 2062–2074, 2018.

[90] K. Yeo, "Lower bounds for (batch) pir with private preprocessing," in *Annual International Conference on the Theory and Applications of Cryptographic Techniques*. Springer, 2023, pp. 518–550.

[91] X. Yi, R. Paulet, E. Bertino, X. Yi, R. Paulet, and E. Bertino, *Homomorphic encryption*. Springer, 2014.

[92] Y. Zhong, H. Li, Y. J. Wu, I. Zarkadas, J. Tao, E. Mesterhazy, M. Makris, J. Yang, A. Tai, R. Stutsman *et al.*, "{XRP}:{In-Kernel} storage functions with {eBPF}," in *16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)*, 2022, pp. 375–393.

[93] K. Zhou, Q. Hou, R. Wang, and B. Guo, "Real-time kd-tree construction on graphics hardware," *ACM Transactions on Graphics (TOG)*, vol. 27, no. 5, pp. 1–11, 2008.

[94] W. Zhou, Y. Cai, Y. Peng, S. Wang, K. Ma, and F. Li, "Veridb: An sgx-based verifiable database," in *Proceedings of the 2021 International Conference on Management of Data*, 2021, pp. 2182–2194.