FLYBOAT

Flyboat Electronic LLC — North American sales & engineering center

ULTIMA Board-Mounted SPD Modules

Surge protective modules with built-in disconnector for OEM integration · Datasheet

The ULTIMA series is a family of surge protective modules that mount directly on the equipments printed circuit board — no DIN rail, no separate housing. Each module combines our own metal oxide varistor chips with a built-in thermal disconnector and an alarm contact for remote status signaling, in a compact flame-retardant housing that solders or plugs onto the board. The modules are made by Guiyang High-Tech Yige Electronic Co., Ltd. and supplied to equipment manufacturers for integration into their own products; in North America they are supported by Flyboat Electronic LLC, the factorys sales and engineering center in Bellevue, WA.

ULTIMA modules are supplied on an OEM basis for integration into end equipment; the modules themselves carry no UL listing, and end-product certification remains with the equipment manufacturer. Type-code reading, materials and the OEM supply boundary are documented on the ULTIMA page at www.flyboatmov.com.

ULTIMA B10 — In 10 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U150 (V)	Energy 2 ms (J)
B10K60/11	90~110	60	85	10	20	360	165	110
B10K75/11	108~132	75	100	10	20	400	200	135
B10K275/11	390~470	275	350	10	20	1050	710	450
B10K300/11	430~510	300	385	10	20	1150	780	480
B10K320/11	460~560	320	415	10	20	1250	845	510
B10K385/11	580~660	385	505	10	20	1500	1025	620
B10K420/11	630~740	420	560	10	20	1600	1120	620
B10K460/11	680~810	460	615	10	20	1700	1240	640
B10K510/11	740~900	510	670	10	20	1900	1355	670

ULTIMA B10 — In 10 kA class

Model	Construction	Size, excl. pins (mm)	Protected modes	Uc (V)	In (kA)	Up (V)
B10K510/21	22S-1P chip; horizontal mounting, 2 plug pins; built-in microswitch	42 × 28.3 × 18	Single-phase	510	10	1900
B10K385/21	385	1500				
B10K320/21	320	1250				

Model	Construction	Size, excl. pins (mm)	Protected modes	Uc (V)	In (kA)	Up (V)
B10K275/21	275	1150				
B10K60/21	60	360				

ULTIMA B10 — In 10 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U150 (V)	Energy 2 ms (J)
B10K60/31	90~110	60	85	10	20	360	165	110
B10K75/31	108~132	75	100	10	20	400	200	135
B10K275/31	390~470	275	350	10	20	1050	710	450
B10K300/31	430~510	300	385	10	20	1150	780	480
B10K320/31	460~560	320	415	10	20	1250	845	510
B10K385/31	580~660	385	505	10	20	1500	1025	620
B10K420/31	630~740	420	560	10	20	1600	1120	620
B10K460/31	680~810	460	615	10	20	1700	1240	640
B10K510/31	740~900	510	670	10	20	1900	1355	670

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/11	90~110	60	85	20	40	360	165	190
B20K75/11	108~132	75	100	20	40	400	200	230
B20K275/11	390~470	275	350	20	40	1050	710	910
B20K300/11	430~510	300	385	20	40	1150	780	980
B20K320/11	460~560	320	415	20	40	1250	845	1050
B20K385/11	580~660	385	505	20	40	1500	1025	1240
B20K420/11	630~740	420	560	20	40	1600	1120	1240
B20K460/11	680~810	460	615	20	40	1700	1240	1270
B20K510/11	740~900	510	670	20	40	1900	1355	1350

ULTIMA B20 — In 20 kA class

Model	Construction	Size, excl. pins (mm)	Protected modes	Uc (V)	In (kA)	Up (V)
B20K420/21	34S-2P chips with independent disconnectors; horizontal mounting, 3 plug pins; dual built-in microswitches	47.1 × 38 × 18	Two-phase	420	20	1600
B20K385/21	385	1500				
B20K350/21	350	1350				
B20K275/21	275	1150				

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/31	90~110	60	85	20	40	360	165	190
B20K75/31	108~132	75	100	20	40	400	200	230
B20K275/31	390~470	275	350	20	40	1050	710	910
B20K300/31	430~510	300	385	20	40	1150	780	980
B20K320/31	460~560	320	415	20	40	1250	845	1050
B20K385/31	580~660	385	505	20	40	1500	1025	1240
B20K420/31	630~740	420	560	20	40	1600	1120	1240
B20K460/31	680~810	460	615	20	40	1700	1240	1270
B20K510/31	740~900	510	670	20	40	1900	1355	1350

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K350/41	510 ~ 510	350	450	20	40	1400	930	1100
B20K385/41	580~660	385	505	20	40	1550	1025	1200
B20K420/41	660~740	420	560	20	40	1650	1120	1200

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/51	90~110	60	85	20	40	360	165	190
B20K75/51	108~132	75	100	20	40	400	200	230
B20K275/51	390~470	275	350	20	40	1050	710	910
B20K300/51	430~510	300	385	20	40	1150	780	980

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K320/51	460~560	320	415	20	40	1250	845	1050
B20K385/51	580~660	385	505	20	40	1500	1025	1240
B20K420/51	630~740	420	560	20	40	1600	1120	1250
B20K460/51	680~810	460	615	20	40	1700	1240	1280
B20K510/51	740~900	510	670	20	40	1900	1355	1350

ULTIMA B40 — In 40 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B40K350/41	510 ~ 510	350	450	40	80	1400	930	2300
B40K385/41	580~660	385	505	40	80	1550	1025	2450
B40K420/41	660~740	420	560	40	80	1650	1120	2450

Samples and OEM design-in support — North America: Thomas Dong, Flyboat Electronic LLC (thomasd@flyboatmov.com); China: Colin Fei (colinf@flyboatmov.com).