FLYBOAT

Flyboat Electronic LLC — North American sales & engineering center

ULTIMA Board-Mounted SPD Modules

Surge protective modules with built-in disconnector for OEM integration · Datasheet

The ULTIMA series is a family of surge protective modules that mount directly on the equipments printed circuit board — no DIN rail, no separate housing. Each module combines our own metal oxide varistor chips with a built-in thermal disconnector and an alarm contact for remote status signaling, in a compact flame-retardant housing that solders or plugs onto the board. The modules are made by Guiyang High-Tech Yige Electronic Co., Ltd. and supplied to equipment manufacturers for integration into their own products; in North America they are supported by Flyboat Electronic LLC, the factorys sales and engineering center in Bellevue, WA. Scan with WeChat to share this page ULTIMA Module Datasheet PDF — complete ratings tables for every model grade.

ULTIMA modules are supplied on an OEM basis for integration into end equipment; the modules themselves carry no UL listing, and end-product certification remains with the equipment manufacturer. Type-code reading, materials and the OEM supply boundary are documented on the ULTIMA page at www.flyboatmov.com.

ULTIMA B10 — In 10 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U150 (V)	Energy 2 ms (J)
B10K60/11	90~110	60	85	10	20	360	165	110
B10K75/11	108~132	75	100	10	20	400	200	135
B10K275/11	390~470	275	350	10	20	1050	710	450
B10K300/11	430~510	300	385	10	20	1150	780	480
B10K320/11	460~560	320	415	10	20	1250	845	510
B10K385/11	580~660	385	505	10	20	1500	1025	620
B10K420/11	630~740	420	560	10	20	1600	1120	620
B10K460/11	680~810	460	615	10	20	1700	1240	640
B10K510/11	740~900	510	670	10	20	1900	1355	670

ULTIMA B10 — In 10 kA class

Model	Construction	Size, excl. pins (mm)	Protected modes	Uc (V)	In (kA)	Up (V)
B10K510/21	22S-1P chip; horizontal mounting, 2 plug pins; built-in microswitch	42 × 28.3 × 18	Single-phase	510	10	1900
B10K385/21	385	1500				
B10K320/21	320	1250				
B10K275/21	275	1150				
B10K60/21	60	360				

ULTIMA B10 — In 10 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U150 (V)	Energy 2 ms (J)
B10K60/31	90~110	60	85	10	20	360	165	110
B10K75/31	108~132	75	100	10	20	400	200	135
B10K275/31	390~470	275	350	10	20	1050	710	450
B10K300/31	430~510	300	385	10	20	1150	780	480
B10K320/31	460~560	320	415	10	20	1250	845	510
B10K385/31	580~660	385	505	10	20	1500	1025	620

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U150 (V)	Energy 2 ms (J)
B10K420/31	630~740	420	560	10	20	1600	1120	620
B10K460/31	680~810	460	615	10	20	1700	1240	640
B10K510/31	740~900	510	670	10	20	1900	1355	670

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/11	90~110	60	85	20	40	360	165	190
B20K75/11	108~132	75	100	20	40	400	200	230
B20K275/11	390~470	275	350	20	40	1050	710	910
B20K300/11	430~510	300	385	20	40	1150	780	980
B20K320/11	460~560	320	415	20	40	1250	845	1050
B20K385/11	580~660	385	505	20	40	1500	1025	1240
B20K420/11	630~740	420	560	20	40	1600	1120	1240
B20K460/11	680~810	460	615	20	40	1700	1240	1270
B20K510/11	740~900	510	670	20	40	1900	1355	1350

ULTIMA B20 — In 20 kA class

Model	Construction	Size, excl. pins (mm)	Protected modes	Uc (V)	In (kA)	Up (V)
B20K420/21	34S-2P chips with independent disconnectors; horizontal mounting, 3 plug pins; dual built-in microswitches	47.1 × 38 × 18	Two-phase	420	20	1600
B20K385/21	385	1500				
B20K350/21	350	1350				
B20K275/21	275	1150				

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/31	90~110	60	85	20	40	360	165	190
B20K75/31	108~132	75	100	20	40	400	200	230
B20K275/31	390~470	275	350	20	40	1050	710	910
B20K300/31	430~510	300	385	20	40	1150	780	980
B20K320/31	460~560	320	415	20	40	1250	845	1050
B20K385/31	580~660	385	505	20	40	1500	1025	1240
B20K420/31	630~740	420	560	20	40	1600	1120	1240
B20K460/31	680~810	460	615	20	40	1700	1240	1270
B20K510/31	740~900	510	670	20	40	1900	1355	1350

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K350/41	510 ~ 510	350	450	20	40	1400	930	1100
B20K385/41	580~660	385	505	20	40	1550	1025	1200
B20K420/41	660~740	420	560	20	40	1650	1120	1200

ULTIMA B20 — In 20 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K60/51	90~110	60	85	20	40	360	165	190

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B20K75/51	108~132	75	100	20	40	400	200	230
B20K275/51	390~470	275	350	20	40	1050	710	910
B20K300/51	430~510	300	385	20	40	1150	780	980
B20K320/51	460~560	320	415	20	40	1250	845	1050
B20K385/51	580~660	385	505	20	40	1500	1025	1240
B20K420/51	630~740	420	560	20	40	1600	1120	1250
B20K460/51	680~810	460	615	20	40	1700	1240	1280
B20K510/51	740~900	510	670	20	40	1900	1355	1350

ULTIMA B40 — In 40 kA class

Model	U1mA (V)	UAC (V)	UDC (V)	In (kA)	Imax (kA)	Up (V)	U300 (V)	Energy 2 ms (J)
B40K350/41	510 ~ 510	350	450	40	80	1400	930	2300
B40K385/41	580~660	385	505	40	80	1550	1025	2450
B40K420/41	660~740	420	560	40	80	1650	1120	2450

Samples and OEM design-in support — North America: Thomas Dong, Flyboat Electronic LLC (thomasd@flyboatmov.com); China: Colin Fei (colinf@flyboatmov.com).