

若泽数据--mail 465邮件发送案例

1.先去QQ邮箱，开启SMTP和获取授权码

2.停止服务：

```
service sendmail stop
chkconfig sendmail off
```

3.启动postfix服务：

```
service postfix start
chkconfig postfix on
postfix check
systemctl status postfix
```

4.调整参数：

```
vi /etc/postfix/main.cf
inet_interfaces = all
```

5.创建认证：

```
mkdir -p /root/.certs/
echo -n | openssl s_client -connect smtp.qq.com:465 | sed -ne '/-BEGIN CERTIFICATE
-/,/-END CERTIFICATE-/p' > ~/.certs/qq.crt
certutil -A -n "GeoTrust SSL CA" -t "C,," -d ~/.certs -i ~/.certs/qq.crt
certutil -A -n "GeoTrust Global CA" -t "C,," -d ~/.certs -i ~/.certs/qq.crt
certutil -L -d /root/.certs

cd /root/.certs
certutil -A -n "GeoTrust SSL CA - G3" -t "Pu,Pu,Pu" -d ./ -i qq.crt
```

6.配置邮件发送者：

```
vi /etc/mail.rc
set from=2643854124@qq.com
set smtp=smtps://smtp.qq.com:465
set smtp-auth-user=2643854124
#授权码
set smtp-auth-password=cnnjaqnhtohmeahg
set smtp-auth=login
set ssl-verify=ignore
set nss-config-dir=/root/.certs
```

7.测试：

```
echo hello word | mail -s " title" 2643854124@qq.com
```

#当然实时查看 Linux 日志

```
tail -f /var/log/maillog
```

8.标准:

发邮件不带附件

```
EMAIL=2643854124@qq.com
```

```
echo -e "`date "+%Y-%m-%d %H:%M:%S"` : The current running $JOB_NAME job num is  
$RUNNINGNUM in 192.168.137.201 ....." | mail \  
-r "From: alertAdmin <${EMAIL}>" \  
-s "Warn: Skip the new $JOB_NAME spark job." ${EMAIL}
```

发邮件带附件

```
echo -e "`date "+%Y-%m-%d %H:%M:%S"` : Please to check the fail sql attachement."  
|  
mailx \  
-r "From: alertAdmin <${EMAIL}>" \  
-a error.log \  
-s "Critical:KSSH fail sql." ${EMAIL}
```